A COMPLETE VISUAL GUIDE

Regularization

Ridge, Lasso & Elastic Net — from the very first intuition all the way to the matrix calculus, the geometry, and the interview questions that trip people up.

Beginner → Advanced | Math + Code + Visuals | Machine Learning

CONTENTS

What's Inside

01	What Is Regularization, Really?
02	The Problem It Solves: Overfitting & Underfitting
03	The Bias–Variance Tradeoff
04	Quick Refresher: Linear Regression & the Loss Function
05	Ridge Regression (L2 Regularization)
06	Coding Ridge Regression From Scratch
07	Lasso Regression (L1 Regularization)
08	Why Lasso Zeroes Out Coefficients (and Ridge Doesn't)
09	Elastic Net: The Best of Both Worlds
10	Choosing Lambda: The Sweet Spot
11	Ridge vs Lasso — The Full Comparison
12	Practical Tips & Rules of Thumb
13	Interview Questions You Must Be Able to Answer
14	Final Cheat Sheet

📌 HOW TO READ THIS GUIDE

Every idea is introduced with plain intuition first, then backed with the actual math, then shown as a picture, and finally tied to real code run on a real dataset (scikit-learn's diabetes dataset — the same one used throughout this tutorial). Nothing from the original material is skipped; it's just been reorganized, cleaned up, and made visual.

SECTION 01 · BASICS

What Is Regularization, Really?

If you look it up, the textbook definition says something like:

> **DEFINITION**
>
> **Regularization** is a technique in which we deliberately add extra information (a "penalty") into a machine learning model's training process so that the model doesn't fit the training data *too* perfectly — the goal is to reduce **overfitting** and make the model generalize better to new, unseen data.

That's the formal definition — but here's the intuition behind it. Imagine you're studying for an exam by memorizing the exact answers to last year's practice questions, word for word, instead of understanding the underlying concept. You'll score 100% on that exact practice paper, but the moment the real exam asks a slightly different question, you'll fail. That's exactly what an overfit machine learning model does: it "memorizes" the training data instead of learning the general pattern.

Regularization is one of three classic families of techniques used to improve a machine learning model's real-world performance:

1. Bagging
2. Boosting
3. Regularization ← this guide

This guide focuses entirely on regularization, and specifically on the three techniques that are used most heavily with linear models (Linear Regression, Logistic Regression, and even Perceptrons):

- Ridge Regression (L2)
- Lasso Regression (L1)
- Elastic Net (L1 + L2)

Why do we need this at all?

The whole idea of linear regression is to find the "best fit line":

$$\hat{y} = mx + b$$

To find the best `m` (slope) and `b` (intercept), we minimize a **loss function** — usually the Mean Squared Error (MSE):

$$J(m, b) = \frac{1}{n}\sum_{i=1}^{n}(y_i - (mx_i + b))^2$$

The problem: if we let the model minimize this loss with total freedom, especially when we have many input columns or a high-degree polynomial, the model can grow extremely large coefficients and bend itself into a wild, wiggly shape that passes almost exactly through every single training point. That's overfitting. Regularization fixes this by adding one more term to the loss function that *punishes* the model for having large coefficients.

SECTION 02 · THE CORE PROBLEM

Overfitting & Underfitting

Before we can appreciate regularization, we need to clearly see the disease it cures. A model can go wrong in two opposite directions:

- **Underfitting** — the model is too simple to capture the pattern in the data. It performs poorly on *both* training and testing data.
- **Overfitting** — the model is too complex. It performs *exceptionally well* on training data, but performs poorly (or wildly inconsistently) on testing data or any new dataset.
- **Good fit** — the sweet spot in between, where the model captures the real underlying trend without chasing every bit of noise.




Fig 2.1 — The same 22 data points, fit with a degree-1 (underfit), degree-4 (good fit), and degree-16 (overfit) polynomial. Notice how the overfit curve swings wildly just to touch every point.

⚠ HOW TO DETECT OVERFITTING IN PRACTICE

Overfitting is the situation where a machine learning model performs exceptionally well on training data but not so well on testing data — performance on a different dataset gives noticeably different (usually worse) results. If your training accuracy is 98% and your test accuracy is 61%, that gap is the fingerprint of overfitting.

A tiny numeric example

Suppose we're comparing two candidate lines fit to the same small dataset. For a particular point where the actual slope-driven prediction differs slightly, one line gives a squared error contribution of about **2.25**, and a second, slightly different line gives about **2.03**. Small differences like this — repeated across every data point and summed up — are exactly what the loss function (MSE) is measuring, and it's exactly this quantity that regularization will now modify by adding a penalty term.

SECTION 03 · FOUNDATIONAL THEORY

The Bias–Variance Tradeoff

This is the single most important mental model for understanding *why* regularization works.

- **Bias** — error from overly simplistic assumptions. High bias = the model doesn't even fit the training data well (underfitting).
- **Variance** — error from being overly sensitive to small fluctuations in the training data. High variance = the model fits the training data almost perfectly, but its predictions swing wildly when trained on a slightly different sample (overfitting).

$$\text{Error} = \text{Bias}^2 + \text{Variance} + \text{Irreducible Error}$$

Every model's total prediction error can be decomposed into these two components plus a fixed irreducible noise term. The tricky part: bias and variance move in **opposite directions**. Push one down, and the other tends to go up. Regularization is our dial for controlling exactly this tradeoff.




Fig 3.1 — As lambda (the regularization strength) increases, bias rises and variance falls. Total error is minimized somewhere in the middle — never at the extremes.

> **KEY INSIGHT**
>
> A small regularization strength (lambda close to 0) keeps variance low bias... wait — let's say it plainly: **small lambda → low bias, high variance (tends toward overfitting)**. **Large lambda → high bias, low variance (tends toward underfitting)**. The entire game of regularization is choosing a lambda that lands you in the valley of the total-error curve above.

SECTION 04 · REFRESHER

Linear Regression & the Loss Function

To understand Ridge and Lasso, we need to be completely comfortable with how plain (unregularized) linear regression is solved — this is usually called **Ordinary Least Squares (OLS)**.

Single input column

With one input feature, we're solving for a slope `m` and intercept `b` that minimize the sum of squared errors. Taking partial derivatives of the loss with respect to `m` and `b` and setting them to zero gives the classic closed-form solution:

$$m = \frac{\sum_i (x_i - \bar{x})(y_i - \bar{y})}{\sum_i (x_i - \bar{x})^2}$$

Many input columns — the matrix form

When you have more than one input column, it's far cleaner to write everything using matrices. Stack every row of input features (with an extra column of 1's for the intercept) into a matrix `X`, and every target value into a vector `y`. Then the loss function becomes:

$$\hat{y} = mx + b$$

Minimizing $(Xw - y)^T(Xw - y)$ with respect to the weight vector `w` (which bundles the intercept and all slopes together) and setting the derivative to zero gives:

$$W = (X^T X)^{-1} X^T y$$

This is the Ordinary Least Squares closed-form solution. It works well — until $X^T X$ becomes difficult to invert (e.g. when columns are correlated, or you have more columns than rows), or until the model starts overfitting because nothing is stopping the weights from growing arbitrarily large. That's the exact gap Ridge Regression fills.

SECTION 05 · RIDGE REGRESSION

Ridge Regression (L2 Regularization)

Ridge regression takes the ordinary least squares loss function and adds a penalty proportional to the **sum of squares** of the coefficients:

$$J(w) = \sum_{i=1}^{n} (y_i - \hat{y}_i)^2 + \lambda \sum_{j=1}^{k} w_j^2$$

READING THE FORMULA

`λ` (lambda), also called the **hyperparameter alpha** in scikit-learn, controls how strongly we punish large weights.

$\lambda \in [0, \infty)$

When `λ = 0`, this reduces exactly to ordinary linear regression (no regularization at all). As `λ` grows, the model is forced to keep its weights smaller and smaller.

Deriving the single-variable case

Just like we did for OLS, we can take the ridge loss function for a single input column, differentiate with respect to `m`, and set it to zero. Working through the algebra (the derivation splits the loss into an MSE term and a penalty term, differentiates both, and solves for `m`) gives a strikingly clean result:

$$m = \frac{\sum_i (x_i - \bar{x})(y_i - \bar{y})}{\sum_i (x_i - \bar{x})^2 + \lambda}$$

Compare this to the plain OLS formula from the previous section — the only difference is that `λ` has been **added into the denominator**. That one small change is the entire mechanism of ridge regression, and it's the detail that explains almost everything else in this section, so hold onto it.

The matrix (multi-variable) closed-form solution

Following the exact same derivation as OLS, but adding `λwᵀw` to the loss before differentiating, the optimal weight vector becomes:

$$W = (X^T X + \lambda I)^{-1} X^T y$$

MATH NOTE — WHAT IS/HERE?

`I` is the identity matrix, sized (columns + 1) × (columns + 1) to match `XᵀX`. Adding `λI` before inverting has a wonderful side benefit: it makes the matrix easier to invert even when `XᵀX` is close to singular (this is actually where the name "ridge" historically comes from — adding a small "ridge" of values along the diagonal).

Why coefficients shrink but never hit exactly zero

Look again at the single-variable formula. Because `λ` sits in the **denominator**, increasing it can only ever divide the numerator by a bigger and bigger number — pushing `m` closer and closer to zero, but mathematically it can never fully cancel the numerator out to land exactly on zero (unless the numerator itself was already zero). This single algebraic fact is why ridge regression shrinks weights smoothly without ever fully eliminating a feature.




Fig 5.1 — For a single coefficient, increasing lambda in Ridge (left) smoothly slides the minimum of the loss curve toward zero. In Lasso (right), the sharp "kink" at zero eventually captures the minimum completely.

What this looks like on real data

Below is Ridge Regression run on scikit-learn's diabetes dataset (442 patients, 10 standardized input columns — age, sex, bmi, blood pressure, and six blood serum measurements — predicting a quantitative measure of disease progression):




Fig 5.2 — As alpha increases (log scale), every coefficient shrinks toward zero, but even at alpha = 10,000, none of them are exactly zero — they just become tiny.

TWO THINGS TO ALWAYS REMEMBER ABOUT RIDGE

- The **larger** a coefficient originally was, the **faster** it shrinks as lambda increases (look at the `s1` curve above — it starts around −38 and drops the fastest).
- No coefficient **ever** becomes exactly zero — it only approaches zero asymptotically. Ridge never performs automatic feature selection.

Finding the right alpha

Too little regularization and you overfit; too much and you underfit. Plotting the R^2 score on both the training and testing splits as alpha increases makes this trade-off completely visible:

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \bar{y})^2}$$



Fig 5.3 — Training R^2 keeps falling as alpha grows (the model is being restrained), but testing R^2 actually rises for a while before falling — that peak is your best alpha.

SECTION 06 · HANDS-ON CODE

Coding Ridge Regression

The one-line, production way (scikit-learn)

python

```python
from sklearn.linear_model import Ridge
from sklearn.datasets import load_diabetes
from sklearn.model_selection import train_test_split

X, y = load_diabetes(return_X_y=True)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=2)

# alpha here IS lambda -- scikit-learn just calls it alpha
reg = Ridge(alpha=0.1, solver='cholesky')
reg.fit(X_train, y_train)

print("R2 score:", reg.score(X_test, y_test))
print("Coefficients:", reg.coef_)
print("Intercept:", reg.intercept_)
```

Building it yourself from the matrix formula

This is the exact closed-form solution derived in the previous section, turned into code. It's a great exercise because it forces you to see that scikit-learn's `Ridge` isn't magic — it's just this formula, solved efficiently.

python — my_ridge.py

```python
import numpy as np

class MyRidge:
    def __init__(self, alpha=0.1):
        self.alpha = alpha
        self.m = None       # will hold all slope coefficients
        self.b = None       # will hold the intercept

    def fit(self, X_train, y_train):
        # add a column of 1's so the intercept is folded into the same matrix math
        X_train = np.insert(X_train, 0, 1, axis=1)

        # identity matrix -- but don't penalize the intercept term
        I = np.identity(X_train.shape[1])
        I[0][0] = 0

        # W = (X^T X + lambda * I)^-1 * X^T * y
        result = np.linalg.inv(
            np.dot(X_train.T, X_train) + self.alpha * I
        ).dot(X_train.T).dot(y_train)

        self.b = result[0]
        self.m = result[1:]

    def predict(self, X_test):
        return np.dot(X_test, self.m) + self.b
```

🧮 WHY WE ZERO OUT THE INTERCEPT ROW OF I

The intercept represents where the line crosses the y-axis — shrinking it doesn't help fight overfitting the way shrinking slope coefficients does, so by convention we exclude it from the penalty. That's why `I[0][0]` is set to `0`.

Solving it with Gradient Descent instead

The closed-form (matrix inverse) solution above has a serious weakness: inverting a large matrix has roughly `O(n³)` time complexity. On very large datasets this becomes painfully slow. The practical fix is Gradient Descent — take small steps downhill on the loss surface instead of solving for the minimum in one shot.

$$\frac{\partial J}{\partial w} = -2X^T(y - Xw) + 2\lambda w$$

$$w_{\text{new}} = w_{\text{old}} - \eta \frac{\partial J}{\partial w}$$

python — my_ridge_gd.py

```python
import numpy as np

class MyRidgeGD:
    def __init__(self, epochs, learning_rate, alpha):
        self.learning_rate = learning_rate
        self.epochs = epochs
        self.alpha = alpha
        self.coef_ = None
        self.intercept_ = None

    def fit(self, X_train, y_train):
        self.coef_ = np.ones(X_train.shape[1])
        self.intercept_ = 0
        theta = np.insert(self.coef_, 0, self.intercept_)
        X_train = np.insert(X_train, 0, 1, axis=1)

        for i in range(self.epochs):
            theta_derivative = (
                X_train.T.dot(X_train).dot(theta)
                - X_train.T.dot(y_train)
                + self.alpha * theta
            )
            theta = theta - self.learning_rate * theta_derivative

        self.coef_ = theta[1:]
        self.intercept_ = theta[0]

    def predict(self, X_test):
        return np.dot(X_test, self.coef_) + self.intercept_
```

> **NOTE**
>
> Unlike scikit-learn's built-in `SGDRegressor`, which automatically decays its learning rate over time, this simple version uses a fixed learning rate — so the result will be close to, but not identical to, the closed-form solution. Try running it with different `epochs` and `learning_rate` values on the diabetes dataset and compare the R² score to `MyRidge` above.

SECTION 07 · LASSO REGRESSION

Lasso Regression (L1 Regularization)

Lasso stands for **Least Absolute Shrinkage and Selection Operator**. It's built exactly like Ridge, with one small but explosive change: instead of penalizing the **sum of squares** of the coefficients, it penalizes the **sum of absolute values**:

$$J(w) = \sum_{i=1}^{n}(y_i - \hat{y}_i)^2 + \lambda \sum_{j=1}^{k}|w_j|$$

That's it — that's the only difference in the formula. But this tiny change in the penalty term (squares → absolute values) completely changes the personality of the resulting model.

What actually happens on real data




*Fig 7.1 — As alpha increases, coefficients don't just shrink — they get knocked out to **exactly zero**, one by one. By alpha ≈ 20, only two or three features (bmi, s5, bp) survive.*

WHY THIS MATTERS: AUTOMATIC FEATURE SELECTION

Because unimportant coefficients become *exactly* zero (not just very small), Lasso effectively deletes those features from the model for you. If you're working with a high-dimensional dataset where you suspect many columns are noise, Lasso will quietly perform feature selection as a side effect of training — Ridge cannot do this.

The geometric intuition (why a diamond changes everything)

Regularization can be viewed as a constrained optimization problem: minimize the plain MSE loss, but keep the weight vector inside a "budget" region.

$\|w\|_1 = \sum_{j=1}^{k}|w_j| \leq t$

for Ridge, and

$\|w\|_1 = \sum_{j=1} |w_j| < t$

for Lasso.




Fig 7.2 — The red contours are the unregularized loss function's "level curves" (closer to the center = lower error). The colored shape is the constraint region. The final solution is wherever the loss contour first touches the constraint boundary.

Here's the entire secret in one sentence: a **circle** (Ridge's constraint) has no corners, so the loss contour almost always touches it at some smooth point where both coordinates are non-zero. A **diamond** (Lasso's constraint) has sharp **corners** sitting exactly on the axes — and it is geometrically far more likely for the loss contour to first touch the diamond precisely at one of those corners, where one of the coordinates is exactly zero.

> ⚠ **INTERVIEW-FAVORITE FOLLOW-UP**
>
> "Why is Ridge called Ridge?" — this traces back to a more advanced discussion of *hard-constraint* vs *soft-constraint* optimization formulations, where the shape of the loss surface, once constrained, visually resembles a ridge. It's a deeper rabbit hole than most courses go into — the geometric picture above is what you need for 95% of practical and interview purposes.

SECTION 08 · DEEP DIVE

Why Lasso Zeroes Out Coefficients

This is one of the most commonly asked machine learning interview questions — and most people can only answer it geometrically (Section 07). Here's the actual algebra, worked through for the single-variable case, exactly the way you'd derive it by hand.

Step 1 — recall the OLS and Ridge formulas

Plain OLS:

$$m = \frac{\sum_i (x_i - \bar{x})(y_i - \bar{y})}{\sum_i (x_i - \bar{x})^2}$$

Ridge (lambda joins the **denominator**):

$$m = \frac{\sum_i (x_i - \bar{x})(y_i - \bar{y})}{\sum_i (x_i - \bar{x})^2 + \lambda}$$

Step 2 — differentiate the Lasso loss

The Lasso loss contains $\lambda|m|$, and the absolute value function isn't differentiable at zero — so we must split the problem into cases based on the sign of m. Carrying out the same differentiate-and-set-to-zero process for each case produces two different formulas:

$$m = \frac{\sum_i (x_i - \bar{x})(y_i - \bar{y}) - \lambda}{\sum_i (x_i - \bar{x})^2} \quad \text{(if slope} > 0\text{)}$$

$$m = \frac{\sum_i (x_i - \bar{x})(y_i - \bar{y}) + \lambda}{\sum_i (x_i - \bar{x})^2} \quad \text{(if slope} < 0\text{)}$$

🧮 THE CRITICAL DIFFERENCE FROM RIDGE

Notice λ now sits in the **numerator**, being directly added or subtracted — not in the denominator like Ridge. This is called **soft-thresholding**, and it behaves completely differently:

- As you increase λ, you are directly subtracting (or adding) it from the numerator, so the result shrinks **linearly** and will eventually cross zero.
- The moment the computed value would flip sign (become negative when it should be positive, or vice-versa), the algorithm instead **freezes the coefficient at exactly zero** — because using the "wrong-sign" formula would push it the wrong direction. This is exactly the kink you saw in Fig 5.1.

In plain code — the soft-thresholding function

This tiny function is the mathematical heart of every Lasso solver (including scikit-learn's, which uses a more efficient version of this same idea called coordinate descent):

python

```python
def soft_threshold(rho, lam):
    # rho = the raw correlation term (numerator) before regularization
    if rho < -lam:
        return rho + lam
    elif rho > lam:
        return rho - lam
    else:
        return 0.0   # pinned at exactly zero
```

💡 ONE-SENTENCE ANSWER FOR INTERVIEWS

"Ridge's lambda sits in the denominator of the closed-form solution, so it can only ever shrink a coefficient asymptotically toward zero. Lasso's lambda sits in the numerator, directly subtracted, so once it's large enough it drives the coefficient exactly to zero and pins it there — that's the mathematical origin of Lasso's feature-selection behavior."

Using it in scikit-learn

python

```python
from sklearn.linear_model import Lasso

reg = Lasso(alpha=0.1)   # alpha is lambda again
reg.fit(X_train, y_train)

print("R2 score:", reg.score(X_test, y_test))
print("Coefficients:", reg.coef_)   # many of these will be exactly 0.0
```

SECTION 09 · COMBINING BOTH

Elastic Net: The Best of Both Worlds

By now you've seen the two ends of the spectrum. Ridge keeps every feature but never fully eliminates any of them — perfect when you already know all your columns matter. Lasso aggressively prunes features down to a sparse set — perfect when you know many columns are useless. But real-world datasets rarely come with that kind of certainty attached. What do you do when you're handed a dataset with fifty, a hundred, or a thousand columns and you genuinely have **no idea** in advance which of those two situations you're in?

> **THE MOTIVATING PROBLEM**
>
> If you knew every input column was useful, you'd reach for Ridge. If you knew many columns were noise, you'd reach for Lasso. Elastic Net exists for the very common third case: a large dataset where you simply don't know which of those two assumptions holds, and you don't want to manually test both from scratch.

Elastic Net is nothing more than Ridge and Lasso added together into a single loss function, each penalty carrying its own independent strength, conventionally called `a` (for the L1/Lasso term) and `b` (for the L2/Ridge term):

$$J(w) = \sum_{i=1}^{n}(y_i - \hat{y}_i)^2 + a\sum_j |w_j| + b\sum_j w_j^2$$

Notice this is exactly the Ridge penalty and the Lasso penalty, sitting side by side in the same expression, each scaled by its own coefficient. If `b = 0`, this collapses to pure Lasso. If `a = 0`, this collapses to pure Ridge. Elastic Net simply lets you dial in *how much of each* you want.

How scikit-learn actually parameterizes this

Rather than asking you to tune two raw coefficients `a` and `b` directly, scikit-learn re-parameterizes them into two more intuitive hyperparameters: an overall regularization strength `alpha`, and a mixing ratio `l1_ratio` that decides how that total strength is split between the two penalties:

$$\lambda_{\text{total}} = a + b$$

$$\text{l1_ratio} = \frac{a}{a+b}$$

...which you can just as easily invert to recover the raw penalty strengths from scikit-learn's two parameters:

$$a = \text{l1_ratio} \times \lambda_{\text{total}}$$

$$b = (1 - \text{l1_ratio}) \times \lambda_{\text{total}}$$

READING L1_RATIO

- `l1_ratio = 1.0` → `b = 0` → pure Lasso
- `l1_ratio = 0.0` → `a = 0` → pure Ridge
- `l1_ratio = 0.5` (the scikit-learn default) → an equal 50/50 split between the two penalties
- `l1_ratio = 0.9` → 90% Lasso-style behavior, 10% Ridge-style behavior

The geometric picture

Remember the circle-vs-diamond picture from Sections 7 and 8? Elastic Net's constraint region is what you'd expect from blending the two: a **rounded diamond** (technically closer to a superellipse). It keeps Lasso's corners on the axes — so it can still zero out coefficients — but rounds off the sharp edges the way Ridge's circle does, which makes its behavior on correlated features far more stable.




Fig 9.1 — Elastic Net's constraint region sits between Ridge's smooth circle and Lasso's sharp diamond. It keeps the corners (so it can still perform feature selection) while softening the edges (so it handles correlated features more gracefully than pure Lasso).

The other big reason to use Elastic Net: multicollinearity

Multicollinearity is the situation where two or more input columns are strongly correlated with each other — one changes and the other tends to change right along with it. A classic example is height and weight: as height goes up, weight tends to go up too.




Fig 9.2 — Height and weight are a classic multicollinear pair: knowing one tells you a lot about the other, which confuses a model trying to assign each an independent weight.

⚠ WHY MULTICOLLINEARITY IS A PROBLEM FOR LASSO SPECIFICALLY

When two columns carry almost the same information, plain Lasso tends to pick one of them **somewhat arbitrarily**, drive its coefficient to a large value, and zero out the other entirely — even though both were genuinely informative. Elastic Net's Ridge component discourages this arbitrary, all-or-nothing behavior: correlated features are more likely to shrink *together*, in proportion to their actual usefulness, rather than one being kept and the other being deleted by chance.

What this looks like on real data

Running all four techniques on the diabetes dataset side by side:




Fig 9.3 — On this dataset, a well-tuned Elastic Net edges out plain Ridge, Lasso, and unregularized linear regression on held-out test data — the whole point of blending both penalties.

Code: three ways to use Elastic Net

1. The dedicated `ElasticNet` class — the simplest and most common approach:

python

```python
from sklearn.linear_model import ElasticNet

# alpha = total regularization strength, l1_ratio = mixing proportion
reg = ElasticNet(alpha=0.005, l1_ratio=0.9)
reg.fit(X_train, y_train)

print("R2 score:", reg.score(X_test, y_test))
print("Coefficients:", reg.coef_)
```

2. Via `SGDRegressor` — useful when you're already using gradient-descent-based training and just want to switch the penalty type:

python

```python
from sklearn.linear_model import SGDRegressor

reg = SGDRegressor(
    penalty='elasticnet',   # instead of 'l1' or 'l2'
    alpha=0.005,
    l1_ratio=0.9,
    max_iter=2000,
)
reg.fit(X_train, y_train)
print("R2 score:", reg.score(X_test, y_test))
```

3. Automatic hyperparameter search — since Elastic Net now has *two* hyperparameters to tune instead of one, cross-

validation becomes even more valuable:

python

```python
from sklearn.linear_model import ElasticNetCV

reg = ElasticNetCV(
    alphas=[0.001, 0.01, 0.1, 1],
    l1_ratio=[0.1, 0.5, 0.7, 0.9, 0.95, 0.99],
    cv=5,
)
reg.fit(X_train, y_train)
print("Best alpha:", reg.alpha_)
print("Best l1_ratio:", reg.l1_ratio_)
```

🎯 PRACTICAL RECOMMENDATION

The dedicated `ElasticNet` class is more numerically optimized specifically for this combined penalty than manually configuring `SGDRegressor`, so prefer it unless you have a specific reason (like wanting to combine it with other SGD-specific settings, or online / incremental learning) to use the SGD route.

💡 QUICK SUMMARY — WHEN TO REACH FOR ELASTIC NET

- You have a **large number of input columns** and no prior knowledge of which ones matter.
- Your input columns show meaningful **multicollinearity**.
- You want the option of automatic feature selection (like Lasso) without fully committing to Lasso's sometimes-unstable, all-or-nothing behavior on correlated groups.

SECTION 10 · MODEL SELECTION

Choosing Lambda: The Sweet Spot

Lambda (alpha) is a **hyperparameter** — it is not learned from the data by the optimization process itself; you have to search for a good value. There are two closely related concerns to think through together: bias/variance, and generalization error.

Effect on bias and variance

- **Very small lambda** → the model fits training data very tightly → low bias, but the fit is very sensitive to which exact training points you got → high variance.
- **Very large lambda** → the model gets pushed toward a flat, overly simple fit → high bias, but it becomes very stable across different training samples → low variance.

The practical recipe

1. Split your data into training and testing (or use cross-validation).
2. Train the model across a wide range of lambda values — usually spaced on a log scale, e.g. `0.0001, 0.001, 0.01, 0.1, 1, 10, 100, 1000`.
3. Plot training vs testing performance (R^2 or MSE) against lambda.
4. Pick the lambda where testing performance peaks (or MSE is lowest) — this is almost always somewhere in the "valley" of the bias-variance curve, not at either extreme.

IN SCIKIT-LEARN, THIS SEARCH IS AUTOMATED FOR YOU

```
from sklearn.linear_model import RidgeCV, LassoCV

ridge_cv = RidgeCV(alphas=[0.001, 0.01, 0.1, 1, 10, 100])
ridge_cv.fit(X_train, y_train)
print("Best alpha:", ridge_cv.alpha_)

lasso_cv = LassoCV(cv=5)
lasso_cv.fit(X_train, y_train)
print("Best alpha:", lasso_cv.alpha_)
```

Revisit Fig 5.3 from Section 5 — that's exactly this process carried out on the diabetes dataset, and it shows the peak testing R^2 score happens around alpha ≈ 0.15, not at alpha = 0 (plain linear regression, which overfits slightly) nor at very high alpha (which underfits).

SECTION 11 · COMPARISON

Ridge vs Lasso — The Full Comparison

Aspect	Ridge (L2)	Lasso (L1)
Penalty term	Sum of squared coefficients	Sum of absolute coefficients
Coefficients can reach exactly 0?	No — only approach it	Yes — routinely
Performs feature selection?	No	Yes, automatically
Constraint region shape	Circle / sphere (smooth)	Diamond (has corners)
Best when...	Most features genuinely matter, and are correlated	Many features are irrelevant / you want a sparse, interpretable model
Closed-form solution exists?	Yes — matrix inverse	No general closed form — needs iterative solvers (coordinate descent)
Sensitivity to correlated features	Shrinks correlated features together, more stable	Arbitrarily picks one from a correlated group, drops the rest
Effect of a very large lambda	All coefficients shrink close to 0, model underfits	All coefficients become exactly 0, model underfits severely
Common alternate name	Tikhonov regularization	Least Absolute Shrinkage and Selection Operator

THE ONE PRACTICAL TIP WORTH MEMORIZING

Regularization is most useful when the **number of input columns is reasonably large** (roughly two or more, and increasingly valuable as that number grows). With a single input feature, there's very little for regularization to do — its entire value comes from taming many coefficients working together.

SECTION 12 · PRACTICAL GUIDANCE

Rules of Thumb

Choosing between Ridge, Lasso, and Elastic Net

- Start with **Ridge** as your default regularized baseline — it's stable, has a closed-form solution, and rarely does anything surprising.
- Switch to **Lasso** when you suspect many of your features are noise, or when you specifically want a sparse, easy-to-explain model (fewer non-zero coefficients = easier to interpret and deploy).
- Reach for **Elastic Net** when you have many correlated features and want feature selection without Lasso's instability on correlated groups.

Always remember to scale your features first

Because the penalty term sums up coefficients directly, a feature measured in the thousands (like "annual salary") will naturally have a tiny coefficient, while a feature measured in single digits (like "years of experience") will have a large one — and the penalty would unfairly crush the second one much harder. Always standardize (zero mean, unit variance) your features before applying Ridge or Lasso.

python

```python
from sklearn.preprocessing import StandardScaler

scaler = StandardScaler()
X_train_scaled = scaler.fit_transform(X_train)
X_test_scaled = scaler.transform(X_test)
```

Watch out for these common mistakes

⚠ PITFALLS

- **Regularizing the intercept.** The intercept should almost always be excluded from the penalty term (see the `I[0][0] = 0` trick in Section 6).
- **Fitting the scaler on the test set.** Always call `fit_transform` on the training set and only `transform` (never `fit`) on the test set — otherwise you leak information from the test set into training.
- **Assuming Lasso is always better because it's "smarter."** If every feature genuinely contributes signal, Lasso's aggressive zeroing can throw away useful information and actually perform worse than Ridge.

SECTION 13 · INTERVIEW PREP

Questions You Must Be Able to Answer

Q1. WHAT HAPPENS TO THE COEFFICIENTS AS YOU INCREASE LAMBDA?

A: In both Ridge and Lasso, coefficients shrink toward zero. Larger-magnitude coefficients shrink faster than smaller ones. In Ridge, no coefficient ever reaches exactly zero. In Lasso, coefficients are driven to exactly zero once lambda passes a certain threshold for that feature.

Q2. WHAT IS THE EFFECT OF REGULARIZATION ON BIAS AND VARIANCE?

A: Increasing lambda increases bias and decreases variance. Decreasing lambda does the opposite. There's a sweet-spot lambda that minimizes total error (see Section 10).

Q3. WHY DOES LASSO PERFORM FEATURE SELECTION BUT RIDGE DOESN'T?

A: In the closed-form single-variable solutions, Ridge's lambda appears in the *denominator* (only ever asymptotically shrinking the coefficient), while Lasso's lambda appears in the *numerator*, directly subtracted — which can and does drive coefficients to exactly zero once large enough (soft-thresholding). Geometrically, this is because Lasso's L1 constraint region is a diamond with corners on the axes, while Ridge's L2 region is a smooth circle with no corners (Section 7 & 8).

Q4. WHAT HAPPENS TO THE LOSS FUNCTION'S SHAPE AS LAMBDA INCREASES?

A: The loss curve (plotted against a single coefficient) becomes steeper and its minimum shifts toward the origin. In Ridge, the minimum slides smoothly. In Lasso, the curve develops a visible "kink" exactly at zero, and once lambda is large enough, that kink captures the minimum completely.

Q5. WHEN SHOULD YOU PREFER RIDGE OVER LASSO, OR VICE VERSA?

A: Prefer Ridge when you believe most of your features carry real signal and are correlated with each other. Prefer Lasso when you suspect many features are irrelevant and you want automatic feature selection or a more interpretable, sparse model.

Q6. WHY SHOULD REGULARIZATION ONLY BE USED WHEN THERE ARE TWO OR MORE INPUT FEATURES?

A: With a single feature, there's only one coefficient to shrink, and the practical benefit is minimal. Regularization's value compounds as the number of features (and the risk of overfitting) grows.

Q7. WHAT'S THE TIME-COMPLEXITY CONCERN WITH THE CLOSED-FORM RIDGE SOLUTION, AND HOW DO YOU GET AROUND IT?

A: The matrix inversion in the closed-form solution costs roughly $O(n^3)$, which becomes impractical for very large datasets or very high dimensional data. Gradient Descent (or its stochastic/mini-batch variants) is used instead, trading an exact one-shot solution for an iterative, scalable approximation.

SECTION 14 · WRAP-UP

Final Cheat Sheet

Concept	Formula / Idea
OLS loss	Minimize sum of squared errors — no penalty
Ridge loss	MSE + $\lambda \cdot \sum w^2$
Lasso loss	MSE + $\lambda \cdot \sum \lvert w \rvert$
Elastic Net loss	MSE + $\lambda_1 \sum \lvert w \rvert + \lambda_2 \sum w^2$
Ridge closed form	$W = (X^T X + \lambda I)^{-1} X^T y$
Lasso solver	Coordinate descent / soft-thresholding (no closed form)
lambda = 0	Reduces to plain linear regression
lambda → ∞	Ridge → all weights near 0 (but not 0); Lasso → all weights exactly 0
Small lambda	Low bias, high variance (risk of overfitting)
Large lambda	High bias, low variance (risk of underfitting)

🎓 THE ONE-PARAGRAPH SUMMARY

Regularization adds a penalty to the loss function so that a model is punished for having large coefficients, which fights overfitting by trading a little bit of training accuracy for much better generalization. Ridge (L2) shrinks coefficients smoothly toward zero using a squared penalty and never eliminates a feature. Lasso (L1) uses an absolute-value penalty that can drive coefficients to exactly zero, giving it the extra power of automatic feature selection. Elastic Net blends both. The regularization strength, lambda, is a hyperparameter you tune by watching where testing performance peaks as bias and variance trade off against each other.

Built as a structured, from-scratch-to-production study guide on Regularization.
Ridge, Lasso, and Elastic Net charts generated from scikit-learn's diabetes dataset.