

MONASH ENGINEERING ENG1060

EFFICIENT CODING

Presented by Tony Vo

Slides by Tony Vo





EFFICIENT CODING



- When you start dealing with complex and large problems, speed is important
 - Make sure your code is correct and well documented before making it faster
- General rules for faster MATLAB code
 - Pre-allocate matrices
 - Avoid creating variables unnecessarily
 - Use functions for repeated code
 - Vectorise your code where possible
 - Suppress unimportant outputs

PRE-ALLOCATE MATRICES



 MATLAB will automatically resize a matrix if you assign a value to non-existent elements

- Resizing a matrix takes time
 - Pre-allocate a matrix if you know it's final size

PRE-ALLOCATE MATRICES



- We often pre-allocate matrices with the zeros function
 - Complementary functions are length and size

```
% preallocate2.m
clc; clear all; close all;
tic

%setting up variables
time = [1:10; 11:20; 21:30; 31:40];
[r,c] = size(time);

%pre-allocating
speed = zeros(r,c);
```

```
%stepping through each time value for i = 1:r  
for j = 1:c  
if time(i,c) < 30  
speed(i,c) = time(i,c).^2;  
elseif time(i,c) < 60  
speed(i,c) = time(i,c).^3;  
else  
speed(i,c) = time(i,c);  
end  
end  
end  
toc
```



THE DIFFERENCE PRE-ALLOCATION MAKES

- Pre-allocating can speed up the code by orders of magnitude!
 - Pre-allocated: Elapsed time is 0.000201 seconds.
 - No allocation: Elapsed time is 0.012240 seconds.

```
% no_preallocate.m
clc; clear all; close all;
tic
max n = 6e4:
% A lot of values in my_matrix2
% my_matrix2(1) = 1^2; my_matrix2(2) = 2^2 etc...
for n = 1:max n
  my_matrix2(n) = n^2;
end
toc
```

```
% preallocate.m
clc; clear all; close all;
tic
max n = 6e4;
% A lot of values in my_matrix2
% my_matrix2(1) = 1^2; my_matrix2(2) = 2^2 etc...
my_matrix2 = zeros(1, max_n);
for n = 1:max n
  my_matrix2(n) = n^2;
end
toc
```



AVOID CREATING VARIABLES UNNECESSARILY

- It takes time to create variables, especially large matrices
 - So, the fewer variables you create, the faster your code
- As with pre-allocation, this is important with large matrices
- Example:

```
>> A = ones(1e6,1);
>> B = A + 3;
>> % C is same as above
>> C = 4*ones(1e6,1);
```

MONASH University

USE FUNCTIONS FOR REPEATED CODE

- Functions facilitate code reusability and can make your code faster
- MATLAB will compile your functions and store them in memory for future use
 - This means that after calling a function once, every call to the same function will be faster than the first
- Example: SineTaylor() function from previous lectures
 - Function is recalled in a for loop for each term

$$\sin(x) = \sum_{n=0}^{\infty} \frac{(-1)^n}{(2n+1)!} x^{2n+1}$$



VECTORIZE YOUR CODE WHERE POSSIBLE

- Loops in MATLAB are very slow
 - Especially compared to C/C++ and Fortran
- MATLAB is designed to rapidly perform matrix-to-matrix operations
 - Hence its name MATrix LABoratory
- You can vectorise your code by using matrix operations to replace loops
 - Vectorisation takes a bit of thinking and planning before programming

MONASH University

VECTORIZE YOUR CODE WHERE POSSIBLE

Examples

- Computes the sine of t values ranging from 0 to 10
- Computes the volume of a cone for D and H values

```
tic

i = 0;

for t = 0:0.01:10

i = i + 1;

y(i) = sin(t);

end

toc
```

```
tic
t = 0:0.01:10;
y = sin(t);
toc
```

```
tic

D=linspace(1,100,10000);

H=linspace(pi,40,10000);

for n = 1:length(D)

V(n) = 1/12*pi*(D(n)^2)*H(n);

end

toc
```

```
tic

D=linspace(1,100,10000);

H=linspace(pi,40,10000);

V = 1/12*pi*(D.^2).*H;

toc
```

SUPPRESS OUTPUTS




- Frequent printing and plotting of outputs can significantly slow down the execution of your code
 - Ensure that you suppress everything and only print important information with fprintf
 - Only plot data that is useful
- Example: In a 4-for loop structure, suppressing 7 lines of code yielded almost 5 times increase in speed
 - Elapsed time is 11.189162 seconds. (unsuppressed code)
 - Elapsed time is 2.477280 seconds. (suppressed code)






- Use the profiler to find sections of code that run slowly
 - Only do this if you NEED to make your program faster
 - Time invested in this task may not be worth it







THE FORMAT COMMAND



- When dealing with real numbers that are very large or small, you may want to adjust the way MATLAB displays information
 - You can do this using the "format" command
- Number format examples:
 - format short/long
 - format bank
 - format hex

```
Command Window
    >> format long
    >> pi
    ans =
        3.141592653589793

>> format short
    >> pi
    ans =
        3.1416
```

THE FORMAT COMMAND



- The format command can also adjust the line spacing
 - format compact/loose

```
Command Window

>> format loose
>> pi

ans =

3.1416

>> format compact
>> pi

ans =

3.1416

>> sommat compact
>> pi

ans =

3.1416
>>
```

SUMMARY



- Efficient coding
- Pre-allocating, functions, vectorisation and suppression
- Formatting your output
- Should you try to replace all loops with vectorisation?