

MONASH ENGINEERING ENG1060

PSEUDOCODE

Presented by Tony Vo

Slides by Tony Vo





WHAT IS PSEUDOCODE?



- Pseudocode is an informal description of what your code intends to do
 - It allows programmers to express their logical steps in a readable format
 - Forces programmers to organise their thoughts
 - Allows others to check your logic before you code
- Major pseudocode components:
 - Variables, assignment, input/output, conditions, repetition
- Thinking ahead reduces the amount of errors/hurdles during the programming stage

PSEUDOCODE: EXAMPLE



- Checking if a student has passed or failed
- Major pseudocode components:
 - Variables
 - Assignment
 - Input/output
 - Conditions
 - Repetition

```
% Checking if a student has passed of failed
% Initialise variables: score
% if score variable is greater or equal to 50, print "pass"
% if score variable is lower than 50, print "fail"
```

EXAMPLE PROBLEM



 Suppose you project that you will be able to deposit the following monthly amounts into a savings account, which pays 3% annual interest compounded monthly, for a period of 5 years. The account initially has no money in it.

Year	1	2	3	4	5
Monthly Deposit (\$)	300	350	400	450	500

 At the start of each year, you withdraw \$3000 to buy a certificate of deposit (CD), which pays 6% interest compounded annually.

EXAMPLE PROBLEM



 Write a MATLAB program to compute how much money you will have at the end of 5 years (total of savings account and CDs).

Assumptions

- You will deposit money in the savings account on the 1st of the month
- Savings account interest paid on the last day of the month
- You withdraw money to buy CD on the 1st day of the year (from year 2 to year 5)
- CD interest paid on the last day of the year.

STEP 1: PSEUDOCODE



- As with any complicated problem, we can start by writing pseudocode
- Major pseudocode components:
 - Variables
 - Assignment
 - Input/output
 - Conditions
 - Repetition

- % Initialise variables
- % savings, CD, monthly deposit
- % Savings account
- % loop for years
- % loop for months
- % calculating interest for 12 months in 1 year
- % deduct the CD
- % CD account
- % interest on CD account over years 2 to 5
- % Adding savings and CD



Year	1	2	3	4	5
Monthly Deposit (\$)	300	350	400	450	500

```
% Initialise variables
% savings, CD, monthly deposit
savings = 0;
CD = 0;
deposit = [300 350 400 450 500];
% Savings account
% loop for years
% loop for months
% calculating interest for 12 months in 1 year (3/12 = 0.25)
% deduct the CD
% CD account
% interest on CD account over years 2 to 5
% Adding savings and CD
```



```
% Initialise variables
% savings, CD, monthly deposit
savings = 0;
CD = 0;
deposit = [300 350 400 450 500];
% Savings account
% loop for years
% loop for months
% calculating interest for 12 months in 1 year (3/12 = 0.25)
% deduct the CD
for year = 1:5 % for years 1 to 5
  % what happens inside each year????
end
% CD account
% interest on CD account over years 2 to 5
% Adding savings and CD
```



```
% Initialise variables
% savings, CD, monthly deposit
savings = 0;
CD = 0:
deposit = [300 350 400 450 500];
% Savings account
% loop for years
% loop for months
% calculating interest for 12 months in 1 year (3/12 = 0.25)
% deduct the CD
for year = 1:5 % for years 1 to 5
  for month = 1:12
          % what happens inside each month????
  end
end
% CD account
% interest on CD account over years 2 to 5
% Adding savings and CD
```



```
% Initialise variables
% savings, CD, monthly deposit
savings = 0;
CD = 0:
deposit = [300 350 400 450 500];
% Savings account
% loop for years
% loop for months
% calculating interest for 12 months in 1 year (3/12 = 0.25)
% deduct the CD
for year = 1.5 % for years 1 to 5
  for month = 1:12
    savings = (1.0025)*(savings+deposit(year)); % calculating interest for 12 months in 1 year
  end
       % how do we subtract the CD????
end
% CD account
% interest on CD account over years 2 to 5
% Adding savings and CD
```

MONASH University

```
% Initialise variables
% savings, CD, monthly deposit
savings = 0;
CD = 0;
deposit = [300 350 400 450 500];
% Savings account
% loop for years
% loop for months
% calculating interest for 12 months in 1 year (3/12 = 0.25)
% deduct the CD
for year = 1:5 % for years 1 to 5
  for month = 1:12
    savings = (1.0025)*(savings+deposit(year)); % calculating interest for 12 months in 1 year
  end
  savings = savings - 3000; % subtracting the CD
end
% CD account
% interest on CD account over years 2 to 5
       % next???
% Adding savings and CD
```



```
% Initialise variables
% savings, CD, monthly deposit
savings = 0;
CD = 0:
deposit = [300 350 400 450 500];
% Savings account
% comments cut
for year = 1.5 % for years 1 to 5
  for month = 1:12
    savings = (1.0025)*(savings+deposit(year)); % calculating interest for 12 months in 1 year
  end
  savings = savings - 3000; % subtracting the CD
end
% CD account
% interest on CD account over years 2 to 5
for k = 2.5 % from year 2 to year 5
  CD = CD + (1.06^{(k-1)})*3000;
end
% Adding savings and CD
  % how do we add the savings and CD accounts?
```



```
% Initialise variables
% savings, CD, monthly deposit
savings = 0;
CD = 0;
deposit = [300 350 400 450 500];
% Savings account
% comments cut
for year = 1.5 % for years 1 to 5
  for month = 1:12
    savings = (1.0025)*(savings+deposit(year)); % calculating interest for 12 months in 1 year
  end
  savings = savings - 3000; % subtracting the CD
end
% CD account
% interest on CD account over years 2 to 5
for k = 2.5 % from year 2 to year 5
  CD = CD + (1.06^{(k-1)})*3000;
end
% Adding savings and CD
% adding the extra 3000 as at the end of year 5, no need to buy a CD
Total savings = savings + CD + 3000;
```

STEP 3: VALIDATE YOUR CODE



- Run your code to ensure that there are no syntax errors
 - Address any errors that are encountered
- Justify your answers. Does it look correct?
 - Check against analytical answers if possible
 - Use different tools (e.g. plot) to validate your answer
 - If the numbers look incorrect, begin debugging your code

SUMMARY



- Engineering problems are often too complicated to code on-the-fly
- Pseudocode allows you to plan your coding in a readable format
- Review your code as not all scenarios are thought out at the initial stage
- Is there a difference between comments and pseudocode?