

APOLLO VALVES - INDUSTRIAL SPECIFICATION SHEET

Series 77F-100-01 Stainless Steel 3-Piece Full Port Ball Valve

1. Product Summary & Identity

Manufacturer Part Number (MPN): 77F14801
Brand: Apollo Valves (Aalberts Integrated Piping Systems)
Manufacturer: Conbraco Industries Inc
Catalog Description: 2 INCH 316SS 3-PC FULL PORT BALL VALVE 1000 WOG FNPT

2. Engineering Specifications & Ratings

Nominal Pipe Size:	2 in (DN50)
Body Material:	Cast Stainless Steel ASTM A351 CF8M (316 SS)
Ball & Stem Material:	316 Stainless Steel
Pressure Rating (WOG):	1000 psi CWP / PN16
Steam Rating (WSP):	150 psi SWP
Connection Type:	Female NPT Threaded (ANSI B1.20.1)
Port Type:	Full Port Design (Direct Flow, Low Pressure Drop)
Actuator Mounting Pad:	ISO 5211 Direct Mount Pad F07/F10
Seat & Packing Material:	Multifill PTFE / RPTFE (Reinforced Teflon)
Temperature Range:	-50 deg F to 450 deg F (-45 deg C to 232 deg C)
Handle Type:	304SS Locking Lever with Blue Vinyl Grip
Standard Certifications:	MSS SP-110, ASME B16.34, NACE MR0175, API 607 Fire-Safe

3. Critical Dimensions

Overall Length (L):	5.59 in (142 mm)
Center to Top Height (H):	5.31 in (135 mm)
Center to Stem Pad (H1):	2.95 in (75 mm)
Lever Length (L1):	7.48 in (190 mm)
Port Diameter (A):	2.00 in (51 mm)
Unit Weight:	7.85 lb (3.56 kg)
Packaging Quantity:	1 ea (Master Pack: 6 ea)