

ALLOCATING PRECISION ACROSS ATTENTION KV AND RECURRENT STATE IN HYBRID LINEAR-ATTENTION SERVING

Anonymous Authors¹

ABSTRACT

Hybrid linear-attention models pair a small set of GQA attention layers with interleaved Gated Delta Network (GDN) layers, so serving memory is split between a growing, quantizable attention KV cache and a fixed per-sequence recurrent state that no KV quantizer touches. Existing systems optimize the KV bit-width and leave state precision fixed. We show that state precision is a second, composable budget dimension. On Qwen3.5-2B/9B served with vLLM on an RTX 5090, switching the GDN state from fp32 to bf16 raises int4-KV capacity by 1.11–1.41x across context lengths 4K–16K (a conservative lower bound: all four measured cells fall below the architecture-derived model, errors -3.24% to -0.18%), and raises the compound int4-over-fp16 KV ratio from 2.245x to 2.675x at 2B/4K. Quality effects are bounded: perplexity shows no detectable change, GSM8K has a significant but under-powered 1.0-point regression at 2B and none at 9B, and RULER shows no detectable difference within wide intervals. Paired goodput gains appear in the Random60 overload region and are reproduced in an independent run, while boundaries remain workload- and threshold-dependent. We report both the capacity model and the exact statistical boundaries of every quality and serving claim.

1 INTRODUCTION

KV caches are the dominant memory consumer in LLM serving, and KV quantization is the standard lever for fitting more context and concurrency into a fixed GPU budget (Liu et al., 2024; Hooper et al., 2024; Sharma et al., 2024). The field has largely been built on attention-only transformers, in which every layer contributes a growing, homogeneous, quantizable cache.

Hybrid linear-attention models break that assumption. Qwen3.5, the subject of this paper, interleaves 18 (2B) or 24 (9B) Gated Delta Network (GDN) layers (Yang et al., 2025) with 6 (2B) or 8 (9B) GQA attention layers. The GDN layers keep no per-token KV; instead each sequence carries a fixed recurrent state that is allocated from the same GPU memory pool as the attention KV. Consequently the serving memory footprint of a hybrid model is two-dimensional: a per-token component that KV quantization can shrink, and a per-sequence state component whose size depends on its own data type. State precision is a deployment switch in vLLM (`mamba_ssm_cache_dtype`), but existing budget analyses, including prior work on state compression itself (Dao, 2026; vLLM Project, 2026), do not treat it as

a dimension that should be jointly allocated with the KV bit-width.

This paper is a system study. It contributes measurement, an architecture-derived capacity model, and a closed-loop evaluation of the two-dimensional precision budget: (i) an architecture-derived capacity model $C(L) = M/(A \cdot L + G)$ in which A is the per-token attention-KV footprint at the chosen KV bit-width and G is the per-sequence state footprint at the chosen state precision; (ii) a capacity measurement protocol that probes exact token capacity on the serving engine and verifies the resolved configurations; (iii) a quality and serving evaluation whose negative and partially-reproduced results are reported at the same precision as the positive ones.

The headline result is a capacity effect. Under int4 KV, bf16 state increases token capacity by 1.3755x (2B, 4K), 1.4063x (9B, 4K), 1.1149x (2B, 16K), and 1.1398x (9B, 16K), and every measured cell falls below the architecture-derived prediction, which justifies treating the model as a conservative lower bound for the int4 column (sign test $P = 0.0625$; errors -0.18% to -3.24%). The compound ratio of int4 over fp16 KV rises from 2.245 to 2.675 at 2B/4K when the state is also bf16. The fp16-KV column is reported cell-by-cell because its signs are mixed ($+2.86\%$, $+3.53\%$, -2.83%); block-rounding granularity shifts with layout and we do not treat the fp16 column as a bound.

The quality evidence is bounded. Perplexity changes

¹Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. **AUTHORERR: Missing \mlsyscorrespondingauthor.**

Preliminary work. Under review by the Machine Learning and Systems (MLSys) Conference. Do not distribute.

are within $[-0.013, +0.007]$ (C4) and $[-0.045, +0.058]$ (PG19) with all confidence intervals containing zero. GSM8K (200 seeded items, 9 seeds) shows a significant 1.0-point regression at 2B state-bf16 ($p = 0.025$), which we report together with its pre-registered minimum detectable effect of 1.16 points and 67.5% observed power; the 9B model shows no regression. RULER intervals are wide (± 5 –33 points) and we make no equivalence claim: the protocol simply cannot detect a difference at 20 samples. Serving boundaries are workload- and threshold-dependent; paired goodput gains in the Random60 overload region reappear in an independent reproduction, but two boundary cells and the ShareGPT 250 ms direction do not, and we restrict every serving claim accordingly.

2 BACKGROUND AND RELATED WORK

KV cache quantization and eviction. KIVI (Liu et al., 2024) and KVQuant (Hooper et al., 2024) established 2–4-bit per-token-head KV quantization; MiniKV (Sharma et al., 2024) and TurboQuant (Zandieh et al., 2025) push toward 2-bit regimes with system co-design. Eviction and hybrid policies (H2O (Zhang et al., 2023), StreamingLLM (Xiao et al., 2023), SnapKV (Li et al., 2024)) release memory by dropping tokens rather than reducing precision. All of these target attention-only models. On a hybrid model they compress only the attention layers; the GDN state remains untouched. Recent system-level work also co-optimizes eviction with quantization within the attention-KV budget (HqeKV (Wang et al., 2026), RDKV (Zhang et al., 2026), ARKV (Lei & Ilager, 2026)).

Hybrid linear-attention architectures. Mamba (Gu & Dao, 2023) and Mamba2 (Dao & Gu, 2024) established selective state-space layers; Gated Delta Networks (Yang et al., 2025) make the recurrence a delta rule. Production hybrids (Jamba (Lieber et al., 2024), RecurrentGemma (Botev et al., 2024), Zamba (Glorioso et al., 2024), Qwen3.5 (Team, 2026)) interleave such layers with a small number of full-attention layers. Serving them requires a per-sequence state in addition to the attention KV; vLLM’s PagedAttention memory manager (Kwon et al., 2023) now allocates both from the same GPU pool.

State precision and compression. Quantizing SSM states has been explored in the low-precision inference literature: ReplaySSM proposes caching inputs instead of state, and vLLM exposes a configurable state-dtype path (Dao, 2026; vLLM Project, 2026); recurrent state caching also appears in inference frameworks such as FlashInfer (Ye et al., 2025). QPruningKV (Zhang et al., 2025) characterized the token-precision trade-off under a fixed byte budget for attention models. State compression itself is prior art. The gap is joint budget accounting: serving systems expose state dtype without analyzing it as a precision dimension that multiplies

with the KV bit-width decision, and without validating the resulting capacity-quality-serving trade-off with replicated measurements.

3 PRECISION BUDGET MODEL

Let L be the context length, A_f and A_q the per-token attention-KV bytes at fp16 and int4 KV respectively, and G the per-sequence state bytes at the chosen state dtype. The maximum number of context tokens served on a single GPU with M bytes available for KV plus state is

$$C(L) = \frac{M}{A \cdot L + G}, \quad (1)$$

where $A \in \{A_f, A_q\}$ and G depends on the state dtype. The capacity ratio from switching the state fp32 to bf16 is

$$r_{state}(L) = \frac{AL + G_{fp32}}{AL + G_{bf16}}, \quad (2)$$

which decreases with L : state dominates at short context, KV dominates at long context. The corresponding KV ratio at a fixed state dtype is $r_{kv}(L) = (A_f L + G)/(A_q L + G)$. The parameters A_q , A_f , and G are derived from the model configuration and the vLLM page layout (per-layer state shapes and padded block sizes), independent of the probed token counts, so the comparison of Eq. (2) against measurements is not circular. Details of the derivation and the padded block accounting are in the appendix.

4 EVALUATION SETUP

Platform and engine. Qwen3.5-2B and Qwen3.5-9B served from a vLLM worktree (commit 55f4768) on a single RTX 5090 (32 GB), with `gpu_memory_utilization=0.85`. All runs record the resolved configuration (`kv_cache_dtype`, `mamba_ssm_cache_dtype`, `sha256` of the serving config) per attempt.

Capacity probes. We use the engine’s maximum-token probe with 4K/16K context, uniform int4 KV (`int4_per_token_head`) or fp16 KV, and state fp32/bf16. Each probe is verified against the resolved dtype and the recorded block counts. The 2x2 capacity experiment is summarized in Table 1.

Quality. Perplexity is measured with a chunk-level harness (write-back rounding at chunk boundaries, chunk 128) on C4 and PG19, 5 sequences, 3 dataset seeds; we report in Section 6 why this harness is an approximation. Reasoning quality uses the vLLM kernel path: GSM8K (Cobbe et al., 2021) with 200 seeded items per seed, greedy, no chain-of-thought, 9 seeds; RULER (Hsieh et al., 2024) with 3 dataset seeds and the engine seed fixed. All comparisons are paired

Table 1. Capacity ratio r_{state} from bf16 state. Measured token capacity ratio and architecture-derived prediction; signed gap is (measured–predicted)/predicted. int4 column: all four cells are below the prediction (conservative lower bound). fp16 column reported per cell.

KV	Model	L	fp32 tok	bf16 tok	gap
int4	2B	4096	2,692,710	3,703,954	−2.37%
int4	2B	16384	4,895,837	5,458,458	−3.24%
int4	9B	4096	315,392	443,538	−0.18%
int4	9B	16384	573,440	653,635	−1.07%
fp16	2B	4096	1,199,383	1,384,448	+2.86%
fp16	2B	16384	1,552,143	1,661,337	+3.53%
fp16	9B	4096	144,104	161,899	−2.83%

across seeds and reported as deltas with 95% confidence intervals.

Serving. Protocol v3: piecewise constant Poisson arrivals, 120 s warmup, 60 s (300 s for boundary confirmation) measurement windows, TTFT thresholds 250–3000 ms, TPOT 200 ms, goodput/offered ≥ 0.95 required for a sustainable boundary, failures counted in the denominator, 3 seeds. Workloads: Random60 (60-token requests) and ShareGPT300 (300-token traces (LMSYS, 2023)). The formal matrix was followed by an independent reproduction with the same contracts; both are committed as atomic artifacts (MLSys, 2026).

5 RESULTS

5.1 Capacity

Table 1 and Figure 2 report the capacity measurements. Under int4 KV, bf16 state raises capacity by 37.6% (2B, 4K), 40.6% (9B, 4K), 11.5% (2B, 16K), and 14.0% (9B, 16K). The fp16-KV column shows smaller gains (7.0–15.4% at 4K) with mixed prediction signs. The discrete page-block rounding is the source of the residual: fp32/bf16 block sizes change with layout (e.g., int4 2B: 2064/1072 tokens per block; fp16: 544/288), and the same rounding that makes the int4 column conservative flips sign under fp16 KV. We therefore frame the capacity model as a conservative lower bound only for the int4-KV column. Figure 1 shows the mechanism: bf16 state halves the per-block state footprint, which doubles the number of allocatable GPU blocks, and the measured ratio is the integer-arithmetic outcome of that re-partitioning.

Figure 2b also shows the compound KV ratio: with fp32 state, int4 KV yields 2.2451x over fp16 KV at 2B/4K; with bf16 state the same comparison yields 2.6754x. The two budget dimensions compound: the state switch and the KV switch do not share memory and their gains multiply.




Figure 1. Block granularity under fp32 vs. bf16 state. (a) Tokens per GPU block and (b) number of allocated GPU blocks for the seven capacity cells. bf16 halves the per-block state footprint; the discrete re-partitioning of blocks explains the residual between measured and modeled r_{state} in Table 1.




Figure 2. Precision budget for hybrid serving. (a) GDN recurrent state (fixed per sequence) and attention KV (growing with context) both draw from the same GPU pool; both bit-width (KV) and state precision are allocatable. (b) Measured vs. predicted r_{state} for the int4/fp16 KV columns (7 cells; gap labels are signed percent error). int4 column is a conservative lower bound: all four gaps are negative.

5.2 Quality: perplexity and reasoning

Perplexity. Under int4 KV, the bf16-state marginal perplexity change is -0.0029 $[-0.0129, +0.0072]$ on C4 and $+0.0065$ $[-0.0447, +0.0578]$ on PG19 (3 seeds, paired 95% CI). Both intervals contain zero, and the magnitude is the same as the state change under fp16 KV ($-0.0003/+0.0004$), so stacking state-bf16 onto int4 KV introduces no measurable additional perplexity cost. The harness is a chunk-level approximation (Section 6); these numbers are supporting evidence for the kernel-level claim, not a substitute for it. Figure 5 quantifies both statements: chunk-boundary rounding moves PPL by roughly 87% when the chunk size is reduced to one, while the marginal state cost under int4 KV stays within 0.007 of the fp16-KV cost on both corpora.

GSM8K. Figure 3 summarizes the 9-seed paired deltas. At 2B, bf16 state loses 1.00 point $[-1.71, -0.29]$, $p = 0.025$,




Figure 3. GSM8K paired deltas. 200 seeded items, greedy, no chain-of-thought, 9 dataset seeds; points and 95% paired CIs. Red intervals exclude zero. The 2B state and int4 regressions are significant; the 2B state effect is below the pre-registered MDE (1.16 pp) with 67.5% power.

with a pre-registered minimum detectable effect of 1.16 points and 67.5% observed power; this is a significant regression whose effect size is below the pre-registered MDE, and we report both. Uniform int4 KV loses 2.72 points $[-4.20, -1.24]$, $p = 0.007$, power 88.3%. Stacking state-bf16 onto int4 KV shows a marginal +1.17 points $[-0.33, +2.66]$ relative to int4 alone: no additional regression. At 9B, bf16 state gains 0.33 points $[-0.07, +0.73]$, $p = 0.141$: no detectable regression. We do not aggregate the 2B and 9B effects. Figure 6 shows the same data at seed resolution: the nine thin lines pair each dataset seed across allocations, and the between-seed spread is what the confidence intervals in Figure 3 summarize.

RULER. Figure 4 reports the five cells that previously showed nonzero single-seed differences (FWE and NIAH-multiquery, 4K/8K, 2B/9B). With three dataset seeds, every confidence interval contains zero; the FWE intervals are ± 5 –33 points wide. We make no equivalence claim: the correct statement is that the protocol cannot detect a difference at 20 samples per cell. The earlier single-seed nonzero differences were dataset-lottery noise.

5.3 Per-layer sensitivity

We separately asked whether any single GDN layer should be kept at higher precision. Bf16 was applied to one GDN layer at a time (18 configurations, 2 corpora, 3 seeds, 36 tests). Two raw intervals excluded zero (C4, layers 2 and 8, $p = 0.049$ and $p = 0.0036$), but neither survives Bonferroni ($\alpha/36$) or BH-FDR correction. There is no evidence for a per-layer precision benefit, so the paper’s allocation dimension is the whole-state switch rather than layer-wise state precision (Figure 7).




Figure 4. Perplexity stacking and RULER. (a) PPL marginal change of bf16 state under int4 KV (C4/PG19, 3 seeds). (b) RULER deltas (bf16 minus fp32 state) for the five previously nonzero cells; 3 dataset seeds, wide CIs, no detectable difference.




Figure 5. Harness boundary and stacking cost. (a) Chunk-level write-back rounding: chunk=1 raises C4 PPL by roughly 87% relative to chunk=128 (1 seed, 1 sequence), so PPL is a chunk-level approximation. (b) Marginal state-bf16 PPL delta under fp16 KV vs. int4 KV (3 seeds): stacking introduces no measurable additional cost.

5.4 Serving

Table 2 reports sustainable arrival rates for int4 and int4+bf16 allocations under the v3 protocol, and Figure 8 shows paired goodput deltas in the overload region.

The only repeated boundary difference is Random60 at 1000 ms (35 vs. 40 in the formal matrix), and it did not reappear in the reproduction (int4 also reached 40 there). ShareGPT at 250 ms shows opposite directions between the two runs. We therefore do not present either workload as improved; the boundary tables are measurements, and we report them without assigning an effect.

What does replicate is the paired goodput delta in the Random60 overload region. At r40, bf16 state improves goodput by 0.334 $[0.078, 0.589]$ at 250 ms and 0.215 $[0.154, 0.276]$ at 500 ms; the independent reproduction measures 0.304 $[0.250, 0.359]$ and 0.138 $[0.082, 0.195]$. At r45/r50 and 2000–3000 ms the deltas are smaller but consistently positive in both runs (e.g., r45/3000 ms: 0.367 $[0.308, 0.426]$ vs. 0.372 $[0.310, 0.435]$). These are paired goodput effects




Figure 6. **GSM8K per-seed paired accuracy**. 200 seeded items, greedy, no chain-of-thought, 9 dataset seeds. Thin lines connect the same seed across allocations; the blue line and markers are seed means. (a) 2B across four allocations; (b) 9B across two.




Figure 7. **Per-layer state sensitivity (2B, C4/PG19, 3 seeds)**. Each row is bf16 applied to one GDN layer; points and paired 95% CIs are deltas against the fp32 baseline. Red rows (C4 layers 2 and 8) have raw $p < 0.05$ and are not significant after Bonferroni or BH-FDR correction.

under a fixed offered rate; we stop short of treating them as sustainable-SLO improvements. The mechanism is only partially isolated: bf16 state changes the allocator’s page/block geometry as well as bytes, and the capacity-to-latency chain is one candidate explanation among several. ShareGPT at 500 ms and above shows boundary parity in both runs.

6 LIMITATIONS

Harness boundary. The perplexity harness rounds the state at chunk boundaries (chunk 128). A chunk-1 ablation changes PPL from 19.35 to 36.16 (+87%), which shows the harness is not equivalent to per-token kernel semantics. We treat PPL as supporting evidence and place the kernel-path quality conclusions (GSM8K, RULER) on the vLLM serving path.

Generalization. All evidence is from Qwen3.5-2B/9B on one RTX 5090. Claims are scoped to GDN-based hybrids; Mamba2-style architectures and other hardware are untested.

Table 2. **Sustainable rate boundaries (req/s, 3 seeds, protocol v3)**. Formal matrix; values in parentheses are the independent reproduction. Differences between runs at Random60/1000 ms and ShareGPT/250 ms show that single boundary cells are run-sensitive and are not claimed as effects.

Workload	Config	250	500	1000	2000	3000
Random60	int4	30	35	35 (40)	40	40
Random60	int4+bf16	30	35	40	40	40
ShareGPT	int4	40 (35)	40	40	40	40
ShareGPT	int4+bf16	35 (40)	40	40	40	40




Figure 8. **Serving, Random60 overload region**. (a) Paired goodput delta (bf16 minus fp32 state) at rates 40–50 req/s, all thresholds, formal and independent reproduction, 3 seeds each, 95% CI. (b) Sustainable-rate boundary parity map (int4 vs. int4+bf16); orange cells differ between allocations, teal cells are equal, with the reproduction value in parentheses.

fp16-state quality is smoke-tested only; fp8/int8 state precisions are future work, so we make no claims about a full precision spectrum.

Serving variability. Overload-region goodput is stable in direction but not in magnitude across runs; boundary cells are run-sensitive. A workload with very long requests or a different mix may not show the effect. We did not test tensor-parallel or multi-GPU configurations, offloading, or prefix caching, each of which changes the memory equation.

Statistical resolution. GSM8K at 2B detects a 1.0-point regression with 67.5% power; effects smaller than ~ 1.16 points are below the pre-registered MDE. RULER cannot distinguish differences smaller than tens of points at 20 samples.

7 CONCLUSION

Hybrid linear-attention serving has two allocatable precision dimensions: the attention-KV bit-width and the recurrent-state dtype. We measured the capacity, quality, and serving consequences of treating both as a joint budget. The capacity model is a conservative lower bound under int4 KV, the compound $KV \times$ state gain is real (2.245 to 2.675 at 2B/4K), quality degradation is bounded and disclosed at the level of statistical power, and the serving benefit is a replicated,

workload-limited paired goodput effect. We release the full measurement contracts, per-seed data, and reproduction artifacts so that the boundary cells and null results can be audited independently. Long-form and retrieval evidence beyond GSM8K and RULER (e.g., LongBench (Bai et al., 2024)) remains single-seed pilot evidence and is excluded from the claims above.

REFERENCES

- Bai, Y., Lv, X., Zhang, J., Lyu, H., Tang, J., Huang, Z., Du, Z., Liu, X., Zeng, A., Hou, L., Dong, Y., Tang, J., and Li, J. Longbench: A bilingual, multitask benchmark for long context understanding. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 3119–3137, 2024.
- Botev, A., De, S., Smith, S. L., Fernando, A., Muraru, G.-C., Haroun, R., Berrada, L., Pascanu, R., Sessa, P. G., Dadashi, R., Hussenot, L., Ferret, J., Girgin, S., Bachem, O., Andreev, A., Kenealy, K., Mesnard, T., Hardin, C., Bhupatiraju, S., Pathak, S., Sifre, L., Rivière, M., Kale, M. S., Love, J., Tafti, P., Joulin, A., Fiedel, N., Senter, E., Chen, Y., Srinivasan, S., Desjardins, G., Budden, D., Doucet, A., Vikram, S., Paszke, A., Gale, T., Borgeaud, S., Chen, C., Brock, A., Paterson, A., Brennan, J., Risdal, M., Gundluru, R., Devanathan, N., Mooney, P., Chauhan, N., Culliton, P., Martins, L. G., Bandy, E., Huntsperger, D., Cameron, G., Zucker, A., Warkentin, T., Peran, L., Giang, M., Ghahramani, Z., Farabet, C., Kavukcuoglu, K., Hassabis, D., Hadsell, R., Teh, Y. W., and de Freitas, N. Recurrentgemma: Moving past transformers for efficient open language models. *arXiv preprint arXiv:2404.07839*, 2024.
- Cobbe, K., Kosaraju, V., Bavarian, M., Chen, M., Jun, H., Kaiser, L., Plappert, M., Tworek, J., Hilton, J., Nakano, R., Hesse, C., and Schulman, J. Training verifiers to solve math word problems. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.
- Dao, T. Replayssm: Cache ssm inputs, not state. *Technical blog*, 2026.
- Dao, T. and Gu, A. Transformers are ssms: Generalized models and efficient algorithms through structured state space duality. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024.
- Glorioso, P., Anthony, Q., Tokpanov, Y., Whittington, J., Pilaault, J., Ibrahim, A., and Millidge, B. Zamba: A compact 7b ssm hybrid model. *arXiv preprint arXiv:2405.16712*, 2024.
- Gu, A. and Dao, T. Mamba: Linear-time sequence modeling with selective state spaces. *arXiv preprint arXiv:2312.00752*, 2023.
- Hooper, C., Kim, S., Mohammadzadeh, H., Mahoney, M. W., Shao, Y. S., Keutzer, K., and Gholami, A. Kvquant: Towards 10 million context length llm inference with kv cache quantization. *arXiv preprint arXiv:2401.18079*, 2024.
- Hsieh, C.-P., Sun, S., Krizan, S., Acharya, S., Rekesh, D., Jia, F., Zhang, Y., and Ginsburg, B. Ruler: What’s the real context size of your long-context language models? In *Conference on Language Modeling (COLM)*, 2024.
- Kwon, W., Li, Z., Zhuang, S., Sheng, Y., Zheng, L., Yu, C. H., Gonzalez, J. E., Zhang, H., and Stoica, I. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th Symposium on Operating Systems Principles (SOSP)*, 2023.
- Lei, J. and Ilager, S. Arkv: Adaptive and resource-efficient kv cache management under limited memory budget for long-context inference in llms. In *Proceedings of the 26th IEEE/ACM International Symposium on Cluster, Cloud and Internet Computing (CCGRID)*, 2026.
- Li, Y., Huang, Y., Yang, B., Venkitesh, B., Locatelli, A., Ye, H., Cai, T., Lewis, P., and Chen, D. Snapkv: Llm knows what you are looking for before generation. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.
- Lieber, O., Lenz, B., Bata, H., Cohen, G., Osin, J., Dalmedigos, I., Safahi, E., Meirom, S., Belinkov, Y., Shalev-Shwartz, S., Abend, O., Alon, R., Asaf, T., Bergman, U., Bar-Tal, Y., Gershon, H., Shtrichman, R., Matias, Y., Weinberger, N., Shapira, Y., Mizrahi, O., and Grinshpoun, T. Jamba: A hybrid transformer-mamba language model. *arXiv preprint arXiv:2403.19887*, 2024.
- Liu, Z., Yuan, J., Jin, H., Zhong, S., Xu, Z., Braverman, V., Chen, B., and Hu, X. Kivi: A tuning-free asymmetric 2bit quantization for kv cache. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024. URL <https://arxiv.org/abs/2402.02750>.
- LMSYS. Sharegpt vicuna unfiltered dataset. Hugging Face dataset repository (lmsys/sharegpt_vicuna_unfiltered), 2023.
- MLSys. Mlsys 2026 call for artifact evaluations. <https://mlsys.org/Conferences/2026/CallForAEs>, 2026.
- Sharma, A., Ding, H., Li, J., Dani, N., and Zhang, M. Minikv: Pushing the limits of llm inference via 2-bit layer-discriminative kv cache. *arXiv preprint arXiv:2411.18077*, 2024.
- Team, A. Q. Qwen3.5 model card (hybrid gated deltanet + gqa architecture). Hugging Face model repository, 2026.

- vLLM Project. vllm pull request 43518: Fp8 ssm cache checkpointing (flashinfer ssu). <https://github.com/vllm-project/vllm/pull/43518>, 2026.
- Wang, H., Gu, Y., Li, F., Wang, Z., Liu, Z., Wang, N., Li, X., and Yu, G. Hqkv: Towards hybrid quantization and eviction for kv cache in long-context llm inference. In *Findings of the Association for Computational Linguistics: ACL 2026*, 2026.
- Xiao, G., Tian, Y., Chen, B., Han, S., and Lewis, M. Efficient streaming language models with attention sinks. *arXiv preprint arXiv:2309.17453*, 2023.
- Yang, S., Kautz, J., and Hatamizadeh, A. Gated delta networks: Improving mamba2 with delta rule. In *International Conference on Learning Representations (ICLR)*, 2025.
- Ye, Z., Chen, L., Lai, R., Lin, W., Zhang, Y., Wang, S., Chen, T., Kasikci, B., Grover, V., Krishnamurthy, A., and Ceze, L. Flashinfer: Efficient and customizable attention engine for llm inference serving. *arXiv preprint arXiv:2501.01005*, 2025.
- Zandieh, A., Daliri, M., Hadian, M., and Mirrokni, V. Turboquant: Extreme kv-cache compression for long-context llm inference. *arXiv preprint arXiv:2504.19874*, 2025.
- Zhang, J., Zhu, D., Song, Y., Wu, W., Kuang, C., Li, X., Shang, L., Liu, Q., and Li, S. More tokens, lower precision: Towards the optimal token-precision trade-off in kv cache compression. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, 2025.
- Zhang, J., Guo, H., Benini, L., and Li, Y. Rdkv: Rate-distortion bit allocation for joint eviction and quantization of the kv cache. *arXiv preprint arXiv:2605.08317*, 2026.
- Zhang, Z., Sheng, Y., Zhou, T., Chen, T., Zheng, L., Cai, R., Song, Z., Tian, Y., Ré, C., Barrett, C. W., Wang, Z., and Chen, B. H2o: Heavy-hitter oracle for efficient generative inference of large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

A CAPACITY MODEL DERIVATION

For Qwen3.5-2B, the GDN state per sequence is derived from the vLLM `MambaStateShapeCalculator` path: 18 layers $\times$ 1,085,440 bytes per layer at fp32 (code-derived; the 9B state is 24.84 MiB). The per-token attention-KV footprints A_f and A_q are computed from the GQA head/layer configuration and the vLLM packed page layout (fp16: 2 bytes per element; int4: 0.5 bytes per element). G for bf16 is half of G_{fp32} . Eq. (2) uses these derived values; the predicted ratios reported in Table 1 are evaluated with no

fitted parameters. The observed residual is attributable to the allocator’s discrete block rounding, which we verified from the per-attempt block-size and block-count records.