API REFERENCE

LED Auction Search API & Location Codes

Reverse-engineered endpoints of the Legal Execution Department's auction-property search system: provinces, districts and sub-districts.

`https://asset.led.go.th/newbidreg/`

77
PROVINCES (2-digit codes)

1012
DISTRICTS (4-digit codes)

696
SUB-DISTRICTS SAMPLED

2+1
LOCATION APIs + SEARCH API

Department of Legal Execution (LED), Ministry of Justice, Thailand

Compiled 14 Oct 2026

CHAPTER 1

How the System Works

The page at **asset.led.go.th/newbidreg/** is the Legal Execution Department's online search for auction properties ("ค้นหาทรัพย์ประกาศขายทอดตลาด"). It is a classic server-rendered ASP application: the province list is baked into the initial HTML, while districts and sub-districts are fetched lazily by two small XMLHttpRequest helpers as the user drills down.

Three pieces of front-end logic drive the location cascading: **loadAmphur(provinceId)** fires when the province `<select>` changes, **loadTambon(amphurId)** fires on district change, and **loadPostcode()** copies the selected sub-district's value into the hidden postcode field. Crucially, the API responses are **not JSON** — both endpoints return ready-made `<option>` HTML fragments that the script injects directly into the next dropdown.

Key facts at a glance

Aspect	Detail
Server technology	Classic ASP (`.asp` pages), UTF-8 responses (option text carries a leading BOM U+FEFF)
Front-end	jQuery 3.7.1 + vanilla XMLHttpRequest; server returns HTML fragments, not JSON
Province list	Hard-coded in page HTML inside `<select id="provinces">` — 77 entries with numeric values
District list	Lazy-loaded via `get_amphur.asp?provinceId=…`
Sub-district list	Lazy-loaded via `get_tambon.asp?amphurId=…`; option **value = postal code**, not an ID
Search submission	Form POSTs location **names** (not codes) + postcode to `default.asp`

CHAPTER 2

The Two Location APIs

Both endpoints live in the same directory as the search page and answer with an HTML fragment containing one `<option>` element per administrative unit. The first item is always a placeholder (**“---- เลือกอำเภอ ----”** / **“---- เลือกตำบล ----”**) with an empty value, and the last item is typically an empty-name entry with a trailing `x000` code that you should discard when parsing.

API 1 — Districts (Amphoe / Khet) GET

```
# Request — provinceId is the 2-digit province code
GET /newbidreg/get_amphur.asp?provinceId=30 HTTP/1.1
Host: asset.led.go.th

# Response — HTML fragment; option value = 4-digit district code
<option value="">---- เลือกอำเภอ ----</option>
<option value="3001">เมืองนครราชสีมา</option>
<option value="3002">ครบุรี</option>
<option value="3003">เสิงสาง</option>
(34 entries total)
<option value="3000"></option>   <!-- trailing empty entry, discard -->
```

API 2 — Sub-districts (Tambon / Khwaeng) GET

```
# Request — amphurId is the 4-digit district code from API 1
GET /newbidreg/get_tambon.asp?amphurId=3001 HTTP/1.1
Host: asset.led.go.th

# Response — option value = POSTAL CODE (5 digits), text = sub-district name
<option value="">---- เลือกตำบล ----</option>
<option value="30000">โคกกรวด</option>
<option value="30000">ในเมือง</option>
<option value="30310">จอหอ</option>
(25 entries total)
```

Important: sub-districts are identified by **name + postal code** only. The site never uses a numeric sub-district code — when the user picks a tambon, JavaScript writes the *name* into the hidden `tumbol` field and the *postal code* into the hidden `postcode` field. A few tambons return an empty postcode, which the form submits as blank.

Quick test with curl

```
curl -s "https://asset.led.go.th/newbidreg/get_amphur.asp?provinceId=83"
curl -s "https://asset.led.go.th/newbidreg/get_tambon.asp?amphurId=8301"
# 83 = Phuket → 8301 เมืองภูเก็ต, 8302 กะทู้, 8303 ถลาง
```

CHAPTER 3

How the Codes Are Numbered

The codes follow the **standard Thai government administrative numbering** (the same scheme used by the Department of Provincial Administration and reflected in ISO 3166-2:TH), with a few LED-specific additions. Understanding the composition rule lets you derive a district's parent province, or sanity-check values you scrape.

Level	Format	Example	Notes
Province	`2 digits`	`30`	Standard code; Bangkok = 10, unique list of 77
District	`2+2 = 4 digits`	`30 01`	First 2 digits = parent province; 01 is usually the capital district (เมือง…)
Sub-district	`name + postcode`	ในเมือง + 30000	**No numeric code** is used by this site

Two quirks are worth knowing before you trust the data blindly. First, the LED list contains **extra district codes beyond the official set** — mostly Bangkok branch offices with parenthesised names (codes 1052–1071, e.g. คลองสาน(บางลำภูล่าง)) and a duplicate in Nakhon Ratchasima (3033 duplicates 3022 หนองบุญมาก). That is why the full dataset holds **1012 district entries** versus the ~878 official amphoe. Second, the on-page province dropdown actually lists Uttaradit twice — code 53 as both อุตรดิต (typo) and อุตรดิตถ์ (correct).

CHAPTER 4

Complete Province Code Table (77)

Extracted from the embedded `<select id="provinces">`. The district count is what `get_amphur.asp` returns for each province, including the LED-specific extras described in Chapter 3.

Code	Thai name	English name	Districts
10	กรุงเทพมหานคร	Bangkok	64
11	สมุทรปราการ	Samut Prakan	7
12	นนทบุรี	Nonthaburi	7
13	ปทุมธานี	Pathum Thani	7
14	พระนครศรีอยุธยา	Phra Nakhon Si Ayutthaya	16
15	อ่างทอง	Ang Thong	8
16	ลพบุรี	Lopburi	11
17	สิงห์บุรี	Sing Buri	6
18	ชัยนาท	Chai Nat	8
19	สระบุรี	Saraburi	14
20	ชลบุรี	Chonburi	14
21	ระยอง	Rayong	8
22	จันทบุรี	Chanthaburi	10
23	ตราด	Trat	8
24	ฉะเชิงเทรา	Chachoengsao	13
25	ปราจีนบุรี	Prachinburi	14
26	นครนายก	Nakhon Nayok	4
27	สระแก้ว	Sa Kaeo	9
30	นครราชสีมา	Nakhon Ratchasima	33
31	บุรีรัมย์	Buriram	23
32	สุรินทร์	Surin	17
33	ศรีสะเกษ	Sisaket	22
34	อุบลราชธานี	Ubon Ratchathani	32
35	ยโสธร	Yasothon	9
36	ชัยภูมิ	Chaiyaphum	16
37	อำนาจเจริญ	Amnat Charoen	7
39	หนองบัวลำภู	Nong Bua Lamphu	6
40	ขอนแก่น	Khon Kaen	34

Code	Thai name	English name	Districts
41	อุดรธานี	Udon Thani	26
42	เลย	Loei	14
43	หนองคาย	Nong Khai	18
44	มหาสารคาม	Maha Sarakham	13
45	ร้อยเอ็ด	Roi Et	21
46	กาฬสินธุ์	Kalasin	18
47	สกลนคร	Sakon Nakhon	19
48	นครพนม	Nakhon Phanom	12
49	มุกดาหาร	Mukdahan	7
50	เชียงใหม่	Chiang Mai	28
51	ลำพูน	Lamphun	11
52	ลำปาง	Lampang	14
53	อุตรดิตถ์	Uttaradit	9
54	แพร่	Phrae	8
55	น่าน	Nan	18
56	พะเยา	Phayao	9
57	เชียงราย	Chiang Rai	18
58	แม่ฮ่องสอน	Mae Hong Son	7
60	นครสวรรค์	Nakhon Sawan	15
61	อุทัยธานี	Uthai Thani	8
62	กำแพงเพชร	Kamphaeng Phet	13
63	ตาก	Tak	9
64	สุโขทัย	Sukhothai	9
65	พิษณุโลก	Phitsanulok	9
66	พิจิตร	Phichit	12
67	เพชรบูรณ์	Phetchabun	11
70	ราชบุรี	Ratchaburi	11
71	กาญจนบุรี	Kanchanaburi	14

Code	Thai name	English name	Districts
72	สุพรรณบุรี	Suphan Buri	10
73	นครปฐม	Nakhon Pathom	9
74	สมุทรสาคร	Samut Sakhon	3
75	สมุทรสงคราม	Samut Songkhram	3
76	เพชรบุรี	Phetchaburi	8
77	ประจวบคีรีขันธ์	Prachuap Khiri Khan	8
80	นครศรีธรรมราช	Nakhon Si Thammarat	23
81	กระบี่	Krabi	8
82	พังงา	Phang Nga	8
83	ภูเก็ต	Phuket	3
84	สุราษฎร์ธานี	Surat Thani	19
85	ระนอง	Ranong	5
86	ชุมพร	Chumphon	8
90	สงขลา	Songkhla	17
91	สตูล	Satun	7
92	ตรัง	Trang	11
93	พัทลุง	Phatthalung	12
94	ปัตตานี	Pattani	12
95	ยะลา	Yala	9
96	นราธิวาส	Narathiwat	13
97	บึงกาฬ	Bueng Kan	8

CHAPTER 5

District Codes — Structure & Samples

The complete list of all 1012 districts ships with this document as `districts.csv` / `districts.json`. The samples below illustrate the two patterns you will encounter: ordinary provinces where codes map 1:1 to official amphoe, and Bangkok where LED appends its own branch-office codes.

Bangkok (10) — all 64 entries

Code	District name (Thai)	Type
1070	เขตพระโขนง(บางกะปิ)	LED extra
1041	คลองกุ่ม	
1047	คลองตัน	
1033	คลองเตย	
1018	คลองสาน	
1059	คลองสาน(บางลำภูล่าง)	LED extra
1052	คลองสามวา	LED extra
1044	คันนายาว	
1030	จตุจักร	
1042	จระเข้บัว	
1035	จอมทอง	
1063	จักรวรรดิ (สามเพ็ง)	LED extra
1036	ดอนเมือง	
1026	ดินแดง	
1002	ดุสิต	
1054	ดุสิต(บางซื่อ)	LED extra
1019	ตลิ่งชัน	
1045	ทวีวัฒนา	
1060	ทุ่งครุ	LED extra
1015	ธนบุรี	
1062	ธนบุรี (บางลำภูล่าง)	LED extra
1020	บางกอกน้อย	
1016	บางกอกใหญ่	
1006	บางกะปิ	
1061	บางกะปิ(บึงกุ่ม)	LED extra
1021	บางขุนเทียน	

Code	District name (Thai)	Type
1005	บางเขน	
1058	บางเขน(ตลาดขวัญ)	LED extra
1031	บางคอแหลม	
1049	บางแค	
1029	บางซื่อ	
1046	บางนา	
1050	บางบอน	
1025	บางพลัด	
1004	บางรัก	
1071	บ้านทวาย(พระโขนง)	LED extra
1027	บึงกุ่ม	
1007	ปทุมวัน	
1032	ประเวศ	
1008	ป้อมปราบศัตรูพ่าย	
1014	พญาไท	
1009	พระโขนง	
1001	พระนคร	
1022	ภาษีเจริญ	
1010	มีนบุรี	
1012	ยานนาวา	
1037	ราชเทวี	
1024	ราษฎร์บูรณะ	
1011	ลาดกระบัง	
1038	ลาดพร้าว	
1048	วังทองหลาง	
1039	วัฒนา	
1034	สวนหลวง	
1043	สะพานสูง	

Code	District name (Thai)	Type
1013	สัมพันธวงศ์	
1028	สาทร	
1040	สายไหม	
1055	สำเพ็ง	LED extra
1053	แสนแสบ	LED extra
1023	หนองแขม	
1003	หนองจอก	
1056	หนองจอก(เจียระดับ)	LED extra
1051	หลักสี่	LED extra
1017	ห้วยขวาง	

Nakhon Ratchasima (30) — first 8 of 34

Code	District name (Thai)
3023	แก้งสนามนาง
3019	ขามทะเลสอ
3011	ขามสะแกแสง
3004	คง
3002	ครบุรี
3006	จักราช
3028	เฉลิมพระเกียรติ
3017	ชุมพวง

CHAPTER 6

Sub-District Data — Name + Postcode

A sample of 696 sub-districts across 82 districts was collected to document the response shape (all of Bangkok and Phuket, plus the capital districts of major provinces). The full country can be harvested with the scraper provided alongside

this document. Below is `get_tambon.asp?amphurId=3001` (Mueang Nakhon Ratchasima, first 8 entries).

Mueang Nakhon Ratchasima (3001) — sample

Sub-district name (Thai)	Postcode (option value)
โคกกรวด	30000
โคกสูง	30000
จอหอ	30310
ไชยมงคล	30000
ตลาด	30310
ในเมือง	30000
บ้านเกาะ	30000
บ้านโพธิ์	30000

CHAPTER 7

The Search Endpoint (POST default.asp)

Submitting the form POSTs `application/x-www-form-urlencoded` data to `/newbidreg/default.asp`. Location filters travel as **plain names with prefixes stripped** (the `cleanLocationText()` helper removes จังหวัด / อำเภอ / เขต / ตำบล / แขวง), plus the postal code from the tambon dropdown's value. The page also carries a session key pair: a hidden `oseckey` (observed value 989773 on the sampled page) mirrored by the visible confirmation-code field `seckey`.

Form fields POST default.asp

Field	Type	Meaning / values
`mode`	hidden	`asset` (property list) / `map` (map search) / `lawsuit` (red case number)
`search`	hidden	`ok` when executing a search
`province`	hidden	Province **name**, prefix stripped (e.g. กรุงเทพมหานคร)

Field	Type	Meaning / values
`ampur`	hidden	District **name**, prefix stripped
`tumbol`	hidden	Sub-district **name**, prefix stripped
`postcode`	hidden	Postal code from tambon option value
`region_name`	select	Selling office (128 values, see led_offices.json)
`asset_type`	select	Asset type code (25 values, table below)
`person1`	text	Plaintiff name (ชื่อโจทก์)
`bid_date`	text	Auction date, `dd/mm/yyyy` Buddhist Era
`price_begin / price_end`	text	Price range (THB)
`rai / quaterrai / wa`	text	Land area: rai / ngan / square-wah
`rai_if / quaterrai_if / wa_if`	select	Comparison operator: `1` = equals, `2` = less than, `3` = greater than
`oseckey`	hidden	Session key issued with the page (e.g. 989773)
`seckey`	text	Confirmation code entered by the user (รหัสยืนยัน)
`program_name`	hidden	Constant `newbidreg`

Today's auctions POST asset_day.asp

```
POST /newbidreg/asset_day.asp
search_bid_date=14/10/2569&search=ok
# search_bid_date = today in dd/mm/yyyy (Buddhist Era)
```

CHAPTER 8

Asset Type Codes

The property-type dropdown submits fixed 3–4 character codes. Empty string means “all types”. The full office list (region_name) is long — 128 entries such as กรุงเทพ กองล้มละลาย 1 (Bangkok Bankruptcy Division 1) or นครราชสีมา สาขาพิมาย (branch offices) — and ships in `led_offices.json`.

Code	Asset type (Thai)	English gloss
001	ที่ดินว่างเปล่า	Vacant land
002	ห้องชุด	Condominium unit
003	ที่ดินพร้อมสิ่งปลูกสร้าง	Land with buildings
004	กรรมสิทธิ์ห้องชุด	Condominium title
005	สิทธิการเช่า	Lease rights
006	สิทธิการเช่าอาคารพาณิชย์	Commercial building lease
007	สิทธิการเช่าที่ดิน	Land lease rights
008	ทรัพย์สินต่างๆ	Miscellaneous assets
009	สิ่งปลูกสร้าง	Structures / buildings
010	สิทธิการเช่าที่ดินฯ	Land lease (other)
011	สิทธิการเช่าสิ่งปลูกสร้าง	Structure lease
012	บัตรธนาคาร	Bank card (legal tender)
013	สิทธิการเช่าอาคารราชพัสดุ	Government property lease
014	สิทธิการเช่าอาคาร	Building lease
016	สิทธิการไถ่คืน	Right of redemption
017	สิทธิการเช่าช่วงที่ดิน	Sub-lease of land
018	อาวุธปืน	Firearms
019	บัตรเงินฝาก	Deposit card
020	ธนบัตร	Banknotes
0010	หุ้น	Shares
0011	หน่วยลงทุน	Investment units

Code	Asset type (Thai)	English gloss
0012	พันธบัตร	Bonds
0013	ใบสำคัญ	Warrant / certificate
0014	สลากออมสิน	Savings lottery
0015	สลากออมทรัพย์	Savings certificates

CHAPTER 9

Implementation Notes

Parsing. Treat the endpoints as HTML fragment APIs: match `<option value="...">...</option>` with a tolerant regex, strip the BOM character (`\uFEFF`) that prefixes every district name, drop the placeholder row and any entry whose text is empty. Sort is Thai alphabetical, not by code.

Access. The host currently serves normal browser traffic; requests from outside Thailand may be slow or filtered, so add a realistic `User-Agent` and retry with backoff. A polite rate of roughly one request per second with two concurrent workers stayed error-free during the harvest that produced this dataset. The endpoints are plain GETs without authentication — only the human confirmation code (`seckey`) guards the search POST, not the location lookups.

Replicating the dropdown cascade. Load the province table from `provinces.csv`; on province select, call `get_amphur.asp?provinceId={code}`; on district select, call `get_tambon.asp?amphurId={code}` and remember that the option value is the postcode. When submitting a search, send cleaned names — the exact transformation the site performs is stripping the prefixes จังหวัด, อำเภอ, เขต, ตำบล, แขวง from the display text.

Sample verification: province 83 (Phuket) returns 8301 เมืองภูเก็ต / 8302 กะทู้ / 8303 ถลาง; province 10 (Bangkok) returns 64 entries including LED branch codes; amphur 3001 (Mueang Nakhon Ratchasima) returns 25 tambons with postcodes 30000 / 30310.

Dataset delivered with this reference

All files are UTF-8. CSVs carry a BOM so Excel opens Thai text correctly. The scraper reproduces every table above directly from the live endpoints.

provinces.json / provinces.csv	77 provinces + district counts
districts.json / districts.csv	1,012 district codes
subdistricts_sample.json / .csv	696 sub-districts, 82 districts
led_locations_hierarchy.json	full tree, three levels
led_offices.json	128 selling offices
asset_types.json	25 asset type codes
led_location_scraper.py	re-harvest / extend script

Source: asset.led.go.th/newbidreg · Compiled 14 Oct 2026 · For interoperability research