# CPE334 Software Engineering — Deliverable 1

## NutTiew (นัดติว) — One-to-One Tutoring Appointment System

- **Academic Term:** Semester 1/2026
- **Department & Institution:** Department of Computer Engineering, Faculty of Engineering, King Mongkut's University of Technology Thonburi (KMUTT)
- **Assigned Theme:** Theme 1 — Appointment & Scheduling
- **Repository URL:** https://github.com/Tanaboonnnnn/CPE334-NutTiew
- **Current verified source:** `sprint1@9aa37c0` (10 November 2026; PR #47 merged; latest React calendar, real PostgreSQL 18 / Playwright E2E; see Part F recheck).
- **Integration Staging Base SHA:** `9d24fca` on branch `sprint1`
- **Verified Code & DB Baseline SHA:** `808b906` on branch `docs/18-deliverable-1-integration` (PR #43)
- **Verified GitHub Actions CI Run:** Run 42783770373 — 3/3 Jobs PASS ( `Unit / types / build` , `PostgreSQL 18 / Auth / Slot / Race A` , `Microsoft Edge / Auth / Tutor UI E2E` )
- **Target Release Branch:** `main` (PR #43 merged into sprint1 on 10 Nov 2026; remaining step is reviewed `sprint1 -> main` release PR and immutable tag)
- **Course Handout Deadline:** 8 November 2026, 23:59 ICT *(subsequent PR remediation & final submission timing transparently documented below)*
- **Report Compilation Date:** 10 November 2026 (Asia/Bangkok)
- **Total PDF Pages:** 215 pages

---

### Team Members & Identification

| Student Full Name | Student ID | GitHub Username | Project Role & Responsibility |
|---|---|---|---|
| **Tanboon Teawsawat** | *(Supplied Privately via LEB2 handoff)* | @Tanaboonnnnn | Requirements Discovery Lead (Q01–Q32), Whole-Product SRS & SDS Architecture, Three-Sprint Plan, Project #6 Kanban, Peer Reviewer |
| **Chxtamos** | *(Supplied Privately via LEB2 handoff)* | @Chxtamos | Express 5 REST API & PostgreSQL Schema/Trigger Implementation, Concurrency Lock Ordering, React 19 UI, Automated Tests, PDF Lead |

> **Privacy Notice on Student Identification:** In compliance with student privacy protection and academic repository standards, full KMUTT Student ID numbers are withheld from public Git commit histories and supplied privately through the official university course submission portal (LEB2).

---

## Executive Summary & Document Navigation Guide

**NutTiew (นัดติว)** is a one-to-one tutoring appointment and scheduling web application developed under CPE334 Software Engineering. This document is a **fully self-contained Deliverable 1 submission** packaging **Parts A through F** verbatim from approved canonical repository contracts and verified Sprint 1 test runs, gradable completely offline without opening the repository.

## Actual PDF Page Ranges & Traceability Navigation

| Document Part / Section | Primary Content & Scope | Relevant Requirement / Contract IDs | PDF Pages |
|---|---|---|---|
| **Cover, Team & Navigation** | Metadata, team roles, confidentiality note, actual PDF navigation index | D1 §4.3 | p. 1–2 |
| **Part A: Whole-Product SRS** | Complete problem domain, actors, Sprints 1–3 requirements, rules & Q01–Q32 | `FR-001..036`, `BR-001..035`, `NFR-001..016`, `Q01–Q32` | p. 3–32 |
| **Part B: Feature Inventory & Traceability** | Whole-product feature catalog and canonical `AC-S1-01..35` / `VC/TEST-S1-01..39` mapping | `F-S1-01..05`, `F-S2-01..05`, `F-S3-01..02`, `AC-S1-01..35` | p. 33–48 |
| **Part C: Whole-Product System SDS** | System architecture, Express 5 + React 19 + PostgreSQL DDL, Mermaid diagrams, future Lab 5 deployment design | C4 diagrams, `btree_gist`, `slot_guard_s1`, `booking_guard_s1` | p. 49–66 |
| **Part D: Feasible Three-Sprint Plan** | Milestones, feature dependency order, two-student capacity, risks & Sprint 1 DoD boundary | Deliverable D1/D2/Final checkpoints | p. 67–73 |
| **Part E: Sprint 1 Feature Contracts & STSs** | Complete embedded Part E Feature SDS, UI Spec, UX Amendments, API Spec, Data Spec, Transaction Spec, STS & DoD | All 6 Part E components (30 full contract docs) | p. 74–194 |
| — **E.1 F-S1-01 Authentication & Sessions** | SDS, UI Spec, API Contract, Data Contract, STS & Gate | `AUTH-01..23`, `OD-005-A..E` | p. 74–87 |
| — **E.2 F-S1-02 Tutor Slot Availability** | SDS, UI Spec, Tutor Calendar UX Decision, API Spec, Data Spec, STS | `SLOT-01..17`, Race A | p. 87–111 |
| — **E.3 Shared Booking Data Foundation** | Foundation SDS, Shared Data Spec, Shared DB STS & Trigger Guards | `BDF-01..28`, `booking_guard_s1` | p. 111–126 |
| — **E.4 F-S1-03 Customer Availability** | SDS, UI Spec, Monthly Calendar Option A UX amendment (10 Nov), API & Data Contract, STS | `AVA-01..19` | p. 126–154 |
| — **E.5 F-S1-04 Exclusive Booking & Races** | SDS, UI Spec, API Spec, Data Spec, Transaction Lock/Retry Contract, STS | `BOOK-01..33`, Race B, Race C, `BDF-23` | p. 154–175 |
| — **E.6 F-S1-05 Booking Retrieval & Tutor View** | SDS, UI Spec, API Spec, Data Contract, STS | `RET-01..17`, `INV-RET-01..05` | p. 175–194 |
| **Part F: Sprint 1 Verification & Release Evidence** | 199 distinct tests, `AC-S1-01..35` & `VC/TEST-S1-01..39` matrices, Race A/B/C proofs, verbatim excerpts, TDD history, 8 journey screenshots, peer reviews, contributions, AI use & honest DoD | 199/199 tests PASS; release/LEB2 pending | p. 195–215 |

# Part A: Whole-Product Software Requirements Specification (SRS)

## 0. Document control

| Field | Value |
|---|---|
| Product | CPE334 NutTiew, Theme 1: Appointment and Scheduling (tutoring context) |
| Course | CPE334, Introduction to Software Engineering in the Age of AI Agents, semester 1/2026 |
| Repository | Tanaboonnnnn/CPE334-NutTiew |
| Artifact / version | `docs/srs.md`, v0.1.0, 3 November 2026 |
| Status | **DRAFT FOR PEER REVIEW; NOT INSTRUCTOR-APPROVED** |
| Requirements engineer / PR author | @Tanaboonnnnn |
| Required independent reviewer | @Chxtamos (review request and approval are separate actions) |
| Coverage | Whole-product software requirements for Sprints 1, 2 and 3 |
| Primary readers | Stakeholder/instructor, peer reviewer, requirements/design engineers, test authors and release reviewers |
| Baseline | Confirmed stakeholder decisions Q01-Q32, reviewed Sprint 1 `docs/requirements.md`, available instructor handouts |
| Instructor-source status | `group_work_specs_v1.pdf` was examined; explicitly **Draft for instructor review**, issued 6 October 2026. The final `group_work_specs.docx`, amendments and Theme 1 eligibility are **UNVERIFIED**; formal sign-off is blocked (OD-011/012). |
| Implementation and verification status | This artifact specifies planned behavior and planned validation. It does not certify code, executed tests, a deployed release or passed acceptance tests. |
| Delivery boundary | Deliverable 1 **Part A only**. Parts B-F and Labs 5-7 are separate deliverables. |

### 0.1 Reading rules and status vocabulary

- **Confirmed (Qxx):** a stakeholder decision recorded in the agreed Q01-Q32 baseline. Its product behavior is binding unless a new decision is explicitly approved.
- **Instructor-draft requirement (GW/D1):** a rule contained in the instructor-format handouts actually examined. Treat it as the available course baseline, subject to comparison with the final Master Specification.
- **Engineering interpretation:** a precise, reviewable reading of a confirmed outcome, not a new stakeholder policy (for example, transaction-safe evaluation of Q05).
- **Proposed:** a team suggestion or target that cannot be presented as approved until its owner decides.
- **Open / pending approval:** the source does not settle a policy or the necessary independent confirmation is absent.
- **Verified:** a test or source check actually performed with recorded evidence. No application verification is claimed here.

The statement `MUST` denotes a confirmed stakeholder rule or an applicable instructor-draft minimum, with its provenance in the requirement catalog. `SHOULD (PROPOSED)` is not an acceptance condition until approved. New numeric limits, schema fields, API responses, or service policies must not be disguised as existing requirements.

### 0.2 Navigation


1. Executive overview
2. Stakeholders, actors and glossary
3. Product scope and sprint boundaries
4. System context and user journeys

5. Functional requirements
6. Business rules
7. Non-functional requirements
8. Authorization and privacy
9. Logical domain and lifecycle
10. Time, conflicts and concurrency
11. Exception and boundary scenarios
12. Source and requirement traceability
13. Open decisions and approval gates
14. Exclusions and future compatibility
15. Verification planning
16. Risks, dependencies and change control
17. Review checklist and sign-off
18. References

### 0.3 Document history

| Version | Date | Change | Review / approval |
|---|---|---|---|
| 0.1.0 | 2026-11-03 | Initial whole-product SRS based on Q01-Q32, the Sprint 1 baseline and identified instructor handouts | Draft; independent review and instructor Master verification outstanding |

## 1. Executive overview

### 1.1 Problem, objective and value

Learners need a dependable way to reserve one-to-one lessons with a Tutor at times the Tutor has actually offered. Tutors need control of their own availability and a trustworthy view of reservations. Without a single authoritative reservation workflow, a learner may see stale availability, two learners may claim the same lesson, or one learner may inadvertently reserve overlapping lessons with different Tutors. Cancellation, rescheduling and schedule changes add further ways for the displayed calendar to disagree with the saved records.

NutTiew will let a Tutor publish individual sixty-minute offers and let a Customer reserve an eligible offer. The complete product will support tightly governed cancellation and rescheduling, private Tutor-cancellation notifications, controlled withdrawal of unused offers and a Tutor-only appointment summary. A successful operation must leave coherent persisted records; a failed operation must not change the booking/schedule outcome by accident.

Business value is a clear reservation trail and fewer schedule conflicts, with the Tutor and Customer seeing only records their roles are permitted to access. Payment collection, lesson delivery and attendance certification are not part of the confirmed service.

### 1.2 System boundary and principal risks

The software boundary covers authenticated web interactions, server-side role/ownership and business-rule checks, and persistent storage of Slots, Bookings, history and authorized notifications. A browser's display is never authoritative for a reservation; accepted mutations are determined by the server against current committed data.

Principal risks are simultaneous conflicting writes, ambiguous scheduling policies, disclosure of another learner's booking/cancellation reason, incorrect timezone or cutoff interpretation, loss of history on rescheduling/withdrawal, and treating proposed engineering limits as stakeholder approvals. The final instructor Master and team Theme allocation are also unverified (Section 13).

### 1.3 Agreed product model

One Booking reserves **one exclusive 60-minute Slot** for **one Customer and one Tutor**. The Tutor is the Staff actor; the Customer is the learner. Slots are explicitly published one at a time. Same-Tutor currently offered Slots do not overlap, and one Customer's

active reservations do not overlap across Tutors. Adjacent time intervals are permitted by the conflict rules. Appointments that have ended remain `Booked` unless legitimately cancelled; their `Past` label is a time-derived presentation, not evidence that a lesson was completed.

## 2. Stakeholders, actors and glossary

### 2.1 Roles and boundaries

| Actor / stakeholder | Goal and responsibility | Permitted product operations | Trust, visibility and restrictions |
|---|---|---|---|
| **Customer (Learner)** | Find and reserve one-to-one tutoring; maintain their own bookings | Authenticated availability, create Booking, view own Booking, cancel and reschedule their own eligible Booking, read own Tutor-cancellation notification | Cannot publish/manage Tutor Slots, view another Customer's private records, see Tutor-only summary, or cancel/reschedule another Customer's Booking |
| **Tutor (Staff)** | Offer time, serve assigned Bookings, maintain own timetable | Publish individual Slots, view own authorized schedule/Bookings, cancel assigned Booking within policy, withdraw eligible own Slot, read own Appointment Summary | No global management of another Tutor's schedule; no Customer-originated rescheduling; no arbitrary Customer private data |
| **Anonymous visitor** | Reach the entry/login experience | Access a login interface; authenticate with valid credentials | Cannot read protected identity, private availability/schedule/Booking/notification data, or mutate Slots/Bookings. Public availability is not promised by the baseline. |
| **Application / server** | Apply business policy and own data consistency | Authenticate session, authorize requests, sample server time, arbitrate conflicts, persist atomic outcomes and return role-filtered views | Client IDs, clocks, role flags and stale UI state cannot override server rules |
| **Instructor / product owner** | Confirm permitted theme, assess business baseline and approve material changes | Review the SRS, decide unresolved policy and course-source conflicts | Final Master and Theme assignment require dated evidence |
| **Team reviewer** | Independently check requirements, tests and change history | Review the Issue-linked PR and approve/request changes | Review request, review submission, approval and merge are distinct recorded states |

**Tutor = Staff** is a role equivalence in this product. It does not introduce a separate administrator role. If a Tutor also wants to book a lesson as a learner, an explicit account/role policy would be required; staff privileges alone do not grant Customer-only actions.

### 2.2 Glossary

| Term | Definition |
|---|---|
| Availability Slot / Slot | One Tutor-owned individual offer with a specified start and end exactly 60 minutes apart (Q03-Q04) |
| Currently offered Slot | A published, not-withdrawn offer; it may be unoccupied or occupied |
| Bookable Slot | Currently offered, unoccupied, valid future Slot satisfying the new-Booking cutoff and all eligibility checks at the authoritative decision time |
| Withdrawn Slot | Retained historical Slot that is no longer offered; cannot itself be reactivated (Q32) |
| Appointment | Scheduled one-to-one Customer/Tutor interval associated with a Booking and Slot; not proof of attendance |
| Booking | Persistent reservation with stable identity, owner, assigned Slot/Tutor and business state |
| Active Booking | A `Booked` reservation that has not been cancelled; passage of the session end does not automatically release it |

| Term | Definition |
|---|---|
| Cancelled Booking | Booking transitioned to `Cancelled` by an authorized cancellation workflow; retained according to unresolved data-governance policy |
| Reschedule | Authorized atomic reassignment of an existing Booking to a different eligible Slot while preserving Booking ID and success history |
| Reschedule history | Record of a **successful** change containing old/new Tutor, Slot/time and change timestamp (Q15) |
| In-app notification | Private persisted message for a Customer whose Booking was cancelled by their Tutor (Q21-Q25) |
| Appointment Summary | Tutor-only view of the authorized Tutor's Upcoming Booked, Past Booked and Cancelled counts and underlying lists (Q31) |
| Half-open interval | `[start, end)` ; includes the start, excludes the end, permitting back-to-back adjacency without overlap |
| Business timezone | `Asia/Bangkok` (UTC+07:00), uniform for scheduling and display; the server clock is authoritative |
| T_elig | Server-derived eligibility instant sampled in the final guarded transaction check after any contention wait; adopted as the precise Sprint 1 review interpretation of Q05, subject to Feature SDS approval |
| FR / BR / NFR | Functional requirement / business rule / non-functional requirement |
| AC / STS / VAL | Acceptance criterion / software test specification / **planned** validation scenario in this SRS |

## 3. Product scope and sprint boundaries

### 3.1 Confirmed whole-product capabilities

The agreed product includes Tutor-owned 60-minute slot publishing; Customer browsing and exclusive booking; persisted, role-limited Booking views; Customer cancellation with reopening; Customer-initiated one-time atomic rescheduling (including across Tutors); Tutor cancellation with mandatory reason and Slot withdrawal; private in-app notice with durable read access; controlled withdrawal/replacement of unoccupied future offers; and an authorized Tutor summary. Q01-Q32 are the behavioral baseline, not thirty-two optional enhancements.

### 3.2 Instructor minimum and technical constraints

The examined Group Work Specification v1 §§5-6 and Theme 1 example require a meaningful, tested UI → API/application → persistent-database journey, real login/logout/current identity in Sprint 1, Customer and Staff roles, backend authorization, protected Customer/Staff data, persistent Booking, past/invalid/occupied rejection and concurrent single-Slot exclusivity. The instructor materials call for versioned engineering contracts, automated tests, reviewed GitHub PRs, and later Docker/GCP/CI deployment; the Sprint 1 working software and evidence are **separate Issues** from this SRS.

### 3.3 Sprint allocation is a planning proposal

| Sprint | Proposed delivery responsibility | Requirement status |
|---|---|---|
| **Sprint 1, Deliverable 1** | Login/logout/current identity, role/ownership enforcement, manual sixty-minute Tutor Slots, own Tutor schedule, availability browsing, exclusive Booking, own Customer/Tutor reads, persistence, invalid/too-soon/overlap rejection, three concurrency invariants, Bangkok time, Booked/Past correctness | Scope aligns with reviewed `docs/requirements.md` and the available Theme 1 minimum |
| **Sprint 2, proposed** | Customer cancellation/reopening; one-time Customer reschedule across Tutors, atomic history; Tutor cancellation/reason/withdrawal; authorized unoccupied Slot withdrawal; private cancellation notifications and history | Q07-Q27 and Q32 are confirmed **product rules**; placing these in Sprint 2 is a **proposal**, not an additional stakeholder decision |
| **Sprint 3, proposed** | Tutor-only summary with three categories, counts and lists; remaining approved refinements, integration and full regression | Q31 is a confirmed product rule; timing and scope allocation require review in Issue #12 |

Part D's detailed three-sprint plan belongs to **Issue #12**. This table assigns responsibility so SRS verification is understandable without writing that separate plan. A later-sprint requirement is not a claim that its UI, API or code already exists.

### 3.4 Explicit exclusions, assumptions and unresolved policy

Payments, pricing, self-registration, email/SMS/push reminders, group sessions, lesson platform/location, external calendar synchronization, attendance verification, automatic recurring Slots, and a global administrator are **not approved product capabilities**. They are excluded from the currently agreed baseline; adding them requires a decision and change review, not implementation by inference.

Working hours, permitted days, maximum look-ahead, allowed start-minute grid, exact availability presentation, retention/deletion policy, in-progress summary classification, session/token mechanics, retry response behavior and proposed quality thresholds are **open** (Section 13). In particular, no confirmed working-hours restriction does not establish a promise of twenty-four-hour service.

## 4. System context and user journeys

For each journey below, `S1/S2/S3` is the **proposed verification sprint**, not proof of delivery. On any rejected mutation, previously committed records remain authoritative. API paths, database schema, error codes and UI field layouts belong to the separate design/contracts.

### 4.1 J-01: Tutor publishes one Slot (S1)

**Preconditions:** authenticated Tutor; proposed start is valid/future and does not intersect a currently offered Slot belonging to the same Tutor. **Flow:** Tutor selects one Bangkok start; server derives/checks a sixty-minute interval, confirms ownership and current-offer non-overlap, then persists one offer. **Alternatives/failures:** invalid, past, wrong-role or conflicting proposals are refused; simultaneous overlapping proposals must not both commit. **Postcondition:** the Tutor can retrieve the new unoccupied Slot on their own schedule. **References:** FR-005..007, BR-002..004/006/035; VAL-003..005.

### 4.2 J-02: Customer finds an eligible Slot (S1)

**Preconditions:** authenticated Customer and one or more current offers. **Flow:** server returns permitted Tutor/time details and correct eligibility as of the lookup; Customer selects an offer. **Alternatives/failures:** occupied, too-soon and past Slots cannot be presented as guaranteed bookable; no third-party Booking or cancellation reason is disclosed. Whether ineligible offers are hidden or visibly marked is an open UI decision. **Postcondition:** a possible selection, **not** a reservation. **References:** FR-008/009, BR-005/028/029; VAL-006/036.

### 4.3 J-03: Customer books an exclusive session (S1)

**Preconditions:** authenticated Customer; unoccupied currently offered Slot; no overlapping Active Booking for that Customer; at least 60 minutes before start at authoritative eligibility check. **Flow:** server revalidates all rules under transaction/concurrency control, commits one `Booked` record with trusted Customer and Slot's Tutor, then returns success. **Alternatives/failures:** stale selection, too-soon request, duplicate claim, same-Customer overlap or persistence failure produces no conflicting/partial committed claim. **Postcondition:** Slot is occupied and the Booking is retrievable by its owner and authorized Tutor. **References:** FR-010..013/016/018, BR-001/005/028/034; VAL-007..011/014/030.

### 4.4 J-04: Customer retrieves their Booking (S1)

**Preconditions:** Customer owns a committed Booking. **Flow:** Customer requests own list/detail; server authenticates and filters by ownership, returning saved Tutor/Slot/interval and correct business state. **Alternatives/failures:** a known foreign Booking ID yields no private payload; expired session cannot recover protected content. **Postcondition:** no state change; elapsed appointment may display `Past` while retaining `Booked`. **References:** FR-014/016/017, BR-002/030; VAL-012/013.

### 4.5 J-05: Tutor inspects their schedule and Bookings (S1)

**Preconditions:** authenticated Tutor. **Flow:** server retrieves only Slots and associated Bookings on the Tutor's authorized schedule. **Alternatives/failures:** another Tutor's ID or manipulated filters cannot expand access; no global Customer data retrieval. **Postcondition:** read-only, persisted schedule/Booking view. **References:** FR-007/015, BR-002/033; VAL-002/012.

### 4.6 J-06: Customer cancels own Booking (S2)

**Preconditions:** authenticated owning Customer; active Booking starts at least 30 minutes from authoritative request decision. **Flow:** cancel the Booking as `Cancelled` and reopen its original Slot as one consistent persisted change. **Alternatives/failures:** nonowner, already cancelled or less-than-30-minute attempt is rejected with unchanged records. **Postcondition:** the reopened offer may still be **unbookable** under the independent 60-minute new-Booking rule. **References:** FR-020/021, BR-007/008; VAL-015/016.

### 4.7 J-07: Customer reschedules once (S2)

**Preconditions:** owning Customer; current `Booked` appointment and desired unoccupied Slot; original and destination each start at least 60 minutes after the authoritative decision; no earlier successful reschedule. **Flow:** atomically move the same Booking ID to the destination (possibly a different Tutor), reopen the old Slot, record old/new Tutor/Slot/interval and change time, and increment successful-reschedule count once. **Alternatives/failures:** late original/destination, occupied destination, unauthorized owner, quota exhausted, conflict or persistence failure leaves original Booking, old Slot, destination and history unchanged; failed attempt does **not** consume allowance. **Postcondition:** one live reservation with retained identity and audit history. **References:** FR-022..027, BR-009..016; VAL-017..020.

### 4.8 J-08: Tutor cancels their assigned Booking (S2)

**Preconditions:** authenticated currently assigned Tutor, active Booking at least 60 minutes away, meaningful nonblank reason. **Flow:** server atomically cancels the Booking, withdraws its Slot instead of reopening it, preserves the reason for the owning Customer and creates their private in-app notification. **Alternatives/failures:** wrong Tutor, too-late request, blank/meaningless reason or failed persistence gives no partial cancellation/withdrawal/notification. **Postcondition:** Booking is `Cancelled`, original Slot withdrawn and the Customer informed through the application. **References:** FR-028..031, BR-017..023/026; VAL-021..023.

### 4.9 J-09: Customer reads and rereads a private notice (S2)

**Preconditions:** successful Tutor cancellation created a notice addressed to Customer. **Flow:** Customer reads notice and reason, marks it read if supported, and later opens it again; cancelled Booking detail also shows the authorized reason. **Alternatives/failures:** different Customer, Tutor without applicable authorization or anonymous request gets no notice/reason. **Postcondition:** read state must not erase the message, and no timer automatically expires it. A separate retention/deletion policy remains open. **References:** FR-031/032, BR-021..025; VAL-023/024.

### 4.10 J-10: Tutor withdraws an unoccupied future Slot (S2)

**Preconditions:** authenticated owning Tutor; unoccupied future currently offered Slot. **Flow:** Tutor withdraws that Slot, preserves it as history, then may independently create a **new Slot ID** at a permitted time, even if it overlaps the withdrawn interval. **Alternatives/failures:** direct edit/delete/withdraw while an Active Booking exists is forbidden; withdrawn Slot cannot be reactivated under the same identity. **Postcondition:** old Slot remains historical and no longer blocks current-offer overlap checks. **References:** FR-033/034, BR-026/027/032; VAL-025..027.

### 4.11 J-11: Tutor views Appointment Summary (S3)

**Preconditions:** authenticated Tutor with authorized scheduling records. **Flow:** server provides counts and corresponding lists for Upcoming Booked, Past Booked and Cancelled, restricted to that Tutor's authorized scope; summary rows may lead to permitted details. **Alternatives/failures:** Customer/anonymous/foreign Tutor access is denied; an appointment in progress has no approved bucket until OD-006 is resolved. **Postcondition:** report read changes no Booking business state and does not imply attendance. **References:** FR-035/036, BR-030/031; VAL-028/029.

## 5. Functional requirements

Every `FR-xxx` is a stable **whole-product** identifier. `FR-S1-01..19` remain unchanged in the reviewed Sprint 1 source; the explicit crosswalk is in §12.4. `M` means Must for the stated **product baseline**, not an assertion that a later-sprint feature is due in Sprint 1. Sprint allocation is proposed in §3.3. Each `VAL-xxx` identifies a **planned** way to inspect the requirement, never a passed test. Every mutating FR implicitly requires the backend identity, ownership, timing and transaction rules in §§6, 8 and 10.

## 5.1 Identity and access

| ID | Actor and testable requirement, including safe failure | Source | Priority / sprint | Planned proof; dependency |
|---|---|---|---|---|
| **FR-001** | **Customer/Tutor:** With existing valid credentials, authenticate and establish only that principal's effective role; reject invalid credentials without authenticated access. | GW §5.2; Sprint 1 baseline | M / S1 | VAL-001; identity contract |
| **FR-002** | **Authenticated Customer/Tutor:** Return the current principal's own identity and role without accepting a client-supplied impersonation; anonymous requests reveal no protected identity. | GW §5.2 | M / S1 | VAL-001/002; FR-001 |
| **FR-003** | **Authenticated Customer/Tutor:** Log out and render the prior session/access unusable for protected operations; the exact invalidation/expiry method must be decided in the auth contract. | GW §5.2 | M / S1 | VAL-001/002; OD-005 |
| **FR-004** | **Application/server:** Authenticate and enforce role and record ownership on every protected Slot, Booking, notification and summary action, including crafted requests and URL/ID access; reject unauthorized access without private payload. | GW §5.2/Theme 1; Q02 | M / S1, extended S2/S3 | VAL-002/036; FR-001/002 |

## 5.2 Tutor availability, discovery and new Booking

| ID | Actor and testable requirement, including safe failure | Source | Priority / sprint | Planned proof; dependency |
|---|---|---|---|---|
| **FR-005** | **Tutor:** Given authorization to their own schedule and a valid future start, publish exactly one explicit sixty-minute Slot; persist it under the authenticated Tutor, without recurrence or auto-generated bulk offers. | Q02-Q04; Theme 1 | M / S1 | VAL-003; FR-004, OD-001..003 |
| **FR-006** | **Server on Tutor creation:** Reject malformed/past Slots and overlaps between currently offered Slots of the same Tutor; permit adjacent intervals and independent same-time offers by another Tutor when otherwise valid; leave existing offers unchanged on rejection. | Q03/Q06/Q29; Theme 1 | M / S1 | VAL-004/005; FR-005 |
| **FR-007** | **Tutor:** Retrieve own offered Slots and authorized occupied/unoccupied schedule view from committed data; reject another Tutor's protected schedule lookup. | Q02; Theme 1 | M / S1 | VAL-002/012; FR-004/005 |
| **FR-008** | **Customer:** Browse Tutor/Slot/time information sufficient to choose a specific offer, without disclosure of another Customer's private reservation; the concrete field allowlist remains an API-contract choice. | Q01/Q02; Theme 1 | M / S1 | VAL-006/036; FR-004/005 |
| **FR-009** | **Server/availability view:** Mark an offer bookable only when current, unoccupied, eligible and not too close to its start; an earlier view must not guarantee later acceptance. Hide-versus-disabled presentation is unresolved. | Q05/Q06; Theme 1 | M / S1 | VAL-006/009; OD-004 |
| **FR-010** | **Customer:** Given an eligible Slot and no overlapping Active Booking, request one exclusive reservation for their authenticated identity; commit one `Booked` Booking referencing the actual Slot and Tutor before acknowledging success. | Q01/Q05; Theme 1 | M / S1 | VAL-007; FR-001/004/005 |
| **FR-011** | **Server on Booking:** Revalidate offered/unoccupied state, user ownership, cutoff and overlaps immediately before a guarded Booking write; reject stale, invalid, past, too-soon or occupied choices with no partial reservation. | Q05/Q06/Q28; Theme 1; engineering interpretation of T_elig | M / S1 | VAL-008/009/014; FR-010 |
| **FR-012** | **Server on competing Bookings:** Under simultaneous attempts by different Customers for the same exclusive Slot, allow at most one committed Active Booking and never return two successful claims. | Q01; Theme 1 | M / S1 | VAL-010; FR-010/011 |
| **FR-013** | **Server on Customer Booking:** Reject the same Customer's overlapping Active reservation, including requests for two different Tutors; accept adjacency under this specific rule, with at most one conflicting success under concurrency. | Q28 | M / S1 | VAL-004/011; FR-010/011 |

| ID | Actor and testable requirement, including safe failure | Source | Priority / sprint | Planned proof; dependency |
|---|---|---|---|---|
| **FR-014** | **Customer:** Retrieve a persisted list and detail of **own** Bookings with Booking identity, Tutor/Slot/interval and business status; foreign IDs must not disclose Booking data. | Q02/Q30; Theme 1 | M / S1 | VAL-012/036; FR-004/010 |
| **FR-015** | **Tutor:** Retrieve Bookings attached to the Tutor's authorized schedule only; requesting another Tutor's records must not disclose them. | Q02; Theme 1 | M / S1 | VAL-002/012; FR-004/010 |
| **FR-016** | **Application:** Authorized reopened/refresh/restart views must reflect successfully committed Slots/Bookings and correct ownership; a failed transaction must not produce a persisted or reported phantom Booking. | GW §5.1; Theme 1 | M / S1 | VAL-007/014; FR-005/010 |
| **FR-017** | **Application views:** Display `Booked` accurately and, when a Booking's end is past, optionally derive `Past`; never assert `Completed`, attendance or auto-release solely from elapsed time. | Q30 | M / S1 | VAL-013; FR-014/015 |
| **FR-018** | **Application/server:** Return an observable, non-success rejection for forbidden, invalid, stale, conflicting or failed mutations, without leaking protected records or leaving partial state. Specific HTTP status/payload formats remain contract decisions. | Q02/Q05/Q06/Q28; Theme 1 | M / S1, extended S2 | VAL-002/014/030; OD-005/013 |
| **FR-019** | **System:** Support the Tutor offer → Customer browse → committed Booking → authorized retrieval journey through a real UI, application/API and durable database, surviving refresh and application restart. | GW §5.1; D1 §2 | M / S1 | VAL-007/031; engineering contracts outside Issue #9 |

## 5.3 Customer cancellation and rescheduling

| ID | Actor and testable requirement, including safe failure | Source | Priority / sprint | Planned proof; dependency |
|---|---|---|---|---|
| **FR-020** | **Owning Customer:** Cancel their current Booking when the Appointment starts **at least 30 minutes** after the server's authoritative decision; at the exact boundary allow, below it deny; foreign or nonactive Booking cannot be cancelled. | Q07 | M / proposed S2 | VAL-015; FR-004/014 |
| **FR-021** | **Server on successful Customer cancellation:** Change Booking to `Cancelled` and reopen its **same** original Slot atomically; keep it unbookable for any later new request failing the independent Q05 cutoff. | Q08/Q05 | M / proposed S2 | VAL-015/016; FR-020 |
| **FR-022** | **Owning Customer:** Initiate rescheduling of an existing `Booked` Booking; reject nonowners and disallowed Booking state. | Q09 | M / proposed S2 | VAL-017; FR-004/014 |
| **FR-023** | **Server on reschedule:** Require both original Appointment start **and destination Slot start** to be at least 60 minutes away at authoritative decision; reject either too-late side including the just-below-boundary case. | Q10/Q11 | M / proposed S2 | VAL-018; FR-022 |
| **FR-024** | **Owning Customer:** Select a valid destination with a different Tutor if desired; do not restrict rescheduling to the original Tutor, while still enforcing destination occupancy and same-Customer overlap. | Q12/Q28 | M / proposed S2 | VAL-019; FR-023 |
| **FR-025** | **Server on reschedule:** Atomically update Booking assignment, occupy destination, release/reopen original Slot and record history; any validation, conflict or persistence failure leaves all related records at their pre-attempt state. | Q13/Q14 | M / proposed S2 | VAL-020; FR-022..024 |
| **FR-026** | **Server:** Preserve the Booking ID across a successful reschedule and append a successful-change record with former/new Tutor, Slot/interval and timestamp; rejected attempts do not create successful history. | Q15 | M / proposed S2 | VAL-020; FR-025 |
| **FR-027** | **Server:** Permit **at most one successful** reschedule per Booking; a failed attempt leaves the allowance available, while a second successful-change request is rejected. | Q16 | M / proposed S2 | VAL-017/020; FR-025/026 |

### 5.4 Tutor cancellation, Slot withdrawal and notice

| ID | Actor and testable requirement, including safe failure | Source | Priority / sprint | Planned proof; dependency |
|---|---|---|---|---|
| **FR-028** | **Currently assigned Tutor:** Cancel an Active Booking belonging to the Tutor's authorized schedule only when its start is at least 60 minutes away; exact boundary passes and wrong-Tutor/too-late attempts fail. | Q17/Q18 | M / proposed S2 | VAL-021; FR-004/015 |
| **FR-029** | **Tutor/server:** Require a meaningful nonblank reason before accepting Tutor cancellation; reject absent, whitespace-only or semantically empty reason without changing Booking or Slot. Length/format details need approved design. | Q20 | M / proposed S2 | VAL-021; FR-028, OD-014 |
| **FR-030** | **Server on successful Tutor cancellation:** Mark Booking `Cancelled` and **withdraw** its original Slot instead of reopening it; preserve trace/history and ensure no partial outcome. | Q19 | M / proposed S2 | VAL-022; FR-028/029 |
| **FR-031** | **Server:** On successful Tutor cancellation create one private in-app notice for that Booking's owning Customer, including the authorized reason; the reason also appears in that Customer's cancelled Booking details, never in third-party views. | Q21-Q23 | M / proposed S2 | VAL-023/036; FR-028..030 |
| **FR-032** | **Owning Customer:** Retrieve and reread Tutor-cancellation notices after marking them read; absence of automatic time-based expiry must hold, while deletion/retention governance remains undecided. | Q24/Q25 | M / proposed S2 | VAL-024; FR-031, OD-008 |
| **FR-033** | **Server/Tutor:** Forbid direct edit, deletion or withdrawal of a Slot while it carries an Active Booking; require the separate authorized cancellation workflow first. | Q26 | M / proposed S2 | VAL-025; FR-004/028 |
| **FR-034** | **Owning Tutor:** Withdraw an **unoccupied future** currently offered Slot while retaining its history; permit later creation of a distinct new Slot with a new ID that may overlap the withdrawn interval; reject reopening/reactivating the withdrawn historical Slot. | Q27/Q32 | M / proposed S2 | VAL-026/027; FR-005/033 |

### 5.5 Tutor-only reporting

| ID | Actor and testable requirement, including safe failure | Source | Priority / sprint | Planned proof; dependency |
|---|---|---|---|---|
| **FR-035** | **Tutor:** Retrieve an Appointment Summary with **counts and corresponding lists** for Upcoming Booked, Past Booked and Cancelled on the Tutor's authorized schedule, calculated from stored Booking state and server time; in-progress classification remains OD-006. | Q31/Q30 | M / proposed S3 | VAL-028/029; FR-015/017/028 |
| **FR-036** | **Server:** Deny Customers, anonymous callers and unrelated Tutors access to the Tutor-only summary and its linked Booking details; counts/lists must share the same visibility and classification criteria. | Q31/Q02 | M / proposed S3 | VAL-029/036; FR-004/035 |

## 6. Business rules

Each rule below is a normative **business outcome** sourced to a Q decision or an explicitly identified instructor minimum. The `VAL` column gives a planned check. Rule numbers follow **Q01-Q32** deliberately, making omitted stakeholder decisions detectable; BR-033..035 capture additional instructor/security and integrity constraints. These IDs are **new product IDs**, not replacements for the existing `BR-S1-*` IDs.

| ID | Normative rule and boundary | Authority | Verification sprint / anchor |
|---|---|---|---|
| **BR-001** | One Slot reserves one exclusive **one-to-one** Customer/Tutor session; at most one Active Booking may claim it. | Q01 | S1 / VAL-007/010 |
| **BR-002** | Tutor = Staff and may manage or inspect **their own** authorized schedule; Customer = learner and may inspect only own private Booking data. | Q02 | S1 / VAL-002/012 |
| **BR-003** | Every Availability Slot has a duration of **exactly 60 minutes**. | Q03 | S1 / VAL-003/004 |

| ID | Normative rule and boundary | Authority | Verification sprint / anchor |
|---|---|---|---|
| **BR-004** | Tutor creates **individual explicit** Slots; no automatic recurrence or bulk Slot generation is authorized. | Q04 | S1 / VAL-003 |
| **BR-005** | For a new Booking, `SlotStart - authoritative server eligibility time >= 60 minutes`; equality is eligible, even if later commit succeeds after the check. A 59:59 remaining interval fails. | Q05; reviewed T_elig interpretation | S1 / VAL-008/009 |
| **BR-006** | Two **currently offered** Slots of the **same Tutor** cannot overlap. Adjacent half-open intervals are permitted; different Tutors may independently offer the same time. | Q06 | S1 / VAL-004/005 |
| **BR-007** | Only the owning Customer may cancel an Active Booking at least **30 minutes** before Appointment start, including equality. | Q07 | proposed S2 / VAL-015 |
| **BR-008** | Successful Customer cancellation reopens the **original** Slot, but a future new Booking still independently requires BR-005. | Q08 | proposed S2 / VAL-016 |
| **BR-009** | Only the Booking-owning Customer may initiate its reschedule. | Q09 | proposed S2 / VAL-017 |
| **BR-010** | Reschedule's **original** Appointment must start at least 60 minutes after the authoritative decision; equality passes. | Q10 | proposed S2 / VAL-018 |
| **BR-011** | Reschedule's **destination** Slot must start at least 60 minutes after the authoritative decision; equality passes. | Q11 | proposed S2 / VAL-018 |
| **BR-012** | A valid Customer reschedule may move to another Tutor; original-Tutor-only restrictions are forbidden. | Q12 | proposed S2 / VAL-019 |
| **BR-013** | Reschedule is **all-or-nothing** across assignment, both Slot states and successful history. Failure leaves the previous Booking intact. | Q13 | proposed S2 / VAL-020 |
| **BR-014** | Successful reschedule reopens the original Slot, subject to independent new-Booking eligibility. | Q14 | proposed S2 / VAL-020/016 |
| **BR-015** | Successful reschedule keeps the **same Booking ID** and records old/new Tutor, Slot/time and change timestamp. | Q15 | proposed S2 / VAL-020 |
| **BR-016** | At most **one successful** reschedule per Booking; failures do **not** use that allowance. | Q16 | proposed S2 / VAL-017/020 |
| **BR-017** | Only the **currently authorized Tutor assigned to the Booking** may cancel it as Tutor. | Q17 | proposed S2 / VAL-021 |
| **BR-018** | Tutor cancellation requires Appointment start at least **60 minutes** after the authoritative decision, equality included. | Q18 | proposed S2 / VAL-021 |
| **BR-019** | Successful Tutor cancellation **withdraws** the original Slot; it must not reopen it. | Q19 | proposed S2 / VAL-022 |
| **BR-020** | Tutor cancellation requires a **meaningful nonblank reason**; an empty/whitespace-only input is invalid. Further textual-validation details require approval. | Q20 | proposed S2 / VAL-021 |
| **BR-021** | Each successful Tutor cancellation creates an in-app notice for the **affected owning Customer only**. | Q21 | proposed S2 / VAL-023 |
| **BR-022** | Tutor-cancellation reason is visible only to the **owning Customer**, not to other Customers or unrelated Tutors in accessible results. | Q22 | proposed S2 / VAL-023/036 |
| **BR-023** | That Customer sees the cancellation reason in both the **in-app notice** and **cancelled Booking detail**. | Q23 | proposed S2 / VAL-023 |
| **BR-024** | Reading a notification does not make it inaccessible; it remains available to reread. | Q24 | proposed S2 / VAL-024 |
| **BR-025** | Notifications do **not** expire automatically with elapsed time. This does not settle user/admin deletion, retention or privacy governance. | Q25 | proposed S2 / VAL-024 |

| ID | Normative rule and boundary | Authority | Verification sprint / anchor |
|---|---|---|---|
| **BR-026** | Tutor cannot directly edit, delete or withdraw a Slot with an **Active Booking**; the authorized Booking cancellation must occur first. | Q26 | proposed S2 / VAL-025 |
| **BR-027** | Tutor may withdraw an **own, unoccupied future Slot** and create a **separate new** Slot while preserving withdrawal history. | Q27 | proposed S2 / VAL-026 |
| **BR-028** | One Customer cannot have overlapping **Active Bookings** across any Tutors; **adjacent** appointments do not overlap. | Q28 | S1 / VAL-004/011 |
| **BR-029** | `Asia/Bangkok` (UTC+07:00) is the business timezone; authoritative time comes from the server, not a browser or user-supplied timestamp. | Q29 | S1 / VAL-008/013 |
| **BR-030** | Booking business states are `Booked` and `Cancelled`; `Past` is **derived from time**, not a third state or evidence of `Completed` /attendance. | Q30 | S1 (Booked/Past), S2 (Cancelled) / VAL-013/015 |
| **BR-031** | Only authorized Tutor gets Appointment Summary **counts and lists** for Upcoming Booked, Past Booked and Cancelled. Customer gets no Tutor-only summary. | Q31 | proposed S3 / VAL-028/029 |
| **BR-032** | Historical **withdrawn** Slots do not block a new separate overlapping offer; they are **not reactivated under the same historical Slot ID**. | Q32 | proposed S2 / VAL-027 |
| **BR-033** | Protected actions require server-enforced authenticated role/ownership checks; anonymous, foreign-record and cross-role operations cannot gain private data or mutation rights. | GW §5.2; Theme 1 | S1 and extensions / VAL-001/002/036 |
| **BR-034** | Accepted Booking/Slot mutations commit an internally consistent outcome; rejected validations, contention and persistence failures cannot leave partially claimed Slots, duplicate active reservations or false success. The precise locking/constraint scheme is not selected here. | GW §5.1/Theme 1; Q01/Q06/Q28 outcome | S1 and extensions / VAL-005/010/011/014/020 |
| **BR-035** | Invalid or nonfuture Slot proposals and attempts to book past, occupied or ineligible offers are rejected without changing committed records; rules beyond confirmed time policies cannot be fabricated. | GW Theme 1; Q03/Q05/Q29 | S1 / VAL-004/006/014 |

**Interval rule:** `[startA, endA)` overlaps `[startB, endB)` exactly when `startA < endB && startB < endA`. If A ends at 14:00 and B begins at 14:00, then `startB < endA` is false. Consequently, the appointment intervals are adjacent rather than conflicting. This comparison governs BR-006 and BR-028; other validity and cutoff rules still apply.

**Rule interactions that need separate checks:** A Slot reopened 30 minutes before a session by Customer cancellation is offered again under BR-008, yet BR-005 prevents a new Booking inside its 60-minute cutoff. Tutor cancellation takes the opposite path: BR-019 withdraws the Slot and BR-032 allows a later **separate** overlapping offer. A successful reschedule releases only its original Slot, claims the destination and preserves its Booking identity in **one** transaction; a failed reschedule consumes neither the destination nor the one-success allowance.

## 7. Non-functional requirements

The following targets separate **required outcomes** from **proposed quantification**. Where a metric is unapproved, the measurement describes a candidate acceptance gate, not a claim that the system already meets it. A quality attribute without an invented availability or performance promise can still have a concrete correctness inspection.

| ID | Attribute and requirement / measured target | Source and approval status | Planned check; sprint / approval owner |
|---|---|---|---|
| **NFR-001** | **Authorization:** every enumerated anonymous, forbidden-role, foreign-Customer and foreign-Tutor protected API path must reject or filter without private payload disclosure. Measure zero unauthorized record disclosure in seeded negative cases. | **Required outcome**, GW §5.2/Q02 | VAL-002/036; S1-S3; backend/peer review |

| ID | Attribute and requirement / measured target | Source and approval status | Planned check; sprint / approval owner |
|---|---|---|---|
| **NFR-002** | **Credential security:** with locally managed passwords, store adaptive salted hashes, not plaintext; tracked repository content contains no real credentials. Verify using test DB inspection and secret/config review. | **Required**, GW §5.2 | VAL-034; S1; auth contract |
| **NFR-003** | **Durability:** an accepted Slot/Booking and its authorized view must persist after browser refresh and application-process restart against the same data store; no in-memory-only persistence. | **Required**, GW §5.1/D1 §2 | VAL-007/031; S1, regression S2/S3 |
| **NFR-004** | **Concurrent conflict integrity:** all three real-DB races must preserve BR-001/006/028, regardless of interleaving; a 20-attempt same-Slot stress burst and a 10-attempt same-Customer burst are **proposed test sizes**, not approved business capacity limits. | Outcome **required**; run sizes **PROPOSED**, baseline NFR-S1-04/05 | VAL-005/010/011; S1; size via OD-010 |
| **NFR-005** | **Atomic consistency:** accepted cancellation/reschedule/Booking/withdrawal changes all required records together; deliberate persistence failures leave the prior committed state and no false confirmation. | **Required outcome**, Q13/Q19 and Theme 1 integrity | VAL-014/020/022; S1/S2 |
| **NFR-006** | **Time correctness:** cutoff checks use server-authoritative instants; accept exact 60:00 or 30:00 boundaries as applicable, reject just-below; Bangkok calendar/hour remains stable for a non-Bangkok browser. | **Required**, Q05/Q07/Q10/Q11/Q18/Q29 | VAL-008/009/013/015/018/021; S1/S2 |
| **NFR-007** | **Data minimization:** protected Booking, reason, notification and report responses do not expose third-party identity, cancellation reason, credentials or arbitrary private schedule fields. Review response bodies and negative payloads, not UI controls only. | **Required**, Q02/Q21-Q23/Q31, GW §5.2 | VAL-023/029/036; S1-S3 |
| **NFR-008** | **Retry safety:** repeated/uncertain-response requests cannot violate exclusivity, successful reschedule quota or atomic history. Whether retries return the original success response and any token format/retention are open. | Invariant **required**; protocol **OPEN** | VAL-030/020; S1/S2; OD-013 |
| **NFR-009** | **Keyboard usability (PROPOSED):** complete login, availability, Booking and own-detail flows by keyboard with visible focus on primary controls; record manual checklist, browser and failures. | **PROPOSED**, baseline NFR-S1-09, not stakeholder-approved | VAL-033; candidate S1/S3; OD-010, @Tanaboonnnnn/@Chxtamos |
| **NFR-010** | **Local response time (PROPOSED):** p95 availability and own-Booking-detail requests at or below **2.0 s**, each measured over at least **50** warm-up-excluded requests with documented hardware, fixture size and database. | **PROPOSED**, baseline NFR-S1-10, not instructor-approved | VAL-032; candidate S1/S3; OD-010, team review |
| **NFR-011** | **Change traceability:** each implemented requirement must identify source Q/GW/D1, accountable feature/Issue, reviewed contract, planned verification and release evidence; changes to Q rules need recorded stakeholder approval. | **Required process**, D1 Parts A-E / AGENTS.md | VAL-031, document/PR inspection; S1-S3 |
| **NFR-012** | **Reproducibility:** engineering evidence must identify code version, environment/setup, DB/seed preparation, test commands and real pass/fail/skip results; mere presence of tests is not a pass. | **Required process**, GW §5.3, D1 | VAL-031; S1-S3 |
| **NFR-013** | **Deployment readiness:** the selected architecture must support container packaging and durable GCP deployment, with build/tests on relevant PRs and repeatable accepted release from `main` after Lab 5. No cloud success is asserted at D1. | **Required later**, GW §§5.1/5.3; Lab 5 | VAL-035; Lab 5 and later; separate Issues |
| **NFR-014** | **Notice durability:** a Tutor-cancellation notice remains retrievable after being read and is not removed solely by age; additional retention/deletion rights await owner decision. | **Required**, Q24/Q25 | VAL-024; proposed S2, OD-008 |

| ID | Attribute and requirement / measured target | Source and approval status | Planned check; sprint / approval owner |
|---|---|---|---|
| **NFR-015** | **Safe diagnostics:** response errors expose no credentials, session tokens, protected reason or internal stack traces; operational logs must avoid secrets and preserve enough non-sensitive context to investigate failed mutations. Exact logging fields/retention are engineering decisions. | Security outcome **required** by GW §5.2; logging structure **PROPOSED** | VAL-034/036; S1-S3; OD-005/008 |
| **NFR-016** | **Reporting correctness:** for every defined Tutor Summary category, count must equal its corresponding accessible row set under the same time/state predicates; no completion is inferred from elapsed time. Treatment of in-progress sessions remains open. | **Required**, Q30/Q31 | VAL-028/029; proposed S3, OD-006/009 |

**Approval rule:** Do not copy `NFR-009` or `NFR-010` into a feature's final acceptance contract as a mandatory threshold until the product decision owner and peer reviewer approve it, including environment and workload. No uptime SLA, password complexity number, request-rate limit, backup frequency, pagination size or retention period has been approved by Q01-Q32.

## 8. Authorization and privacy

Server authorization is authoritative. The role in an authenticated principal, the actual Booking owner and the Tutor assigned to the relevant Slot/Booking determine access. URL parameters, browser state, hidden buttons or a submitted `customerId` / `tutorId` are not an authorization grant.

Legend: **Own** means only records owned/assigned under the stated condition; **Deny** means protected access is forbidden; **N/A** means no product-level action is assigned to that role. Login at the anonymous boundary requires valid credentials, not a public session. S2/S3 actions are **planned**, not present in Sprint 1.

| Operation / protected view | Anonymous | Customer | Tutor (Staff) | Planned sprint |
|---|---|---|---|---|
| Open login / submit valid credentials | Login only | Login | Login | S1 |
| View current authenticated identity | Deny | Own | Own | S1 |
| Logout current session | N/A | Own | Own | S1 |
| Create explicit Slot | Deny | Deny | **Own schedule** | S1 |
| Inspect offered/occupied Tutor schedule | Deny | Deny | **Own schedule** | S1 |
| Discover customer-facing availability | No public policy approved | Authenticated offers, privacy-filtered | N/A as Customer workflow | S1 |
| Create new Booking | Deny | **Own identity**, eligible Slot | Deny under Tutor authority | S1 |
| Retrieve Customer Booking list/detail | Deny | **Owned Bookings only** | No global Customer query | S1 |
| Retrieve Tutor Booking schedule | Deny | Deny | **Currently authorized Tutor schedule only** | S1 |
| Cancel a Customer Booking | Deny | **Owning Customer**, Q07 cutoff | Deny via Customer route | S2 |
| Reschedule Booking | Deny | **Owning Customer**, quota and both cutoffs | Deny | S2 |
| Cancel a Booking as Tutor | Deny | Deny | **Currently assigned Tutor**, cutoff + reason | S2 |
| Direct edit/delete/withdraw occupied Slot | Deny | Deny | **Deny while Active Booking exists** | S2 |
| Withdraw unoccupied future offered Slot | Deny | Deny | **Own Slot** | S2 |
| Read Tutor-cancellation notification | Deny | **Notice addressee only** | Deny | S2 |

| Operation / protected view | Anonymous | Customer | Tutor (Staff) | Planned sprint |
|---|---|---|---|---|
| Read Tutor-cancellation reason in notice/detail | Deny | **Owning Customer only** | No read authority inferred from Tutor role | S2 |
| View Appointment Summary counts/lists | Deny | Deny | **Own authorized Tutor summary only** | S3 |
| Read another Customer's or another Tutor's restricted records | Deny | Deny | Deny | All |

### 8.1 Protected response and mutation boundaries

- **Customer availability:** sufficient non-sensitive Tutor label/identifier and Slot start/end to make a selection; do not include another Customer's Booking, contact information, cancellation reason or restricted schedule data. Exact field names, availability visibility and sorting are pending OD-004.
- **Customer's own Booking:** stable Booking ID, relevant Tutor and current appointment interval, business status, plus authorized history and reason only when applicable. Do not expose another learner's Booking through direct IDs, searches, pagination or error responses.
- **Tutor's schedule:** current Tutor's permitted Slot/Booking facts. The precise Customer identity representation shown to a Tutor is an unapproved minimum-field decision; it must be justified and bounded in the API/UI contracts. Reschedule-history visibility for prior Tutors, if any, is unresolved and cannot create global access.
- **Cancellation notice:** only the targeted Customer sees its contents; the reason is present in that Customer's cancelled Booking detail. Read state is separate from deletion or automatic expiry. No consent is implied to broadcast reasons to other Tutors or Customers.
- **Write authorization:** Booking owner comes from the authenticated Customer, Tutor ownership from the actual Slot and currently assigned Booking, and cancellation/reschedule eligibility from server state. Any failed authentication or ownership check must precede protected detail disclosure.
- **Error safety:** choose precise 401/403/404 behavior, conflict codes and error fields in separate feature API contracts; whatever the choice, rejected access must disclose no protected information. Never use a success response for an uncommitted write.

## 9. Logical domain and lifecycle

The following is a **logical requirements model**, not a relational schema, migration design or API DTO. Detailed entity fields, keys, constraints, indexing, locking and storage implementation are assigned to Issue #11 and subsequent Feature SDS.

| Concept | Required logical information and relationships | Invariants / lifecycle |
|---|---|---|
| Authenticated user | Stable identity, effective role Customer or Tutor; session lifecycle | Identity is server-trusted; a principal cannot gain another role through submitted IDs |
| Tutor schedule | Association of one Tutor with their own Slots and associated authorized Bookings | Cross-Tutor reads/writes restricted; current offer list differs from withdrawal history |
| Availability Slot | Stable Slot identity, Tutor owner, scheduled start/end, currently offered or withdrawn historical meaning, occupancy relationship | Exactly 60 minutes; one Tutor per Slot; currently offered same-Tutor Slots cannot overlap; withdrawn ID not reactivated |
| Booking | Stable Booking identity, owning Customer, **current** Slot/Tutor assignment, scheduled interval and `Booked` or `Cancelled` status | At most one Active Booking per Slot; one Customer cannot hold overlapping Active Bookings; identity survives reschedule |
| Successful reschedule history | One record per successful change, including Booking ID, old/new Tutor and Slot/interval, server change timestamp | At most one successful entry per Booking under Q16; a rejected attempt does not produce a successful entry |
| Cancellation reason | Meaningful nonblank reason supplied on Tutor cancellation and associated with its Booking | Owning Customer sees it in notice and cancelled Booking detail; unauthorized callers never see it |

| Concept | Required logical information and relationships | Invariants / lifecycle |
|---|---|---|
| In-app notification | Owner Customer, related Tutor-cancelled Booking, private message/reason and read-state meaning | Remains accessible when read; no automatic age expiry; deletion/retention rules open |
| Historical withdrawn Slot | Former Slot identity, Tutor, original interval and withdrawn status/history | Not a current offer; does not block new separate overlapping offers; never reactivated under same Slot ID |
| Tutor Appointment Summary | Authorized Tutor scope and derived categories: Upcoming Booked, Past Booked, Cancelled | Counts equal corresponding lists; no global Customer view; in-progress category pending |

### 9.1 Booking state and Slot lifecycle

The only agreed **Booking business states** are `Booked` and `Cancelled` (Q30).

1. **New Booking success:** eligible Slot becomes occupied and a Booking is created in `Booked`. Failure creates no Booking or occupied change.
2. **Customer cancellation:** `Booked → Cancelled` for an authorized owner at the 30-minute cutoff; original Slot becomes a currently offered unoccupied Slot (Q07-Q08).
3. **Customer reschedule:** Booking **remains** `Booked` and retains its ID; the assignment moves atomically to the destination; original Slot reopens and successful history is appended (Q09-Q16).
4. **Tutor cancellation:** `Booked → Cancelled` for the currently assigned authorized Tutor at the 60-minute cutoff, requiring reason; original Slot is **withdrawn**, and the private notification is created (Q17-Q25).
5. **Tutor withdrawal without Booking:** offered unoccupied future Slot becomes historical withdrawn; a **new Slot**, with a distinct ID, may subsequently be offered (Q26-Q27/Q32).
6. **Elapsed time:** past the appointment **end**, the display may derive `Past`; `Booked` remains `Booked`. There is no `Completed`, `Attended`, `No-show`, auto-cancel or implied auto-release transition.

An active Booking is one still in `Booked`, **even if the lesson's end is past**. This protects historical consistency and prevents inappropriate automatic release. State transition details at time boundaries and unsupported repeated cancellation attempts require explicit negative validation. Which cancellation actor performed a `Cancelled` transition and the historical detail available to each role must be represented without assuming an additional business state.

### 9.2 Cardinality and conservation obligations

- One Slot has one owning Tutor and is attached to **at most one Active Booking** at a given time; one Customer may have multiple Bookings only when none of the Active intervals overlap.
- A successful reschedule conserves **one Booking ID** while moving its *current* appointment link. Old/new links remain in history rather than becoming two live Bookings.
- Customer cancellation preserves the Slot as a potentially available offer. Tutor cancellation preserves the Slot **as withdrawn history**. These outcomes are intentionally different.
- Failed cancellation, reschedule, creation or Booking cannot leave part of the change committed, including premature notification creation, wrong successful-reschedule count or incorrect occupancy.
- Reports are projections of the authoritative logical entities; a report count cannot independently redefine Booking state, ownership or elapsed-time semantics.

## 10. Time, conflicts and concurrency

### 10.1 One timezone and explicit inequalities

All user-visible appointment times use `Asia/Bangkok` (UTC+07:00). The server controls the clock used for acceptance checks. Persisted instants and transport representation are engineering choices, but must preserve this business meaning independent of the client's timezone, locale and clock skew.

Let `S` be the relevant appointment or Slot start instant and `T` the authoritative server instant at the applicable guarded decision point. Equality at each confirmed cutoff **passes**, if all other rules pass.

| Action | Confirmed eligibility formula | Example for 15:00 start (Bangkok) | Primary source |
|---|---|---|---|
| **New Booking** | `S - T_elig >= 60 min` | `14:00:00` eligible; `14:00:01` too late | Q05; BR-005 |
| **Customer cancellation** | `S - T >= 30 min` | `14:30:00` eligible; `14:30:01` too late | Q07; BR-007 |
| **Reschedule old Appointment** | `OldStart - T >= 60 min` | Old `15:00` ; `14:00:00` eligible | Q10; BR-010 |
| **Reschedule destination** | `NewStart - T >= 60 min` | Destination `15:00` ; `14:00:01` too late | Q11; BR-011 |
| **Tutor cancellation** | `S - T >= 60 min` | `14:00:00` eligible; `14:00:01` too late | Q18; BR-018 |
| **Tutor Slot creation** | Start must be valid and in future; **no Q05 new-Booking cutoff imposed** | Future valid start; further scheduling grid/hours/horizon open | Q03/Q04; Theme 1; OD-001..003 |

**New-Booking precision ( `T_elig` ):** The reviewed Sprint 1 baseline defines a single server-authoritative time sampled **inside the transaction after contention waits and immediately before final guarded validation/write**. An HTTP request for a 15:00 Slot may arrive at 13:59:59 yet wait until `T_elig=14:00:01` ; it must be denied. If `T_elig=14:00:00` , a later commit timestamp alone does not invalidate the previously valid guarded check. This is an **engineering interpretation** for review, not permission to weaken Q05 or ignore other checks. The Feature SDS must confirm the actual transaction/time-control design and tests (AC-S1-35, VC/TEST-S1-39).

For **later** cancellation/rescheduling cutoffs, Q07/Q10/Q11/Q18 settle the numerical boundary and server-clock authority through Q29; the exact transactional sampling order, lock behavior and retry handling must still be set in their Feature SDS. Using the same final-guard pattern as `T_elig` is a **proposal** for consistent implementation, not an independently confirmed stakeholder Q decision.

### 10.2 Half-open overlap and Current versus Historical

Two intervals intersect iff `a.start < b.end && b.start < a.end` . Exact adjacency ( `a.end = b.start` ) is allowed under BR-006 and BR-028. Partial overlap by even one positive-duration instant is prohibited for same-Tutor currently offered Slots and the same Customer's Active Bookings.

A **withdrawn historical** Slot must be excluded from the set of current offers checked against new Slot creation. This does **not** exempt a current occupied offer from same-Tutor overlap rules, and it does not mean an old historical Slot may be reactivated. Different Tutors' offered intervals may coincide; **one Customer** still cannot reserve overlapping intervals across them.

### 10.3 Three mandatory race proofs

| Hazard | Simultaneous operation | Required final committed state | Planned contract/test |
|---|---|---|---|
| **Race A: Tutor current offers** | Same Tutor creates two partially overlapping 60-minute offered Slots | At most one of the conflicting offers remains current; loser has no partial Slot. If different Tutors create same time, both can be valid. | Slot contract, VAL-005; baseline AC-S1-13 / VC-S1-37 |
| **Race B: exclusive Slot** | Two distinct Customers attempt the same eligible Slot | At most one Active Booking occupies that Slot. No second success or orphan occupancy. | Booking contract, VAL-010; baseline AC-S1-25 / VC-S1-25 |
| **Race C: Customer across Tutors** | One Customer simultaneously requests two distinct overlapping offers from different Tutors | At most one conflicting Active Booking commits for that Customer, despite each Slot being individually free. | Booking contract, VAL-011; baseline AC-S1-26 / VC-S1-26 |

For all three, controlled concurrency tests must start requests under actual overlap/interleaving and inspect **committed database state**, not only returned HTTP codes or disabled frontend controls. The System/Feature SDS must choose an isolation/locking/constraint strategy that enforces these outcomes for every write path. No particular SQL lock, ORM, idempotency key or isolation level is approved by this SRS.

### 10.4 Atomic change, stale reads and uncertain responses

- A stale availability view cannot reserve or grandfather an occupied/withdrawn/too-soon Slot. The server checks current state at the final write guard, and a rejected request changes no Booking or Slot relationship.
- A duplicate click, network retry or unknown response after a possible commit must preserve the invariants. Returning an existing success versus a conflict is an **unresolved transport/idempotency decision** (OD-013).
- A failed Customer cancellation leaves `Booked` and occupancy unchanged; a successful cancellation reopens the same Slot. A failed Tutor cancellation must not leave the Slot withdrawn or a false private notice.
- A failed reschedule leaves the original Booking assignment and its Slot occupied, destination unoccupied, no success history and the one-success quota unconsumed. This also holds when destination is taken concurrently.
- Under a lost database write or rollback, no client may be told a reservation/change succeeded unless the corresponding complete state committed. Exact error vocabulary and reconciliation behavior belong to the later design contracts.

## 11. Exception and boundary scenarios

This is a requirements-level outcome matrix. `VAL` cases are **planned**, and actual fixtures, HTTP status codes and test files are owned by later STS/implementation Issues.

| Scenario | Trigger / precondition | Observable required outcome | Governing rules; planned check |
|---|---|---|---|
| Invalid Slot start/duration | Missing, malformed, past or non-sixty-minute proposed offer | No invalid Slot, no changed existing offer | BR-003/035; VAL-003/004 |
| Same Tutor overlap | Existing 13:00-14:00 current offer; proposed 13:30-14:30 | Reject proposed Slot; original preserved | BR-006; VAL-004 |
| Slot adjacency | Existing 13:00-14:00; proposed 14:00-15:00 | Adjacency itself does not reject otherwise-valid offer | BR-006; VAL-004 |
| Cross-Tutor offers | Tutors A/B each create 13:00-14:00 | Both current offers allowed if each independently valid | BR-006; VAL-004 |
| Unauthorized Slot write | Customer or Tutor B targets Tutor A's schedule | No change to Tutor A's offers; no protected disclosure | BR-002/033; VAL-002 |
| Anonymous Booking | Caller lacks session | No Booking or protected data | BR-033; VAL-002 |
| Foreign Customer Booking | Customer B guesses A's Booking ID | No private details or related notification/reason exposed | BR-002/022/033; VAL-002/036 |
| Foreign Tutor schedule | Tutor B guesses Tutor A's schedule/Booking ID | No foreign schedule or private Booking disclosed | BR-002/033; VAL-002 |
| Too-soon new Booking | Slot at 15:00; `T_elig=14:00:01` | Reject without occupation | BR-005; VAL-008 |
| Exact new-Booking boundary | Slot at 15:00; `T_elig=14:00:00` | Lead-time rule passes, subject to all other guards | BR-005; VAL-008 |
| Cutoff crossed while waiting | HTTP arrives 13:59:59; final `T_elig=14:00:01` | Reject, regardless of early HTTP arrival | BR-005/034; VAL-009 |
| Occupied Slot/stale list | Availability was earlier displayed, but now occupied/withdrawn | No duplicate or false Booking; view reconciles | BR-001/034; VAL-006/014 |
| Same Customer across Tutors | Active 13:00-14:00, candidate 13:30-14:30 | Reject overlapping Booking | BR-028; VAL-011 |
| Adjacent Customer appointment | Active ends 14:00; proposed begins 14:00 | Overlap rule permits; independent lead-time applies | BR-028/005; VAL-004/011 |
| Race A | Concurrent same-Tutor overlapping Slot creation | At most one conflicting offer committed | BR-006/034; VAL-005 |

| Scenario | Trigger / precondition | Observable required outcome | Governing rules; planned check |
|---|---|---|---|
| Race B | Two Customers, one Slot concurrently | At most one Active claim committed | BR-001/034; VAL-010 |
| Race C | One Customer, overlapping Tutor Slots concurrently | No two overlapping Active bookings commit | BR-028/034; VAL-011 |
| Fault during Booking persistence | Failure before transaction completion | No phantom success, partial Booking or inconsistent occupation | BR-034; VAL-014 |
| Customer cancellation at cutoff | At `start - 30:00` versus just after | Equality eligible; just-after denied, no partial state | BR-007; VAL-015 |
| Reopened Slot inside booking cutoff | Customer cancels 30 minutes before start | Original Slot reopened, but new Booking at fewer than 60 minutes rejected | BR-008/005; VAL-016 |
| Reschedule wrong owner / quota | Foreign Customer or already one success | Reject, old Booking and history unchanged | BR-009/016; VAL-017 |
| Reschedule original/destination cutoffs | Old or destination starts at `T + 59:59` | Reject even if other start qualifies; exact `T + 60:00` eligible | BR-010/011; VAL-018 |
| Reschedule across Tutors | Valid new Tutor offered Slot | Accept; same Booking ID, new Tutor/Slot, old Slot reopened | BR-012..015; VAL-019/020 |
| Reschedule failure/rollback | Destination occupied, transaction fault, collision or late boundary | No partial move, lost reservation, false history or consumed quota | BR-013/016; VAL-020 |
| Tutor cancellation cutoff/ownership | Wrong assigned Tutor, `start - 59:59`, or exact 60:00 | Wrong/late denied; exact boundary eligible with valid reason | BR-017/018; VAL-021 |
| Missing Tutor cancellation reason | Empty, whitespace-only or meaninglessly empty reason | No cancellation/withdrawal/notice | BR-020; VAL-021 |
| Tutor cancellation state | Valid cancellation reason and cutoff | Booking Cancelled, original Slot withdrawn **not reopened**, private notice created | BR-019/021; VAL-022/023 |
| Notification privacy/re-read | Wrong Customer reads; owner reads twice | Wrong reader denied; owner sees reason and may reopen read notice | BR-021..025; VAL-023/024 |
| Direct occupied Slot change | Tutor edits/deletes/withdraws own Slot with Active Booking | Deny direct change until authorized Booking cancellation | BR-026; VAL-025 |
| Historical withdrawn overlap | Tutor withdraws unoccupied future 13:00-14:00 then creates new 13:00-14:00 offer | New distinct ID allowed; old history preserved; old ID not reactivated | BR-027/032; VAL-026/027 |
| Summary and protected counts | Tutor requests own categories; Customer or foreign Tutor requests same | Authorized counts equal lists; unauthorized gets no report | BR-030/031; VAL-028/029 |
| Browser outside Bangkok | UTC/other-zone device displays Slot and sends operation | Same intended Bangkok hour and cutoff evaluation; server time wins | BR-029; VAL-013 |
| Booking ended | Now after appointment end; no cancellation | `Past` may appear, `Booked` persists; no Completed/attendance or auto-release | BR-030; VAL-013 |

## 12. Source and requirement traceability

### 12.1 Provenance and audit rules

The tables below are **self-contained Part A coverage evidence**; they are **not** the separate Deliverable 1 Part B feature inventory or `docs/traceability.md` assigned to Issue #10.

- **SRC-Q:** stakeholder discovery decisions Q01-Q32 as recorded in the already reviewed/merged Sprint 1 requirements source; each row below is marked **Confirmed stakeholder baseline**, not independently instructor-approved.
- **SRC-GW-v1:** `group_work_specs_v1.pdf`, issued 6 October 2026, explicitly **Draft for instructor review**. Requirements drawn from it may need delta review against the missing final Master.
- **SRC-D1-v1:** `project_deliverable_1_v1.pdf`, due 8 November 2026; inspected from the supplied project archive.
- **SRC-S1:** `docs/requirements.md` as present on the `sprint1` baseline after merged PR #7; retains the original FR/BR/NFR/AC/VC naming.
- **SRC-AGENT:** repository root `AGENTS.md` merged through PR #20; this governs workflow, not new product behavior.

**Coverage criterion:** every Q decision has a product rule, an appropriate FR or NFR, a planned verification and proposed delivery sprint. An unapproved additional policy is listed in Section 13, not silently inserted into a Q row. At the requirements-writing stage, `VAL` is a test **plan**, not executed validation.

### 12.2 Stakeholder Q01-Q32 decision coverage audit

Every decision in this table has approval state **Confirmed in stakeholder discovery baseline**. The current document, final instructor source and engineering contract have **not** yet received their own approval. Some decisions were confirmed for the **product** but are scheduled in a **proposed** future sprint.

| Q | Confirmed meaning (condensed without changing boundary) | Product FR / BR / applicable NFR | Target verification sprint | Planned evidence |
|---|---|---|---|---|
| **Q01** | Exclusive one-Customer/one-Tutor session | FR-010/012; BR-001; NFR-004 | S1 | VAL-007/010 |
| **Q02** | Tutor = Staff, Customer = learner, schedule/Booking ownership | FR-004/007/014/015; BR-002; NFR-001 | S1 | VAL-002/012 |
| **Q03** | Slot lasts exactly 60 minutes | FR-005/006; BR-003 | S1 | VAL-003/004 |
| **Q04** | Tutor creates Slots individually, without bulk/recurrence | FR-005; BR-004 | S1 | VAL-003 |
| **Q05** | New Booking at least 60 minutes ahead; equality eligible | FR-009/011; BR-005; NFR-006 | S1 | VAL-008/009 |
| **Q06** | Same-Tutor current offered Slot non-overlap, adjacency valid | FR-006; BR-006; NFR-004 | S1 | VAL-004/005 |
| **Q07** | Only owner Customer cancels at least 30 minutes ahead | FR-020; BR-007; NFR-006 | proposed S2 | VAL-015 |
| **Q08** | Customer cancellation reopens original Slot, Q05 still applies | FR-021; BR-008 | proposed S2 | VAL-016 |
| **Q09** | Only owning Customer initiates reschedule | FR-022; BR-009 | proposed S2 | VAL-017 |
| **Q10** | Original appointment at least 60 minutes ahead to reschedule | FR-023; BR-010; NFR-006 | proposed S2 | VAL-018 |
| **Q11** | Destination Slot at least 60 minutes ahead | FR-023; BR-011; NFR-006 | proposed S2 | VAL-018 |
| **Q12** | Cross-Tutor reschedule allowed | FR-024; BR-012 | proposed S2 | VAL-019 |
| **Q13** | Reschedule atomic/all-or-nothing | FR-025; BR-013; NFR-005 | proposed S2 | VAL-020 |
| **Q14** | Reschedule reopens old Slot | FR-025; BR-014 | proposed S2 | VAL-020 |
| **Q15** | Same Booking ID; successful old/new Tutor, Slot/time, timestamp history | FR-026; BR-015 | proposed S2 | VAL-020 |
| **Q16** | One successful reschedule max; failures do not consume quota | FR-027; BR-016; NFR-008 | proposed S2 | VAL-017/020 |
| **Q17** | Only currently assigned authorized Tutor cancels | FR-028; BR-017; NFR-001 | proposed S2 | VAL-021 |

| Q | Confirmed meaning (condensed without changing boundary) | Product FR / BR / applicable NFR | Target verification sprint | Planned evidence |
|---|---|---|---|---|
| **Q18** | Tutor cancellation at least 60 minutes ahead | FR-028; BR-018; NFR-006 | proposed S2 | VAL-021 |
| **Q19** | Tutor cancellation withdraws original Slot, does not reopen | FR-030; BR-019; NFR-005 | proposed S2 | VAL-022 |
| **Q20** | Tutor cancellation reason meaningful and nonblank | FR-029; BR-020 | proposed S2 | VAL-021 |
| **Q21** | Tutor cancellation creates in-app notice only for owning Customer | FR-031; BR-021; NFR-007 | proposed S2 | VAL-023 |
| **Q22** | Reason visible only to affected owning Customer | FR-031; BR-022; NFR-007 | proposed S2 | VAL-023/036 |
| **Q23** | Reason in both private notice and cancelled Booking detail | FR-031; BR-023; NFR-007 | proposed S2 | VAL-023 |
| **Q24** | Read notice remains accessible | FR-032; BR-024; NFR-014 | proposed S2 | VAL-024 |
| **Q25** | No automatic time-based notice expiry; other retention open | FR-032; BR-025; NFR-014 | proposed S2 | VAL-024 |
| **Q26** | Active Booking blocks direct Slot edit/delete/withdrawal | FR-033; BR-026 | proposed S2 | VAL-025 |
| **Q27** | Tutor withdraws own unoccupied future Slot, recreates separate Slot; history retained | FR-034; BR-027 | proposed S2 | VAL-026 |
| **Q28** | One Customer's Active Bookings never overlap across Tutors; adjacency allowed | FR-013; BR-028; NFR-004 | S1 | VAL-004/011 |
| **Q29** | Bangkok timezone, server-authoritative clock | FR-011/017; BR-029; NFR-006 | S1 | VAL-008/013 |
| **Q30** | States Booked/Cancelled; Past derived and not Completed | FR-017/035; BR-030; NFR-016 | S1 (Booked/Past), S2 (Cancelled), S3 (report) | VAL-013/015/028 |
| **Q31** | Tutor-only summary with Upcoming Booked/Past Booked/Cancelled counts and lists | FR-035/036; BR-031; NFR-016 | proposed S3 | VAL-028/029 |
| **Q32** | Withdrawn history does not block separate overlap or permit same-ID reactivation | FR-034; BR-032 | proposed S2 | VAL-027 |

**Audit result at drafting:** Q01-Q32 are each accounted for in a distinct row, with an authorized meaning and planned validation. No Q decision is excluded from the whole-product baseline. Formal source approval and code/test completion remain separate gates.

## 12.3 Available instructor requirements to SRS mapping

| Instructor-draft source | Requirement actually stated in examined handout | Whole-product mapping | Earliest planned verification | Source status |
|---|---|---|---|---|
| GW v1 §5.1 | Working UI → application/API → persistent DB, meaningful domain transaction, restart durability | FR-016/019; NFR-003; BR-034 | S1: VAL-007/031 | **Draft; final master not checked** |
| GW v1 §5.2 | Real login, logout, current identity, session lifecycle, two roles | FR-001..004; NFR-002 | S1: VAL-001/034 | **Draft; final master not checked** |
| GW v1 §5.2 / Theme 1 | Customer own Booking only, Tutor authorized schedule, backend role checks | FR-004/007/014/015; BR-002/033; NFR-001/007 | S1: VAL-002/012/036 | **Draft; final master not checked** |
| GW v1 §6 Theme 1 | Staff creates Slot, Customer views/Books/retrieves; reject occupied/past/invalid; competing single-Slot claims | FR-005..016; BR-001/035; NFR-004/005 | S1: VAL-003..014 | **Draft; eligibility not checked** |

| Instructor-draft source | Requirement actually stated in examined handout | Whole-product mapping | Earliest planned verification | Source status |
|---|---|---|---|---|
| GW v1 §6 Theme 1 | Complete product cancellation/rescheduling, schedule administration, appointment reporting | FR-020..036; BR-007..027/031/032 | proposed S2/S3: VAL-015..029 | **Draft; combined with Q decisions** |
| GW v1 §5.3 | Reviewed GitHub workflow, automated PR build/test and later Docker/GCP delivery | NFR-011/012/013 | S1 contract/review VAL-031; Lab 5 VAL-035 | **Draft; separate engineering Issues** |
| D1 v1 §§3.1-3.4 | Whole-product SRS with FR/BR/NFR, measurable verification and 3-sprint allocation | Document §§0-18; NFR-011/012 | Part A document inspection; later Parts B-D | **Version examined; master cross-check pending** |

No line in the available handouts prescribes a tutoring price, service modality, weekday hours, maximum scheduling horizon, minute increment, performance p95 or automatic attendance state. Adding such a constraint would require an explicit source or approved decision.

### 12.4 Sprint 1 baseline ID crosswalk and consistency

The original `docs/requirements.md` is a **Sprint 1 document** and retains all its IDs. The product-level IDs in this SRS are new identifiers and do not rewrite or renumber the source. The old file's header documents its initial draft stage; GitHub PR #7 is now **merged**, as verified from PR history. The single approved surgical correction in Issue #9 updates its §16.1 AC range to `AC-S1-01..35`; `AC-S1-35` itself already exists in that file and maps to `VC/TEST-S1-39`.

**FR crosswalk:** the meanings of `FR-S1-01..19` correspond **in order** to `FR-001..019`. Specifically:

| Sprint 1 IDs | Whole-product IDs | Requirement group |
|---|---|---|
| FR-S1-01..04 | FR-001..004 | Login, identity, logout, backend authorization |
| FR-S1-05..07 | FR-005..007 | Tutor Slot creation, validity/overlap, own schedule |
| FR-S1-08..09 | FR-008..009 | Customer availability and bookability |
| FR-S1-10..13 | FR-010..013 | Booking, cutoff, exclusive claim, Customer overlap |
| FR-S1-14..17 | FR-014..017 | Private reads, persistence and Booked/Past |
| FR-S1-18..19 | FR-018..019 | Failure handling and full-stack vertical slice |

**BR crosswalk:** the Sprint 1 source sometimes separates one Q rule into several narrower guards. These remain distinct IDs in that document.

| Baseline BR-S1 | Product BR | Baseline BR-S1 | Product BR |
|---|---|---|---|
| 01 | BR-001 | 12 | BR-029 |
| 02 | BR-003 | 13 | BR-005/034 (T_elig interpretation) |
| 03 | BR-004 | 14 | BR-030 |
| 04 | BR-002 | 15 | BR-002 |
| 05 | BR-006 | 16 | BR-002 |
| 06 | BR-006 | 17 | BR-033 |
| 07 | BR-005 | 18 | BR-034 |
| 08 | BR-001 | 19 | BR-001/028/034 |
| 09 | BR-028 | 20 | BR-002/033 |
| 10 | BR-028 | 21 | BR-005/034 |

| Baseline BR-S1 | Product BR | Baseline BR-S1 | Product BR |
|---|---|---|---|
| 11 | BR-035 | 22 | BR-030 |

**NFR crosswalk:** the first number below is the original Sprint 1 suffix; proposed versus required status must carry forward unchanged.

| Baseline NFR-S1 | Product NFR | Baseline NFR-S1 | Product NFR |
|---|---|---|---|
| 01 | NFR-001/007 | 07 | NFR-012 |
| 02 | NFR-002 | 08 | NFR-007/015 |
| 03 | NFR-003 | 09 | NFR-009 (**PROPOSED**) |
| 04 | NFR-004 (stress size proposed) | 10 | NFR-010 (**PROPOSED**) |
| 05 | NFR-004 (stress size proposed) | 11 | NFR-005 |
| 06 | NFR-006 | 12 | NFR-011 |

**Existing AC and validation anchors (not duplicated as a Part E STS):**

| Existing Sprint 1 evidence anchor | Product verification and meaning |
|---|---|
| AC-S1-01..07; VC/TEST-S1-01..07 | VAL-001/002; login, identity, logout, authorization |
| AC-S1-08..14; VC/TEST-S1-08..14, 37 | VAL-003..005/013; Slot duration, ownership, overlap and Race A |
| AC-S1-15..18; VC/TEST-S1-13/15/22 | VAL-006/013; availability, privacy, stale view |
| AC-S1-19..24; VC/TEST-S1-16..24 | VAL-007/008/011; Booking, lead-time and overlap |
| AC-S1-25; VC/TEST-S1-25 | VAL-010; Race B |
| AC-S1-26; VC/TEST-S1-26 | VAL-011; Race C |
| AC-S1-27..29; VC/TEST-S1-22/27/33/38 | VAL-014/030; rollback, conflict, duplicates |
| AC-S1-30..34; VC/TEST-S1-28..32 | VAL-012/013; owned reads, Tutor visibility and Past |
| **AC-S1-35; VC/TEST-S1-39** | **VAL-009; booking request crossing cutoff while waiting** |
| VC/TEST-S1-34..36 | VAL-031/032/033/034; planned reproducibility, security, UX and performance checks |

All `AC-S1-01..35` and `VC-S1-01..39` / `TEST-S1-01..39` remain owned by the original baseline; references here are cross-references, not redefinitions or claims that test code exists.

## 13. Open decisions and approval gates

This register is the **explicit home for uncertainty**. A proposed choice below is not approved simply because the SRS names it. Existing confirmed Q01-Q32 behavior must remain intact while decisions are obtained. `OD` IDs are SRS decision-register identifiers, not requirements or new stakeholder Q numbers.

| ID | Question and existing evidence | Affected scope / reasonable options | Decision owner and required stage | Status / risk |
|---|---|---|---|---|
| **OD-001** | Which Tutor working days, opening hours, holidays and calendar boundaries apply? Q03 fixes duration, not operating hours; baseline TBD-S1-01 is open. | FR-005/006, BR-035; explicitly approve a restriction or document why none is imposed. | @Tanaboonnnnn proposes; @Chxtamos reviews **before Slot Feature SDS**; stakeholder approval for any new business constraint | **OPEN.** An invented workweek could reject valid requests. |

| ID | Question and existing evidence | Affected scope / reasonable options | Decision owner and required stage | Status / risk |
|---|---|---|---|---|
| **OD-002** | Is there a maximum advance scheduling/booking horizon? Q05 provides only a **minimum** lead time; baseline TBD-S1-02 is open. | FR-005/009/011; choose approved upper bound or explicitly decide none, without assuming 7/14/30 days. | Stakeholder decision documented by team and reviewed **before Slot/Booking contracts** | **OPEN.** Inconsistent form and server validation risk. |
| **OD-003** | What start-minute increments are permitted? Exactly 60-minute duration does not imply starts at :00 or :30; baseline TBD-S1-03. | FR-005/006; approve a grid or leave all otherwise-valid minute instants available as a documented decision. | Stakeholder/team + peer **before Slot SDS/STS** | **OPEN.** Hidden UI grid could alter business scope. |
| **OD-004** | Should Customer availability show only bookable Slots or all offers with unavailable markers? Which Tutor labels, sort/filter/page and sensitive fields? Baseline TBD-S1-04 and PR #7 review. | FR-008/009, FR-014/015, NFR-007. Bookable-only is **proposed**, not approved; either presentation must avoid false availability and private data. | Team API/UI contract, @Chxtamos **before S1 feature implementation** | **OPEN PROPOSAL.** UX/privacy ambiguity. |
| **OD-005** | What are session/token invalidation, expiry, refresh and replay safeguards, safe error schemas and exact transactional/time-control mechanisms? Baseline TBD-S1-05. | FR-001..004/011/018, NFR-001/002/015; evaluate technologies in System/Feature SDS without changing the business outcomes. | Engineering design by @Tanaboonnnnn; peer review **before code** | **OPEN DESIGN.** Security and cutoff implementation risk. |
| **OD-006** | Where does an appointment **in progress** fall in Upcoming Booked versus Past Booked? Q30 says Past is derived; the S1 glossary derives it after **end**. Q31 names only the three summary categories. | FR-035, BR-030/031, NFR-016; options include a separately disclosed in-progress subgroup or a specifically approved treatment, without inventing a third Booking **state**. | Stakeholder clarifies; peer review **before S3 Summary SDS/STS** | **OPEN.** Counts could silently omit or misclassify a current lesson. |
| **OD-007** | May the same withdrawn historical Slot be reactivated? **No**: Q32 explicitly prohibits reactivation. Only whether any special restoration request needs a **new separately approved** workflow remains undecided. | FR-034, BR-032. Normal design uses **new Slot ID**; no override is authorized by current baseline. | Q32 already governs; any proposed exception needs **new stakeholder approval before scope change** | **REACTIVATION PROHIBITED; hypothetical exception UNSPECIFIED.** Do not treat prohibition as an open permission. |
| **OD-008** | How long may private reasons/notifications/history be retained or deleted, and by whom? Q24/Q25 require rereadability and no automatic time expiry, but do not resolve user deletion or formal retention governance. | FR-031/032, NFR-007/014/015; no auto-expiry, pending deletion/export/access policy. | Stakeholder/data owner and security reviewer **before notice design/sign-off** | **OPEN.** Privacy and durability tradeoff. |
| **OD-009** | Which filtering, ordering, pagination, category counting snapshots and historical associations apply to Tutor Summary? Q31 gives categories/counts/lists, not query shape or page size. | FR-035/036, NFR-016, OD-006; approve lists and counts against same filters and visibility. | Team + @Chxtamos **before S3 Summary SDS/STS** | **OPEN DESIGN.** Count/list disagreement. |
| **OD-010** | Are keyboard-only flow and p95 <= 2.0 s acceptable product NFR targets? What machines, fixtures, concurrency sample size and exact workloads are approved? PR #7 keeps thresholds proposed. | NFR-004 run sizes, NFR-009/010 targets; accept, revise or defer explicit criteria with recorded methodology. | @Tanaboonnnnn and @Chxtamos, stakeholder/instructor if required **before affected STS approval** | **OPEN PROPOSAL.** No measured performance/UX result yet. |

| ID | Question and existing evidence | Affected scope / reasonable options | Decision owner and required stage | Status / risk |
|---|---|---|---|---|
| **OD-011** | Is the examined `group_work_specs_v1.pdf` the latest final Master? The available copy states **Draft for instructor review, issued 6 Oct 2026**; D1 references `group_work_specs.docx` as master. Searches in the locally approved repository and connected Drive did not locate a newer authoritative master. | All source-derived GW/Theme 1 entries. Obtain current instructor-issued `group_work_specs.docx` or dated official amendment; compare every Part A/Theme rule, record version/date and differences. | Instructor/TA source; @Tanaboonnnnn verifies and @Chxtamos reviews **before formal SRS/Deliverable sign-off** | **UNVERIFIED; FORMAL SIGN-OFF BLOCKED.** PR may proceed as a labeled draft. |
| **OD-012** | Is Theme 1 officially assigned to this two-student team? GW v1 §6 allocates themes from students' final ID digits; no dated assignment/ID evidence is present in reviewed materials. | Entire tutoring context. Obtain instructor/TA theme confirmation or verifiable eligibility record. | Instructor/TA; @Tanaboonnnnn supplies; @Chxtamos checks **before formal sign-off** | **UNVERIFIED; FORMAL SIGN-OFF BLOCKED.** Do not claim eligibility proved. |
| **OD-013** | What result, idempotency key and replay window should repeated Booking/reschedule/cancel submissions use after network uncertainty? Q invariants constrain outcomes but not response protocol. | FR-018/025/027, NFR-008; choose recoverable reconciliation and duplicate policies with real-DB validation. | Engineering + @Chxtamos **before related Feature SDS/STS** | **OPEN DESIGN.** Duplicate effects and misleading response risk. |
| **OD-014** | What exactly qualifies as a `meaningful` Tutor cancellation reason beyond nonblank? Q20 rules out empty/meaningless text but sets no byte count or prohibited vocabulary. | FR-029, BR-020; propose a reviewable validation policy; do not invent a word/minimum-length requirement as confirmed. | Stakeholder/team review **before S2 Tutor cancellation SDS/STS** | **OPEN DETAIL.** Overly weak or arbitrary rejection risk. |
| **OD-015** | Which historical Booking/reschedule fields may a **previous Tutor** see after cross-Tutor reassignment? Q12/Q15 require history; Q02 restricts protected Tutor scope. | FR-015/024/026, NFR-007; evaluate authorized history without granting foreign schedule lookup. | Stakeholder/team privacy and peer **before S2 reschedule SDS/STS** | **OPEN PRIVACY DESIGN.** History must exist without broadening unrelated Tutor access. |

## 13.1 Source-verification record and required delta procedure

| Item checked | Evidence actually available | Finding | Approval consequence |
|---|---|---|---|
| Group Work Specification | `group_work_specs_v1.pdf` in user-supplied `group_project_spec_files.zip`; 15 pages; title page states "Semester 1/2026; Draft for instructor review; Issued: 6 October 2026" | Contains GW §§5.1-5.3 and Theme 1 §6, including full-stack, authentication, team workflow and appointment example | **Draft verified as draft; final master unverified** |
| Deliverable 1 instructions | `project_deliverable_1_v1.pdf` in same archive; 8 pages; due 8 Nov 2026 at 23:59 | Part A requires whole-product FR/BR/NFR and reviewable assumptions; Parts B-D cover product, E-F Sprint 1 | Applied as available D1 instruction; check against later amendments |
| Current repo baseline | `docs/requirements.md` on remote `sprint1`, merged PR #7; root `AGENTS.md`, merged PR #20 | Stable S1 identifiers and Q01-Q32 applicability, peer review/dispositions and repo rules are available | Source verified for this document, **not** instructor-approved by that fact |
| Final master file | Instructor's referenced `group_work_specs.docx` and dated amendments | Not present in the examined supplied archive, current repo or relevant connected Drive search results | **Cannot compute a final-vs-draft difference**; OD-011 blocks sign-off |
| Formal Theme 1 allocation | Student ID digit/official theme decision or instructor/TA confirmation | Not present in the examined evidence | **Cannot certify eligibility**; OD-012 blocks sign-off |

When the final master becomes available, record **filename, issue date, version, source URL/location, reviewer, comparison date, changed requirements and affected FR/BR/NFR/AC/VAL IDs**. If a clause contradicts Q01-Q32, record the conflict and ask the correct decision owner before amending the baseline. Do not overwrite confirmed stakeholder rules silently.

## 14. Exclusions and future compatibility

The project uses three distinct categories, with different approval consequences:

| Category | Example | Consequence |
|---|---|---|
| **Not approved for this product** | Payments, lesson mode/video link, group tutoring, course catalogs, email/SMS reminders, external calendar, attendance, new admin role | No requirement or implementation follows from the current baseline; stakeholder and instructor scope approval would be needed to add one. |
| **Agreed for product, deferred from Sprint 1** | Customer cancellation/reopening (Q07-Q08), reschedule/history (Q09-Q16), Tutor cancellation/reason/notice/withdrawal (Q17-Q27/Q32), Tutor-only summary (Q31) | Must be covered in the whole-product SRS now, but remains **proposed S2/S3 allocation** with future reviewed contracts and code. |
| **Engineering solution not yet selected** | API paths/schema, transaction lock strategy, session/token design, presentation/filtering, idempotency, logging details, measured UX/performance targets | Must preserve business outcomes; propose and approve in SDS/STS, with no invented stakeholder policy. |

**Forward compatibility from S1:** the Booking model must later support `Cancelled` without inventing `Completed`; reschedule must retain the Booking ID/history and update Tutor association; withdrawn Slots must remain historical without blocking current offers; reasons/notifications need ownership boundaries; Tutor summary must use the same authoritative state and time semantics. These constraints are requirements for future design, not authorization to implement S2 features in S1.

## 15. Verification planning

Each `VAL-xxx` is an **unexecuted requirements-level verification plan**, not an executable STS or a report of passing tests. The test author must later specify fixtures, exact inputs, controlled server clock, synchronized race barriers where relevant, database assertions, expected API/UI behavior, and concrete result/version. Below, `negative` means a forbidden or failed case; `boundary` means exact equality and just below/above as appropriate.

### 15.1 Planned validation catalog

| Anchor | Scope and planned method | Required observable evidence | Linked requirements | Target |
|---|---|---|---|---|
| **VAL-001** | API/UI: valid and invalid Customer/Tutor login, identity query, logout and old-session reuse | Correct own role, bad credentials denied, no usable access after logout | FR-001/002/003; BR-033; NFR-001 | S1 |
| **VAL-002** | API integration: anonymous, forged role, foreign Slot/Booking IDs and wrong Tutor requests | All protected actions denied/filtered, payload contains no foreign private data | FR-004/007/014/015/018; BR-002/033; NFR-001 | S1 and regression |
| **VAL-003** | UI/API/DB: Tutor creates one future offer; invalid duration/automatic recurrence attempt | Exactly one owned 60-minute offer saved; no automatic repeating Slots | FR-005; BR-003/004; NFR-003 | S1 |
| **VAL-004** | Boundary/API/DB: past/invalid, same-Tutor overlap, adjacency, different-Tutor same-time, Customer adjacency | Invalid/overlapping offer denied; adjacency/cross-Tutor allowed when other checks pass | FR-006/013; BR-003/006/028/035 | S1 |
| **VAL-005** | Real-DB synchronized Race A: concurrent same-Tutor overlapping offer creation | At most one conflicting current Slot committed; losing attempt no partial Slot | FR-006; BR-006/034; NFR-004 | S1 |
| **VAL-006** | Availability API/UI: eligible, past, occupied, too-soon and stale offers | No false selectable booking; no private third-party data; server rechecks stale result | FR-008/009; BR-005/035; NFR-007 | S1 |

| Anchor | Scope and planned method | Required observable evidence | Linked requirements | Target |
|---|---|---|---|---|
| **VAL-007** | E2E/API/DB: authorized offer → availability → Booking → reload/restart → own retrieval | Exactly one Booked reservation saved and readable from persistent DB by authorized actors | FR-010/016/019; BR-001; NFR-003 | S1 |
| **VAL-008** | Controlled backend clock: exact 60:00 vs 59:59 cutoff and wrong browser timezone | Exact boundary eligible, below rejected; correct Bangkok scheduling meaning | FR-011; BR-005/029; NFR-006 | S1 |
| **VAL-009** | Controlled transaction waiting at Q05 cutoff, including prior HTTP arrival | Reject when final guarded `T_elig` is too late; no false success or occupied Slot | FR-009/011; BR-005/034; NFR-006 | S1 |
| **VAL-010** | Real-DB synchronized Race B: two Customers, one Slot | At most one committed Active Booking and one occupied Slot | FR-012; BR-001/034; NFR-004 | S1 |
| **VAL-011** | API/DB sequential plus synchronized Race C: same Customer, overlapping Tutors | No overlapping Active Bookings committed; adjacency allowed by overlap rule | FR-013; BR-028/034; NFR-004 | S1 |
| **VAL-012** | API/UI: own Customer list/detail; Tutor schedule; foreign IDs, refresh | Authorized records visible and persisted, foreign data absent | FR-007/014/015; BR-002; NFR-001/007 | S1 |
| **VAL-013** | Time/UI/API: past end, non-Bangkok device and Booking status check | Past display may be derived; status remains Booked; no Completed or time shift | FR-017; BR-029/030; NFR-006 | S1, report regression S3 |
| **VAL-014** | DB fault injection and stale selection/invalid input for Slot or Booking | No partial claim, false confirmation or mutation after rejection | FR-011/016/018; BR-034/035; NFR-005 | S1 |
| **VAL-015** | S2 API/DB: owning/nonowning Customer cancel; exact 30:00 and just below | Valid owner cancels to Cancelled with Slot re-open; invalid leaves original untouched | FR-020/021; BR-007; NFR-006 | proposed S2 |
| **VAL-016** | S2 boundary/DB: newly reopened original Slot inside new-Booking cutoff | Slot exists as offered/unoccupied but new Booking under 60 minutes denied | FR-021; BR-005/008/014 | proposed S2 |
| **VAL-017** | S2 API/DB: foreign Customer reschedule, one previous success, unsuccessful attempt | Foreign/second-success rejected; failed attempt leaves quota available | FR-022/027; BR-009/016; NFR-008 | proposed S2 |
| **VAL-018** | S2 controlled clock: old and destination starts at exactly 60:00 vs just below | Both boundaries enforced independently; no partial move | FR-023; BR-010/011; NFR-006 | proposed S2 |
| **VAL-019** | S2 API/DB: valid cross-Tutor destination | New Tutor assignment allowed, independent conflicts still enforced | FR-024; BR-012/028 | proposed S2 |
| **VAL-020** | S2 real-DB: successful and rejected reschedule, destination collision, forced rollback | Same Booking ID; old/new history on success only; old Slot reopened, destination claimed, failed attempt restores prior state/quota | FR-025/026/027; BR-013..016; NFR-005/008 | proposed S2 |
| **VAL-021** | S2 API: current versus wrong Tutor; exact 60:00, 59:59; blank/meaningless reason | Only valid owner/cutoff/reason permits action; otherwise no state changes | FR-028/029; BR-017/018/020; NFR-006 | proposed S2 |
| **VAL-022** | S2 API/DB: Tutor cancellation with committed Booking/Slot relation | Booking Cancelled; original Slot withdrawn, not reoffered; no partial result on fault | FR-030; BR-019; NFR-005 | proposed S2 |
| **VAL-023** | S2 API/UI: successful Tutor cancellation; owning vs foreign Customer, reason fields | Exactly intended owner gets notice and reason in both notice and Booking detail; no leak | FR-031; BR-021..023; NFR-007 | proposed S2 |
| **VAL-024** | S2 persistence/UI: mark notice read, reenter later, simulate age passage | Same owner can reread; no automatic time expiry; deletion policy remains unresolved | FR-032; BR-024/025; NFR-014 | proposed S2 |

| Anchor | Scope and planned method | Required observable evidence | Linked requirements | Target |
|---|---|---|---|---|
| **VAL-025** | S2 API/DB: attempt direct edit/delete/withdraw with Active Booking | All such direct operations denied without modifying occupied Slot | FR-033; BR-026 | proposed S2 |
| **VAL-026** | S2 API/DB: own unoccupied future withdraw and separate new Slot creation | Old historical record retained; new distinct ID accepted if otherwise valid | FR-034; BR-027 | proposed S2 |
| **VAL-027** | S2 API/DB: new offer overlapping withdrawn history and attempted historical reactivation | New offer not blocked by withdrawn Slot; original ID not reactivated | FR-034; BR-032 | proposed S2 |
| **VAL-028** | S3 API/UI/DB: known Booked-upcoming, Booked-past and Cancelled fixtures | Counts and accessible lists match exact categories and state/time without Completed | FR-035; BR-030/031; NFR-016 | proposed S3 |
| **VAL-029** | S3 API: Customer/anonymous/foreign Tutor summary; in-progress fixture | No foreign summary; in-progress category follows **approved future decision**, not guessed default | FR-035/036; BR-031; NFR-001/016 | proposed S3 |
| **VAL-030** | API/DB: repeated/uncertain Booking or reschedule calls | Invariants/quota/history unchanged by unsafe duplicates; concrete retry response to be specified | FR-018/025/027; BR-001/034; NFR-008 | S1/S2 |
| **VAL-031** | Documentation/release evidence review and reproducible local start | Documented SHA, setup, persistent data checks, actual command outputs, peer-reviewed PR chain | FR-019; NFR-003/011/012 | S1-S3 |
| **VAL-032** | Candidate p95 benchmark over 50+ warm-up-excluded GETs per operation with recorded environment | Record raw data/p95 and compare only after threshold approval; **no execution here** | NFR-010 | proposed S1/S3 |
| **VAL-033** | Candidate manual keyboard walk-through with recorded browser/focus checklist | Record accessibility findings; compare only after target approval | NFR-009 | proposed S1/S3 |
| **VAL-034** | Security review of stored test passwords, secrets/configuration and error/log traces | No plaintext secrets and no protected fields; approved hashing method demonstrated when implemented | NFR-002/015; FR-001 | S1 and regression |
| **VAL-035** | Lab 5+ pipeline/packaging/deploy check, linked release/version | Docker/GCP persistence, required PR build/test gate and repeatable main release with actual outputs | NFR-013 | Lab 5+, outside Issue #9 |
| **VAL-036** | Negative API payload inspection for availability, Booking, notification, summary and error paths | No foreign owner data, cancellation reason or restricted Tutor records in serialized results | FR-004/008/014/015/031/036; BR-022/033; NFR-001/007/015 | S1-S3 |

### 15.2 Coverage and test-readiness boundaries

At the **requirements** stage, VAL-001..036 give a planned validation path for each FR-001..036, BR-001..035 and NFR-001..016. Crosswalk §12.4 preserves the planned Sprint 1 anchors `AC-S1-01..35` and `VC/TEST-S1-01..39`. The true implementation later needs tests that fail for the right reason before code (TDD), seeded role fixtures, a controlled server clock, a real transactional database for the three races, injected rollback failures and exact recorded outcomes. Final Test Specification IDs, test source files and pass/fail counts belong to Parts E/F, not this SRS.

**Validation is not approval:** a structural ID check validates document consistency, a teammate review evaluates the requirements, a formal stakeholder decision authorizes disputed behavior, and an executed test validates implemented behavior. These evidence types must not be substituted for one another.

## 16. Risks, dependencies and change control

| Risk / dependency | Exposure | Control and required evidence | Owner / gate |
|---|---|---|---|
| Final instructor specification and Theme unverified | Wrong scope or unapproved team topic | Locate dated final Master + Theme decision; record exact version and differences; revise via reviewed PR | Instructor/TA, @Tanaboonnnnn; OD-011/012 before formal sign-off |
| New working-hours/horizon/start grid invented in design | Unapproved rejection of valid scheduling | Keep OD-001..003 open, seek specific policy approval, update FR/BR/AC/VAL before implementation | Product decision owner; Slot/Booking contracts |
| Concurrent Slot/Booking collisions | Double offers, double claims, cross-Tutor overlap | Synchronized real-DB Race A/B/C tests and reviewable transaction guarantees | Engineering + @Chxtamos; S1 contracts |
| Cutoff evaluated at client or early request time | Incorrect exact-boundary outcomes | Preserve Q05 and reviewed `T_elig` interpretation, test contention crossing; define S2 mutation decision points | Feature contract reviewers |
| Partial reschedule/cancellation/notification writes | Lost reservation, wrong Slot state or private false notice | Atomic transaction and fault-injection evidence, exact history/quota assertions | S2 Feature SDS/STS |
| Privacy and reschedule history | Other Customer/Tutor sees reason, past association or summary | Role/record matrix plus full response allowlist review and negative API tests; OD-015 | Security/data owner + peer |
| Summary in-progress classification | Incorrect count/list or dropped current session | Decide OD-006 and OD-009 before S3 contract; compare counts to underlying authorized row sets | Stakeholder and peer |
| Unapproved NFR target silently treated as pass gate | Unsupported performance or UX claims | Record approval status and environment/method before adopting; preserve measured results | OD-010; team/stakeholder |
| Feature-order dependency | Later sprints assume unavailable S1 identity/transaction model | S1 auth/Slots/Booking first; S2 cancel/reschedule/notice/withdraw; S3 reports/hardening; revalidate after review | Issue #12 planning, separate implementation Issues |
| Scope or document drift | Q decisions contradicted, undocumented changes enter app | Versioned SRS and explicit change record with source/decision owner, affected IDs, planned tests and peer review | All future PRs |

**Change-control procedure:** A proposal changing Q01-Q32 must identify the decision ID, present its source and impact, obtain explicit stakeholder approval, then revise affected product FR/BR/NFR, open decisions, acceptance/validation mappings and the later design/test contracts in reviewable commits. An instructor-final discrepancy requires a recorded source comparison and decision owner. A formatting or technical design choice must not silently relax a confirmed cutoff, role boundary, one-to-one exclusivity, transaction integrity or notification privacy rule.

## 17. Review checklist and sign-off

These checkboxes are review tasks, **not claims of completion**. Human reviewer should inspect the entire document against the linked evidence.

### 17.1 Reviewer checklist for @Chxtamos

- [ ] Whole-product scope is distinct from the Sprint 1-only source; S2/S3 capabilities are present without inventing implementation.
- [ ] Every Q01-Q32 appears once in §12.2 and the mapped FR/BR describes the same approved decision, with no unsupported extra business policy.

- [ ] All FR-001..036, BR-001..035 and NFR-001..016 have unique meanings, sources, proposed target sprints and usable validation anchors.
- [ ] Theme 1/Deliverable 1 instructor minimum is accurately identified as an **examined draft** where appropriate, not falsely claimed final.
- [ ] Exactly sixty-minute manual offers, Q05 equality, Q07 30-minute equality, Q10/Q11/Q18 60-minute equalities and Bangkok server time agree across catalogs and scenarios.
- [ ] Same-Tutor current offers, exclusive Slot and same-Customer cross-Tutor races are three **separate** committed-DB obligations; adjacency and withdrawn-history exceptions are correct.
- [ ] Customer cancellation reopens old Slot, but Tutor cancellation withdraws old Slot; failed reschedule preserves old Booking and quota; one success preserves Booking ID/history.
- [ ] Privacy matrix denies foreign Customer/Tutor reads, notice/reason leaks and Customer access to the Tutor-only summary.
- [ ] Booked/Cancelled are the only Booking business states; Past is derived; no Completed/attendance assumption appears.
- [ ] Open policies OD-001..015, especially final Master/Theme and proposed NFR performance/UX targets, are not written as approvals.
- [ ] Existing Sprint 1 `FR-S1`, `BR-S1`, `NFR-S1`, `AC-S1` and `VC/TEST-S1` identifiers are not redefined; §16.1 in `requirements.md` includes `AC-S1-35`.
- [ ] Full-document Markdown, relative links, table consistency, ID references, source accuracy, scope and Git file allowlist are checked.
- [ ] No application code, Feature SDS, test implementation or release/deployment claims are part of Issue #9.
- [ ] A real GitHub **Review Request** was issued to @Chxtamos, and their subsequent review is separately recorded before any merge.

### 17.2 Sign-off record

| Review gate | Responsible party | Current evidence and status |
|---|---|---|
| Author's requirements drafting/structural validation | @Tanaboonnnnn | Document submitted as draft for Issue #9; structural/semantic review results belong in PR verification report |
| Independent peer review | @Chxtamos | **PENDING**; no approval recorded in this SRS |
| Material open policy/NFR decisions | Stakeholder/product owner and team | **PENDING** OD-001..006, OD-008..010, OD-013..015 |
| Final instructor Master version and Theme 1 eligibility | Instructor/TA, verified by team | **UNVERIFIED** OD-011/012; formal approval **BLOCKED** |
| Whole-product SRS approval | Authorized decision owner following independent review | **NOT APPROVED** |
| Application implementation, automated tests, release and deployment | Separate engineering Issues | **NOT VERIFIED BY THIS DOCUMENT** |

The SRS can be reviewed and improved through an Issue-linked PR while these external gates are open. Peer approval alone must not be represented as the instructor's final requirements approval. No merge is authorized by this document.

## 18. References

Only materials actually inspected or explicitly provided as the agreed baseline are listed as evidence. Titles and versions are reproduced from sources, without fabricated approval dates or inaccessible references.

| Key | Source and location | Purpose / limitation |
|---|---|---|
| SRC-Q, SRC-S1 | Sprint 1 Requirements Specification, `docs/requirements.md` on sprint1; stakeholder decisions Q01-Q32 and numbered Sprint 1 catalog | Verified repository baseline from merged PR #7. This is **not** the whole-product SRS or proof of final instructor approval. |

| Key | Source and location | Purpose / limitation |
|---|---|---|
| SRC-GW-v1 | `group_work_specs_v1.pdf`, CPE 334 Group Work Specification, **Draft for instructor review**, issued **6 October 2026**, 15 pages; user-supplied `group_project_spec_files.zip` | Actual available theme/technical/course handout. Its final `group_work_specs.docx` replacement was **not verified**. |
| SRC-D1-v1 | `project_deliverable_1_v1.pdf`, CPE 334 Project Deliverable 1, due 8 November 2026 at 23:59, 8 pages; same supplied archive | Whole-product Part A requirements and downstream Parts B-F boundaries. |
| SRC-AGENT | Repository AGENTS.md, incorporated by PR #20 | Repository workflow, scope, verification and no-self-merge obligations, **not new stakeholder rules**. |
| SRC-ISSUE | Issue #9: D1-01 Part A Whole-product SRS | Assigned deliverable, allowed files and acceptance criteria. |
| SRC-REVIEW | PR #7 review history | Peer feedback and final correction request that §16.1 include `AC-S1-35`; independently reviewed S1 baseline. |
| Structural reference only | SE-Project-God-of-Merchandise-Store | Repository root listing was accessible, but no SRS file was available to inspect there. **No Store business rule, quotation or claimed SRS content is used**. |

**End of v0.1.0 draft.** This document can support independent engineering review. Formal sign-off remains subject to the final instructor Master/Theme confirmation, resolution of material open decisions and an actual reviewer decision.

# Part B: Feature Inventory & Requirements Traceability Matrix

## B.1 Feature Inventory (docs/features.md)

Draft for teammate review. SRS is authoritative. Sprint 2/3 allocations are proposed, not approved.

| Stable ID | Feature and required outcome | Actor | Sprint | Dependency | Linked FR/BR/NFR | Planned verification |
|---|---|---|---|---|---|---|
| F-S1-01 | Customer/Tutor can log in, retrieve trusted identity, and log out; backend rejects unauthorized roles and records | Customer/Tutor | S1 | none | FR-001, FR-002, FR-003, FR-004, BR-002, BR-033, NFR-001, NFR-002 | VAL-001/002 (planned) |
| F-S1-02 | Tutor creates and retrieves own 60-minute Slots; concurrent overlap is rejected and adjacent offers allowed | Tutor | S1 | F-S1-01 | FR-005, FR-006, FR-007, BR-003, BR-004, BR-006, BR-035 | VAL-003/004/005 (planned) |
| F-S1-03 | Customer discovers eligible Tutor/time offers without third-party Booking data | Customer | S1 | F-S1-02 | FR-008, FR-009 | VAL-006 (planned) |
| F-S1-04 | Customer books one eligible Slot persistently; concurrent same-Slot claims and overlapping Customer bookings are rejected | Customer | S1 | F-S1-01/02/03 | FR-010, FR-011, FR-012, FR-013, BR-001, BR-005, BR-028, NFR-008 (S1 Booking retry safety) | VAL-007..011/014/030 (planned) |
| F-S1-05 | Customer reads only own persisted Bookings and Tutor reads only own schedule after refresh; Past is not Completed | Customer/Tutor | S1 | F-S1-01/04 | FR-014, FR-015, FR-016, FR-017, BR-030 | VAL-012/013 (planned) |

| Stable ID | Feature and required outcome | Actor | Sprint | Dependency | Linked FR/BR/NFR | Planned verification |
|---|---|---|---|---|---|---|
| F-S2-01 | Customer cancels own eligible Booking and atomically reopens original Slot (proposed) | Customer | S2 proposed | F-S1-04 | FR-020, FR-021, BR-007, BR-008 | VAL-015/016 (planned) |
| F-S2-02 | Customer reschedules at most once, even across Tutors, retaining ID and atomic history (proposed) | Customer | S2 proposed | F-S1-04/05 | FR-022, FR-023, FR-024, FR-025, FR-026, FR-027, BR-009, BR-010, BR-011, BR-012, BR-013, BR-014, BR-015, BR-016, NFR-008 | VAL-017..020 (planned) |
| F-S2-03 | Authorized Tutor cancels with a reason and atomically withdraws the Slot (proposed) | Tutor | S2 proposed | F-S1-02/04 | FR-028, FR-029, FR-030, BR-017, BR-018, BR-019, BR-020 | VAL-021/022 (planned) |
| F-S2-04 | Owning Customer privately reads and rereads durable cancellation notice (proposed) | Customer | S2 proposed | F-S2-03 | FR-031, FR-032, BR-021, BR-022, BR-023, BR-024, BR-025, NFR-014 | VAL-023/024 (planned) |
| F-S2-05 | Tutor withdraws unoccupied future Slot, preserving history and allowing distinct replacement (proposed) | Tutor | S2 proposed | F-S1-02 | FR-033, FR-034, BR-026, BR-027, BR-032 | VAL-025..027 (planned) |

| Stable ID | Feature and required outcome | Actor | Sprint | Dependency | Linked FR/BR/NFR | Planned verification |
|---|---|---|---|---|---|---|
| F-S3-01 | Tutor views authorized counts and matching lists for Upcoming, Past and Cancelled (proposed) | Tutor | S3 proposed | F-S1-05 | FR-035, FR-036, BR-031, NFR-016 | VAL-028/029 (planned) |
| SYS-01 | System preserves atomic/durable changes, authorization, reproducible evidence and a proposed deployment design | System | S1-S3/Lab5+ | all | FR-018, FR-019, BR-029, BR-034, NFR-003, NFR-004, NFR-005, NFR-006, NFR-007, NFR-009, NFR-010, NFR-011, NFR-012, NFR-013, NFR-015 | VAL-005/006/010/011/012/014/020/022/023/029/030..036 (planned across S1/S2/S3) |

### Baseline and invariants

F-S1-01..05 retain the five accepted Sprint 1 identities (Auth, Tutor Slots, Availability, Booking, Protected Read) from requirements.md. SYS-01 owns cross-cutting engineering obligations, while all features still enforce role and record authorization. NFR-004 is shared by F-S1-02 (Race A) and F-S1-04 (Races B/C), while NFR-007 privacy applies to F-S1-03/F-S1-05 in S1, F-S2-04 in proposed S2, and F-S3-01 in proposed S3. These shared applications do not create duplicate primary owners; see traceability.md.

Race A: F-S1-02 / Q06 / FR-006 / BR-006/034 / VAL-005 — same-Tutor overlapping offered Slots.

Race B: F-S1-04 / Q01 / FR-012 / BR-001/034 / VAL-010 — two Customers, one Slot.

Race C: F-S1-04 / Q28 / FR-013 / BR-028/034 / VAL-011 — one Customer, overlapping Tutors.

All three require actual committed database checks. S2 cancellation, rescheduling, withdrawal and notices and S3 summary are planned only. See traceability.md for coverage and SRS §13 for OD-001..015.

### Acceptance and review

Each feature must preserve its listed requirement outcomes and planned VAL evidence; Feature SDS/STS must be peer reviewed before implementation. Owner @Chxtamos; independent reviewer @Tanaboonnnnn. Issue #10 requires a PR into sprint1.

---

## B.2 Requirement Traceability Matrix (docs/traceability.md)

DRAFT. Source: SRS, features, Sprint 1 requirements. All validation is PLANNED, NOT EXECUTED.

| Product requirement | Complete SRS intent (linked source) | Accountable feature / responsibility | Target sprint | Planned validation |
|---|---|---|---|---|
| FR-001 | Customer/Tutor: With existing valid credentials, authenticate and establish only that principal's effective role; reject invalid credentials without authenticated access. (full FR-001) | F-S1-01 | S1 | VAL-001 (planned) |

| Product requirement | Complete SRS intent (linked source) | Accountable feature / responsibility | Target sprint | Planned validation |
|---|---|---|---|---|
| FR-002 | Authenticated Customer/Tutor: Return the current principal's own identity and role without accepting a client-supplied impersonation; anonymous requests reveal no protected identity. (full FR-002) | F-S1-01 | S1 | VAL-001, VAL-002 (planned) |
| FR-003 | Authenticated Customer/Tutor: Log out and render the prior session/access unusable for protected operations; the exact invalidation/expiry method must be decided in the auth contract. (full FR-003) | F-S1-01 | S1 | VAL-001, VAL-002 (planned) |
| FR-004 | Application/server: Authenticate and enforce role and record ownership on every protected Slot, Booking, notification and summary action, including crafted requests and URL/ID access; reject unauthorized access without private payload. (full FR-004) | F-S1-01 | S1 / S2 proposed / S3 proposed | VAL-002, VAL-036 (planned) |
| FR-005 | Tutor: Given authorization to their own schedule and a valid future start, publish exactly one explicit sixty-minute Slot; persist it under the authenticated Tutor, without recurrence or auto-generated bulk offers. (full FR-005) | F-S1-02 | S1 | VAL-003 (planned) |
| FR-006 | Server on Tutor creation: Reject malformed/past Slots and overlaps between currently offered Slots of the same Tutor; permit adjacent intervals and independent same-time offers by another Tutor when otherwise valid; leave existing offers unchanged on rejection. (full FR-006) | F-S1-02 | S1 | VAL-004, VAL-005 (planned) |
| FR-007 | Tutor: Retrieve own offered Slots and authorized occupied/unoccupied schedule view from committed data; reject another Tutor's protected schedule lookup. (full FR-007) | F-S1-02 | S1 | VAL-002, VAL-012 (planned) |
| FR-008 | Customer: Browse Tutor/Slot/time information sufficient to choose a specific offer, without disclosure of another Customer's private reservation; the concrete field allowlist remains an API-contract choice. (full FR-008) | F-S1-03 | S1 | VAL-006, VAL-036 (planned) |
| FR-009 | Server/availability view: Mark an offer bookable only when current, unoccupied, eligible and not too close to its start; an earlier view must not guarantee later acceptance. Hide-versus-disabled presentation is unresolved. (full FR-009) | F-S1-03 | S1 | VAL-006, VAL-009 (planned) |
| FR-010 | Customer: Given an eligible Slot and no overlapping Active Booking, request one exclusive reservation for their authenticated identity; commit one `Booked` Booking referencing the actual Slot and Tutor before acknowledging success. (full FR-010) | F-S1-04 | S1 | VAL-007 (planned) |
| FR-011 | Server on Booking: Revalidate offered/unoccupied state, user ownership, cutoff and overlaps immediately before a guarded Booking write; reject stale, invalid, past, too-soon or occupied choices with no partial reservation. (full FR-011) | F-S1-04 | S1 | VAL-008, VAL-009, VAL-014 (planned) |
| FR-012 | Server on competing Bookings: Under simultaneous attempts by different Customers for the same exclusive Slot, allow at most one committed Active Booking and never return two successful claims. (full FR-012) | F-S1-04 | S1 | VAL-010 (planned) |
| FR-013 | Server on Customer Booking: Reject the same Customer's overlapping Active reservation, including requests for two different Tutors; accept adjacency under this specific rule, with at most one conflicting success under concurrency. (full FR-013) | F-S1-04 | S1 | VAL-004, VAL-011 (planned) |
| FR-014 | Customer: Retrieve a persisted list and detail of own Bookings with Booking identity, Tutor/Slot/interval and business status; foreign IDs must not disclose Booking data. (full FR-014) | F-S1-05 | S1 | VAL-012, VAL-036 (planned) |

| Product requirement | Complete SRS intent (linked source) | Accountable feature / responsibility | Target sprint | Planned validation |
|---|---|---|---|---|
| FR-015 | Tutor: Retrieve Bookings attached to the Tutor's authorized schedule only; requesting another Tutor's records must not disclose them. (full FR-015) | F-S1-05 | S1 | VAL-002, VAL-012 (planned) |
| FR-016 | Application: Authorized reopened/refresh/restart views must reflect successfully committed Slots/Bookings and correct ownership; a failed transaction must not produce a persisted or reported phantom Booking. (full FR-016) | F-S1-05 | S1 | VAL-007, VAL-014 (planned) |
| FR-017 | Application views: Display `Booked` accurately and, when a Booking's end is past, optionally derive `Past`; never assert `Completed`, attendance or auto-release solely from elapsed time. (full FR-017) | F-S1-05 | S1 | VAL-013 (planned) |
| FR-018 | Application/server: Return an observable, non-success rejection for forbidden, invalid, stale, conflicting or failed mutations, without leaking protected records or leaving partial state. Specific HTTP status/payload formats remain contract decisions. (full FR-018) | SYS-01 | S1-S3/Lab5+ | VAL-002, VAL-014, VAL-030 (planned) |
| FR-019 | System: Support the Tutor offer → Customer browse → committed Booking → authorized retrieval journey through a real UI, application/API and durable database, surviving refresh and application restart. (full FR-019) | SYS-01 | S1-S3/Lab5+ | VAL-007, VAL-031 (planned) |
| FR-020 | Owning Customer: Cancel their current Booking when the Appointment starts at least 30 minutes after the server's authoritative decision; at the exact boundary allow, below it deny; foreign or nonactive Booking cannot be cancelled. (full FR-020) | F-S2-01 | S2 proposed | VAL-015 (planned) |
| FR-021 | Server on successful Customer cancellation: Change Booking to `Cancelled` and reopen its same original Slot atomically; keep it unbookable for any later new request failing the independent Q05 cutoff. (full FR-021) | F-S2-01 | S2 proposed | VAL-015, VAL-016 (planned) |
| FR-022 | Owning Customer: Initiate rescheduling of an existing `Booked` Booking; reject nonowners and disallowed Booking state. (full FR-022) | F-S2-02 | S2 proposed | VAL-017 (planned) |
| FR-023 | Server on reschedule: Require both original Appointment start and destination Slot start to be at least 60 minutes away at authoritative decision; reject either too-late side including the just-below-boundary case. (full FR-023) | F-S2-02 | S2 proposed | VAL-018 (planned) |
| FR-024 | Owning Customer: Select a valid destination with a different Tutor if desired; do not restrict rescheduling to the original Tutor, while still enforcing destination occupancy and same-Customer overlap. (full FR-024) | F-S2-02 | S2 proposed | VAL-019 (planned) |
| FR-025 | Server on reschedule: Atomically update Booking assignment, occupy destination, release/reopen original Slot and record history; any validation, conflict or persistence failure leaves all related records at their pre-attempt state. (full FR-025) | F-S2-02 | S2 proposed | VAL-020 (planned) |
| FR-026 | Server: Preserve the Booking ID across a successful reschedule and append a successful-change record with former/new Tutor, Slot/interval and timestamp; rejected attempts do not create successful history. (full FR-026) | F-S2-02 | S2 proposed | VAL-020 (planned) |
| FR-027 | Server: Permit at most one successful reschedule per Booking; a failed attempt leaves the allowance available, while a second successful-change request is rejected. (full FR-027) | F-S2-02 | S2 proposed | VAL-017, VAL-020 (planned) |

| Product requirement | Complete SRS intent (linked source) | Accountable feature / responsibility | Target sprint | Planned validation |
|---|---|---|---|---|
| FR-028 | Currently assigned Tutor: Cancel an Active Booking belonging to the Tutor's authorized schedule only when its start is at least 60 minutes away; exact boundary passes and wrong-Tutor/too-late attempts fail. (full FR-028) | F-S2-03 | S2 proposed | VAL-021 (planned) |
| FR-029 | Tutor/server: Require a meaningful nonblank reason before accepting Tutor cancellation; reject absent, whitespace-only or semantically empty reason without changing Booking or Slot. Length/format details need approved design. (full FR-029) | F-S2-03 | S2 proposed | VAL-021 (planned) |
| FR-030 | Server on successful Tutor cancellation: Mark Booking `Cancelled` and withdraw its original Slot instead of reopening it; preserve trace/history and ensure no partial outcome. (full FR-030) | F-S2-03 | S2 proposed | VAL-022 (planned) |
| FR-031 | Server: On successful Tutor cancellation create one private in-app notice for that Booking's owning Customer, including the authorized reason; the reason also appears in that Customer's cancelled Booking details, never in third-party views. (full FR-031) | F-S2-04 | S2 proposed | VAL-023, VAL-036 (planned) |
| FR-032 | Owning Customer: Retrieve and reread Tutor-cancellation notices after marking them read; absence of automatic time-based expiry must hold, while deletion/retention governance remains undecided. (full FR-032) | F-S2-04 | S2 proposed | VAL-024 (planned) |
| FR-033 | Server/Tutor: Forbid direct edit, deletion or withdrawal of a Slot while it carries an Active Booking; require the separate authorized cancellation workflow first. (full FR-033) | F-S2-05 | S2 proposed | VAL-025 (planned) |
| FR-034 | Owning Tutor: Withdraw an unoccupied future currently offered Slot while retaining its history; permit later creation of a distinct new Slot with a new ID that may overlap the withdrawn interval; reject reopening/reactivating the withdrawn historical Slot. (full FR-034) | F-S2-05 | S2 proposed | VAL-026, VAL-027 (planned) |
| FR-035 | Tutor: Retrieve an Appointment Summary with counts and corresponding lists for Upcoming Booked, Past Booked and Cancelled on the Tutor's authorized schedule, calculated from stored Booking state and server time; in-progress classification remains OD-006. (full FR-035) | F-S3-01 | S3 proposed | VAL-028, VAL-029 (planned) |
| FR-036 | Server: Deny Customers, anonymous callers and unrelated Tutors access to the Tutor-only summary and its linked Booking details; counts/lists must share the same visibility and classification criteria. (full FR-036) | F-S3-01 | S3 proposed | VAL-029, VAL-036 (planned) |
| BR-001 | One Slot reserves one exclusive one-to-one Customer/Tutor session; at most one Active Booking may claim it. (full BR-001) | F-S1-04 | S1 | VAL-007, VAL-010 (planned) |
| BR-002 | Tutor = Staff and may manage or inspect their own authorized schedule; Customer = learner and may inspect only own private Booking data. (full BR-002) | F-S1-01 | S1 | VAL-002, VAL-012 (planned) |
| BR-003 | Every Availability Slot has a duration of exactly 60 minutes. (full BR-003) | F-S1-02 | S1 | VAL-003, VAL-004 (planned) |
| BR-004 | Tutor creates individual explicit Slots; no automatic recurrence or bulk Slot generation is authorized. (full BR-004) | F-S1-02 | S1 | VAL-003 (planned) |
| BR-005 | For a new Booking, `SlotStart - authoritative server eligibility time >= 60 minutes`; equality is eligible, even if later commit succeeds after the check. A 59:59 remaining interval fails. (full BR-005) | F-S1-04 | S1 | VAL-008, VAL-009 (planned) |

| Product requirement | Complete SRS intent (linked source) | Accountable feature / responsibility | Target sprint | Planned validation |
|---|---|---|---|---|
| BR-006 | Two currently offered Slots of the same Tutor cannot overlap. Adjacent half-open intervals are permitted; different Tutors may independently offer the same time. (full BR-006) | F-S1-02 | S1 | VAL-004, VAL-005 (planned) |
| BR-007 | Only the owning Customer may cancel an Active Booking at least 30 minutes before Appointment start, including equality. (full BR-007) | F-S2-01 | S2 proposed | VAL-015 (planned) |
| BR-008 | Successful Customer cancellation reopens the original Slot, but a future new Booking still independently requires BR-005. (full BR-008) | F-S2-01 | S2 proposed | VAL-016 (planned) |
| BR-009 | Only the Booking-owning Customer may initiate its reschedule. (full BR-009) | F-S2-02 | S2 proposed | VAL-017 (planned) |
| BR-010 | Reschedule's original Appointment must start at least 60 minutes after the authoritative decision; equality passes. (full BR-010) | F-S2-02 | S2 proposed | VAL-018 (planned) |
| BR-011 | Reschedule's destination Slot must start at least 60 minutes after the authoritative decision; equality passes. (full BR-011) | F-S2-02 | S2 proposed | VAL-018 (planned) |
| BR-012 | A valid Customer reschedule may move to another Tutor; original-Tutor-only restrictions are forbidden. (full BR-012) | F-S2-02 | S2 proposed | VAL-019 (planned) |
| BR-013 | Reschedule is all-or-nothing across assignment, both Slot states and successful history. Failure leaves the previous Booking intact. (full BR-013) | F-S2-02 | S2 proposed | VAL-020 (planned) |
| BR-014 | Successful reschedule reopens the original Slot, subject to independent new-Booking eligibility. (full BR-014) | F-S2-02 | S2 proposed | VAL-016, VAL-020 (planned) |
| BR-015 | Successful reschedule keeps the same Booking ID and records old/new Tutor, Slot/time and change timestamp. (full BR-015) | F-S2-02 | S2 proposed | VAL-020 (planned) |
| BR-016 | At most one successful reschedule per Booking; failures do not use that allowance. (full BR-016) | F-S2-02 | S2 proposed | VAL-017, VAL-020 (planned) |
| BR-017 | Only the currently authorized Tutor assigned to the Booking may cancel it as Tutor. (full BR-017) | F-S2-03 | S2 proposed | VAL-021 (planned) |
| BR-018 | Tutor cancellation requires Appointment start at least 60 minutes after the authoritative decision, equality included. (full BR-018) | F-S2-03 | S2 proposed | VAL-021 (planned) |
| BR-019 | Successful Tutor cancellation withdraws the original Slot; it must not reopen it. (full BR-019) | F-S2-03 | S2 proposed | VAL-022 (planned) |
| BR-020 | Tutor cancellation requires a meaningful nonblank reason; an empty/whitespace-only input is invalid. Further textual-validation details require approval. (full BR-020) | F-S2-03 | S2 proposed | VAL-021 (planned) |
| BR-021 | Each successful Tutor cancellation creates an in-app notice for the affected owning Customer only. (full BR-021) | F-S2-04 | S2 proposed | VAL-023 (planned) |
| BR-022 | Tutor-cancellation reason is visible only to the owning Customer, not to other Customers or unrelated Tutors in accessible results. (full BR-022) | F-S2-04 | S2 proposed | VAL-023, VAL-036 (planned) |
| BR-023 | That Customer sees the cancellation reason in both the in-app notice and cancelled Booking detail. (full BR-023) | F-S2-04 | S2 proposed | VAL-023 (planned) |
| BR-024 | Reading a notification does not make it inaccessible; it remains available to reread. (full BR-024) | F-S2-04 | S2 proposed | VAL-024 (planned) |
| BR-025 | Notifications do not expire automatically with elapsed time. This does not settle user/admin deletion, retention or privacy governance. (full BR-025) | F-S2-04 | S2 proposed | VAL-024 (planned) |

| Product requirement | Complete SRS intent (linked source) | Accountable feature / responsibility | Target sprint | Planned validation |
|---|---|---|---|---|
| BR-026 | Tutor cannot directly edit, delete or withdraw a Slot with an Active Booking; the authorized Booking cancellation must occur first. (full BR-026) | F-S2-05 | S2 proposed | VAL-025 (planned) |
| BR-027 | Tutor may withdraw an own, unoccupied future Slot and create a separate new Slot while preserving withdrawal history. (full BR-027) | F-S2-05 | S2 proposed | VAL-026 (planned) |
| BR-028 | One Customer cannot have overlapping Active Bookings across any Tutors; adjacent appointments do not overlap. (full BR-028) | F-S1-04 | S1 | VAL-004, VAL-011 (planned) |
| BR-029 | `Asia/Bangkok` (UTC+07:00) is the business timezone; authoritative time comes from the server, not a browser or user-supplied timestamp. (full BR-029) | SYS-01 | S1-S3/Lab5+ | VAL-008, VAL-013 (planned) |
| BR-030 | Booking business states are `Booked` and `Cancelled`; `Past` is derived from time, not a third state or evidence of `Completed`/attendance. (full BR-030) | F-S1-05 (shared: F-S2-01/03, F-S3-01) | S1 / S2 proposed / S3 proposed | VAL-013, VAL-015 (planned) |
| BR-031 | Only authorized Tutor gets Appointment Summary counts and lists for Upcoming Booked, Past Booked and Cancelled. Customer gets no Tutor-only summary. (full BR-031) | F-S3-01 | S3 proposed | VAL-028, VAL-029 (planned) |
| BR-032 | Historical withdrawn Slots do not block a new separate overlapping offer; they are not reactivated under the same historical Slot ID. (full BR-032) | F-S2-05 | S2 proposed | VAL-027 (planned) |
| BR-033 | Protected actions require server-enforced authenticated role/ownership checks; anonymous, foreign-record and cross-role operations cannot gain private data or mutation rights. (full BR-033) | F-S1-01 | S1 / S2 proposed / S3 proposed | VAL-001, VAL-002, VAL-036 (planned) |
| BR-034 | Accepted Booking/Slot mutations commit an internally consistent outcome; rejected validations, contention and persistence failures cannot leave partially claimed Slots, duplicate active reservations or false success. The precise locking/constraint scheme is not selected here. (full BR-034) | SYS-01 (shared: F-S1-02/04, F-S2-02/03) | S1 / S2 proposed | VAL-005, VAL-010, VAL-011, VAL-014, VAL-020, VAL-022 (planned) |
| BR-035 | Invalid or nonfuture Slot proposals and attempts to book past, occupied or ineligible offers are rejected without changing committed records; rules beyond confirmed time policies cannot be fabricated. (full BR-035) | F-S1-02 | S1 | VAL-004, VAL-006, VAL-014 (planned) |
| NFR-001 | Authorization: every enumerated anonymous, forbidden-role, foreign-Customer and foreign-Tutor protected API path must reject or filter without private payload disclosure. Measure zero unauthorized record disclosure in seeded negative cases. (full NFR-001) | F-S1-01 (auth foundation; role/ownership regression for each new S2/S3 endpoint) | S1 / S2 proposed / S3 proposed | VAL-002, VAL-036 (planned; repeat authorization regression as endpoints expand) |
| NFR-002 | Credential security: with locally managed passwords, store adaptive salted hashes, not plaintext; tracked repository content contains no real credentials. Verify using test DB inspection and secret/config review. (full NFR-002) | F-S1-01 | S1 | VAL-034 (planned) |
| NFR-003 | Durability: an accepted Slot/Booking and its authorized view must persist after browser refresh and application-process restart against the same data store; no in-memory-only persistence. (full NFR-003) | SYS-01 | S1 / S2 proposed / S3 proposed | VAL-007, VAL-031 (planned) |
| NFR-004 | Concurrent conflict integrity: all three real-DB races must preserve BR-001/006/028, regardless of interleaving; a 20-attempt same-Slot stress burst and a 10-attempt same-Customer burst are proposed test sizes, not approved business capacity limits. (full NFR-004) | SYS-01 (shared: F-S1-02, F-S1-04) | S1 | VAL-005, VAL-010, VAL-011 (planned) |

| Product requirement | Complete SRS intent (linked source) | Accountable feature / responsibility | Target sprint | Planned validation |
|---|---|---|---|---|
| NFR-005 | Atomic consistency: accepted cancellation/reschedule/Booking/withdrawal changes all required records together; deliberate persistence failures leave the prior committed state and no false confirmation. (full NFR-005) | SYS-01 | S1 / S2 proposed / S3 proposed | VAL-014, VAL-020, VAL-022 (planned) |
| NFR-006 | Time correctness: cutoff checks use server-authoritative instants; accept exact 60:00 or 30:00 boundaries as applicable, reject just-below; Bangkok calendar/hour remains stable for a non-Bangkok browser. (full NFR-006) | SYS-01 | S1 / S2 proposed / S3 proposed | VAL-008, VAL-009, VAL-013, VAL-015, VAL-018, VAL-021 (planned) |
| NFR-007 | Data minimization: protected Booking, reason, notification and report responses do not expose third-party identity, cancellation reason, credentials or arbitrary private schedule fields. Review response bodies and negative payloads, not UI controls only. (full NFR-007) | SYS-01 (shared: F-S1-03/05, F-S2-04, F-S3-01) | S1 / S2 proposed / S3 proposed | VAL-006, VAL-012, VAL-023, VAL-029, VAL-036 (planned) |
| NFR-008 | Retry safety: repeated/uncertain-response requests cannot violate exclusivity, successful reschedule quota or atomic history. Whether retries return the original success response and any token format/retention are open. (full NFR-008) | F-S1-04 (S1 Booking retry; AC-S1-29 / VC/TEST-S1-38); F-S2-02 (S2 proposed Reschedule retry) | S1 / S2 proposed | VAL-030 (S1), VAL-020 (S2 proposed; planned) |
| NFR-009 | Keyboard usability (PROPOSED): complete login, availability, Booking and own-detail flows by keyboard with visible focus on primary controls; record manual checklist, browser and failures. (full NFR-009) | SYS-01 | S1-S3/Lab5+ | VAL-033 (planned) |
| NFR-010 | Local response time (PROPOSED): p95 availability and own-Booking-detail requests at or below 2.0 s, each measured over at least 50 warm-up-excluded requests with documented hardware, fixture size and database. (full NFR-010) | SYS-01 | S1-S3/Lab5+ | VAL-032 (planned) |
| NFR-011 | Change traceability: each implemented requirement must identify source Q/GW/D1, accountable feature/Issue, reviewed contract, planned verification and release evidence; changes to Q rules need recorded stakeholder approval. (full NFR-011) | SYS-01 | S1-S3/Lab5+ | VAL-031 (planned) |
| NFR-012 | Reproducibility: engineering evidence must identify code version, environment/setup, DB/seed preparation, test commands and real pass/fail/skip results; mere presence of tests is not a pass. (full NFR-012) | SYS-01 | S1-S3/Lab5+ | VAL-031 (planned) |
| NFR-013 | Deployment readiness: the selected architecture must support container packaging and durable GCP deployment, with build/tests on relevant PRs and repeatable accepted release from `main` after Lab 5. No cloud success is asserted at D1. (full NFR-013) | SYS-01 | S1-S3/Lab5+ | VAL-035 (planned) |
| NFR-014 | Notice durability: a Tutor-cancellation notice remains retrievable after being read and is not removed solely by age; additional retention/deletion rights await owner decision. (full NFR-014) | F-S2-04 | S2 proposed | VAL-024 (planned) |
| NFR-015 | Safe diagnostics: response errors expose no credentials, session tokens, protected reason or internal stack traces; operational logs must avoid secrets and preserve enough non-sensitive context to investigate failed mutations. Exact logging fields/retention are engineering decisions. (full NFR-015) | SYS-01 | S1 / S2 proposed / S3 proposed | VAL-034, VAL-036 (planned) |
| NFR-016 | Reporting correctness: for every defined Tutor Summary category, count must equal its corresponding accessible row set under the same time/state predicates; no completion is inferred from elapsed time. Treatment of in-progress sessions remains open. (full NFR-016) | F-S3-01 | S3 proposed | VAL-028, VAL-029 (planned) |

## Q01–Q32 accountability

Confirmed meanings and full Q-to-FR/BR/VAL crosswalk remain in SRS §12.2.

| Decision | Owner | Sprint |
|---|---|---|
| Q01 | F-S1-04 | S1 |
| Q02 | F-S1-01 | S1 |
| Q03 | F-S1-02 | S1 |
| Q04 | F-S1-02 | S1 |
| Q05 | F-S1-04 | S1 |
| Q06 | F-S1-02 | S1 |
| Q07 | F-S2-01 | S2 proposed |
| Q08 | F-S2-01 | S2 proposed |
| Q09 | F-S2-02 | S2 proposed |
| Q10 | F-S2-02 | S2 proposed |
| Q11 | F-S2-02 | S2 proposed |
| Q12 | F-S2-02 | S2 proposed |
| Q13 | F-S2-02 | S2 proposed |
| Q14 | F-S2-02 | S2 proposed |
| Q15 | F-S2-02 | S2 proposed |
| Q16 | F-S2-02 | S2 proposed |
| Q17 | F-S2-03 | S2 proposed |
| Q18 | F-S2-03 | S2 proposed |
| Q19 | F-S2-03 | S2 proposed |
| Q20 | F-S2-03 | S2 proposed |
| Q21 | F-S2-04 | S2 proposed |
| Q22 | F-S2-04 | S2 proposed |
| Q23 | F-S2-04 | S2 proposed |
| Q24 | F-S2-04 | S2 proposed |
| Q25 | F-S2-04 | S2 proposed |
| Q26 | F-S2-05 | S2 proposed |
| Q27 | F-S2-05 | S2 proposed |
| Q28 | F-S1-04 | S1 |
| Q29 | SYS-01 | S1-S3/Lab5+ |
| Q30 | F-S1-05 (Booked/Past); F-S2-01 and F-S2-03 (Cancelled); F-S3-01 (summary/report) | S1 / S2 proposed / S3 proposed |
| Q31 | F-S3-01 | S3 proposed |
| Q32 | F-S2-05 | S2 proposed |

## Sprint 1 acceptance and test mapping

All 35 AC and all 39 VC/TEST identifiers below are **planned evidence anchors, not executed results**. IDs, scenarios and expected outcomes are taken from requirements.md §9 and §13; this document only assigns feature ownership. Shared entries do not dilute primary accountability.

### Acceptance criteria: AC-S1-01..35

| AC ID | Primary owner | Other impacted owner | Baseline scenario and expected result | Planned VC reference |
|---|---|---|---|---|
| AC-S1-01 | F-S1-01 | — | Existing valid Customer credentials — Authenticated principal is Customer; user sees correct own identity/role | VC-01/03 (planned) |
| AC-S1-02 | F-S1-01 | — | Existing valid Tutor credentials — Authenticated principal is Tutor; own-schedule operations are available | VC-01/03 (planned) |
| AC-S1-03 | F-S1-01 | — | Invalid password or unknown credentials — Access denied; no protected identity/session returned | VC-02 (planned) |
| AC-S1-04 | F-S1-01 | — | Authenticated user — Protected action rejected according to documented session lifecycle | VC-04 (planned) |
| AC-S1-05 | F-S1-01 | — | Unauthenticated browser or caller — No operation granted and no private payload disclosed | VC-05 (planned) |
| AC-S1-06 | F-S1-01 | — | Authenticated Customer — Backend denies request; Tutor schedule unchanged | VC-06 (planned) |
| AC-S1-07 | F-S1-01 | F-S1-05 | Tutor A and B have different schedules — No protected records or writes under B's identity | VC-07/31 (planned) |
| AC-S1-08 | F-S1-02 | — | Own authorized Tutor schedule; valid future Bangkok start — Exactly one 60-minute offered Slot is persisted and available on schedule refresh | VC-08/14 (planned) |
| AC-S1-09 | F-S1-02 | — | Same Tutor offers 13:00–14:00 — New Slot rejected, existing Slot unchanged | VC-09 (planned) |
| AC-S1-10 | F-S1-02 | — | Same Tutor offers 13:00–14:00 — Adjacent Slot allowed by non-overlap rule, subject to independent validity | VC-10 (planned) |
| AC-S1-11 | F-S1-02 | — | Tutor A offers 13:00–14:00 — Different Tutor offer permitted | VC-11 (planned) |
| AC-S1-12 | F-S1-02 | — | Invalid or past date/start — No invalid Slot persisted, no collateral mutation | VC-12 (planned) |
| AC-S1-13 | F-S1-02 | — | Same Tutor proposes two overlapping Slot writes concurrently — Database never contains two overlapping currently offered Slots for that Tutor | VC-37 (planned) |
| AC-S1-14 | F-S1-02 | F-S1-03 | Browser timezone is not Bangkok — Same intended Bangkok appointment date and hour displayed | VC-13 (planned) |

| AC ID | Primary owner | Other impacted owner | Baseline scenario and expected result | Planned VC reference |
|---|---|---|---|---|
| AC-S1-15 | F-S1-03 | — | Customer logged in; eligible offered Slot exists — Selectable Tutor and Bangkok appointment times shown without private other-Customer details | VC-15 (planned) |
| AC-S1-16 | F-S1-03 | — | Offered Slot occupied or inside Q05 cutoff — Slot is not selectable as bookable and never reveals its Customer; proposed default: show only currently bookable offers, pending the reviewed UI contract in TBD-S1-04 | VC-15/22 (planned) |
| AC-S1-17 | F-S1-03 | — | Displayed offer becomes ineligible before submission — Backend rechecks and rejects; UI does not report a successful Booking | VC-22 (planned) |
| AC-S1-18 | F-S1-03 | — | Device locale is another timezone — Bangkok time meaning does not drift with device timezone | VC-13/15 (planned) |
| AC-S1-19 | F-S1-04 | — | Eligible unoccupied Slot, Customer logged in without overlapping Booking — One Booked record is committed with correct Customer, Tutor and Slot identifiers | VC-16 (planned) |
| AC-S1-20 | F-S1-04 | — | Slot begins 15:00; backend `T_elig` is exactly 14:00:00 — Exact 60-minute cutoff accepted if all other checks pass and transaction subsequently commits | VC-17 (planned) |
| AC-S1-21 | F-S1-04 | — | Slot begins 15:00; backend `T_elig` is 14:00:01 — Less-than-60-minute cutoff rejected, no Booking or occupation | VC-18 (planned) |
| AC-S1-22 | F-S1-04 | — | Customer A owns active Booking on Slot X — Second request rejected, first Booking preserved | VC-19 (planned) |
| AC-S1-23 | F-S1-04 | — | Customer holds Tutor A 13:00–14:00 — Reject overlapping appointment even across Tutors | VC-20 (planned) |
| AC-S1-24 | F-S1-04 | — | Customer holds an interval ending 14:00 — Adjacency itself not blocked; other checks still apply | VC-21 (planned) |
| AC-S1-25 | F-S1-04 | — | Two Customers simultaneously request one eligible Slot — At most one committed Active Booking; no false second success | VC-25 (planned) |
| AC-S1-26 | F-S1-04 | — | Same Customer concurrently requests distinct overlapping Tutor Slots — No two overlapping Active Bookings committed for Customer | VC-26 (planned) |
| AC-S1-27 | F-S1-04 | F-S1-02 | Previously eligible Slot becomes invalid/occupied or persistence fails — No phantom success, partial Booking or inconsistent occupied state | VC-22/27/33 (planned) |
| AC-S1-28 | F-S1-04 | F-S1-01 | Customer alters request body to impersonate other identity/Tutor — Owner derived from trusted session; Tutor from actual Slot, not supplied roles | VC-24 (planned) |
| AC-S1-29 | F-S1-04 | — | Customer repeats request while first outcome might be unknown — Exclusivity and Customer-overlap invariants hold; exact retry response remains contract TBD | VC-38 (planned) |
| AC-S1-30 | F-S1-05 | — | Customer already has a committed Booking — Correct Booking identity, Tutor, Bangkok interval and Booked status | VC-28 (planned) |

| AC ID | Primary owner | Other impacted owner | Baseline scenario and expected result | Planned VC reference |
|---|---|---|---|---|
| AC-S1-31 | F-S1-05 | — | Customer A has Booking; Customer B knows its ID — No protected Booking information disclosed | VC-29 (planned) |
| AC-S1-32 | F-S1-05 | — | Tutor owns current Booking schedule — Authorized Booking visible on own schedule only | VC-30 (planned) |
| AC-S1-33 | F-S1-05 | — | Tutor B knows Tutor A schedule ID — No protected foreign Tutor Booking disclosed | VC-31 (planned) |
| AC-S1-34 | F-S1-05 | — | Booked 13:00–14:00 appointment now ended — Booking still Booked; may show Past; no Completed/attendance assertion | VC-32 (planned) |
| AC-S1-35 | F-S1-04 | — | Slot starts 15:00; Booking HTTP request reaches server at 13:59:59 but waits for contention until final transactional `T_elig` is 14:00:01 — Reject as less than 60 minutes remaining, preserve Slot and all previously committed Bookings, and do not report success merely because HTTP arrival preceded the cutoff | VC-39 (planned) |

### Verification cases: VC/TEST-S1-01..39

| VC / TEST ID | Primary owner | Other impacted owner | Baseline scenario and expected result | Status |
|---|---|---|---|---|
| VC-S1-01/TEST-S1-01 | F-S1-01 | — | Existing Customer and Tutor demo credentials → each logs in — Correct own identity/role; no cross-role grant | Planned, not run |
| VC-S1-02/TEST-S1-02 | F-S1-01 | — | Invalid password → login attempt — Authentication refused; no valid session/identity exposed | Planned, not run |
| VC-S1-03/TEST-S1-03 | F-S1-01 | — | Logged-in user → current identity query — Authenticated user's own ID and role, not arbitrary submitted identity | Planned, not run |
| VC-S1-04/TEST-S1-04 | F-S1-01 | — | Logged-in user → logout → reuse prior access — Protected access rejected according to chosen session lifecycle | Planned, not run |
| VC-S1-05/TEST-S1-05 | F-S1-01 | — | Anonymous caller → private Booking / create Slot / book — All protected actions denied without protected data | Planned, not run |
| VC-S1-06/TEST-S1-06 | F-S1-01 | — | Customer → attempts Tutor-only create action — Rejected by backend, even when request is crafted manually | Planned, not run |
| VC-S1-07/TEST-S1-07 | F-S1-01 | — | Tutor A → attempts to create/view private schedule of Tutor B — Access rejected or B's records absent; A's own schedule unaffected | Planned, not run |
| VC-S1-08/TEST-S1-08 | F-S1-02 | — | Authorized Tutor; future date → create one Slot — Exactly one offered 60-minute Slot persisted under that Tutor | Planned, not run |
| VC-S1-09/TEST-S1-09 | F-S1-02 | — | Tutor's offered Slot 13:00–14:00 → create 13:30–14:30 — Reject overlap; old Slot unchanged, no duplicate offer | Planned, not run |

| VC / TEST ID | Primary owner | Other impacted owner | Baseline scenario and expected result | Status |
|---|---|---|---|---|
| VC-S1-10/TEST-S1-10 | F-S1-02 | — | Tutor's offered Slot 13:00–14:00 → create 14:00–15:00 — Overlap rule permits adjacency; other validity checks remain | Planned, not run |
| VC-S1-11/TEST-S1-11 | F-S1-02 | — | Tutor A offers 13:00–14:00 → Tutor B creates same time — Allowed as distinct Tutor offer if valid | Planned, not run |
| VC-S1-12/TEST-S1-12 | F-S1-02 | — | Proposed Slot starts in the past/invalid → Tutor submits — Reject with no stored Slot or collateral mutation | Planned, not run |
| VC-S1-13/TEST-S1-13 | F-S1-02 | F-S1-03 | Time shown by browser in another timezone → create/check Bangkok Slot — Tutor and Customer see same intended Bangkok appointment time | Planned, not run |
| VC-S1-14/TEST-S1-14 | F-S1-02 | — | Tutor owns offered Slot → opens schedule after refresh — Exact Slot and correct offered/occupied state still visible | Planned, not run |
| VC-S1-15/TEST-S1-15 | F-S1-03 | — | Customer logged in; eligible future offered Slot → browse — Tutor and time identifiable; no other Customer's private details exposed | Planned, not run |
| VC-S1-16/TEST-S1-16 | F-S1-04 | — | Eligible unoccupied Slot → Customer requests Booking — One persisted Booking, state Booked, own Customer and selected Tutor/Slot | Planned, not run |
| VC-S1-17/TEST-S1-17 | F-S1-04 | — | Slot at 15:00, backend `T_elig` is 14:00:00 — Exactly 60-minute Q05 lead time passes if otherwise valid; later commit does not retroactively invalidate a passing checked write | Planned, not run |
| VC-S1-18/TEST-S1-18 | F-S1-04 | — | Slot at 15:00, backend `T_elig` is 14:00:01 — Q05 lead time fails; no Booking/occupation | Planned, not run |
| VC-S1-19/TEST-S1-19 | F-S1-04 | — | Offered Slot already occupied → another Customer books it — Reject; previous Booking preserved and only one active claim remains | Planned, not run |
| VC-S1-20/TEST-S1-20 | F-S1-04 | — | Customer holds 13:00–14:00 Tutor A → books 13:30–14:30 Tutor B — Reject cross-Tutor Customer overlap with no second Booking | Planned, not run |
| VC-S1-21/TEST-S1-21 | F-S1-04 | — | Customer holds 13:00–14:00 → requests 14:00–15:00 — Customer-overlap check permits adjacent interval, subject to lead time | Planned, not run |
| VC-S1-22/TEST-S1-22 | F-S1-04 | F-S1-03 | Selected Slot was eligible at browse but is taken/too soon by submission — Backend rejects stale selection; no false success | Planned, not run |
| VC-S1-23/TEST-S1-23 | F-S1-04 | F-S1-01 | Invalid/missing/past Slot or unauthorized actor → booking attempt — Reject without claimed Slot or private data disclosure | Planned, not run |
| VC-S1-24/TEST-S1-24 | F-S1-04 | F-S1-01 | Customer alters client-supplied user/Tutor ownership IDs — Persist Booking only for authenticated Customer and actual Slot Tutor, or reject | Planned, not run |
| VC-S1-25/TEST-S1-25 | F-S1-04 | — | Two distinct Customers submit concurrently for same eligible exclusive Slot — At most one committed Active Booking; other gets non-success; DB invariant holds | Planned, not run |

| VC / TEST ID | Primary owner | Other impacted owner | Baseline scenario and expected result | Status |
|---|---|---|---|---|
| VC-S1-26/TEST-S1-26 | F-S1-04 | — | One Customer submits concurrently for distinct overlapping eligible Slots of two Tutors — No two overlapping Active Bookings commit; no partial losing claim | Planned, not run |
| VC-S1-27/TEST-S1-27 | F-S1-04 | — | Persistence failure injected before Booking transaction finishes — No false success, no committed Booking or partial occupied Slot | Planned, not run |
| VC-S1-28/TEST-S1-28 | F-S1-05 | — | Customer creates successful Booking → refresh/restart app with same DB — Own Booking and identity/time/state retrievable unchanged | Planned, not run |
| VC-S1-29/TEST-S1-29 | F-S1-05 | — | Customer B knows Customer A's Booking ID → tries detail/list — Private Booking content not revealed | Planned, not run |
| VC-S1-30/TEST-S1-30 | F-S1-05 | — | Tutor A → inspect own schedule with Booking — Correct assigned Booking visible without exposing another Tutor's protected records | Planned, not run |
| VC-S1-31/TEST-S1-31 | F-S1-05 | — | Tutor B knows Tutor A's schedule/Booking identifiers → read attempt — Access denied/filtered; Tutor A records remain private | Planned, not run |
| VC-S1-32/TEST-S1-32 | F-S1-05 | — | Booking interval fully elapsed, no cancellation → open Booking — Business state remains Booked; may show Past; never Completed or assumed attended | Planned, not run |
| VC-S1-33/TEST-S1-33 | F-S1-04 | — | User submits failed/invalid request → reopen respective views — No new phantom Booking, no changed Slot occupancy from failed attempt | Planned, not run |
| VC-S1-34/TEST-S1-34 | SYS-01 | F-S1-01/02/03/04/05 | Real app boot and seed setup → complete J-S1-01 then J-S1-02 through UI and DB — Full verified workflow, repeatable commands and actual test results recorded later | Planned, not run |
| VC-S1-35/TEST-S1-35 | SYS-01 | F-S1-01 | Test invalid access and inspect tracked env/config — No plaintext stored passwords/secrets and no private-data leaks | Planned, not run |
| VC-S1-36/TEST-S1-36 | SYS-01 | F-S1-03/05 | Benchmark local availability/details and keyboard-only walk-through — Record measurements/checklist; compare with proposed, not approved, UX/performance targets | Planned, not run |
| VC-S1-37/TEST-S1-37 | F-S1-02 | — | Two requests concurrently create overlapping future offered Slots for same Tutor — At most one overlapping offer commits; no partial side effects | Planned, not run |
| VC-S1-38/TEST-S1-38 | F-S1-04 | — | Customer duplicates Booking submission while first outcome is in flight or unknown — At most one Active Booking for a Slot; Customer overlap invariant preserved, response semantics defined later | Planned, not run |
| VC-S1-39/TEST-S1-39 | F-S1-04 | — | For 15:00 Slot, request arrives at 13:59:59 but transaction waits until `T_elig = 14:00:01` before final guarded write — Refuse too-late Booking with no partial occupancy, despite pre-cutoff arrival; use controlled server clock/transaction synchronization, not client timestamps | Planned, not run |

### Three separate real-database race obligations

| Race | Owner | AC and VC/TEST evidence | Must prove |
|---|---|---|---|
| A: same Tutor creates overlapping offered Slots | F-S1-02 | AC-S1-13; VC/TEST-S1-37 | At most one conflicting current offer commits |

| Race | Owner | AC and VC/TEST evidence | Must prove |
|---|---|---|---|
| B: two Customers compete for one exclusive Slot | F-S1-04 | AC-S1-25; VC/TEST-S1-25 | At most one active claim commits, no false success |
| C: one Customer books overlapping Slots with different Tutors | F-S1-04 | AC-S1-26; VC/TEST-S1-26 | No overlapping active Bookings commit for that Customer |

Changes to future-sprint validation or policy proposals require the SRS §13 approval gates. There is no claim that any of the above tests has been run.

### Audit and approval gates

FR: 36/36 assigned; BR: 35/35 assigned; NFR: 16/16 assigned; Q: 32/32 assigned. No silent orphans. SYS-01 owns cross-cutting requirements while relevant features must still satisfy them.

S2/S3 assignments are proposals pending team approval in Issue #12. OD-001..015 remain open or conditional per SRS §13; OD-011/012 instructor Master/Theme unverified, so final sign-off is blocked. Proposed NFR-009/010 are not mandatory thresholds until approved.

Issue #10 PR into sprint1 requires @Tanaboonnnnn peer review; this document neither proves test passes nor grants stakeholder approval.

# Part C: Whole-Product System Software Design Specification (SDS)

## 0. Document control and design authority

| Field | Value |
|---|---|
| Deliverable | CPE334 Deliverable 1, Part C; GitHub Issue #11 |
| Artifact | docs/system-sds.md, design draft v0.1.0, 3 November 2026 |
| Product | One-to-one Tutoring Appointment System (Theme 1: Appointment & Scheduling) |
| Coverage | Whole-product architecture for Sprints 1–3; detailed implementation contracts remain feature-scoped |
| Author / required peer reviewer | @Tanaboonnnnn / @Chxtamos |
| Status | **PROPOSED ENGINEERING DESIGN — pending substantive peer review; NOT instructor-approved or implemented** |
| Intended integration | Issue branch -> reviewed PR into sprint1 -> later separately reviewed sprint1 -> main |
| Repo state inspected | Remote sprint1 at ba577db79ccee6c0f0861b761fb361bbb252b027 (3 Nov 2026); tracked files are AGENTS.md, README.md and docs/*.md; no application scaffold, package manifest, Prisma schema or CI was present |
| Source gates | Final instructor Master and official team Theme 1 allocation remain unverified (SRS OD-011/OD-012); do not infer formal sign-off |

**Order of authority.** An instructor-issued *final* Master/change notice outranks the available draft handout. Until verified, use the reviewed stakeholder decisions Q01–Q32, whole-product SRS, Sprint 1 requirements, feature inventory, traceability, Issue #11 and root AGENTS.md. The documents describe different levels: business rules are normative outcomes; technology choices in this SDS are **engineering proposals awaiting peer approval**, not new stakeholder rules. Preserve all existing IDs and report conflicts before modifying them.

**Boundary.** This file selects a feasible architecture and explains verifiable invariants. It does **not** add app code, create a working API, run database tests, deploy to GCP, or finalize individual endpoint/field validation contracts. Part E Feature SDS/STS must be versioned and peer-reviewed **before** each corresponding feature's code. Sprint 2/3 placement remains proposed until Issue #12 is accepted.

## 1. Design objectives and decisions

The Sprint 1 minimum is a working **browser UI -> authenticated API/service -> durable relational database** slice: login/logout/current user, Tutor publishing individual 60-minute offered Slots, Customer availability discovery and exclusive Booking, authorized Customer/Tutor reads, and the three concurrency invariants. Records survive refresh and restart. Sprint 2 adds cancellation, one-time cross-Tutor rescheduling, withdrawn Slot history and durable private notices; Sprint 3 adds a Tutor-only summary. Payments, attendance confirmation, recurring/bulk Slots, automatic SLA or notifications by email/SMS are **not authorized** by the product baseline.

### 1.1 Engineering decision register

| Decision | Selected design / reason | Trade-off and current approval |
|---|---|---|
| **SD-01** | A TypeScript modular monolith, not microservices: a single Express API exposes bounded identity, scheduling, Booking and future notice/report modules. | Smaller operational and review burden for two students; **proposed for peer approval**. |
| **SD-02** | React 19 + Vite 8, client-side navigation, accessible shared form/list/status components. | No SSR complexity for the accepted workflows; **proposed**. |

| Decision | Selected design / reason | Trade-off and current approval |
|---|---|---|
| **SD-03** | Node.js 24 LTS + npm 11 workspaces with one root lockfile; Express 5, TypeScript 5.9. | Matches the inspected development runtime and supports reproducible builds; **proposed**. |
| **SD-04** | PostgreSQL 18, Prisma 7 with PostgreSQL adapter, versioned SQL migrations; native PostgreSQL range/exclusion constraints supplement ORM checks. | Relational integrity is essential for races A/B/C; raw SQL constraints require review and DB-specific tests; **proposed**. |
| **SD-05** | Keep one immutable 60-minute time interval per Slot. Derive Tutor schedule from owned Slots and Bookings, not a separate writable schedule table. | Avoids drift and unnecessary entity state; a Tutor schedule is a **logical read projection**. |
| **SD-06** | Derive occupancy from an active Booking; do not independently toggle a fragile Slot.isBooked flag. Maintain Slot lifecycle Offered/Withdrawn for later history. | Simplifies atomic cancellation/reschedule and protects historical records; **proposed**. |
| **SD-07** | PostgreSQL unique/exclusion constraints + SERIALIZABLE transactions + deterministic row locks + bounded retries for genuine transaction aborts. | More careful migrations and error handling; selected to prove all three real-DB races. |
| **SD-08** | Use DB clock_timestamp() *after lock contention* at the final guarded eligibility decision, and UTC instants in storage/transport with Asia/Bangkok presentation. | Prevents the Q05 request-arrival-time bug; clock/rounding tests are mandatory. |
| **SD-09** | Local Argon2id password hashes and opaque, server-revocable, cookie-based sessions; roles and record ownership checked by API/service. | Simpler reliable logout than stateless unrevocable tokens; cookie and CSRF safeguards are mandatory. |
| **SD-10** | A single-origin production web/API deployment (API can serve built web assets), durable managed PostgreSQL and managed secrets on GCP later. | Avoids cross-origin cookie/CORS complexity; **planning only** for Lab 5. |
| **SD-11** | Structured JSON errors and response allowlists; generated request IDs, no secrets, stack traces or third-party record details. | Feature SDS specifies exact endpoints/DTOs, not this whole-system overview. |
| **SD-12** | No invented Tutor work hours, look-ahead maximum, start-minute grid, private data visibility or retry-key retention policy. | Unresolved stakeholder choices remain gates OD-001..015, not implicit defaults. |

All SD-01..12 require review in Issue #11's PR. These selections are *decisions proposed for approval*, not evidence of running packages, applied SQL or instructor authorization.


## 1.2 Technology baseline (design pins, not installed app dependencies)

| Layer / tool | Version target | Basis / implementation note |
|---|---|---|
| Node.js / npm | Node 24.x LTS; npm 11.x | Actual inspected machine: v24.14.0 / 11.18.0; choose Node 24 rather than introducing new Node 26 to this project. |
| Frontend | React 19.3.1, Vite 8.3.5, React Router 7.x | Candidate current registry versions checked 3 Nov; Router exact patch determined when installed. |
| API and validation | Express 5.3.0, TypeScript 5.9.3, Zod 4.6.7 | End-to-end TypeScript, validated boundaries; deliberately choose mature TS 5.9 rather than a new major. |
| DB/ORM | PostgreSQL 18.x; prisma, @prisma/client and @prisma/adapter-pg **7.10.1** plus pg | Prisma 7 requires its supported driver-adapter/config path; maintain SQL migrations for exclusions/partial indexes. |
| Credential/session | argon2 0.45.2; Node crypto secure random and SHA-256 for session-token digests | Password hashes use Argon2id with distinct salts; token digests are **not** password hashes. |
| Tests | Vitest 5.1.0, Supertest 7.3.1, Playwright 1.64.1; real PostgreSQL | Versions were read from npm registry; no project test suite currently exists. |
| Local tooling | Git, Docker, PostgreSQL service/container, optional psql | Docker CLI detected (29.9.2); psql CLI was **not found on PATH**. No DB container or running DB was verified. |

**Version discipline:** Record these as *proposed baseline pins*. During the scoped Part E implementation, check real peer-dependency compatibility, resolve patches using npm install, commit package-lock.json, use npm ci thereafter, and update this table only

through an explained reviewed change. Do not claim that a package is installed merely because npm registry reports it. The PostgreSQL 18 target must also be checked against the GCP managed offering and required extensions before Lab 5.

## 2. System architecture and component boundaries




- **UI:** renders navigation and the permitted controls, converts UTC instants for display in Asia/Bangkok, preserves form state on errors. UI checks are usability feedback **not authorization**.
- **Transport/API boundary:** authenticates the session, validates and normalizes input, imposes request/body limits, assigns a correlation ID, calls one application use case, and serializes an explicit data allowlist.
- **Domain/services:** keep time and Booking rules, role/record ownership, mutation transaction boundaries and feature-specific outcomes in one place. A controller must not implement a second inconsistent cutoff check.
- **Persistence:** Prisma Client manages typed access, migration provenance and transactions; reviewed parameterized SQL handles PostgreSQL row locking, constraints and DB-time sampling where required. No in-memory array acts as the source of truth.
- **Future capabilities:** Customer cancellation/reschedule and Tutor withdrawal/notice reuse the Booking service and Slot/Booking constraints. Tutor summary derives count and list from the same authorized query predicates; no independent source of state.

**Boundaries:** anonymous browser -> session-checked API is the primary trust boundary; API -> database uses a least-privileged account. A client-provided customerId, tutorId, user role, Booking owner, current status or cutoff timestamp is **never trusted**. Public Customer availability is a deliberately narrow projection, not the Tutor's restricted full schedule. API and web may be separately built in development but share one origin through the Vite proxy; production can serve prebuilt web assets through the API image.


**Suggested future repository layout** (none of these folders are created by Issue #11):

```
package.json                # private npm workspaces, pinned Node/npm; scripts
package-lock.json           # committed after first install
apps/web/                   # React/Vite, routes, page components, API client
apps/api/src/               # Express controllers, auth, services, DB adapter
apps/api/prisma/            # Prisma schema, versioned migrations, seed
apps/api/prisma.config.ts   # Prisma 7 connection/migration/seed configuration
apps/api/test/              # API, DB-integrity and concurrency tests
docs/                      # product SRS, traceability, System SDS, Feature SDS/STS
```

No separate payment, background-queue, cache, notification-provider or microservice infrastructure is required by Sprint 1.

## 3. Relational domain, ownership and evolution

### 3.1 Entity relationship view




A **Tutor Schedule** is the filtered projection of one Tutor's Slots and the currently assigned Bookings. It is **not** a second mutable appointment record. This keeps Q02 ownership, Q06 overlap and Q31 counts attached to authoritative relations.

### 3.2 Proposed entities and keys

| Entity (stage) | Essential columns / relationships | Validation and persistence invariant |
|---|---|---|
| **User (S1)** | id UUID PK; email with normalized unique index; passwordHash; role Customer/Tutor; isActive; timestamps | Exactly one effective role per account; active account for authentication; role/ownership verified server-side, never from a client body. No self-registration is in scope. |

| Entity (stage) | Essential columns / relationships | Validation and persistence invariant |
|---|---|---|
| **Session (S1)** | id UUID PK; userId FK -> User; unique tokenDigest; createdAt; expiresAt; revokedAt (nullable); optional revocationReason for audit (proposal) | Store digest, not raw cookie token. Logout revokes **presented Session only**; proposed credential reset/compromise handling revokes **all** relevant User sessions. No protected request may use a revoked/expired token or inactive User (OD-005). |
| **Slot (S1 fields, S2 lifecycle)** | id UUID PK; tutorId FK -> User; startsAt and endsAt TIMESTAMPTZ; lifecycle Offered or Withdrawn; createdAt; withdrawnAt nullable | Interval exactly 60 minutes; immutable Tutor/time/ID; offered Slots of one Tutor never overlap; withdrawn Slot never reactivated under the same ID. |
| **Booking (S1 fields, S2 extension)** | id UUID PK; customerId FK -> User; currentSlotId FK -> Slot; startsAt/endsAt current interval snapshot; status Booked or Cancelled; cancellationActor and tutorCancellationReason nullable (S2); timestamps | One active Booking per Slot; one Customer's active windows never overlap; interval copied from locked Slot, never accepted from a client; current Tutor derives from Slot.tutorId. |
| **RescheduleHistory (S2 only)** | id UUID PK; bookingId FK -> Booking **UNIQUE**; old/new Slot IDs and Tutor IDs; old/new intervals; changedAt | Successful change appends exactly one immutable record while retaining Booking ID. Rejected change appends none and uses no quota. |
| **Notification (S2 only)** | id UUID PK; recipientCustomerId FK -> User; bookingId FK -> Booking; kind TutorCancelled; createdAt; readAt nullable | One relevant private notice per successful Tutor cancellation, persisted in the same transaction; readAt never deletes the notice. Reason may be safely projected from owning Booking rather than duplicated. |

- Slot -> Booking is **one-to-many historically**, but **zero-or-one active**. Cancelled Bookings keep their Slot history and no longer occupy it. Slot Offered means **published**, not necessarily free: occupancy is calculated from Booking status Booked.
- Past is a derived display classification for Booked appointments whose **end** is earlier than the evaluation instant; it is **not** a Booking status, and the application must never invent Completed or attendance.
- A Customer cancellation sets Booking Cancelled and leaves its original Slot Offered; another new Booking must still pass Q05 independently. A Tutor cancellation sets Booking Cancelled and original Slot Withdrawn **in one transaction**. Direct withdrawal while an active Booking exists is forbidden.
- On reschedule (S2), retain Booking.id, move currentSlotId and current interval, write history atomically, free the original offered Slot and claim the destination. Rescheduling to a different Tutor is valid when all rules pass. Prior-Tutor historical visibility is **not** assumed (OD-015).
- Optional reporting fields, Tutor profile, teaching subject, room, payment, price or attendance are **not** mandatory and must not be added on invented stakeholder authority.
- FKs ensure stable ownership references; User role cannot be inferred from an arbitrary FK alone, so service authorization additionally validates role/active status. The database user is not granted app-user impersonation rights.

### 3.3 Native PostgreSQL constraints (migration intent, not executed SQL)

Prisma schema alone cannot express the required conditional interval/exclusion guarantees in the chosen design. Part E must keep the following *reviewed migration logic* in a versioned SQL migration, test applying it against a fresh PostgreSQL 18 database, and ensure Prisma-generated migrations **do not drop** these constraints. Actual column names/types must match the implemented schema before applying the snippets.

```
-- Requires btree_gist to compare UUID equality inside GiST exclusions.
CREATE EXTENSION IF NOT EXISTS btree_gist;

ALTER TABLE "Slot"
  ADD CONSTRAINT slot_exactly_one_hour
  CHECK ("endsAt" = "startsAt" + INTERVAL '60 minutes');

ALTER TABLE "Slot"
  ADD CONSTRAINT offered_slot_no_overlap_per_tutor
  EXCLUDE USING gist (
    "tutorId" WITH =,
    tstzrange("startsAt", "endsAt", '[)') WITH &&
  )
  WHERE ("lifecycle" = 'Offered');

-- Both cancelled and rescheduled history may refer to a Slot,
-- but at most one current Booked record may occupy it.
CREATE UNIQUE INDEX booking_one_active_per_slot
  ON "Booking" ("currentSlotId")
  WHERE "status" = 'Booked';

ALTER TABLE "Booking"
  ADD CONSTRAINT booked_customer_no_overlap
  EXCLUDE USING gist (
    "customerId" WITH =,
    tstzrange("startsAt", "endsAt", '[)') WITH &&
  )
  WHERE ("status" = 'Booked');

-- Protect the duplicated current appointment interval from diverging
-- from the immutable selected Slot, including reschedule updates.
ALTER TABLE "Slot"
  ADD CONSTRAINT slot_id_window_unique
  UNIQUE ("id", "startsAt", "endsAt");

ALTER TABLE "Booking"
  ADD CONSTRAINT booking_current_slot_window_fk
  FOREIGN KEY ("currentSlotId", "startsAt", "endsAt")
  REFERENCES "Slot" ("id", "startsAt", "endsAt")
  ON UPDATE RESTRICT;
```

**Migration preconditions:** all identifiers not-null where needed; UUID columns really use UUID; timestamps use TIMESTAMPTZ; enums/columns have the exact quoted values above or their implemented equivalents. Add explicit FK/indexes for customerId, tutorId, currentSlotId and history/notice references, and check nonblank required values in the appropriate feature contract. The database exclusion predicates are **only** for currently Offered Slots and **only** for Booked Bookings: past *Booked* still counts as active, whereas withdrawn historical Slots do not block new distinct offers (Q32). Adjacent half-open intervals never conflict.

The preceding constraints directly enforce **same-Tutor offered overlap** (Race A), **single active owner per Slot** (Race B) and **same-Customer active time overlap** (Race C). They do **not** by themselves enforce the cross-table lifecycle invariant:

**I-L (Q26/Q27/Q32, FR-033/034, BR-026/032/034):** For every committed Booking whose status is Booked, the referenced Slot **must** have lifecycle Offered. Conversely, a committed Withdrawn Slot **must never** have any active Booked Booking. This holds across all application instances, including a direct SQL mutation that bypasses an application service guard. A historical Withdrawn Slot cannot transition back to Offered under the same ID.

**Required database enforcement contract (to implement and prove in the Part E migrations, not executable SQL supplied here):**

1. Install a PostgreSQL **immediate BEFORE INSERT/UPDATE row trigger on Booking** for changes affecting status, currentSlotId or the interval. When the resulting Booking is Booked, lock the referenced Slot row with SELECT … FOR UPDATE (within the writer's transaction), then reject unless lifecycle is Offered, the Slot is still eligible, and the immutable Slot interval matches the Booking. For **new Booking INSERT**, this guard also samples the DB-authoritative Q05 clock *after* required locks, as clarified in §§4 and 7.3. The existing unique/exclusion constraints remain in force. The runtime service must acquire the §7.1 locks **before** changing Booking; the trigger is a final DB guard even when a service is bypassed.
2. Install a PostgreSQL **immediate BEFORE UPDATE lifecycle trigger on Slot**. On Offered -> Withdrawn, the updating transaction already holds the Slot row lock; reject if any Booked Booking references it. On Withdrawn -> Offered, reject unconditionally

(Q32). Do not permit arbitrary changes to Slot ID/Tutor/interval or DELETE of an occupied Slot. For Tutor cancellation, change the Booking to Cancelled **before** withdrawing its Slot within one atomic transaction, after obtaining all locks in §7.1 order.

3. Both trigger paths must use the same serialized Slot row for the target Slot; a competing Booking/withdrawal writer must wait and then re-read lifecycle/occupancy on a fresh transaction view or abort/retry on Serializable serialization failure. Triggers must throw a non-success error so the entire transaction rolls back, not silently repair partial state. The database account used by the API must not have privilege to disable triggers. An unexpected direct SQL writer may deadlock against the documented service lock order; that attempt must abort/retry, **never commit an invalid lifecycle**.
4. **Implementation gate:** Part E must validate actual PostgreSQL trigger firing order, locking, MVCC visibility and Serializable failure behavior with a disposable real DB. If the proposed immediate trigger/locking protocol cannot demonstrate I-L at commit under all tested interleavings, revise the implementation contract (e.g., additional DB serialization/constraint strategy) **before** accepting the feature. Documentation alone does not prove the triggers safe. Do not defer enforcement as optional S2 work: the Booking guard belongs to S1 and the withdrawal guard must exist before S2 withdrawal is enabled.

**Traceable proof:** S1 F-S1-04/STS tests direct SQL attempts to insert a Booked Booking against a Withdrawn Slot once the lifecycle exists; S2 F-S2-05 and F-S2-03/STS test direct withdrawal of an occupied Slot and simultaneous Booking-versus-withdrawal; SYS-01 checks the resulting committed Slot/Booking rows, error response and rollback. See the inter-operation cases in §7.5. Any S1-only migration whose Slot enum does not yet expose Withdrawn must record the planned forward-compatible gate, not claim S2 lifecycle was already tested.

## 4. Time model and business transitions

- **Business timezone:** IANA Asia/Bangkok, UTC+07:00 for all stakeholder-facing date/time calculations and display (BR-029/Q29).
- **Storage/transport:** TIMESTAMPTZ instants in PostgreSQL and RFC 3339 ISO-8601 timestamps with an explicit offset on wire, normalized to UTC Z in JSON responses. Reject timezone-free date-time strings in mutation input. Render with an explicit Asia/Bangkok formatter; browser timezone or clock cannot affect eligibility.
- **Intervals:** half-open [startsAt, endsAt); overlap exactly when a.start < b.end AND b.start < a.end. Exact adjacency is permitted for one Tutor's offers and a Customer's active Bookings (Q06/Q28).
- **Tutor creation:** future 60-minute Slot; do **not** silently apply the **new Booking** 60-minute cutoff to Slot creation; proposed hours, horizon and minute grid stay OD-001..003.
- **New Booking (Q05):** S - T_elig >= **60 min**, equality passes. T_elig is a fresh DB-authoritative instant obtained **inside the transaction after relevant lock/contention waits and immediately before the final guarded write**. It is **not** HTTP arrival time, transaction start time, client time or commit time.
- **Customer cancellation (Q07, S2):** start minus authoritative decision >= **30 min**, equality passes; reopen original Slot but Q05 still applies to later claims.
- **Reschedule (Q10/Q11, S2):** both original appointment and destination start are >= **60 min** away at authoritative decision, equality passes; at most one successful reschedule (Q16).
- **Tutor cancellation (Q18, S2):** start minus authoritative decision >= **60 min**, equality passes; requires meaningful nonblank reason and withdraws Slot.
- **Q30:** status Booked/Cancelled only; Past after interval end is derived, never Completed. How *in-progress* lessons fit the S3 summary is still OD-006.

**Q05 contention example:** 15:00 Slot, request arrives 13:59:59, but waits for a row lock until the authoritative guarded instant is 14:00:01. The request **fails** (59m59s remaining). If the guarded instant is exactly 14:00:00 and all other checks pass, a commit *after* that instant does not itself invalidate eligibility. Always revalidate upon retry of an aborted transaction; do not reuse an earlier T_elig.

**Operational precision (OD-005, F-S1-04):** The authoritative Q05 guard is **inside the PostgreSQL Booking INSERT trigger**, after the relevant User/Customer and Slot locking protocol in §7.1 and before the Booking row can be accepted; a prior HTTP/controller check is only advisory. Every valid mutation path must acquire the same conflict-serialization rows so competing Booking, cancellation and withdrawal operations cannot produce a *new* conflict-capable wait after this guard. PostgreSQL unique/exclusion checks can still wait implicitly if some writer bypasses the expected lock protocol. An implementation must not claim success from a T_elig sampled before such an unaccounted wait: its Part E transaction adapter must demonstrate a **no-post-guard-contention**

**invariant** with real DB tests, or explicitly abort and retry the whole transaction with a fresh DB clock on detecting an unaccounted wait. If detection cannot be proven reliably, the design is **blocked for code acceptance** until an alternative DB guard/serialization strategy is verified. Do not replace this with a blanket commit-time cutoff: SRS Q05 permits a genuinely valid guarded check whose commit happens later. See §7.3 and required barrier case VC/TEST-S1-39 in §7.5.

## 5. Authorization, authentication and data minimization

### 5.1 Server-enforced role and record matrix

Legend: **own** means tied to the authenticated principal/actual entity ownership, **no** means forbidden, **public policy TBD** must not be interpreted as permitted anonymous access. The stage column is the proposed delivery stage, not a claim that code exists.

| Operation | Anonymous | Customer | Tutor/Staff | Stage |
|---|---|---|---|---|
| Submit credentials on login screen | login only | login | login | S1 |
| Get current identity and logout | no | own | own | S1 |
| Publish/read Tutor's restricted Slots/schedule | no | no | own Tutor schedule only | S1 |
| Discover narrow availability | **no unless approved** | authenticated, privacy-filtered | no Customer privilege by Tutor role | S1 |
| Book an eligible offered Slot | no | as authenticated Customer | no | S1 |
| Read private Customer Booking list/detail | no | owned Bookings only | no global Customer lookup | S1 |
| Read Tutor's attached Booking schedule | no | no | own authorized Tutor schedule only | S1 |
| Cancel or reschedule Customer Booking | no | owned eligible Booking only | no via Customer route | S2 |
| Tutor-cancel assigned Booking with reason | no | no | currently assigned Tutor only | S2 |
| Withdraw unoccupied future Offered Slot | no | no | owner Tutor, **no** if active Booking | S2 |
| Read private cancellation notice/reason | no | addressed Customer / owned cancelled Booking only | no unrelated record or prior-Tutor privilege | S2 |
| Tutor Summary counts and lists | no | no | own Tutor scope only | S3 |
| Any foreign Customer/foreign Tutor record | no | no | no | all |

**Every record query is scoped on the server** by session principal + actual customerId/Slot.tutorId, including nested detail IDs, list filters, pagination, exports (if ever approved), and error branches. For Tutor reads join the Booking's current Slot to its actual Tutor; do not grant global Customer visibility. For historical cross-Tutor movement, keep OD-015 closed-by-explicit-decision **before** revealing anything to a former Tutor. Frontend hiding of controls cannot substitute for API checks.

### 5.2 Credential and session contract proposal (OD-005 gate)

1. **Accounts:** pre-provisioned Customer/Tutor accounts for Sprint 1. Validate a canonicalized, uniquely indexed email; use Argon2id with unique salt and configurable reviewed work factors. Never store plaintext passwords, seed shared known production passwords, expose hash fields in JSON or log credentials.
2. **Login:** validate input and account active state, verify Argon2id hash, issue a cryptographically random **at least 256-bit opaque session token** (not a predictable UUID). Persist only a SHA-256 digest with userId, creation, expiration and revocation state. Send raw token only via HttpOnly cookie.

3. **Cookie:** Secure, HttpOnly, SameSite=Lax, Path=/, no Domain in HTTPS production. A non-Secure local-development exception may be used **only** for localhost HTTP and never in production; document the local cookie name/behavior in F-S1-01.
4. **Expiry: OD-005 candidate policy, NOT approved:** eight-hour absolute expiry from createdAt, with no implicit refresh; a protected request checks token digest, expiresAt > server time, revokedAt IS NULL, User.isActive and effective role against persisted state on each request. An expired cookie never restores access, even if the browser retains it.
5. **Revocation and replacement policy (OD-005 proposal; approval required in F-S1-01):** a normal **login** creates one new Session and leaves other valid Sessions unchanged (no hidden rotation); **logout** transactionally revokes only the Session presented by the cookie and acknowledges completion/clears that cookie **after DB commit**. If optional explicit **session rotation** is added later, revoke the old Session and create its replacement in **one DB transaction**, then issue the new cookie only after successful commit; an old token must never work after rotation. A **password/credential change** (not an S1 feature) is proposed to revoke *all* prior Sessions for that User and create one replacement atomically if the authenticated change succeeds. An authorized **compromise response** (not an S1 feature) would revoke *all* Sessions without implicitly creating a new token. **User deactivation** (future administrative action) must deny every token immediately on the next protected request by User.isActive check and should revoke all User Sessions in the same transaction as deactivation. No password-change, compromise or administrative UI/API is authorized by this SDS.
6. **Atomicity/failure semantics:** any failed logout update or optional rotation/change transaction is a non-success, not a claim of revoked/issued state; do not deliver a new session cookie until its persisted record commits. Logout is idempotently safe for a previously revoked presented token (never grants access). Unknown network outcome is reconciled by checking current session validity rather than assuming rollback. Exact TTL, all-session revocation triggers, CSRF-token format and rate limiting remain **OD-005** engineering decisions subject to peer approval.
7. **Browser safeguards:** same-origin production; CSRF token tied to the session plus server Origin/Referer checks for cookie-authenticated mutation routes. Enforce HTTPS and validate reverse-proxy trust configuration. No auth token in browser localStorage or client-controlled role claims.
8. **Failure handling:** use non-enumerating login errors, input size limits and bounded login-attempt protections; specific rate limits/password policy and expiry/refresh decisions require F-S1-01 review under OD-005. Authenticated foreign-record errors disclose no private payload.

**Proposed auth negative-test matrix (F-S1-01 STS, VAL-001/002/034/036):**

| Precondition / action | Expected persisted state and protected API result |
|---|---|
| Login twice from different browsers (normal login) | Two independent valid Sessions (unless future approved policy changes); logging out one does not revoke the other. |
| Logout with cookie A, then reuse A | Session A revoked in DB after successful logout transaction; stale A denied on /current-user and every protected resource; cookie B from independent login remains valid. |
| Optional rotation or successful credential change (future) | One atomic replacement and old-token revocation for rotation, or all old Sessions revoked for credential change; every old cookie denied and only committed new cookie accepted. Inject failure and assert no partially delivered replacement. |
| Authorized compromise revoke-all (future) | All existing Sessions invalid, no fresh Session created implicitly; old cookies denied. |
| Deactivate User (future) while a session exists | A protected API call made after deactivation denies access even if revokedAt was not yet observed; deactivation and bulk revocation tested atomically when implemented. |
| Now >= expiresAt, manually replay still-present cookie | 401/non-success and no protected fields; subsequent login requires fresh valid credentials, not implicit renewal. |
| Invalid/unknown credentials, wrong role, forged owner ID, invalid CSRF or revoked Session | Sanitized non-success without protected payload, credential enumeration, session token or stack trace. |

These are **planned API and persistence tests**, not executed results. Explicit test fixtures and error status mapping belong to F-S1-01 Feature SDS/STS; the eight-hour expiration, bulk invalidation and future rotation behaviors are proposed OD-005 choices, not confirmed stakeholder policy.

### 5.3 Data exposure contract

- **Customer availability:** only an approved safe Tutor label/ID, Slot ID and UTC interval, plus agreed availability indication; **never** another Customer's Booking, email/phone, cancellation reason or full restricted schedule.
- **Customer own Booking:** Booking ID, relevant Tutor/Slot/time, status, and only that Customer's approved history/reason. Cross-customer list/detail guesses reveal no data.
- **Tutor schedule:** only owned Slots and permitted Booking fields. Customer identity display remains unapproved; use the minimum necessary representation and obtain approval in F-S1-05 API/UI contracts.
- **Notice (S2):** only the recipient Customer can reread; reason additionally appears in that Customer's cancelled Booking details. Reading must not delete or automatically age-expire it (Q24/25). Data deletion/retention and prior-Tutor history are open OD-008/015.
- **Logs/errors:** redact cookie, token, password/hash, personal Booking and private reason. Emit non-sensitive correlation IDs and structured failure codes only. No raw SQL errors, internal stack traces or secrets in responses.

## 6. Shared API and UI contracts

### 6.1 Shared API conventions (not feature-specific endpoint signatures)

- Same-origin HTTPS JSON; path prefix proposed /api/v1. Auth operations conceptually cover login, current-user retrieval and logout; Slot/availability/Booking endpoints and exact URL/method combinations are **deferred to the relevant Part E api-spec.md**.
- JSON keys use lowerCamelCase; IDs use opaque UUID strings; instants use RFC 3339 UTC strings with Z. Pagination/ordering defaults, safe Tutor labels and detailed request/response DTOs are **not frozen** here (OD-004/009).
- Validate path, query and JSON bodies with Zod and server checks (types, length/size, ISO offset, 60-minute arithmetic, state and identity). Reject unknown privileged identity/status fields; construct writes from trusted session and locked DB records. Parameterize all SQL.
- On successful *mutations*, only return confirmed committed outcomes; do not imply a Booking exists before commit. Read results may become stale; a displayed Available marker is not a lease or lock.
- Standard candidate response envelope:

```
{
  "data": {
    "id": "server-generated-uuid",
    "startsAt": "2026-11-08T08:00:00.000Z"
  },
  "meta": { "requestId": "opaque-correlation-id" }
}
```

```
{
  "error": {
    "code": "SLOT_UNAVAILABLE",
    "message": "This appointment is no longer available.",
    "requestId": "opaque-correlation-id"
  }
}
```

- **Proposed status vocabulary:** 400 malformed input; 401 no valid session; 403 wrong role without record detail; 404 missing/foreign record when existence would disclose privacy; 409 occupied/stale overlap or rejected conflict; 422 well-formed but invalid field/business condition; 429 rate limit; 500/503 internal or transient persistence failure, sanitized. Exact endpoint-specific mapping and stable error codes belong to Feature SDS/API Spec and tests. Error messages must not reveal whether a foreign Booking exists.
- Use request IDs for tracing. UTC wire timestamps round-trip to Bangkok displays exactly; server determines time comparisons, not the browser. Do not serialize Prisma objects/columns wholesale without response allowlists.

### 6.2 Screen inventory and navigation

| Screen / state | Role and stage | Minimum behavior |
|---|---|---|
| Login / signed-out | Anonymous, S1 | Validated login, generic auth failure, keyboard access and session continuity. |
| Customer availability | Customer, S1 | Tutor + time discovery, loading/empty/no-match/error states, eligibility/refresh indication; bookable-only vs disabled items remains OD-004. |
| Customer Booking confirmation + My Bookings/detail | Customer, S1 | Display only committed Bookings after successful write, own list/detail and accurate Booked/Past; refresh preserves data. |
| Tutor Slot publish and own schedule | Tutor, S1 | Single start input with derived 60-min end, validation/errors, Offered/occupied distinction, own attached Bookings. |
| Customer cancel/reschedule and history | Customer, **S2 proposed** | Cutoffs, one-success quota, retained Booking ID, cross-Tutor selection, no partial confirmation. |
| Tutor cancellation/Slot withdrawal | Tutor, **S2 proposed** | Current assignment/ownership, nonblank reason, distinct cancelled vs withdrawn consequences. |
| In-app notices | Customer, **S2 proposed** | Private read/reread without automatic expiry; no broadcast. |
| Tutor Appointment Summary | Tutor, **S3 proposed** | Matching category counts and lists, correct owner scope; in-progress bucket OD-006. |

**Shared UI conventions:** accessible labeled controls, visible focus, keyboard use, field-level validation plus server error banners, pending/disabled submit state (not a concurrency proof), explicit empty vs no-results states, retry controls for safe reads, confirmation only after committed write, and responsive phone/tablet/desktop layouts. App role navigation is based on current-user API, but API still enforces every permission. Use consistent loading skeletons/spinners, success, stale/conflict, offline, forbidden and not-found states. Avoid silently clearing a form after transient or validation errors; revalidate server-side on resubmit. Proposed performance (p95 <=2.0 s) and keyboard acceptance thresholds are OD-010 and **not approved NFR gates**.

## 7. Transaction protocol and three race proofs

### 7.1 Shared mutation invariants

1. **I-A (Q06):** at most one currently Offered Slot for a Tutor overlaps a given offered interval; one-hour duration, same-Tutor adjacency allowed.
2. **I-B (Q01):** at most one current Booked Booking uses any Slot; a failed attempt leaves no orphan reservation or false success.
3. **I-C (Q28):** one Customer has no overlapping current Booked intervals across Tutors; adjacency allowed.
4. **I-T (Q05/Q29):** time and validity are checked at authoritative post-contention T_elig; exact 60:00 is eligible, 59:59 is not.
5. **I-P (atomic persistence):** all accepted changes are committed together; a rejected, aborted or failed write leaves the previous committed state and non-success response. Past Booked stays Booked.

**Global lock hierarchy for every domain mutation (SD-07 / OD-005):** lock **all affected User principals in ascending UUID order** (including Customer and the currently assigned/selected Tutors), then **all affected Slot rows in ascending UUID order**, then **existing Booking rows in ascending UUID order**. Lock the required principal rows even if the operation seems to need only the Customer or Tutor: this provides a single agreed order across creation, booking, cancellation, reschedule and withdrawal. PostgreSQL Serializable isolation and the constraints/triggers in §3.3 are mandatory backstops, not substitutes for that order.

| Operation | User locks first (ascending UUID) | Slot locks next (ascending UUID) | Booking locks last and guarded change |
|---|---|---|---|
| **Tutor Slot creation (S1)** | Authenticated Tutor | None (new Slot does not yet exist) | None; insert Offered Slot after Tutor lock, validate no overlap at DB constraint |
| **Customer new Booking (S1)** | Authenticated Customer **and selected Slot's actual Tutor** | Selected Offered Slot | No existing Booking required for new claim; read active conflicts after locks, trigger-guarded insert |

| Operation | User locks first (ascending UUID) | Slot locks next (ascending UUID) | Booking locks last and guarded change |
|---|---|---|---|
| **Customer cancellation (S2)** | Booking owner Customer **and current Slot's Tutor** | Current Slot | Current Booking; verify owner/status/cutoff; update to Cancelled, leaving Slot Offered |
| **Customer reschedule (S2)** | Booking owner Customer, **original Tutor and destination Tutor** (deduplicate/sort) | Original and destination Slots, sorted | Current Booking; validate current assignment and Q10/Q11, update same Booking and unique history atomically |
| **Tutor cancellation (S2)** | Current assigned Tutor **and owning Customer** | Current Slot | Current Booking; validate assignment/reason/Q18, set Booking Cancelled **before** withdrawing Slot and inserting private notice in same transaction |
| **Tutor Slot withdrawal (S2)** | Owning Tutor | Target Offered Slot | If active Booking discovered, reject; no direct mutation of an occupied Slot, then withdraw it |

**Non-authoritative discovery pre-read:** Customer cancellation, reschedule and Tutor cancellation need the current Booking's Customer/current Slot/Tutor IDs to know which principal and Slot locks to take; booking and reschedule also need the selected destination's real Tutor. First perform an **unlocked, read-only lookup** of Booking/Slot references for lock-set discovery, *not* as an authorization or business-rule decision. Begin (or restart) a Serializable transaction, lock the complete discovered User set and Slot set in the global order, then lock/re-read the Booking and selected Slot(s). Verify that **all** discovered IDs, current assignments/status, relevant owners and intervals are unchanged. If any membership/assignment changed or a relevant row disappeared, abort and retry from a **fresh discovery** with no locks carried over; never add a missing earlier-order User/Slot lock while holding a later-order Booking lock. Only the post-lock state can authorize the actual write. Locking pre-reads are forbidden as the sole proof of current state. Subsequent triggers lock already-held Slot rows, and nonconforming writers must abort on deadlock/serialization/conflict rather than bypass invariants.

**Part E lock-order proof obligation:** review actual SQL/Prisma query order for **each row of the table**, instrument concurrent transactions that discover changed assignments between pre-read and locked re-read, and demonstrate retries/rollback without partial rows. A missing lock, unconstrained direct SQL writer or unaccounted post-guard wait is a failed proof gate, not an accepted shortcut.

### 7.2 Tutor Slot creation (Race A; F-S1-02)

1. Authenticate a live Tutor and validate candidate start/derived end from the request (no client tutorId authority).
2. Begin one database transaction (proposed Serializable); lock that Tutor principal row. Recheck active Tutor identity, future time and any *approved* calendar constraints.
3. Insert Offered Slot. PostgreSQL's conditional GiST exclusion rejects a same-Tutor overlapping Offered window even under simultaneous writers. Adjacent windows or same-time offers by **different** Tutors are permitted when otherwise valid.
4. Commit, then return success; on exclusion/serialization conflict, roll back and return a controlled non-success unless a bounded full retry can legitimately succeed. Never update a historical Withdrawn Slot to Offered.

**Proof:** Q06, FR-006, BR-006/034, NFR-004, F-S1-02, VAL-005, AC-S1-13, VC/TEST-S1-37. Use a synchronized barrier with overlapping starts; inspect committed Slot rows and verify the loser did not create a partial Slot.

### 7.3 Exclusive Booking (Races B/C and Q05; F-S1-04)

1. Authenticate current Customer and validate request contains a Slot reference, not a spoofable customerId/role/start timestamp.
2. Discover the selected Slot's real Tutor as a **non-authoritative pre-read**. Begin one database transaction with **Serializable isolation** and lock **both Customer and Tutor User rows in ascending UUID order**, followed by the selected Slot row. Revalidate that Slot.tutorId still matches the discovered Tutor and that the Customer remains active; on mismatch abort and restart discovery without adding an out-of-order lock. This serializes same-Customer and same-Tutor write paths under §7.1, not only the selected Slot.
3. Re-read Slot lifecycle Offered, immutable interval, occupancy and the Customer's **all-Tutor** Booked intervals inside the transaction. Compute availability from committed Booking relations, not a stale browser list.

4. Once all conflict-relevant principal/Slot locks are held, perform server-side preliminary validation. For the final authoritative Q05 decision, the **Booking INSERT row trigger** in §3.3 samples PostgreSQL **clock_timestamp() after its required Slot lock**, then evaluates Slot.start - T_elig >= 60 minutes *before accepting the new row*. It uses current locked Offered Slot state and DB-owned interval, not request time or a client field. A preliminary application time check is not T_elig.
5. The shared User/Slot locks and DB trigger prevent ordinary competing writes from introducing a fresh conflict-capable wait *after* T_elig: Race B shares the Slot lock and Race C shares the Customer lock, including with later S2 mutations. If a DB unique/GiST index check nevertheless waits on an unaccounted competing writer, **do not trust the earlier T_elig**. Part E must either prove no such post-guard wait can occur under the actual DB trigger/lock arrangement, or instrument/detect it and abort/retry the complete operation so the new attempt samples a fresh post-contention T_elig. Any attempt that cannot establish this proof is blocked, not marked as a successful Booking. Do not substitute a blanket commit-time time check that would reject an otherwise valid exact-boundary guarded decision.
6. Unique active-slot index blocks a second Customer on the same Slot (B); Customer range exclusion blocks overlapping Booked windows across Tutors (C), including separate application processes. Catch and classify exclusion/unique/serialization errors without treating them as successful claims.
7. Commit the Booking transaction; **only after confirmed commit** send success/Booking ID. A transaction rollback leaves no Booking and does not change occupancy, which is derived from the Booked row.

**Proof B:** Q01, FR-012, BR-001/034; F-S1-04, VAL-010, AC-S1-25 and VC/TEST-S1-25. **Proof C:** Q28, FR-013, BR-028/034; F-S1-04, VAL-011, AC-S1-26 and VC/TEST-S1-26. **Q05 proof:** FR-011, BR-005, VAL-008/009, AC-S1-35 and VC/TEST-S1-39. Force a **synchronized row-lock wait crossing** the exact 60-minute cutoff and assert the trigger's T_elig occurs *after* that wait. Include a second fixture for an unexpected **index/constraint wait** after preliminary validation, prove it cannot silently reuse a stale T_elig, and inspect the committed DB state. Include same-Customer adjacent intervals as permitted control cases. These are verification obligations, not claims of observed DB behavior.

### 7.4 Failure, retry, and later transitions

- **Rollback and retry:** handle known PostgreSQL SQLSTATE 40001 (serialization) and 40P01 (deadlock), including their ORM equivalents (Prisma P2034), by rolling back the **whole** transaction, using bounded jittered retries (**three attempts proposed**), reacquiring locks and **resampling T_elig** every time. A unique violation 23505 or exclusion 23P01 indicating a genuine conflicting offer/Booking is a *business conflict*, not permission to spin until one magically succeeds. Exhausted retries produce sanitized non-success. Do not retry non-idempotent effects outside the transaction.
- **Unknown response after possible commit:** network failure is not evidence of rollback. No blind duplicate success or changed Booking ID. In S1, reconcile through authenticated own-Booking reads and preserve invariants; an optional durable idempotency-key/result registry, payload fingerprint, key lifetime and repeated-response behavior remain **OD-013** to approve in F-S1-04/S2 Feature SDS. Never claim exactly-once delivery without such a contract.
- **Injected DB failure:** fail after validation / between scheduled statements, roll back, verify committed Booking and Slot state unchanged and API does not say success (FR-016/018, BR-034, VAL-014).
- **Stale UI:** an earlier Available card can become occupied, withdrawn or too close to start. Reject gracefully and refresh; frontend reservation indicators do not reserve database rows (FR-009/011).
- **Customer cancellation S2:** discover original Slot/Tutor from Booking only to identify the lock set; lock Customer + Tutor principals (UUID order), original Slot, then Booking. Revalidate ownership/current assignment and Q07 at authoritative transaction decision; set Booking Cancelled atomically. The original Offered Slot becomes unoccupied because occupancy is derived; Q05 still gates any new claim (VAL-015/016).
- **Customer reschedule S2:** discover original and destination Slot/Tutor references as a non-authoritative lock set; lock Customer + both Tutor principals (UUID order), **both** Slots (UUID order), then Booking. Revalidate original assignment, destination ownership, both 60-minute cutoffs and no conflicting other Customer bookings; atomically change currentSlotId + interval and append UNIQUE RescheduleHistory. Keep Booking ID; a failed attempt preserves destination, original and one-success allowance (VAL-017..020). On changed discovered IDs restart the full transaction.
- **Tutor cancellation S2:** discover the current Customer/current Slot only to determine locks; lock both User principals, Slot, then Booking per §7.1 and revalidate currently assigned Tutor, Q18 cutoff and nonblank reason; in one transaction set Booking Cancelled **before** Slot Withdrawn and then persist one private Notification. Failure leaves all three prior states, no notice (VAL-021..024).

- **Tutor withdrawal S2:** lock owning Tutor principal, target Slot, revalidate no active Booking and future Offered status, then withdraw. DB lifecycle trigger independently forbids an occupied withdrawal; no reactivation of historical ID. A new distinct Slot may later overlap that withdrawn historical interval (VAL-025..027).
- **Summary S3:** use a consistent snapshot or equivalent single-query predicate for count and list under the same Tutor/Booking filters; no inferred Completed. In-progress classification is gated (VAL-028/029).

### 7.5 Minimum real-database verification contract

| Case | Real-DB setup / observable committed assertion | Owner |
|---|---|---|
| Race A (VAL-005) | Same Tutor submits overlapping Offered Slot inserts concurrently under a barrier; at most one currently Offered overlap persists; a distinct Tutor's same-time Slot and same-Tutor adjacency may succeed. | F-S1-02 SDS/STS |
| Race B (VAL-010) | Two Customers concurrently book the same valid Slot; exactly one Booked row after both settle; no two success responses or partial state. | F-S1-04 SDS/STS |
| Race C (VAL-011) | One Customer concurrently claims distinct overlapping Slots from two Tutors; never two overlapping Booked rows; adjacent control case allowed. | F-S1-04 SDS/STS |
| **Cutoff after lock wait (VAL-008/009; VC/TEST-S1-39)** | Use a real controlled barrier: start Booking at 60m+ while a competing transaction holds the required Customer/Slot row lock, release after the cutoff, assert the INSERT trigger's T_elig is **after** wait and Booking is rejected; run exact 60:00 control and a forced unexpected index wait case to reject stale-time success or block design acceptance until a proven retry strategy exists. Inspect committed rows and timestamps from the DB, not the request-arrival clock. | F-S1-04 SDS/STS; SYS-01 gate |
| Persistence fault (VAL-014) | Inject post-validation DB write/commit failure; verify no partial committed Booking, false success or Slot occupancy. | F-S1-04 + SYS-01 |
| Auth/privacy (VAL-002/034/036) | Anonymous, wrong-role, foreign-Booking, foreign-Tutor, client-supplied IDs, revoked session; inspect entire payload, not only UI. | F-S1-01/05 + SYS-01 |
| Durability (VAL-007/031) | Create Slot and Booking through actual UI/API/DB; restart app against same DB; retrieve correct owner-scoped state. | F-S1-02/04/05 + SYS-01 |
| **Booking vs Slot withdrawal (S2, Q26/27; VAL-025/026 plus VAL-014)** | Start an eligible new Booking and unoccupied-Slot withdrawal concurrently with synchronized barrier; force both winning orders. Final state must be **(Offered + one Booked)** or **(Withdrawn + zero Booked)**, never Withdrawn with a Booked row. Include a direct SQL attempt bypassing the service guard; trigger must reject and rollback without ghost occupancy. | F-S1-04 Booking contract (S1 guard); F-S2-05 withdrawal SDS/STS (S2 execution); SYS-01 |
| **Reschedule vs Tutor cancellation (S2, Q12/13/17/19/21; VAL-020/022/023)** | One Booking is simultaneously moved to a different Tutor and cancelled by its formerly assigned Tutor. Synchronize both orders. Verify same Booking ID, one-or-zero successful RescheduleHistory rows, correct old/new Slot lifecycle, currently authorized Tutor, and **notice/reason only if Tutor cancellation really committed**. Losing operation must leave no partial history, withdrawal or notice. | F-S2-02 + F-S2-03/04 SDS/STS; SYS-01 |
| **Customer cancellation vs new Booking (S2, Q07/08/05; VAL-015/016/010)** | Original customer cancels sufficiently far ahead (>60m) while a second customer claims the same original Slot. Force cancellation-first and contender-first interleavings; at most one active Booked occupant, existing Booking becomes Cancelled only when its transaction commits, Slot remains Offered, and new Booking succeeds **only after** released occupancy and an independent Q05 check. No false double-success or partial status. | F-S2-01 + F-S1-04 Booking regression SDS/STS; SYS-01 |
| Later regression (VAL-015..029) | S2 cancellation/reschedule/notification and S3 count/list rules; verify required constraints and no identity/time/privacy regression. | Corresponding S2/S3 SDS/STS |

Tests must deliberately synchronize competing transactions, inspect **final committed rows**, include a losing contender and fault rollback, and record database version, setup/seed, command, Git SHA, pass/fail/skip counts and evidence. Pure mocks, Promise.all without synchronized interleaving, or HTTP-only checks are **insufficient** for the race obligations. These are **planned tests, NOT executed results**.

## 8. Reproducible local development and future delivery

### 8.1 Proposed scripts and configuration (not yet present)

Use one npm-workspaces root and two application packages. Proposed scripts to add in Part E, not commands claimed to work today:

```
npm ci                      # install exact locked project dependency graph
npm run db:up               # start local PostgreSQL (Docker Compose or existing service)
npm run db:migrate          # local: Prisma migrate dev incl. reviewed SQL constraints
npm run db:seed             # idempotent LOCAL/TEST-only Customer/Tutor fixtures
npm run dev                 # web + API; Vite same-origin /api proxy
npm run typecheck
npm run lint
npm run test:unit
npm run test:api
npm run test:db             # real PG + barriers + committed-row assertions
npm run test:e2e            # real UI/API/DB flow
npm run build
npm run db:migrate:deploy   # later release: reviewed Prisma migrate deploy
```

Document and implement each script before presenting it as runnable. Provide README setup prerequisites (Node 24, npm 11, PostgreSQL 18 or agreed compatible version, Docker optional), exact .env.example placeholders, startup/teardown instructions and fresh DB reset procedure **only for disposable development/test DBs**. Never reset a real or shared database. Use separate TEST_DATABASE_URL, migrations and unique test fixtures to prevent contamination. Seed is **idempotent**, uses only fictional records and does not expose known shared/production account credentials. Tests should use isolated DBs and rollback/cleanup of test fixtures.

### 8.2 Proposed environment variable names (examples, not secrets)

```
NODE_ENV=development
PORT=3000
DATABASE_URL=postgresql://APP_USER:CHANGE_ME@localhost:5432/nuttiew_dev
TEST_DATABASE_URL=postgresql://TEST_USER:CHANGE_ME@localhost:5432/nuttiew_test
SESSION_COOKIE_NAME=nuttiew_session_dev
SESSION_SECRET=GENERATE_A_STRONG_LOCAL_ONLY_SECRET
TRUST_PROXY=false
WEB_ORIGIN=http://localhost:5173
```

All values above are **placeholders**, never deployable credentials. In the proposed opaque-token/digest scheme, a SESSION_SECRET is only required if a separately signed CSRF/session adjunct is approved; do not treat it as a replacement for true random tokens or a reason to store raw sessions. Commit only .env.example and ignore real .env, test output, DB dumps and secrets. Do not place passwords/API keys in sample responses, tests or logs. For deployment use secret management; fail fast when required config is missing. Production cookies require HTTPS, Secure, HttpOnly and a reviewed proxy/host setup.

### 8.3 Database migration and operational readiness

- Create Prisma 7 schema and adapter configuration, include versioned custom SQL for CHECK, partial unique, GiST exclusion and composite FK. Check extension permissions (btree_gist), upgrade compatibility and migration dry-run on a new DB. Use a single migration authority, not Prisma db push on production.
- Index foreign keys/read paths, including Tutor Slots by owner+startsAt, Booking by customer and current slot, and future Notice recipient/time; verify query plans when data size makes it useful. Avoid storing computed Booked/Past or redundant occupancy counters.
- Preserve existing rows as S2/S3 migrations add lifecycle, history and notice features; use additive/default/backfill strategy, then constraints, never destructive drop-and-recreate. Test up/down or safe forward recovery and backup first; rollback a release by correcting forward schema where unsafe to reverse.
- Separate development/test/prod databases and least-privilege accounts. Production migrations run as privileged release step, API uses narrower runtime credentials. Define backup/restore and secret rotation in Lab 5 operations; no retention or uptime SLA invented at D1.

### 8.4 Docker/GCP and CI/CD future design only




- **Lab 5 target:** build a production image with Node 24, compile React assets, serve the same-origin site and Express API in a Cloud Run service, connect to a supported Cloud SQL PostgreSQL major over an authenticated/private connector, use Secret Manager and service identity. Confirm Cloud SQL major/extension support, SQL connection pooling and migration permissions before implementation.
- **CI plan:** on each PR run lockfile install, typecheck, lint, build, unit/API tests, and real-DB integration/concurrency suites with an ephemeral PostgreSQL service and migrations; record explicit status. Deploy only reviewed/accepted main releases; enforce branch protection and no secrets in PR logs.
- **Scale:** Cloud Run instances are stateless and may overlap; PostgreSQL unique/exclusion and serializable transaction invariants must hold **across instances**, not only one Node process. Session state remains in DB, never a single-process memory map. Cap DB pool size for serverless instance multiplication.
- **Current evidence:** no app image, deployed Cloud Run, Cloud SQL, GitHub Actions quality gate or successful execution was created by Issue #11. The course's supplied Lecture 11 material frames Docker/CI/CD/GCP as later Lab 5 work, not an assertion of delivery.

## 9. Requirements-to-design-to-verification traceability

| Design responsibility | Requirement / feature IDs (authoritative in SRS and inventory) | Planned checks and downstream contract |
|---|---|---|
| Auth, session, role/owner boundaries | FR-001..004; BR-002/033; NFR-001/002/015; F-S1-01 | VAL-001/002/034/036; F-S1-01 Feature SDS/STS, session expiry, CSRF, bad roles/ownership |
| Offered 60-minute Slot / Tutor ownership | FR-005..007; BR-003/004/006/029/035; F-S1-02 | VAL-003/004/005; AC-S1-13; VC/TEST-S1-37; migration constraint and Race A |
| Availability and safe Customer projections | FR-008/009; NFR-007; F-S1-03 | VAL-006/009/036; stale/empty/privacy/refresh UI and API |
| Exclusive Booking and time/concurrency | FR-010..013/018; BR-001/005/028/034; NFR-004/005/006/008; F-S1-04 | VAL-007..011/014/030; AC-S1-25/26/35; VC/TEST-S1-25/26/39; Races B/C, T_elig, retry |
| Persisted private Booking and correct status | FR-014..017/019; BR-030; NFR-003/007; F-S1-05 | VAL-012/013/031/036; restart, owner scope, Past not Completed |
| Cross-cutting system ownership | FR-018/019; BR-029/033/034; NFR-003..008/011/012/013/015; SYS-01 | VAL-014/031/034/035/036; migrations, safe error, CI/GCP future plan |
| Customer cancellation | FR-020/021; BR-007/008; F-S2-01 **proposed** | VAL-015/016; Q05 remains independent after reopen |
| Cross-Tutor one-success reschedule | FR-022..027; BR-009..016; F-S2-02 **proposed** | VAL-017..020; same Booking ID, at most one history, atomic cross-Slot movement |
| Tutor cancellation and withdrawal | FR-028..030/033/034; BR-017..020/026/027/032; F-S2-03/05 **proposed** | VAL-021/022/025..027; no occupied withdrawal, reason and distinct ID |
| Private notice and cancellation reason | FR-031/032; BR-021..025; NFR-014; F-S2-04 **proposed** | VAL-023/024/036; read/reread, no age expiry, data minimization |
| Tutor-only summary | FR-035/036; BR-030/031; NFR-016; F-S3-01 **proposed** | VAL-028/029/036; consistent counts/lists, in-progress decision gate |

**Coverage boundary:** All stakeholder decisions Q01–Q32 are represented through BR-001..032 with extra BR-033..035 for instructor/security/integrity, and FR-001..036 / NFR-001..016 remain controlled by SRS. The detailed ID-to-feature/VAL crosswalk is in traceability. This SDS adds design mappings and **does not** redefine or renumber any source requirement. VAL, AC and VC/TEST references above are **planned evidence**, not passed tests. Feature-specific exact test lists and acceptance results must be established in each Part E STS.

## 10. Outstanding gates, review checklist and next authorized work

| Gate | Required disposition before the indicated step |
|---|---|
| OD-001/002/003 | Decide Tutor operating hours/days, maximum horizon and start-minute grid **before F-S1-02 final contract**; do not fabricate restrictions. |
| OD-004 | Approve availability display, safe Tutor labels, field allowlists, sorting/filtering and list behavior **before F-S1-03/05 API/UI contracts**. |
| **OD-005** | Peer-approve stack integration, proposed eight-hour Session TTL/CSRF policy, specific **current-only logout vs all-session credential/compromise revocation**, atomic rotation, precise API errors, DB lifecycle triggers, lock order, post-guard wait treatment and failure handling **before S1 code**. |
| OD-006 | Classify in-progress appointments for Upcoming/Past summary without creating Completed state **before S3 summary contract**. |
| OD-007 | Q32 already **prohibits** reactivation of withdrawn historical Slot; any exception needs *new* stakeholder authority, not a default. |
| OD-008/009 | Privacy retention/deletion and summary count/list snapshot/pagination **before corresponding S2/S3 contracts**. |
| OD-010 | Proposed keyboard/p95 thresholds and DB race stress sample sizes need approved methods/fixtures; not mandatory until approved. |
| **OD-011/012** | Final instructor Master document and formal Theme 1 eligibility **still unverified**, blocking official sign-off; this design may only be reviewed as a draft. |
| **OD-013** | Retry idempotency-key shape/window and unknown-commit reconciliation **before Booking/Reschedule Feature SDS/STS**. |
| OD-014/015 | Meaningful Tutor reason validation and previous-Tutor history visibility **before corresponding S2 design contracts**. |
| Issue #12 | Sprint 2/3 assignment and feasible capacity remain proposed pending peer-reviewed three-sprint plan. |

**Issue #11 review checklist (independent @Chxtamos review required):**

1. Confirm the real repo has no implementation and that this PR changes **only** docs/system-sds.md.
2. Challenge proposed Node/React/Vite/Express/Prisma/Postgres versions and Prisma 7 adapter/migration details; verify reproducible future commands are clearly **not yet executable**.
3. Validate ERD cardinalities, no redundant writable Tutor schedule or occupied flag, immutable 60-minute Slot, FKs, conditional indexes/exclusions and S2 history/notice compatibility.
4. Confirm all three race invariants with DB-executed planned test proof, post-lock Q05 clock semantics, equality/adjoining windows, atomic rollback and bounded retry contract.
5. Confirm anonymous/Customer/Tutor role and **record** enforcement, cookie/token hygiene, CSRF protection, privacy-safe response allowlists and error discipline.
6. Confirm required Q07–Q32 later behavior is represented *without* prematurely exposing Sprint 2/3 endpoints, and OD-001..015 / Master/Theme blockers remain visible.
7. Check source links, consistent IDs, no fabricated test/deployment/approval claims and a substantive GitHub review. An AI self-check is not a teammate approval.

**Exit / handoff:** After a documentation-only diff check and this Issue's scoped review, open a PR from the Issue branch to sprint1, request @Chxtamos and **leave it open**. Only a real teammate's review and an explicitly authorized later merge can satisfy the full Issue DoD. Issue #12 can use this draft for feasibility but cannot claim it is already signed off. Part E should author **versioned feature contracts first**, then implement/test the S1 slice on their own Issue branches.

## 11. References and provenance

- Product authority: Whole-product SRS, Sprint 1 baseline, Feature inventory, Traceability, AGENTS.md, Issue #11.

- Instructor materials cited by the SRS: Group Work Specification v1, **marked draft**, issued 6 October 2026; Deliverable 1 v1 for 8 November 2026. **Authoritative final Master and Theme allocation not verified** (SRS OD-011/012).
- Version support: Node.js releases, Vite supported releases; npm registry version metadata examined 3 November 2026. These justify *proposed* targets, not installed project libraries.
- PostgreSQL 18 CREATE TABLE / exclusion constraints and range types.
- Prisma 7 transaction isolation and retry; implementation must validate compatibility with the **chosen** Prisma 7 adapter and API.
- No test execution, generated migration, package installation or cloud deployment was performed **as part of authoring this specification**.

# Part D: Feasible Three-Sprint Delivery Plan

> **Status: PROPOSED — Issue #12 / Deliverable 1 Part D.** This plan is not a record of feature completion, executed tests, instructor authorization, or accepted release. The team must peer-review dates, capacity and Sprint 2/3 allocations. Product rules Q01–Q32 are controlled by SRS; Sprint 1 identities by requirements; assignments by Feature Inventory, traceability, and architecture by System SDS.

## 1. Document control, authority, scope

| Item | Plan |
|---|---|
| Issue | #12 — D1-04 Part D |
| Owner / peer reviewer | @Chxtamos / @Tanaboonnnnn (independent human review) |
| Product / people | NutTiew one-to-one tutoring appointments; two students |
| Integration / release | Issue `docs/*` or `feature/*` branch → reviewed PR into `sprint1` → separate reviewed release PR into `main` |
| Mandatory Sprint 1 checkpoint | **D1: 8 November 2026, 23:59 Asia/Bangkok** |
| Later checkpoints stated by Issue #12 | **D2: 29 November 2026** (Sprint 2 and evidence of Sprint 3 progress); **completion: 13 December 2026** (Sprint 3) |
| Source limitation | Reviewer-cited Group Work Specification v1, Deliverable 2 v1 and Final Delivery v1 inform these Lab, D2 and final checkpoints. The authoritative final Master and official Theme allocation remain unverified (OD-011/012). |
| Scope | Schedule, responsibilities, interdependencies, test/review outcomes, risks and fallback; **no app implementation, no simulated test pass, no direct edits to `main` / `sprint1`** |

**Baseline:** At planning time `sprint1` contains `AGENTS.md`, `README.md`, `docs/requirements.md`, `docs/srs.md`, `docs/features.md`, `docs/traceability.md`, and `docs/system-sds.md`; no application scaffold is established. A documentation merge is not a working app or a passing test. The team must build a genuine UI → API → durable DB journey in Sprint 1. The concrete stack in the System SDS is **proposed**, not installed/approved: React/Vite, Express/TypeScript/Node, PostgreSQL/Prisma. The Part E feature contracts must validate integration feasibility before writing code.

## 2. Sprint goals and non-negotiable scope

| Sprint | Product scope (stable IDs) | Objective accepted outcome | Planned verification / release |
|---|---|---|---|
| **S1 — D1** | **F-S1-01** Authentication; **F-S1-02** Tutor Slots; **F-S1-03** Availability; **F-S1-04** exclusive Booking; **F-S1-05** protected Booking/Tutor reads; **SYS-01** integrity, privacy, persistence and evidence | Real Customer/Tutor login, logout and current identity; backend role/record checks; future single 60-minute Tutor offers; customer discovery, eligible booking, durable own records; Q28 cross-Tutor overlap prevented; all three DB races and Bangkok clock boundary handled; UI/API/DB function end-to-end | VAL-001..014 (especially **Race A VAL-005, Race B VAL-010, Race C VAL-011**), VAL-030/031/034/036 as applicable; AC-S1-01..35 and VC/TEST-S1-01..39 (real PASS/FAIL/SKIP recorded only upon execution); review/merge PR `sprint1 → main`; D1 evidence and submission |
| **S2 - proposed D2 with Lab 5-7** | **F-S2-01** cancellation/reopen, **F-S2-02** single reschedule/history, **F-S2-03** Tutor cancellation, **F-S2-04** private notice, **F-S2-05** Slot withdrawal, and SYS-01 regression | Q07-Q27/Q32, ownership and atomic persistence must work in tested candidate | S2 VAL-015..027 and cross-operation race evidence, peer-reviewed SDS/STS before code; Lab 5-7 evidence; D2 integrated reviewed main/GCP release also includes one implemented/tested S3 workflow |

| Sprint | Product scope (stable IDs) | Objective accepted outcome | Planned verification / release |
|---|---|---|---|
| **S3 - D2 tested increment and mandatory Final completion** | **F-S3-01** Tutor-authorized summary: D2 minimum Past Booked count/list, then **Upcoming Booked and Cancelled counts + matching lists** mandatory for Final | By 25 Nov test Past Booked in UI/API/DB; by **30 Nov** complete all three owner-filtered categories with consistent count/list, approved OD-006 in-progress rule, independent review and deployed regression; Final 13 Dec acceptance | Real DB **VAL-028**, **VAL-029**, **VAL-036** fixtures, unauthorized-role/foreign-Tutor negatives, versioned PR/SHA and CI/GCP deployment; no category considered optional polish |

**Mandatory S1 boundary cannot be traded away:** real credentials/session; own roles and record-level checks; exactly 60-minute Slot publishing; Customer availability; Booking with 60-minute cutoff and exclusive real-DB guarantees; Customer/Tutor private reads; persistence across refresh/restart; denied invalid/past/occupied/overlap requests; authenticated end-to-end UI/API/DB; negative and synchronized real-DB tests for Race A/B/C; accepted release on `main`. Demo-only mocks, memory-only records, UI-only blocking, a PR without a release, or tests described but not run do **not** satisfy this scope.

## 3. Feature dependencies, owners and verification handoffs

**Ownership plan:** Owner is accountable for getting a change reviewed and verifiable, not sole author of all code. @Chxtamos leads Part D and existing Issues #13/#15/#17; @Tanaboonnnnn leads existing Issues #14/#16/#18. The team coordinates shared architecture and migrations; no Issue assignment changes are made by this plan. These are **planning assignments requiring team agreement**, not a reassignment of existing GitHub Issues. The author of each PR must have the **other human teammate** review. Any actual feature-Issue owner/reviewer already assigned by GitHub prevails until explicitly updated.

| Work package | Depends on | Proposed accountable driver / independent reviewer | Exit evidence (not yet executed) |
|---|---|---|---|
| A / B / C baseline | Issue #9 SRS, #10 Feature Inventory, #11 System SDS | Issue-specific existing assignees; both check consistency | Document references and reviewed PRs integrated in `sprint1`; technical choices and OD gates still identified |
| Shared project scaffold + database (SYS-01) | reviewed SD-01..12 / OD-005; environment and schema/migration decisions | @Tanaboonnnnn / @Chxtamos | Runnable reproducible local install, migrations/seed and data persistence; secrets excluded |
| F-S1-01 (#13) | System SDS; own **Feature SDS + UI/API/data contracts + STS reviewed before code** | @Chxtamos / @Tanaboonnnnn (existing Issue owner/reviewer) | VAL-001/002/034/036; actual login/logout/role/session tests |
| F-S1-02 (#14) | F-S1-01; same Part E contract gate; DB exclusion constraint strategy | @Tanaboonnnnn / @Chxtamos (existing Issue owner/reviewer) | VAL-003..005; real-DB overlapping offer Race A and negative cases |
| F-S1-03 (#15) | F-S1-02, authenticated API; OD-004 safe availability fields | @Chxtamos / @Tanaboonnnnn (existing Issue owner/reviewer) | VAL-006/009/036; stale/too-soon/occupied privacy-safe responses |
| F-S1-04 (#16) | F-S1-01/02/03; DB uniqueness/exclusion/trigger and OD-005/013 guards | @Tanaboonnnnn / @Chxtamos (existing Issue owner/reviewer) | VAL-007..011/014/030; Race B/C, Q05 wait crossing and rollback/duplicate safety |
| F-S1-05 (#17) | F-S1-01/04; approved response allowlist | @Chxtamos / @Tanaboonnnnn (existing Issue owner/reviewer) | VAL-012/013/031/036; own Customer/Tutor reads and persistence |
| F-S2-01/02 | F-S1-04/05; S2 Part E contracts and Q07–Q16; OD-013 | Team to assign/peer review before S2 | VAL-015..020, 030; correct cancelled/reopened or one-history reschedule state |
| F-S2-03/04/05 | F-S1-02/04; cancellation/notice/withdrawal integrity; OD-008/014/015 | Team to assign/peer review before S2 | VAL-021..027, 036 and Booking-vs-withdraw / reschedule-vs-Tutor-cancel race |

| Work package | Depends on | Proposed accountable driver / independent reviewer | Exit evidence (not yet executed) |
|---|---|---|---|
| F-S3-01 - full Final scope | F-S1-05, Booked/Cancelled persisted records and S2 lifecycle; OD-006 in-progress classification and OD-009 query snapshot gate | @Chxtamos implementation/test lead; @Tanaboonnnnn independent reviewer (planning assignment) | Past Booked implemented/tested by 25 Nov for D2; prepare reviewed SDS/STS and fixtures for **Upcoming Booked and Cancelled** by 25 Nov, implement/test them on **30 Nov** (counts + matching lists), VAL-028/029/036, regression, PR integration and GCP redeploy before exams; full scope mandatory for Final |

**Contract-before-code sequence for each Feature:** source SRS FR/BR/NFR + accepted AC/Q → versioned Feature SDS (`specification.md`, applicable `ui-spec.md` / `api-spec.md`, data/transaction contract) → STS (`tests.md`, named failing/negative cases, evidence criteria) → *independent PR review* → feature code + tests → actual build/unit/API/DB/E2E results → reviewed feature PR to `sprint1`. A stub file or unreviewed spec does not open the implementation gate. SYS-01's migration/locking/Q05 design requires independent real PostgreSQL proof before Booking claims completion.

## 4. Sequence, checkpoints and integration strategy

Dates below are **planning allocations**, not claims that tasks were performed or promises of completion. Work is highly compressed: use checkpoints as stop/go decisions and escalate capacity risk, not as permission to skip mandatory acceptance.

| Date/window (ICT) | Planned step | Exit / escalation |
|---|---|---|
| **3 Nov** | Review merged Parts A/B/C, approve feasibility/pending OD-005, author/review Part D; list per-feature Issues/contracts; test local Node/Postgres compatibility | Traceability/stack gaps owned; if local DB unavailable, escalate immediately rather than marking setup done |
| **4 Nov** | Review System SDS security/schema details and Part E specs/STS for F-S1-01 and F-S1-02; prepare scaffold/migration/seed, auth/slot test fixtures | Contracts reviewed **before code**, migration applies on clean local test DB, no secrets |
| **5 Nov** | Complete auth and Tutor Slot vertical slice; real DB and Race A; prepare F-S1-03/04 contract reviews | Negative role/overlap tests with actual committed state; ownership and Q05 blocking issues escalated |
| **6 Nov** | Availability + Booking implementation, Q05 guard, Race B/C, fail/duplicate handling, protected reads contract/code | Real DB barriers and persisted rows, no second success; any unproven constraint is a release blocker |
| **7 Nov** | End-to-end UI/API/DB journeys, security/private read checks, restart durability, real test evidence; review feature PRs then integrate `sprint1` | All S1 AC/VC mapped to observed pass/fail/skip; blockers fixed, never silently waived |
| **8 Nov before 23:59** | Issue #18 (@Tanaboonnnnn owner / @Chxtamos reviewer) independent integration review, separately reviewed `sprint1 → main` release, versioned evidence/submission package: whole-product Parts A–D, per-feature Part E SDS/STS, Part F source/test logs and release SHA, and required D1 PDF/report per authoritative course instructions | Only claim D1 acceptance if main contains the working slice and actual tests/review/release evidence; instructor/Theme gates remain explicit |
| **9-11 Nov - S2 and Lab 5 setup** | Both review S2 feature SDS/STS before code. @Tanaboonnnnn leads Docker/GCP/Cloud SQL/secrets; @Chxtamos leads CI and S1 regression planning | Reviewed contracts, migration/seed setup and CI plan; reserve **at least 50% of combined planned capacity** for Lab 5 to 15 Nov; available hours remain unknown |
| **12-15 Nov - Lab 5 due 15 Nov** | Both: Docker, CI/CD, GCP Cloud Run with durable Cloud SQL; @Tanaboonnnnn deployment driver and @Chxtamos test/peer-review driver | Version/commit/image SHA, CI run URL/status, GCP URL/version, secret checks, post-deploy auth/Booking and DB restart persistence evidence. Lab 5 due 15 Nov, after D1 but mandatory for D2 |

| Date/window (ICT) | Planned step | Exit / escalation |
|---|---|---|
| **16-19 Nov - S2 and Lab 6 setup** | Both implement reviewed F-S2-01..05 in dependency order; @Chxtamos prepares cross-team UAT scenarios/defect log and @Tanaboonnnnn deployed candidate/fixes | S2 VAL-015..027/DB race and rollback proof as ready; reserve **at least one-third of combined planned capacity** for Lab 6/UAT/retests |
| **20-22 Nov - Lab 6 due 22 Nov** | Both run cross-team UAT; @Chxtamos coordinates scenario/evidence/defect log, @Tanaboonnnnn triages repairs and re-tests | Dated UAT outcomes, defect IDs/severity/owners, linked repair PRs and re-test results; feed residual defects into D2 regression |
| **23-25 Nov - D2 S3 working increment plus full-category preparation** | @Chxtamos obtains independent peer review of the **full F-S3-01 SDS/STS before code**, covering all three category predicates, same-time snapshot, OD-006 and fixtures. Implement real Tutor-only DB-backed Past Booked count/list via UI/API and prepare shared count/list query/UI and tests for Upcoming and Cancelled. @Tanaboonnnnn reviews | By 25 Nov Past Booked **implemented and tested** for D2, with real DB VAL-028/029/036 and source SHA; complete category test specification and prerequisites for mandatory Upcoming+Cancelled by 30 Nov. Prototype-only does not satisfy D2 |
| **26-28 Nov - Lab 7 and D2 candidate** | @Tanaboonnnnn leads Lab 7 TA-approved change request, impact and updated reviewed contract, red-green regression, CI/GCP redeploy, five date-stamped sourced metrics and short retrospective; @Chxtamos leads S1/S2/S3 regression and D2 PDF; both review integration/release PR and UAT fixes | By 28 Nov tagged main/GCP candidate with CI run/status, SHA, URL/version, DB durability and S1/S2 + tested S3 Past Booked, plus Lab 7 evidence: TA approval reference, contract impact, red/green test logs, redeploy proof, five dated sourced measurements with units, short retro. Missing approvals/evidence = BLOCKED |
| **29 Nov - D2 and Lab 7 due** | Both verify main/GCP candidate and submit D2 self-contained PDF via LEB2; @Tanaboonnnnn checks release and Lab 7 change/metrics/retro, @Chxtamos PDF/evidence/receipt | Integrated main/GCP candidate with tested S1/S2 and **at least one tested S3 Past Booked workflow**, CI/post-deploy persistence and regression, UAT retests and Lab 5-7 evidence. Missing gate = NOT MET; Upcoming+Cancelled remain **mandatory Final**, scheduled 30 Nov |
| **30 Nov - mandatory F-S3-01 completion and release freeze** | @Chxtamos implements **Upcoming Booked and Cancelled counts + matching lists** in authorized UI/API/DB based on already-reviewed full F-S3-01 SDS/STS and reusable fixtures; @Tanaboonnnnn independently reviews actual tests/PR. Both integrate into sprint1, independently review sprint1-to-main release, run regression and CI/GCP redeploy; draft final PDF/video script | **By 30 Nov** all **three mandatory FR-035 categories** implemented/tested and deployed: Upcoming/Past/Cancelled fixtures, count=list matching owner/time snapshot, wrong-role/foreign-Tutor denials, approved OD-006 classification/no Completed state, VAL-028/029/036 real DB results, peer review, SHA/CI/GCP and post-deploy persistence/regression. **Critical one-day capacity risk**: reusable query/UI and all-category contract/tests ready by 25 Nov; escalate if infeasible rather than silently defer |
| **1-11 Dec - final exams and release monitoring only** | Protect exam time: no new core S3 implementation. @Chxtamos final PDF/video assembly, @Tanaboonnnnn security/release checks and low-risk regression | Full three-category Summary already implemented, tested, reviewed and deployed by 30 Nov; remaining mandatory gaps or unresolved OD-006 explicitly block Final rather than become optional refinements |
| **12-13 Dec - final due 13 Dec** | Both verify deployed accepted release with **Upcoming Booked, Past Booked, Cancelled counts and matching lists**, replay real-DB VAL-028/029/036, authorization and time classifications, submit final PDF plus demo video with both members explaining | Full S3 scope, security/regression, release SHA, CI/GCP redeploy proof and submission receipt. A missing mandatory category means Final NOT MET, not last-day implementation |

**Integration cadence:** no feature PR before its reviewed contracts; PRs are independently reviewed (no self-approval), and only accepted feature branches land on `sprint1`. After final S1 verification, open a separate `sprint1 → main` release PR and review it. Avoid simultaneous merge conflicts by naming file/feature ownership and sequencing schema migrations before dependent services. GitHub Project #6 advances `Backlog → Specified → Started → PR Review → Fixing → Done` based on verified work, not calendar dates.

## 5. Definition of Done and objective evidence

| Gate | S1 acceptance and measured evidence | Outcome if absent |
|---|---|---|
| Source/contract | Part A/B/C references and applicable **peer-reviewed Part E SDS/STS before implementation**, including stable IDs | Contract/implementation gate **BLOCKED** |
| Working path | Customer/Tutor UI → authenticated API → durable relational DB, real login/logout/current identity and persisted own records after restart | **NOT DONE** if mock/in-memory/UI-only |
| Domain | Exactly 60-minute Slots, no same-Tutor active overlap; valid/invalid/occupied/too-soon cutoffs; one Active Booking per Slot; no cross-Tutor Customer overlap | **NOT DONE** if invariant unproven |
| Security | Backend role + record authorization, sanitized error/data allowlists, credentials hashed, no secrets committed | **NOT DONE** on unauthorized read/write |
| Race / rollback | Synchronized *real DB* Races A/B/C, Q05 post-wait boundary, rejected writes and injected rollback, final committed rows inspected | **NOT DONE** if HTTP-only/mock-only |
| Tests | VAL-001..014 and S1-applicable VAL-030/031/034/036; AC-S1-01..35 / VC/TEST-S1-01..39 have actual command, setup, SHA and PASS/FAIL/SKIP records | No manufactured PASS; unresolved required FAIL/NOT RUN blocks release |
| Integration / delivery | Peer-reviewed feature PRs into `sprint1`; independently reviewed `sprint1 → main` PR; release SHA and D1 artifact/evidence by deadline | Staging/PR alone **does not count as accepted release** |

**D2 acceptance gate (after D1):** Peer-reviewed Part E SDS/STS must precede all S2/S3 code. By 29 Nov produce tested S1+S2 AND at least one **implemented/tested S3** rule in a reviewed integrated **main** release candidate deployed on **GCP via Lab 5 CI/CD**. Record version/tag, SHA, CI run/status, GCP URL/version, post-deploy DB persistence, S1/S2/S3 regression and authorization/negative tests. Lab 6 UAT defects/re-tests and Lab 7 maintenance/metrics feed this evidence. Submit a self-contained **D2 PDF via LEB2**. By 13 Dec provide final PDF and demo video with BOTH students explaining; reserve exams 1-11 Dec. Do not claim these plans are executed tests or deployments; not required at D1. **Separate Final F-S3-01 gate:** D2 Past Booked is only a minimum slice. Complete Upcoming Booked and Cancelled plus Past Booked counts/lists, approved OD-006, real-DB VAL-028/029/036, review, integration, CI/GCP redeploy by 30 Nov; Final 13 Dec requires full summary, not optional enhancements.

## 6. Capacity, risks, gates and controlled fallback

**Two-person feasibility:** D1 leaves roughly five calendar days from 3 Nov; after D1, Lab 5/6/7 overlap with mandatory S2 and at least one tested S3 rule before D2. Allocate approximately half of combined planned capacity to Lab 5 through 15 Nov, one-third to Lab 6 through 22 Nov, prioritize Lab 7/main/GCP/PDF on 26-29 Nov and prepare final artifacts before 1-11 Dec exams. Actual student hours are UNKNOWN; these fractions are planning safeguards, not capacity proof. Both students peer-review opposite authored PRs. If core correctness/review/release gates fail, explicitly report NOT MET instead of silently reducing mandatory scope. The 30 Nov full-S3 completion/review/deploy is a one-day critical-path risk; prepare approved contracts, reusable UI/API/DB and fixtures by 25 Nov, record remaining work and escalate lack of capacity instead of claiming acceptance.

| Risk / open gate | Owner / checkpoint | Containment and defensible fallback |
|---|---|---|
| **OD-011/012:** final instructor Master and formal Theme eligibility unverified | @Tanaboonnnnn obtains instructor/TA evidence; @Chxtamos compares before formal D1 sign-off | Present drafts as provisional, record source/version/delta; **do not** assert instructor sign-off |
| **OD-005:** proposed stack, session, DB triggers/locking and Q05 post-contention proof not yet accepted/executed | @Tanaboonnnnn design lead + @Chxtamos review, before Part E implementation | Probe real DB early; choose reviewed simpler implementation only if it still proves Race A/B/C and Q05; **never** remove DB integrity checks |
| **OD-001..004:** Tutor hours/horizon/grid, availability safe fields unresolved | Product decision owner/team before F-S1-02/03 final contracts | Implement only confirmed constraints; defer optional filtering and non-approved input restrictions, not mandatory Slot/browse outcomes |

| Risk / open gate | Owner / checkpoint | Containment and defensible fallback |
|---|---|---|
| **OD-013:** duplicate/unknown-response Booking retry contract | F-S1-04 owner with peer review before Booking SDS/STS sign-off | Preserve at-most-one and reconcile with authorized own reads while token/replay protocol remains explicitly proposed; don't claim exactly-once response |
| **OD-006/008/009/014/015:** in-progress summary, retention, reporting snapshot, meaningful reason, prior-Tutor privacy | Relevant S2/S3 feature owner and stakeholder/team before affected contract | Mark blocking decisions and do not invent product rules; no unauthorized historical visibility |
| Missing local DB/toolchain or incompatible Postgres extension/ORM migration | Shared SYS-01 owner, setup checkpoint | Prioritize reproducible dev DB and constraints, temporarily replace an unworkable ORM detail **via reviewed design delta**, not with memory-only or unguarded writes |
| Late failed Race A/B/C, Q05, auth, persistence, or release checks | Both people, S1 test/release gates | Stop false acceptance, record FAIL/NOT RUN and remediate smallest cause; escalate deadline impact. **Do not quietly cut mandatory S1 feature** |
| Reviewer unavailable/merge queue and limited two-person capacity | Each PR author requests other teammate promptly; daily check-in | Keep PRs small, parallelize independent reviewable contracts, capture unresolved blockers; no self-approve or skip release PR |
| Missing Lab 5/6/7 evidence, UAT re-tests, or D2 main/GCP candidate | @Tanaboonnnnn deployment and Lab 5/7, @Chxtamos Lab 6/UAT/regression | Reserve Lab capacity and capture exact failed gates; no false D2 deployment or passed-test claims |
| Missing full FR-035 category set or exam capacity | @Chxtamos implementation/tests, @Tanaboonnnnn independent reviewer/redeploy; all categories due 30 Nov | Deliver Past Booked for D2 25 Nov, prepare full SDS/STS/tests beforehand; Upcoming+Cancelled implementation, regression, review and GCP redeploy on 30 Nov. Never call mandatory categories optional polish |
| Optional UI polish, benchmarks/accessibility thresholds not approved | Owner TBD / OD-010 | Defer nonessential polish and unapproved thresholds after mandatory S1 correctness and tested end-to-end flow; document what remains |

**Fallback hierarchy:** (1) resolve source/data/security blockers; (2) protect mandatory S1 real UI/API/durable DB and Race A/B/C; (3) protect D2 tested S2 features, one implemented/tested S3 rule, Lab 5-7 and deployed main/GCP candidate; (4) simplify ONLY optional UI polish/refinements with peer/team approval; (5) if a required checkpoint fails, state NOT MET and preserve failing evidence rather than asserting acceptance. **FR-035 Upcoming/Past/Cancelled are three mandatory Final categories and cannot be deferred as optional UI polish.**

## 7. Coverage and approval checklist

- **S1 features:** F-S1-01..05 + SYS-01, all mandatory Sprint 1 acceptance/test IDs `AC-S1-01..35`, `VC/TEST-S1-01..39`, Q01/Q02/Q03/Q04/Q05/Q06/Q28/Q29/Q30 as applicable; planned VAL-001..014, VAL-030/031/034/036.
- **S2 proposed:** F-S2-01..05 and VAL-015..027, VAL-030/036; S1 authorization/time/atomicity regression; Q07..Q27/Q32 and relevant privacy rules.
- **S3 proposed: F-S3-01 Past Booked** implemented/tested for D2 minimum by 25 Nov, then **Upcoming Booked and Cancelled counts + matching lists** implemented/tested, peer-reviewed, regression checked and deployed by **30 Nov**, before exam period. Real DB **VAL-028**, **VAL-029**, **VAL-036**, Tutor ownership, consistent state/time and OD-006 approval gate; all three mandatory for Final.
- **System NFR:** NFR-001..008/011/012/014/015/016 mapped to sprint features; NFR-009/010 proposed OD-010 thresholds, not approved. NFR-013 requires **Lab 5 Docker/CI/GCP by 15 Nov** and a **main/GCP deployed candidate by D2 29 Nov**, NOT by D1; Lab 6 UAT/retests due 22 Nov and Lab 7 maintenance/metrics due 29 Nov. D2 PDF via LEB2, final PDF and both-student demo video due 13 Dec according to reviewer-cited v1 handouts.
- **Explicit remaining gates:** OD-001..015 tracked in SRS; Issue #12 planning review does not close them automatically, does not approve new product rules and does not certify instructor/Theme eligibility.
- **Approval:** The two students must review and accept this allocation as a plan. @Tanaboonnnnn supplies substantive peer review on the Issue #12 PR into `sprint1`; @Chxtamos cannot self-approve or self-merge. The actual accepted D1 code/release and test evidence belong to later feature/integration Issues, not this Part D document.

## 8. References

- Issue #12 — Part D plan
- Whole-product SRS, especially §§3, 10, 13, 15
- Sprint 1 requirements and AC/VC IDs
- Feature inventory and cross-sprint traceability
- System SDS, especially §§1, 3, 5, 7–10
- AGENTS.md: local issue branch, review, validation and acceptance gates

**PR #24 source provenance:** This revision follows reviewer citations of group_work_specs_v1.pdf section 4, project_deliverable_2_v1.pdf sections 2/3.3/3.5, and project_final_delivery_v1.pdf. The complete handouts were not independently opened for this edit; final instructor Master and Theme sign-off remain open (OD-011/012).

**Final F-S3-01 acceptance boundary:** The D2 Past Booked count/list is only a partial milestone. Final demands DB-derived owner-filtered counts **and corresponding lists** for Upcoming Booked, Past Booked and Cancelled. Complete the remaining two on 30 Nov, test all three with VAL-028/029/036 against real DB fixtures and wrong-role/foreign-record negatives, uphold same time/visibility snapshot and explicit OD-006 policy; peer-reviewed feature PR to sprint1, reviewed release to main, CI/GCP post-deploy regression. If missing, Final is NOT MET.

**Lab 7 v1 proof obligation (per second review):** TA-approved change request with source/approval reference -> impact analysis and reviewed updated contract -> failing-then-passing regression evidence -> CI/CD redeploy with runtime SHA/URL -> **five dated metrics** with units and sources -> brief team retrospective. No fabricated TA approval or metrics.

# Part E: Sprint 1 Feature Specifications & Software Test Specifications

> **Completeness Notice:** Every reviewed and accepted Sprint 1 Part E contract ( `specification.md` , `ui-spec.md` , `ui-decision-2026-11-05.md` , `api-spec.md` , `data-spec.md` , `transaction-spec.md` , and `tests.md` ) is embedded **verbatim in full** below so this PDF stands alone without external repository links.

## E.1 F-S1-01: Authentication, Sessions & Rate Limiting

### E.1.1 F-S1-01 Authentication Feature SDS (specification.md)

> **Part E contract; not implemented or runtime-tested.** Issue #13, owner @Chxtamos, reviewer @Tanaboonnnnn. Decision approval from PR #25 Conversation #6624817784: **OD-005-A/B/C/E and Auth UI direction APPROVED; OD-005-D APPROVED (PR #25 reviewer comment #6625521193)** reviewed and accepted in PR #25 comment #6625521193. The reviewed and approved Part E PR #25 was merged into `sprint1` before Part F implementation. Instructor-final Master/Theme gates remain separate.

#### Authority and scope

Follow Sprint 1 requirements FR-S1-01..04, AC-S1-01..07, BR-S1-04/16/17/20, NFR-S1-01/02/07/08 and VC-01..07/31/35; whole-product SRS FR-001..004, BR-002/033, VAL-001/002/034/036; System SDS SD-09 and section 5; Feature Inventory; three-sprint plan. Tutor and Staff are one business role. This feature owns **login, current trusted identity, logout, sessions, and reusable server access guards**; Slot/Booking persistence and actual row-level proofs depend on Issues #14–17.

#### Proposed architecture and decisions (OD-005)

Single-origin React/Vite client and Express/TypeScript backend with durable PostgreSQL User and Session records (Prisma adapter/SQL migration details to verify before code). Credentials are Argon2id salted hashes. Valid login obtains 32 random CSPRNG bytes; the opaque cookie contains the raw token while the database stores **only** a unique SHA-256 token digest. Set cookie **after** Session insert commit. Client role, claimed owner IDs, headers or query parameters never grant authority.

| Topic | Proposed Part F behavior | Review decision |
|---|---|---|
| Cookie | `nuttiew_session` ; `HttpOnly; Secure; SameSite=Lax; Path=/` ; no Domain; localhost HTTP only uses `nuttiew_session_dev` with Secure=false | Production HTTPS, proxy setup, allowed origins |
| Lifetime | **Eight-hour absolute** lifetime from DB creation; no rolling renewal; check `expiresAt > serverNow` , `revokedAt IS NULL` , active User and role on every request | **OD-005-A APPROVED as decision; implementation/tests NOT RUN** (PR #25 comment #6624817784) |
| Login | Existing Customer/Tutor accounts only, normalized unique email, generic error for unknown/wrong/inactive, no new cookie on failure; separate logins create independent sessions | Hash cost, rate limiting, input bounds, seed policy |
| Logout | CSRF-protected POST; atomically revoke **presented session only**; send 204 and expire cookie **after DB commit**; replay old cookie denied; independent other session stays valid | **OD-005-B APPROVED as decision; implementation/tests NOT RUN** |
| CSRF | Approved Session-bound HMAC token with same-origin Origin/Referer rules and read-only token bootstrap; no cross-origin credentialed CORS; matched on unsafe requests | **OD-005-C APPROVED as decision; implementation/tests NOT RUN** |
| Error/privacy | Uniform invalid-login result; no email enumeration, raw secrets, stack/SQL error, foreign resource details; no session token in JSON/localStorage/logs | Exact status/code response schema in API contract |

| Topic | Proposed Part F behavior | Review decision |
|---|---|---|
| Future | Password reset, role switching, rotation/revoke-all administration and S2/S3 operations not implemented | Separate approved feature contract |

If Session insert or logout revocation fails, **do not claim success**. An expired/revoked token is never implicitly refreshed. Each protected request loads a live Session and active User from persistent DB; after restart the same valid cookie continues until actual expiry. Session identity must derive from the database, not the client.

### Server-side permission boundary

| Action | Anonymous | Customer | Tutor | Record-level predicate |
|---|---|---|---|---|
| Login | Credential exchange | Allowed | Allowed | Valid existing active account |
| Own identity/logout | 401 | Own session | Own session | Valid unexpired/unrevoked Session joined to active User |
| Tutor Slot create/read | 401 | 403 | Own schedule only | Create `tutorId` from principal; read SQL where `Slot.tutorId = principal.id` |
| Customer Booking create/read | 401 | Own only | 403/general reads denied | `customerId = principal.id` from session, not request |
| Tutor Booking/schedule read | 401 | 403 | Own only | Derive Tutor from persisted Slot and filter by principal |
| Foreign record | 401 | No protected data | No protected data | Privacy-safe 404 for foreign/missing ID |

`requireSession`, `requireRole`, `requireOwnedResource` and owner-filtered DB queries are interface intentions; their actual domain integrations require Issues #14–17. Hidden buttons, forged `role`, `customerId` or `tutorId` cannot replace backend checks. Avoid existence leaks via foreign-record responses.

### Part E → Part F gate

#### OD-005 decision sheet — A/B/C/D/E approved decisions; Part F tests tracked separately

The explicit human decision is recorded in PR #25 Conversation comment **#6624817784**: **OD-005-A/B/C/E and Auth UI direction APPROVED**, **OD-005-D APPROVED (PR #25 reviewer comment #6625521193)**. The updated in-flight reservation tradeoff was expressly approved by @Tanaboonnnnn in PR #25 comment #6625521193. **Approval of an engineering decision is not proof of a passing implementation**; Part E was independently reviewed and merged into `sprint1`; Part F acceptance and tests remain separately reviewable. Instructor-final Master/Theme gates remain separate. Detailed protocols: API, Data, STS.

| Decision | Concrete proposed value/behavior | Approver / gate |
|---|---|---|
| OD-005-A Session TTL | Absolute **28,800 seconds (8 hours)**, measured from persisted `createdAt`, no sliding refresh; strict `expiresAt > DB/server now`, `revokedAt IS NULL` and `User.isActive` for every protected call; cookie Max-Age **<= 28800** | **APPROVED decision** by @Tanaboonnnnn, comment #6624817784; Part F tests NOT RUN |
| OD-005-B Logout | **Current presented Session only**, DB revocation commit **before** 204/clear-cookie, captured-cookie replay 401; another Session B remains usable; DB write fault must not be reported as success | **APPROVED decision** by @Tanaboonnnnn, comment #6624817784; Part F tests NOT RUN |
| OD-005-C CSRF and origin | **Session-bound HMAC CSRF (approved in PR Conversation comment 6624817784):** create and persist a nonsecret 32-byte `csrfNonce` once at login; derive a stable MAC from managed server HMAC key + Session ID + nonce using the canonical expression **outside this GFM table** in API/Data. Repeated read-only `GET /auth/csrf` returns the same MAC without DB mutations; multiple tabs work. Unsafe methods constant-time verify against the live Session, and A's token fails for B; logout/expiry revokes it. No per-GET rotation. Same-origin Origin/Referer fallback and cross-site safeguards remain as documented; managed versioned keys require secure overlap and retirement | **APPROVED by @Tanaboonnnnn in PR Conversation comment 6624817784**; implement/test in Part F, AUTH-13/17/18/21 |

| Decision | Concrete proposed value/behavior | Approver / gate |
|---|---|---|
| OD-005-D Rate limit | **Reviewer-requested revision, APPROVED design in PR #25 reviewer comment #6625521193:** 15-minute PostgreSQL-backed HMAC-keyed account and trusted-IP buckets. Per account allow **5 failed credential attempts/15min** (successful logins do not increase failure count); per trusted IP allow **20 total login attempts/15min** (success and failure both counted). Before Argon2, reserve one IP attempt and one **account in-flight permit** atomically under row locks, but do **not** increment account failure count until the credential result is known. On failed credential validation commit one account failure and release its permit; on successful validation release the permit **without incrementing failures**. Enforce the account failure quota against **failed + in-flight reservations** so simultaneous attempts across instances cannot bypass five. Do not hold DB row locks during Argon2. A rejected attempt returns generic 429 and never creates a Session. Fixed UTC 15-minute windows, managed HMAC key, trusted proxy allowlist, fail-closed DB errors and nonenumerating responses remain required. See Data contract for transaction boundaries, window rollover and crash-recovery policy | @Tanaboonnnnn requested **5 failed-only/account + 20 total/IP** in PR #25 Conversation comment 6624817784; **OD-005-D APPROVED (PR #25 reviewer comment #6625521193)**, revised atomic permit protocol and all-valid saturation tradeoff expressly approved in PR #25 comment #6625521193; implementation verification tracked in AUTH-20/22 |
| OD-005-E Input bounds | JSON request body **<= 4 KiB**; email **3–254 Unicode code points** after trimming, normalized lowercase and valid email syntax; password **1–128 UTF-8 bytes**, no trimming or Unicode normalization of secret; strict only `email` and `password` keys; malformed/oversized → 400/413 and no DB Session insert. Avoid timing-dependent account enumeration (dummy Argon2 verification for unknown account) | **APPROVED decision** by @Tanaboonnnnn, comment #6624817784; Part F tests NOT RUN |

**Pre-code acceptance record (PR #25 Conversation comment 6624817784, 4 Nov 2026):** @Chxtamos = proposal owner; @Tanaboonnnnn confirmed **OD-005-A (8h absolute TTL), B (current-session logout), C (HMAC CSRF/Origin), E (input bounds) and Auth UI direction APPROVED** in that comment, and **OD-005-D APPROVED (PR #25 reviewer comment #6625521193)** (failed-only account threshold, total trusted-IP threshold). This document reflects those stated decisions, not an implementation/test pass. **The revised OD-005-D permit protocol was expressly approved by @Tanaboonnnnn in PR #25 comment #6625521193 and Part E was merged into `sprint1`.** This approval is a design decision, not Part F verification or a finding that AUTH-01..23 all pass. Source baseline remains SD-09, FR-S1-01..04 and OD-005. If browser/CI clients lack acceptable Origin/Referer for unsafe requests, reject rather than bypass security.

Contract links: API, UI, persistent data, STS/tests. Human teammate must approve session TTL, CSRF, logout scope, rate limits, response schemas and the documents before coding. Later Part F work starts on a fresh branch from reviewed `sprint1`, first records a failing test where feasible, implements genuine UI→API→PostgreSQL, and publishes real test logs and a separately reviewed code PR. This document has **NOT RUN** status for every app/DB test and does **not** close Issue #13.

> **Approval-state update (2026-11-04):** @Tanaboonnnnn expressly approved OD-005-D, including the temporary sixth-correct-login 429 tradeoff, in PR #25 comment #6625521193, with follow-up review confirmation in PR #25 review #5765005104. The approved Part E contract was merged into sprint1. This corrects historical pending-status text only; implementation and the AUTH-01..23 tests are independently tracked in Part F verification ledger.

---

### E.1.2 F-S1-01 Authentication UI Specification (ui-spec.md)

> Part E UX **contract**, not implemented UI or test evidence. **Auth UI design direction APPROVED** by @Tanaboonnnnn in PR #25 Conversation comment #6624817784; implementation, browser review and AUTH-15/23 remain NOT RUN. OD-005-D approved in PR #25 reviewer comment #6625521193; Part E merged into sprint1; Part F verification remains separate. See SDS, API, STS. Role navigation does not authorize an API request.

| UI state | Action | Observable expected behavior | Trusted server interaction |
|---|---|---|---|
| Signed out | Open app | Labeled email/password form, no protected data or role selector; login is permitted | `GET /api/v1/auth/me` missing cookie → 401; show login |
| Pending | Submit credentials | Disable duplicate submit while pending, visible status, do not print password | `POST /auth/login` (same origin) |

| UI state | Action | Observable expected behavior | Trusted server interaction |
|---|---|---|---|
| Customer success | Valid Customer login | Show server-issued **own account reference plus effective Customer role**, not just generic “Customer”. Proposal: “บัญชี: ...a1b2c3d4 · Customer”, where suffix is last 8 hex characters of authenticated UUID (short label, not unique security identifier) | `GET /auth/me` derives `id` and `role` from DB Session/User, never client input or stale state |
| Tutor success | Valid Tutor login | Show **own account reference plus Tutor role** and own schedule navigation. After switching account, no previous C1/T1 identity persists | Same trusted `/auth/me` response, domain authorization still enforced by API |
| Bad credentials | Unknown/wrong/inactive account | Generic identical error, no account enumeration, no protected data | 401 `LOGIN_FAILED` |
| Bad form | Blank/invalid inputs | Keyboard-accessible field errors; server revalidates | 400 `INVALID_INPUT` |
| Reload | Active/expired Session | Loading until current-user response; active survives refresh; revoked/expired loses identity | `GET /auth/me` then authorized or signed out |
| Logout | Authenticated principal clicks logout | Obtain in-memory CSRF token, post logout; clear UI identity after **confirmed 204 only**. On network/DB error show uncertainty and retry rather than falsely claim revocation | `GET /auth/csrf` → `POST /auth/logout` |
| Forged navigation | Customer attempts Tutor URL or Tutor A accesses Tutor B ID | UI access-denied state with no private data; backend still applies 403/404 | Role and DB owner checks in later Issues #14–17 |

### Interaction and security requirements

Use native `<label>` elements for email/password, `autocomplete=email` and `current-password`, visible focus and keyboard Tab/Enter flow, live status/error announcement, no user-selectable role, no credential or raw session storage in URLs, localStorage, analytics or logs. Because the cookie is HttpOnly, JavaScript never reads bearer secret; CSRF value is memory-only and cleared after sign-out. Avoid showing cached protected identity after 401 or after a stale request finishes late. If logout commit fails, do not present successful sign-out based solely on clearing frontend state.

### Future UI evidence (Part F only)

Record real browser/API/DB verification of Customer and Tutor login, wrong password, trusted role on refresh, logout and replay denial, keyboard navigation and forged access attempts. Screenshots of a hidden Tutor button are **not** a backend permission test. Actual screenshots, Playwright results and integration evidence are **NOT RUN** at this Part E phase.

### Auth-only visual direction — APPROVED design decision, implementation/tests pending

The approved visual direction is a **calm tutoring/scheduling utility**, not a landing or marketing page, scoped to **F-S1-01 only**. @Tanaboonnnnn approved the direction and tokens in PR #25 Conversation comment #6624817784; this is a **decision approval**, not evidence that a browser-rendered UI exists or passes accessibility checks. Part F must implement and verify it with AUTH-15/23 after the now-completed OD-005-D approval and Part E merge gates. These visual decisions are team technical/UX choices, not new instructor business rules.

| Element | Desktop | Mobile and acceptance |
|---|---|---|
| Anatomy | Small text-only NutTiew wordmark, concise sign-in heading, subdued helper, left-aligned visible email/password labels and inputs, one prominent primary action, quiet real help text only | Keep same order; no role picker, imaginary schedules, testimonials, hero or extra CTAs |
| Layout | Warm neutral page, readable **400–440px maximum** form column with content left-aligned, centered within available canvas; **no nested cards** | At 320/375px use 16px horizontal gutters and full remaining width; at 768/1280px preserve readable column, no horizontal overflow |
| Spacing and corners | 4/8/12/16/24/32px spacing scale; 8px label gap, 16px field gap, 24–32px section separation, 8px radius | Input/button internal padding 12–16px; target size **at least 44 by 44 CSS px**; avoid clipping or overlapping text |
| Typography | Thai/English legible stack: Noto Sans Thai, Sarabun, system-ui, sans-serif; heading 24px/1.3 weight 600; body 16px/1.5; labels 14–16px/1.5 | Input font >=16px; keep bilingual text readable without truncation and clear focus/navigation order |

| Element | Desktop | Mobile and acceptance |
|---|---|---|
| Semantic colors | **--auth-bg #F6F4EF** warm neutral, **--auth-surface #FFFFFF**, **--auth-text #262B28** graphite, **--auth-muted #4F5853**, **--auth-accent #285C4B** single muted pine green, **--auth-border #77877B** visible input boundary, **--auth-focus #285C4B**, **--auth-error #9C2B2B** (error status only) | Verify actual text/background pairs **>=4.5:1 normal text**, functional input border against white AND warm canvas **>=3:1 non-text contrast** (WCAG 2.2 SC 1.4.11); >=2px focus indicator; white-on-accent primary action; never convey errors by color alone |

**Anti-template gate:** do not use generic purple/blue gradients, glassmorphism, glow/blur floating blobs, gratuitous 3D stock mascots, decorative emoji, card-in-card layouts, fictional schedules/testimonials, or generic landing hero/CTA sections. Ordinary accessible icons and focus states are allowed when functional. Do not redesign Booking/Tutor pages in Issue #13.

**Auth form accessibility and failure recovery — concrete acceptance rules**

- Inputs must be **type=email and type=password**, with visible associated labels and **autocomplete=email/current-password**; permit paste and password-manager autofill. A show/hide-password control is a type=button control with accessible name reflecting current action, aria-pressed state, retained input value and focus; it must never accidentally submit.
- Field-specific errors must appear adjacent to fields, linked with **aria-describedby** and **aria-invalid**. For failed client validation, move focus to the first invalid input. For failed server submit, focus the short role=alert summary and announce it to a screen reader. Generic login copy must **not** distinguish unknown vs inactive account vs wrong password (e.g. "อีเมลหรือรหัสผ่านไม่ถูกต้อง").
- All visible interactive controls, including submit, show/hide and logout, must have **>=44 x 44px** usable targets. Confirm visible **focus-visible**, keyboard Tab/Enter navigation, touch usability and no role picker. UI navigation never substitutes backend ownership checks.
- Loading and duplicate submit: show a visible pending state and disable repeat submit only during active request; after failure/timeout, return to an actionable retry state. Do not leave an indefinite spinner. Do not show an authenticated screen from a client-selected role.
- Reload, expiry and stale responses: on refresh hide protected content until a fresh /auth/me 200; on 401, clear in-memory identity and CSRF and render signed-out. Use request generation IDs or abort/ignore-stale logic so a late successful login/me response cannot restore identity after logout, 401 or a newer auth transition.
- Uncertain logout: when network/503 fails, do not claim revocation; stop protected interactions and display a short retry/check-session message. Only confirmed logout 204 or fresh /auth/me 401 can finalize the signed-out state. Discard late old-identity responses. No password/session token in console, URL or browser storage.
- **AC-S1-01/02 visible own identity:** after trusted 200 `/auth/me`, render a **server-derived short UUID account reference (last 8 hex digits, explicitly labeled "บัญชี") plus effective role**, not simply a Customer/Tutor role tag shared by all accounts. A shortened UUID is only a privacy-preserving visual hint and may collide; never use it for authorization or claim global uniqueness. The backend continues to use the full ID. Part F must check that seeded C1/C2 and T1/T2 test accounts yield distinguishable visible references; if not, submit any proposed longer UUID display for peer review, not add email/displayName without privacy approval. Clear both reference and role during reload, 401, logout and session switch, then render only from the latest `/auth/me` response. **Auth UI direction was approved** in comment #6624817784; the exact rendered identity label still requires AUTH-23 visual/functional verification in Part F.

> **Approval-state update (2026-11-04):** @Tanaboonnnnn expressly approved OD-005-D, including the temporary sixth-correct-login 429 tradeoff, in PR #25 comment #6625521193, with follow-up review confirmation in PR #25 review #5765005104. The approved Part E contract was merged into sprint1. This corrects historical pending-status text only; implementation and the AUTH-01..23 tests are independently tracked in Part F verification ledger.

---

### E.1.3 F-S1-01 Authentication API Contract (api-spec.md)

> **Part E contract; not implemented or runtime-tested.** See Feature SDS, UI, data and STS. PR #25 Conversation #6624817784 **approved OD-005-A/B/C/E and Auth UI decisions**; revised **OD-005-D APPROVED (PR #25 reviewer comment #6625521193)** review accepted in PR #25 comment #6625521193. `/api/v1` follows System SDS §6. Part E was reviewed and merged into `sprint1` before Part F.

### Shared transport and payload

- JSON UTF-8, strict allowlisted inputs, bounded body/email/password sizes; response `Cache-Control: no-store`; browser credentials sent via same-origin cookie automatically. No role or owner parameters accepted as authority.
- Success identity allowlist: `{ "user": { "id": "<UUID>", "role": "Customer" | "Tutor" } }`; never expose password hash, session ID, digest, token or other Customer/Tutor data. Email is excluded pending explicit approved UI need.
- Error envelope: `{ "error": { "code": "CODE", "message": "Generic safe description" }, "requestId": "<opaque id>" }`. No SQL errors, stack traces, raw credentials, account enumeration or private IDs.

| Method / path | Request / session check | Success | Proposed errors / privacy |
|---|---|---|---|
| `POST /api/v1/auth/login` | `{ "email": string, "password": string }` only; check same-origin `Origin`, active User and Argon2id hash | 200 identity DTO; `Set-Cookie` only after PostgreSQL Session insert commits | 400 `INVALID_INPUT`; uniform 401 `LOGIN_FAILED` for wrong, unknown and inactive; 403 `ORIGIN_DENIED`; approved 429 throttling; safe 503 on DB failure; no auth cookie on failure |
| `GET /api/v1/auth/me` | Live session cookie; read-only | 200 identity DTO derived from persisted User/Session | 401 `UNAUTHENTICATED` on missing, expired, revoked or inactive; no private payload |
| `GET /api/v1/auth/csrf` | Live cookie plus same-origin request; token never stored in browser localStorage | 200 `{ "csrfToken": "<opaque per-session value>" }` and `no-store` | 401 if no session; 403 for invalid cross-origin; lifetime/representation **OD-005** |
| `POST /api/v1/auth/logout` | Live cookie, allowed Origin and valid `X-CSRF-Token`; no other request fields | 204 empty body after **transactional current-session revocation commit**, expire presented cookie | 401 if session invalid; 403 `CSRF_DENIED` if invalid/missing Origin/CSRF; 503 DB failure **without falsely clearing live session or reporting success** |

### Cookie, authorization and replay contract

Production cookie is `nuttiew_session` with `HttpOnly; Secure; SameSite=Lax; Path=/`, no Domain; max age cannot exceed Session expiry. **OD-005-A 8-hour absolute TTL and OD-005-B current-session-only logout are APPROVED decisions (PR #25 comment #6624817784); implementation and tests are NOT RUN.** Only localhost HTTP may set `Secure=false` with distinct `nuttiew_session_dev`; never do so for remote HTTP. The server generates 32 bytes with a CSPRNG and stores only its SHA-256 digest (not the raw cookie) in DB. Every protected request checks active User plus unexpired, nonrevoked Session against server time. Logout must be **replay resistant**: manually restoring old cookie still returns 401; other independent sessions stay live.

**OD-005-C Origin/CSRF decision APPROVED by @Tanaboonnnnn in PR #25 comment #6624817784; implementation/tests NOT RUN:** Do **not** require an `Origin` header on read-only `GET /api/v1/auth/csrf`, because same-origin browser GET may omit it. This GET requires a valid live cookie and same-origin/no-credentialed-CORS deployment; when `Sec-Fetch-Site` exists and equals `cross-site`, reject 403. **Stable derived CSRF lifecycle:** on login store a **32-byte random** `Session.csrfNonce` **(nonsecret)**, not a one-way hash of an unavailable raw CSRF token. A separately managed **256-bit-minimum** `AUTH_CSRF_HMAC_KEY` derives the response `base64url(HMAC-SHA256(key, 'NutTiew-CSRF-v1' || 0x00 || Session UUID bytes || csrfNonce))`. Repeated GET requests for a live Session derive the **same token without changing DB state**; both tabs and in-flight requests keep working. Server reconstructs the expected MAC from presented Session, rejects malformed header, and **constant-time compares** decoded `X-CSRF-Token` to the expected MAC on unsafe operations. A's token cannot authorize B even for the same User; expired/revoked Sessions fail first. CSRF token valid until session expiry/revocation or an explicitly reviewed key rotation. No raw token in DB/logs/browser persistent storage, and `Cache-Control: no-store` for GET; session-issued nonce and production key management/rotation are specified in Data and SDS. **Part E OD-005-D was approved by @Tanaboonnnnn (PR #25 comment #6625521193) and the approved Part E was merged into `sprint1`; Part F implementation and test acceptance are reviewed separately.**

For `POST /auth/login`, `POST /auth/logout` and other unsafe cookie-mutating methods: compare `Origin` (scheme, host, port) to a **configured canonical web origin**, never to untrusted `Host` or forwarded headers. If `Origin` is present but foreign/malformed/`null`, **403** even if `Referer` appears local. If `Origin` is absent, permit **only** a syntactically valid `Referer` with matching canonical origin and `Sec-Fetch-Site` not `cross-site`; with neither header or forged/cross-site metadata, **403**. Any explicit `Sec-Fetch-Site: cross-site` also denies. Logout additionally requires `X-CSRF-Token` bound to the current Session before

revocation. No credentialed cross-origin CORS. **OD-005-C decision approved**, browser/security execution remains pending Part F; see SDS decision sheet and AUTH-13/17.

**Login input contract (OD-005-E APPROVED in PR #25 Conversation comment 6624817784):** body **<=4 KiB**, only `email` and `password`; trimmed lowercased email **3–254 code points** with email syntax validation; password **1–128 UTF-8 bytes**, unchanged and never trimmed. Malformed shape 400, oversized body 413; identical 401 `LOGIN_FAILED` for unknown, wrong and inactive credentials with dummy Argon2 verification for unknown identity to reduce enumeration.

**Reviewer-requested OD-005-D rate-limit policy (APPROVED design, PR #25 comment #6625521193; Part F implementation evidence separate):** PostgreSQL 15-minute fixed UTC windows, two HMAC-keyed buckets: **5 FAILED credential verifications/account/15min**, with successful login **not counted as a failure**, and **20 TOTAL login attempts/trusted IP/15min**, including successful and failed requests. To avoid a race, a short admission transaction locks both rows in a stable order; rejects on `account.failed + account.inFlight >= 5` or `ip.attempts >= 20` with indistinguishable **429** `RATE_LIMITED`; otherwise increments **IP total attempts** and reserves **account in-flight permit** and commits before Argon2. After credential verification, a separate short row-locked transaction releases the same permit and increments account **failed** only for wrong/unknown/inactive credentials. The Session and success 200/Set-Cookie must not be issued until that final transaction successfully commits and permits were settled; DB failure returns sanitized 503, no auth cookie. Untrusted proxy headers never choose the IP. A successful result spends one IP request but zero account failure quota. Reservation lease expiry and fixed-window rollover are defined in Data atomic protocol; AUTH-20/22 prove failed-only counters and concurrent upper bounds. **OD-005-D design approval was explicitly granted in PR #25 comment #6625521193; Part F evidence, including AUTH-20/22, still requires independent review.**

#### Future dependent domain endpoint rules (not implemented here)

Issue #14/17 Tutor routes require `requireSession` → `requireRole('Tutor')` → owner-filtered query (`Slot.tutorId`/associated Booking's Slot Tutor ID equals principal). Issue #16/17 Customer routes require `Customer` and `Booking.customerId === principal.id`, with foreign and missing resource IDs both 404. On wrong role return 403; missing session return 401. Reject forged `role`, `tutorId`, `customerId`, `userId` or arbitrary principal headers at every path. This contract does **not** create those Slot/Booking endpoints.

**Verification status:** endpoint implementations, persistence and API tests **NOT RUN**. Corresponding scenarios are specified in STS.

> **Approval-state update (2026-11-04):** @Tanaboonnnnn expressly approved OD-005-D, including the temporary sixth-correct-login 429 tradeoff, in PR #25 comment #6625521193, with follow-up review confirmation in PR #25 review #5765005104. The approved Part E contract was merged into sprint1. This corrects historical pending-status text only; implementation and the AUTH-01..23 tests are independently tracked in Part F verification ledger.

---

### E.1.4 F-S1-01 Identity & Session Data Contract (data-spec.md)

> **Part E data contract — no migration created or executed.** Based on System SDS §3/5 and Feature SDS. PR #25 Conversation comment #6624817784 **APPROVED OD-005-A/B/C/E and Auth UI decisions**; **OD-005-D APPROVED (PR #25 reviewer comment #6625521193)** approved in PR #25 comment #6625521193. Part E contains design contracts only; its approved changes were merged into `sprint1` before Part F. Part F migration and test evidence is tracked separately in `verification-ledger.md`.

| Field | Data / constraints | Security and semantics |
|---|---|---|
| `User.id` | UUID PK | Trust server-generated principal identity |
| `User.email` | normalized unique text, canonicalization reviewed before implementation | Private credential identifier; not returned by minimal current-user DTO |
| `User.passwordHash` | nonnull Argon2id encoded hash with distinct random salt | Never plaintext, reversible, in API JSON or logs |
| `User.role` | enum `Customer` / `Tutor` (Tutor = Staff) | Authoritative DB role, not client form/header/body |
| `User.isActive` | boolean, active for auth | Any inactive user denied on next protected request |

| Field | Data / constraints | Security and semantics |
|---|---|---|
| `User.createdAt/updatedAt` | persisted timestamptz | Not part of minimal identity response |
| `Session.id` | UUID PK | Internal, not exposed as bearer cookie |
| `Session.userId` | indexed FK → User.id | Authorization joins actual principal |
| `Session.tokenDigest` | unique 32-byte SHA-256 digest from 256-bit random token | Raw token lives only in HttpOnly cookie, never persisted |
| `Session.createdAt/expiresAt` | server timestamptz, expiresAt > createdAt; **8h absolute TTL approved** | Server clock, no sliding renewal; **OD-005-A decision APPROVED**, implementation/tests NOT RUN |
| `Session.revokedAt` | nullable timestamptz | Logout transaction revokes presented Session only; no reuse after commit |
| `Session.csrfNonce` | 32-byte random BYTEA, generated once at login, not exposed; **not a CSRF token or digest** | Nonsecret per-session HMAC input; repeated GET derives stable token without DB write |
| `Session.csrfKeyVersion` | short key-identifier of managed HMAC key version | At login snapshot current key version; old version can be verified until all dependent Sessions expire, then retire; no secret stored in DB |

**Atomic lifecycle:** create Session row and commit **before** sending authenticated cookie; on logout mark current row revoked and commit **before** responding 204 or expiring cookie. On failed DB write report sanitized failure and preserve actual session state. Expired/revoked/inactive rows fail identity checks after app restart; cleaning expired rows does not restore access.

**OD-005-C decision APPROVED (PR #25 Conversation #6624817784); stable, reproducible, read-only GET; implementation/tests NOT RUN:** At successful login generate a **32-byte CSPRNG nonce** and persist it as `Session.csrfNonce` (32 bytes, **nonsecret**, never included in API responses), plus `Session.csrfKeyVersion` for the current managed key. Maintain separate **256-bit minimum** `AUTH_CSRF_HMAC_KEY` in deployment secret manager, not source/DB/client. For live Session S derive `T = base64url(HMAC-SHA256(key[S.csrfKeyVersion], UTF8("NutTiew-CSRF-v1") || 0x00 || UUIDbytes(S.id) || S.csrfNonce))`. The server **does not store** `T` **or its hash**. Each authorized `GET /auth/csrf` recomputes and returns exactly the same T while Session/key version remain unchanged; zero database mutation and no per-GET rotation, so two tabs and requests already in flight retain valid tokens. Unsafe cookie-authenticated POST recomputes T from the currently presented live Session and constant-time verifies the decoded 32-byte MAC against the supplied `X-CSRF-Token` (strict base64url syntax/length); tokens from Session A are invalid for B. Expiry, logout revocation and inactive User invalidate T because Session authorization fails first. `GET /auth/csrf` may omit Origin and rejects explicit cross-site Fetch Metadata; browser must enforce no-store, no cross-origin credentialed CORS, no token in logs/storage. Unsafe requests require exact canonical Origin or same-origin Referer fallback only when Origin absent. **Key rotation:** new Sessions use the new key ID; keep old key securely available to validators for at most one 8h Session TTL after the last Session with old ID was minted, then retire. Unknown/missing key version fails closed; key exposure requires incident revocation/rotation plan, not a silent deploy.

**PostgreSQL limiter schema, OD-005-D (APPROVED design, PR #25 comment #6625521193):** use a scalar PostgreSQL `BYTEA` with an explicit **32-octet CHECK, not** `BYTEA[32]` (which denotes an array and does not enforce digest length). Proposed DDL for `AuthAttemptBucket`:

```
CREATE TABLE "AuthAttemptBucket" (
  "kind" TEXT NOT NULL CHECK ("kind" IN ('account', 'ip')),
  "keyDigest" BYTEA NOT NULL CHECK (octet_length("keyDigest") = 32),
  "windowStart" TIMESTAMPTZ NOT NULL,
  "attempts" INTEGER NOT NULL DEFAULT 0 CHECK ("attempts" >= 0),
  "inFlight" INTEGER NOT NULL DEFAULT 0 CHECK ("inFlight" >= 0),
  "updatedAt" TIMESTAMPTZ NOT NULL,
  PRIMARY KEY ("kind", "keyDigest", "windowStart")
);
CREATE INDEX "AuthAttemptBucket_windowStart_idx"
  ON "AuthAttemptBucket" ("windowStart");
```

The `kind` column is **TEXT with an explicit CHECK** (not pseudo-SQL `ENUM account/ip`); any equivalent Prisma migration must retain the PostgreSQL CHECK constraints and exact composite PK. This table definition is **a reviewable proposal, not a migration executed in Part E**. Use HMAC-SHA256 with a **separate secret** `AUTH_RATE_KEY` (32+ random bytes managed in Secret Manager) over domain-separated UTF-8 `account:<canonicalEmail>` or `ip:<trustedCanonicalIP>`; do not persist enumerable raw/hash-only email or client IP. The server derives trusted client IP from directly observed socket / **explicitly allowlisted ingress proxy**, never arbitrary client-provided `X-Forwarded-For`; deployment review must approve the proxy chain.

**Counter interpretation (OD-005-D, revised per Conversation comment 6624817784, APPROVED design in PR #25 reviewer comment #6625521193):** `kind='account'` stores `attempts` **= committed failed credentials only**, never successful logins; `kind='ip'` stores `attempts` **= every admitted login**, successful or failed. Account `inFlight` tracks admitted but unsettled credential checks, not failures, and prevents a burst from bypassing five failures. The account window is the UTC fixed quarter-hour chosen **at admission**; subsequent settle uses that same `windowStart`, even after wall-clock rollover. Only authorized PostgreSQL writes change buckets. Retain composite PK, digest-length CHECK, and consistent row locks.

**Reservation persistence for crash/retry safety:** an `AuthAttemptReservation(id UUID PK, accountKeyDigest BYTEA NOT NULL CHECK(octet_length(accountKeyDigest)=32), ipKeyDigest BYTEA NOT NULL CHECK(octet_length(ipKeyDigest)=32), windowStart TIMESTAMPTZ NOT NULL, admittedAt TIMESTAMPTZ NOT NULL, leaseUntil TIMESTAMPTZ NOT NULL, status TEXT NOT NULL CHECK(status IN ('pending','failed','success','abandoned')))` records each admitted verification. Account/IP bucket rows refer to the same fixed window and key digests; a reservation ID is internal, not accepted from the browser. An application instance holds an in-memory reference to its UUID for the one login operation, not an authorization token. Database cleanup is forbidden while pending reservations exist for its window. **Lease is 60 seconds after admission**, pending expiry is not permission to assume a password was correct: expired pending reservations are settled as `abandoned` **without increasing account failed count**, releasing account `inFlight`; IP total remains spent. Requests still executing after a lease expired must **fail without session issuance**, even if password verifies; they must not settle twice. Sweep stale reservations under row locks at admission/recovery, never with non-atomic read→write, and verify worker timeouts prevent long-running stale success.

**Exact atomic phases (no PostgreSQL row lock across Argon2):**

1. **Admit, short SERIALIZABLE or row-locked transaction:** resolve canonical email/verified trusted client IP and UTC 15-min window. Insert account and IP buckets using `INSERT ... ON CONFLICT DO NOTHING`; lock bucket rows in deterministic `(kind,keyDigest,windowStart)` order. Reconcile *expired pending* reservations for the account bucket under the same lock (decrement `inFlight` and mark `abandoned`, never lower failure count). Reject with generic 429 when **account.attempts + account.inFlight >= 5** or **ip.attempts >= 20**. Otherwise increment **account.inFlight by one** and **IP.attempts by one**, insert `pending` reservation, COMMIT. Even if IP is full, failed-account count does not change; a denied request cannot create Session. If a transaction retries due to deadlock/serialization conflict, retry the **whole transaction** with bounded backoff and unique reservation ID; never count the same reservation twice.
2. **Verify outside transaction:** run Argon2id (including dummy hash for unknown accounts), using bounded worker timeout. Unknown, wrong and inactive User all count as credential **failure**. A correct active User counts as **success**. Nothing may send a success cookie yet.
3. **Settle, short row-locked transaction:** lock the same admission-window account bucket, plus reservation row in a consistent order; require `pending`, unexpired `leaseUntil`, and the matching UUID/window. **Failure:** decrement `inFlight`, increment account `attempts` exactly once, mark `failed`, commit; return uniform 401. **Success:** decrement `inFlight`, do **not** increment account attempts, mark `success`, and insert durable Session **in that same transaction**; commit before 200/Set-Cookie. If reservation has already expired/abandoned, reject safe 503 without issuing a session even if credentials were valid. If a DB write fails, no success response/cookie; the remaining pending lease is recovered later. No duplicate settle or Session from replayed reservation.
4. **Recovery and windows:** after restart the next admission reconciles overdue `pending` records **under locks**. A reservation always settles in its original bucket even across window rollover; new requests use the new aligned bucket. Reconciliation never converts abandoned requests into a credential failure. Store recent expired-window records long enough to reconcile (e.g. >30 minutes) and keep old keys/rows until no pending records. A fixed window can admit up to five failures near the end and five in the next window: **not sliding-window protection**. This account lockout and temporary all-valid saturation tradeoff was approved under OD-005-D in PR #25 comment #6625521193; Part F verification remains separate.

**Privacy and failure behavior:** A rejected login returns the same 429 envelope for unknown, wrong, inactive and existing accounts. The service must perform the same keyed bucket lookup/admission logic for any syntactically valid email, whether a User exists or not; do not expose account existence through error body/headers or obviously different code paths. Use HMAC-SHA256 with a **separate secret** `AUTH_RATE_KEY` (32+ random bytes managed in Secret Manager) over domain-separated `account:<canonicalEmail>` and `ip:<trustedCanonicalIP>`; raw email/IP must not be written to the limiter. `X-Forwarded-For` is only trusted from explicitly allowlisted ingress proxies. Database outages fail closed with sanitized 503. **OD-005-D is an approved Part E design** (PR #25 reviewer comment #6625521193). Part F implements the protocol, with selected PostgreSQL integration and stress tests verified; the full AUTH-01..23 acceptance suite remains PARTIAL, and this text does not assert deployment approval.

**Bounds (OD-005-E):** JSON body <=4 KiB, email 3–254 Unicode code points after trim/lowercase and syntax validation, password 1–128 UTF-8 bytes without normalization, no unknown keys. Reject malformed/oversized input before authentication and never create a Session. Dummy Argon2 verification for unknown account avoids obvious quick-return enumeration; transport normalization and limits must be human-approved.

**Demo seed plan:** generate two independent Customer and two Tutor accounts, each password supplied from a local ignored test-only secret or generated at bootstrap then hashed; record only safe account identifiers and role. Seed inactive/expired/revoked Session cases for STS. Never commit password examples, seed known production passwords, .env, token, private key or database dump. No unreviewed administrator, registration, password-change or bulk-revocation features. Slot/Booking data and migrations belong to Issues #14–17 and are only cross-feature authorization dependencies.

> **Approval-state update (2026-11-04):** @Tanaboonnnnn expressly approved OD-005-D, including the temporary sixth-correct-login 429 tradeoff, in PR #25 comment #6625521193, with follow-up review confirmation in PR #25 review #5765005104. The approved Part E contract was merged into sprint1. This corrects historical pending-status text only; implementation and the AUTH-01..23 tests are independently tracked in Part F verification ledger.

---

### E.1.5 F-S1-01 Authentication Software Test Specification (tests.md)

> **Proposed E-0.1 / all cases NOT RUN.** Review alongside SDS, API, UI and Data before implementing Feature code. Issue #13 requires separately reviewed Part E and Part F PRs; planning tests cannot satisfy the implementation DoD.

#### Proposed harness and recorded evidence

Part F uses real PostgreSQL with applied migrations, generated non-committed test-only secrets, two independent Customers C1/C2 and two Tutors T1/T2, inactive User, expired/revoked Sessions and sessions A/B. API tests with Supertest/Vitest, selected real-browser Playwright/UI, DB row inspections and selected service/unit checks. Tool and package versions must be confirmed during implementation; the repo currently has **no app, installed test suite, migration, or test DB proven running**.

For each real run preserve exact command, source SHA, environment/Node/PostgreSQL/migration identity, sanitized request/result logs, PASS/FAIL/SKIP counts, expected vs observed DB Session rows and response fields. A mock-only authorization unit test **does not prove** UI→API→persistent DB. Domain rows and endpoints in Issues #14–17 are a **later shared integration gate**, never silently counted PASS at Part E stage.

#### Planned tests (no results claimed)

| ID | Trace identifiers | Setup and action | Expected API, database and UI result | Execution stage |
|---|---|---|---|---|
| AUTH-01 | FR-S1-01, FR-001, AC-S1-01/02, VC-01, VAL-001 | Login C1 and T1 using correct pre-provisioned credentials | 200 own trusted role; distinct HttpOnly cookies; two committed Session digest rows and active User join | Part F API/DB |
| AUTH-02 | FR-S1-01, AC-S1-03, VC-02, VAL-001 | Unknown email, wrong password, inactive user | Same generic 401 response; no authenticated cookie or new Session; no user enumeration | Part F API/DB |

| ID | Trace identifiers | Setup and action | Expected API, database and UI result | Execution stage |
|---|---|---|---|---|
| AUTH-03 | FR-S1-02, FR-002, VC-03, VAL-001/002 | Valid C1/T1 cookie, then forged role/userId headers/query/body | GET /auth/me returns only DB-derived own id/role; no hash, token, foreign identity | Part F API/DB |
| AUTH-04 | FR-S1-03, AC-S1-04, VC-04, VAL-001/002 | Save cookie A, get valid CSRF and Origin, logout, replay saved A | DB revokedAt committed; 204 only after commit; replay A denied 401 and no protected fields | Part F API/DB |
| AUTH-05 | FR-S1-03, VC-04, VAL-002 | Login twice A/B, logout A, request with B | A denied, B still valid, ordinary logout did not revoke B | Part F API/DB; OD-005 |
| AUTH-06 | FR-S1-02/03, VC-04/05, VAL-002 | Expired/revoked session or inactive User; restart app with persistent DB | Every stale credential denied; live B continues until expiry across restart | Part F API/DB |
| AUTH-07 | FR-S1-04, AC-S1-05, VC-05, VAL-002/036 | Anonymous calls current-user and protected Slot/Booking routes | 401 with no private payload or mutation; domain route checks run only after Issues #14–17 | Auth now / domain later |
| AUTH-08 | FR-S1-04, BR-S1-17/20, AC-S1-06, VC-06, VAL-002/036 | C1 forges Tutor Slot create or role=Tutor | Backend 403, no Slot row committed; UI hiding Tutor control insufficient | Cross-feature #14 |
| AUTH-09 | FR-S1-04, BR-S1-16/20, AC-S1-07, VC-07/31, VAL-002/036 | Tutor T1 guesses Tutor T2 schedule/Booking IDs | Privacy-safe denial/404, no T2 payload or mutation | Cross-feature #14/#17 |
| AUTH-10 | FR-S1-04, NFR-S1-01, VC-31/35, VAL-002/036 | Customer C1 requests C2 Booking ID/list | 404 foreign/missing indistinguishable, no private Booking fields | Cross-feature #16/#17 |
| AUTH-11 | NFR-S1-02/08, VC-35, VAL-034 | Inspect real User, Session and logs/tracked config | Argon2id salted hash, SHA-256 digest only, no plaintext passwords/bearer tokens or tracked secrets | Part F API/DB + Git |
| AUTH-12 | OD-005, FR-S1-03, VAL-002 | Inject Session INSERT fault at login or revocation UPDATE fault at logout | No success/session cookie before insert commit; no false 204/cookie clear if revoke fails; DB remains source of truth | Part F DB failure |
| AUTH-13 | OD-005, VAL-002/036 | Cross-origin login, missing/wrong CSRF/Origin on logout; later unsafe domain routes | 403 before mutation, no foreign fields, no new Session | Part F auth / domain later |
| AUTH-14 | OD-005, VC-04, VAL-002 | At expiresAt boundary, repeat logout, concurrent replay of old A | Exactly-at-expiry denied; revoked A never regains access | Part F DB/clock |
| AUTH-15 | AC-S1-01/02/03/04, NFR-S1-09 proposed; auth visual direction and WCAG 2.2 SC 1.4.11 | At **320/375/768/1280px** verify login, error, pending, Customer/Tutor success, expiry/reload/logout-uncertain, show/hide password, keyboard Tab/Enter, password-manager autofill/paste, delayed/duplicate submit and stale responses | No horizontal overflow; >=44x44px targets, normal-text contrast >=4.5:1; **visible form-input boundaries and functional non-text focus cues >=3:1 against adjacent white/warm surfaces** (review token `#77877B`), visible focus and screen-reader error announcement. Capture screenshots or human visual sign-off with reviewer/date/SHA; inspect anti-template criteria. **NOT RUN** | Part F UI / human visual review |
| AUTH-16 | BR-S1-20, FR-S1-04, VAL-036 | Test auth guard and owner predicates with client-supplied impersonation fields | Ignore client claims; service checks authenticated principal and owner-filtered DB predicates | Part F auth + domain later |

| ID | Trace identifiers | Setup and action | Expected API, database and UI result | Execution stage |
|---|---|---|---|---|
| AUTH-17 | OD-005-C, VAL-002/036 | Create Session A with `csrfNonce` and key version, same-origin `GET /auth/csrf` **without Origin**; repeat GET 10x with two tabs, including concurrent GET requests and a restarted API server; cross-site, anonymous and foreign credentials cases | **Identical decoded 32-byte MAC on every live A GET** with **zero Session writes** (compare before/after DB nonce/version/updatedAt), no `Set-Cookie` rotation, no-store; explicit `Sec-Fetch-Site: cross-site` 403; anonymous 401; no credentialed cross-origin CORS | Part F API/CSRF + real DB |
| AUTH-18 | OD-005-C, VAL-002/036 | Sessions A/B of same User; two tabs fetch A token, race two unsafe A POST requests against logout A while B stays live. Cross-check exact Origin, missing Origin + local Referer, forged/null Origin, missing both, cross-site Fetch Metadata, invalid/other-session CSRF | A token works for repeated eligible A POST until logout transaction commits; all requests using A **after revocation** 401 (even if valid MAC); A MAC fails on B; B's own token works. Explicit hostile combinations 403 before mutation; DB end state has only intended committed effects and revoked A; no unauthorized success | Part F API/CSRF + concurrency |
| AUTH-19 | OD-005-A/B, FR-S1-03, AC-S1-04, VAL-001/002 | Advance controlled authoritative time to 28,799s, 28,800s, 28,801s after creation; logout A while independent B exists; inject logout DB failure | Absolute 8h expiry boundary, no rolling refresh, A replay 401 after committed logout, B still live if unexpired, failure never falsely reports 204 | Part F clock/API/DB, requires OD-005 approval |
| AUTH-20 | OD-005-D/E, AC-S1-03, VAL-001/034 | Test 4KiB boundary/oversize JSON, unknown keys, email 2/3/254/255 code points and password 0/1/128/129 UTF-8 bytes. On separate fresh buckets run **three successful active-User logins followed by five wrong-password attempts** for the same account; then sixth invalid attempt. Run unknown/inactive account identities and 20 valid-shaped attempts from one trusted IP to distinct accounts | 400/413 does not create Session. **Three successes: account failed count stays 0, IP total rises 3**; five invalid attempts: account failed count rises to 5, IP total rises 5 more; next account attempt 429 (even with correct password), independent of prior successes. IP quota counts **all** 20 admitted requests and denies 21st with 429. Confirm generic failure/429 envelope, no existence leak, HMAC bucket keys, trusted proxy restrictions. OD-005-D and OD-005-E are **APPROVED design decisions** (PR #25 comment #6625521193), while Part F AUTH-20 test evidence still requires independent review | Part F API/DB, planned |
| AUTH-21 | OD-005-C, FR-S1-03, VAL-002/036 | Concurrent A GET/unsafe POST from two tabs, restart server, create separate Session B, advance to expiry, logout A; simulate key-version transition with approved old-key overlap | A token remains reproducible under same nonce/version across tabs/restarts; no GET writes or unexpected token invalidation. B token differs and A's token rejected on B; A rejected after expiry/logout. Old session version works until expiry under retained key; missing key version fails closed. Log Session nonce/key version/digest **metadata only**, never raw token/key | Part F API/DB/CSRF, planned |

| ID | Trace identifiers | Setup and action | Expected API, database and UI result | Execution stage |
|---|---|---|---|---|
| AUTH-22 | OD-005-D, VAL-001/034/036 | Synchronized **30–50 login requests on >=2 API instances** targeting same account/IP: all wrong, all correct and mixed passwords. **Use an Argon2 test barrier to hold exactly five all-correct requests in-flight** ( `account.failed=0` , `account.inFlight=5` , IP bucket 5), then submit a sixth **correct-password** request from a trusted IP with remaining IP quota. Release barrier, finish five successful verifications, and retry the sixth after settlement **within the same 15-min account window**. Also test multiple accounts on one IP, one account across IPs, forged X-Forwarded-For, crash/lease expiry and UTC rollover | **Temporary concurrency cap acceptance:** while `failed=0` and `inFlight=5` , the sixth correct login MUST return generic **429** `RATE_LIMITED` with **no Session/cookie and no extra account failure or IP reservation** (because admission rejects atomically). This is temporary *capacity saturation*, **not** five failed logins. Once the first five settle successfully, `inFlight=0` , account `failed` remains **0**; retrying the sixth **must be admitted** if IP total is below 20, credentials are correct and the lease/window is valid, and creates its Session after commit. UI may invite manual retry once outstanding work finishes; **no automatic background retry** and no promise of an exact wait interval. Record observed 429/retry sequence, before/after counters, responses, and IP/account bucket snapshots; retry during ongoing saturation may also receive 429. With 5 committed failures, retry is still 429 for that window even after inFlight=0. Across 30–50 requests, assert committed failed <=5 and `failed + inFlight <=5` at all times; success never increments failed; IP admits <=20 total (success + failure). Persisted reservations settle once, crash/60s leases reconcile without negative inFlight or stale Session; DB errors fail closed with sanitized 503. **The all-valid saturation availability tradeoff was expressly approved as a Part E design in PR #25 reviewer comment #6625521193.** Part F has run two-process all-correct/all-wrong HTTP stress and a permit saturation/retry DB case; deterministic Argon2 barrier, mixed-credential stress and forced-crash cases remain **NOT RUN**, so AUTH-22 remains **PARTIAL**. | Part F multi-instance/PostgreSQL stress, planned |
| AUTH-23 | AC-S1-01/02, FR-S1-02, VAL-001/002 | Seed C1/C2 and T1/T2 with distinct UUIDs. Sign in sequentially, reload, switch sessions, delayed old `/auth/me` response and logout, verify visible account reference | UI shows **current server-derived short UUID account reference + effective role** and not generic role alone; C1 != C2, T1 != T2 for selected fixtures, no old ID/role after reload, 401 or switch. No added email/displayName/PII. Correlate visible label with returned id/role and backend DB; if 8-hex suffix collides, require approved longer UUID display | Part F browser/UI, planned |

### Auth visual review checklist (Part F evidence, not current approval)

At **320, 375, 768, 1280 CSS px**, inspect typography Thai/English, form width/padding/button, labels and errors without overflow, responsive keyboard/touch affordances, screenshots for signed out/loading/invalid/Customer/Tutor/expired/logout-uncertain. Assert computed text contrast >=4.5:1, **non-text input border and focus cues >=3:1 against each adjacent background** (white and warm neutral), focus-visible and all action targets >=44px; screen-reader test must announce field and generic auth errors. Test password-manager autofill, paste, show/hide accessible name/pressed state and duplicate submission under slow network. Test current account reference+role for C1/C2/T1/T2 and clear on session switch/401/logout. Simulate stale `/auth/me` success arriving after a newer 401/logout, and network outage during logout; no old identity or false signed-out success. Require recorded **human visual review/sign-off** (name, date, SHA) or actual screenshot audit when UI exists; a documented style proposal is not evidence that rendered UI passes. Explicitly reject unapproved generic purple gradients/glass cards/glow blobs/3D decorations/fake schedules.

### Negative-response/privacy assertions

For each 401/403/404/429/503 failure inspect status and sanitized error envelope; assert no `passwordHash` , session or CSRF token, SQL/stack details, foreign identity or Booking data. A Set-Cookie **clearing** an invalid token is not a new authenticated cookie. Verify failed writes leave no new Session, Slot or Booking row. 403 wrong-role and privacy-safe 404 missing/foreign-row are distinct.

**Independent review / go-no-go checklist**

- [x] Per **@Tanaboonnnnn's PR #25 Conversation decision 6624817784**, **OD-005-A, B, C, E and Auth UI Direction are APPROVED as documented**. **OD-005-D APPROVED (PR #25 reviewer comment #6625521193)**, with reviewer-mandated **5 FAILED logins/account/15min (do not count successful logins)** plus **20 TOTAL attempts/trusted-IP/15min (count both success and failure)**. The human reviewer **expressly accepted the revised reservation/atomic settlement and recovery protocol** in PR #25 comment #6625521193; do not mistake design approval for a passed Part F implementation or all AUTH tests. Retain cross-origin/CSRF security, strict 4KiB/email/password bounds, API-safe errors and human review/merge gate. Author may not self-approve.
- [ ] Trace AC-S1-01..07, FR-S1-01..04, BR-S1-04/16/17/20, NFR-S1-01/02/07/08 and VAL-001/002/034/036 to named cases above, noting cross-feature tests are NOT RUN until domain routes exist.
- [x] Reviewed and approved Part E PR #25 was merged into `sprint1` before F-S1-01 Part F implementation. Reference PR #25 and approval comment #6625521193; does not indicate Part F tests have passed.
- [ ] On separate Part F branch from latest `sprint1`, write failing tests first, implement real UI/API/PostgreSQL, run actual tests, publish source SHA/results and open independent feature-code PR for human review. **Issue #13 remains open until implementation and review/merge evidence exist.**

> **Approval-state update (2026-11-04):** @Tanaboonnnnn expressly approved OD-005-D, including the temporary sixth-correct-login 429 tradeoff, in PR #25 comment #6625521193, with follow-up review confirmation in PR #25 review #5765005104. The approved Part E contract was merged into sprint1. This corrects historical pending-status text only; implementation and the AUTH-01..23 tests are independently tracked in Part F verification ledger.

---

## E.2 F-S1-02: Tutor Slot Availability & Scheduling

### E.2.1 F-S1-02 Tutor Slot Feature SDS (specification.md)

> **UX-only amendment proposed 2026-11-05 (owner-directed, peer acceptance pending):** Replace only the Tutor screen's former narrow form/list presentation with a NutTiew navy/orange 24-hour client-side calendar plus complete private chronological agenda. See dated UX decision, new UI contract, and UX-R1…UX-R6 STS.
> **Unchanged:** Auth/Customer visual design, Tutor role/owner/session/CSRF, exactly 60-minute future Offered Slot semantics, PostgreSQL race protection, strict POST + full-list GET contract, DTO fields, Asia/Bangkok timestamps, Option A no hour/day/horizon/grid constraints, safe uncertain-write reconciliation, and denial of cross-Tutor private data. Calendar day navigation is a pure read-only **client-side projection**, never a business rule or a new GET filter. This amendment has **not** yet received independent peer approval; the baseline Part E history below is preserved.

> **Mandatory sequential amendment gate (new UI direction):** this specification/UX decision/STS update is **Part E only**. Obtain @Chxtamos peer acceptance and merge this docs-only amendment into `sprint1` before opening a separate Part F Dashboard code PR from the updated base. This preserves the original Issue #14 two-PR rule.
> **Additional UX-R5 obligations:** initial/retry GET 503 must not assert an empty schedule; unknown count remains unknown until 200. On Logout click, hide account identity and all private Slots immediately and suspend protected interactions, while retaining the previous Tutor ID **only internally** for uncertain Session recheck. A confirmed Logout 204 or `/auth/me` 401 finalizes signed-out. Only a fresh same-Tutor `/auth/me` 200 **followed by fresh own-list GET 200** may restore the Dashboard and actions; otherwise remain hidden/blocked. Owner-selected 768px two-day / 1280px three-day / mobile agenda design, full-own-list summary and WCAG 2.2 AA target are detailed in dated UX decision.
> See UI contract and UX-R5-GET / UX-R5-LOGOUT STS. No backend/API/DB changes.

> **DOCS-ONLY NEW DASHBOARD CONTRACT / AWAITING PEER ACCEPTANCE.** Issue #14, owner @Tanaboonnnnn, reviewer @Chxtamos. **Historical initial Part E baseline:** `sprint1` `6fd3931` (PR #25/#26), from before Slot implementation. **Current PR #30 base:** `sprint1` `ed451be2ca3e366bdfc1900f4c4697aa7e50b6a0`, with the previously reviewed and merged Slot feature from PR #27/#28 already implemented and tested. This amended UI contract itself neither runs nor approves new Dashboard implementation; its review/merge precedes the *new* Part F UI code-only PR.

### Sources and traceability

Authority: Sprint 1 requirements Q02/Q03/Q04/Q06/Q29, FR-S1-04..07/18/19, BR-S1-02..06/11/12/17/18/20/21, AC-S1-08..14, VC/TEST-S1-08..14/37; SRS FR-004..007, BR-002/003/004/006/029/033/034/035 and OD-001..005/011/012; System SDS §§3.3/4/7.2; Feature Inventory; Traceability; Auth Part E and merged PR #26; AGENTS.

The Tutor (=Staff) owns their schedule. A Slot is one explicitly dated 60-minute `Offered` interval; Tutor Schedule is an owner-filtered read projection, **not** another mutable table. Publication state does not imply unoccupied after Booking exists.

### Scope

In Part F, an authenticated active Tutor creates exactly one valid **future** 60-minute Slot for **their own** identity and reads persisted own Slots on refresh/restart. The Sprint 1 API surface is **POST /api/v1/tutor/slots** and **GET /api/v1/tutor/slots** only: no individual-detail GET, pagination or filters. Any query parameter, including `?tutorId=other`, is rejected, not used to choose an owner. Reads use authenticated `principal.userId`, ordered by `startsAt,id` ascending, with the fixed safe DTO in HTTP contract. Reject malformed/past requests, wrong role/owner, conflicting same-Tutor offers and simultaneous overlapping creates. Adjacent same-Tutor Slots and identical hours from distinct Tutors are permitted. Use Asia/Bangkok business time.

**Out of scope:** Customer availability #15, Booking and Q05 60-minute new-Booking cutoff #16, protected Booking views #17, release #18, bulk/recurring slots, edit/delete/withdraw, cancellation, notifications, summary and payments. Future `Withdrawn` compatibility is not permission to implement Sprint 2.

### Invariants and user journey

1. Tutor logs in using existing Auth, opens My Availability and sees only own committed Slots.
2. Tutor chooses Bangkok calendar date and **any minute** (`HH:mm`, e.g. 13:17); UI derives end = start + 60m. API accepts strict RFC3339 instants with explicit offset/Z and **zero seconds + zero fractional seconds only** (optional 1–3 all-zero fractional digits). Reject nonzero seconds/fractions without rounding; this transport precision does **not** add an hourly/quarter-hour start grid. Server ignores any client role or owner.

3. API checks DB-backed Session/Tutor role, Origin and HMAC CSRF. Transaction locks User principal and rechecks active Tutor and future time **after contention** using DB clock; inserts `Offered` Slot under `principal.userId`.
4. PostgreSQL CHECK enforces exactly 60m; conditional GiST EXCLUDE prevents two currently `Offered` Slots of the same Tutor overlapping. A versioned **database trigger** rejects normal SQL UPDATE/DELETE/TRUNCATE in Sprint 1 and direct INSERT into non-`Offered` lifecycle. COMMIT before 201.
5. Rejected mutation rolls back and does not change existing Slot rows. GET returns owner-filtered durable data.

Use half-open intervals `[start,end)`: overlap iff `a.start < b.end AND b.start < a.end`. 13:00–14:00 + 13:30–14:30 conflict; 13:00–14:00 + 14:00–15:00 allowed. Two Tutors can each offer 13:00–14:00.

**SLOT-I1:** exactly 60m and immutable identity/owner/interval, enforced against ordinary direct SQL by the Sprint 1 trigger (all UPDATE/DELETE/TRUNCATE rejected). **I2:** no overlapping currently Offered Slots per Tutor, even under Race A. **I3:** active Tutor-only identity from Session. **I4:** strictly future by authoritative post-lock DB time; no Q05 Booking cutoff on Slot creation. **I5:** no partial writes/false success; restart durability. **I6:** UTC storage and Bangkok display. **I7:** no Withdrawn insertion/transition in Sprint 1; later approved Sprint 2 transition is one-way `Offered -> Withdrawn`, never `Withdrawn -> Offered` on an old ID, with separately verified migration and tests. Privileged DDL/superuser tampering is outside the ordinary DML invariant and must be controlled by DB privileges.

**Original Slot AC mapping — historical Part E verification plan**

The AC-to-VC mapping below was written as the **original Slot Part E test

plan**, before the Slot feature was implemented.** It is not a statement

that these tests remain unexecuted.** The merged Slot Part F work (PR #28)

already has recorded real API/PostgreSQL/browser executions, including

failures, reruns, exact commands and remaining limitations in the

Slot Part F verification ledger. Consult that

ledger and the relevant GitHub CI run for actual outcomes at their

respective commit SHAs; this historical table is a traceability map,

not a live PASS/FAIL dashboard.

The **new Tutor Calendar Dashboard amendment** and its

`UX-R1…UX-R6`, `UX-R5-GET-01/02` and `UX-R5-LOGOUT-01/02` acceptance

checks are separate **planned Part E requirements** in

the amended STS. This docs-only PR neither implements nor

executes those new Dashboard/Logout checks; subsequent Part F code and

independent peer review remain necessary. Human WCAG 2.2 AA signoff

is likewise **NOT RUN**.

| AC | Expected | Test |
|---|---|---|
| AC-S1-08 | One future owned 60m Slot persisted/read on refresh | VC-S1-08/14 |
| AC-S1-09 | Same-Tutor positive overlap rejected | VC-S1-09 |
| AC-S1-10 | Same-Tutor adjacency accepted | VC-S1-10 |
| AC-S1-11 | Different Tutors same hour accepted | VC-S1-11 |
| AC-S1-12 | Invalid/past input rejected without mutation | VC-S1-12 |
| AC-S1-13 | Race A: never two overlapping committed Offered rows | VC-S1-37 |

| AC | Expected | Test |
|---|---|---|
| AC-S1-14 | Browser timezone cannot change Bangkok appointment | VC-S1-13 |

Related product validations: VAL-002/003/004/005/012/013/031/036. Cross-feature Auth cases AUTH-07/08/09/16 become testable via real Slot routes in Part F.

### Decision record — scope owner direction and outstanding approvals

**Recorded 2026-11-04 (Asia/Bangkok).** The Issue #14 requester/owner explicitly selected **Option A** for the **Sprint 1 implementation scope** in the project conversation. This is **owner direction**, not independent stakeholder/instructor approval and not proof of 24/7 Tutor availability. Peer reviewer @Chxtamos must explicitly accept/reject this scoped no-extra-restriction decision in GitHub; stakeholder policy remains unresolved until a separate approval or requirements revision.

| Decision | Sprint 1 include/exclude decision from owner | Approval status / future change gate |
|---|---|---|
| **OD-001 / TBD-S1-01** working days/hours/holidays | **EXCLUDE** any extra hours, weekday or holiday restriction; include strictly future, valid 60m Slot rule only. | Owner chose A 2026-11-04; **peer review pending**; no 24/7 stakeholder promise. New restriction requires reviewed Q/FR/BR/AC/VC update. |
| **OD-002 / TBD-S1-02** maximum advance horizon | **EXCLUDE** a new 7/14/30-day or other business maximum; include only confirmed future-time check. | Owner chose A 2026-11-04; **peer review pending**; stakeholder maximum policy still unresolved. |
| **OD-003 / TBD-S1-03** start-minute grid | **EXCLUDE** :00-only, quarter-hour and any other start grid; **include** every `HH:mm` minute as valid if the Slot otherwise meets rules. | Owner chose A 2026-11-04; **peer review pending**; minute-level **transport precision** (zero seconds/fractions) is a separate, proposed engineering validation, not a business grid. |
| **OD-004 / TBD-S1-04** Tutor read interface | **PROPOSE** POST+own-list GET only, no detail GET or list filtering/pagination in Sprint 1; reject all query params, order `startsAt ASC,id ASC`, allowlist `id,startsAt,endsAt,lifecycle,occupancy`, empty array allowed. | Proposed engineering contract **pending @Chxtamos review**; Customer discovery #15 has separate interface. |
| **OD-005 / TBD-S1-05** transaction/error/security | **PROPOSE** `SERIALIZABLE` + Tutor User lock, DB CHECK/GiST + Sprint 1 immutability/lifecycle trigger, bounded transient retries, shared Auth CSRF/Origin and error envelope. | Proposed engineering contract **pending @Chxtamos review**; actual migrations and race tests are Part F only. |
| **OD-011/012** final Master/Theme 1 | No additional claim. | Final instructor/TA specification and formal theme assignment **unverified**; must not be treated as sign-off. |

**Changes after this decision:** additions to working hours, horizon or minute grid need a dated stakeholder/team rule, updated requirement IDs and fresh peer review; neither a form default nor an API validator may silently introduce them.

### Definition of Done / two-PR gate

**Part E:** five cross-linked versioned docs (UI, HTTP, data, STS, this SDS) with decisions and Race A proof plan. Human @Chxtamos review + approved documentation PR merged into `sprint1` before feature code.

**Part F:** separate feature branch from latest `sprint1`; TDD RED→GREEN, real UI→Express→PostgreSQL, native constraint/transaction, negative auth/privacy, synchronized Race A, restart and fault tests, actual command/result/SHA evidence and peer-reviewed code PR into `sprint1`. No fabricated PASS and no direct main/sprint1 pushes. `sprint1→main` release belongs to #18.

---

### E.2.2 F-S1-02 Tutor Availability UI Specification (ui-spec.md)

> **2026-11-05 proposed visual-contract amendment (pending peer review):** The feature owner selected the @Chxtamos Tutorix-inspired **NutTiew Tutor Calendar Dashboard** as the new Tutor presentation. See dated UX decision. The older approved form+list content below remains a *historical Part E baseline*; its Auth palette and prohibition on calendar presentation are **proposed to be superseded for the Tutor view only**. The HTTP/DB/security/UTC/ ownership/business-rule contract is **not** being superseded. Do not label this amendment peer-approved until review actually occurs.

> **Review sequencing:** this is a new **docs-only Part E proposal**; it must receive peer approval and merge into `sprint1` before the separate Tutor Dashboard Part F implementation PR. Original Part E PR #27 / Part F PR #28 remain historical, previously merged baselines. A combined docs-and-code PR is not a substitute for this gate.

**Amendment: Tutor Calendar Dashboard candidate**

- Desktop uses a navy `#202B44` sidebar, a bright canvas `#F7F8FB`,

white surfaces, orange `#F47736` call-to-action with the **explicit

contrast-safe foreground/border/focus pairing below**, and

deliberate dark text/focus. These tokens are **scoped to the Tutor

dashboard**; existing Auth Login/Customer palette remains unchanged.

- **Required CTA pairing (WCAG 2.2 AA design target, not human signoff):**

button fill `#F47736`, **dark-ink label/icon** `#172137` (measured

**5.76:1** against the orange fill), and a **1 CSS px solid border

`#D96123`** to distinguish the component from adjacent surfaces

(**3.48:1** against canvas `#F7F8FB`; **3.69:1** against white).

The keyboard focus indicator is **3 CSS px solid `#AA4519` with

`outline-offset: 3px`** outside the button/border, contrasting

**5.53:1** with the canvas or **5.87:1** with white. These values

are calculated from the specified sRGB tokens; Part F must verify

computed browser colors, focus visibility, hover/disabled/error

states and adjacent backgrounds. **Do not use white text on

`#F47736` (only 2.79:1), or the unbordered orange fill as the

only visible control boundary** (2.62:1 against canvas, 2.79:1

against white). This pairing does not by itself certify WCAG AA.

- Sidebar contains only functional ตารางเวลาของฉัน, บัญชีของฉัน

and ออกจากระบบ. Account data and role come from trusted `/auth/me`.

Do **not** construct fake Students, Revenue, Messages, Bookings,

notifications, learner names, courses or rescheduling.

- บัญชีของฉัน links to the in-page `#account-details` section,

not a new route or editable profile. That section displays exactly

**Tutor** role and a shortened account ID derived from trusted

`GET /api/v1/auth/me` `user.id` and `user.role`; it must not surface

unverified login-form email or invented profile fields. Hide the

section while Logout is pending or uncertain, along with all other

identifying UI.

- Header: ตารางเวลาติวของฉัน, role/account reference, `Asia/Bangkok`

and `+ เพิ่มช่วงเวลาติว` that takes the user to the inline form.

- Calendar: accessible **24-hour** local timeline, **3 days at

widths >1060px **(including desktop 1280px),** 2 days at 621–1060px**

(including tablet 768px). At **320/375px and all widths <=620px**,

the complete Agenda replaces the timeline. Responsive breakpoint

checks must include 620/621 and 1060/1061px. Slot cards use genuine

Offered records and computed minute-exact offsets (no snapping), including 13:17, 13:59,

and a 23:30→00:30 date crossing. Hour marks are presentation ticks.

Previous/Next/Today/day picker only change local view state and never

append filters to `GET /api/v1/tutor/slots`.

- Mobile 320/375: no horizontal overflow; use a complete **agenda/list

fallback **instead of a squeezed timeline. The** รายการ Slot ทั้งหมด**

agenda is **available after successful authenticated GET 200** and

preserves `startsAt ASC, id ASC` for all returned private Slots,

including dates outside the current calendar. Hide the Agenda on

initial load/GET error, Logout pending/uncertain or account switch;

do not silently paginate, crop or hide other times when authorized.

- **Counts must not be conflated:** the summary ช่วงเวลาที่เปิดไว้ทั้งหมด

is the total number of Slots from the **full unfiltered own-list GET

across all dates**, unaffected by Prev/Next/Today/day selection.

ช่วงที่แสดง counts distinct committed own Slots that intersect

the displayed Calendar viewport only; a Slot spanning midnight is

counted once per viewport even if rendered in two day columns.

Both metrics are **unknown** `–` **until a successful GET 200**, and

must never falsely show zero during GET/Retry failures.

- The create form retains native labeled Bangkok date and any-minute

time, derived read-only +60-minute end, POST security, real loading,

conflict (409), invalid (400/422), and uncertain 503/network states. After success or ambiguous write, reconcile with owner-only GET. The old T1 authenticated 200 must never reappear after T2 login.

- **Read-side state machine:** until the authenticated own-list GET returns 200, the schedule is **unknown**, not empty. Initial load shows progress, initial GET 503/network failure or retry 503 shows an accessible error with a working โหลดอีกครั้ง control, **hides** the empty/full Agenda and Calendar, and shows unknown `–` instead of an unverified zero summary. Only a confirmed 200 + `data: []` may show ยังไม่มีช่วงเวลาติวที่เปิดไว้ and total zero; a confirmed 200 with rows restores all committed own Slots. These rules apply to both initial load and later refresh failures and must prevent stale old-Tutor data from reappearing.
- **Auth/logout guard inherited from F-S1-01 and owner decision 2026-11-06: **starting** synchronously on Logout click**, unmount or hide the Tutor account reference, signed-in status, private Slot cards, Calendar and Agenda. Immediately block protected actions (including the create form, header CTA and any pending CSRF-to-POST flow), invalidate stale UI request generations and prevent any **new** Slot POST after Logout begins. Any POST sent *before* Logout may already have committed; do not claim a server rollback from UI alone. Retain the prior Tutor ID **only in internal non-rendered state**.
  **UI hidden does not equal Session revoked**: only confirmed Logout HTTP 204 or a fresh `/api/v1/auth/me` 401 finalizes signed-out status. If Logout returns network/503/timeout uncertainty, private data stays hidden and protected actions stay blocked; show an accessible ลองออกจากระบบอีกครั้ง / ตรวจสอบเซสชัน recovery path.
  A fresh `/api/v1/auth/me` HTTP 200 with **exactly the same Tutor ID and Tutor role** permits a *new* authenticated own-list GET; restore the Dashboard and protected interactions **only after that GET succeeds**. A 401 clears internal identity, a different identity cannot unlock prior Tutor data, and recheck 503/network keeps the Dashboard hidden/blocked. Old T1 authorized HTTP 200 responses must never repaint private content after Logout or account switch.
- **For state consistency:** `suspended/uncertain` is a third presentation state distinct from both `authenticated/visible` and

`confirmed signed-out`. Do not display authenticated identity while suspended; do not falsely claim Logout succeeded after an unknown response. The earlier Part E state table below is historical and the amended logout rows directly below supersede its old generic "Logout or account switch" wording for the new Tutor Dashboard.

- Required new test IDs: **UX-R1…UX-R6** from the dated decision. Add screenshots from *real DB-backed browser sessions* at 320, 375, 768 and 1280, and keyboard/contrast evidence. The new design targets **WCAG 2.2 Level AA **(all applicable A/AA criteria), measured at** 4.5:1 normal text / 3:1 large text**,** 3:1 non-text components and required visual states**, visible/unobscured keyboard focus, AA **24x24 CSS px minimum target or normative exceptions** with a stricter project **44x44px primary-control** target, and usable 320 CSS px reflow without unexpected two-axis scrolling. Record automated samples separately from complete manual assessment. For read-side failure and logout guard tests, use **UX-R5-GET-01/02** and **UX-R5-LOGOUT-01/02** in STS. **Human WCAG 2.2 AA signoff remains NOT RUN until a person performs it**.

> **PROPOSED DASHBOARD UX AMENDMENT / NO NEW IMPLEMENTATION IN THIS DOCS-ONLY PR.** The existing Slot API, DB and Auth implementation from merged PR #28 already exists. The new dashboard/logout acceptance cases in this amendment are *planned*, not executed or accepted by this documentation alone. Issue #14, @Tanaboonnnnn owner, @Chxtamos reviewer. See SDS and owner decision, HTTP, Data, STS, Auth UI direction.

### Screen and navigation

"My Availability / ตารางเวลาติวของฉัน" is an authenticated Tutor-only view. Use the current `GET /api/v1/auth/me` trusted DB-derived role and session identity; do not invent a role selector. Reuse approved NutTiew look from Auth Part E: warm neutral background `#F6F4EF`, graphite text `#262B28`, restrained pine accent `#285C4B`, Thai/English readable typography, visible focus and minimal functional layout. Keep the Tutor screen separate from existing Auth-only `apps/web/src/main.tsx`; avoid unrelated Auth redesign.

**Minimum surface:** a create form, a derived 60-minute end preview, and a chronological **full own-list** of current Tutor's persisted Slots ordered `startsAt ASC,id ASC`. The Sprint 1 UI calls **only POST /api/v1/tutor/slots and GET /api/v1/tutor/slots**. No detail view/`:id` route, filters, pagination, date-range selector, drag-and-drop week calendar, bulk/recurring generation, delete/edit/withdraw or Customer Booking UI in #14. A list is sufficient if it meets accepted flows; this does not establish a future unlimited-scale guarantee.

### Form controls

| Control | Visible behavior | Validation / authority |
|---|---|---|
| Role/account display | Latest server-issued Tutor identity; authorized route | Display is not backend authorization |

| Control | Visible behavior | Validation / authority |
|---|---|---|
| Bangkok calendar date | Labeled `YYYY-MM-DD` selection | **Owner chose Sprint 1 Option A**: no extra workdays, holidays or max advance horizon (OD-001/002); still strictly future |
| Start time | Labeled `HH:mm`, Bangkok civil time, **any minute** such as 13:17 | No top-of-hour/quarter-hour grid (OD-003). UI has minute precision only; API seconds/fraction must be **zero**, not silently rounded |
| End time | Read-only start + exactly 60m, including cross-midnight day rollover | Client cannot submit arbitrary duration/end |
| Create Slot | Visible pending state; prevent accidental double-click | Database remains authoritative for concurrent writes |
| Schedule rows | Bangkok date/time, lifecycle `Offered`, safe derived `occupancy` | No other Customer names/emails; exactly the HTTP DTO allowlist. Offered does not imply Customer-bookable under Q05 |
| Error feedback | Keep user input and show actionable safe error | Never show false success after 409/422/503 |

**Timezone and precision contract:** combine Bangkok civil date and `HH:mm` explicitly with `Asia/Bangkok` or a verified `+07:00` offset; construct a valid RFC3339 timestamp with seconds `:00`, optional fractional `.000`, and explicit offset; convert to UTC `.000Z` before POST. **Do not** rely on `new Date('YYYY-MM-DDTHH:mm')` device-local parsing. Format returned UTC with `Intl.DateTimeFormat` and `timeZone:'Asia/Bangkok'` or a tested equivalent. 13:00:00 and 13:00:00.000 are accepted, **13:00:30 and 13:00:00.500 rejected without rounding** by API even when sent outside this form. Any HH:mm minute (13:00, 13:17, 13:59) is allowed if otherwise future/valid. Test UTC/Tokyo and cross-midnight 23:30→00:30 Bangkok.

### Observable UI states

| State | Behavior |
|---|---|
| Auth pending | Do not show private schedule until `/auth/me` confirms Tutor |
| Loading | Display status, not fake appointments |
| Empty (authenticated own-list GET 200 with `data: []` only) | Show "ยังไม่มีช่วงเวลาติวที่เปิดไว้" and usable creation form; never infer empty from a failed/unknown GET |
| Editing | Show selected Bangkok start and derived end |
| Creating | Clear pending indicator, one request in flight; no phantom success |
| 201 Created | Show committed confirmation and refresh own-list from server |
| 409 Overlap | "ช่วงเวลานี้ทับกับเวลาที่เปิดไว้แล้ว"; retain fields, focus error |
| 400/422 Invalid | Field-linked invalid/past message, no Slot added |
| 401/403 | Clear private list, signed-out or access denied; no unauthorized data |
| 403 CSRF/Origin | No success; recover session/CSRF where allowed |
| POST 503/network timeout | Indeterminate write outcome: show uncertainty, refresh own-list before a duplicate submit; GET 503 is a separate read-side unknown state, not empty |
| Logout starts (new Tutor dashboard amendment) | Immediately hide old account ID, signed-in status, Calendar and Agenda; block Create and any new protected POST synchronously, invalidate old requests; retain prior Tutor ID internally only for recheck, do **not** assert signed-out yet |
| Logout response 503/network/timeout | Keep all private surfaces hidden and protected actions blocked; announce outcome unknown and expose retry Logout / check Session, not fake Logout success |
| Fresh same-Tutor `/auth/me` 200 after uncertain Logout | Re-read complete authenticated own-list GET; restore Tutor identity, Calendar, Agenda and actions **only after successful owner GET**. Failed own-list GET retains privacy/blocked state |
| Fresh `/auth/me` 401 or confirmed Logout HTTP 204 | Finalize signed-out, clear internal identity and private data, prevent stale T1 responses |

| State | Behavior |
| --- | --- |
| Different account or failed `/auth/me` recheck | Never unlock the previous Tutor; clear or retain only hidden internal comparison state as appropriate, all private surfaces hidden and protected writes blocked |
| Account switch without Logout | Invalidate previous owner generation, immediately hide old identity and Slots and use only the newly verified account's authenticated own-list |

The current Auth UI has request-generation guards for stale `/me` responses. The new Tutor view must use equivalent lifecycle cancellation/generation checks. **Required privacy scenario:** T1 GET starts but its response is held; the user logs out or switches to T2; then release the old T1 success response. The UI must **never re-display T1 Slots** in T2's/current signed-out view; authenticated owner-list GET for T2 must include only T2 rows. This is a planned deterministic E2E negative, **not** a passed test.

**Accessibility / responsive acceptance**

- 320/375px: usable single-column form/list; 768/1280px: readable restrained page width; no horizontal overflow.
- Labeled date/time inputs, `aria-invalid` and associated `aria-describedby` messages, accessible alert/status updates and keyboard order.
- At least 44x44px interactive targets, visible `:focus-visible` and adequate contrast checked rather than assumed. No color-only conflict message.
- Avoid faux calendars/testimonials, generic hero pages, unnecessary visual ornament or decorative random UI.
- Part F evidence: real screenshots at 320/375/768/1280, manual keyboard/contrast check with reviewer/date/SHA, UTC vs Bangkok browser test, create/error/empty/refresh/restart flows.

**Review decisions**

**Decision state:** owner @Tanaboonnnnn selected Option A on 2026-11-04 for **Sprint 1 scope only**: no additional workday/hour, advance horizon or start-minute grid constraint; not a 24/7 stakeholder claim. The minute-level input/transport precision is an independent engineering validation proposal. Peer reviewer @Chxtamos must accept/reject that policy scope and the **no-detail, no-filter, no-pagination own-list**/DTO/ordering contract, session failure recovery and shared Auth visual design. No UI or automated test result is claimed by this document.

---

### E.2.3 F-S1-02 UX Decision Amendment — Tutor Calendar Dashboard (ui-decision-2026-11-05.md)

**Decision owner:** @Tanaboonnnnn (requested in conversation on 2026-11-05).

**Visual direction source:** @Chxtamos's detailed *Tutorix-inspired Calendar Dashboard*

change-request text, reproduced in the owner's accepted task instructions;

the screenshot itself is **not available as a verifiable GitHub artifact**.

**Review status:** owner-selected design direction; **this is a docs-only

Part E amendment proposed for independent peer acceptance and merge before

any new Part F dashboard implementation PR may be accepted**. It does not

retroactively validate work previously started in a mixed docs/code PR.

**Baseline:** original Slot Part E PR #27 and Part F PR #28 (merged into `sprint1`

at `ed451be2ca3e366bdfc1900f4c4697aa7e50b6a0`).

**Two-PR gate for this new visual change:** review and merge the *new*

docs-only UX amendment into `sprint1` first. Only then branch the

Tutor Dashboard implementation from that updated `sprint1` and open a

separate code PR. The earlier combined PR #29 did not satisfy this

sequencing requirement and cannot count as the accepted Part E gate.

**Superseded visual layout, retained domain contract**

The previous *Tutor screen* used the approved Auth warm-neutral/pine palette and a narrow create-form-first full-list layout. Replace **only the Tutor presentation** with a navy/orange scheduling dashboard: a genuine sidebar, account details, a 24-hour date timeline with **three day columns at 1280px and wider**, two day columns at 621–1060px** (including 768px), read-only arbitrary-minute 60-minute Slot blocks, an inline create panel, and a complete all-slots chronological agenda. **At 320/375px and up to 620px**, replace the timeline with the full accessible agenda.

All navigation is real. No fake Students, Revenue, Messages, Bookings, notification counts, subjects, learners, reschedule or demo appointments.

**Not superseded:** the F-S1-01 Login/Auth appearance, trusted identity, session handling, the F-S1-02 API and DB contract, immutable Slot semantics, the Option A absence of working hours/advance-horizon/grid limitations, UTC transport/Asia-Bangkok display, cross-midnight precision, full private own-list, network-uncertainty reconciliation and stale-success protection.

**Owner-selected CTA contrast pairing (Tutor view only):** use orange `#F47736` with dark text/icons `#172137` (**5.76:1** on orange), `#D96123` border (**3.48:1** against `#F7F8FB` canvas; **3.69:1** against white), and a `3px` `#AA4519` keyboard focus outline offset outward by `3px` (**5.53:1** against canvas, **5.87:1** against white). Do **not** use white text on orange (**2.79:1**) or rely on the orange fill alone for component visibility (**2.62:1** against canvas). Ratios are token calculations for the design contract, **not evidence of a complete WCAG audit**; verify rendered styles and states in Part F. This does not recolor the previously approved Auth/Customer UI.

**Ownership and display boundaries**

- Only `GET /api/v1/tutor/slots` (full owner DTO list, no query) and `POST /api/v1/tutor/slots`; calendar navigation is in memory and never changes server-side selection. The agenda shows **every** returned Slot.
- **Functional account link:** `บัญชีของฉัน` navigates to the in-page `#account-details` section, which displays **only the Tutor role and a shortened account ID supplied by trusted `/api/v1/auth/me`**. No separate profile route, profile-edit capability, email pulled from a

login form, or additional personal fields are authorized by this scope.

- Calendar day positions use **real minute offsets**, not 15/30/60-minute snapping. The hour grid marks time visually but imposes no creation rule. Days cover 00:00 through 24:00, with cross-midnight slices appearing on their respective dates.
- The **overview total** counts **every persisted Slot in the complete authenticated Tutor owner-only GET response across all dates**, even outside the current Calendar viewport. It never changes when the user navigates days. The Calendar-only **"ช่วงที่แสดง"** metric is a separate number: count of distinct own Slots intersecting the currently displayed day columns (a cross-midnight Slot counts once per viewport, not twice per rendered day fragment).
  Both numbers derive from real returned Slots only **after successful GET**. On initial GET failure/retry failure show a retryable error, suppress Calendar and Agenda (including false empty claims), and display an unknown count ( `–` ). Empty means confirmed **200 with** `data: []` only. The UI must label `Offered` as an opened time, **not** as a confirmed Customer Booking. Until Issue #16, occupancy is the existing safely derived `Unoccupied`.
- **Owner-selected logout privacy (2026-11-06):** from the instant Logout begins, **hide the account identity/status and all private Slot cards, Agenda and Calendar** and block protected Slot mutation controls. Retain the previous Tutor ID **only in internal non-rendered state** for comparison against a later `/api/v1/auth/me` response; this hidden state is **not** a claim that the server Session was revoked. If Logout is uncertain (503/network/timeout), show an accessible retry-logout/check-session path with private content still hidden. Restore access **only** after a fresh authenticated `/auth/me` 200 confirms the **same Tutor ID** and a fresh owner-list GET succeeds; 204 Logout or `/auth/me` 401 finalizes signed-out state. If a recheck fails or confirms another identity, continue to block the old Tutor.
- No new API parameters, endpoints, schema, booking, withdrawal, editing, deletion, bulk operation, recurrence, working-hours rule, or role selector.

**Accessibility and acceptance**

The redesign targets **WCAG 2.2 Level AA** across all applicable Level A and AA success criteria, including:

normal text contrast **>=4.5:1**, large text **>=3:1** (SC 1.4.3),
non-text UI controls/necessary state indicators **>=3:1** against
adjacent colors (SC 1.4.11), complete keyboard operation (2.1.1),
visible keyboard focus (2.4.7) not entirely obscured (2.4.11),
target sizes **>=24x24 CSS px or the defined AA exceptions**
(2.5.8), and functional **320 CSS px reflow without two-dimensional
scrolling** except for intrinsic two-dimensional content (1.4.10).
**Project rule:** actionable primary controls meet the stricter
**44x44 CSS px** target. Verify labels, status text,
errors and color-independent meaning; reduced motion must not hide
focus or essential information. This is an acceptance **target, not a
claim of conformance**. Automated samples do not substitute for a
complete human keyboard/contrast/reflow accessibility signoff.
Color is never the sole Slot status indicator. The 24-hour timeline is a *visual
projection*: every Slot remains readable in its accessible agenda row.
**UX-R1:** desktop navy sidebar, white canvas, orange CTA with the
specified dark-ink/border/focus contrast pairing,
real Tutor role/ID and no fictitious navigation or figures.
**UX-R2:** real Slot clock placement at arbitrary minutes (13:17, 13:59);
cross-midnight and all-day (24-hour) access without work-hour restrictions.
**UX-R3:** date navigation locally changes only the calendar; full own-list
agenda remains complete, ordered, and owner-private.
**UX-R4:** at 320/375px render full mobile agenda, at 768px
render a **two-day timeline**, at 1280px render **three days**;
test 620/621px and 1060/1061px breakpoints; verify keyboard labels,
WCAG 2.2 AA text/non-text contrast, visible unobscured focus,
targets and 320px reflow without horizontal overflow.
**UX-R5:** unchanged secure create/CSRF/GET refresh, 409/422/503 recovery
and old-Tutor delayed-200 safety. Specifically, GET 503 then failed retry
must not display empty state, and authorized GET 200 restores genuine
nonempty/empty own-list. **Logout pending/uncertain** immediately hides
private identity and Slots and suspends protected mutations, retaining
the old Tutor ID internally only for safe comparison. It must provide
an actionable retry/check-session path and only re-enable on a fresh
`/api/v1/auth/me` 200 confirming the same Tutor plus a successful fresh
owner-list GET; 204/401 finalizes signed-out without falsely claiming

logout success after 503.

**UX-R6:** evidence must be from actual app, real PostgreSQL and Browser,

not a mock screenshot; include automatic checks and explicitly distinguish

human accessibility verification not performed.

**Approval gate:** the owner has selected this direction. @Chxtamos must

accept and merge **this docs-only Part E amendment first**. No new

implementation PR can claim the pre-code gate is met before that merge.

Human WCAG 2.2 AA/keyboard/contrast/reflow signoff is a separate

**NOT RUN** manual gate, not implied by passing Playwright.

---

### E.2.4 F-S1-02 Slot HTTP Contract (api-spec.md)

> **REVISED PROPOSED CONTRACT / NOT IMPLEMENTED / independent peer review required.** Issue #14. Cross-references: Feature SDS, UI, Data, STS, Auth Contract. Engineering choices below require @Chxtamos review; they are **not** instructor-approved endpoint signatures.

#### Transport, authorization and ownership

Use the existing same-origin Express `/api/v1` JSON stack, DB-backed `requireSession`, `requireRole('Tutor')`, `getPrincipal(req)`, safe error envelope, per-request requestId and Cache-Control:no-store from PR #26. All Slot writes derive `tutorId` from trusted `principal.userId`; never accept client owner/role/lifecycle/end/duration. Restrict own-list SQL by `tutorId=principal.userId`.

Unsafe POST requires **canonical Origin/Referer and Sec-Fetch-Site checks plus current Session-bound X-CSRF-Token** obtained from `GET /api/v1/auth/csrf`. Do not duplicate an inconsistent CSRF implementation; small reusable guard may be extracted from Auth while retaining old Auth behavior/tests. Browser cookies remain HttpOnly.

Request timestamps require RFC3339 explicit offset or Z; do **not** interpret timezone-free date strings using browser device zone. **Minute-level protocol:** seconds **must be 00**, fractional seconds may be absent or **1–3 zero digits** ( `.0` , `.00` , `.000` ); reject any nonzero seconds/fractions without rounding, and reject malformed calendar dates, offsets and missing seconds. This is a **technical precision boundary**, not a business minute grid: 13:00, 13:17 and 13:59 are all valid proposed starts if future. DB stores UTC instants and API returns ISO UTC `Z` with `.000`; UI displays Asia/Bangkok.

**Positive/negative wire examples (proposed):**

| Submitted timestamp (illustrative future date) | Decision / normalized instant |
|---|---|
| `2026-11-06T13:00:00+07:00` or `2026-11-06T13:00:00.000+07:00` | Accept; `2026-11-06T06:00:00.000Z` |
| `2026-11-06T13:17:00+07:00` | Accept; `2026-11-06T06:17:00.000Z` (no top-of-hour grid) |
| `2026-11-06T13:00:30+07:00` | Reject 400 INVALID_INPUT; no silent floor/round |
| `2026-11-06T13:00:00.500+07:00` | Reject 400 INVALID_INPUT; no silent floor/round |
| `2026-11-06T13:00+07:00` , `2026-02-30T13:00:00+07:00` , timezone-free string | Reject 400 INVALID_INPUT |

The examples describe **precision**, not approval for those dates to be within Tutor working hours. All accepted timestamps must additionally pass the **strictly-future DB-time test**.

### Proposed endpoints

| Method/path | Request | Success | Enforcement |
|---|---|---|---|
| `POST /api/v1/tutor/slots` | Exactly `{"startsAt":"2026-11-06T06:00:00.000Z"}`; no query parameters | 201 committed Slot DTO | Session, Tutor, Origin, CSRF, future at DB decision, exactly 60m, native exclusion |
| `GET /api/v1/tutor/slots` | **No** query parameters, including `tutorId` | 200 own-only array (empty `[]` valid), ordered `startsAt ASC,id ASC` | Session, Tutor, SQL `WHERE "tutorId"=principal.userId` |

**OD-004 design decision proposed for approval: No** `GET /api/v1/tutor/slots/:id` in Sprint 1; no list filter, date range, pagination, cursor or query-based owner selector. An unknown query parameter on POST or GET (notably `?tutorId=T2`) returns **400 INVALID_INPUT** with no data. Unregistered detail paths do not retrieve a foreign/missing Slot and return 404 (no detail endpoint exists); their response body is not a defined Slot-detail DTO. The full own-list is a **Sprint 1 minimum**, not an unlimited scalability/retention guarantee; introduction of pagination or detail access requires a separately reviewed interface revision. Customer browse/read functionality is owned by #15, and protected Booking reads by #17.

### Example request

```
POST /api/v1/tutor/slots
Origin: http://localhost:5173
Content-Type: application/json
Cookie: nuttiew_session_dev=<opaque>
X-CSRF-Token: <session-bound>

{"startsAt":"2026-11-06T06:00:00.000Z"}
```

This is 13:00 Bangkok, ending 14:00 Bangkok, for illustration only.

### Example response after confirmed COMMIT

```
{
  "data": {
    "id": "c62bfb8b-2530-4a7c-979c-a9a6d16be0df",
    "startsAt": "2026-11-06T06:00:00.000Z",
    "endsAt": "2026-11-06T07:00:00.000Z",
    "lifecycle": "Offered",
    "occupancy": "Unoccupied"
  },
  "meta": {"requestId":"opaque-request-id"}
}
```

The **entire allowed Slot DTO** is exactly `id` (UUID), `startsAt` and `endsAt` (UTC ISO `.000Z`), `lifecycle` (currently `Offered`), and `occupancy` (`Unoccupied` or `Occupied`). No `tutorId`, User email, Customer ID, Booking payload or extra database columns are serialized. The Tutor identity is already trusted from `/api/v1/auth/me`. Own-list returns `{"data":[<same-safe-slot-DTO>],"meta":{"requestId":"..."}}`, or `{"data":[],"meta":{"requestId":"..."}}` when empty. Sort ascending `startsAt` then UUID `id`, no pagination/filter. `occupancy` is **derived**, not a mutable `Slot.isBooked` column: until #16 Booking exists each new offer is `Unoccupied`; after #16 it must be recomputed from committed active `Booked` rows and can be `Occupied` without changing `lifecycle`. Offered publication is distinct from Customer-bookable eligibility (#15). This field set/order is frozen **as a review proposal**, not peer-approved yet.

### Proposed safe errors

| Condition | Status / code | Required DB outcome |
|---|---|---|
| No valid Session | 401 UNAUTHENTICATED | No mutation/private data |
| Customer tries Tutor routes | 403 FORBIDDEN | No mutation |
| Client tries owner/role/endsAt/unknown extra POST keys | 400 INVALID_INPUT | No mutation |

| Condition | Status / code | Required DB outcome |
|---|---|---|
| Any GET/POST query parameter, including forged `?tutorId=T2` | 400 INVALID_INPUT | No foreign response or mutation |
| Malformed/offsetless/missing start, nonzero seconds/fraction, invalid calendar/offset | 400 INVALID_INPUT | No mutation and no rounding |
| Valid but nonfuture start at post-lock DB clock | 422 SLOT_INVALID_TIME | No mutation |
| Overlap of currently Offered same-Tutor Slots | 409 SLOT_OVERLAP | Prior Slot unchanged |
| `GET /api/v1/tutor/slots/:id` (not a Sprint 1 route) | 404 (unregistered route) | No Slot-detail lookup or foreign ownership side channel |
| Missing/wrong CSRF or Origin | 403 CSRF_DENIED / ORIGIN_DENIED | No mutation |
| DB retry exhausted / unavailable | 503 SERVICE_UNAVAILABLE | No false 201; uncertain responses reconciled via own GET |
| Unexpected internal failure | 500 INTERNAL_ERROR | No raw SQL/stack/secrets |

Errors use the existing envelope `{"error":{"code":"...","message":"..."},"requestId":"..."}`; proposed SLOT-specific codes require peer sign-off. A genuine exclusion SQLSTATE 23P01 is conflict, not infinite retry; 40001/40P01 may trigger bounded **whole-transaction** retry. Never claim exactly-once HTTP delivery without approved idempotency policy.

### Review gate

Peer-review the **two-route-only** choice, minute-precision/no-rounding examples, exact allowlist and ascending order, explicit **no pagination/filter** policy, strict query rejection, trusted Tutor ownership, CSRF/Origin reuse and status mapping. Test anonymous, wrong-role, forged GET owner query, late own-list response after logout/account switch, stale cookies, overlap/race and no unsafe successful response. All tests planned, **not executed** in Part E.

---

## E.2.5 F-S1-02 Slot Data & Transaction Contract (data-spec.md)

> **PROPOSED SQL, NOT APPLIED OR TESTED.** Issue #14. See SDS, HTTP, UI, STS and whole-product System SDS §§3.3, 7.1–7.2.

### Existing DB baseline

Merged PR #26 includes Prisma `User`, `Session`, `AuthAttemptBucket`, `AuthAttemptReservation` and auth migration `20261104000000_auth`; it does **not** include Slot or Booking. Preserve merged auth migration unchanged. Add a **new forward-only Slot migration** and Prisma Slot model/User relation. Auth transactions use `pg` Pool, Prisma for schema/migration; one Slot mutation must use **one pg PoolClient**, not independent Prisma/pg transactions falsely described as atomic.

### Proposed Slot model

| Field | Type / policy |
|---|---|
| `id` | UUID PK, immutable |
| `tutorId` | UUID NOT NULL FK to `User.id`, owner from Session |
| `startsAt`, `endsAt` | TIMESTAMPTZ NOT NULL, exact one hour apart |
| `lifecycle` | Offered now, Withdrawn reserved for Sprint 2 |
| `createdAt` | DB-generated timestamp |
| `withdrawnAt` | NULL for Offered; later Sprint 2 history |

Tutor Schedule is `WHERE tutorId=principal.userId`, not a separate writable Schedule table. Once #16 exists, occupancy derives from active Booked rows, not a stored `isBooked` flag. **Sprint 1 read contract:** only the authenticated Tutor's full owner-list GET

(no `:id` route, query filters or pagination); strict-query rejection prevents client-supplied `tutorId` from changing owner scope. Sort by `"startsAt" ASC,"id" ASC` and project **only** the approved-for-review DTO fields. `occupancy` is computed as Unoccupied at #14 because no Booking relation exists yet, and must become derived from active Booked rows in #16.

**Proposed migration fragment (requires peer review and disposable DB proof)**

```
CREATE EXTENSION IF NOT EXISTS btree_gist;

CREATE TABLE "Slot" (
  "id" UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  "tutorId" UUID NOT NULL REFERENCES "User"("id") ON DELETE RESTRICT,
  "startsAt" TIMESTAMPTZ NOT NULL,
  "endsAt" TIMESTAMPTZ NOT NULL,
  "lifecycle" TEXT NOT NULL DEFAULT 'Offered'
    CHECK ("lifecycle" IN ('Offered','Withdrawn')),
  "createdAt" TIMESTAMPTZ NOT NULL DEFAULT now(),
  "withdrawnAt" TIMESTAMPTZ,
  CONSTRAINT slot_exactly_one_hour
    CHECK ("endsAt" = "startsAt" + INTERVAL '60 minutes'),
  CONSTRAINT slot_lifecycle_consistent
    CHECK (
      ("lifecycle"='Offered' AND "withdrawnAt" IS NULL)
      OR ("lifecycle"='Withdrawn' AND "withdrawnAt" IS NOT NULL)
    )
);
CREATE INDEX "Slot_tutorId_startsAt_idx"
  ON "Slot" ("tutorId","startsAt","id");
ALTER TABLE "Slot" ADD CONSTRAINT offered_slot_no_overlap_per_tutor
  EXCLUDE USING gist (
    "tutorId" WITH =,
    tstzrange("startsAt","endsAt",'[)') WITH &&
  )
  WHERE ("lifecycle"='Offered');

-- Sprint 1 ordinary-DML invariant: only new Offered Slots may be inserted.
-- Every UPDATE/DELETE/TRUNCATE is denied at the database, not just in Express.
CREATE FUNCTION slot_guard_s1() RETURNS trigger
LANGUAGE plpgsql AS $$
BEGIN
  IF TG_OP = 'INSERT' THEN
    IF NEW."lifecycle" <> 'Offered' OR NEW."withdrawnAt" IS NOT NULL THEN
      RAISE EXCEPTION 'Sprint 1 only permits Offered Slot inserts'
        USING ERRCODE = '23514', CONSTRAINT = 'slot_s1_insert_lifecycle';
    END IF;
    RETURN NEW;
  END IF;
  RAISE EXCEPTION 'Slot mutation is forbidden in Sprint 1'
    USING ERRCODE = '23514', CONSTRAINT = 'slot_s1_immutable';
  RETURN NULL; -- Unreachable: every non-INSERT raises an exception.
END;
$$;

CREATE TRIGGER slot_s1_insert_guard BEFORE INSERT ON "Slot"
  FOR EACH ROW EXECUTE FUNCTION slot_guard_s1();
CREATE TRIGGER slot_s1_update_delete_guard BEFORE UPDATE OR DELETE ON "Slot"
  FOR EACH ROW EXECUTE FUNCTION slot_guard_s1();
CREATE TRIGGER slot_s1_truncate_guard BEFORE TRUNCATE ON "Slot"
  FOR EACH STATEMENT EXECUTE FUNCTION slot_guard_s1();
```

Notes: Auth migration already creates `pgcrypto` /UUID generation, but `btree_gist` installation rights must be verified on actual Postgres 17/18 and future deployment. Prisma cannot fully express conditional exclusion or PL/pgSQL guards: preserve native SQL in later migrations. Do **not** add a time-relative `CHECK startsAt>now()`, as a historical valid Slot eventually becomes past while remaining persisted. A FK alone does not enforce authenticated Tutor ownership: verify/lock User in the write transaction. The application exposes **no** update/delete/withdraw route in Sprint 1.

**Database-level operation / transition matrix (P1 review decision)**

| Operation attempted by ordinary SQL/API | Sprint 1 result | Expected DB proof |
|---|---|---|
| `INSERT` as `Offered` with NULL `withdrawnAt`, future 60-minute interval, valid owner | **Allowed** only after all server authorization/time and native constraints; direct SQL has **no Session ownership proof** | New row committed if checks pass |
| `INSERT` with `Withdrawn` and a timestamp, or a non-NULL `withdrawnAt` | **Denied** by insert trigger | SQLSTATE **23514**, constraint `slot_s1_insert_lifecycle`; zero rows |
| `UPDATE` any existing row (including `id`, `tutorId`, `startsAt`, `endsAt`, `lifecycle`, `withdrawnAt` or no-op update) | **Denied** unconditionally by row-level trigger | SQLSTATE **23514**, constraint `slot_s1_immutable`; row unchanged |
| `DELETE` any Slot | **Denied** by row-level trigger | SQLSTATE **23514**, constraint `slot_s1_immutable`; row still present |
| `TRUNCATE` Slot | **Denied** by statement trigger; may additionally lack privilege for runtime DB role | SQLSTATE **23514** (owner in test) or **42501** (insufficient privilege), table unchanged |
| `Offered -> Withdrawn` or `Withdrawn -> Offered` | **Neither permitted in Sprint 1**; no `Withdrawn` row can be written normally | Attempted UPDATE rejected as above; direct reactivation fixture deferred until S2 |
| Sprint 2 reviewed `Offered -> Withdrawn` | **NOT IMPLEMENTED**; requires a separate migration replacing the restrictive trigger, one-way transition with non-NULL `withdrawnAt` and an atomic no-active-Booking check | New S2 tests/review, not #14 PASS |
| Sprint 2 attempted `Withdrawn -> Offered` (same ID), change ID/owner/start/end, or DELETE | **Must remain denied** even after S2 one-way migration | Future S2 direct-SQL negative tests; **NOT RUN** in #14 |

The explicit SQLSTATE values above come from **proposed** `RAISE EXCEPTION` clauses, not a claim that this migration has been applied. PostgreSQL privileged DDL can disable/drop triggers; runtime role must not have schema/table ownership, superuser, or trigger-disabling privileges in a production-equivalent environment. Part F must verify the actual role/permission setup; a deployment that uses a schema-owner runtime connection cannot claim resistance to malicious DDL. Privileged test teardown must use an **isolated disposable DB/schema**, not `DELETE FROM "Slot"` that the invariant correctly rejects.

### Transaction and Race A

1. Verify `requireSession`, Tutor role, Origin and Session CSRF at HTTP edge. Strictly parse **valid** RFC3339 start with explicit timezone: seconds exactly `:00`, optional fractional part 1–3 **zero digits only**; e.g. `13:17:00Z` or `13:17:00.000+07:00` permitted, `13:00:30` / `13:00:00.500` rejected **without rounding**, as are invalid civil dates/offsets. Derive +60m end on server.
2. Begin **SERIALIZABLE** transaction on one `pg.PoolClient`; don't reuse generic Auth `transaction()` helper that begins with default isolation.
3. Lock `User` row `SELECT id,role,isActive FROM "User" WHERE id=$1 FOR UPDATE` with `principal.userId`. Recheck active and Tutor role **after** lock. Current transaction's locking hierarchy matches System SDS User-before-Slot.
4. Sample fresh DB `clock_timestamp()` after lock. Require start strictly future; **do not impose Q05 Booking lead time** or unapproved working hours/horizon/grid.
5. Insert Offered row using trusted tutorId. Duration CHECK and same-Tutor Offered GiST EXCLUDE are last-resort DB safeguards, including two concurrent writers/instances. Distinct Tutors and adjacent half-open intervals remain allowed.
6. COMMIT **before** 201. On any failure, ROLLBACK and release. Map exclusion `23P01` to safe 409 Conflict; `40001` serialization / `40P01` deadlock eligible for **full fresh transaction** bounded retry (3 attempts proposed), not infinite retry of an actual overlap. DB unavailable/exhaustion -> safe non-success; uncertain client-side response can require owner GET reconciliation.

### Verification obligations

- Fresh disposable DB: apply Auth then Slot migration, inspect native constraints and indexes, regenerate Prisma client; record DB version, actual SQLSTATEs and application behavior.

- Real Race A with two independent connections, explicit lock/barrier ensuring contention: capture A/B `pg_backend_pid()`, observe `pg_blocking_pids(B_pid)` **containing A_pid** from an independent observer while A holds the User lock; then release A. Require both winner orders, observed HTTP statuses and SQLSTATE (if thrown), committed post-race rows and invariant check. Also test direct SQL bypass of HTTP precheck; random `Promise.all()` alone is insufficient. Avoid a timeout-only or sleep-only "race" proof.
- Prove 59m duration direct SQL rejected, same-Tutor positive overlap rejected, adjacency and different-Tutor same hour accepted. Inject transactional fault, confirm zero partial commits and no 201.
- Check **own-list** SQL owner filter, strict-query denial of `GET /api/v1/tutor/slots?tutorId=T2`, response allowlist, no foreign Customer/Booking information, and no `GET :id` route. Test stale owner-list response arriving after logout/account switch (old T1 payload must never render under T2), role mutation, revoked session and CSRF failures.
- Retain current `apps/api/package.json` behavior but **wire new Slot DB tests** into `npm run test:db` discovery; current command enumerates Auth tests, so a new file could otherwise be omitted silently.
- Record exact `npm ci`, `db:generate`, `db:migrate`, `typecheck`, `build`, `test`, `test:db`, `test:e2e` and Race A results by SHA in Part F; **none are run by Part E**.

#### Review-required engineering decisions

Peer review the proposed `slot_guard_s1` trigger and operation matrix, SQLSTATE 23514 assertions, future one-way migration gate, actual runtime DB privilege separation, lock ordering and Serializable behavior; accept/reject no-detail/no-pagination/no-filter own-list and minute-precision transport. No blanket architectural refactoring of #13.

---

### E.2.6 F-S1-02 Tutor Slot Software Test Specification (tests.md)

> **UX delta proposed 2026-11-05:** preserve SLOT-01...SLOT-20 below; add these *new, not-yet-executed-at-design-time* dashboard checks from the dated UX decision. The older Part E run ledger is historical; actual new executions belong in the Part F verification ledger, not this planned list.

| ID | New dashboard evidence to collect |
|---|---|
| UX-R1 | Logged-in Tutor sees original NutTiew identity, navy/orange shell, no fake data or actions; `บัญชีของฉัน` navigates to in-page `#account-details` showing **only role and shortened ID from trusted /auth/me**; Customer sees original authorized Auth page |
| UX-R2 | Real PG Slot at Bangkok 13:17 and 13:59 positions at exact minute-offset, 23:30→00:30 splits over two dates; all 24 hours accessible |
| UX-R3 | Prev/Next/Today and day picker change local view without changing GET URL; all returned Slot IDs remain in chronological agenda. **Overview count** equals full own-list Slot count across **all dates** and is constant across viewport navigation; `ช่วงที่แสดง` separately counts distinct Slots intersecting the current window (including cross-midnight only once per window) |
| UX-R4 | Real app **320/375px = full mobile Agenda** ( `<=620px` ), **768px = two-day timeline** ( `621–1060px` ), **1280px = three-day timeline** ( `>1060px` ); check 620/621 and 1060/1061 boundaries; screenshots, 320 CSS px reflow/no unexpected horizontal scroll, keyboard-only nav and visible unobscured focus, valid labels/status, primary controls **>=44x44 CSS px** and applicable WCAG 2.2 AA target size **>=24x24 CSS px or normative exception**. Record separate **>=4.5:1 normal text**, **>=3:1 large text**, **>=3:1 UI/non-text** computed contrast for all critical states. Automated subset is not conformance; manual human WCAG 2.2 AA signoff **NOT RUN** until actually assessed |
| UX-R5 | Re-run existing SLOT-09/12/14/15/18/20, including real 200-after-switch privacy and uncertain-POST reconciliation, with new shell |
| **UX-R5-GET-01** | Authenticated Tutor with 4 committed own Slots: initial GET 503 → retry GET 503 show loading/error and retry only, **no empty Agenda/Calendar/zero**; next genuine GET 200 restores all 4 Slot IDs, sorted and private |
| **UX-R5-GET-02** | Authenticated Tutor with **no** committed Slot: initial GET 503 → retry GET 503 must not claim an empty schedule; only authorized GET 200 with `data: []` may show true empty state and 0 total |

| ID | New dashboard evidence to collect |
|---|---|
| **UX-R5-LOGOUT-01** | T1 starts Logout: hold CSRF and Logout requests, then inject HTTP 503, network loss or timeout. **Immediately hide T1 account ID, signed-in status, Calendar, Agenda and private cards; block Create/header CTA and any new protected POST before and after uncertainty**. Attempt creation and verify **zero new POST /api/v1/tutor/slots after Logout begins**, no newly committed Slot row. A pre-Logout in-flight POST may have committed and is not asserted rolled back. A failed `/auth/me` recheck keeps content hidden/actions blocked; do not falsely claim Logout succeeded |
| **UX-R5-LOGOUT-02** | After T1 uncertain Logout, retry Logout or `/auth/me` session check. A **fresh /auth/me 200 matching exact internal T1 ID and Tutor role** must be followed by fresh owner-list GET 200 **before** restoring T1 display or Create; failed owner GET stays hidden/blocked. Fresh Logout 204 or `/auth/me` 401 finalizes signed-out; different account or recheck 503/network stays blocked; stale T1 authorized 200 never repopulates hidden content |
| UX-R6 | Real rendered screenshots from DB-backed Tutor account; no invented data or unimplemented domain action |

**Provenance / test gate:** the above are **Part E planned acceptance checks**, not outcomes of this docs-only PR. The implementation PR must link these stable IDs to real Playwright/DB evidence with RED→GREEN for unsafe Logout and GET states, rerun the original SLOT-01…20 and Auth regressions, and record exact commit SHA and hosted CI. Do not mark this design accepted before peer review and merge.

**WCAG evidence gate:** the Part F verification report must distinguish (a) automated measured contrast/keyboard/viewport samples, (b) manual inspection of all applicable WCAG 2.2 A/AA criteria including SC 1.4.3/1.4.10/1.4.11, 2.1.1, 2.4.7/2.4.11 and 2.5.8, and (c) explicit NOT RUN items with reviewer, date and exact implementation SHA. The old handful of 4.5:1 samples does **not** establish WCAG 2.2 AA.

For UX-R4, validate the CTA's full rendered pairing (not just its label): `#172137` text/icons on `#F47736` fill (target calculated **5.76:1**), `#D96123` visible border versus both `#F7F8FB` canvas and white (calculated **3.48:1 / 3.69:1**), and `#AA4519` `3px` offset keyboard focus outline against both backgrounds (calculated **5.53:1 / 5.87:1**). Verify hover, disabled, keyboard, zoom and any additional component states using **actual computed browser colors**. White text on orange and borderless orange on canvas/white are **not accepted**. This is a future Part F test obligation, not a test PASS recorded by this Part E PR.

> **NEW DASHBOARD UX TESTS PLANNED / NOT RUN IN THIS DOCS-ONLY PR.** The original SLOT-01...SLOT-20 design and earlier implementation/tests from merged PR #28 are historical, **not missing** in today's `sprint1`. Issue #14, owner @Tanaboonnnnn, reviewer @Chxtamos. Source contracts: SDS / owner policy decision, HTTP, UI, Data / DB trigger matrix.
>
> **Historical baseline only:** `sprint1` `6fd3931` was the **original Part E snapshot before Slot implementation** and had Auth tests but no Slot code/migration/test. **Current PR #30 base:** `sprint1` `ed451be2ca3e366bdfc1900f4c4697aa7e50b6a0` **already contains** the original Slot API, DB migration and tests from merged PR #27/#28. The new dashboard/Logout cases above are not claimed executed by this documentation PR.

### Test harness, data and TDD evidence

Use **clean disposable** real PostgreSQL with Auth migration plus **new** Slot migration, test-only accounts T1/T2 (Tutor) and C1 (Customer), authenticated session cookies and session-bound CSRF, Supertest/Vitest, at least two independent `pg` connections plus an observer connection, Playwright for real Tutor flow. Test dates are future relative to **database authoritative time**, not hardcoded as perpetually valid. Never commit passwords/keys. Test names must match stable AC/VC and execute through actual npm scripts. Because Slot direct DELETE/TRUNCATE is intentionally blocked, isolate and roll back fixtures or drop an **entire test-owned DB/schema as privileged teardown**; do not depend on deleting persisted production-like Slot rows for test cleanup.

Record **RED** first (missing route/schema/constraint causes expected failure), **GREEN** after implementation, command, exact SHA, PG/Node version, migration revision, PASS/FAIL/SKIP and final DB rows. UI-only warnings and `Promise.all()` without verified contention do not prove Race A.

### Original Slot STS cases — historical Part E test plan

The `SLOT-01` through `SLOT-20` cases below were **planned before the

original Slot implementation**, and many were subsequently exercised

by the reviewed Part F work (PR #28). This section records the original

**expected observations**, not the current execution state.

For actual command output, PASS/FAIL/rerun counts and limitations at

their recorded commit SHAs, see the separate

original Slot Part F verification ledger.

The **new Dashboard UX and Logout tests above are separately PLANNED

and have not been executed by this docs-only PR**.

| STS | Trace IDs | Setup/action | Required observable result |
|---|---|---|---|
| SLOT-01 | AC-S1-08, VC/TEST-S1-08, VAL-003 | T1 authenticated, POST future Bangkok 13:00 | 201, one DB Offered Slot owned T1, end exactly 14:00 |
| SLOT-02 | AC-S1-08, VC/TEST-S1-14, VAL-031 | T1 GET own list (no filters), refresh/restart API with same DB | Same committed Slot ID and UTC times, own account from `/auth/me`; exact safe DTO, `startsAt,id` ascending, no in-memory substitute |
| SLOT-03 | AC-S1-09, VC/TEST-S1-09, VAL-004 | T1 already offers 13:00–14:00, proposes 13:30–14:30 | 409; old row unchanged, no second row |
| SLOT-04 | AC-S1-10, VC/TEST-S1-10 | T1 creates 13:00–14:00 then 14:00–15:00 | Both rows committed; adjacency permitted |

| STS | Trace IDs | Setup/action | Required observable result |
|---|---|---|---|
| SLOT-05 | AC-S1-11, VC/TEST-S1-11 | T1/T2 both create same 13:00–14:00 future window | Both succeed, distinct owner rows |
| SLOT-06 | AC-S1-12, VC/TEST-S1-12 | Missing/invalid/offsetless timestamps, invalid civil date/offset, past/equal-now, extra client owner/duration | Defined 400/422; no new/modified row; no silent timestamp normalization |
| SLOT-07 | AC-S1-05/06, VC/TEST-S1-05/06, AUTH-07/08 | Anonymous/Customer tries Tutor POST and protected GET | 401/403, no private response or write |
| SLOT-08 | AC-S1-07, VC/TEST-S1-07/31, AUTH-09/16 | T1 GET `/tutor/slots?tutorId=T2`, T1 GET unregistered `/:id` for T2/missing UUID, T1 POST forged `tutorId` / `role` | GET forged query **400**, no T2 rows; no detail route, both detail paths 404/no Slot payload; strict POST 400, T2 unchanged |
| SLOT-09 | AC-S1-14, VC/TEST-S1-13, VAL-013 | Open same Slot in Bangkok, UTC and Tokyo browser zones; cross midnight | Same intended Bangkok date/hour, exact 60m, same UTC instant |
| SLOT-10 | AC-S1-13, **VC/TEST-S1-37**, VAL-005 | Two same-Tutor overlapping creates with deterministic barriers; capture A/B `pg_backend_pid()` and verify observer `pg_blocking_pids(B_pid)` includes A | At most one conflicting Offered row committed; loser non-success; log true lock wait, HTTP outcomes, SQLSTATE and no ghost row |
| SLOT-11 | AC-S1-13, VC/TEST-S1-37 | Reverse A/B winner order using two API instances/independent DB connections; direct SQL bypass of HTTP guard | Native exclusion prevents overlap; record observed blocker/wait, SQLSTATE (often 23P01/40001 depending order), committed rows and exact winner |
| SLOT-12 | NFR-S1-11, BR-S1-18/034 | Inject SQL failure before commit, simulate DB unavailable | Rollback, zero partial data, safe 503/non-success, no false 201 |
| SLOT-13 | NFR-S1-01/08, AUTH-13/16 | Invalid/missing CSRF, wrong Origin, revoked cookie | Denied, DB unchanged; sanitized error without secrets |
| SLOT-14 | AC-S1-08/14, FR-S1-19 | Real Tutor UI login→create→refresh→full own-list (no detail/filter/page); process restart | Database-backed end-to-end path persists; safe DTO/occupancy (Unoccupied at #14), deterministic order |
| SLOT-15 | Proposed NFR-S1-09/VAL-033 | Keyboard, contrast/targets, viewports 320/375/768/1280; 409/422/503 | Visible focus/alerts, no overflow, error recovery and no false success |
| SLOT-16 | SLOT-I1/I2, VAL-004/005 | Direct SQL 59-minute insert, overlap insert; inspect pg constraint/index | CHECK and GiST exclusion deny invalid committed rows |
| SLOT-17 | SLOT-I1/I3/I4/I7 | Lock Tutor, deactivate/role change; direct `INSERT Withdrawn`, `UPDATE` each of `id/tutorId/startsAt/endsAt/lifecycle/withdrawnAt` and a no-op update, `DELETE`, `TRUNCATE` | API rejects invalid owner; S1 DB trigger rejects INSERT Withdrawn/UPDATE/DELETE with **23514** and identified constraint; TRUNCATE **23514/42501**, unchanged committed row counts; no S2 reactivation PASS claim |
| SLOT-18 | SLOT-I5, retry safety | Duplicate POST/unknown network outcome | At most one overlapping offer, GET used for reconciliation, no false exactly-once promise |
| SLOT-19 | AC-S1-12/14, VC/TEST-S1-12/13, OD-003 | Send RFC3339 future `13:00:00` / `13:00:00.000` / `13:17:00` with offsets, and `13:00:30` / `13:00:00.500`, leap-day/invalid-day, missing offset; run in UTC/Tokyo browser zone | Accept second/fraction **zero** and **any minute**; 400 for nonzero seconds/fraction/invalid civil time; no rounding/DB row; Bangkok hour unchanged |

| STS | Trace IDs | Setup/action | Required observable result |
|---|---|---|---|
| SLOT-20 | AC-S1-07, AUTH-09/16, privacy | Hold a successful T1 owner-list GET; logout or switch to T2 while pending; release old T1 response after T2/current signed-out state | Old T1 Slots **never reappear**; T2 own-list contains only T2; stale GET cannot update protected view after session change |

### Deterministic Race A procedure

1. Open A/B on **independent** PostgreSQL sessions. Both target overlapping Offered intervals of T1 on an approved future Bangkok date. Prepare T1 identity/auth fixtures.
2. A begins SERIALIZABLE, captures `SELECT pg_backend_pid() AS a_pid` and locks T1 `User FOR UPDATE`; hold A at an **explicit test-only barrier** before COMMIT. B begins with an independently checked-out `pg.PoolClient` / second API instance; a test-only instrumentation seam records B's `pg_backend_pid()` **before** it attempts the same User lock. This seam must not become a production HTTP test hook.
3. Using an independent observer connection, repeatedly query `SELECT pg_blocking_pids($1::int) AS blockers` with B PID under a **bounded test timeout**, until it includes A PID (optionally corroborate `pg_stat_activity.wait_event_type='Lock'`). **Fail the race test** if no actual blocking pair is observed; do not proceed on guessed timing/sleep alone.
4. Release A, let it INSERT+COMMIT, then allow B to resume/full-transaction retry. B either returns a safe conflict or aborts with an attributable SQLSTATE, never commits overlapping Offered state. Record both request statuses (201 vs 409/transaction error as contracted), observed SQLSTATE(s), A/B backend PIDs, blocker observation and retry count.
5. From a **fresh post-commit observer connection**, query `SELECT id,"tutorId","startsAt","endsAt","lifecycle" FROM "Slot" WHERE "tutorId"=$1 ORDER BY "startsAt",id` and independently assert no pair of Offered half-open ranges intersects; record row IDs/counts. Reverse winner order; repeat direct SQL inserts on separate connections that bypass Express to prove GiST backstop. Controls: same-Tutor adjacency and different-Tutor same-hour must both pass.
6. Inject a DB failure before COMMIT and verify rollback plus safe response; restart API and re-read committed rows.

Important: Test with real PostgreSQL, not SQLite, only ORM mock, or HTTP status without DB assertions. A `23P01` conflict is not a successful retry; bounded `40001` / `40P01` retries start new transactions and must still fail an actual overlap. Tests **must** prove B waited on A, not only that two requests were launched.

### Original privacy and DB immutability procedures (historical Part E plan)

The procedures below were originally written **before the Slot feature

was implemented**, not as a claim that the original privacy or

immutability tests are still unexecuted. Actual Slot Part F evidence,

including executed SLOT-17/19/20 cases and residual manual/production

verification gaps, is recorded in the

verification ledger. Do not infer new

Dashboard UX acceptance from these historical checks.

- **SLOT-08:** authenticate as T1. Request `GET /api/v1/tutor/slots?tutorId=T2`, `?page=1` or another unknown query. All return 400 INVALID_INPUT and no foreign rows; own unfiltered GET returns only T1 rows. `GET /api/v1/tutor/slots/{T2SlotId}` and an unknown UUID both return 404 because **there is no detail route**, not because a foreign record was looked up. A forged `tutorId` in POST is a 400. No query can change `WHERE tutorId=principal.userId`.
- **SLOT-20:** with T1 signed in, intercept/hold a genuine successful T1 GET while the component is mounted. Trigger Logout (or switch auth identity to T2), clear protected state and issue T2 own-list if applicable. Release the **old 200** response **after** logout/new T2 success. Assert no T1 row IDs/time appear; verify T2 can see only T2 data. Repeat with a 401 or network failure from the stale request.
- **SLOT-17:** on an Offered fixture row use real SQL to attempt UPDATE ID, owner, start, end, lifecycle, withdrawnAt, and no-op UPDATE; ordinary UPDATE/DELETE must throw **SQLSTATE 23514 /** `slot_s1_immutable`; INSERT Withdrawn must throw **23514 /** `slot_s1_insert_lifecycle`; TRUNCATE must throw **23514** (or runtime **42501**). Compare pre/post committed row images/count. **Withdrawn→Offered cannot be executed in Sprint 1** because Withdrawn creation and updates are forbidden;

mark it **DEFERRED TO SPRINT 2**, not PASS. Sprint 2 migration must explicitly permit one-way Offered→Withdrawn and separately prove no reactivation. Check production-equivalent DB runtime credential cannot disable the protective trigger via DDL; if it can, report the privilege gap rather than claiming immutable DB protection.

- **SLOT-19:** check that the UI produces `HH:mm -> HH:mm:00.000+07:00`, API validates full real civil date+offset, accepts every minute (including 13:17), rejects 13:00:30/13:00:00.500 without rounding and that cross-midnight +60m retains date meaning under UTC/Tokyo browser emulation.

### Feature integration limits

AUTH-07/08/09 and domain part of AUTH-16 are exercised with actual Slot routes in #14. Customer availability and stale selection belong to #15; Booking cutoff Q05 and races B/C belong to #16; Customer-private Booking reads belong to #17; final integrated `sprint1→main` release to #18. Do not report those as #14 PASS.

### Original pre-Part-F run checklist — historical planning snapshot

**The status cells below describe the original pre-implementation

checklist, not the present Slot feature or its current PASS/FAIL state.**

The original test commands and Race A/immutability/precision/privacy

cases were subsequently executed in Part F; the authoritative

observed outcomes, any failures, reruns and limitations are in the

original Slot Part F verification ledger.

The new Dashboard UX-R1…R6, GET/Logout acceptance tests, and any

future regression reruns must be documented **separately** in their

own Part F evidence. Human WCAG signoff remains **NOT RUN** until

performed, and any stakeholder policy approval remains a separate gate.

| Original planned command/check | Historical Part E state — consult linked Part F ledger for actual result |
|---|---|
| `npm ci` / `npm run db:generate` / `npm run db:migrate` (fresh DB) | Planned in original Part E; check actual Part F ledger |
| `npm run typecheck` / `npm run build` | Planned in original Part E; check actual Part F ledger |
| `npm test`, `npm run test:db` with Slot test discovered | Planned in original Part E; check actual Part F ledger |
| `npm run test:e2e` including Tutor UI | Planned in original Part E; check actual Part F ledger |
| Real DB Race A observed `pg_blocking_pids()` / direct SQL / rollback / restart | Planned in original Part E; check actual Part F ledger |
| SLOT-17 immutability trigger and Sprint 1 mutation matrix | Planned in original Part E; check actual Part F ledger |
| SLOT-19/20 precision and stale protected GET tests | Planned in original Part E; check actual Part F ledger |
| Human WCAG/keyboard/contrast signoff (separate manual gate) | **NOT RUN** for the new Dashboard; no human conformance claim |
| Stakeholder/instructor OD policy approvals | Separately gated; no approval implied by test execution |

**Original pre-code review gate (historical):** @Chxtamos reviewed

the original Slot Part E contract through PR #27 before the Slot

implementation in PR #28. For the **new** Tutor Calendar Dashboard,

the amended Part E in PR #30 still requires independent approval and

merge **before** a new code-only Part F PR; this historical checklist

does not satisfy that new gate.

## E.3 Shared Booking Data Foundation (D1-08A)

### E.3.1 D1-08A Shared Booking Data Foundation SDS (specification.md)

> **PROPOSED CONTRACT — awaiting human peer review.** Issue #33. Contract owner: @Chxtamos. Required peer reviewer / F-S1-04 owner: @Tanaboonnnnn. This Part E change is documentation only. It does not add a Prisma model, migration, endpoint, UI, fixture, or test implementation; it does not claim that any database test has run.

#### 1. Purpose and authority

Define one shared, durable PostgreSQL/Prisma Booking representation for:

- #15 — F-S1-03 Customer Availability, which reads persisted Bookings to exclude occupied Slots and the authenticated Customer's overlapping appointments.
- #16 — F-S1-04 Exclusive Booking, which owns Booking creation and the application transaction/lock/retry protocol. The shared database guard trigger is owned by #33 Part F, not duplicated in #16.

The approved Part E contract for #15 selected Route B: this shared foundation must be reviewed and merged separately before either feature implements Booking-dependent behavior. This document is the proposed contract for that review; it is not itself approval.

Source hierarchy:

1. Sprint 1 requirements: Q01, Q05, Q28, Q30; FR-S1-10..13; BR-S1-08..10, BR-S1-13, BR-S1-19; AC-S1-19, AC-S1-25, AC-S1-26, AC-S1-35; NFR-S1-03..05 and NFR-S1-12.
2. System SDS: §§3.2–3.3 (entities and native PostgreSQL constraints), §4 (time/state semantics), §§7.1 and 7.3 (lock/transaction responsibilities), §7.5 (real-database verification).
3. #15 accepted Feature SDS and data contract and data spec, merged by PR #32.
4. #16 issue scope. Its own Part E contract must still define the Booking API/transaction and OD-013 retry behavior; this foundation does not pre-empt those choices.

#### 2. Verified baseline at the Part E branch point

This contract branch is based on `sprint1` commit `98d984169fff6b8ec0ff467c15abb441ca5cadd7` (PR #32 merge).

- `apps/api/prisma/schema.prisma` contains `User`, `Session`, `AuthAttemptBucket`, `AuthAttemptReservation`, and `Slot`; there is no `Booking` model.
- Existing migrations are `20261104000000_auth` and `20261105000000_tutor_slots`; neither creates a Booking table.
- The Auth migration installs `pgcrypto`. The Tutor Slots migration installs `btree_gist`, creates the immutable Sprint 1 Slot table, and enforces same-Tutor Offered-Slot non-overlap.
- `Slot` currently has UUID `id` and `tutorId`, `startsAt` / `endsAt` as `TIMESTAMPTZ(6)`, `lifecycle` defaulting to `Offered`, `createdAt`, and nullable `withdrawnAt`. Sprint 1's Slot triggers reject ordinary updates/deletes and `TRUNCATE`; the current migration does not enable a Withdrawn lifecycle transition.
- `User.role` is persisted as text with the existing Customer/Tutor constraint. A foreign key to `User` alone does not prove that the referenced account has the Customer role or is active; the application must check both using the authenticated principal.
- The System SDS targets PostgreSQL 18.x. No database migration or PostgreSQL compatibility test is executed by this documentation-only PR; the actual database version and `btree_gist` privileges must be recorded during Part F.

Do not edit, squash, replace, or regenerate the existing Auth/Slot migrations as part of this foundation.

#### 3. Proposed shared data contract

The canonical field list, relation semantics, SQL constraints, and Prisma mapping are in data-spec.md. The core decisions proposed for peer acceptance are:

| ID | Proposed contract | Rationale / trace |
|---|---|---|
| BDF-D01 | `Booking.id` is a server-generated UUID primary key and an **application-level immutable identity**. PostgreSQL enforces primary-key uniqueness and non-nullability but the primary key alone does not reject an ID-changing `UPDATE`. Sprint 1's append-only guard separately rejects Booking `UPDATE` / `DELETE` / `TRUNCATE` as lifecycle boundaries; this is not a dedicated ID-immutability guarantee or ID-specific trigger. | Stable identity for persistence and later authorized retrieval; FR-S1-10, FR-S1-14. |
| BDF-D02 | `customerId` is a required FK to `User.id`; delete/update is restricted. The service additionally verifies `role = Customer` and `isActive = true` from the authenticated Session. | Preserve ownership and do not trust client identity; FR-S1-04/10, BR-S1-13. |
| BDF-D03 | `currentSlotId` is a required FK to the selected `Slot`. The current Tutor is derived from `Slot.tutorId`; Booking does not duplicate `tutorId`. | Avoid two mutable sources of Tutor ownership; System SDS §3.2. |
| BDF-D04 | Persist `startsAt` and `endsAt` as `TIMESTAMPTZ(6)` snapshots copied from the selected Slot, never accepted from the client. A composite FK `(currentSlotId, startsAt, endsAt) → Slot(id, startsAt, endsAt)` enforces that the snapshot matches the immutable Slot. | Required by System SDS §3.3 and #15 data-spec; prevents a Booking interval drifting away from its Slot. |
| BDF-D05 | `status` is text constrained to exactly `Booked` or `Cancelled`; new Sprint 1 Booking writes begin as `Booked`. Only `Booked` is active/occupying. `Cancelled` is retained for the shared state model and isolated DB tests; no cancellation workflow is added in Sprint 1. | Q30, BR-S1-08/09/10. `Past` is derived display classification, not a status. |
| BDF-D06 | Intervals are valid only when `startsAt < endsAt` and use half-open `[start,end)` semantics. | BR-S1-09/10; adjacent appointments are allowed. |
| BDF-D07 | Parent deletion and primary-key mutation are restricted for both Customer and Slot references. | Preserve Booking history and stable references; no deletion/retention policy is invented. |
| BDF-D08 | PostgreSQL partial unique and exclusion constraints are the final integrity boundary for active Slot exclusivity and Customer overlap. | FR-S1-12/13, BR-S1-08/09/19, NFR-S1-04. |
| BDF-D09 | Add a forward-only migration; current baseline has no Booking rows, so no Booking backfill is required. Existing Auth/Slot data and constraints must remain unchanged. | Safe migration from the verified `sprint1` baseline. |
| BDF-D10 | Store `createdAt` and `updatedAt` as `TIMESTAMPTZ(6)`. `createdAt` is DB-defaulted; Prisma `@updatedAt` maintains `updatedAt` for application updates. These are metadata, not booking eligibility clocks. | Consistent with the System SDS entity model; Q05 continues to use its separate authoritative `T_elig`. |
| BDF-D11 | **#33 Part F owns one versioned `booking_guard_s1()` function and its two PostgreSQL trigger registrations** in the shared Booking migration (remediated in Issue #39): a row-level `BEFORE INSERT OR UPDATE OR DELETE` trigger and a statement-level `BEFORE TRUNCATE` trigger. INSERT enforces the System SDS User → Slot lock hierarchy at the database level by acquiring `User(customerId) FOR UPDATE` before locking `Slot` and before index insertion in `BEFORE ROW` trigger, eliminating direct-SQL GiST exclusion index contention, reverse wait, and `40P01` deadlock for concurrent application transactions; it then applies the Offered-Slot/Q05 guard after the Slot lock; every UPDATE/DELETE/TRUNCATE is rejected with SQLSTATE `0A000`. **#16 owns the application transaction adapter**, including the System SDS User → Slot → Booking lock order, Serializable transaction and no-post-guard-contention proof or whole-transaction retry. #16 must not create a duplicate Booking guard. | System SDS §§3.3, 7.1 and 7.3; BR-S1-07/13/18/19; AC-S1-25/26/35; VC/TEST-S1-25/26/39; Issue #39. |
| BDF-D12 | **Sprint 1 Booking is append-only after INSERT:** no row `UPDATE`, `DELETE`, or table `TRUNCATE`. #33 Part F enforces this with the row-level and statement-level guards in BDF-D11, following the existing Slot migration pattern. Deployment must separate the application runtime role from the migration/table-owner role; runtime is non-owner/non-superuser, has no `UPDATE` / `DELETE` / `TRUNCATE` or DDL/trigger-management privileges, and cannot bypass triggers through replication-role settings. No routine application/admin deletion exception is part of Sprint 1. BDF-24..26 verify the runtime role, both destructive operations, and final committed occupancy. | Preserve committed Booking history and derived Slot occupancy; prevent direct-SQL deletion from releasing a Slot without an approved lifecycle action. |

All BDF-D01..D12 entries are **proposals awaiting human review**, not stakeholder decisions or accepted implementation facts. BDF-D11 resolves trigger ownership; BDF-D12 makes the Sprint 1 append-only/role boundary explicit. Both must be accepted by the

consuming feature owners before any migration is authored.

### 4. Integrity and responsibility boundaries

#### 4.1 Database-owned invariants

The database must reject:

- missing or invalid Customer/Slot references;
- a non-positive Booking interval or a snapshot that differs from its referenced Slot;
- an unsupported Booking status;
- a second `Booked` row for the same `currentSlotId`;
- any positive-duration overlap between `Booked` intervals belonging to the same `customerId`, including across different Tutors;
- every Booking `UPDATE` or `DELETE` in Sprint 1, and every Booking-table `TRUNCATE`, including direct SQL.

`Cancelled` rows do not occupy a Slot and do not participate in the Customer-overlap exclusion. A `Booked` row remains Active after its end time; elapsed time does not cancel or release it.

#### 4.2 Application and transaction responsibilities

- #16 derives `customerId` from the live authenticated Session, reads the selected Slot and its actual Tutor from PostgreSQL, copies the persisted Slot interval, and sets the initial status to `Booked`. Client-supplied Customer/Tutor IDs, status, interval, or cutoff timestamps are not authoritative.
- The database FK does not enforce `User.role` or `isActive`; #16 must validate those within its agreed transaction/locking protocol.
- The unique and exclusion constraints protect committed state even when concurrent requests arrive through separate API processes. Application error mapping must treat constraint/serialization conflicts as non-success and must never report a Booking before commit.
- **#33 Part F owns the database guard artifact.** Its forward-only migration installs one `booking_guard_s1()` function with a row-level `BEFORE INSERT OR UPDATE OR DELETE` trigger and a statement-level `BEFORE TRUNCATE` trigger, following the existing Slot migration's row/statement guard pattern. The function rejects every `UPDATE` and `DELETE` at entry with SQLSTATE `0A000`, including `Cancelled → Booked`, `Booked → Cancelled`, moves and metadata updates; the statement trigger rejects every `TRUNCATE` with the same SQLSTATE. For a `Booked` INSERT, the function first acquires `User(customerId) FOR UPDATE` in `BEFORE ROW` trigger (enforcing the System SDS User → Slot lock hierarchy for direct-SQL writers before tuple insertion into unique or GiST exclusion indexes, preventing reverse wait and `40P01` deadlocks), then locks and re-reads the referenced Slot and rejects a missing or non-`Offered` Slot; it samples PostgreSQL `clock_timestamp()` only after acquiring both locks and enforces Q05 (`startsAt - T_elig >= 60 minutes`). The composite FK remains the final interval-snapshot equality constraint. The app runtime role must be separate from the migration/table owner, non-owner/non-superuser, lack UPDATE/DELETE/TRUNCATE and DDL/trigger-management privileges, and have no trigger-bypass capability. No Booking API or application service is added to #33.
- **#16 owns application transaction coordination, not a second copy of the trigger.** Its Part E contract must specify the System SDS global lock order: all affected User rows (Customer and selected Slot's actual Tutor) in ascending UUID order, then all affected Slot rows in ascending UUID order, then existing Booking rows in ascending UUID order; use Serializable isolation as specified. The service must acquire the Slot lock before the guarded INSERT so the trigger re-locks an already-held row. #16 must prove no conflict-capable unique/exclusion wait occurs after `T_elig`; if it cannot prove that invariant, it must abort/retry the entire transaction and sample a fresh DB clock. The trigger and indexes are database backstops, not substitutes for the application lock protocol.
- `Booking.id` immutability remains an application-level identity invariant: #16 generates it server-side and any future supported update path must not accept a replacement ID. The PostgreSQL primary key alone is not an immutability guard. Sprint 1's blanket Booking mutation prohibition (UPDATE/DELETE/TRUNCATE) is a separate lifecycle rule, not a dedicated ID-immutability trigger or ID-specific DB test.
- **Sprint 1 Booking rows are append-only:** the database rejects UPDATE/DELETE/TRUNCATE, while the application runtime role is not permitted to UPDATE/DELETE/TRUNCATE or alter/disable the guards. The migration/table-owner role is separate and is not used by API runtime processes.

- #15 is read-only: it consumes `status = Booked`, `currentSlotId`, and the persisted interval for availability predicates. It must not create/update Booking records or add `Slot.isBooked`.

#### 4.3 Explicit exclusions

No Booking HTTP route/controller/service, UI, private Booking retrieval, cancellation/reschedule operation, Booking deletion/truncation workflow, `RescheduleHistory`, `Notification`, cancellation actor/reason, idempotency registry, payment, attendance, `Completed` state, or Slot withdrawal workflow is included. OD-013 retry-response semantics remain owned by #16. Issue #15's OD-002 60-day availability horizon is not a Booking column or a change to Q05.

### 5. Migration and compatibility plan

Part F of #33 may begin only after the Part E contract is accepted by both consuming feature owners **and** the #16 Part E transaction contract has been reviewed so the trigger and application use one agreed lock protocol.

1. Accept this Part E contract with both #15 and #16 feature owners.
2. Complete and peer-review #16 Part E's application transaction contract, including the §7.1 User → Slot → Booking lock order, Serializable behavior, retry semantics and the real-DB no-post-guard-contention proof strategy. This is a design dependency, not permission to implement the Booking API early.
3. Start from the then-current remote `sprint1`; re-check the schema/migration baseline. Add a new timestamped Prisma migration and matching model/relations; do not rewrite or regenerate existing Auth/Slot migrations.
4. In that **#33 Part F migration**, create the shared Booking table/constraints and the `booking_guard_s1()` function with row-level INSERT/UPDATE/DELETE and statement-level TRUNCATE trigger registrations described in BDF-D11/D12 and data-spec.md §7. Provision a separate non-owner application runtime role with no UPDATE/DELETE/TRUNCATE or DDL/trigger-management privileges; do not create a duplicate Booking guard in #16.
5. Confirm `btree_gist` is installed and usable by the migration role on the actual target PostgreSQL version. The current Slot migration already installs it; any repeated extension statement must be idempotent and must not drop the extension.
6. Run **BDF-01..BDF-22 and BDF-24..BDF-26 as the #33 pre-merge foundation proof gate** on real PostgreSQL, including fresh/upgrade migration tests, direct-SQL Offered/UPDATE/DELETE/TRUNCATE-guard tests, Q05 boundary and post-lock wait tests, synchronized DB-level race tests, runtime-role privilege checks, and inspection of final committed rows. Record PostgreSQL version, extension version/availability, exact commands, source SHA, and PASS/FAIL/SKIP/BLOCKED results. **BDF-23 is not part of this pre-merge gate** because it requires the complete #16 application transaction adapter.
7. Review and merge the #33 Part F migration into `sprint1` only after BDF-01..BDF-22 and BDF-24..BDF-26 pass; record its exact merged schema SHA in Issues #15 and #16. Only then may #15/#16 implement Booking-dependent application behavior against that accepted SHA.
8. After the merged schema SHA exists and the #16 Part F transaction adapter is implemented, #16 runs **BDF-23 as the joint post-merge integration gate** using the actual application adapter and real PostgreSQL barriers. Record the evidence in #16 and cross-link it from #33; do not claim BDF-23 PASS before this point. BDF-23 does not block the #33 migration PR from merging.
9. The complementary Slot lifecycle trigger for `Offered → Withdrawn` / no reactivation is a separate Sprint 2 migration and **must exist before any Sprint 2 withdrawal workflow is enabled**; it is not part of this Sprint 1 Booking foundation.

### 6. Peer-review checklist and open integration gate

The required reviewer @Tanaboonnnnn is also the provisional owner of #16, so this review must explicitly confirm that the shared fields/constraints satisfy both #15 and #16. Please review:

- [ ] BDF-D01..D12: field list, status semantics, interval snapshot, timestamps, ID-immutability boundary, trigger ownership, append-only DELETE/TRUNCATE guard and no duplicated Tutor ownership.
- [ ] Both FK delete/update policies and the composite Slot-window FK.
- [ ] Partial unique index and GiST exclusion semantics, including concurrent writes and adjacent intervals.
- [ ] `btree_gist` availability/permissions on the actual target PostgreSQL deployment.
- [ ] BDF-D11/D12: #33 Part F owns the shared guard function, row/statement triggers and append-only policy; #16 owns the application lock/transaction/retry adapter. Confirm the exact merge sequence and no duplicate guard is planned.

- [ ] #16 Part E records the System SDS User → Slot → Booking lock order and no-post-guard-contention / whole-transaction retry strategy before #33 Part F migration implementation.
- [ ] #33 Part F passes BDF-01..BDF-22 and BDF-24..BDF-26 before migration merge, including Offered/Q05, UPDATE/DELETE/TRUNCATE guards, `Cancelled → Booked`, Q05 60:00/59:59, post-lock cutoff crossing and runtime-role privilege boundary.
- [ ] #16 Part F owns BDF-23 after the #33 schema SHA is merged; this joint adapter proof is cross-linked from #33 and is not a pre-merge blocker for the #33 migration PR.
- [ ] No accidental Sprint 2 workflow, API/UI, `Slot.isBooked`, or OD-013 retry decision.

**P1 resolution proposed:** #33 Part F owns the one Booking guard function plus row-level INSERT/UPDATE/DELETE and statement-level TRUNCATE trigger registrations; it must pass BDF-01..BDF-22 and BDF-24..BDF-26 before its migration PR merges. The row/statement guards reject UPDATE/DELETE/TRUNCATE, while the separate non-owner app runtime role has no destructive DML or trigger/DDL bypass privileges. BDF-24/25 prove that committed Booking rows and derived occupancy survive attempted DELETE/TRUNCATE; BDF-26 proves the runtime-role boundary. #16 Part E/F owns the application lock order, transaction adapter and no-post-guard-contention / full-retry proof; #16 runs BDF-23 only after the #33 schema SHA is merged. The order is #34 Part E acceptance → #16 Part E acceptance → #33 Part F migration + BDF-01..BDF-22 and BDF-24..BDF-26 proof/merge → #15/#16 application implementation → #16 BDF-23 joint integration proof. BDF-23 is not a prerequisite for the #33 migration PR merge. This remains a proposed contract pending human acceptance; no implementation or test result is claimed here.

### 7. Traceability

| Foundation invariant | Requirements / tests |
|---|---|
| One active Booking per Slot | FR-S1-12, BR-S1-08/19, AC-S1-25, BDF-10/11 |
| One Customer cannot overlap active intervals across Tutors | FR-S1-13, BR-S1-09/10/19, AC-S1-26, BDF-12/13/14 |
| Slot interval snapshot and valid references | FR-S1-10/16, System SDS §3.3, BDF-05..09 |
| Cancelled is non-occupying; Past is not a state or completion | Q30, BR-S1-14, BR-S1-22, BDF-04/15 |
| #33 pre-merge DB durability, concurrency and append-only evidence | NFR-S1-03/04/05/12, BDF-01..22 and BDF-24..26 |
| #16 post-merge application/DB contention integration | System SDS §§7.1/7.3, BDF-23 (after #33 schema SHA) |
| Availability read predicates | #15 AVA-02, AVA-15, AVA-16, AVA-17 after the merged schema SHA is recorded |

### 8. Part E Definition of Done

- [ ] The required human peer reviewer has reviewed and accepted the common data shape and invariants for both #15 and #16.
- [ ] BDF-D11 trigger ownership, BDF-D12 append-only/role boundary, merge order, lock-order dependency and real-PostgreSQL proof gates are explicitly accepted by both feature owners.
- [ ] Any review changes are incorporated into the contract documents and the final accepted decisions are recorded in the PR.
- [ ] Part F migration work remains a separate reviewed change; no migration or implementation result is claimed by this Part E PR.

Overall Issue #33 remains open until its Part F migration and real-PostgreSQL verification acceptance criteria are completed, reviewed, merged, and the exact schema SHA is published to #15 and #16.

---

## E.3.2 D1-08A Shared Booking Data Specification (data-spec.md)

> **Proposed mapping and SQL intent only. NOT an applied migration, Prisma schema change, or PostgreSQL test result.**
> See foundation SDS, test plan, and whole-product System SDS §§3.2–3.3.

### 1. Canonical Booking fields

| Field | PostgreSQL / Prisma type | Nullability / default | Contract |
|---|---|---|---|
| `id` | `UUID` / `String` `@db.Uuid` | NOT NULL; server-generated UUID | Stable identity and **application-level immutable invariant**. PostgreSQL's primary key enforces uniqueness and NOT NULL but does not itself prevent an ID-changing `UPDATE`. Sprint 1's append-only Booking guard separately prohibits UPDATE, DELETE and TRUNCATE; this is a lifecycle boundary, not a dedicated ID-immutability guarantee. |
| `customerId` | `UUID` / `String` `@db.Uuid` | NOT NULL | FK to `User.id`; derived from authenticated Customer Session by #16, never accepted as an owner claim from the client. |
| `currentSlotId` | `UUID` / `String` `@db.Uuid` | NOT NULL | FK to the selected `Slot`; identifies the currently assigned Slot. |
| `startsAt` | `TIMESTAMPTZ(6)` / `DateTime` `@db.Timestamptz(6)` | NOT NULL | Persisted copy of the selected Slot's `startsAt`; not client input. |
| `endsAt` | `TIMESTAMPTZ(6)` / `DateTime` `@db.Timestamptz(6)` | NOT NULL | Persisted copy of the selected Slot's `endsAt`; not client input; must be greater than `startsAt`. |
| `status` | `TEXT` / `String` | NOT NULL; default `Booked` | CHECK permits exactly `Booked` or `Cancelled`. Only `Booked` occupies/conflicts. |
| `createdAt` | `TIMESTAMPTZ(6)` / `DateTime` `@db.Timestamptz(6)` | NOT NULL; `now()` | Database creation timestamp. |
| `updatedAt` | `TIMESTAMPTZ(6)` / `DateTime` `@db.Timestamptz(6)` | NOT NULL; initially `now()` | Prisma `@updatedAt` for application updates; metadata only, not a business clock or audit log. |

`tutorId` is intentionally **not** stored on Booking. The current Tutor is `Slot.tutorId` through `currentSlotId`. This prevents a duplicated Tutor reference from diverging from the selected Slot. The authenticated principal's role/active status remains an application authorization check; a normal FK cannot enforce a cross-table `User.role = 'Customer'` condition.

`Booking.id` is generated by the server/database on creation and is never accepted as mutable input. The #16 application contract must not expose an operation that replaces it; any future supported update path must preserve the original ID. This is an **application-level identity guarantee**, not a dedicated PostgreSQL ID-immutability guarantee. The separate Sprint 1 append-only prohibition below is a lifecycle boundary, not an ID-specific guard; no ID-specific trigger or SQL test is included in this foundation.

### 2. Relationship and delete/update policy

| Relationship | Cardinality | Proposed FK | Delete / update |
|---|---|---|---|
| `Booking.customerId → User.id` | One User to many Bookings | `booking_customer_fk` | `ON DELETE RESTRICT ON UPDATE RESTRICT` |
| `Booking.(currentSlotId, startsAt, endsAt) → Slot.(id, startsAt, endsAt)` | One Slot to many historical Bookings; zero or one active `Booked` Booking | `booking_current_slot_window_fk` | `ON DELETE RESTRICT ON UPDATE RESTRICT` |

The composite Slot FK requires a matching unique key on `Slot(id, startsAt, endsAt)`. `Slot.id` is already the primary key; the composite unique key exists specifically so PostgreSQL can enforce that the persisted Booking interval always matches its referenced Slot. It also prevents Slot time changes while a Booking references that exact interval. Existing Sprint 1 Slot immutability remains unchanged.

Restricting parent deletion preserves referenced Booking history and avoids cascading away a Customer's or Tutor's appointment record. Separately, Sprint 1 Booking rows themselves are append-only: UPDATE/DELETE are rejected by a row-level guard, TRUNCATE is rejected by a statement-level guard, and the application runtime role has no UPDATE/DELETE/TRUNCATE or DDL/trigger-management privileges. No routine application/admin exception may delete or truncate a Booking in Sprint 1. This is an engineering persistence boundary, **not** a general product data-retention policy. Any future anonymization, deletion, or archival workflow requires a separate decision and migration. Parent IDs are stable; they are not edited in normal operation.

### 3. Status and interval semantics

- `Booked` is the only Active/occupying state. A `Booked` row remains Active even after `endsAt`; elapsed time may be displayed as `Past`, but does not update status, imply attendance, create `Completed`, or release the Slot.
- `Cancelled` is a valid shared state and is excluded from both active constraints. No Customer/Tutor cancellation action is introduced in Sprint 1 by this foundation. Cancelled rows in foundation tests are isolated test fixtures; cancellation workflows and metadata remain later-scope work.
- The database must enforce `startsAt < endsAt`.
- Intervals use half-open `[startsAt, endsAt)` semantics. Positive-duration overlap is exactly `existing.startsAt < candidate.endsAt AND candidate.startsAt < existing.endsAt`. Adjacent intervals are allowed.
- The interval is copied from the actual selected Slot after it is read/locked by #16. A composite FK, not application convention alone, guarantees that `Booking.startsAt/endsAt` equal the referenced Slot's values.

### 4. Proposed Prisma mapping

The following is a **review target**, not code to paste without running Prisma validation against the exact project version. SQL-only partial/exclusion constraints are specified in §5 and must not be removed by a later generated migration.

```
model User {
  // Existing fields/relations remain unchanged.
  customerBookings Booking[] @relation("BookingCustomer")
}

model Slot {
  // Existing fields/relations remain unchanged.
  bookings Booking[] @relation("BookingCurrentSlot")

  // Required target key for the composite Booking FK.
  @@unique([id, startsAt, endsAt], map: "slot_id_window_unique")
}

model Booking {
  // Stable identity; BDF-D01 is application-level. Sprint 1 separately rejects Booking UPDATE/DELETE/TRUNCATE.
  id            String   @id @default(uuid()) @db.Uuid
  customerId    String   @db.Uuid
  currentSlotId String   @db.Uuid
  startsAt      DateTime @db.Timestamptz(6)
  endsAt        DateTime @db.Timestamptz(6)
  status        String   @default("Booked")
  createdAt     DateTime @default(now()) @db.Timestamptz(6)
  updatedAt     DateTime @default(now()) @updatedAt @db.Timestamptz(6)

  customer User @relation(
    "BookingCustomer",
    fields: [customerId],
    references: [id],
    onDelete: Restrict,
    onUpdate: Restrict,
    map: "booking_customer_fk"
  )
  currentSlot Slot @relation(
    "BookingCurrentSlot",
    fields: [currentSlotId, startsAt, endsAt],
    references: [id, startsAt, endsAt],
    onDelete: Restrict,
    onUpdate: Restrict,
    map: "booking_current_slot_window_fk"
  )

  @@index([customerId], map: "Booking_customerId_idx")
  @@index([currentSlotId], map: "Booking_currentSlotId_idx")
}
```

Do not add a Prisma `@@unique([currentSlotId])`: that would incorrectly prevent a Cancelled historical Booking and a later Booking from referring to the same Slot. The active-only uniqueness rule is a SQL partial unique index.

### 5. Proposed PostgreSQL migration intent

This fragment records the intended table/index constraints for peer review. It is **not** a complete timestamped migration and has not been run. The #33 Part F migration must also install the `booking_guard_s1()` function and row-level/statement-level trigger registrations specified in §7; they are deliberately not represented as completed SQL implementation here. Reconcile exact constraint names, Prisma migration output, extension/role privileges, and trigger behavior before acceptance.

```sql
-- Already installed by the merged Tutor Slots migration on the normal chain.
-- Keep this idempotent for a fresh/verified baseline; never DROP the extension.
CREATE EXTENSION IF NOT EXISTS btree_gist;

-- PostgreSQL requires a unique referenced key for the composite FK.
ALTER TABLE "Slot"
  ADD CONSTRAINT slot_id_window_unique
  UNIQUE ("id", "startsAt", "endsAt");

CREATE TABLE "Booking" (
  "id" UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  "customerId" UUID NOT NULL,
  "currentSlotId" UUID NOT NULL,
  "startsAt" TIMESTAMPTZ(6) NOT NULL,
  "endsAt" TIMESTAMPTZ(6) NOT NULL,
  "status" TEXT NOT NULL DEFAULT 'Booked',
  "createdAt" TIMESTAMPTZ(6) NOT NULL DEFAULT now(),
  "updatedAt" TIMESTAMPTZ(6) NOT NULL DEFAULT now(),
  CONSTRAINT booking_status_check
    CHECK ("status" IN ('Booked', 'Cancelled')),
  CONSTRAINT booking_positive_interval
    CHECK ("startsAt" < "endsAt"),
  CONSTRAINT booking_customer_fk
    FOREIGN KEY ("customerId")
    REFERENCES "User" ("id")
    ON DELETE RESTRICT ON UPDATE RESTRICT,
  CONSTRAINT booking_current_slot_window_fk
    FOREIGN KEY ("currentSlotId", "startsAt", "endsAt")
    REFERENCES "Slot" ("id", "startsAt", "endsAt")
    ON DELETE RESTRICT ON UPDATE RESTRICT
);

-- Full indexes also support parent-FK checks for historical Cancelled rows.
CREATE INDEX "Booking_customerId_idx"
  ON "Booking" ("customerId");
CREATE INDEX "Booking_currentSlotId_idx"
  ON "Booking" ("currentSlotId");

-- Race B: one active Booking at most for one exclusive Slot.
CREATE UNIQUE INDEX booking_one_active_per_slot
  ON "Booking" ("currentSlotId")
  WHERE "status" = 'Booked';

-- Race C: one Customer cannot have positive-duration overlapping active windows.
-- [start,end) allows exact adjacency. btree_gist supplies UUID equality in GiST.
ALTER TABLE "Booking"
  ADD CONSTRAINT booked_customer_no_overlap
  EXCLUDE USING gist (
    "customerId" WITH =,
    tstzrange("startsAt", "endsAt", '[)') WITH &&
  )
  WHERE ("status" = 'Booked');
```

### Constraint behavior matrix

| Attempt | Expected database result |
|---|---|
| Insert valid `Booked` row with real Customer, Slot and matching interval | Accept one committed row. |
| Insert valid `Cancelled` fixture for a real Customer/Slot | Accept; it does not occupy or conflict. |
| Insert `startsAt >= endsAt` | Reject by `booking_positive_interval`. |
| Insert unsupported status | Reject by `booking_status_check`. |
| Insert unknown Customer or Slot | Reject by the corresponding FK. |
| Insert Booking interval that differs from the referenced Slot | Reject by `booking_current_slot_window_fk`. |

| Attempt | Expected database result |
| --- | --- |
| Insert second `Booked` row for same Slot | Reject by `booking_one_active_per_slot`, including concurrent attempts. |
| Insert overlapping `Booked` interval for same Customer on another Tutor's Slot | Reject by `booked_customer_no_overlap`, including concurrent attempts. |
| Insert adjacent `Booked` interval for same Customer | Accept if all other constraints pass. |
| Insert overlapping row after prior row is `Cancelled` | Accept if all other constraints pass. |
| Delete referenced User or Slot / update referenced primary key or Slot window | Reject by restrictive FK. |
| `DELETE FROM Booking` in Sprint 1 | Reject by the row-level `BEFORE DELETE` guard (`0A000`); runtime role also lacks DELETE privilege (`42501`). |
| `TRUNCATE Booking` in Sprint 1 | Reject by the statement-level `BEFORE TRUNCATE` guard (`0A000`); runtime role also lacks TRUNCATE privilege (`42501`). |

### 6. Index and extension notes

- `Booking_customerId_idx` and `Booking_currentSlotId_idx` are full B-tree indexes. They also cover FK checks for Cancelled historical rows; the active-only partial index does not.
- `booking_one_active_per_slot` is partial on `status = 'Booked'`; cancelled history may share a Slot reference.
- `booked_customer_no_overlap` is a GiST exclusion constraint over Customer UUID equality and the half-open timestamp range. `btree_gist` is required for the UUID equality operator class. Verify the extension and its version/permissions on the actual PostgreSQL target; do not assume a local extension install proves managed-database availability.
- The exclusion constraint's GiST index also supports the overlap predicate; any extra query index must be justified by real `EXPLAIN (ANALYZE, BUFFERS)` evidence, not added speculatively.
- `Slot(id, startsAt, endsAt)` composite unique key is required for the composite FK even though `id` is already unique.

### 7. Booking trigger ownership and Sprint 1 guard

#### 7.1 Explicit owner and merge order (BDF-D11)

**Decision proposed for peer acceptance:** one `booking_guard_s1()` function and its two trigger registrations are database artifacts owned by **Issue #33 Part F** and installed by the shared Booking migration: (1) a row-level `BEFORE INSERT OR UPDATE OR DELETE` trigger and (2) a statement-level `BEFORE TRUNCATE` trigger. Both use the same guard function; #16 does not create a second guard migration. **Issue #16 owns the application transaction adapter** that acquires the System SDS locks before the INSERT guard runs and proves the post-guard contention behavior. This split follows the System SDS §§3.3, 7.1 and 7.3 and Issue #33's shared database-enforced foundation scope.

The required sequence is:

1. Both #15 and #16 feature owners accept this #33 Part E contract.
2. #16 Part E is reviewed and records the exact application lock order, Serializable transaction, retry behavior and no-post-guard-contention proof strategy. The #33 migration must implement against that agreed protocol.
3. #33 Part F adds the Prisma Booking model, forward-only SQL migration, integrity constraints, the shared Booking guard function/trigger registrations, and the application-role privilege boundary; it then runs the **#33 pre-merge foundation proof set BDF-01..BDF-22 plus BDF-24..BDF-26** in tests.md. BDF-23 is explicitly excluded from this pre-merge gate.
4. The reviewed #33 Part F PR may merge into `sprint1` only after BDF-01..BDF-22 and BDF-24..BDF-26 pass; record its exact merged schema SHA in Issues #15 and #16.
5. Only after that schema SHA exists may #15/#16 begin Booking-dependent application implementation. #16 Part F then owns and runs **BDF-23 as a joint integration gate** against its complete application transaction adapter. #16 must not duplicate the trigger in its own migration.

### 7.2 Required Booking trigger behavior in #33 Part F

The migration must install one shared PostgreSQL `booking_guard_s1()` trigger function with two registrations on `Booking`: (1) a row-level `BEFORE INSERT OR UPDATE OR DELETE` trigger (not a column-limited UPDATE trigger), and (2) a statement-level `BEFORE TRUNCATE` trigger. The row-level trigger's first operation for **every** `UPDATE` **or** `DELETE` must be to reject the operation with stable SQLSTATE `0A000` (`feature_not_supported`) before inspecting mutable row values, acquiring a Slot lock, or evaluating Q05. This blocks `Cancelled → Booked`, `Booked → Cancelled`, Slot/window moves, Customer reassignment, ID replacement, metadata-only updates and direct row deletion. The statement-level trigger rejects every `TRUNCATE` statement with the same SQLSTATE; a row-level DELETE trigger alone is insufficient because TRUNCATE does not fire row triggers. No Sprint 1 application path or direct-SQL path may update/delete/truncate a Booking row.

For an `INSERT` whose `NEW.status = 'Booked'`, the trigger must (remediated in Issue #39):

1. Lock the Customer User row with `PERFORM 1 FROM public."User" AS u WHERE u."id" = NEW."customerId" FOR UPDATE;` in `BEFORE ROW` trigger. If `customerId` does not exist, the query returns zero rows without failing, allowing the composite FK (`booking_customer_fk`) to raise standard foreign key violation `23503`. Acquiring the Customer User lock inside `BEFORE ROW` trigger guarantees that direct-SQL writers acquire `User(customerId)` before inserting uncommitted tuples into table heap, unique index, or `booked_customer_no_overlap` GiST exclusion index, preventing post-`T_elig` reverse wait and `40P01` deadlock on concurrent application transactions.

1. Lock the referenced Slot row with `SELECT ... FOR UPDATE` and re-read its persisted lifecycle and interval in the writer's transaction.
2. Reject if the Slot does not exist, is not currently `Offered`, or its interval does not match the Booking snapshot. The composite FK independently enforces interval equality and remains mandatory.
3. Only after both User and Slot locks have been acquired, sample PostgreSQL `clock_timestamp()` as `T_elig` and reject unless `Slot.startsAt - T_elig >= interval '60 minutes'`. Equality passes; 59:59 fails. Do not accept a client-supplied or application-precomputed timestamp as authoritative.
4. Raise a non-success database error on rejection so the entire transaction rolls back. The trigger is a final DB guard for direct SQL/application bypass; it does not replace service authorization, the application lock order or the unique/exclusion constraints.

An `INSERT` of a valid `Cancelled` test fixture remains possible and does not occupy a Slot; the blanket UPDATE prohibition prevents that fixture (or any other row) from being transitioned to `Booked`. The DELETE and TRUNCATE guards preserve committed Booking history and prevent occupancy from disappearing without a reviewed lifecycle action. This closes the direct-SQL `Cancelled → Booked` Q05 bypass and deletion/truncation bypass without adding a Sprint 2 cancellation/reschedule workflow. These table-wide mutation prohibitions are Sprint 1 lifecycle boundaries, not a dedicated `Booking.id` immutability policy. Any future update/cancellation/reschedule/deletion behavior requires its own reviewed contract and migration before enablement.

### 7.3 #16 application transaction responsibility

Before issuing the guarded INSERT, #16 must use the System SDS global hierarchy: lock all affected User principals (authenticated Customer and selected Slot's actual Tutor) in ascending UUID order, then all affected Slot rows in ascending UUID order, then existing Booking rows in ascending UUID order. Use Serializable isolation as specified. The selected Slot must already be locked by the application transaction when the trigger executes, so the trigger's `SELECT ... FOR UPDATE` does not introduce a new lock-order inversion or an unaccounted post-`T_elig` wait.

The #16 Part E/Part F proof must show that no conflict-capable unique/exclusion wait can occur after the trigger samples `T_elig`. If an unaccounted wait is possible, the complete transaction must abort and retry with all locks reacquired and a fresh DB clock; never reuse the earlier `T_elig` or substitute a blanket commit-time cutoff. The actual no-post-guard-contention or full-transaction retry behavior is a real-PostgreSQL acceptance gate, not a documentation-only claim.

### 7.4 Application runtime database role boundary

The deployed application runtime role must be distinct from the migration/table-owner role. It must not own `Booking`, be a superuser, inherit membership in the migration/owner role, or have DDL/trigger-management privileges. It must not have `UPDATE`, `DELETE`, or `TRUNCATE` privileges on `Booking`, and must not be able to set `session_replication_role` to bypass triggers. It retains only the read/insert privileges needed by the application. Migration credentials are used only by the migration/deployment path

and are never used by API runtime processes. No application, operations, or administrator role is authorized to delete/truncate Sprint 1 Booking rows. The migration/table-owner role is for schema changes only and is not used for runtime or data-purge operations. Any future deletion, retention, or archival workflow requires a separate reviewed decision and migration; no emergency trigger-bypass exception is assumed.

BDF-24 and BDF-25 test the real application runtime role's privilege denial and independently exercise the row/statement guards with a non-owner, non-bypass DML probe role. BDF-26 verifies role ownership, membership, DDL/trigger and replication-bypass boundaries. If the deployed environment cannot provide this separation, the foundation gate is BLOCKED and must not be reported PASS.

#### 7.5 Later Slot lifecycle trigger boundary

The complementary Slot `BEFORE UPDATE` lifecycle guard for `Offered → Withdrawn`, rejection of occupied withdrawal and permanent rejection of `Withdrawn → Offered` is **not part of this Sprint 1 foundation migration**, because the Sprint 1 Slot trigger does not permit a Withdrawn transition and #33 excludes the Sprint 2 withdrawal workflow. A separate reviewed Sprint 2 migration must install and real-DB-test that guard **before** any withdrawal feature is enabled. Do not defer or omit the Sprint 1 Booking row/statement guards or runtime-role boundary described above.

### 8. Migration/backfill constraints

- Use a new forward-only migration after the existing Auth and Tutor Slots migrations.
- Include the `booking_guard_s1()` function and its row-level/statement-level trigger registrations from §7 in the #33 Part F migration; provision the runtime role separately from the migration/table owner; do not create a duplicate Booking guard in #16.
- The verified baseline contains no Booking table/rows; no backfill or synthetic production data is needed.
- Provision separate migration/table-owner and application runtime roles. The runtime role must not own Booking, be superuser, inherit the owner role, hold UPDATE/DELETE/TRUNCATE or DDL/trigger-management privileges, or bypass triggers.
- Preserve all existing User, Session, AuthAttempt, Slot rows, indexes, triggers and constraints. Do not edit old migration files.
- Do not add `Slot.isBooked` or another denormalized occupancy flag. Occupancy is derived from `Booking.status = 'Booked'` and `currentSlotId`.
- No Booking API, application service, UI, cancellation/reschedule workflow, history, notification, or OD-013 idempotency mechanism belongs in this migration.
- Run both fresh-database and exact-baseline upgrade tests on disposable PostgreSQL databases. The database version and extension availability are evidence fields in tests.md.

---

## E.3.3 D1-08A Shared Booking Data Test Specification (tests.md)

> **PLANNED TESTS ONLY — NOT IMPLEMENTED OR RUN.** Passing these cases requires real PostgreSQL and inspection of committed rows/constraint outcomes; Prisma mocks or HTTP-only assertions are insufficient. **Gate split:** BDF-01..BDF-22 and BDF-24..BDF-26 are the #33 Part F pre-merge foundation gate. BDF-23 is a separate #16 Part F joint integration gate, run only after the #33 migration is merged and its exact schema SHA is recorded; BDF-23 must not block the #33 migration PR merge. See foundation SDS and data spec.

### 1. Test environment and evidence

- Use a disposable PostgreSQL database, not a shared or production database.
- Record `SELECT version()`, server major/minor, installed `btree_gist` extension version, migration-owner and application-runtime role names/privileges, Node/Prisma versions, migration SHA, source SHA, fixture IDs, exact command, and PASS/FAIL/SKIP/BLOCKED result. Never expose credentials.
- Run one migration test from an empty database and another from the exact `sprint1` migration chain. Do not use a manually approximated schema.
- Use synthetic Customers and Tutors only. Create actual committed Slot and Booking rows satisfying all FKs/constraints.
- For concurrency tests, use separate PostgreSQL connections and explicit synchronization barriers. `Promise.all` without a controlled interleaving is not sufficient. Inspect the final committed rows after both transactions settle.

- Tests that use a Cancelled Booking must create an isolated `Cancelled` fixture with a direct INSERT inside the disposable database. Do not use UPDATE or DELETE to create or mutate a fixture, and never TRUNCATE to reset it: the Sprint 1 Booking guards reject these operations. UPDATE/DELETE/TRUNCATE appear only as explicit negative-test actions in BDF-20 and BDF-24/25.
- Verify that the application runtime role is distinct from the migration/table-owner role and is not owner/superuser; it has no UPDATE/DELETE/TRUNCATE or DDL/trigger-management privilege and cannot set `session_replication_role` to bypass triggers.
- No test case below is a PASS in this Part E PR.

### 2. Planned database test cases

| ID | Trace | Setup / action | Required observable result |
|---|---|---|---|
| BDF-01 | NFR-S1-12 | Apply the agreed migration chain to an empty disposable PostgreSQL database. | Migration completes; Prisma schema and SQL constraints agree; Booking table, FKs, checks and indexes exist. |
| BDF-02 | NFR-S1-03/12 | Build a disposable database by applying every current `sprint1` migration, then apply the Booking foundation migration. | Upgrade succeeds without manual schema repair. |
| BDF-03 | NFR-S1-03/05 | Compare Auth/Slot rows and schema objects before/after the foundation migration. | Existing User, Session, AuthAttempt and Slot data, triggers, indexes and constraints are preserved; no destructive old-migration edit. |
| BDF-04 | Q30, BR-S1-14, BR-S1-22 | Insert a valid `Booked` row and a valid `Cancelled` test row with matching real Customer/Slot references; after the Booked interval ends, read the stored state and derived display classification. | Both statuses persist exactly; `Booked` remains the business status after elapsed time, `Past` is display-only, and `Cancelled` is historical/non-occupying. |
| BDF-05 | Data contract | Insert `startsAt = endsAt` and `startsAt > endsAt`. | Both reject at PostgreSQL `booking_positive_interval`; no row commits. |
| BDF-06 | Data contract | Insert a status outside `Booked` / `Cancelled`. | Reject at `booking_status_check`; no row commits. |
| BDF-07 | FR-S1-10 | Insert with a non-existent `customerId`. | Reject by `booking_customer_fk`; no row commits. |
| BDF-08 | FR-S1-10 | Insert with a non-existent `currentSlotId` /Slot-window reference. | Reject by `booking_current_slot_window_fk`; no row commits. |
| BDF-09 | System SDS §3.3 | Insert a Booking whose `currentSlotId` is real but whose `startsAt` or `endsAt` differs from that Slot. | Reject by the composite Slot-window FK; persisted Slot/Booking data remain unchanged. |
| BDF-10 | FR-S1-12, BR-S1-08 | Sequentially insert two `Booked` rows for the same Slot and different Customers. | First commits; second is rejected by `booking_one_active_per_slot`; exactly one active row remains. |
| BDF-11 | AC-S1-25, NFR-S1-04 | Two Customers concurrently insert a `Booked` row for the same Slot under a barrier. | At most one transaction commits; exactly one active row remains; no two success outcomes or partial claims. |
| BDF-12 | FR-S1-13, BR-S1-09 | One Customer has a `Booked` interval on Tutor A; insert a positive-overlap Booking for a distinct Tutor B Slot. | Second row is rejected by `booked_customer_no_overlap`; first row remains unchanged. |
| BDF-13 | AC-S1-26, NFR-S1-04 | One Customer concurrently inserts Bookings for distinct overlapping Slots owned by two Tutors under a barrier. | At most one overlapping active row commits; final committed state contains no same-Customer overlap. |
| BDF-14 | BR-S1-10 | One Customer has `[13:00,14:00)` and inserts `[14:00,15:00)`. | Both commit if all other constraints pass; exact adjacency is not an overlap. |

| ID | Trace | Setup / action | Required observable result |
|---|---|---|---|
| BDF-15 | Q30, #15 AVA-17 | In separate controls: (a) Customer A has a Cancelled row on Slot S and Customer B books Slot S; (b) Customer A has a Cancelled interval on Tutor A and books an overlapping Slot on Tutor B. | Both new Booked rows commit; Cancelled history neither occupies the Slot nor participates in Customer overlap. |
| BDF-16 | Data contract | Attempt to delete a referenced Customer/Slot or mutate a referenced parent primary key/Slot window. | Operations reject and parent/Booking remain intact. Record the actual guard/constraint: the existing Slot immutability trigger may reject Slot mutations before the composite FK is evaluated; verify the FK definition independently. `Booking.id` mutation is intentionally not a DB test because BDF-D01 defines its immutability at the application boundary only. |
| BDF-17 | #15 AVA-02/15/16/17 | Query persisted rows using `status = 'Booked'`, `currentSlotId`, and half-open interval predicates. | Occupied Slot and same-Customer overlap predicates match actual committed data; adjacent and Cancelled controls are handled correctly. |
| BDF-18 | System SDS §3.3 | Verify `btree_gist` exists and supports the UUID equality/range exclusion migration under the actual migration role. | Extension creation/use succeeds on the recorded target version without dropping an existing extension; missing privilege/version is BLOCKED, not silently skipped. |
| BDF-19 | NFR-S1-12 | Inspect Prisma model, migration SQL, and database catalog after generation/deploy. | Relations/types/indexes match; Prisma schema drift or a generated migration dropping SQL-only partial/exclusion constraints fails the test. |
| BDF-20 | System SDS §3.3; BDF-D11 | In a disposable DB, create a controlled non-`Offered` Slot fixture using privileged setup only, restore normal Slot guards, then use a non-owner DML probe role with INSERT/UPDATE privileges but no DDL/trigger bypass to attempt a direct-SQL `Booked` INSERT against it. Separately, INSERT a valid `Cancelled` fixture for an `Offered` Slot whose start is less than 60 minutes away, then use the same probe role to attempt direct SQL `UPDATE status = 'Booked'` (the `Cancelled → Booked` Q05-bypass case). Also attempt a `Booked → Cancelled` or Slot/window UPDATE as a control. | The trigger rejects the non-`Offered` `Booked` INSERT and rejects **every UPDATE** with SQLSTATE `0A000`, including `Cancelled → Booked` even though Q05 would fail; no row changes state, no moved/active Booking commits, and the original fixture rows remain intact. This proves the guard independently of the #16 API. |
| BDF-21 | Q05; System SDS §§3.3/4; BDF-D11 | In the disposable DB, exercise the Q05 comparison with fixed DB-side `startsAt` / `T_elig` instants at exactly 60:00 and 59:59; separately execute the actual trigger path with the non-owner DML probe role and real PostgreSQL clock; verify it reads `clock_timestamp()` only after the Slot lock, never a caller-supplied time. | The exact comparison accepts 60:00 and rejects 59:59; the trigger integration proves the authoritative time source/order. If the exact-boundary subcase cannot be exercised without bypassing the production decision path, mark that subcase BLOCKED rather than PASS. |
| BDF-22 | System SDS §§3.3/7.1/7.3; BDF-D11 | On independent PostgreSQL sessions, hold the selected Slot row lock in transaction A. Start a direct Booking INSERT using the non-owner DML probe role in transaction B while the Slot has more than 60 minutes remaining, then release A only after the cutoff has passed. Capture both backend PIDs, `pg_blocking_pids`, trigger-observed `T_elig`, SQLSTATE and final rows. | B waits on the Slot lock; after the lock is acquired the trigger samples a fresh `T_elig` and rejects the now-too-late Booking. No row commits. This proves the trigger does not sample Q05 before its own Slot-lock wait. |
| BDF-23 | System SDS §§7.1/7.3; #16 Part E/F; BDF-D11 | **Run only after #33 Part F is merged and its exact schema SHA is recorded.** Run the complete #16 transaction adapter against real PostgreSQL with independent sessions and synchronized same-Slot and same-Customer/cross-Tutor attempts. Instrument lock waits and trigger `T_elig`; include a control that forces an unexpected conflict-capable index/constraint wait. | Prove all conflict-capable waits occur before `T_elig`; otherwise the complete transaction aborts/retries with all locks reacquired and a fresh DB clock. Inspect final committed rows and prove no stale-eligibility success, duplicate claim or partial write. This is a **post-merge joint integration gate**, owned by #16; it is not part of the #33 pre-merge gate (BDF-01..22 and BDF-24..26). |

| ID | Trace | Setup / action | Required observable result |
|---|---|---|---|
| BDF-24 | BDF-D12; Sprint 1 append-only contract | Commit a valid `Booked` fixture and confirm its Slot is occupied. Using the actual application runtime role, attempt direct `DELETE FROM "Booking" WHERE id = ...`; then, in a disposable test database, use a non-owner DML probe role with DELETE privilege but no trigger/DDL bypass to exercise the row-level guard. | The runtime role is denied by privilege ( `42501` ); the probe role is rejected by the `BEFORE DELETE` guard ( `0A000` ). After rollback and a fresh connection, the committed Booking row still exists and the Slot remains occupied. No cancellation/deletion endpoint is involved. |
| BDF-25 | BDF-D12; Sprint 1 append-only contract | Commit a valid `Booked` fixture and confirm its Slot is occupied. Using the actual application runtime role, attempt `TRUNCATE TABLE "Booking"`; then, in a disposable test database, use a non-owner DML probe role with TRUNCATE privilege but no trigger/DDL bypass to exercise the statement-level guard. | The runtime role is denied by privilege ( `42501` ); the probe role is rejected by the `BEFORE TRUNCATE` statement guard ( `0A000` ). After rollback and a fresh connection, the committed Booking row still exists and the Slot remains occupied. This proves the statement guard is not replaced by a row-level DELETE trigger. |
| BDF-26 | BDF-D12; least-privilege deployment boundary | Connect as the configured application runtime role and inspect `current_user` , role attributes/membership, table ownership and effective privileges. Attempt `ALTER TABLE "Booking" DISABLE TRIGGER ALL` and `SET session_replication_role = replica` ; inspect whether the role owns the table, is superuser, inherits the migration/owner role, or has DDL/trigger-management privileges. | Runtime role is distinct from the migration/table owner, is not owner/superuser, has no UPDATE/DELETE/TRUNCATE or DDL/trigger-management privileges, cannot disable the guards or set replication-role bypass, and retains only required application SELECT/INSERT access. Any missing separation is BLOCKED, not PASS. |
| BDF-28 | Issue #39 remediation; BDF-D11 | Targeted red→green 2-writer proof (Adapter protocol + direct-SQL Rogue): Part 1 reproduces the legacy canonical #33 baseline in a disposable schema showing Adapter blocks on Rogue in GiST (reverse wait); Part 2 proves that under migration `20261109000000_booking_guard_user_lock` , Rogue is blocked inside `booking_guard_s1()` on `User(customerId) FOR UPDATE` before index entry, Adapter INSERT completes with zero reverse wait ( `adapterReverseBlockers = []` ), delays across 60m cutoff and commits successfully ("valid 60:00 guard may still commit later"), Rogue unblocks and fails with `23P01` (never `40P01` deadlock), and exactly 1 Booked row commits. | **PASS** |

### 3. Constraint outcome interpretation

Expected PostgreSQL classes for isolated negative cases:

- CHECK violations: SQLSTATE `23514` .
- Foreign-key violations: SQLSTATE `23503` .
- Unique partial-index conflicts: SQLSTATE `23505` .
- Exclusion conflicts: SQLSTATE `23P01` .
- The Sprint 1 Booking row guard raises SQLSTATE `0A000` ( `feature_not_supported` ) for UPDATE/DELETE and the statement-level TRUNCATE guard raises the same code; BDF-20, BDF-24 and BDF-25 must verify the guards. The application runtime role's denied UPDATE/DELETE/TRUNCATE privileges raise `42501` .
- Serializable/deadlock outcomes may surface as `40001` / `40P01` if the accepted transaction strategy uses them; #16 must classify and handle them according to its reviewed contract.

For concurrent cases, do not require one exact error code when PostgreSQL may report a serialization failure under the selected isolation/locking design. The acceptance oracle is the final committed state plus correctly classified non-success for the losing operation.

### 4. Tests owned outside this foundation

| Behavior | Owner / evidence |
|---|---|
| Customer role, active account and Session-derived `customerId` | #16 API/transaction tests; the FK alone does not enforce role. |

| Behavior | Owner / evidence |
|---|---|
| Booking Offered-state, Q05 database guard and Sprint 1 row-level UPDATE/DELETE prohibition ( `BEFORE INSERT OR UPDATE OR DELETE` , 60:00/59:59, Slot-lock wait, `Cancelled → Booked` rejection) | #33 Part F migration and BDF-20..22; all are pre-merge foundation gates and direct-SQL tests must prove the trigger independently of the API. |
| Booking DELETE/TRUNCATE guard and application runtime role boundary | #33 Part F migration/deployment contract and BDF-24..26; pre-merge gates prove actual runtime privilege denial, row/statement trigger rejection and committed occupancy preservation. |
| Application lock order and no-post-guard-contention / full-transaction retry proof | #16 Part E/F and BDF-23; run only after #33 Part F is merged and the schema SHA is recorded. BDF-23 is not a prerequisite for #33 migration merge. |
| `Booking.id` immutability | Application-level invariant only (BDF-D01): #16 generates the ID server-side and accepts no ID replacement. Any future update/reschedule path must prove it preserves the original ID; no DB immutability guard or SQL negative test is claimed by #33. |
| Duplicate/uncertain HTTP request response semantics (OD-013) | #16 Part E decision and #16 API tests; not decided here. |
| Customer availability 60-day horizon and safe response allowlist | #15 AVA tests; OD-002 is confirmed as 60 days in Issue #15. |
| Browser/UI, Bangkok rendering, session switch and accessibility | #15 UI/API/E2E tests; not a database foundation test. |
| Customer/Tutor Booking retrieval and record-level privacy | F-S1-05 owner contract/tests; no retrieval endpoint is added here. |
| Sprint 2 cancellation/reschedule/withdrawal/notification and Slot lifecycle transition triggers | Separate Sprint 2 contracts and migrations; this Part E does not implement them. |

### 5. Part F evidence ledger template

The implementation PR must replace this planned status with actual results; do not copy `PASS` without command output and final database inspection.

| Evidence field | Required value |
|---|---|
| PostgreSQL server | Exact `SELECT version()` output |
| Extensions | `btree_gist` version and migration-role privilege evidence |
| Database roles | Application runtime role, migration/table-owner role, role memberships, ownership and effective Booking privileges |
| Destructive-operation proof | DELETE/TRUNCATE runtime denial, guard-probe SQLSTATEs, committed Booking row and occupied Slot after rollback |
| Base schema | Exact `sprint1` migration head SHA |
| Migration | New migration path and SHA |
| Test source | Commit SHA and test file paths |
| Commands | Exact fresh DB, baseline upgrade, and test commands |
| Results | Count of PASS / FAIL / SKIP / BLOCKED; link logs/evidence |
| Concurrency | Barrier setup, connections, final committed rows, losing error classification |
| Review | Human reviewer and accepted schema SHA |

**Part E status:** BDF-01..BDF-26 are planned, with the execution split above. #33 Part F must pass BDF-01..BDF-22 and BDF-24..BDF-26 before its migration PR merges; #16 Part F runs BDF-23 after the merged schema SHA exists. No migration, database test, API, UI, or concurrency result is claimed by this documentation-only PR.

---

## E.4 F-S1-03: Customer Availability Browse & Filter

---

### E.4.1 F-S1-03 Customer Availability Feature SDS (specification.md)

> **2026-11-10 UX-only Option A amendment proposed (Issue #44, pending peer acceptance):** Replace only the Customer Availability page's simultaneous full-list presentation ( `dateGroups.map(...)` ) with **Option A — Date-First Monthly Calendar (Progressive Disclosure)** as requested in Issue #15 comment #6763909620. See dated UX decision, amended UI contract, and `UX-CAL-01..10` STS. This follow-up is separate from Deliverable 1 (#18 / PR #43).
>
> **Unchanged domain/security contract:** `GET /api/v1/customer/availability` remains unfiltered with zero query parameters ( `BR-S1-20` , `OD-AV-03` ), returning exact DTO allowlist ( `slotId` , `tutorRef` , `startsAt` , `endsAt` , `meta.evaluatedAt` , `Cache-Control: no-store` ), single PostgreSQL `T_view` , `OD-AV-01..08` , `OD-AV-02` display-name gate, `F-S1-04` CSRF/Session Binding/ `T_elig` /SERIALIZABLE Booking safety, and `F-S1-05` `การจองของฉัน` tab.
>
> **`OD-002` conflict & provenance reconciliation:** docs/srs.md and historical Part E ( `PR #32` ) §4/§5 below originally recorded `OD-002` (maximum advance horizon) as `OPEN` . Subsequently, Issue #15 comments #6685976712 / #6721920473 and merged Part F PR #37 ( `apps/api/src/availability.ts` , `AVA-03` ) confirmed and implemented **`OD-002 = 60 days`** evaluated at database `T_view` ( `Slot.startsAt <= view_clock.evaluated_at + INTERVAL '60 days'` ). Month navigation uses validated server offers + `meta.evaluatedAt` dynamically, never browser-clock filtering or hardcoded 2–3 month limits.
>
> **Mandatory sequential gate (Two-PR Gate):** Obtain independent peer review from @Tanaboonnnnn and merge this docs-only Part E amendment into `sprint1` before branching any Part F React/CSS/test implementation PR under Issue #44. Historical `#15` baseline Part E/Part F artifacts remain merged via PR #32 and PR #37.

> **Historical baseline Part E note (PR #32):** Issue #15; provisional owner @Chxtamos; independent peer reviewer @Tanaboonnnnn. Decision states below reflect the peer-review decision record in PR #32 comment #6683929084. These are engineering/design decisions, not new stakeholder business rules. This change does not implement UI/API code, add a migration, execute tests or close the issue.

#### 1. Authority and scope

Sources: Sprint 1 requirements (FR-S1-08/09/13/18, AC-S1-15..18, BR-S1-06/07/09/10/11/12/15/17/20/21, NFR-S1-01/07/08/09/10/12, Q28), SRS, System SDS, Feature Inventory, Traceability, AGENTS.md, accepted Auth contract and Tutor Slot contract.

**Outcome:** an authenticated Customer discovers a real eligible Tutor Slot, identifies the Tutor using an approved public display name when its data gate is cleared (otherwise an opaque Tutor reference), sees Bangkok start/end time, and selects that offer without seeing another Customer's private Booking data.

**In scope:** Customer-only read access to current Offered Slots; Customer-specific bookability projection; safe Tutor/Slot references; a conditional Tutor public-display-name data gate; UTC API and Asia/Bangkok UI time; privacy allowlist; loading/empty/error/retry/session-change states; planned API, DB, browser, timezone and privacy tests.

**Out of scope:** Booking create/confirm/history/detail (#16/#17); Tutor Slot management/dashboard (#14); public/anonymous discovery; any unapproved Tutor profile/name/email/phone or Customer identity; subject, rating, price, location, messaging, payments, notifications, cancellation/reschedule, recurring Slots; new Tutor hours, weekdays, holidays, maximum horizon or start-minute grid; any mutable Slot.isBooked flag or Booking schema owned by #15.

Part E is documentation only. Part F must be a separate code-only branch/PR after this contract is peer-accepted.

#### 2. Dependencies and verified repository facts

Issue #13 Auth and Issue #14 Tutor Slots/Dashboard are closed. PR #31 is merged into sprint1. This branch is based on sprint1 SHA 551a9469e3d3a7e8e3ae004a382862c4f3e87e0e.

**Selected sequencing route — B: a separately scoped shared data foundation.** At this base, `apps/api/prisma/schema.prisma` contains User, Session, AuthAttemptBucket, AuthAttemptReservation and Slot, but no Booking model/table.

`apps/api/src/slots.ts` currently projects Tutor own-list occupancy as Unoccupied because #16 has not introduced Booking; that projection is not a Customer-availability occupancy source.

The team selected a separate Issue/PR for the shared Booking data foundation, with schema, migration, ownership and sequencing reviewed before either feature relies on it. The minimum persisted fields needed by this contract are `id`, `customerId`, `currentSlotId`, `startsAt`, `endsAt` and `status` (`Booked` / `Cancelled`); `currentSlotId` is the occupancy relation and the persisted Booking interval is the Customer-overlap source. Booking mutation remains owned by #16 and must not move into #15.

**Foundation tracking (not yet created):** proposed implementation owner @Chxtamos; peer reviewer @Tanaboonnnnn; dependency links #15 and #16; exact foundation Issue/PR URL and reviewed migration/schema SHA are **TBD** until that separate work is created and accepted. This PR does not create the Issue/PR or approve a migration. Until the shared foundation is reviewed, merged and its exact SHA recorded against the Part F branch, occupancy-dependent Part F work is a hard **STOP GATE**. Do not invent `Slot.isBooked`, assume all Slots are unoccupied, or create a partial Booking schema under #15.

### 3. Actors and journey

| Actor | Result |
|---|---|
| Anonymous | 401; no offer data |
| Authenticated Customer | 200 safe availability projection |
| Authenticated Tutor | 403; no Customer availability payload |
| Server | Derives Customer identity from live Session; derives eligibility from persisted Slot/Booking and database time |

1. Customer opens the availability screen.
2. UI verifies GET /api/v1/auth/me and requires trusted role Customer.
3. UI calls the Customer availability GET with the same-origin HttpOnly Session cookie.
4. Server enforces Session and Customer role, reads eligible offers and serializes only the approved allowlist.
5. UI displays an approved Tutor public display name only after the separate data-approval gate; otherwise it displays the opaque Tutor reference. It also displays Bangkok start/end. Selecting a Slot changes transient UI state only; it is not a Booking or reservation.
6. Later #16 receives only the selected Slot ID and independently rechecks offer state, occupancy, Q05 and all Booking rules in its authoritative transaction. A prior availability response is never a lock, lease or guarantee.

### 4. Eligibility and time

For one read, `T_view` is one database-authoritative instant sampled for the availability query. Under the confirmed Customer-specific bookable-only policy, include a Slot only when:

1. lifecycle is Offered;
2. no active Booking with status Booked references that Slot;
3. startsAt - T_view is at least 60 minutes (60:00 included; 59:59 excluded);
4. no Active Booking owned by the authenticated Customer overlaps this Slot, even when the existing Booking belongs to a different Tutor; and
5. the persisted Slot interval and Tutor ownership remain valid under the accepted Slot contract.

**Customer-specific overlap predicate (BR-S1-09/10, Q28):** derive the owner only from `principal.userId` supplied by the live Session. Exclude a candidate Slot when an existing Booking has `customerId = principal.userId`, `status = Booked`, and its persisted interval overlaps the candidate using half-open intervals: `booking.startsAt < slot.endsAt AND slot.startsAt < booking.endsAt`. A Cancelled Booking does not conflict; exact adjacency is allowed. This is an eligibility predicate only: the query may test existence but must not return or disclose any matching Booking or Customer data. The same Customer's overlapping Booking on another Tutor must make the candidate unavailable to that Customer; another Customer's Booking must not affect this Customer's overlap predicate.

T_view is an indicative read timestamp, **not** #16's transactional T_elig. Booking T_elig must be sampled by the authoritative Booking transaction after relevant contention waits, immediately before the guarded write. The availability UI must never imply a

displayed Slot is reserved or guaranteed to remain bookable.

PostgreSQL stores TIMESTAMPTZ; API returns RFC 3339 UTC instants ending Z; UI formats explicitly with Asia/Bangkok regardless of device timezone. Never use browser time or a client timestamp for eligibility. OD-002 (maximum advance horizon) remains OPEN: this contract does not choose an upper bound and does not claim an approved unlimited horizon. Resolve OD-002 before Part F; do not silently add a horizon, hours, weekday, holiday or minute-grid policy.

A Slot can become occupied or cross Q05 after T_view. If #16 later rejects a stale selection, UI shows non-success and refreshes; #15 does not create a fake Booking endpoint.

### 5. Peer-review decision record

The following states record the decisions in PR #32 comment #6683929084. “Confirmed” means the team engineering/design choice recorded by peer review; it does not claim a new stakeholder business rule or implementation/test completion.

| ID | Decision / contract | Status |
|---|---|---|
| OD-AV-01 Display | Customer-specific bookable-only: return/display only Slots that pass current Slot offer, occupancy, Q05 and the authenticated Customer's BR-S1-09/10 overlap rules at `T_view`. | **CONFIRMED design choice**; not a Booking guarantee. |
| OD-AV-02 Tutor identity | Desired UI identity is an approved Tutor public display name. Do not read/add/publish a name until its source, owner/consent, field, migration and allowlist are approved. Until then use opaque `tutorRef`. | **CONDITIONAL DATA-APPROVAL GATE**. |
| OD-AV-03 List | No filters or pagination in Sprint 1; stable order `startsAt ASC → tutorRef ASC → slotId ASC`. | **CONFIRMED technical constraint**; not an unlimited-horizon decision. |
| OD-AV-04 Clock | One PostgreSQL `T_view` per read; `meta.evaluatedAt` is present for both populated and empty success responses. | **CONFIRMED**; not a substitute for #16 `T_elig`. |
| OD-AV-05 Occupancy | Exclude a Slot through active `Booking.status = Booked` and `Booking.currentSlotId = Slot.id`; never store duplicate `Slot.isBooked`. Customer overlap is a separate owner-derived interval predicate. | **CONFIRMED invariant**; schema-dependent Part F STOP GATE. |
| OD-AV-06 Error/privacy | Reuse existing API/session security, Customer role, session binding, request ID/error envelope, `Cache-Control: no-store`, and distinguish error from empty. | **CONFIRMED**. |
| OD-AV-07 Performance | Record p95 under a reproducible Part F workload; ≤2.0s remains a proposed reference only. | **NON-BLOCKING MEASUREMENT**; no pass/fail threshold approved. |
| OD-AV-08 Visual | Customer UI remains light/readable but shares NutTiew brand, typography, related colors/accents, spacing, components, focus and navigation patterns with Tutor Dashboard. Role-specific layouts are allowed within one design system. | **CONFIRMED design direction**. |
| OD-002 Horizon | No maximum advance horizon, working hours, weekday, holiday or minute-grid rule is selected. | **OPEN**; resolve before Part F. |
| #15 ↔ #16 data foundation | Use a separately scoped shared Booking data-foundation Issue/PR (route B); record owner, reviewer, dependency links and exact accepted schema SHA. | **SELECTED; NOT CREATED**. Part F STOP GATE remains. |
| NFR-S1-09 accessibility | Plan keyboard, focus, announcements and responsive checks; collect actual evidence in Part F. | **TEST PLAN ACCEPTED**; no WCAG 2.2 AA or 44px conformance claim. |

#### Conditional Tutor public-display-name gate

- **Proposed source:** an explicit public display name supplied/maintained by the Tutor; never derive it from `User.email`, login credentials or a guessed profile field.
- **Proposed field/type:** nullable `User.tutorDisplayName` (`String?` / PostgreSQL `TEXT`), used only for Tutor accounts. This is a candidate contract, not an approved schema change.
- **Data owner and permission:** the Tutor is the source/data owner and must explicitly opt in to customer-facing display. The product/stakeholder owner must record approval for publication; @Chxtamos owns this feature contract and @Tanaboonnnnn

is the peer reviewer. Record the actual approving stakeholder and consent rule before migration.

- **Migration/seed:** only a separate reviewed forward-only migration after the data gate is accepted; no default, no backfill from email, and existing Tutors remain `NULL`. Seed only clearly test-only synthetic values in isolated test fixtures; never present fixture names as real Tutor identity.
- **API/UI allowlist:** until the gate is cleared, omit `tutorDisplayName` and show `tutorRef`. After approval, add only the approved nullable field to the response allowlist and render it only when present; never add email, phone or other profile fields.
- **Privacy evidence:** planned AVA-18 verifies no name is inferred from email, no unapproved field is returned, and—only after approval—the approved display field is the sole additional Tutor identity field. AVA-05 continues to inspect the full response allowlist.

### 6. Acceptance and traceability

| Source | F-S1-03 outcome | Planned STS |
|---|---|---|
| FR-S1-08 / AC-S1-15 | Customer identifies a specific Tutor using approved display name after its gate, otherwise opaque reference, plus Slot start/end | AVA-01, AVA-05, AVA-18 |
| FR-S1-09 / AC-S1-16 | Anything shown as bookable is current, unoccupied, outside Q05 cutoff and non-overlapping for this Customer | AVA-02, AVA-03, AVA-15, AVA-16, AVA-17 |
| AC-S1-17 | Stale offer is revalidated by #16; no false Booking success | AVA-11 |
| AC-S1-18 / BR-S1-12 | Bangkok time meaning is independent of device locale | AVA-04 |
| BR-S1-06/07/08/09/10/11/15/17/20/21 | Distinct Tutor offers, Slot occupancy, Q05/future-time eligibility, Customer-specific non-overlap and adjacency, role and privacy | AVA-02/03/05/06/07/15/16/17 |
| FR-S1-18 | Failed/unauthorized reads communicate non-success without private disclosure or false availability | AVA-05/06/10 |
| NFR-S1-01/08 | Deny anonymous/wrong role; no secret or private Booking leakage | AVA-05/06/12 |
| NFR-S1-07/12 | Reproducible evidence, stable IDs and reviewed PR | Part F ledger/PR |
| NFR-S1-09 | Keyboard, focus, announcements and responsive behavior are planned for manual/browser verification | AVA-13 |
| NFR-S1-10 | Record p95 and workload evidence; ≤2.0s is non-blocking and not an approved threshold | AVA-14 |
| OD-AV-08 | Customer and Tutor screens share NutTiew brand, typography, spacing, colors/accents, components, focus and navigation patterns with role-specific layouts | AVA-19 |

Whole-product trace anchors: FR-008/009, NFR-007/009/010, VAL-006/009/033/036, VC-S1-13/TEST-S1-13, VC-S1-15/TEST-S1-15, VC-S1-22/TEST-S1-22 and VC-S1-36/TEST-S1-36. These are planned links, not test results.

### 7. Definition of Done

**Part E**

- [ ] Five cross-linked documents exist: Feature SDS, UI spec, API spec, data spec and STS.
- [ ] FR-S1-08/09 and AC-S1-15..18 map to explicit rules, response fields, UI states and tests.
- [ ] PR #32 peer decisions are recorded with explicit CONFIRMED / CONDITIONAL / OPEN / STOP GATE states; no engineering choice is mislabeled as stakeholder business approval.
- [ ] Customer-specific bookable-only predicate includes same-Customer cross-Tutor overlap and half-open adjacency; owner comes only from the live Session.
- [ ] Empty success response always contains DB `meta.evaluatedAt` and `Cache-Control: no-store`; query returns one metadata row even when there are no offers.
- [ ] Tutor public display name remains behind its source/consent/schema/migration/allowlist gate; no email-derived or invented production name is exposed.

- [ ] Response allowlist excludes Customer identity/Booking data, credentials, Session fields and unrestricted Tutor fields.
- [ ] Shared data-foundation route B is recorded with proposed owner/reviewer/dependencies; exact Issue/PR and schema SHA remain pending, so Part F is blocked until accepted. No fake occupancy flag is added.
- [ ] Markdown links/structure and git diff --check pass.
- [ ] PR contains only the five F-S1-03 Markdown files, targets sprint1, links #15 and requests @Tanaboonnnnn.
- [ ] PR stays open for independent human review; no self-approval or self-merge.

**Part F — separate implementation PR**

- [ ] Start from updated sprint1 after Part E acceptance and the separately reviewed/merged shared Booking data foundation; record its exact schema SHA.
- [ ] Implement Customer-only UI → Express API → PostgreSQL read projection from real Slot and Booking rows.
- [ ] Verify occupied exclusion, Customer-specific cross-Tutor overlap and adjacency, Q05 boundary, approved Tutor-name allowlist gate, Bangkok rendering, auth/role denial, empty/error/retry and session-change privacy.
- [ ] Run keyboard/focus/announcement/responsive checks and record evidence; do not claim WCAG 2.2 AA or a 44px target pass without the corresponding assessment.
- [ ] Record real commands/results, DB/migration, source SHA and hosted CI.
- [ ] Open separate code-only PR into sprint1 and obtain peer review.

**Verification boundary:** this Part E change is documentation only. No build, API test, migration, Booking query, browser E2E, performance benchmark or accessibility audit is claimed as run or passed.

### 8. UX follow-up amendment gate (Issue #44)

**Issue #44 Part E — docs-only UX amendment**

- [ ] Updated Option A specs cross-linked consistently across UX decision 2026-11-10, UI spec, STS, this SDS, and F-S1-04 UI cross-reference.
- [ ] Resolved Part E design choices explicitly recorded: 6 default time groups + `ดูเวลาเพิ่มเติม`, no morning/afternoon/evening filter chips, and non-sticky inline `#selected-offer-summary` placed directly after the day's time list.
- [ ] Phase 1 boundary preserved: `GET /api/v1/customer/availability` uses zero query parameters ( `400 INVALID_INPUT` on unknown query), unchanged DTO/privacy allowlist, unchanged `F-S1-04` CSRF/Session Binding/ `T_elig` /SERIALIZABLE locking, and unchanged `F-S1-05` `การจองของฉัน` tab.
- [ ] `OD-002` ( `60 days` at DB `T_view` vs initial `PR #32` / `docs/srs.md` `OPEN` status) reconciled with provenance instead of silent overwrite.
- [ ] `UX-CAL-01..10` planned without renumbering `AC-S1-01..35` or `AVA-01..19` ; no `apps/` , `e2e/` , or schema files touched.
- [ ] Docs-only PR targets `sprint1` , links `#44` (and references `#15` / `#16` ), requests @Tanaboonnnnn peer review, and waits open for approval before any Part F code begins.

**Issue #44 Part F — separate implementation PR**

- [ ] Branch fresh from merged `sprint1` only after Part E acceptance and implement client-side Option A monthly calendar & CSS responsive layout in `apps/web/src/customer-availability.tsx` / `.css` .
- [ ] Execute `UX-CAL-01..10` plus full `AVA-*` , `BOOK-*` , and `RET-*` regressions against real PostgreSQL and Microsoft Edge ( `320/375/768/1280` CSS px screenshots, `500+` seeded offers, cross-year & leap-year checks, `UTC` / `America/Los_Angeles` tz checks, failed-GET/malformed-DTO/logout/unknown-outcome checks) on exact CI HEAD.
- [ ] Distinguish automated checks cleanly from manual human WCAG 2.2 AA audit (**NOT RUN** unless performed by human reviewer).

---

### E.4.2 F-S1-03 Customer Availability UI Specification (ui-spec.md)

> **2026-11-10 UX-only Option A amendment (Issue #44, pending peer review):** Replace only the simultaneous full-list layout ( `dateGroups.map(...)` ) with **Option A — Date-First Monthly Calendar (Progressive Disclosure)** as directed in Issue #15 comment #6763909620 and detailed in UX decision 2026-11-10. The historical Part E baseline below (PR #32 / Part F PR #37) remains preserved for traceability; only its simultaneous chronological full-list page layout is proposed to be superseded. The read-only API contract (API), PostgreSQL eligibility/T_view ( `OD-002 = 60 days` ), `OD-AV-01..08` , `F-S1-04` confirmation/security (F-S1-04 UI), and `F-S1-05` `การจองของฉัน` tab (F-S1-05 UI) remain **unchanged**.

> **Review sequencing (Two-PR Gate):** This is a **docs-only Part E amendment** under Issue #44 (separate from Deliverable 1 #18 / PR #43). Obtain independent review from @Tanaboonnnnn and merge into `sprint1` **before** opening the Part F code-only PR.

#### Amendment: Option A Date-First Monthly Calendar (Issue #44)

##### A.1 Screen anatomy and progressive disclosure flow

1. **Preserved NutTiew Customer Shell:** Keep the single Navy `#202B44` sidebar ( `เลือกช่วงเวลาติว` , `การจองของฉัน` , `บัญชีของฉัน` , `ออกจากระบบ` ), top status/breadcrumb bar, `#account-details` , and session/logout guard transitions identically across desktop and collapsed mobile navigation.
2. **Hero Header:**
   - `h1#availability-heading` : เลือกช่วงเวลาติว
   - Helper instruction: เลือกวันที่สะดวก แล้วเลือกช่วงเวลา alongside explicit **Asia/Bangkok (UTC+07:00)** notice
   - Optional `ตรวจสอบล่าสุด` from response `meta.evaluatedAt` formatted explicitly in `Asia/Bangkok`
   - Primary refresh control: `โหลดข้อมูลล่าสุด`
3. **Balanced Calendar + Day Time Workspace ( `#availability-section` when `offers.length > 0` after authenticated `200` ):**
   - **Step 1 — Monthly Calendar (~40% left column on desktop `>= 768px` , first block on `< 768px` ):**
     - Month/Year heading ( `th-TH-u-ca-gregory-nu-latn` in `Asia/Bangkok` , e.g., `พฤศจิกายน 2026` , `มกราคม 2027` ) + Prev ( `เดือนก่อนหน้า` ) and Next ( `เดือนถัดไป` ) `<button type="button">` controls supporting cross-month/year rollovers ( `Nov -> Dec -> Jan` ) and leap Februaries ( `28` / `29` days).
     - Derived month bounds span from earliest eligible offer month (or `evaluatedAt` month) through `max(latestOfferMonth, month(evaluatedAt + 60 days))` without browser-clock eligibility filtering or hardcoded month limits.
     - 7-column Mon–Sun weekday grid ( `จ` , `อ` , `พ` , `พฤ` , `ศ` , `ส` , `อา` ). Out-of-month filler slots render as inert non-focusable spacers ( `aria-hidden="true"` ).
     - Each in-month day renders as a native `<button type="button">` displaying the day numeral and **eligible Slot offer count** ( `N ช่วงเวลา` — total offers returned for that Bangkok day, **not** unique Tutor count). Zero-offer days show non-color empty markings ( `–` / subtle dashed neutral styling, accessible label e.g. `"13 พ.ย. 2026 ไม่มีช่วงเวลาว่าง"` ) and `disabled` state by design ( `กดวันไม่ได้ตามดีไซน์` ). Eligible days show accessible label matching `bangkokLongDate` , e.g. `"12 พ.ย. 2026 มี 8 ช่วงเวลา"` and `aria-pressed={isSelected}` plus non-color active badge/border cues.
   - **Step 2 — Selected Day Time Groups (~60% right column on desktop `>= 768px` , second block on `< 768px` ):**
     - Heading displays the selected Bangkok date + offer count for that day (e.g., `12 พ.ย. 2026 · 8 ช่วงเวลา` ).
     - Group offers matching `bangkokDayKey(new Date(offer.startsAt)) === selectedDayKey` by **exact** `(startsAt, endsAt)` **UTC instant pair** using memoized indexing from validated offers only, preserving deterministic server order ( `startsAt ASC, tutorRef ASC, slotId ASC` ). Never snap arbitrary minutes (e.g., `10:15` , `23:30` ) to hourly buckets and never merge distinct `slotId` s.
     - **Omit quick period filter chips** (no morning/afternoon/evening chips in Phase 1).
     - Render time groups **collapsed by default** and display the **first 6 time groups** for the selected day initially; when `groups.length > 6` , render a native `<button type="button">` **`ดูเวลาเพิ่มเติม`** to reveal all remaining groups for that

date without API filtering or truncating offers.

- Each time-group toggle button ( `aria-expanded={isExpanded}` ) displays Bangkok `HH:mm–HH:mm น.` , explicit `สิ้นสุดในวันถัดไป` badge when `bangkokDayKey(startsAt) !== bangkokDayKey(endsAt)` , and option count ( `N ตัวเลือก` ).
- Expanding a group reveals `<ul>` offer items ( `[data-testid="availability-offer"]` , `data-offer-slot-id` , `data-tutor-ref` ) in exact server `tutorRef ASC, slotId ASC` order, displaying opaque `tutorRef` (or approved `tutorDisplayName` only after `OD-AV-02` ), Bangkok date/duration, and `เลือกช่วงเวลานี้` / `เลือกช่วงเวลานี้แล้ว` ( `aria-pressed` ).

4. **Step 3 — Non-Sticky Inline Selection & Confirmation Summary ( `#selected-offer-summary` ):**
   - Placed directly **below the selected day's time list** inside the right column on desktop ( `>= 768px` ) and directly **below the day's time list** in the mobile vertical stack ( `320/375px` ). Never `position: fixed` or `position: sticky` over interactive controls or focus outlines ( `WCAG 2.2 SC 2.4.11` ).
   - Remains mounted whenever `activeOffer && !loading && !listError` , preserving active transient selection and any unresolved `UnknownBookingOutcome` even when switching calendar days/months or when `refresh()` returns `data: []` .
   - Displays Bangkok date/time, cross-midnight badge when applicable, opaque `tutorRef` , explicit disclaimer **"**การเลือกช่วงเวลานี้ยังไม่ใช่การจอง และยังไม่ได้ล็อกสิทธิ์จนกว่าจะยืนยันการจองในขั้นตอนถัดไป**"**, `ยืนยันการจอง` / `ส่งคำขอเดิมอีกครั้ง` , `ยกเลิกการเลือก` , and CSRF retry if needed — using the unchanged `F-S1-04` confirmation flow.

### A.2 Calendar state machine extensions (additive to §3 baseline)

| State | Trigger | Required Option A behavior |
|---|---|---|
| Confirmed populated landing | First valid `200` with `data.length > 0` and valid `X-NutTiew-Session-Binding` | Build memoized day map; open earliest eligible offer month ( `data[0]` ); auto-select earliest eligible `selectedDayKey` ; keep time groups collapsed initially; preserve `selectedSlotId` / `unknownOutcome` rules |
| Confirmed global empty | Valid `200` with `data: []` | Render `ยังไม่มีช่วงเวลาติวที่พร้อมให้เลือก` without empty calendar availability; keep `unknownOutcome` summary rendered if unresolved |
| Selected day/month empty | Valid `200` with `data.length > 0` , while viewed month or retained `selectedDayKey` (e.g., post-booking/refresh) has 0 offers | Render day/month empty panel inside Step 2 explaining no offers exist for that date/month; never label whole system globally empty |
| Read error / malformed DTO | Network, timeout, `500` , `503` , invalid `startsAt` / `endsAt` / `evaluatedAt` , or malformed DTO item | Hide calendar grid, counts, and derived state ( `offers = []` ); render `#availability-error` + `โหลดอีกครั้ง` ; never show `0` counts as confirmed empty |
| Month / day navigation | User clicks `เดือนก่อนหน้า` , `เดือนถัดไป` , eligible date button, `ดูเวลาเพิ่มเติม` , or time-group toggle | Update local UI view state only; zero `GET` query params, zero `POST` triggers; preserve existing `selectedSlotId` , `selectedOfferSnapshot` , and `unknownOutcome` lock |
| UnknownBookingOutcome lock | Unresolved Booking POST ( `503 BOOKING_OUTCOME_UNKNOWN` / network abort/timeout) | Keep `#selected-offer-summary` + `ส่งคำขอเดิมอีกครั้ง` ; block ( `disabled` ) switching selection to any different `slotId` across all days/time groups until reconciled |
| Session change / logout | Logout click, `logoutError` , `401` / `403` , binding mismatch, `nuttiew-auth-changed` event | Immediately abort in-flight requests, clear offers, calendar selection, day map, and CSRF state; ignore delayed responses from prior Session |

### A.3 Responsive breakpoints, hit targets, and accessibility targets

| Viewport | Layout | Calendar/target geometry |
|---|---|---|
| `320 CSS px` | Single vertical stack ( `Calendar` -> `Day Time Groups` -> inline `#selected-offer-summary` ); zero horizontal overflow | All non-grid buttons (month step, time groups, `ดูเวลาเพิ่มเติม` , offer select, confirm) target `>= 44×44 CSS px` ; day buttons keep height `>= 44 CSS px` and width `>= 36 CSS px` (exceeding WCAG 2.2 AA SC 2.5.8 `24×24px` minimum) so 7 columns never overflow or clip at `320px` |

| Viewport | Layout | Calendar/target geometry |
|---|---|---|
| `375 CSS px` | Single vertical stack; compact mobile gutters; zero horizontal overflow | Every interactive button including all 7-column day cells achieves `>= 44×44 CSS px` |
| `>= 768px` (incl. `768px` & `1280px`) | Balanced two-column content area (~40% Calendar, ~60% Day Time Groups + inline `#selected-offer-summary`); no second sidebar | Use `minmax(344px, 40%) minmax(0, 60%)` when main area has two-pane width (collapsed sidebar at `768px`, full width at `1280px`) so all day buttons remain `>= 44×44 CSS px` with zero overflow |

- **Live announcements & keyboard navigation:** Announce selected date transitions concisely in `aria-live="polite"` (e.g., `"เลือกวันที่ 12 พ.ย. 2026 พบ 8 ช่วงเวลา"`), never reading 500 offer rows. Preserve logical DOM/Tab order across month controls -> eligible days -> time-group accordions -> `ดูเวลาเพิ่มเติม` -> expanded offer buttons -> inline `#selected-offer-summary`.
- **Contrast, reduced motion, zoom:** Maintain `#172137` dark ink on `#F47736` CTA (`5.76:1`), `#D96123` border (`>= 3:1`), `#66778A` interactive borders (`4.59:1` on white), `#455A76` muted ink (`>= 4.5:1`), `3px solid #AA4519` focus outline (`offset: 3px`), `@media (prefers-reduced-motion: reduce)`, and `200%` zoom usability without obscured focus.
- **Timezone invariance:** Compute Bangkok month titles, day keys (`YYYY-MM-DD`), weekday headers, cross-midnight checks, and `HH:mm` labels exclusively in `Asia/Bangkok`, independent of `UTC` or `America/Los_Angeles` browser settings.
- **Phase 1 boundary & Phase 2 deferment:** `GET /api/v1/customer/availability` remains unfiltered in Phase 1. Any future query/pagination addition requires profiling justification plus a separate Part E API amendment. All `UX-CAL-01..10` checks in STS §2 and manual human WCAG 2.2 AA sign-off are **PLANNED / NOT RUN**.

---

### Baseline specification (historical Part E PR #32)

> **Historical note (`OD-002` reconciliation):** Content below preserves the original Part E baseline (`PR #32`). Its `OD-002` `OPEN` statement in §2 below was superseded on 2026-11-06 / 2026-11-08 by confirmed `60 days` evaluated against database `T_view` in Issue #15 and Part F PR #37; see UX decision 2026-11-10 §1.

> **Part E UI contract only; no UI implementation/browser test.** Customer-specific bookable-only and the shared NutTiew design direction are recorded as peer decisions in Feature SDS. Tutor display name remains conditional on its separate data-approval gate. See API, Data, STS.

### 1. Screen and visual direction

Screen: ช่วงเวลาติวที่พร้อมให้เลือก — authenticated Customer availability discovery.

This is a focused scheduling utility, not a marketing page or a visually separate application. Customer Availability and the Tutor Calendar Dashboard share one NutTiew design system while allowing role-specific layouts.

| Shared product token | Customer Availability application |
|---|---|
| Brand / navigation | Text-only NutTiew wordmark; shared navy `#202B44` for brand/navigation and the same active-navigation, account and logout patterns as Tutor Dashboard |
| Canvas / surface | Light canvas `#F7F8FB`, white surface `#FFFFFF`; no nested cards |
| Text | Dark ink `#172137`; muted text must remain contrast-safe on the shared light surfaces |
| Primary action | Orange `#F47736` with dark-ink label/icon `#172137` and border `#D96123`; do not use white text on orange |
| Focus | Shared visible focus ring `3px solid #AA4519` with `outline-offset: 3px`; verify it remains unobscured in every state |
| Typography | Noto Sans Thai, Sarabun, system-ui, sans-serif; use the same type hierarchy as Tutor Dashboard |
| Spacing / corners | Shared 4/8/12/16/24/32px spacing scale and 8px radius; align component padding and row rhythm with Tutor Dashboard |

Use the same reusable button, status, focus and navigation patterns as Tutor Dashboard. Desktop navigation follows the same NutTiew shell; only Customer-authorized destinations are shown (availability, account and logout), never Tutor-only or unimplemented menus. At mobile widths use the same accessible collapsed-navigation behavior. Keep the Customer content light and readable; do not create a second brand palette with an unrelated accent.

No gradients, glassmorphism, hero banners, fake Tutor profiles, testimonials, ratings, prices, message panels, decorative emoji or card-in-card layouts. The orange CTA pairing and focus values are design tokens from the Tutor UI contract, not proof of WCAG conformance; Part F must verify actual rendered states and contrast.

### 2. Screen anatomy

1. Small text-only NutTiew wordmark.
2. Heading: เลือกช่วงเวลาติว.
3. Helper: appointment times are displayed in Asia/Bangkok.
4. Optional ตรวจสอบล่าสุด timestamp from response meta.evaluatedAt.
5. Chronological offers grouped by Bangkok calendar date.
6. Each offer shows an approved Tutor public display name when the OD-AV-02 data gate is cleared; otherwise it shows the stable opaque Tutor reference. Also show Bangkok date, 24-hour start/end and a เลือกช่วงเวลานี้ action.
7. Selected-offer summary uses the same approved name/fallback reference and time, and must state that selection **is not a Booking**.

Selecting an offer stores slotId in transient UI state only. It does not POST, reserve, occupy or confirm a Booking. The later #16 flow owns confirmation and must revalidate the selected Slot on the server.

**Display policy OD-AV-01**

**Confirmed: Customer-specific bookable-only.** Show only offers the API evaluated as bookable for the authenticated Customer at `meta.evaluatedAt`: current Offered Slot, not occupied by an Active `Booked` row, at least 60 minutes before start, and not overlapping that Customer's own Active Booking even if the existing Booking belongs to another Tutor. Exact adjacency is allowed. Do not render unavailable offers or disclose why another Slot was excluded.

The maximum advance horizon remains open under SRS OD-002. The UI must not invent a date cap or imply that an unlimited horizon has been approved; update the visible range only after the team records that decision.

### 3. UI states

| State | Trigger | Required behavior |
|---|---|---|
| Session loading | /auth/me pending | Hide offers; show progress |
| Signed out | /auth/me returns 401 | Clear offers/selection; show Auth |
| Wrong role | Principal is not Customer | Access denied; do not call/render Customer availability |
| Initial loading | Customer verified; availability GET pending | Show progress, not empty/zero |
| Populated | 200 with offers | Render authorized offers in server order |
| Confirmed empty | 200 with data: [] | Show ยังไม่มีช่วงเวลาติวที่พร้อมให้เลือก |
| Read error | Network/timeout/500/503 | Show error and โหลดอีกครั้ง; never show empty/zero |
| Selection | Customer selects an offer | Mark selected; state no Booking was created |
| Stale selection | Later #16 rejects it | Show non-success, clear/mark stale selection, refresh; never show Booked |
| Session changed | Logout/account switch/binding mismatch | Immediately clear offers/selection and ignore late old-session responses |

Only a successful authorized 200 with data: [] may render confirmed-empty. A failed request or malformed payload is not an empty result.

### 4. Interaction and accessibility

- Semantic headings, native buttons, visible labels and logical Tab/Enter order.

- Every offer is keyboard selectable; selected state is communicated with text/semantics, not color alone.
- Visible :focus-visible; focus must not be obscured. Move focus to an error summary for blocking failures where appropriate.
- Announce loading, result count, empty and error transitions without repeatedly announcing the entire list.
- Primary controls target at least 44×44 CSS px as a design target only; this is not a verified pass. Part F records actual target-size, contrast, focus, zoom and 320 CSS px reflow evidence.
- NFR-S1-09 test planning is accepted, but this specification does not claim WCAG 2.2 AA conformance. Do not report WCAG AA or 44px as passed without the corresponding manual/browser evidence.

#### 5. Responsive behavior

| Viewport | Proposed layout |
|---|---|
| 320/375 CSS px | Single-column list, 16px side gutters, no horizontal overflow |
| 768 CSS px | Readable constrained list; no unnecessary calendar grid |
| 1280 CSS px | Centered readable column; rows may place metadata/action in two columns |

Preserve the same chronological offer set and field visibility at every viewport. Do not crop offers or hide Tutor/time on mobile.

#### 6. Privacy and content rules

Show only the approved Tutor public display name when the OD-AV-02 gate is cleared; otherwise show the opaque Tutor reference, plus Slot date/time. The server-side overlap check may use the authenticated Customer ID but must not reveal whether a matching Active Booking exists, which Tutor owns it, or any Booking/Customer details. Never derive a name from email or invent a name. Do not show/fetch Customer identity, emails/phones, Booking IDs/reasons, Tutor email, credentials/session fields or full private Tutor schedule. No unapproved profile fields, subjects, ratings, prices, locations, images or unrelated availability. No Booking confirmed/Booked/Reserved state in #15.

#### 7. Acceptance mapping

| Criterion | UI requirement |
|---|---|
| AC-S1-15 | Selectable approved Tutor display name after its data gate, otherwise opaque Tutor reference, and Bangkok start/end |
| AC-S1-16 | Occupied/inside-cutoff offers and offers overlapping this Customer's Active Booking are excluded from the bookable-only list |
| AC-S1-17 | Selection is not reservation; #16 revalidates and UI shows non-success |
| AC-S1-18 | Asia/Bangkok rendering independent of device timezone |

Part F must capture real DB-backed browser evidence at 320/375/768/1280 CSS px and test keyboard selection, loading/empty/error/retry, 401/403, session switch, timezone and stale #16 response. None has been run in Part E.

---

### E.4.2a F-S1-03 Monthly Calendar UX Decision (ui-decision-2026-11-10.md)

**Follow-up Issue:** #44 (linked to #15 Customer Availability and #16 Exclusive Booking).

**Product direction owner:** @Tanaboonnnnn (Issue #15 comment #6763909620).

**Feature-contract author:** @Chxtamos; **Independent peer reviewer:** @Tanaboonnnnn.

**Verified `sprint1` base:** `744958117c5ee9a3f4875578485f00f65a7cdc22` (following merged Deliverable 1 PR #43, F-S1-05 PR #42, F-S1-04 PR #38, and F-S1-03 PR #37).

> **Two-PR Gate & Release Separation:** This document records a **docs-only Part E UX amendment** for peer review before any Part F React/CSS/E2E code change begins. It is **not** a blocking defect or change request against Deliverable 1 PR #43 or Issue #18. Obtain @Tanaboonnnnn's review approval and merge this docs-only amendment to `sprint1` first; only then branch the separate Part F implementation PR from the updated `sprint1`.

### 1. Superseded presentation and retained domain contracts

#### Replaced presentation

In the baseline `F-S1-03` implementation ( `apps/web/src/customer-availability.tsx` ), `groupOffersByBangkokDate(offers)` renders every eligible Bangkok date group and every offer row ( `dateGroups.map(...group.items.map(...))` ) simultaneously in one long vertical list. When 500+ offers are returned across up to 60 days, Customers must scroll across many screens and scan repeated same-time offers across multiple Tutors.

This amendment replaces **only the Availability browsing layout** inside the Customer portal ( `เลือกช่วงเวลาติว` ) with **Option A — Date-First Monthly Calendar (Progressive Disclosure)**:

1. Choose a date on the monthly calendar ( `1. เลือกวันที่` ).
2. View distinct chronological time slots for that selected date ( `2. เลือกเวลา` ).
3. Expand a time group to see distinct `tutorRef` + `slotId` options and pick one offer ( `เลือกช่วงเวลานี้` ).
4. Review the inline selected-offer summary ( `3. ตรวจสรุปและยืนยันการจอง` ) and explicitly submit via the unchanged `F-S1-04` booking confirmation flow.

#### Strictly unchanged contracts and boundaries

- **Customer portal shell & navigation:** Retain the NutTiew sidebar ( `เลือกช่วงเวลาติว` , `การจองของฉัน` from `F-S1-05` #17, `บัญชีของฉัน` , `ออกจากระบบ` ), account banner, guarded logout transitions ( `logoutBusy` / `logoutError` suspension + `recheckSession` ), `X-NutTiew-Session-Binding` checks, and `nuttiew-auth-changed` cross-tab synchronization.
- **Phase 1 read-only HTTP & DTO contract (API spec):** Continue calling `GET /api/v1/customer/availability` with **zero query parameters**. Client controls must never append `?from=` , `?to=` , `?page=` , `?cursor=` , or `?limit=` (which the backend rightly rejects with `400 INVALID_INPUT` under `BR-S1-20` and `OD-AV-03` ). Consume only the validated allowlist `{ slotId, tutorRef, startsAt, endsAt }` and `meta.evaluatedAt` with `Cache-Control: no-store` .
- **Server-authoritative eligibility & concurrency ( `OD-AV-01` , `F-S1-04` ):** Retain `Slot.lifecycle = 'Offered'` , active Tutor check, PostgreSQL `T_view` lower bound ( `+60 minutes` , `Q05` ), `NOT EXISTS` active Slot occupancy, half-open `[startsAt, endsAt)` same-Customer cross-Tutor overlap check, and deterministic server sort ( `startsAt ASC, tutorRef ASC, slotId ASC` ). Confirmation continues through `GET /api/v1/auth/csrf` -> second `GET /api/v1/auth/me` binding check -> `POST /api/v1/customer/bookings` ( `{"slotId"}` only) -> `SERIALIZABLE` + `booking_guard_s1()` at authoritative DB `T_elig` , handling `201 Created` , `200 OK` natural-key replay, `409 SLOT_UNAVAILABLE` / `CUSTOMER_OVERLAP` , `422 BOOKING_NOT_ELIGIBLE` , and `503` / `UnknownBookingOutcome` retry lock without change.
- **Tutor privacy ( `OD-AV-02` ):** Retain `tutorRef` UUID fallback until `OD-AV-02` ( `User.tutorDisplayName` consent, stakeholder publication sign-off, forward-only migration) clears in a separate change. Never derive names from email, fetch Customer/Booking private details, or fabricate ratings, subjects, prices, locations, avatars, testimonials, or booking statuses.

#### `OD-002` horizon provenance reconciliation

Per repository verification rules, conflicting documentation states are recorded explicitly rather than silently overwritten:

- docs/srs.md ( `OD-002` ) and the historical initial `F-S1-03` Part E baseline (PR #32) recorded `OD-002` (maximum advance booking horizon) as `OPEN` .
- Subsequently, on 2026-11-06 and 2026-11-08 in Issue #15 comments #6685976712 / #6721920473 and the merged `F-S1-03` Part F implementation (PR #37, `apps/api/src/availability.ts` ), the team confirmed and implemented **`OD-002 = 60 days`** for Customer Availability ( `Slot.startsAt <= view_clock.evaluated_at + INTERVAL '60 days'` , verified by `AVA-03` against PostgreSQL `T_view` ). Meanwhile, Tutor Slot creation ( `F-S1-02` ) retains its accepted Sprint 1 Option A rule (future check without a 60-day cap).
- **UI obligation under Option A:** The calendar **never** enforces its own client-clock date cutoff and **never** hardcodes a fixed 2- or 3-month cap. All navigable months and eligible dates derive strictly from the authenticated `200` offers and server `meta.evaluatedAt` reference ( `evaluatedAt` through `max(latestOfferStart, evaluatedAt + 60 days)` ), cleanly supporting year boundaries ( `Nov -> Dec -> Jan` ) and leap years ( `28` / `29` Feb).

## 2. Option A interaction contract and settled Part E choices

### 2.1 Monthly calendar header & landing rules

- **Instruction & anchor metadata:** Render the existing `เลือกช่วงเวลาติว` hero heading, short subtitle `"เลือกวันที่สะดวก แล้วเลือกช่วงเวลา"` alongside the explicit `Asia/Bangkok (UTC+07:00)` note, server `ตรวจสอบล่าสุด` (`meta.evaluatedAt` in `Asia/Bangkok`), and `โหลดข้อมูลล่าสุด` button.
- **Confirmed initial landing after authenticated `200`:**
  - Before a valid response passes session-binding validation and strict DTO/UTC timestamp checks, the schedule state is **loading** (or **read error** on `500` / `503` /network/timeout/malformed DTO) — never a zero-offer calendar grid.
  - When confirmed `data: []`, render the existing global confirmed-empty surface (`ยังไม่มีช่วงเวลาติวที่พร้อมให้เลือก`), with no fabricated calendar availability.
  - When `data.length > 0`, derive a memoized index `Map<BangkokDayKey, CustomerAvailabilityOffer[]>` once per validated payload, open the calendar to the **Bangkok calendar month containing the earliest eligible offer (`data[0]`)**, and **preselect that earliest eligible day** (`selectedDayKey`) automatically if no day is currently selected in this component mount. (If the Customer refreshes after selecting or interacting with a day, keep their chosen `selectedDayKey` unless they reset tabs/remount, so if a booked Slot disappears cleanly, that day's updated state stays visible instead of jumping unexpectedly.)
- **7-column Mon–Sun calendar grid (`จ`, `อ`, `พ`, `พฤ`, `ศ`, `ส`, `อา`):**
  - Display Thai month name and Christian-era year formatted explicitly in `Asia/Bangkok` (`th-TH-u-ca-gregory-nu-latn`, consistent with existing `bangkokLongDate` across `F-S1-02..05`, e.g., `พฤศจิกายน 2026`, `มกราคม 2027`).
  - Provide Prev Month (`เดือนก่อนหน้า`) and Next Month (`เดือนถัดไป`) `<button type="button">` controls supporting arbitrary month transitions including cross-year rollovers (e.g., Dec -> Jan) and Feb 29 in leap years (e.g., `2028-02-29`), disabled cleanly at the derived min/max bounds (`earliestMonth` through `latestMonth` computed from `evaluatedAt` + offers).
  - Leading/trailing cells outside the displayed month render as non-interactive empty spacers (`aria-hidden="true"`).
  - Each in-month day cell is a native `<button type="button">` displaying the day number and its **eligible Slot offer count** (e.g., `8 ช่วงเวลา`) — **counting actual offers (`offersForDay.length`), never unique Tutor count**.
  - **Zero-offer days inside a month:** Marked visibly empty using non-color indicators (`–` / subtle dashed neutral styling + descriptive text/label `"ไม่มีช่วงเวลาว่าง"`) and `disabled` by design (`"กดวันไม่ได้ตามดีไซน์"`, e.g., `aria-label="13 พ.ย. 2026 ไม่มีช่วงเวลาว่าง"`), never relying on color alone.
  - **Active day cells (`count > 0`):** Selectable via click or `Enter` / `Space`; indicate selected date with explicit `aria-pressed={isSelected}`, non-color indicator (`"กำลังเลือก"` / border accent + check badge), and clear accessible label matching `bangkokLongDate` (`th-TH-u-ca-gregory-nu-latn`), e.g., `"12 พ.ย. 2026 มี 8 ช่วงเวลา"`.

### 2.2 Selected-day time grouping & settled Part E choices

All three UX scope questions raised in `@Tanaboonnnnn`'s brief (§7) are settled for this Part E specification as follows:

1. **Time-group definition & initial visibility limit (Settled Choice #1 = `6` groups + `"ดูเวลาเพิ่มเติม"`):**
   - Filter offers where `bangkokDayKey(new Date(offer.startsAt)) === selectedDayKey`, preserving exact server order (`startsAt ASC, tutorRef ASC, slotId ASC`).
   - Group offers by their exact **`(startsAt, endsAt)` UTC pair** (`groupKey = ${startsAt}|${endsAt}`). Never coerce times to whole hours, never merge different `slotId`s, and never invent a `1h` assumption beyond validated offer endpoints.
   - Each time-group row is a native toggle button (`aria-expanded={isExpanded}`) showing Bangkok wall-clock interval + count (e.g., `09:00–10:00 น. · 3 ตัวเลือก`), plus the explicit **`สิ้นสุดในวันถัดไป`** badge when `bangkokDayKey(startsAt) !== bangkokDayKey(endsAt)` (e.g., `23:30–00:30 น.`).
   - Collapse time groups by default and render at most **6 time groups** initially for the selected day; when more than 6 distinct time groups exist on that day, render a native `<button type="button">` **`ดูเวลาเพิ่มเติม`** (`"ดูเวลาเพิ่มเติม (อีก N ช่วงเวลา)"`) to reveal all remaining groups in chronological order without modifying the API request or discarding eligible offers. Even if all 500+ offers occur on one date, initial interactive DOM controls stay compact (~30 day cells + 6 time-group buttons).

- Expanding a time-group row reveals its individual `<li>` offer items ( `[data-testid="availability-offer"]` with `data-offer-slot-id` and `data-tutor-ref` ) in exact server `tutorRef ASC, slotId ASC` order, each displaying opaque `tutorRef` , Bangkok date/duration text, and `เลือกช่วงเวลานี้` / `เลือกช่วงเวลานี้แล้ว` ( `aria-pressed` ).

2. **Period quick-filter chips (Settled Choice #2 = Omit):**
   - Do **not** add morning/afternoon/evening quick-filter buttons in Phase 1. Omitting artificial time-of-day categories reduces interactive clutter and avoids implying business-hour semantics outside `F-S1-03` .
3. **Selected-offer summary & mobile placement (Settled Choice #3 = Non-sticky inline card after the day's time list):**
   - Render `#selected-offer-summary` inline directly **below the selected day's time-group list** inside the right (~60%) pane on desktop ( `>= 768px` ) and directly below the time-group list in the single vertical stack on mobile ( `320/375px` ).
   - Do **not** apply `position: fixed` or `position: sticky` to the summary/confirm bar on mobile, so focus indicators ( `WCAG 2.2 SC 2.4.11` ), calendar buttons, and expanded offer actions are never obscured.
   - Render `#selected-offer-summary` whenever `activeOffer && !loading && !listError` — including when the user switches calendar month/day OR when `unknownOutcome` persists even if `offers.length === 0` after refresh.
   - Selecting an offer sets transient UI state only and explicitly states: **"**การเลือกช่วงเวลานี้ยังไม่ใช่การจอง และยังไม่ได้ล็อกสิทธิ์จนกว่าจะยืนยันการจองในขั้นตอนถัดไป**"**, exposing `ยืนยันการจอง` (and `ยกเลิกการเลือก` , or `ส่งคำขอเดิมอีกครั้ง` when `unknownOutcome` is active).

### 2.3 Safe view transitions & empty/error distinction

- **No side-effect POST/GET on calendar navigation:** Changing month, clicking another day, expanding a time group, or clicking `"ดูเวลาเพิ่มเติม"` mutates local UI state only. It never dispatches `POST /api/v1/customer/bookings` , never clears or swaps `selectedSlotId` / `selectedOfferSnapshot` , and never clears `unknownOutcome` . While `unknownOutcome` is active for an unresolved `slotId` , selecting any other `slotId` remains locked ( `disabled` ) until retry/reconciliation settles.
- **Day-specific empty state:** Triggered when `offers.length > 0` overall, yet the currently inspected month (e.g., an empty intermediate month within the 60-day horizon) or currently retained `selectedDayKey` (e.g., its last Slot was booked or removed on refresh) has `0` eligible offers. Render an explicit day/month empty panel ( `ยังไม่มีช่วงเวลาว่างในวันที่เลือก` / `ยังไม่มีช่วงเวลาว่างในเดือนนี้` ) directing the user to choose another date or month with available counts.
- **Fail-closed error & session guards:** `401` / `403` , failed `X-NutTiew-Session-Binding` , logout initiation/uncertainty, network/500/503 failure, or invalid DTO timestamp/shape clears or hides calendar/time derived state and offers `โหลดอีกครั้ง` (or session recovery UI) without rendering empty `0` counts or merging stale old-session offers into a new session.

## 3. Responsive layout, tokens, Phase 2 gate, and accessibility target

- **Responsive geometry & `44×44 CSS px` target reconciliation:**
  - **Desktop & tablet ( `>= 768px` ):** Balanced two-column workspace ( `~40%` calendar, `~60%` selected-day time options + inline `#selected-offer-summary` ). Note: on desktop with the 245px sidebar open, maintain adequate width before breaking to two columns (or adjust `.customer-sidebar` collapse / grid breakpoint `>= 768px` when sidebar is collapsed) so calendar grid columns never compress date buttons below `44×44 CSS px` . Use CSS `grid-template-columns: minmax(344px, 40%) minmax(0, 60%)` when horizontal container width >= ~720px so desktop settles at ~40%/60% and 768px fits 7 day columns >= 44px side-by-side cleanly.
  - **Mobile ( `320px` and `375px` ):** Single vertical column (Calendar -> Selected Day Time Groups -> Non-sticky `#selected-offer-summary` ), zero horizontal overflow ( `documentElement.scrollWidth <= window.innerWidth` , WCAG 2.2 SC 1.4.10). Every navigation, month-step, time-group, `"ดูเวลาเพิ่มเติม"` , offer-select, and confirm button targets `>= 44×44 CSS px` . **Explicit 320px math note:** since 7 horizontal day columns × 44px = `308px` plus grid gaps and card padding exceeds 288–304px usable content width at `320px` , at `>= 375px` ( `375` , `768` , `1280px` ) every day button hits `>= 44×44 CSS px` , while at `320px` calendar day buttons prioritize zero page horizontal overflow ( `SC 1.4.10` ) with `>= 44 CSS px` **height** and `>= 36 CSS px` **width** (well above `WCAG 2.2 AA SC 2.5.8` 's `24×24 CSS px` minimum).
- **NutTiew visual tokens & contrast pairing (design targets, verified rendered states in Part F):**
  - Shared tokens: `#202B44` navy sidebar, `#F7F8FB` canvas, `#FFFFFF` card surface, `#172137` dark ink, `#455A76` muted ink ( `>= 4.5:1` target), `#66778A` interactive borders ( `>= 3:1` SC 1.4.11; `4.59:1` on white), `#F47736` primary CTA fill with `#172137` dark text ( `5.76:1` ) and `#D96123` border ( `3.48:1` vs canvas, `3.69:1` vs white), keyboard focus outline `3px`

`solid #AA4519` (`outline-offset: 3px`, `5.53:1` vs canvas, `5.87:1` vs white; `#FFBD94` inside dark navy sidebar). Never use white text on `#F47736`, gradients, glassmorphism, or decorative emojis.

- **Screen-reader & motion accessibility:**
  - Concise `aria-live="polite"` status announcement on day/month selection matching `bangkokLongDate` (e.g., `"เลือกวันที่ 12 พ.ย. 2026 พบ 8 ช่วงเวลา"` or empty-month notice) — never re-announcing hundreds of records.
  - Support `@media (prefers-reduced-motion: reduce)` and `200%` browser zoom without clipping text, losing focus rings, or creating horizontal page scroll.
- **Phase 2 profiling gate (deferred):** If genuine Part F or production profiling demonstrates that returning `500+` JSON records from `GET /api/v1/customer/availability` creates a SQL/network latency bottleneck, propose a **separate reviewed Part E API amendment** (covering date-range/cursor parameters, `T_view` / `60-day` semantics, ordering stability, `BR-S1-20` query validation updates, and privacy checks). Phase 1 strictly forbids query-param expansion in UI PRs.
- **Planned STS & manual gate:** Acceptance criteria `UX-CAL-01..10` are defined in STS §2 alongside preserved regression obligations for `AVA-01..19`, `BOOK-01..33`, and `RET-*`. Every `UX-CAL` item is **PLANNED / NOT RUN** in this docs-only amendment; automated Playwright checks in later Part F must be reported separately from the **manual human WCAG 2.2 AA audit**, which remains **NOT RUN** until human inspection.

---

### E.4.3 F-S1-03 Customer Availability HTTP/API Contract (api-spec.md)

> **Part E docs-only contract; not implemented/runtime-tested.** Peer-review decisions are recorded in Feature SDS §5. See UI, Data, STS, Auth API, Tutor Slot API.

#### 1. Transport and authorization

- Same-origin /api/v1 JSON stack. This GET has no request body.
- Use the existing HttpOnly Session cookie, requireSession and requireRole(Customer).
- Principal comes only from getPrincipal(req) and persisted live Session/User. Never accept customerId, tutorId, role, owner, status, time or eligibility from query/header/body as authority.
- Anonymous: 401 UNAUTHENTICATED. Authenticated Tutor: 403 FORBIDDEN.
- Read-only GET: no CSRF token or unsafe-method Origin check. Preserve same-origin cookie behavior and no credentialed cross-origin CORS.
- Set Cache-Control: no-store. Return the same server-derived X-NutTiew-Session-Binding header as /api/v1/auth/me and Tutor own-Slot GET so UI rejects late data from a different Session, including another Session for the same User.
- Reuse existing request ID and error envelope; do not fork Auth/session logic.

#### 2. Endpoint

| Method/path | Query | Success | Enforcement |
|---|---|---|---|
| GET /api/v1/customer/availability | No query parameters (confirmed OD-AV-03) | 200 safe projection; `data: []` is a valid confirmed-empty result and still includes `meta.evaluatedAt` | Live Session, Customer role, Customer-specific read-time eligibility, allowlist, no-store |

Unknown query parameters (customerId, tutorId, from, to, page, cursor, limit or anything else) return 400 INVALID_INPUT under confirmed OD-AV-03. Any future filter/pagination requires a reviewed contract amendment; do not infer a maximum horizon/date window.

**Success response — Customer-specific bookable-only**

```
{
  "data": [
    {
      "slotId": "c62bfb8b-2530-4a7c-979c-a9a6d16be0df",
      "tutorRef": "4a6f3e1b-58f0-4d6e-9e4c-1c2a5b6d7e8f",
      "startsAt": "2026-11-08T06:00:00.000Z",
      "endsAt": "2026-11-08T07:00:00.000Z"
    }
  ],
  "meta": {
    "requestId": "opaque-request-id",
    "evaluatedAt": "2026-11-08T04:30:00.000Z"
  }
}
```

Values are illustrative. Before the response is written, `data[].startsAt`, `data[].endsAt` and `meta.evaluatedAt` must all be normalized to UTC with exactly three fractional-second digits ( `YYYY-MM-DDTHH:mm:ss.sssZ` ). The data projection uses explicit UTC conversion/formatting ( `AT TIME ZONE 'UTC'` followed by `to_char` ) before constructing JSON; raw PostgreSQL `timestamptz` values must never be serialized into JSON using the connection's session `TimeZone` . The API sends those normalized strings unchanged. `evaluatedAt` is database `T_view` . Every row is bookable for the authenticated Customer at that evaluation instant only; it is not a reservation or guarantee that a later Booking succeeds. `tutorRef` is the current identity fallback because no Tutor display-name field is approved in the base schema.

An empty successful response has the same envelope and metadata, with `data: []` and a non-null RFC 3339 UTC `meta.evaluatedAt` normalized by the same explicit UTC formatting rule. The endpoint sets `Cache-Control: no-store` for populated and empty 200 responses (and for errors). The timestamp comes from the same database statement/read evaluation as the offer list; it is not omitted or generated from the application/browser clock when there are no offers. Populated and empty responses must be byte-for-byte stable in timestamp representation when the PostgreSQL connection `TimeZone` changes between `UTC` and `Asia/Bangkok` for the same persisted instants.

```
{
  "data": [],
  "meta": {
    "requestId": "opaque-request-id",
    "evaluatedAt": "2026-11-08T04:30:00.000Z"
  }
}
```

**Exact response allowlist**

| Field | Type | Meaning |
|---|---|---|
| data | array | Eligible offers under the confirmed unfiltered S1 list |
| data[].slotId | UUID string | Persisted Slot ID; identifier for later Booking selection |
| data[].tutorRef | UUID string | Opaque Tutor reference derived from Slot.tutorId |
| data[].tutorDisplayName | Not currently returned; conditional optional string only after OD-AV-02 data approval | Explicit Tutor-provided public display name; never derived from email. Until approval, this property is absent and the UI uses `tutorRef` . |
| data[].startsAt | RFC 3339 UTC string ending Z | Persisted Slot start |
| data[].endsAt | RFC 3339 UTC string ending Z | Persisted Slot end |
| meta.requestId | opaque string | Existing request correlation ID |
| meta.evaluatedAt | RFC 3339 UTC string ending Z | Database read-evaluation instant T_view |

Never serialize Prisma/SQL rows wholesale. Exclude customerId, Customer name/email/phone, Booking ID/status/reason, Tutor email/phone, unapproved Tutor profile/name fields, password hash, Session ID/token/CSRF, other DB columns, SQL errors and

stack traces. Bookable-only response needs no bookable boolean. The only possible later addition is the specifically approved `tutorDisplayName` field after its data gate and migration are accepted.

OD-AV-01 is confirmed as Customer-specific bookable-only. Any later change to show unavailable offers requires a new reviewed contract amendment; it must never disclose whether unavailability is due to another Customer's Booking or the Q05 cutoff.

### 3. Ordering and read semantics

Confirmed Sprint 1 order: `startsAt ASC`, `tutorRef ASC`, `slotId ASC`. No client-selected order, filters or pagination. OD-AV-03 is a technical list constraint only; OD-002 (maximum advance horizon) remains OPEN. The absence of filters/pagination is not an approved unlimited-horizon policy or a guarantee for unlimited data volume.

Confirmed OD-AV-01/04: sample one PostgreSQL `T_view` for the read. Under Customer-specific bookable-only, a row must be lifecycle Offered, have no active Booked row for its Slot ID, satisfy startsAt - T_view >= 60 minutes, and have no overlapping Active Booking owned by `principal.userId`. The owner is derived from the live Session; it is never accepted from a query parameter, header or body. For the Customer-overlap check, only `status = Booked` rows with `customerId = principal.userId` participate, using persisted Booking interval fields and the half-open predicate `booking.startsAt < slot.endsAt AND slot.startsAt < booking.endsAt`. Cancelled rows do not conflict and adjacent intervals are allowed. This predicate checks existence only and never returns Booking details. Exactly 60:00 is included; 59:59 is excluded. Never use browser time or HTTP arrival time. T_view is not #16 T_elig; #16 repeats the authoritative checks after contention waits.

### 4. Safe errors

| Condition | Status/code | Behavior |
|---|---|---|
| Missing/expired/revoked Session | 401 UNAUTHENTICATED | No offer data |
| Authenticated wrong role | 403 FORBIDDEN | No offer data |
| Unknown/malformed query | 400 INVALID_INPUT | No query-dependent data |
| PostgreSQL unavailable/transient read failure | 503 SERVICE_UNAVAILABLE | Sanitized error; no empty-list fallback |
| Unexpected internal failure | 500 INTERNAL_ERROR | Sanitized; no SQL/stack details |

Error envelope follows the existing API: `{ error: { code, message }, requestId }`. Keep `Cache-Control: no-store` on every success and error response, including 401/403/400/500/503. A failed request is not equivalent to 200 with `data: []`.

### 5. Endpoint boundary

No POST, Booking mutation, reservation hold, Booking confirmation or idempotency key in #15. Do not reuse Tutor own-schedule route. No owner selector, filter, detail route or private Booking read. Selection carries only slotId to #16; #16 owns transactional recheck and Booking outcomes.

### 6. Implementation dependency and verification status

The current sprint1 schema has no Booking model. The Slot-occupancy and Customer-overlap `NOT EXISTS` predicates against active Booked rows are **logical contracts**, not executable against the current schema. Do not ship as “all Slots are unoccupied” or add `Slot.isBooked`. The selected route is a separately scoped shared Booking data-foundation Issue/PR (route B); its Issue/PR and accepted schema SHA are not yet created/recorded. Keep Part F blocked until that foundation is reviewed, merged and its exact SHA is recorded as described in Feature SDS §2.

#### Conditional Tutor display-name data gate (OD-AV-02)

- Candidate source: a public display name explicitly supplied and maintained by the Tutor; never infer it from `User.email` or login identity.
- Candidate field: nullable `User.tutorDisplayName` (`String?` / PostgreSQL `TEXT`), used only for Tutor accounts. The current schema has no such field.
- Data owner: the Tutor; customer-facing publication requires explicit Tutor opt-in and recorded product/stakeholder approval. @Chxtamos owns this contract; @Tanaboonnnnn peer-reviews it. The actual approving stakeholder and consent rule must be recorded before migration.

- Migration: a separate reviewed forward-only migration only after approval; no default and no email backfill. Existing rows remain `NULL`; seed only clearly test-only synthetic values in isolated fixtures.
- Current response: omit `tutorDisplayName`; return `tutorRef`. Only after approval may the exact allowlist add the nullable display-name field. Never add email, phone or unrestricted profile data.
- Planned privacy test: AVA-18 verifies no name is inferred from email, no unapproved field appears, and—after approval only—the approved field is the sole additional Tutor identity property.

This document defines the Part E endpoint contract only. No route, query, API test, browser test or performance result is claimed to exist or pass.

---

### E.4.4 F-S1-03 Customer Availability Data Contract (data-spec.md)

> **Logical read contract only.** No Prisma model, SQL migration, Booking table, index, Tutor-name column or runtime query is created here. Peer-review decision states and the selected shared-data route are recorded in Feature SDS. See API, UI and STS.

#### 1. Existing records at the Part E base

Verified sprint1 base: 551a9469e3d3a7e8e3ae004a382862c4f3e87e0e.

| Record | Relevant fields | F-S1-03 use |
|---|---|---|
| User | id, role, isActive; no display-name field exists | Source of opaque Tutor reference; `tutorDisplayName` is only a conditional future candidate, not present in the base schema |
| Slot | id, tutorId, startsAt, endsAt, lifecycle | Candidate offer, owner and UTC interval |
| Session | persisted user/session/expiry/revocation data | Auth middleware derives Customer principal; Session fields never enter response |
| Booking | **Not present in current Prisma schema/migrations** | Required future occupancy source; see §2 |

The current Slot table has a Tutor owner index (tutorId, startsAt, id), but no isBooked column. The Tutor own-list DTO temporarily returns occupancy Unoccupied because #16 has not introduced Booking; that is not a valid Customer-availability occupancy source after Booking exists.

#### 2. Booking relationship and selected sequencing gate

The System SDS describes Booking fields including customerId, currentSlotId, startsAt, endsAt and business status (Booked or later Cancelled). A current S1 Booked row is an Active Booking and occupies its referenced Slot. The separately reviewed shared data foundation must expose these persisted fields so #15 can check both Slot occupancy and Customer-specific overlap; #15 still does not create or mutate Booking records.

Required logical relation: Booking.currentSlotId = Slot.id AND Booking.status = Booked.

Required Customer-specific relation: `Booking.customerId = principal.userId AND Booking.status = Booked AND Booking.startsAt < Slot.endsAt AND Slot.startsAt < Booking.endsAt`. `principal.userId` is obtained from the authenticated Session, not request input. Booking interval values are the persisted snapshot of its current Slot interval. This is the half-open `[start,end)` overlap rule from requirements.md §3: a Customer's Active Booking with Tutor A excludes an overlapping offer from Tutor B; exact adjacency does not conflict. Cancelled rows are excluded. The query uses `NOT EXISTS` only and never projects the conflicting Booking, Customer ID or reason.

Neither relation can be queried in the current schema because the shared Booking data foundation has not yet been created. The team selected route B to break the #15/#16 dependency without moving Booking mutation into #15. Part E records the correct data source but does not invent Slot.isBooked, assume all Slots remain unoccupied, or create a partial Booking schema under #15.

**Selected route B — separate shared data foundation:** create a dedicated Issue/PR for the shared Booking schema/migration, with #15 and #16 as dependency links. Proposed implementation owner is @Chxtamos and peer reviewer is @Tanaboonnnnn. The

exact foundation Issue/PR, accepted migration and schema SHA are not yet created/recorded; this Part E PR does not create or approve them. Part F remains a hard **STOP GATE** until the shared foundation is reviewed, merged and the exact schema SHA is recorded. Booking mutation remains in #16; #15 only reads the persisted rows.

### 3. Proposed logical read projection

The following is **pseudocode**, not executable SQL against the current base. `$1` is a bound parameter populated only from `principal.userId` after `requireSession` / `requireRole(Customer)`; it is never copied from client input. The statement returns exactly one aggregate row even when `eligible_slots` is empty, so the API can always build `meta.evaluatedAt` from the same T_view.

```
WITH view_clock AS MATERIALIZED (
  SELECT clock_timestamp() AS evaluated_at
),
eligible_slots AS MATERIALIZED (
  SELECT
    s."id" AS "slotId",
    s."tutorId" AS "tutorRef",
    s."startsAt" AS "startsAt",
    s."endsAt" AS "endsAt"
  FROM "Slot" AS s
  CROSS JOIN view_clock
  WHERE s."lifecycle" = 'Offered'
    AND s."startsAt" >= view_clock.evaluated_at + INTERVAL '60 minutes'
    AND NOT EXISTS (
      SELECT 1
      FROM "Booking" AS occupied
      WHERE occupied."currentSlotId" = s."id"
        AND occupied."status" = 'Booked'
    )
    AND NOT EXISTS (
      SELECT 1
      FROM "Booking" AS customer_conflict
      WHERE customer_conflict."customerId" = $1
        AND customer_conflict."status" = 'Booked'
        AND customer_conflict."startsAt" < s."endsAt"
        AND s."startsAt" < customer_conflict."endsAt"
    )
)
SELECT
  COALESCE(
    jsonb_agg(
      jsonb_build_object(
        'slotId', eligible_slots."slotId",
        'tutorRef', eligible_slots."tutorRef",
        'startsAt', to_char(
          eligible_slots."startsAt" AT TIME ZONE 'UTC',
          'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"'
        ),
        'endsAt', to_char(
          eligible_slots."endsAt" AT TIME ZONE 'UTC',
          'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"'
        )
      )
      ORDER BY eligible_slots."startsAt" ASC,
               eligible_slots."tutorRef" ASC,
               eligible_slots."slotId" ASC
    ) FILTER (WHERE eligible_slots."slotId" IS NOT NULL),
    '[]'::jsonb
  ) AS "data",
  to_char(
    view_clock.evaluated_at AT TIME ZONE 'UTC',
    'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"'
  ) AS "evaluatedAt"
FROM view_clock
LEFT JOIN eligible_slots ON TRUE
GROUP BY view_clock.evaluated_at;
```

Intent: sample DB clock once as T_view; use persisted Slot lifecycle/interval; exclude active Booked rows on the candidate Slot; exclude any overlapping Active Booking belonging to the authenticated Customer (including another Tutor); return only the safe

projection; order deterministically. The outer query starts from the one-row `view_clock` CTE and LEFT JOINs the candidate set, then aggregates with a filtered `jsonb_agg` and `COALESCE`. Therefore it returns one row with `data = []` and the same non-null `evaluatedAt` when no candidate exists. This is one SQL statement, not a second clock read or an application-clock fallback. **Before values enter JSON, every timestamp is explicitly normalized to UTC with `AT TIME ZONE 'UTC'` and formatted as `YYYY-MM-DDTHH:mm:ss.sssZ` by `to_char`; no raw `timestamptz` is passed to `jsonb_build_object`.** This makes the wire representation independent of the PostgreSQL connection `TimeZone`. Exact SQL/Prisma query and read-isolation require peer review and a real PostgreSQL test after Booking schema exists. This pseudocode has not been run.

### 4. Time and timezone

- PostgreSQL stores startsAt/endsAt as TIMESTAMPTZ.
- The SQL response projection converts `startsAt`, `endsAt` and `T_view` to UTC before JSON construction: `to_char(value AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"')`. The wire values have exactly three fractional-second digits and end in `Z` (for example `2026-11-08T06:00:00.000Z`). Never put a raw `timestamptz` directly into `jsonb_build_object` or rely on the connection `TimeZone` to serialize it.
- API returns these already-normalized UTC RFC 3339 strings unchanged; it does not reinterpret a timezone-dependent database timestamp string.
- UI always formats Asia/Bangkok (UTC+07:00), independent of browser timezone.
- T_view is the single PostgreSQL time for this read; startsAt - T_view >= 60 minutes is the confirmed Customer-availability read rule and equality passes.
- A Customer's own `Booked` rows are checked by persisted `[startsAt, endsAt)` intervals; only strict overlap is excluded, so adjacency passes. The principal comes from the Session.
- #16 Booking write uses its own authoritative T_elig after contention waits; it must not trust T_view, evaluatedAt, browser time or prior availability.
- OD-002 (maximum advance horizon) remains OPEN. This contract does not choose an upper bound and does not imply an approved unlimited horizon. Resolve OD-002 before Part F; do not invent work-hour/day, holiday or start-minute rules either.

### 5. Response projection and privacy

| Property | Source | Type | Privacy |
|---|---|---|---|
| slotId | Slot.id | UUID string | Safe selection ID, not Booking ID |
| tutorRef | Slot.tutorId | UUID string | Current opaque Tutor reference; no email/name/phone |
| tutorDisplayName | Not present in the current schema; conditional future `User.tutorDisplayName` | Nullable string only after separate data approval and migration | Not returned before approval; never derived from email; Tutor opt-in and publication approval required |
| startsAt | Slot.startsAt | UTC ISO string | Required time |
| endsAt | Slot.endsAt | UTC ISO string | Required time |
| meta.evaluatedAt | T_view | UTC ISO string | Read evaluation time, not Booking guarantee |
| meta.requestId | Existing middleware | opaque string | Correlation only |

Never select/serialize Customer ID/name/email/phone, Booking ID/status/reason, Session ID/token/CSRF, password hash or arbitrary Prisma columns. Request fields cannot choose another Customer/Tutor owner. Tutor UUID is not a credential and grants no authorization; UI compaction is presentation only.

The API must set `Cache-Control: no-store` for populated and empty success responses and every error response. `meta.evaluatedAt` is sourced from the one-row DB clock aggregate in §3 even when `data = []`; do not fall back to an application/browser clock.

**Conditional Tutor public-display-name source and migration gate**

- **Current source fact:** `User` has no display-name/profile field in the reviewed base schema. `email` is an authentication identifier and is never a display-name source.
- **Candidate source/field:** an explicit public display name supplied and maintained by the Tutor, stored as nullable `User.tutorDisplayName` ( `String?` in Prisma / PostgreSQL `TEXT` ), used only for Tutor accounts. This field is a proposal only; it is not added by this PR.
- **Data owner/permission:** the Tutor owns and supplies the value and must explicitly opt in to customer-facing display. The product/stakeholder owner must record publication approval and consent wording. @Chxtamos is the feature-contract owner; @Tanaboonnnnn is the peer reviewer. The actual approving stakeholder and consent rule must be recorded before any migration.
- **Migration/seed:** add the nullable field only through a separate reviewed forward-only migration after approval; no default, no backfill from email, and existing Tutor rows remain `NULL`. Use synthetic names only in isolated test fixtures clearly marked test-only; never make fixture data appear as a real Tutor identity.
- **DTO rule:** until the gate is cleared, omit `tutorDisplayName` entirely and return `tutorRef`. After approval, add only this explicitly approved field to the response allowlist; keep email, phone and other profile fields excluded.
- **Privacy test:** AVA-18 checks absence before approval and checks the exact approved field/allowlist after approval; it also verifies that an email value is never used as a fallback name.

### 6. Storage and mutation boundary

F-S1-03 is read-only: no record writes, tables, columns, migrations, indexes, triggers or occupancy denormalization. It does not alter F-S1-02 Slot owner, immutability, duration or overlap constraints. Booking persistence and transaction integrity belong to #16.

### 7. Part F data verification obligations

1. Seed at least two Tutors and two Customers with test-only opaque IDs.
2. Create real future Offered Slots for multiple Tutors, including same-time offers from different Tutors.
3. With no active Booking, verify expected offers.
4. With a committed Booked row for one Slot, verify it is excluded while other offers remain; inspect full JSON for no Customer/Booking leakage.
5. Verify T_view equality (60:00 included) and below-boundary (59:59 excluded) with controlled DB time.
6. Verify deterministic order, UTC serialization and identical Bangkok display from UTC/other-timezone browsers.
7. Inject read failure; verify no false empty list; retry successfully.
8. Verify role/session isolation, session binding and no stale data after logout/account switch.
9. Verify a Customer's overlapping Active Booking on Tutor A hides an overlapping free Slot on Tutor B for that Customer (AVA-15).
10. Verify exact adjacency is allowed under `[start,end)` (AVA-16); Cancelled rows and another Customer's Active Booking do not create a conflict for the current Customer (AVA-17).
11. Verify Tutor display-name field is absent until the data gate is accepted; after approval, only the approved `tutorDisplayName` field is projected and no email/phone or unapproved profile data leaks (AVA-18).

All are PLANNED / NOT RUN in Part E. Occupancy- and Customer-overlap-dependent checks remain BLOCKED until the separate shared Booking data foundation is reviewed, merged and its exact schema SHA recorded. The positive Tutor-name projection check remains BLOCKED until its separate data-approval and migration gate is cleared.

---

### E.4.5 F-S1-03 Customer Availability Software Test Specification (tests.md)

> **UX delta proposed 2026-11-10 (Issue #44, pending peer review):** preserve `AVA-01..19` below (whose initial `#15` executions are recorded in verification ledger and which remain mandatory regression checks alongside Option A) and add the planned `UX-CAL-01..10` calendar test cases from UX decision 2026-11-10 and amended UI spec. All `UX-CAL-01..10` checks and human WCAG 2.2 AA sign-off are **PLANNED / NOT RUN** in this docs-only Part E PR. Do **not** renumber existing `AC-S1-01..35` or `VC/TEST-S1-01..39`.

> **Historical baseline Part E note (PR #32):** All baseline cases below were originally planned prior to `#15` Part F ( `PR #37` ) and `#16` Part F ( `PR #38` ). Booking-query cases consumed the merged `#33` schema ( `PR #36` ); `AVA-11` now exercises the merged `#16` Booking transaction; `OD-AV-02` Tutor public display-name positive-path remains gated.

#### 1. Baseline availability STS cases (historical Part E PR #32 — AVA-01..19)

> During Issue #44 Part F, existing `AVA-*` browser checks remain required regressions, adapting DOM selection steps only where Option A collapses day/time lists without weakening any eligibility, privacy, order, session-binding, or Booking safety assertion.

| STS ID | Trace | Scenario | Required result | Dependency |
|---|---|---|---|---|
| AVA-01 | FR-S1-08, AC-S1-15, VC/TEST-S1-15, VAL-006 | C1 requests availability with an eligible future Slot | 200; approved Tutor display name if gate is cleared, otherwise opaque Tutor reference; Slot ID and Bangkok start/end identifiable; deterministic order | Shared Booking data foundation + #13/#14; name field remains gated |
| AVA-02 | FR-S1-09, AC-S1-16, BR-S1-08/21, VC/TEST-S1-22 | One Slot has a committed active Booked row; another is free | Occupied Slot not returned as bookable; other offer remains; no Customer/Booking details | Reviewed shared Booking foundation migration + committed test-only Booking rows in disposable PostgreSQL; no #16 endpoint required |
| AVA-03 | FR-S1-09, AC-S1-16, BR-S1-07/11, VC/TEST-S1-17/18, VAL-008/009 | Evaluate a past Slot, exactly 60:00 and 59:59 before start using controlled DB time | Past/59:59 excluded; exactly 60:00 included; browser clock irrelevant | Shared Booking data foundation + DB clock harness |
| AVA-04 | AC-S1-18, BR-S1-12, VC/TEST-S1-13 | Request the same populated fixture with one controlled identical DB `T_view` and PostgreSQL connection `TimeZone` set to `UTC` and `Asia/Bangkok`; also render in Bangkok, UTC and another browser timezone | Wire `startsAt` , `endsAt` and `meta.evaluatedAt` are byte-for-byte identical UTC `...sssZ` strings under both DB settings; Bangkok display is the same intended local date/time under every browser timezone | Reviewed shared Booking foundation migration + populated disposable-DB fixture; DB-session and browser timezone matrix |
| AVA-05 | FR-S1-08, NFR-S1-01/08, NFR-007, VAL-036 | Inspect full JSON with multiple Customers/Tutors | Exact allowlist only; no Customer PII, Booking ID/status/reason, email, Session/token/hash, SQL or stack; Tutor identity is `tutorRef` until name approval | Shared Booking data foundation; name field remains gated |

| STS ID | Trace | Scenario | Required result | Dependency |
|---|---|---|---|---|
| AVA-06 | BR-S1-17, NFR-S1-01, VC/TEST-S1-05/06, VAL-002 | Anonymous and Tutor call Customer endpoint | Anonymous 401; Tutor 403; no offer data | #13/#14 merged |
| AVA-07 | BR-S1-20, NFR-S1-01 | Customer adds customerId/tutorId/role/page/arbitrary query | 400 INVALID_INPUT; identity/owner scope cannot be changed | #13/#14 merged |
| AVA-08 | AC-S1-15, NFR-S1-07 | Seed same-time offers from different Tutors | Stable startsAt/tutorRef/slotId order; no duplicates/hidden rows | Shared Booking data foundation + #14 merged |
| AVA-09 | AC-S1-15, NFR-S1-07/08, VAL-036 | With a controlled identical DB `T_view` and no eligible offers, repeat the empty query with PostgreSQL connection `TimeZone` set to `UTC` and `Asia/Bangkok` | Both wire responses return `data: []`, the same non-null `meta.evaluatedAt` formatted as UTC `...sssZ`, and `Cache-Control: no-store`; the aggregate still returns one metadata row; errors are never mapped to empty | Reviewed shared Booking foundation migration + empty disposable-DB fixture; DB-session timezone matrix |
| AVA-10 | FR-S1-18, NFR-S1-07/08, VAL-036 | GET/retry fails 503/network then later succeeds | Error/retry visible; no empty/zero claim during failure; successful retry restores results | #13/#14 merged |
| AVA-11 | AC-S1-17, FR-S1-09/11, BR-S1-13/21, VC/TEST-S1-22 | Customer selects offer; it becomes occupied or enters Q05 cutoff before Booking | #16 rejects without Booking/false success; UI shows non-success and refreshes | **#16 Booking transaction/endpoint required** |
| AVA-12 | NFR-S1-01/08, BR-S1-20, VAL-036 | Hold old Customer 200; logout/switch Session before releasing it | Old response never repaints; clear offers/selection on Session binding mismatch | #13/#14 merged |
| AVA-13 | NFR-S1-09, VAL-033 | Keyboard-only browse/select through loading/populated/empty/error at 320/375/768/1280 CSS px | Logical focus order, visible/unobscured focus, semantic loading/result/empty/error announcements, responsive reflow, actionable retry and measured target dimensions; 44px is a design target, not a pass without evidence | Part F manual/browser check |
| AVA-14 | NFR-S1-10, VC/TEST-S1-36 | Benchmark local seeded availability GET after warm-up | Record machine/DB/sample/p95/source SHA and workload; ≤2.0s is reference-only and must not determine pass/fail | Part F measurement; no threshold gate |
| AVA-15 | FR-S1-09/13, AC-S1-16, BR-S1-09, Q28, VAL-011 | C1 has Active Booked interval 13:00–14:00 with Tutor A; a free Tutor B Slot is 13:30–14:30 | Exclude Tutor B Slot for C1 because the authenticated Customer already has an overlapping Active Booking on another Tutor; do not return the conflicting Booking or Customer details | Reviewed shared Booking foundation migration + committed test-only Booking rows in disposable PostgreSQL; no #16 endpoint required |
| AVA-16 | FR-S1-09/13, AC-S1-16, BR-S1-10, Q28 | C1 has Active Booked interval 13:00–14:00; a free Tutor B Slot is exactly 14:00–15:00 | Include the candidate because `[start,end)` intervals are adjacent, not overlapping; strict predicate permits equality at the boundary | Reviewed shared Booking foundation migration + committed test-only Booking rows in disposable PostgreSQL; no #16 endpoint required |

| STS ID | Trace | Scenario | Required result | Dependency |
|---|---|---|---|---|
| AVA-17 | FR-S1-09/13, BR-S1-09/10, Q28 | A free candidate Slot overlaps either a Cancelled C1 Booking or an Active Booking of C2 on a different Slot/Tutor | Include the candidate for C1 in both controls; only `customerId = principal.userId AND status = Booked` participates in the Customer-overlap predicate. A separate Active Booking on the candidate Slot itself must still exclude it for everyone under AVA-02 | Reviewed shared Booking foundation migration + committed test-only Booking rows in disposable PostgreSQL; no #16 endpoint required |
| AVA-18 | FR-S1-08, NFR-S1-01/08, VAL-036 | Inspect Tutor identity before and after OD-AV-02 data approval | Before approval, no `tutorDisplayName` field and no email-derived name; after approved migration/consent, only the approved nullable display-name field may be added to allowlist; no email/phone/profile leakage | Current schema for negative case; separate data approval + migration for positive case |
| AVA-19 | OD-AV-08, AC-S1-15 | Compare Customer Availability with Tutor Dashboard at desktop and mobile breakpoints | Shared NutTiew wordmark, typography, spacing, brand/nav colors, button/focus components and navigation behavior; only role-authorized destinations differ | Part F browser visual review |

## 2. UX calendar planned STS

> All cases below are **PLANNED / NOT RUN** in Issue #44 Part E. Execute in the separate Part F implementation branch after this Part E PR merges into `sprint1`.

| STS ID | Trace | Scenario / setup | Required observable result | Method / status |
|---|---|---|---|---|
| **UX-CAL-01** | `FR-S1-08`, `AC-S1-15`, `OD-AV-03`, `UX-CAL` | Authenticated Customer receives `200 OK` with **500+ deterministic offers** across both (a) multi-day distribution up to 60 days and (b) single-day heavy distribution (`> 6` time groups, repeated Tutors) | Renders Option A 7-column monthly calendar + selected day's initial time groups (`<= 6` collapsed groups + `"ดูเวลาเพิ่มเติม"` when `> 6`); no period filter chips; DOM does **not** mount all 500+ offer rows simultaneously; clicking `"ดูเวลาเพิ่มเติม"` reveals all remaining time groups on that day without filtering away eligible offers or sending new HTTP query params | Browser E2E + unit/component check (**PLANNED / NOT RUN**) |
| **UX-CAL-02** | `FR-S1-08/09`, `AC-S1-15/18`, `OD-002`, `OD-AV-03` | Fixture spanning **Nov -> Dec -> Jan** year rollover (`2026-11-28` -> `2027-01-15` within `OD-002` 60-day `T_view`), intermediate empty month (`Dec`), same-time multiple Tutors on one day, and a controlled **leap-year February** (`2028-02-29`) | Initial calendar opens earliest eligible offer month and auto-selects earliest eligible day; each day badge displays **total offer count** (`N ช่วงเวลา`, NOT unique Tutor count); empty dates display non-color empty markings and `disabled`; Prev/Next buttons cross Nov -> Dec -> Jan and Feb 28/29 accurately using server `meta.evaluatedAt` + offers (no browser-clock horizon or hardcoded month count); intermediate empty month renders clear empty message | Controlled `T_view` + Playwright E2E (**PLANNED / NOT RUN**) |
| **UX-CAL-03** | `FR-S1-08`, `AC-S1-15`, `OD-AV-02/03`, `BR-S1-06` | Selected day contains multiple exact `(startsAt, endsAt)` pairs (including non-hourly minutes e.g. `10:15–11:15`, same-time offers from Tutors A/B, and adjacent offers) | Time groups key strictly on exact `(startsAt, endsAt)` pairs without hour snapping or slot merging; selecting a day updates Step 2 only; expanding a time group shows distinct `tutorRef` + `slotId` items in exact server order (`startsAt ASC, tutorRef ASC, slotId ASC`); no email-derived names, ratings, subjects, prices, or private fields appear | Playwright E2E (**PLANNED / NOT RUN**) |

| STS ID | Trace | Scenario / setup | Required observable result | Method / status |
|---|---|---|---|---|
| **UX-CAL-04** | `FR-S1-10/18`, `AC-S1-17`, `BR-S1-21` | Select a Slot, then switch calendar days/months or click `"ดูเวลาเพิ่มเติม"`; repeat while `UnknownBookingOutcome` (`503 BOOKING_OUTCOME_UNKNOWN` / network timeout) is active | Selecting day/month/time NEVER dispatches `POST` and never clears/swaps `selectedSlotId`; `#selected-offer-summary` appears only after clicking a real offer, states selection **is not a Booking**, stays rendered inline (non-sticky) below the day list across day/month changes; when `unknownOutcome` is active, selecting another `slotId` stays disabled until retry reconciles; if refresh removes non-unknown selection, clear selection cleanly and show `staleNotice` without false Booking | Playwright E2E (**PLANNED / NOT RUN**) |
| **UX-CAL-05** | `FR-S1-10..18`, `AC-S1-16..35`, `BOOK-01..33`, `RET-03/06` | End-to-end Booking confirmation and retrieval flows through Option A UI against real PostgreSQL | Confirms `201 Created` (`จองสำเร็จ` + persisted row), `200 OK` natural-key replay, `409 SLOT_UNAVAILABLE`, `409 CUSTOMER_OVERLAP`, `422 BOOKING_NOT_ELIGIBLE` (Q05 cutoff), `503 BOOKING_OUTCOME_UNKNOWN` + `"ส่งคำขอเดิมอีกครั้ง"`, `การจองของฉัน` retrieval tab (`F-S1-05`), and cross-Customer `404` isolation without regression | Real PostgreSQL + Edge E2E (**PLANNED / NOT RUN**) |
| **UX-CAL-06** | `FR-S1-18`, `BR-S1-17/20`, `NFR-S1-01/08` | Inject initial/retry `503`, malformed 200 payload (bad `evaluatedAt` / offer shape), global `200 data: []`, post-refresh/empty-month day empty, `401` / `403`, mismatched `X-NutTiew-Session-Binding`, logout uncertainty, delayed old-Customer `200` after logout/account switch | Fail-closed throughout: loading does not claim empty; `503` /malformed DTO hides calendar/counts and renders retry (`never 0`); only verified `data: []` shows global empty; day empty distinct from global empty; session/binding mismatch, logout, and `401` / `403` abort/clear calendar state immediately and never repaint stale account data | Real DB + mocked HTTP/network fault Edge E2E (**PLANNED / NOT RUN**) |
| **UX-CAL-07** | `AC-S1-18`, `BR-S1-12`, `Q29`, `VC/TEST-S1-13` | Render populated schedule (including midnight-adjacent/cross-midnight `23:30–00:30` Bangkok offer near UTC day change e.g. `16:30Z`) in browsers set to `UTC` and `America/Los_Angeles` | Bangkok month heading, calendar day bucket, `selectedDayKey` header, `HH:mm–HH:mm น.` interval, and `สิ้นสุดในวันถัดไป` badge remain identical across `UTC`, `America/Los_Angeles`, and `Asia/Bangkok` browser timezones | Cross-timezone Playwright E2E (**PLANNED / NOT RUN**) |
| **UX-CAL-08** | `NFR-S1-09`, `VAL-033`, `OD-AV-08` | Keyboard-only flow (`Tab` / `Shift+Tab` / `Enter` / `Space`) across month navigation, active dates, time groups, `"ดูเวลาเพิ่มเติม"`, offer select, inline confirm summary, and cancel/retry; verify ARIA, contrast, `@media (prefers-reduced-motion: reduce)`, and `200%` zoom | Focus ring (`3px solid #AA4519`, offset `3px`) visible and unobscured in all states; `aria-live="polite"` announces `"เลือกวันที่ ... พบ ... ช่วงเวลา"` concisely without dumping all offers; selection/empty meaning uses non-color cues (`aria-pressed`, border/text badge, dash); computed contrast meets `>= 4.5:1` text / `>= 3:1` non-text UI (`5.76:1` dark ink `#172137` on `#F47736`, `#D96123` border, `#66778A` controls); `prefers-reduced-motion` and `200%` zoom remain functional. **Manual human WCAG 2.2 AA audit remains separately tracked `NOT RUN`.** | Edge E2E + CSS telemetry (**PLANNED / NOT RUN**); Human WCAG audit (**NOT RUN Manual Gate**) |

| STS ID | Trace | Scenario / setup | Required observable result | Method / status |
|---|---|---|---|---|
| **UX-CAL-09** | `NFR-S1-09`, `OD-AV-08`, `AVA-01..19`, `BOOK-01..33`, `RET-*` | Capture genuine DB-backed Playwright screenshots at **`320`, `375`, `768`, and `1280` CSS px**; measure element bounding boxes, horizontal overflow, and full sprint regression suites | Zero horizontal overflow ( `scrollWidth <= innerWidth` ) at all 4 widths; desktop `>= 768px` renders ~40/60 two-pane layout; `320/375px` renders vertical stack with non-sticky inline `#selected-offer-summary` never overlapping focus/buttons; all non-grid controls and `>= 375px` day tiles measure `>= 44×44 CSS px` ( `320px` day tiles measure `>= 36×44 CSS px` , exceeding WCAG 2.2 AA `SC 2.5.8` `24×24px` ); all existing `AVA` , `BOOK` , `RET` , `Auth` , and `Slot` regressions pass | Real DB + Edge E2E screenshots (**PLANNED / NOT RUN**) |
| **UX-CAL-10** | `NFR-S1-07/12`, `OD-AV-07` | Run `npm test` , `npm run typecheck` , `npm run build` , PostgreSQL integration suite, Playwright Edge suite, and GitHub Actions CI on **exact Part F HEAD** | All automated CI jobs green on exact PR HEAD; ledger records commit SHA, exact PASS/FAIL/SKIP counts, changed test IDs, before/after screenshots, `AVA-14` latency observation with `500+` rows (confirming whether Phase 2 API pagination is needed), and UX rationale | Full Local + Hosted CI (**PLANNED / NOT RUN**) |

> **Manual Accessibility & Phase 2 Gates:** Passing automated checks in `UX-CAL-08` / `UX-CAL-09` does **not** certify full WCAG 2.2 AA compliance; manual human assistive-technology/WCAG inspection stays explicitly marked `NOT RUN` unless performed and signed off by a human reviewer. Any Phase 2 server query/pagination ( `?from` / `?to` / `?page` ) remains out of scope unless Part F profiling justifies a separate reviewed Part E API amendment.

### 3. Fixtures and execution method

- Use disposable real PostgreSQL with accepted Auth/Slot migrations and the reviewed Booking migration when available.
- Seed test-only C1/C2 Customers and T1/T2 Tutors; do not commit credentials, tokens, real records or DB dumps.
- Seed future Slots relative to DB time, not fixed dates that expire.
- For AVA-02/15/16/17, apply the reviewed shared Booking foundation migration to a disposable PostgreSQL database, then create actual persisted `Booked` / `Cancelled` rows with test-only seed SQL/fixtures that satisfy the schema's constraints. Commit the rows in the DB transaction and query them directly; these read-predicate cases do not call or wait for the #16 Booking endpoint. Never simulate occupancy with Slot.isBooked, bypass DB constraints, or fabricate response-only Booking objects.
- For AVA-09 use the same reviewed foundation in a disposable DB and a controlled DB clock; test both populated/empty projection semantics under connection `TimeZone = 'UTC'` and `'Asia/Bangkok'` .
- For AVA-11 use the real #16 Booking endpoint and its committed transaction outcome; never simulate a successful or rejected Booking in the UI.
- For AVA-15/16/17 use actual committed `Booked` and `Cancelled` rows for two Customer principals and multiple Tutors; assert owner filtering and half-open boundaries from persisted Booking intervals, never from fake Slot flags.
- For AVA-18 do not derive a display name from email. Run the positive allowlist case only after the Tutor-provided field, opt-in, approving stakeholder and forward-only migration are accepted; test fixtures must be explicitly synthetic/test-only.
- For AVA-19 compare actual Customer/Tutor browser renders and computed shared design tokens; do not infer visual consistency from source-only screenshots or claim accessibility conformance from token comparison.
- API tests inspect full response body/headers; for AVA-04/09 set PostgreSQL connection `TimeZone` to `UTC` and `Asia/Bangkok` while holding persisted instants (and `T_view` for AVA-09) constant, then assert identical wire timestamps for `startsAt` , `endsAt` and `meta.evaluatedAt` , each matching `YYYY-MM-DDTHH:mm:ss.sssZ` . Playwright/browser tests separately verify Bangkok rendering across browser timezones.
- Use controlled DB time or deterministic query seam for 60:00/59:59; no sleeps or browser clock.

- Record exact command, environment, Node/PostgreSQL version, migration, source SHA and PASS/FAIL/SKIP/BLOCKED plus observed rows.
- **Option A UX calendar fixtures ( `UX-CAL-01..10` ):**
  - Generate deterministic `500+` synthetic offers covering both multi-day spans (up to `60 days` from controlled DB `T_view` ) and single-day dense offers ( `> 6` distinct `(startsAt, endsAt)` time groups + repeated same-time offers across multiple Tutors).
  - Include controlled DB `T_view` / route fixtures crossing year rollover ( `2026-11 -> 2026-12 -> 2027-01` with `Dec` empty control month) and leap-year February ( `2028-02-29` ).
  - Browser tests under Playwright must capture **before/after** screenshots on genuine DB-backed Customer sessions at `320` , `375` , `768` , and `1280` CSS px plus explicit `UTC` and `America/Los_Angeles` timezone contexts, measuring computed bounding boxes, `documentElement.scrollWidth <= window.innerWidth` , focus visibility, and computed contrast samples cleanly separated from any unexecuted manual human WCAG sign-off.

### 4. Error/UI observations

| API outcome | UI behavior |
|---|---|
| 200 with offers (historical baseline) | Render approved Tutor display name only after its gate, otherwise `tutorRef` ; preserve server order |
| 200 with data: [] | Confirmed-empty state; metadata still includes `evaluatedAt` and response is `no-store` |
| 401 | Clear protected data and return to signed-out Auth |
| 403 | Access denied; no availability data |
| 400 | Safe invalid-request state; do not auto-retry unchanged input |
| 500/503/network/timeout | Error + retry; never empty/success |
| Later #16 stale/occupied/cutoff rejection | Non-success; refresh; do not claim Booking |
| 200 with offers (Option A) | Render monthly calendar opened at earliest eligible month, preselect earliest day (on initial load), display offer counts per day, show `<= 6` collapsed `(startsAt, endsAt)` time groups + `ดูเวลาเพิ่มเติม` , show approved Tutor display name only after `OD-AV-02` gate otherwise `tutorRef` , preserve server order |
| 200 with offers (selected day or month empty) | After refresh or switching to an empty intermediate month within the `T_view` horizon, display explicit day/month-empty message inside Step 2 without falsely asserting global empty when other days retain offers |
| Session-binding mismatch/account switch | Clear offers, calendar state, day index, and selection; ignore stale responses |
| Malformed 200 payload / invalid UTC date | Treat as fail-closed read error ( `#availability-error` + `โหลดอีกครั้ง` ); never commit partial calendar or claim `0` offers |

### 5. AC coverage

| Acceptance criterion | STS |
|---|---|
| AC-S1-15 | AVA-01, AVA-05, AVA-06, AVA-08, AVA-09, AVA-18 |
| AC-S1-16 | AVA-02, AVA-03, AVA-15, AVA-16, AVA-17 |
| AC-S1-17 | AVA-11 |
| AC-S1-18 | AVA-04 |

**Option A UX follow-up traceability (additive `UX-CAL-01..10`, no renumbering of `AC-S1-01..35`)**

| Acceptance / requirement ID | Planned STS |
|---|---|
| AC-S1-15 (`FR-S1-08`, `OD-AV-02/03`) | `AVA-01`, `AVA-05`, `AVA-06`, `AVA-08`, `AVA-09`, `AVA-18`, **`UX-CAL-01..03`** |
| AC-S1-16 (`FR-S1-09`, `OD-002`) | `AVA-02`, `AVA-03`, `AVA-15`, `AVA-16`, `AVA-17`, **`UX-CAL-02`**, **`UX-CAL-05`** |
| AC-S1-17 (`AC-S1-19..35`, `F-S1-04` / `F-S1-05`) | `AVA-11`, **`UX-CAL-04`**, **`UX-CAL-05`** |
| AC-S1-18 (`BR-S1-12`, `VC/TEST-S1-13`) | `AVA-04`, **`UX-CAL-07`** |
| `FR-S1-18`, `NFR-S1-01/08` (fail-closed read & session guards) | `AVA-06`, `AVA-10`, `AVA-12`, **`UX-CAL-06`** |
| `NFR-S1-09`, `OD-AV-08` (accessibility, keyboard, contrast, responsive) | `AVA-13`, `AVA-19`, **`UX-CAL-08`**, **`UX-CAL-09`** |
| `NFR-S1-07/10/12` (CI reproducibility & Phase 2 profiling evidence) | `AVA-14`, **`UX-CAL-10`** |

### 6. Part E boundary and Part F evidence

**Issue #44 Option A UX amendment boundary (current PR)**

- **`UX-CAL-01..10` are PLANNED / NOT RUN** in this docs-only Issue #44 Part E PR. None of the Option A calendar flows, `500+` DOM/viewport captures, cross-year/leap-year interactions, or accessibility telemetry assertions is claimed as executed or passing here.
- **Documentation-only scope:** No `apps/`, `e2e/`, Prisma/SQL migrations, `scripts/compile-deliverable.mjs`, `DELIVERABLE_1.md`, or `.pdf` deliverable files are modified or re-run in this PR. Deliverable 1 (PR #43 / #18) stays untouched.
- **Manual accessibility gate:** Any human WCAG 2.2 AA / assistive-technology inspection remains **NOT RUN** unless executed and signed off separately by a human reviewer; `44×44 CSS px` (`36×44 CSS px` at `320px` day cells) and token contrast values are design targets to verify empirically in Part F, never automated passes.
- **Subsequent Part F execution requirements (separate code PR after `@Tanaboonnnnn` approves and merges Part E to `sprint1`):**
  - Run `UX-CAL-01..10` together with full regressions (`AVA-01..19`, `BOOK-01..33`, `RET-*`, `Auth`, `Slot`) against real PostgreSQL and Microsoft Edge (`npm test`, `npm run typecheck`, `npm run build`, PostgreSQL integration, Playwright Edge suite, and hosted CI on the exact PR HEAD).
  - Capture genuine DB-backed before/after screenshots at `320`, `375`, `768`, and `1280 CSS px` plus `UTC` and `America/Los_Angeles` browser timezone verification; measure `documentElement.scrollWidth <= window.innerWidth`, actual control target boxes, focus visibility, and contrast samples.
  - Record `AVA-14` latency with `500+` seeded rows to verify objectively whether Phase 1 client-side calendar indexing remains sufficient or warrants a separate Phase 2 Part E API query/pagination amendment.
  - Update verification ledger with exact commit SHA, hosted CI run URL, pass/fail/skip counts, changed test IDs, screenshot evidence, and explicit `NOT RUN` manual WCAG boundary.

**Historical `#15` baseline Part E note (superseded execution blockers below)**

- In the original `#15` Part E baseline (`PR #32`), `AVA-01..19` were planned only with none passing at that stage.
- At that baseline stage, DB-backed cases (`AVA-01..05`, `AVA-08..10`, `AVA-12`, `AVA-15..17`) and `AVA-11` awaited `#33` Booking foundation (`PR #36`), `#15` Part F (`PR #37`), and `#16` Part F (`PR #38`); subsequent merged executions and source SHAs are recorded in verification ledger.
- `AVA-18` positive-path display-name verification remains **BLOCKED** under `OD-AV-02` until the Tutor data source, opt-in/publication approval, migration, and allowlist amendment are accepted; its pre-approval absence and anti-email-derivation checks remain required regressions.
- AVA-13/19 are manual/browser checks; AVA-14 records p95 only. No WCAG 2.2 AA, 44px target or ≤2.0s performance pass is claimed or used as a gate here.

- Consistent with Part E separation, no test, migration, API route, query, browser run, benchmark, or manual accessibility audit is executed by this STS documentation amendment.
- Historical `#15` Part F sequencing required the merged `#33` Booking foundation for `AVA-01..10` / `12` / `15..17`, the `#16` endpoint for `AVA-11`, and exact `320/375/768/1280 CSS px` + timezone + keyboard/focus evidence; `AVA-18` positive-path display-name display remains blocked until `OD-AV-02` clears.
- Do not claim full WCAG 2.2 AA without a complete manual assessment.

---

## E.5 F-S1-04: Customer Exclusive Booking & Concurrency Protection

---

### E.5.1 F-S1-04 Exclusive Booking Feature SDS (specification.md)

> **Documentation contract only; not implemented, executed or peer-approved yet.** Issue #16; owner @Chxtamos; independent reviewer @Tanaboonnnnn. This Part E records the user's Sprint 1 Booking decision for OD-013 and selects the PostgreSQL transaction design for review.

#### 1. Authority and baseline

Sources: Sprint 1 requirements (FR-S1-10..13, 16, 18..19; BR-S1-01, 07..13, 18..21; NFR-S1-01, 03..08, 11..12; AC-S1-19..29 and AC-S1-35; VC/TEST-S1-16..27, 33, 38, 39), SRS (Q01/Q02/Q05/Q28..Q30, J-03, OD-013), System SDS (§§3.2–3.3, 6, 7.1, 7.3–7.5), Feature Inventory, and the merged #33 Foundation SDS, data contract and BDF STS.

Accepted dependencies: Auth #13, Tutor Slots #14, Customer Availability #15.

**Verified branch point:** `sprint1` at `ea36ef6fd3ea7e2c2582489d1326adbd335452ee`. PR #34 is merged at this commit. It accepts #33 **Part E documentation only**, not a Booking schema/migration SHA. #33 Part F must merge and publish its exact schema SHA before #16 Part F implements Booking-dependent code.

**Ownership:** #33 owns the canonical Booking model, migration, constraints, one `booking_guard_s1()` trigger and runtime-role boundary. #16 owns the Booking API/application transaction adapter and post-merge BDF-23. #15 remains read-only; #17 owns protected Booking retrieval. #16 must not duplicate #33's model, migration or trigger.

#### 2. Outcome and journey

An authenticated Customer requests one selected Slot. The server derives Customer identity from the live Session, actual Tutor and interval from the persisted Slot, revalidates eligibility under the transaction protocol, and commits one `Booked` row. A new Booking is confirmed only after PostgreSQL acknowledges COMMIT.

1. Customer selects an offer in #15; selection is transient UI state, not a reservation.
2. Customer confirms one selected Slot; the request contains only `slotId`.
3. API authenticates a live Customer Session and derives owner from `principal.userId`.
4. Transaction discovers the actual Tutor, acquires all affected User rows in ascending UUID order and then all affected Slot rows in ascending UUID order, locks and revalidates the authenticated Customer's current Session on the same connection, and only then reads/replays or inserts Booking. After a recognized unique/exclusion failure and ROLLBACK, a fresh READ COMMITTED reconciliation revalidates the current User's active Customer role, then the exact Session, before any Booking read.
5. New row is inserted through the shared #33 guard; Q05 is decided using DB `T_elig` after the Slot lock.
6. Only after COMMIT does API return 201. A repeated same-Customer/same-Slot request returns 200 and the original Booking ID without another INSERT.
7. Invalid, occupied, overlapping, too-soon, unauthorized or failed attempts never produce false success or partial Booking.

#### 3. Scope

**In scope:** Customer-only Booking creation; request/response/error contract; trusted owner derivation; canonical #33 data mapping; PostgreSQL SERIALIZABLE and the User → Slot → Booking domain lock order, with the authenticated Customer Session as an auth sub-lock after User/Slot locks and before Booking access; bounded full-transaction retry; Q05 and no-post-guard-

contention proof; natural-key replay; confirmation/pending/conflict/uncertain UI states; planned STS mapped to existing AC/VC IDs.

**Out of scope:** #33 schema/model/migration/trigger implementation; #15 availability reads; #17 protected Booking list/detail; cancellation, reschedule, withdrawal, notices, payment, attendance, `Completed` or S2/S3 behavior; any Idempotency-Key, registry table, payload fingerprint, replay TTL/window column, new Booking column or new natural-key DB constraint.

### 4. Invariants

| Invariant | F-S1-04 contract |
|---|---|
| Ownership | `customerId = principal.userId` from live active Customer Session; never trust client owner/role. |
| User authorization | Booking belongs to the current active User only while `User.isActive=true` and `User.role='Customer'`. After post-ROLLBACK, revalidate the latest User row from the original `principal.userId` before Session or Booking access; missing/inactive → 401, active wrong role → 403, no Booking DTO. |
| Session validity | HTTP `requireSession` is preliminary only. Lock `principal.sessionId` on the SERIALIZABLE mutation connection after User and Slot lock waits; recheck `revokedAt IS NULL` and `expiresAt > clock_timestamp()` before replay/INSERT. After a recognized `23505` / `23P01` ROLLBACK, a fresh READ COMMITTED reconciliation locks/revalidates current User first, then the same Session before any Booking read/200/409; invalid Session returns 401 with no DTO. |
| Tutor / Slot | `currentSlotId` is selected persisted Slot. Tutor derives through `Slot.tutorId`; Booking does not duplicate `tutorId`. |
| Interval | Copy persisted Slot `startsAt` / `endsAt`; never accept either timestamp or duration from client. |
| State | New Sprint 1 Booking status is `Booked`; `Past` is display-only and does not release occupancy. |
| Exclusivity | At most one Active (`Booked`) row per Slot. |
| Customer overlap | No positive-duration overlapping Active Bookings for one Customer across Tutors; half-open `[start,end)` means adjacency is allowed. |
| Q05 | At authoritative DB `T_elig`, `Slot.startsAt - T_elig >= 60 minutes`; exact 60:00 passes, 59:59 fails. |
| Atomicity | No success before COMMIT; rejected/aborted attempt leaves no partial Booking or phantom occupancy. |
| Lifecycle | Sprint 1 Booking is append-only; this feature performs INSERT only. |

### 5. Decision record — OD-013, Sprint 1 Booking only

**USER-APPROVED — 7 November 2026:** use **Natural-key idempotency without an Idempotency-Key**. The existing active Booking pair `(authenticated customerId, slotId)` identifies a repeated request:

- First successful creation: **201 Created** with the committed Booking ID.
- Same authenticated Customer submits the same Slot again after a successful commit: **200 OK** with the **original Booking ID**; do not insert a second row.
- Different Customer attempts a Slot already occupied by another Customer: **409 Conflict**, without disclosing the other Customer or Booking.
- Same Customer requests a different Slot that overlaps an existing Active Booking: **409 Conflict**.
- If the first response is lost or COMMIT outcome is unknown, retry the **same POST with the same** `slotId`. If the original row committed, reconcile it and return its original ID.

The pair is an application-level lookup/reconciliation key, **not** a new persisted key or database unique constraint. No key format, registry table, fingerprint or replay TTL is added. The committed #33 Booking row is the durable source of truth. A matching row qualifies for replay only while its status is `Booked`; future cancellation/rebooking behavior is outside this Sprint 1 contract.

This resolves the **Booking-create portion** of SRS OD-013 for F-S1-04. OD-013 remains open for future S2 reschedule/cancel operations until those features have their own reviewed contracts. The decision is recorded in Issue #16.

**Replay remains valid after later Tutor account changes:** if the same-pair `Booked` row is already committed, an active Customer with a live Session still receives 200 and the original Booking ID even if that Slot's Tutor is subsequently deactivated or changes away from role `Tutor`. Current Tutor `role='Tutor'` / `isActive=true` eligibility is enforced only when attempting a **new INSERT**.

An ineligible Tutor makes a new claim return generic 409 `SLOT_UNAVAILABLE`, without disclosing Tutor identity/status; it does not revoke or hide an existing Booking replay.

### 6. Engineering selections for peer review

- PostgreSQL **SERIALIZABLE** for every Booking mutation attempt.
- Preserve the System SDS **domain** lock order: all affected User rows in ascending UUID order → all affected Slot rows in ascending UUID order → existing Booking rows in ascending UUID order only where needed. After all User and Slot locks, lock only the current Customer `Session` row ( `principal.sessionId` ) as an authentication sub-lock before any Booking read/lock; this does not reverse the domain order. Hold it through COMMIT. No path may lock Session and then request User, Slot or Booking locks. Existing F-S1-02 takes User → Session but creates a new Slot row without acquiring an existing Slot row lock, so it does not invert this row-lock order. A new Booking INSERT has no pre-existing Booking row to lock.
- Retry the whole transaction for SQLSTATE `40001`, `40P01` or ORM-equivalent `P2034`; maximum **three total mutation attempts**, with fresh discovery/locks and fresh `T_elig` on every new INSERT attempt.
- `23505` / `23P01` are not blind mutation retries. Only structured tuples `23505 / booking_one_active_per_slot` and `23P01 / booked_customer_no_overlap` enter reconciliation; unknown/missing/mismatched tuples fail closed as 500 `INTERNAL_ERROR` without Booking reads. After ROLLBACK, a fresh READ COMMITTED connection locks/revalidates current User ( `isActive`, `role='Customer'` ) first, then the exact Session ( `userId`, `revokedAt`, DB-clock `expiresAt` ) before any Booking read. Missing/inactive User → 401; active wrong role → 403; invalid Session → 401; DB validation unavailable → 503. Only a currently active Customer with a live Session may receive 200 original ID for a same-pair committed row, or the cause-specific 409 if no same-pair row exists.
- Revalidate the live Session on the same SERIALIZABLE connection **after all User and Slot lock waits**: lock `principal.sessionId` with `FOR UPDATE`; verify `userId = principal.userId`, `revokedAt IS NULL` and `expiresAt > clock_timestamp()` before replay/INSERT. A revocation committed during either lock wait is observed after the wait or causes `40001` and a fresh transaction; expiry during a wait fails the DB-clock check. Never return 200 replay or 201 from an invalid Session. A missing exact Session row/owner mismatch at the transactional lock returns 401 immediately; only a PostgreSQL `40001` caused by a concurrent row change/stale snapshot is retried. After Customer/Session authorization, same-pair replay is checked before current Tutor eligibility; an inactive/non-Tutor account rejects only a new claim with 409 `SLOT_UNAVAILABLE`.
- Reuse Auth OD-005-C: obtain the stable CSRF token from `GET /api/v1/auth/csrf`, then call `GET /api/v1/auth/me` again and compare the returned `X-NutTiew-Session-Binding` and identity with the initial result; the CSRF response itself contains only `csrfToken` and is not a binding source. If they differ, discard the token and restart bootstrap. Require `X-NutTiew-Expected-Session-Binding` on the Booking POST; a Session switch after the final recheck must fail before mutation as `SESSION_BINDING_MISMATCH` or `CSRF_DENIED`, then reset bootstrap. The UI must discard late responses after its auth/session epoch changes, including a different Session for the same User.
- #33 trigger uses PostgreSQL `clock_timestamp()` after its Slot lock. Application/browser time, HTTP arrival, transaction-start `now()`, #15 `T_view` and commit time are not authoritative. Non-Offered and Q05 trigger rejections have distinct stable SQLSTATE/constraint pairs: `P0B01 / booking_slot_not_offered` and `P0B02 / booking_q05_min_notice` respectively; #33 Part F must implement and publish this dependency.
- BDF-23 must prove no conflict-capable unique/exclusion wait can occur after `T_elig`, or prove the complete transaction aborts/retries with fresh locks and DB time. A stale-time INSERT that commits after an unaccounted post-guard wait fails the design gate.

These are engineering selections pending independent @Tanaboonnnnn review and real-PostgreSQL proof, not executed results or new stakeholder business rules.

### 7. Acceptance and traceability

| Existing criterion | Contract interpretation | Planned STS |
|---|---|---|
| AC-S1-19 | One eligible request commits one `Booked` row with authenticated Customer, actual Slot/Tutor relationship and copied interval. | BOOK-01 |
| AC-S1-20 and AC-S1-21 | Exact 60:00 passes; 59:59 fails at trigger `T_elig`. | BOOK-02/03 |

| Existing criterion | Contract interpretation | Planned STS |
|---|---|---|
| AC-S1-22 | Another Customer cannot claim an occupied Slot; no private owner data is returned. | BOOK-04 |
| AC-S1-23 and AC-S1-24 | Positive same-Customer overlap across Tutors is denied; adjacency is allowed. | BOOK-05/06 |
| AC-S1-25 and AC-S1-26 | Race B (two Customers/one Slot) and Race C (one Customer/two overlapping Tutors) have separate barriers and final-row assertions. | BOOK-10/11 |
| AC-S1-27 / VC-S1-33 | Stale/invalid selection and persistence failure never produce phantom success or inconsistent occupancy. | BOOK-07/08/12/21/26/27 |
| AC-S1-28 | Customer/Tutor identity is derived from Session/Slot, not request fields. | BOOK-09 |
| BR-S1-13 / OD-005-A/B/C | Current active Customer User and Session remain authorized after User/Slot waits and are revalidated again after ROLLBACK before reconciliation; Session-bound CSRF and binding prevent stale-session mutation or late-response disclosure. | BOOK-26..30 |
| AC-S1-29 / VC-S1-38 | Same-pair replay returns 200 and same Booking ID only for a currently active Customer with a live Session; post-ROLLBACK reconciliation returns 401/403 for invalid current User authorization and 401 for revoked/expired Session. Unknown constraint tuples never produce replay. | BOOK-13..16, BOOK-30 |
| AC-S1-35 / VC-S1-39 | Request arriving before cutoff but waiting until after cutoff is rejected by post-lock DB `T_elig`. | BOOK-17/19 |

Related requirements: FR-S1-10..13, 16, 18..19; BR-S1-01, 07..13, 18..21; NFR-S1-01, 03..08, 11..12; Q01/Q02/Q05/Q28/Q29/Q30; VAL-007..011/014/030. Tests are planned / NOT RUN in Part E.

### 8. Definition of Done

**Part E — specification-only PR**

- [ ] Feature SDS, UI, API, data, transaction and STS documents are cross-linked and consistent.
- [ ] User-approved OD-013 Sprint 1 Booking decision is recorded without closing future S2 retry decisions.
- [ ] PostgreSQL SERIALIZABLE, User → Slot → Session(auth sub-lock) → Booking acquisition, bounded whole-transaction retry and Q05 authority are explicit; after post-ROLLBACK, current User authorization is revalidated before Session, and both are revalidated on a fresh READ COMMITTED connection before Booking reads/200/409.
- [ ] Auth CSRF is acquired through the existing endpoint, tied to the current Session binding, and stale responses are ignored after logout/account/session switch.
- [ ] Non-Offered and Q05 trigger failures have distinct, stable #33 SQLSTATE/constraint mappings and separate STS assertions; unique/exclusion reconciliation allowlists only the exact canonical SQLSTATE/constraint pairs and fails closed for unknown constraints.
- [ ] Same-pair `Booked` replay is checked before occupied/Q05 rejection; returns original ID without INSERT.
- [ ] No-post-guard-contention / BDF-23 is a hard proof gate and is not claimed to have passed.
- [ ] AC-S1-19..29/35 and VC/TEST-S1-16..27/33/38/39 are traceable to planned cases.
- [ ] No Prisma schema, migration, API implementation, UI implementation or executable test is added.
- [ ] Markdown links/structure/IDs and `git diff --check` pass.
- [ ] PR targets `sprint1`, links #16, requests @Tanaboonnnnn and stays open for independent human review.

**Part F — separate implementation PR**

Only after Part E acceptance and #33 Part F schema merge: consume exact schema SHA; implement Customer POST/transaction adapter against the one canonical #33 model/guard; TDD authorization/replay/conflict/Q05/Race B/C/rollback; run BDF-23 with real PostgreSQL; record commands, environment, schema/source SHA and actual results; open a separate reviewed code PR into `sprint1`.

**Verification boundary:** Part E is documentation only. No build, migration, application test, API call, browser test or BDF case is claimed as executed.

### E.5.2 F-S1-04 Customer Booking Confirmation UI Specification (ui-spec.md)

> **Part E UI contract only; no component, route or browser test is implemented.** This flow completes the selection hand-off from F-S1-03 Availability; it does not turn selection into a reservation until the server commits.
>
> **2026-11-10 UX Follow-up Cross-Reference (Issue #44, pending peer review):** Customer availability browsing in F-S1-03 and UX Decision 2026-11-10 is proposed to adopt Option A (Date-First Monthly Calendar). All `F-S1-04` confirmation, CSRF + post-CSRF `/auth/me` binding recheck, server `T_elig` revalidation, `201` / `200` natural-key replay, `409` / `422` / `503` handling, `UnknownBookingOutcome` replacement lockout across calendar switches, and privacy rules remain **unchanged**; `#selected-offer-summary` sits as a non-sticky inline card directly after the selected day's time list without obscuring controls or focus ( `WCAG 2.2 SC 2.4.11` ).

#### 1. Screen and shared design system

Screen: ยืนยันการจองช่วงเวลาติว — confirm one selected offer as an authenticated Customer.

Reuse the NutTiew design system shared with Customer Availability and Tutor Dashboard; do not introduce a separate booking palette.

| Token | Booking confirmation use |
|---|---|
| Brand/navigation | Text-only NutTiew wordmark; shared navy `#202B44` |
| Canvas/surface | Light canvas `#F7F8FB` , white surface `#FFFFFF` ; no nested cards |
| Text | Dark ink `#172137` ; muted text must remain contrast-safe |
| Primary action | Orange `#F47736` , dark-ink label/icon `#172137` , border `#D96123` ; never white text on orange |
| Focus | Visible ring `3px solid #AA4519` , `outline-offset: 3px` ; never clipped |
| Typography | Noto Sans Thai, Sarabun, system-ui, sans-serif |
| Spacing/corners | Shared 4/8/12/16/24/32px scale and 8px radius |

Keep Tutor label/reference and Bangkok appointment date/time clear. No fake profile, rating, price, payment, contact, testimonial, message panel, decorative emoji or unrelated content.

#### 2. Journey and content

1. Call `GET /api/v1/auth/me` with the existing HttpOnly Session cookie. Require role `Customer` ; capture the response's `X-NutTiew-Session-Binding` value with the identity.
2. Call `GET /api/v1/auth/csrf` with the same cookie and obtain the stable Session-bound HMAC token. Its current response contains only `csrfToken` ; it does **not** return `X-NutTiew-Session-Binding` , so do not claim to compare a binding from this response. Keep the token in memory only. Then call `GET /api/v1/auth/me` again with the same cookie and compare its returned binding and identity with the first `/auth/me` result. If either changed (for example, Session A changed to Session B between the two GETs), discard the token and captured state and restart identity/CSRF bootstrap. The CSRF read-only GET may omit `Origin` under the Auth contract, but explicit `Sec-Fetch-Site: cross-site` is rejected. If the cookie changes after this final `/auth/me` check but before POST, the captured expected binding and Session-bound CSRF token remain the final server-side guard: `SESSION_BINDING_MISMATCH` or `CSRF_DENIED` must reject before mutation; clear identity/CSRF state and restart bootstrap.
3. Customer selects a Slot in #15. Selection is transient state, **not** a Booking.
4. Confirmation summary shows only Tutor display name if #15's data gate permits it (otherwise opaque Tutor reference), Bangkok date and 24-hour start/end.
5. Primary action: ยืนยันการจอง. Send only `slotId` in JSON, plus `X-CSRF-Token` and the captured `X-NutTiew-Expected-Session-Binding` ; apply the existing canonical Origin/Referer and Fetch Metadata rules. Never send `customerId` , `tutorId` , Booking ID, status, interval or cutoff time.

6. Capture the current in-memory auth/session epoch, binding and `slotId` when POST starts. Apply a response only if all still match the current auth context; otherwise discard it without displaying the old Booking ID or details.
7. Show confirmed state only after valid 201 or natural-key replay 200 for the still-current Session.
8. Do not add a private Booking list/detail route; #17 owns protected retrieval.

The Session binding is a non-credential response/request consistency value, not authorization and not a replacement for the HttpOnly cookie or CSRF token.

### 3. UI states

| State | Trigger | Required behavior |
|---|---|---|
| Session loading | `/auth/me` pending | Hide private selection details; show progress |
| CSRF loading | `/auth/csrf` pending for the captured Session binding | Keep confirmation disabled; retain token only in memory |
| CSRF/session mismatch | Binding changes between `/auth/me` and `/auth/csrf` or POST returns `SESSION_BINDING_MISMATCH` | Discard token/selection tied to old binding; refresh identity and CSRF before a new confirmation |
| Signed out | `/auth/me` returns 401 | Clear selection/pending state; show Auth |
| Wrong role | Principal is not Customer | Deny flow; do not submit |
| Ready | Customer verified and #15 offer selected | Show summary and one enabled confirm action |
| Submitting | POST in flight | Disable repeated activation; show progress; retain exact `slotId` |
| New success | 201 after COMMIT | Show "จองสำเร็จ"; display returned Booking ID and confirmed time |
| Replay success | 200 same-pair replay | Show same Booking ID and indicate booking already exists; no new local item |
| Conflict | 409 occupied Slot / non-Offered Slot / Customer overlap | No success; explain selected time is unavailable; refresh #15 |
| Not eligible | 422 Q05 minimum-notice cutoff (59:59 or less) | No success; explain offer can no longer be booked; refresh |
| Unknown outcome | Network loss, timeout or `503 BOOKING_OUTCOME_UNKNOWN` | Do not assert success/failure; preserve same `slotId`; offer ส่งคำขอเดิมอีกครั้ง |
| Service unavailable | 503 known no-commit result | Safe error; retain selection for explicit retry |
| Session changed | Logout, login, account switch, or Session A → Session B (including two Sessions for the same User) | Increment auth/session epoch; clear private summary, selected Slot, pending intent, CSRF token and binding; ignore any late response whose captured epoch/binding differs. Never render its Booking ID/details in the new Session. |

### 4. Natural-key retry interaction

- Pending intent is current authenticated Customer plus selected `slotId`; no Idempotency-Key is generated or stored.
- After network failure or ambiguous COMMIT, retry the **same POST body**. Do not silently substitute a newly selected Slot.
- While outcome is unknown, do not offer a different Slot as a replacement for the unresolved intent. First retry/reconcile the original request.
- Same-pair existing `Booked` row returns 200 and original Booking ID; never generate a new ID locally.
- A different Slot is a distinct request and must pass all normal eligibility/overlap rules.
- If page closes and in-memory selection is lost, this contract does not invent a client key or server registry. Once #17's protected own-Booking read is integrated, it provides the normal post-refresh recovery view; #16 alone does not claim cross-reload recovery.
- Clearing UI state on logout/account switch is a privacy boundary, not proof that an already-sent request rolled back. If the old request committed before logout, the commit is not undone; its late response is still discarded after the auth/session epoch

changes. If a stale binding from Session A is sent with Session B's cookie, the API rejects it before mutation.

### 5. Accessibility and interaction

- Semantic heading, visible text labels and native buttons for confirm/retry.
- Keyboard operation, logical Tab order and visible unobscured focus.
- Selected/pending/success/error states are communicated in text/programmatic status, not color alone.
- Announce submitting, confirmed, replayed, conflict and unknown outcome with a polite live region.
- Button disabling is usability feedback, never the concurrency guard.
- NFR-S1-09 remains a proposed usability target. This Part E does **not** claim WCAG 2.2 AA, 44px target-size or rendered contrast conformance; record actual evidence in Part F.

### 6. Privacy and acceptance mapping

Never render Customer ID/email/phone, Session/CSRF data, credentials, another Customer's Booking or private Tutor fields. Conflict messages must not reveal who occupies a Slot. Do not store credentials, Session tokens or CSRF tokens in browser storage.

| Criterion | UI obligation |
|---|---|
| AC-S1-19/20/21 | Confirm only from server's committed/eligibility outcome |
| AC-S1-22/23/24 | Safe conflict/adjacency outcome; no third-party disclosure |
| AC-S1-25 and AC-S1-26 | Truthful under concurrent outcomes; disabled button is not race safety |
| AC-S1-27 / VC/TEST-S1-33 | No phantom success after stale selection or persistence failure |
| AC-S1-28 | No owner/Tutor fields sent from client |
| AC-S1-29 / VC-S1-38 | Same-Slot retry reconciles to original Booking ID |
| AC-S1-35 / VC-S1-39 | Pre-cutoff click cannot override post-wait Q05 rejection |

---

## E.5.3 F-S1-04 Customer Booking HTTP/API Contract (api-spec.md)

> **Proposed API contract for independent review; not implemented or runtime-tested.** See Feature SDS, UI, data, transaction protocol, STS, and the accepted Auth API contract.

### 1. Transport and authorization

- Same-origin JSON under existing Express `/api/v1`; reuse live-session middleware, request ID, safe error envelope and `Cache-Control: no-store`.
- Require a live active Session and `requireRole('Customer')`. Derive `customerId` only from `principal.userId`; derive actual Tutor/interval from PostgreSQL.
- The HTTP `requireSession`/role check is preliminary, not sufficient for reconciliation: the SERIALIZABLE mutation locks/revalidates Customer and Tutor Users, then the exact `principal.sessionId` after all User/Slot waits. If a recognized `23505` / `23P01` causes ROLLBACK, fresh READ COMMITTED reconciliation must lock/revalidate the current User (`isActive` and `role='Customer'`) first, then the exact Session (`userId`, `revokedAt`, DB-clock `expiresAt`), before any Booking read/200 or business 409. Missing/inactive User → 401; active non-Customer → 403; invalid Session → 401; see transaction contract.
- Reuse Auth OD-005-C without a new CSRF scheme: obtain the stable token from `GET /api/v1/auth/csrf` using the same HttpOnly cookie; require `X-CSRF-Token` on POST. The CSRF token is valid only for the Session that issued it.
- Require `X-NutTiew-Expected-Session-Binding`, captured from `X-NutTiew-Session-Binding` on `GET /api/v1/auth/me`. It must match the current `sessionBinding(userId, sessionId)`; missing or mismatched binding returns 403 `SESSION_BINDING_MISMATCH` before mutation. This is a consistency guard, not an authentication credential.
- Unsafe POST applies the Auth canonical Origin/Referer rules and rejects explicit `Sec-Fetch-Site: cross-site`; no credentialed cross-origin CORS. The read-only `GET /api/v1/auth/csrf` may omit Origin but rejects explicit cross-site Fetch Metadata, as defined by Auth #13.

- JSON UTF-8; maximum body 4 KiB; strict key allowlist; no query parameters.
- Client must not submit `customerId`, `tutorId`, role, Booking ID, status, `startsAt`, `endsAt`, duration or `T_elig`.
- No `Idempotency-Key` is required or interpreted. Replay uses authenticated `(customerId, slotId)`.
- Browser sends the existing HttpOnly Session cookie automatically; CSRF token is held in memory only, never in JSON or persistent browser storage.

### 2. Endpoint

| Method/path | Request | Success | Enforcement |
|---|---|---|---|
| `POST /api/v1/customer/bookings` | Exactly `{"slotId":"<UUID>"}`; `X-CSRF-Token` and `X-NutTiew-Expected-Session-Binding` headers; no query parameters | 201 new committed Booking; 200 same-pair replay | Customer Session/role, Origin/CSRF/binding, User → Slot → Session locks, SERIALIZABLE, shared #33 guard and constraints |

No GET/detail/list route is defined here. Protected Booking reads belong to #17; Customer Availability remains #15.

#### Request

```
POST /api/v1/customer/bookings
Origin: http://localhost:5173
Content-Type: application/json
Cookie: nuttiew_session_dev=<opaque>
X-CSRF-Token: <session-bound>
X-NutTiew-Expected-Session-Binding: <value-from-auth-me>

{"slotId":"c62bfb8b-2530-4a7c-979c-a9a6d16be0df"}
```

`slotId` must be a valid UUID. Unknown JSON keys, missing/null `slotId`, malformed JSON, oversized body or query parameters return 400 `INVALID_INPUT` (or existing shared 413 body-limit response). No owner or appointment interval is accepted from caller.

### 3. Success response

#### New Booking — 201 Created, only after COMMIT acknowledgement

```
{
  "data": {
    "id": "9b4d0c3f-0d4f-4c3a-a18d-8b4c9a6d52e1",
    "slotId": "c62bfb8b-2530-4a7c-979c-a9a6d16be0df",
    "startsAt": "2026-11-08T06:00:00.000Z",
    "endsAt": "2026-11-08T07:00:00.000Z",
    "status": "Booked"
  },
  "meta": {"requestId":"opaque-request-id"}
}
```

#### Natural-key replay — 200 OK, original Booking ID

Same DTO and same `id` as previously committed Booking; no new INSERT or Booking ID.

```
{
  "data": {
    "id": "9b4d0c3f-0d4f-4c3a-a18d-8b4c9a6d52e1",
    "slotId": "c62bfb8b-2530-4a7c-979c-a9a6d16be0df",
    "startsAt": "2026-11-08T06:00:00.000Z",
    "endsAt": "2026-11-08T07:00:00.000Z",
    "status": "Booked"
  },
  "meta": {"requestId":"new-request-id"}
}
```

Exact DTO allowlist: Booking `id`, `slotId`, UTC `startsAt`, UTC `endsAt`, business `status` and opaque request ID. Exclude `customerId`, `tutorId`, profiles, Session/CSRF fields, SQL metadata and arbitrary ORM columns. Tutor derives through Slot; #17 owns richer protected reads.

All success/error responses set `Cache-Control: no-store`. Timestamps are UTC RFC 3339 with exactly three fractional digits and `Z`; UI formats them as Asia/Bangkok. The authenticated response must not include Session/CSRF values or owner IDs. The client applies a result only if its captured auth/session epoch and binding still match; a late response is ignored after logout or Session/account switch.

### 4. Safe error contract

| Condition | HTTP / code | Required state |
|---|---|---|
| Missing, expired, revoked Session, exact transactional Session row absent/owner-mismatched after the HTTP guard, or missing/inactive User (including during post-ROLLBACK revalidation) | 401 `UNAUTHENTICATED` | No mutation/private data/Booking DTO; do not read/replay Booking data |
| Authenticated active User whose current role is not Customer (including during post-ROLLBACK revalidation) | 403 `FORBIDDEN` | No mutation/private data/Booking DTO |
| Invalid/missing/extra request field, malformed UUID/JSON, oversized body, query parameter | 400 `INVALID_INPUT` (or shared 413) | No mutation |
| Missing Slot | 404 `SLOT_NOT_FOUND` | No Booking/private information |
| Slot occupied by another Customer, Slot lifecycle is not `Offered`, or the current Tutor is inactive/no longer role `Tutor` for a **new claim** | 409 `SLOT_UNAVAILABLE` | Existing row preserved; no new Booking; no owner/Tutor-status disclosure |
| Customer has a different overlapping Active Booking | 409 `CUSTOMER_OVERLAP` | No conflicting row |
| Q05 fails at DB `T_elig` (59:59 or less) | 422 `BOOKING_NOT_ELIGIBLE` | No Booking/occupancy |
| Invalid/foreign Origin, explicit `Sec-Fetch-Site: cross-site`, missing/wrong/old-Session CSRF | 403 `ORIGIN_DENIED` / `CSRF_DENIED` | No mutation |
| Missing or mismatched `X-NutTiew-Expected-Session-Binding` | 403 `SESSION_BINDING_MISMATCH` | No mutation; refresh identity and CSRF bootstrap |
| Serialization/deadlock retry budget exhausted | 503 `TRANSACTION_RETRY_EXHAUSTED` | All attempts rolled back |
| DB unavailable before mutation, during known rollback handling or during fresh User/Session reconciliation | 503 `SERVICE_UNAVAILABLE` | No false success; never skip live-Session validation |
| COMMIT acknowledgement lost / outcome unknown | 503 `BOOKING_OUTCOME_UNKNOWN` if possible; otherwise network failure | Do not claim rollback/success; retry same POST/ `slotId` |
| Unexpected internal failure | 500 `INTERNAL_ERROR` | No raw SQL/stack/secrets |

Tutor eligibility is checked only for a new INSERT, after active Customer/live-Session authorization and the exact same-pair replay lookup. A previously committed same-pair `Booked` row still returns 200 with its original ID if the Tutor was later deactivated or changed role; current Tutor ineligibility must not invalidate that replay. For a new claim, an inactive or non-`Tutor` account maps to the generic 409 `SLOT_UNAVAILABLE` without disclosing Tutor identity or account state.

#33 Part F must emit these stable trigger diagnostics so #16 can map by cause without guessing or exposing raw DB errors:

| #33 Part F INSERT guard cause | Required PostgreSQL diagnostic | #16 HTTP mapping |
|---|---|---|
| Slot lifecycle is not `Offered` | Custom SQLSTATE `P0B01`; constraint diagnostic `booking_slot_not_offered` | 409 `SLOT_UNAVAILABLE` |
| Q05 minimum-notice check fails at `T_elig` | Custom SQLSTATE `P0B02`; constraint diagnostic `booking_q05_min_notice` | 422 `BOOKING_NOT_ELIGIBLE` |

The SQLSTATEs are stable application-facing trigger contracts (valid five-character custom codes); the diagnostic constraint names are stable identifiers, not raw exception text. #33 owns their implementation. Unknown/unmapped trigger errors fail closed as 500

`INTERNAL_ERROR` and are never guessed to be Q05. BDF-D11's `0A000` remains reserved for forbidden UPDATE/DELETE/TRUNCATE, not INSERT eligibility.

Only these structured SQLSTATE/constraint pairs may enter the unique/exclusion reconciliation path; inspect driver metadata (`code` and `constraint` / `constraint_name`), never parse error text:

| Exact PostgreSQL tuple | Meaning / mapping when no same-pair replay exists |
|---|---|
| `23505 / booking_one_active_per_slot` | 409 `SLOT_UNAVAILABLE` |
| `23P01 / booked_customer_no_overlap` | 409 `CUSTOMER_OVERLAP` |

Any missing, unknown or mismatched tuple (including another `23505`, such as a Booking primary-key violation) rolls back and fails closed as 500 `INTERNAL_ERROR`; it must not enter reconciliation, return 200 or be guessed to be a business conflict. These exact identifiers are owned by #33 Part F and must match its canonical schema.

For a recognized tuple only, ROLLBACK and discard the failed SERIALIZABLE snapshot. On a fresh connection, begin a separate `READ COMMITTED` reconciliation transaction. First lock the current `User` row for `principal.userId` with `FOR UPDATE` and revalidate its latest committed state: missing/inactive → 401 `UNAUTHENTICATED`; active but current role is not Customer → 403 `FORBIDDEN`. Do not read Session or Booking data on either failure. Then lock the exact `Session` row for `principal.sessionId` and `principal.userId` with `FOR UPDATE`, and check `revokedAt IS NULL AND expiresAt > clock_timestamp()`; missing, mismatched, revoked or expired Session → 401 `UNAUTHENTICATED`. Only an active Customer with a live Session may perform one exact-pair `Booked` read: a committed same-pair row with matching interval returns 200 and its original ID; otherwise return the safe 409 mapped from the allowlisted original tuple above. The reconciliation transaction takes no Slot or Booking row locks and performs no mutation. If User/Session DB validation is unavailable, return 503 and fail closed. Do not spin on a genuine conflict.

#### 5. Boundary and review gate

Only this POST is introduced. No Booking GET/list/detail, cancellation, reschedule, deletion or Slot mutation route is added. Peer review endpoint path, request allowlist, 201/200 replay semantics, cause-specific 409/422 mapping, allowlisted SQLSTATE/constraint reconciliation, in-transaction and post-ROLLBACK User/Session revalidation, Auth CSRF/session-binding reuse, DTO privacy, timestamp format and exact #33 trigger diagnostic dependency. All API cases remain PLANNED / NOT RUN in Part E.

---

### E.5.4 F-S1-04 Booking Data Contract (data-spec.md)

> **Consumes #33's shared contract; does not define or implement a second schema.** No Prisma model, SQL migration, trigger, index or database test is added by Issue #16 Part E.

#### 1. Canonical source and ownership

Canonical Booking fields, relations and integrity decisions are owned by #33 Foundation SDS, data specification and BDF STS, merged by PR #34 at `ea36ef6fd3ea7e2c2582489d1326adbd335452ee`.

That is a documentation merge, **not** a future schema/migration SHA. #16 Part F waits for #33 Part F to merge and records its exact schema SHA before implementing Booking-dependent code/tests.

#### 2. Canonical Booking mapping

| Field | Canonical type/source | #16 write rule |
|---|---|---|
| `id` | Server/database-generated UUID PK | Never accept from request; return only after COMMIT or same-pair replay |
| `customerId` | UUID FK to `User.id` | Live authenticated Customer `principal.userId` |
| `currentSlotId` | UUID FK to `Slot.id` | Validated request `slotId` |
| `startsAt` / `endsAt` | `TIMESTAMPTZ(6)` | Copy persisted Slot interval; never client input |

| Field | Canonical type/source | #16 write rule |
|---|---|---|
| `status` | Text: `Booked` / `Cancelled` | New Sprint 1 row always `Booked` |
| `createdAt` / `updatedAt` | `TIMESTAMPTZ(6)` metadata | Not an eligibility clock |

There is **no Booking `tutorId` field**. Current Tutor derives from `Slot.tutorId` through `currentSlotId`. Composite Slot-window FK enforces that copied Booking interval matches the immutable Slot.

### 3. Database invariants consumed

#33 Part F owns and must implement BDF-D01..D12:

- Required Customer/Slot references, restrictive parent delete/update behavior and positive interval.
- Supported `Booked` / `Cancelled` status; only `Booked` occupies/conflicts.
- Composite Slot-window FK matching `currentSlotId`, `startsAt`, `endsAt`.
- Partial unique `booking_one_active_per_slot` for one Active Booking per Slot.
- GiST exclusion `booked_customer_no_overlap` for positive-duration same-Customer Active interval overlap across Tutors; half-open adjacency is allowed.
- One shared `booking_guard_s1()` row-level `BEFORE INSERT OR UPDATE OR DELETE` trigger and statement-level `BEFORE TRUNCATE` trigger, plus runtime-role boundary.
- Sprint 1 append-only lifecycle. #16 performs INSERT only; no UPDATE/DELETE/TRUNCATE operation exists in this feature.

#16 must not duplicate model, trigger, migration, occupancy field or Tutor reference.

### 4. Natural-key replay mapping — no schema addition

Application lookup pair:

```
(authenticated principal.userId, requested slotId)
```

Exact replay predicate:

```
customerId = principal.userId
AND currentSlotId = slotId
AND status = 'Booked'
```

Rules:

1. Query this pair only after the transaction has acquired ordered User and Slot locks, locked/revalidated the current Customer Session, and rechecked Session validity after the final lock wait.
2. Check it **before** occupied-Slot rejection and before a new-booking Q05 check. A matching committed `Booked` row is already successful: return 200 and original ID without INSERT or new `T_elig`.
3. The pair is not a new composite UNIQUE constraint, column, Idempotency-Key, registry, fingerprint or TTL.
4. Only `Booked` qualifies. A future `Cancelled` row is not a replay; S2 rebooking semantics need their own contract.
5. If no matching row exists, apply Slot occupancy, Customer overlap and guarded INSERT checks. Another Customer's occupied Slot or a different overlapping Slot for this Customer is a conflict.
6. Only the exact structured tuples `23505 / booking_one_active_per_slot` and `23P01 / booked_customer_no_overlap` are recognized as Booking business conflicts. Capture SQLSTATE and constraint metadata; never parse error text. Any unknown/missing/mismatched tuple (including a different `23505`) rolls back and returns safe 500 `INTERNAL_ERROR` without entering replay reconciliation.
7. For a recognized tuple, ROLLBACK and discard the failed snapshot; on a fresh connection begin a READ COMMITTED reconciliation transaction. Lock the current User row for the original `principal.userId` first and revalidate latest `isActive`/role: missing or inactive → 401; active but no longer Customer → 403. Only then lock the exact authenticated Session (`principal.sessionId` + `principal.userId`) with `FOR UPDATE` and check `revokedAt IS NULL` and `expiresAt >`

`clock_timestamp()` ; missing/revoked/expired → 401. Do not read Session/Booking after failed User authorization, or Booking after failed Session authorization.

8. Only an active Customer with a live Session may read the exact pair: return 200 for a committed same-pair `Booked` row with matching interval; otherwise return safe 409 mapped only from the recognized original tuple ( `SLOT_UNAVAILABLE` for `23505 / booking_one_active_per_slot` ; `CUSTOMER_OVERLAP` for `23P01 / booked_customer_no_overlap` ). This fresh transaction takes no Slot/Booking row locks and performs no mutation. If User/Session validation is unavailable, return 503 and fail closed.

The existing Booking row is the only durable replay record; retrying same request creates no duplicate active row/history.

#### 5. Read/write and privacy boundary

- F-S1-04 creates a Booking only. #15 availability remains read-only; #17 owns protected Customer list/detail and Tutor schedule Booking reads.
- Do not add `Slot.isBooked` , duplicate Tutor identity, Booking registry or second occupancy source.
- Create DTO contains only Booking ID, Slot ID, copied UTC interval, `Booked` status and request ID. Exclude Customer/Tutor IDs, profiles, contacts, credentials, Session/CSRF values and arbitrary ORM fields.
- Reuse only existing Auth fields for post-rollback revalidation: `User.id` , `User.role` , `User.isActive` , then `Session.id` , `Session.userId` , `Session.revokedAt` and `Session.expiresAt` . Read/lock the User before Session on the fresh READ COMMITTED connection. No User/Session column, Booking field, migration or second authentication schema is added by #16 Part E.
- Conflict responses must not reveal identity or Booking ID of Customer occupying a Slot.
- No retention/deletion behavior is added; BDF-D12 append-only/runtime-role rules apply.

#### 6. Verification boundary

BDF-01..26 remain planned in merged #33 Part E. #33 Part F must run pre-merge BDF-01..22 and BDF-24..26. #16 Part F runs BDF-23 only after exact #33 schema SHA is merged. The exact unique/exclusion constraint identifiers above must be verified against #33 Part F before implementation; a mismatch blocks this adapter rather than widening the allowlist. No Booking schema, query, migration or database result is claimed here.

---

### E.5.5 F-S1-04 PostgreSQL Booking Transaction, Lock & Retry Contract (transaction-spec.md)

> **Selected engineering design for peer review.** Application transaction contract only, not a migration or SQL implementation. #16 owns this adapter; #33 owns the canonical Booking model and single DB guard. Align with System SDS §§7.1/7.3–7.5, BDF-D11/D12 and BDF-23.

#### 1. Selected transaction mechanism

- PostgreSQL **SERIALIZABLE** for each Booking mutation attempt.
- One attempt uses one checked-out PostgreSQL connection (F-S1-02 uses one `pg.PoolClient` for atomic mutation). Do not mix a Prisma transaction and independent `pg` connection and call them one transaction.
- Begin each attempt with `BEGIN ISOLATION LEVEL SERIALIZABLE` ; all locks, reads and INSERT use that same connection.
- Explicit row locks follow System SDS global order. Unique/exclusion constraints and #33 trigger are mandatory backstops, not replacements for application locks.
- Commit before returning 201. Rollback, conflict, retry exhaustion or ambiguous COMMIT must never be represented as confirmed new Booking.

#### 2. Lock-set discovery and global order

The selected Slot's actual Tutor ID determines the full User lock set. First perform an **unlocked, read-only discovery query** for selected Slot `id` and `tutorId` . This is not authorization, a booking check or source of interval values. Missing Slot → safe 404.

For every attempt, acquire locks in this exact order:

| Order | Rows | New Booking operation |
|---|---|---|
| 1 | Affected `User` rows, ascending UUID | Authenticated Customer and selected Slot's actual Tutor; deduplicate IDs |
| 2 | Affected `Slot` rows, ascending UUID | Selected Slot |
| 3 | Current Customer `Session` row | `principal.sessionId`, matched to `principal.userId`; lock only this authenticated Session after **all** User and Slot waits and before any Booking read/lock |
| 4 | Existing `Booking` rows, ascending UUID | No existing Booking is mutated by this INSERT-only operation. Read conflict predicates after User/Slot/Session checks; no nonexistent Booking row can be locked. |

The System SDS **domain** lock hierarchy remains User → Slot → Booking. The current Customer Session row is a subordinate authentication lock after the User and Slot phases but before any Booking access; it does not reverse the domain order. No transaction may lock Session and then request a User, Slot or Booking lock. The existing logout path updates only its Session row and does not acquire User/Slot locks: if logout commits while Booking is waiting for either User or Slot, the later Session lock/revalidation observes revocation or the stale SERIALIZABLE attempt aborts and retries with a fresh snapshot. If Booking obtains the Session lock first, logout waits and is serialized after the Booking transaction. Hold the Session lock through COMMIT/ROLLBACK.

Post-rollback reconciliation is a separate non-mutating authorization/read transaction: it locks the current User row first, then the exact current Session row, and then performs a plain MVCC Booking read (no Booking row lock). It acquires no Slot or Booking row locks. The User → Session → Booking-read sequence preserves the User-before-Session order and cannot invert the User → Slot → Booking domain lock hierarchy. It must never initiate another Booking mutation.

Use deterministic ordered locking or explicit per-ID locks whose acquisition order is verified; do not rely on incidental query-plan order. After User locks, immediately revalidate Customer `role='Customer'` / `isActive=true`. For the selected Tutor, retain the current locked User state but defer the `role='Tutor'` / `isActive=true` eligibility decision until after Session revalidation and the exact-pair replay lookup. A committed same-pair replay belongs to an existing Booking and must remain available to an active Customer with a live Session even if the Tutor was subsequently deactivated or changed role. Only when no qualifying replay exists may an ineligible current Tutor reject a new claim with safe 409 `SLOT_UNAVAILABLE`, without disclosing Tutor/User status. If the lock set/assignment differs, abort and restart from fresh discovery; never add an earlier-order User or Slot lock while holding a later-order Session/Booking lock.

The Session is an existing Auth record, not a Booking data addition. The principal and `sessionId` come from the HTTP guard; never accept either from the request body. The locked Slot row, not discovery pre-read or client data, supplies interval and Tutor association.

### 3. Ordered transaction algorithm

1. **HTTP boundary:** require live Session, active Customer role, allowed Origin, Session-bound CSRF and a matching `X-NutTiew-Expected-Session-Binding`. This is preliminary authentication; it does not replace transactional revalidation. Strictly parse one UUID `slotId`; reject extra body keys/query parameters.
2. **Discovery:** read selected Slot ID/Tutor ID without locks only to discover the User lock set. Missing Slot → 404.
3. **Begin:** check out one DB connection and start a fresh SERIALIZABLE transaction.
4. **Lock Users:** lock Customer and actual Tutor User rows in ascending UUID order. Immediately revalidate Customer `role='Customer'` / `isActive=true`. Retain the selected Tutor's locked current `role` / `isActive` state, but do not reject on Tutor eligibility yet; defer that decision until after Session validation and the same-pair replay lookup in steps 6–8.
5. **Lock Slot:** lock the selected Slot row; re-read/compare Tutor ID, lifecycle and interval. Persisted locked state is authoritative.
6. **Lock current Session after the relevant waits:** on the same connection, lock `principal.sessionId` with `SELECT ... FROM "Session" WHERE id = principal.sessionId AND userId = principal.userId FOR UPDATE`. Do this only after all affected User and Slot locks have been acquired. If this exact lookup returns no row (including an owner mismatch), ROLLBACK and return 401 `UNAUTHENTICATED` immediately; do not read Booking data and do not classify absence as a retryable abort. If PostgreSQL instead raises SQLSTATE `40001` because a concurrent Session update/delete or stale SERIALIZABLE snapshot invalidated the

row operation, ROLLBACK and retry the whole transaction under §6.1; the fresh attempt must re-read the Session and return 401 if it is now absent. Never continue using the HTTP middleware's earlier Session snapshot.

7. **Revalidate Session with DB time:** after the Session row lock is acquired, execute a fresh same-connection check requiring `revokedAt IS NULL AND expiresAt > clock_timestamp()`. If no live matching row exists, ROLLBACK and return 401 `UNAUTHENTICATED`; do not read/replay Booking data. This catches revocation during User/Slot waits and expiry during any preceding wait. Keep the Session lock through transaction end so a concurrent logout is serialized before or after the Booking, never halfway through its authorization decision.
8. **Natural-key replay first:** query `Booking` for exact `(customerId=principal.userId, currentSlotId=slotId, status='Booked')`. If found and interval matches locked Slot, COMMIT the read-only transaction and return 200 with that Booking ID, even if the locked Tutor is now inactive or no longer has role `Tutor`. Do this **before** new-claim Tutor eligibility rejection, occupied-Slot rejection and new-booking Q05. This exception applies only to the already committed same-pair Booking; it does not authorize a new INSERT for an ineligible Tutor.
9. **New-claim Tutor eligibility:** only if step 8 found no same-pair replay, require the selected Tutor's current locked User row to have `role='Tutor'` and `isActive=true`. If the Tutor is inactive or has another role, ROLLBACK and return generic 409 `SLOT_UNAVAILABLE`; do not disclose Tutor identity/status and do not create a Booking. This check never invalidates an existing same-pair replay.
10. **New-claim conflicts:** if any other `Booked` row occupies Slot, return 409 `SLOT_UNAVAILABLE`. If Customer has a different `Booked` interval with positive overlap (`existing.startsAt < slot.endsAt AND slot.startsAt < existing.endsAt`), return 409 `CUSTOMER_OVERLAP`. Exact adjacency is allowed.
11. **Guarded INSERT:** insert one row with server/DB-generated ID, authenticated Customer ID, locked Slot ID, persisted Slot interval and status `Booked`. #33 `booking_guard_s1()` locks/re-reads Slot (already held), then samples DB `clock_timestamp()` as authoritative `T_elig`; enforce `startsAt - T_elig >= interval '60 minutes'`. Exact 60:00 passes; 59:59 fails. Do not substitute application time, PostgreSQL transaction-start `now()`, HTTP arrival, #15 `T_view` or commit time.
12. **Commit:** COMMIT on the same connection. Return 201 with persisted Booking ID only after COMMIT acknowledgement.
13. **Release:** on error, ROLLBACK when connection is usable, release it and classify per §6. No external side effect runs inside transaction.

Same-pair replay is checked only after Customer authorization, live Session revalidation and all relevant User/Slot lock waits. It returns the original committed record before current Tutor eligibility is applied to a new claim, before occupied-Slot rejection and before new-booking Q05; it does not INSERT and does not need new `T_elig`. Every new INSERT must pass current Tutor eligibility and the DB trigger.

### 4. Natural-key replay and uncertain COMMIT

Only replay identity:

```
(authenticated customerId, slotId)
```

| Situation | Result |
|---|---|
| Valid new request commits | 201 with new Booking ID |
| Same Customer repeats same Slot after prior commit | 200 with exact original Booking ID; no INSERT |
| Different Customer submits occupied Slot | 409 `SLOT_UNAVAILABLE`; do not reveal owner |
| Same Customer submits a different overlapping Slot | 409 `CUSTOMER_OVERLAP` |
| Same Customer submits a different non-overlapping Slot | Distinct request; evaluate normal eligibility |
| Existing same-pair row is `Cancelled` | Not a Sprint 1 replay; future rebooking behavior is outside this contract |

A broken connection/timeout around COMMIT does not prove rollback. Server must not claim 201 or silently start a second mutation in the same request. If possible, return 503 `BOOKING_OUTCOME_UNKNOWN`; otherwise client sees network failure. Client retries exact same POST body. A fresh transaction returns 200 if original row committed, or creates one row if it did not. No key registry or TTL is required.

**SERIALIZABLE snapshot caveat:** a concurrent request may take its snapshot before waiting on Customer/Slot lock; lock release does not refresh that snapshot. It may not see the first transaction's newly committed row and PostgreSQL may instead raise 40001 or a unique/exclusion conflict. Do not assume post-lock SELECT sees a newer snapshot. Full mutation retry and post-rollback exact-pair reconciliation in §6 must return 200 for the same pair only after fresh DB active-Customer User and live-Session checks. If that Session was revoked or expired before reconciliation, return 401 with no Booking DTO; never create another row or report a permanent conflict for a valid same-pair commit.

### 5. Race and Q05 safety / no-post-guard-contention proof

#### Race B — two Customers, one Slot

Both attempts lock their own Customer and the same Slot before conflict checks/INSERT. Slot lock serializes compliant API writers. After winner commits, loser sees occupied state on a fresh attempt or loses to unique constraint; at most one active row can commit.

#### Race C — one Customer, two Tutors

Both attempts include same Customer User row in affected User lock set, even though selected Tutors/Slots differ. UUID-sorted User locking serializes Customer's Booking writes before guarded INSERT. GiST exclusion remains final DB backstop; no positive-duration overlapping active rows may commit. Adjacency remains allowed.

#### Q05 — post-contention eligibility

Application acquires known conflict-serialization User/Slot locks before guarded INSERT. #33 trigger's Slot `FOR UPDATE` must re-lock a row already held, so it creates no new Slot wait after `T_elig`. Only trigger-side DB `clock_timestamp()` after that lock is authoritative. A request received at 13:59:59 that waits until 14:00:01 for a 15:00 Slot must fail; a valid 60:00 guard may still commit later.

#### Mandatory no-post-guard-contention proof

Unique active-Slot index and same-Customer GiST exclusion may wait on another transaction after the BEFORE INSERT trigger has sampled `T_elig`. Normal API lock protocol is intended to make every compliant conflicting writer acquire same Customer and/or Slot lock before guarded INSERT: Race B shares Slot; Race C shares Customer; all affected User rows precede Slot rows.

This intent is **not proof** against direct SQL or a writer bypassing the application protocol. BDF-23 must use independent PostgreSQL sessions, backend PIDs, `pg_blocking_pids`, trigger-observed `T_elig`, constraint outcomes and final committed rows. Force an unexpected unique/exclusion index wait after preliminary validation and establish one of:

1. Prove no conflict-capable wait can occur after `T_elig` under actual #33 trigger/role/writer arrangement; or
2. Demonstrate complete transaction aborts before it can commit a stale-time INSERT, then restarts with all locks reacquired and fresh DB `T_elig`.

If a forced post-guard wait can resolve and allow an INSERT to commit using stale `T_elig`, BDF-23 fails. Do not treat SERIALIZABLE alone, application pre-check, random `Promise.all()`, timeout-only test or blanket commit-time cutoff as proof. If neither outcome is demonstrated, #16 Part F is blocked and #33/#16 lock/guard contract must be revised through review.

### 6. Retry, conflict and failure classification

#### 6.1 Full transaction retry

Retry known aborts only: SQLSTATE `40001` (serialization), `40P01` (deadlock), ORM equivalent `P2034` if surfaced, or changed/missing **User/Slot lock-set member** between discovery and locked re-read after abort. An exact transactional Session lookup that returns no row or an owner mismatch is a terminal 401, not a retry condition. A concurrent Session change that PostgreSQL reports as `40001` remains retryable; the fresh attempt must re-read and return 401 if the Session is then absent.

Policy: maximum **three total mutation attempts**, including first. Each retry starts a new transaction/snapshot, rediscovers Slot's actual Tutor, reacquires all locks in order and reruns checks. Every retry reaching a new INSERT invokes trigger and samples fresh `T_elig`. Use short capped exponential jitter; never retry indefinitely. Exhaustion → 503 `TRANSACTION_RETRY_EXHAUSTED`; every failed attempt rolls back.

### 6.2 Unique/exclusion conflict and reconciliation

Only these structured PostgreSQL error tuples are eligible for the unique/exclusion reconciliation path; capture the driver's SQLSTATE and constraint metadata (for example, `code` plus `constraint` / `constraint_name`), never parse human-readable error text:

| SQLSTATE | Exact constraint identifier owned by #33 | Original conflict cause |
|---|---|---|
| `23505` | `booking_one_active_per_slot` | Slot already has an active Booking → `SLOT_UNAVAILABLE` |
| `23P01` | `booked_customer_no_overlap` | Customer has a different overlapping Active Booking → `CUSTOMER_OVERLAP` |

Any missing, unknown or mismatched SQLSTATE/constraint pair (including a different `23505` such as a primary-key violation) is **not** a recognized business conflict: ROLLBACK and return safe 500 `INTERNAL_ERROR`; do not reconcile, read Booking data, return 200 or guess a 409. #33 Part F must publish these exact canonical constraint identifiers; a mismatch is a dependency blocker, not permission to broaden the allowlist.

For a recognized tuple:

1. **Rollback and discard the failed attempt:** ROLLBACK the SERIALIZABLE mutation transaction, release its User/Slot/Session locks and connection, and discard its snapshot and every User/Session authorization observation made in that attempt.
2. **Start a fresh reconciliation transaction:** check out a fresh PostgreSQL connection and begin `BEGIN ISOLATION LEVEL READ COMMITTED`. This is a separate non-mutating authorization/read transaction, not another Booking mutation attempt and does not consume the three-attempt retry budget. Do not mark it SQL `READ ONLY`, because it must lock User and Session rows.
3. **Revalidate the current User before Session or Booking access:** using only the original `principal.userId`, lock the current `"User"` row with `SELECT ... FROM "User" WHERE "id" = $1 FOR UPDATE`. At READ COMMITTED this observes the latest committed User state after any lock wait. If the User is missing or `isActive = false`, ROLLBACK and return 401 `UNAUTHENTICATED`. If the User is active but `role <> 'Customer'`, ROLLBACK and return 403 `FORBIDDEN`. Do not read Session or Booking data and do not return a Booking ID/DTO on either outcome.
4. **Revalidate the exact authenticated Session:** only after the User lock/check, use the original request principal's `sessionId` and `userId` (never request-body values) to lock `"Session"` with `SELECT ... FROM "Session" WHERE "id" = $1 AND "userId" = $2 FOR UPDATE`. A missing row or owner mismatch means ROLLBACK and 401 `UNAUTHENTICATED`. The User → Session order is mandatory; no later step may acquire another User/Slot lock.
5. **Check live Session status using database time while holding the lock:** on the same connection, after the Session lock has been acquired, require `revokedAt IS NULL AND expiresAt > clock_timestamp()`. If revoked or expired, ROLLBACK and return 401 `UNAUTHENTICATED` with no Booking query, ID or DTO. Hold both User and Session locks through reconciliation COMMIT/ROLLBACK so concurrent User deactivation/role change and logout are serialized before or after this authorization/read operation.
6. **Only for a currently active Customer with a live Session, perform one exact-pair read:** query `customerId = principal.userId AND currentSlotId = slotId AND status = 'Booked'` on the same fresh connection. This is a plain non-locking MVCC read; acquire no Slot or Booking row locks and perform no mutation. Confirm the persisted interval matches the selected Slot before treating it as a replay.
7. If the committed same-pair row exists and its interval matches, COMMIT the reconciliation transaction and return 200 with the original Booking ID.
8. If no qualifying same-pair row exists, COMMIT the non-mutating reconciliation transaction and return the safe 409 classified only from the previously allowlisted original constraint tuple: `SLOT_UNAVAILABLE` for `23505 / booking_one_active_per_slot`; `CUSTOMER_OVERLAP` for `23P01 / booked_customer_no_overlap`. Never disclose another Customer or Booking ID.
9. If the fresh connection or User/Session DB validation is unavailable/indeterminate, return 503 `SERVICE_UNAVAILABLE`; never skip authorization, reuse the failed snapshot or return 200/409 from stale data.
10. Never spin until a genuine conflict disappears. The reconciliation read is not a second mutation attempt and does not rerun the trigger or sample `T_elig`.

The fresh **User and Session** checks are mandatory for every post-ROLLBACK path that could return 200 or a business 409. If the User is missing/inactive or no longer has the Customer role, return 401/403 respectively, even if the exact-pair Booking row is

committed. If the Session is revoked/expired before reconciliation, return 401 with no Booking DTO. A live active Customer control case must continue to return 200 with the original ID.

#### 6.3 Other failures

- Non-Offered Slot: rollback and map #33 trigger diagnostic `P0B01` / `booking_slot_not_offered` to 409 `SLOT_UNAVAILABLE`.
- Q05 failure: rollback and map #33 trigger diagnostic `P0B02` / `booking_q05_min_notice` to 422 `BOOKING_NOT_ELIGIBLE`.
- #33 Part F owns and must implement/publish both stable SQLSTATE/constraint pairs. Unknown guard diagnostics fail closed as 500 `INTERNAL_ERROR`; never guess a Q05 failure. BDF-D11's `0A000` is reserved for forbidden UPDATE/DELETE/TRUNCATE, not INSERT eligibility.
- Known DB failure before COMMIT/confirmed rollback: safe 503 `SERVICE_UNAVAILABLE`.
- Ambiguous COMMIT acknowledgement: 503 `BOOKING_OUTCOME_UNKNOWN` if possible; client repeats exact request.
- Unexpected `0A000` on INSERT-only endpoint or any unrecognized/mismatched `23505` / `23P01` SQLSTATE/constraint tuple: rollback, safe 500 `INTERNAL_ERROR` and non-sensitive diagnostics; never enter replay reconciliation for an unknown constraint.
- Malformed/unauthorized requests and business conflicts are not retried.

### 7. Real-PostgreSQL proof gate

BDF-23 is owned by #16 and runs only after #33 Part F merges with exact schema SHA. Evidence must include independent sessions/barriers for Race B/C; backend PIDs/blockers; User → Slot → Session auth-lock order and Session revalidation after waits; fresh READ COMMITTED post-ROLLBACK User-then-Session authorization lock and allowlisted-constraint reconciliation before exact-pair read; trigger Slot lock already held; `T_elig` after required waits; forced unexpected unique/exclusion index wait; 60:00/59:59 and HTTP-arrival-before-cutoff cases; sequential/in-flight/lost-response same-pair replay; pre-COMMIT failure injection; final rows from fresh connection; PostgreSQL version, schema SHA, SQLSTATE/constraint, commands and source commit.

BDF-23 is **PLANNED / NOT RUN** in Part E. If post-guard contention challenge fails, do not approve adapter or claim #16 Part F complete.

---

## E.5.6 F-S1-04 Customer Booking Software Test Specification (tests.md)

> **Planned STS only.** No application code, executable test, migration, PostgreSQL run, browser test or PASS result is included. Execute against actual #33 schema after Part F merge and record exact schema/source SHA.

### 1. Traceability and test setup

Sources: Feature SDS, UI, API, data, transaction contract, Sprint 1 requirements, System SDS and BDF STS.

Part F requires disposable PostgreSQL at target major version/exact #33 schema SHA; synthetic active/inactive Customer and role-change User fixtures, Customer A/B and Tutor A/B; Session A/B (including two Sessions for the same User); real future Offered Slots; at least two independent DB sessions; explicit barriers and observer query; controlled DB clock/request arrival/fault injection/lost HTTP response; browser auth/session-epoch control for late-response cases. For post-ROLLBACK authorization races, provide independent User deactivation/role-change, Session revocation/deletion and Tutor deactivation/role-change transactions and observe lock acquisition order. Capture `pg_backend_pid()` and `pg_blocking_pids`. Random `Promise.all()`, sleep-only race or disabled UI button is insufficient. Inspect final committed rows from a fresh connection.

All cases below are **PLANNED / NOT RUN**.

### 2. Planned STS cases

| ID | Requirement trace | Setup / action | Expected observable result |
|---|---|---|---|
| BOOK-01 | FR-S1-10; AC-S1-19; VC/TEST-S1-16 | Active Customer submits one eligible unoccupied Slot. | 201 only after COMMIT; one `Booked` row with Session Customer, actual Slot and copied interval; response ID equals persisted ID. |

| ID | Requirement trace | Setup / action | Expected observable result |
|---|---|---|---|
| BOOK-02 | FR-S1-11; AC-S1-20; VC/TEST-S1-17 | Slot starts 15:00; trigger `T_elig` exactly 14:00:00. | 60:00 passes; one Booking may commit if other checks pass. |
| BOOK-03 | FR-S1-11; AC-S1-21; VC/TEST-S1-18 | Slot starts 15:00; trigger `T_elig` 14:00:01. | 59:59 fails; no Booking/occupancy; safe 422. |
| BOOK-04 | BR-S1-08; AC-S1-22; VC/TEST-S1-19 | Customer A has committed Booking; Customer B submits same Slot. | 409; A's row preserved; no A identity/Booking detail disclosed. |
| BOOK-05 | BR-S1-09; AC-S1-23; VC/TEST-S1-20 | Customer has 13:00–14:00 with Tutor A; submits 13:30–14:30 with Tutor B. | 409 `CUSTOMER_OVERLAP`; no second row; first remains. |
| BOOK-06 | BR-S1-10; AC-S1-24; VC/TEST-S1-21 | Customer has 13:00–14:00; requests 14:00–15:00 with another Tutor. | Overlap rule permits adjacency if other checks pass. |
| BOOK-07 | FR-S1-11/18; AC-S1-27; VC/TEST-S1-22 | Offer becomes occupied, its lifecycle is no longer `Offered`, its Tutor becomes inactive/changes away from role `Tutor`, or Q05 becomes too close after browse and before a **new** POST. | Server maps occupied/non-Offered/ineligible-Tutor new claims to generic 409 `SLOT_UNAVAILABLE` and Q05 cutoff to 422 `BOOKING_NOT_ELIGIBLE`; no stale-selection success/partial row and no Tutor-status disclosure. Existing same-pair replay is covered separately by BOOK-33. |
| BOOK-08 | FR-S1-11/18; AC-S1-27; VC/TEST-S1-23 | Missing/malformed/past Slot or unauthorized caller attempts Booking. | 400/401/403/404/422 as specified; no mutation/private data. |
| BOOK-09 | BR-S1-20; AC-S1-28; VC/TEST-S1-24 | Customer forges `customerId`, `tutorId`, role, Booking ID or interval. | Extra fields rejected; owner remains Session Customer and Tutor/time derive from real Slot. |
| BOOK-10 | FR-S1-12; AC-S1-25; VC/TEST-S1-25; NFR-S1-04 | Two Customers race for one eligible Slot under synchronized barrier. | At most one committed `Booked` row; loser non-success; no partial claim. |
| BOOK-11 | FR-S1-13; AC-S1-26; VC/TEST-S1-26; NFR-S1-05 | Same Customer concurrently submits distinct overlapping Slots from two Tutors; repeat at proposed 10-attempt load. | No two overlapping Active rows commit; adjacent control allowed. |
| BOOK-12 | FR-S1-18; AC-S1-27; VC/TEST-S1-27 and VC/TEST-S1-33 | Inject DB failure after validation/before COMMIT; reopen state via fresh connection. | Whole transaction rolls back; no Booking, phantom occupancy or success; prior rows unchanged. |
| BOOK-13 | AC-S1-29; VC/TEST-S1-38; OD-013 | After commit, same Customer sends same `slotId` POST again. | 200 with exact original Booking ID/DTO; no second row/new ID. |

| ID | Requirement trace | Setup / action | Expected observable result |
|---|---|---|---|
| BOOK-14 | AC-S1-29; VC/TEST-S1-38; Race B/C | Two same-Customer/same-Slot POSTs overlap in flight under barrier. | One row only; winner 201; duplicate reconciles to 200 with same ID (or retryable abort then same result on fresh attempt). |
| BOOK-15 | AC-S1-29; VC/TEST-S1-38; OD-013 | Let COMMIT succeed but drop HTTP response; Customer resubmits identical POST. | Second request returns 200 with committed original ID; exactly one row. |
| BOOK-16 | AC-S1-29; VC/TEST-S1-38 | Force first attempt to roll back before COMMIT, then retry identical POST. | Retry creates at most one row and returns 201 only after its own COMMIT; no phantom success. |
| BOOK-17 | AC-S1-35; VC/TEST-S1-39; Q05 | 15:00 Slot; HTTP arrives 13:59:59; hold required lock until 14:00:01. | Trigger samples `T_elig` after wait and rejects 59:59; no Booking. |
| BOOK-18 | System SDS §7.1/7.4; SQLSTATE 40001/40P01 | Force serialization failure and deadlock in separate runs. | Roll back whole attempt, rediscover/relock in order and retry no more than three total attempts; no partial rows. |
| BOOK-19 | BDF-23; System SDS §7.3; VC/TEST-S1-39 | Force unexpected unique/exclusion index wait after trigger `T_elig`; instrument PIDs/blockers/trigger time. | Prove no stale-time INSERT can commit, or show full abort/retry with fresh `T_elig`. Otherwise BLOCKED/FAIL. |
| BOOK-20 | NFR-S1-01/08; VC/TEST-S1-23/24 | Inspect full success/error JSON for anonymous, wrong-role, occupied foreign Slot, forged fields and DB errors. | No Customer/Tutor private identity, SQL/stack, credentials, Session/CSRF data or another Booking ID leaks. |
| BOOK-21 | NFR-S1-03/11; VC/TEST-S1-27/33 | Restart app against same DB after success; reopen views after rejected attempt when #17 is integrated. | Committed Booking remains; rejected attempt creates no phantom row/occupancy. |
| BOOK-22 | Transaction contract §2; BDF-23 | Instrument User, Slot and current Session locks for both UUID orderings and concurrent cross-Tutor requests. | Actual acquisition follows User UUID ascending → Slot UUID ascending → current Customer Session auth sub-lock → Booking; domain order remains User → Slot → Booking; no out-of-order acquisition. |
| BOOK-23 | Transaction contract §6.1 | Force three retryable transaction aborts. | Three total attempts maximum; final 503 `TRANSACTION_RETRY_EXHAUSTED`; all attempts rolled back. |
| BOOK-24 | Transaction contract §§2/6 | Change/remove discovered lock-set member between pre-read and locked re-read in isolated fixture. | Abort without acquiring an earlier-order lock late; rediscover/restart whole transaction or safe non-success after budget. |
| BOOK-25 | BDF-23; #33 Part F trigger contract | Independently trigger a non-`Offered` Slot rejection and a Q05 failure at `T_elig`; inspect PostgreSQL SQLSTATE and constraint diagnostics. | Non-Offered is exactly `P0B01 / booking_slot_not_offered` → 409 `SLOT_UNAVAILABLE`; Q05 is exactly `P0B02 / booking_q05_min_notice` → 422 `BOOKING_NOT_ELIGIBLE`. No raw DB diagnostics; any missing/mismatched identifier is BLOCKED. |
| BOOK-26 | BR-S1-13; OD-005-A/B; VC/TEST-S1-23 | Pass HTTP auth, hold the Customer User row in DB session A, start Booking POST in session B and confirm it waits on the User lock. While it waits, revoke that exact Session through logout and commit; then release the User lock. | The Session lock acquired after the wait observes revocation or the stale SERIALIZABLE attempt aborts/retries; fresh attempt returns 401. No 201, no 200 replay, no Booking row and no private replay data. |

| ID | Requirement trace | Setup / action | Expected observable result |
|---|---|---|---|
| BOOK-27 | BR-S1-13; OD-005-A/B; VC/TEST-S1-23 | Hold selected Slot row in DB session A. Start Booking POST, verify it has acquired User lock and is waiting on Slot; in separate runs, either revoke the Session and commit or allow its `expiresAt` to pass; then release Slot. | Session is locked/revalidated only after the Slot wait; revoked/expired Session returns 401 (or stale snapshot forces full retry then 401). No Booking INSERT, no 200 replay and no private data. |
| BOOK-28 | OD-005-C; VC/TEST-S1-23/24 | Attempt POST with missing/wrong CSRF, Session A token with Session B cookie (including same User), missing/mismatched expected binding, foreign Origin, and `Sec-Fetch-Site: cross-site`. Also switch A→B between the initial `GET /auth/me` and `GET /auth/csrf`; verify the client performs a second `GET /auth/me` after CSRF and compares the returned binding/identity. | Reject invalid requests with 403 `CSRF_DENIED` / `SESSION_BINDING_MISMATCH` / `ORIGIN_DENIED` as applicable (401 for invalid Session). If the post-CSRF `/auth/me` binding differs, discard the token and restart bootstrap without POST; no mutation or private Booking data. |
| BOOK-29 | OD-005-B/C; VC/TEST-S1-23/24 | Start a POST under Session A and delay its response; logout A or switch to Session B (same User and different User), then deliver A's late response. Also switch A→B **after** the post-CSRF `GET /auth/me` recheck but before POST, sending A's captured expected binding/token with B's cookie. | UI auth/session epoch discards A's late response and never displays its Booking ID/details under B. The race after the final recheck is rejected before mutation with 403 `SESSION_BINDING_MISMATCH` or `CSRF_DENIED` (depending on middleware order); client clears identity/CSRF state and restarts bootstrap. If A had already committed before logout, do not claim rollback; only the stale response is suppressed. |
| BOOK-30 | BR-S1-13; AC-S1-29; OD-013; VC/TEST-S1-23/38; Transaction contract §6.2 | Cause either (a) a same-pair race that produces the recognized `23505 / booking_one_active_per_slot` after the winning same-pair Booking commits, or (b) a distinct overlapping-Slot conflict that produces `23P01 / booked_customer_no_overlap`; pause after the failed SERIALIZABLE transaction rolls back but before reconciliation. For each cause, run synchronized interleavings where (1) the Customer User is deactivated and committed, (2) its role changes from Customer and commits, (3) the exact Session is revoked and committed, or (4) the barrier is held until DB clock passes Session `expiresAt`; then release. Also run a live active-Customer/live-Session control for each cause. | Reconciliation first locks/revalidates the latest User row: missing/inactive → 401 `UNAUTHENTICATED`; active non-Customer → 403 `FORBIDDEN`; neither reads Session/Booking or returns a DTO. If User remains an active Customer, it locks/revalidates exact Session: revoked/expired → 401 with no Booking read/ID/DTO. For cause (a), live control returns 200 with the original same-pair Booking ID and exactly one committed row; for cause (b), live control returns 409 `CUSTOMER_OVERLAP` and no additional row. Final rows remain unchanged in all rejection cases. If User/Session DB validation is unavailable, return 503; never skip a check. |
| BOOK-31 | Transaction contract §6.2; #33 BDF-D05/D06; AC-S1-22/23; VC/TEST-S1-19/20 | Inject structured PostgreSQL errors for (a) `23505 / booking_one_active_per_slot`, (b) `23P01 / booked_customer_no_overlap`, and negative controls (c) `23505` on a different constraint such as Booking primary key, (d) `23P01` with a different/unknown constraint identifier, and (e) missing constraint metadata. | Only (a)/(b) enter reconciliation. If no exact-pair replay is found, map (a) to 409 `SLOT_UNAVAILABLE` and (b) to 409 `CUSTOMER_OVERLAP`. Negative controls roll back and return safe 500 `INTERNAL_ERROR` without any User/Session/Booking reconciliation read or Booking DTO; never parse error text or infer a business conflict from SQLSTATE alone. Capture structured SQLSTATE/constraint metadata and verify committed rows are unchanged. |

| ID | Requirement trace | Setup / action | Expected observable result |
|---|---|---|---|
| BOOK-32 | Transaction contract §3 step 6 / §6.1; BR-S1-13; VC/TEST-S1-23 | Pass the HTTP Session guard, then delete the exact Session row or make its owner mismatch before the SERIALIZABLE transaction's exact Session lock. In a separate run, force a concurrent Session update/delete that PostgreSQL reports as SQLSTATE `40001`. | Exact lookup returning no row/owner mismatch rolls back and returns 401 `UNAUTHENTICATED` immediately, with no Booking read/replay/DTO and without consuming retry budget. A genuine `40001` rolls back and retries the whole transaction; the fresh attempt re-reads and returns 401 if Session is absent, owner-mismatched, revoked or expired; only a live matching Session may proceed. Never turn a missing Session into 503 `TRANSACTION_RETRY_EXHAUSTED`. |
| BOOK-33 | Transaction contract §3 steps 8–9; API §4; OD-013; AC-S1-29; VC/TEST-S1-38 | Commit a Booking while Tutor is active, then in separate runs deactivate that Tutor or change its role away from `Tutor`. The same active Customer/live Session repeats the exact `slotId`; use a separate unbooked Slot for a new-claim control against the now-ineligible Tutor. | Same-pair replay returns 200 with the original Booking ID and exactly one row despite later Tutor deactivation/role change. A new claim for the ineligible Tutor returns generic 409 `SLOT_UNAVAILABLE`, creates no row and reveals no Tutor identity/status. |

### 3. Required existing-anchor coverage

| Existing anchor | Planned case |
|---|---|
| VC/TEST-S1-16 | BOOK-01 |
| VC/TEST-S1-17 | BOOK-02 |
| VC/TEST-S1-18 | BOOK-03 |
| VC/TEST-S1-19 | BOOK-04, BOOK-31 |
| VC/TEST-S1-20 | BOOK-05, BOOK-31 |
| VC/TEST-S1-21 | BOOK-06 |
| VC/TEST-S1-22 | BOOK-07 |
| VC/TEST-S1-23 | BOOK-08, BOOK-20, BOOK-26..30, BOOK-32 |
| VC/TEST-S1-24 | BOOK-09, BOOK-20, BOOK-28..29 |
| VC/TEST-S1-25 | BOOK-10 |
| VC/TEST-S1-26 | BOOK-11 |
| VC/TEST-S1-27 | BOOK-12, BOOK-21 |
| VC/TEST-S1-33 | BOOK-12, BOOK-21 |
| VC/TEST-S1-38 | BOOK-13..16, BOOK-30, BOOK-33 |
| VC/TEST-S1-39 | BOOK-17, BOOK-19 |
| AC-S1-22/23 | BOOK-04/05, BOOK-31 |
| AC-S1-19..29 | BOOK-01..16, BOOK-20 and BOOK-26..30, BOOK-33 |
| BR-S1-13 | BOOK-26..30, BOOK-32 |
| AC-S1-35 | BOOK-17, BOOK-19 |

Existing AC/VC/TEST IDs remain authoritative; BOOK IDs are F-S1-04 STS IDs, not replacements.

### 4. Part E boundary and Part F evidence

**Part E:** contracts and planned cases only. No test result is PASS, no PostgreSQL query has run, and no schema SHA exists yet.

**Part F evidence per run:** test ID; command; source commit; merged #33 schema SHA; PostgreSQL version; synthetic fixture IDs; backend PIDs/barrier; `T_elig`; SQLSTATE/constraint; expected/actual HTTP result; committed rows before/after; PASS/FAIL/SKIP and reason. Redact secrets/PII.

#33 BDF-01..22 and BDF-24..26 are its Part F pre-merge gates. #16 BDF-23 is the post-merge joint integration gate and runs only after #33 Part F merges.

#### 5. Independent review checklist

- [ ] Confirm endpoint ownership, auth/role/CSRF, request allowlist and safe errors.
- [ ] Confirm Natural-key OD-013 scope, replay precedence and 201/200 behavior.
- [ ] Confirm canonical #33 mapping and no duplicated schema/trigger.
- [ ] Confirm User → Slot → Session(auth sub-lock) → Booking acquisition, SERIALIZABLE snapshot behavior, post-lock-wait User/Session revalidation, and fresh post-ROLLBACK User-then-Session authorization validation before reconciliation read/200/409.
- [ ] Confirm Auth CSRF acquisition, post-CSRF `/auth/me` binding recheck, Session-switch rejection before POST, cross-origin rejection and late-response suppression across different Sessions for the same User.
- [ ] Confirm retry classification, three-attempt bound, exact SQLSTATE/constraint allowlist (including negative controls), safe unknown-constraint failure and unknown COMMIT behavior.
- [ ] Challenge no-post-guard-contention strategy against actual #33 trigger/constraints; retain BDF-23 as hard gate.
- [ ] Confirm AC-S1-19..29/35 and VC/TEST-S1-16..27/33/38/39 coverage.
- [ ] Confirm no code, migration, executable tests or S2 workflow is in this Part E PR.
- [ ] Record actual human peer review; self-check is not approval.

**Status:** PLANNED / NOT RUN. Issue #16 remains open until Part F, BDF-23, actual verification and independent review satisfy its DoD.

---

## E.6 F-S1-05: Protected Booking Retrieval & Authorized Tutor Schedule

---

### E.6.1 F-S1-05 Protected Booking Retrieval Feature SDS (specification.md)

> **Documentation contract only; not implemented, executed, or peer-approved yet.**
> Issue #17; provisional lead @Chxtamos; independent peer reviewer @Tanaboonnnnn.
> This Part E document specifies the data allowlists, authorization boundaries, UI/API contracts, and Software Test Specification (STS) for Sprint 1 Booking retrieval and Tutor schedule inspection. This change does not implement UI/API code, add a migration, execute tests, or close the issue.

---

#### 1. Authority, Baseline, and Mission

##### 1.1 Source Hierarchy

This specification derives from and complies with:

1. **Sprint 1 Requirements**:
   - Functional requirements: `FR-S1-04`, `FR-S1-07`, `FR-S1-14`, `FR-S1-15`, `FR-S1-16`, `FR-S1-17`, `FR-S1-18`, `FR-S1-19`.
   - Business rules: `BR-S1-01`, `BR-S1-02` (60m duration), `BR-S1-03` (manual offer), `BR-S1-12` (Asia/Bangkok timezone), `BR-S1-14`, `BR-S1-15`, `BR-S1-16`, `BR-S1-17`, `BR-S1-18`, `BR-S1-22`.
   - Non-functional requirements: `NFR-S1-01` (Access isolation), `NFR-S1-02` (Credential protection), `NFR-S1-03` (Persistent correctness), `NFR-S1-06` (Time-boundary correctness), `NFR-S1-07` (Reproducible verification), `NFR-S1-08` (No secret leakage), `NFR-S1-09` (Usability proposal — keyboard & visible focus), `NFR-S1-12` (Traceable change & review).

- Acceptance criteria: `AC-S1-30`, `AC-S1-31`, `AC-S1-32`, `AC-S1-33`, `AC-S1-34`.
- Planned validation anchors: `VC/TEST-S1-28`, `VC/TEST-S1-29`, `VC/TEST-S1-30`, `VC/TEST-S1-31`, `VC/TEST-S1-32`.
- Direct stakeholder decisions: `Q01` (Single booking), `Q02` (Role authorization), `Q03` (Fixed 60-minute Slot duration), `Q04` (Manual individual Slot offers, no recurrence), `Q05` (Cutoff lead time), `Q28` (Overlap rules), `Q29` (Single Asia/Bangkok business timezone), `Q30` (Booked vs Past status, never Completed in S1).

2. **Whole-product SRS:** System actors, user journeys `J-01` (Auth), `J-02` (Tutor publishing), `J-03` (Customer booking), `J-04` (Customer booking review), `J-05` (Tutor schedule review).
3. **System SDS:** §§3.2–3.3 (Data entity relations), §4 (API conventions and error envelopes), §5 (Role & record level authorization), §6 (Timezone handling in UTC on wire and Asia/Bangkok on display).
4. **Accepted Preceding Contracts:**
   - Auth F-S1-01: Session cookie, identity, role guard, rate limiting, and CSRF token.
   - Tutor Availability F-S1-02: Owned 60-minute Slots, `startsAt` / `endsAt`, `lifecycle = 'Offered'`.
   - Customer Availability Discovery F-S1-03: Bookable Slot filtering, `T_view` evaluation, opaque Tutor references.
   - Booking Data Foundation D1-08A/B: Canonical `Booking` table, `booking_guard_s1()` trigger, GiST exclusion constraints, and pre-index `User` lock ( `da17acf` ).
   - Exclusive Booking F-S1-04: SERIALIZABLE adapter, natural-key replay, committed `Booked` status.

### 1.2 Repository Baseline

- Integration base: `origin/sprint1` at commit `ed78bbad9da8c828e9b0bd1c79ea8f68f553c9b1`, containing all merged foundations:
  - Auth implementation (PR #26)
  - Tutor Slots & Dashboard (PR #28, PR #31)
  - Shared Booking Data Foundation (PR #36) & Remediation (PR #40)
  - Customer Availability Discovery (PR #37)
  - Customer Exclusive Booking & BDF-23 (PR #38)

---

## 2. Mission and Core Outcomes

### 2.1 The Two Primary User Outcomes

1. **Customer-Private Booking Review ( `FR-S1-14`, `AC-S1-30`, `AC-S1-31` ):**

An authenticated Customer can retrieve a complete list of their **own** committed Bookings and open individual Booking details after browser refresh or application restart. The details display Booking ID, Slot ID, Tutor reference/identity, appointment interval in Asia/Bangkok time, and business status ( `Booked` or time-derived `Past` ). No unauthorized Customer or anonymous caller can read or discover any private Booking payload.

1. **Authorized Tutor Schedule Inspection ( `FR-S1-07`, `FR-S1-15`, `AC-S1-32`, `AC-S1-33` ):**

An authenticated Tutor can inspect the collection of Slots and associated Bookings on their **own** authorized schedule. The Tutor schedule view projects each Slot's occupancy state ( `Unoccupied` vs `Occupied` ) and lists active Bookings assigned to their schedule without leaking other Tutors' restricted schedule records or foreign Customer data. For privacy and data minimization, Customer identity on the Tutor schedule is represented by a pseudonymous truncated reference ( `customerRef: "CUST-" + customerId.slice(0, 8)` ), omitting personal identifiers (name, email, phone) and isolating customer UUIDs from the Tutor wire DTO.

### 2.2 Time-Derived Classification: "Past" is NOT "Completed" ( `FR-S1-17`, `BR-S1-14/22`, `AC-S1-34`, `Q30` )

- In Sprint 1, the database business status of an active appointment is always `'Booked'` (or `'Cancelled'` in future sprints).
- When the appointment window has elapsed relative to the single statement evaluation timestamp ( `endsAt <= meta.evaluatedAt` ), the UI and API classify the presentation as `Past`.
- **Strict Invariant:** An elapsed appointment **MUST NOT** be automatically updated to `'Completed'`, marked as attended, canceled, or released back to the bookable pool. The persisted database row remains `status = 'Booked'`, and the Slot remains

occupied.

---

### 3. Boundaries and Scope

#### 3.1 In Scope for Sprint 1 (F-S1-05)


- **Customer Endpoints:**
  - `GET /api/v1/customer/bookings`: Returns all Bookings belonging strictly to `principal.userId`.
  - `GET /api/v1/customer/bookings/:id`: Returns single Booking detail if owned by `principal.userId`; returns `404 BOOKING_NOT_FOUND` if non-existent or owned by another user.
- **Tutor Endpoints:**
  - `GET /api/v1/tutor/slots`: Updated to project dynamic occupancy (`Occupied` if an active `Booked` row exists on that Slot, else `Unoccupied`).
  - `GET /api/v1/tutor/bookings`: Returns all active Bookings scheduled on Slots owned by `principal.userId`.
- **Backend Record-Level Security:**
  - All ownership filters are strictly bound to `principal.userId` from the authenticated session; never trust client-supplied IDs, query parameters, or route tampering.
  - Fail closed on unauthorized access: anonymous calls return `401 UNAUTHENTICATED`; role mismatches return `403 FORBIDDEN`; foreign record queries return `404 BOOKING_NOT_FOUND` (preventing ID enumeration).
- **Time Handling:**
  - Wire timestamps: Strict ISO 8601 / RFC 3339 UTC strings ending in `Z` with milliseconds (e.g., `YYYY-MM-DDTHH:mm:ss.sssZ`).
  - Evaluation timestamp: API returns `meta.evaluatedAt` representing server-authoritative time used for the `displayStatus` derivation.
  - UI Presentation: Formatted strictly in `Asia/Bangkok` timezone (UTC+7) regardless of local device timezone.
- **Durable Persistence Proof:**
  - Data retrieval queries committed rows from PostgreSQL database tables (`Booking`, `Slot`, `User`).
  - Persistence holds across app restart and browser reloads.

#### 3.2 Explicitly Out of Scope for Sprint 1

- **No Mutation:** F-S1-05 is strictly a read-only retrieval feature; it performs zero database `INSERT`, `UPDATE`, `DELETE`, or schema DDL.
- **No Sprint 2/3 Capabilities:**
  - Customer cancellation (`Q07–Q08`) or rescheduling (`Q09–Q16`).
  - Tutor withdrawal reasons, cancellations, or slot modifications (`Q17–Q20`, `Q26–Q27`, `Q32`).
  - In-app notification center or email delivery (`Q21–Q25`).
  - Tutor appointment summary dashboard with attendance tracking (`Q31`).
  - Review, rating, messaging, payments, or attendance logging.
- **No Unapproved Query Parameters:** No filtering, search, pagination, date-range bounding, or custom sorting is approved for Sprint 1. Requests with unexpected query parameters fail with `400 INVALID_INPUT`.

---

## 4. User Journeys and Actors




## 5. Architectural Invariants and Decisions

| Decision / Invariant ID | Summary | Rationale & Enforcement |
|---|---|---|
| **INV-RET-01: Session-Bound Ownership** | All read queries filter strictly by `principal.userId` extracted from the server-validated session. | Client cannot forge or query other users' data. URL tampering produces `404` or `403`. |
| **INV-RET-02: Safe Enumeration Refusal (404 instead of 403)** | If a Customer requests `/api/v1/customer/bookings/:id` for an ID that exists but belongs to someone else, return `404 BOOKING_NOT_FOUND`. | Returning `403 FORBIDDEN` confirms the ID exists in the system (information leakage). `404` prevents ID brute-forcing. |
| **INV-RET-03: No Phantom Completion** | Elapsed appointments ( `endsAt <= meta.evaluatedAt`, using statement snapshot) have `displayStatus = 'Past'`, while `status = 'Booked'`. | Adheres strictly to `Q30`, `FR-S1-17`, and `BR-S1-22`. Sprint 1 does not implement attendance or completion. |
| **INV-RET-04: Dynamic Slot Occupancy** | `listOwnSlots` determines `occupancy` via an active `Booked` record matching `Booking.currentSlotId = Slot.id`. | Delivers `FR-S1-07` without adding a mutable `Slot.isBooked` column, preserving single-source-of-truth normalization. |
| **INV-RET-05: Strict UTC Wire Normalization & Bangkok Presentation** | Timestamps returned by the API are normalized to UTC with trailing `Z` on the wire, while UI presentation formats strictly in Asia/Bangkok time. | Satisfies `BR-S1-12`, `Q29`, and `NFR-S1-06`; eliminates ambiguity caused by database server or runtime timezone settings. |

| Decision / Invariant ID | Summary | Rationale & Enforcement |
|---|---|---|
| **INV-RET-06: Strict Query Allowlist** | Query strings are forbidden ( `Object.keys(req.query).length === 0` ). | Prevents SQL injection, parameter pollution, and unapproved filtering features ( `NFR-S1-08` ). |
| **INV-RET-07: Minimal Payload Privacy** | Responses exclude password hashes, CSRF nonces, session digests, and unapproved contact data. | Strict DTO allowlists satisfy `NFR-S1-01` and `NFR-S1-08` . |
| **INV-RET-08: Pseudonymous Customer Reference** | `customerRef: "CUST-" + customerId.slice(0, 8)` is a truncated pseudonymous identifier, not an irreversible anonymization. | Provides data minimization for Tutor schedule display by withholding customer name, email, and phone, while maintaining an opaque operational reference. |

### 6. Acceptance Criteria and Traceability Matrix

| Requirement ID | Acceptance Criteria | Business Rule | Verification Anchor | Description |
|---|---|---|---|---|
| `FR-S1-14` , `FR-S1-16` | **AC-S1-30** | `BR-S1-01` , `BR-S1-15` | `VC/TEST-S1-28` | Customer retrieves own list/detail after refresh/restart with exact Booking ID, Tutor, Bangkok interval, and status. |
| `FR-S1-04` , `FR-S1-14` | **AC-S1-31** | `BR-S1-15` , `BR-S1-18` | `VC/TEST-S1-29` | Customer B attempts to view Customer A's Booking ID; API returns safe `404 BOOKING_NOT_FOUND` with zero data leakage. |
| `FR-S1-07` , `FR-S1-15` | **AC-S1-32** | `BR-S1-16` | `VC/TEST-S1-30` | Tutor views Bookings on own schedule; occupied slots display `Occupied` ; only assigned Bookings are visible. |
| `FR-S1-04` , `FR-S1-15` | **AC-S1-33** | `BR-S1-16` , `BR-S1-18` | `VC/TEST-S1-31` | Tutor B attempts to read Tutor A's schedule/bookings; access denied, zero foreign records disclosed. |
| `FR-S1-17` | **AC-S1-34** | `BR-S1-14` , `BR-S1-22` | `VC/TEST-S1-32` | An elapsed appointment displays as `Past` , but persisted business state remains `Booked` , never `Completed` . |

### 7. Definition of Done (DoD)

#### Part E — Specification Stage (Current PR)

- [ ] Complete `specification.md` , `api-spec.md` , `ui-spec.md` , `data-spec.md` , and `tests.md` authored under `docs/features/F-S1-05/` .
- [ ] Invariants, request/response DTO schemas, and error codes strictly mapped to requirements and existing architecture.
- [ ] No application code, migrations, or tests implemented in this documentation PR.
- [ ] Peer review requested from @Tanaboonnnnn and approved before branching Part F.

#### Part F — Implementation Stage (Subsequent Work)

- [ ] Backend route handlers, services, and queries implemented for Customer bookings and Tutor schedule views.
- [ ] Tutor own-slots list updated to project dynamic occupancy from committed `Booking` rows.
- [ ] Customer and Tutor UI components connected to live API endpoints.
- [ ] STS test suite `RET-01..RET-17` executed with real PostgreSQL and Playwright browser, achieving 100% PASS.

## E.6.2 F-S1-05 Protected Booking Retrieval UI Specification (ui-spec.md)

> **Documentation contract only; not implemented yet.**
> Issue #17. This document defines the user interface specifications, layout states, responsive behavior, accessibility guidelines, and timezone presentation for Customer Booking retrieval and Tutor schedule inspection.

### 1. Design System and Visual Tokens

All UI components for F-S1-05 directly reuse and map to the established NutTiew design system tokens from `F-S1-01`, `F-S1-02` (Tutor Dashboard), and `F-S1-03` (Customer Availability) as implemented in `apps/web/src/customer-availability.css` and `apps/web/src/tutor-dashboard.css`. No new or drifting color palette is introduced.

| Design Token | Existing CSS Variable / Value | Purpose & Contrast Specification |
|---|---|---|
| **Canvas Background** | `--customer-canvas` / `--tutor-canvas`: `#f7f8fb` | Light application background across all screens |
| **Surface Card** | Surface: `#ffffff` | Primary content panels, cards, and modals |
| **Brand / Shell Navigation** | `--customer-navy` / `--tutor-navy`: `#202b44`<br>Deep: `#172137` | Top navigation bar, wordmark header, active navigation state |
| **Divider Border** | `--customer-border` / `--tutor-border`: `#e0e6ef` | Section dividers and card container borders |
| **Control Border** | `--customer-control-border`: `#66778a` | Form controls, modal borders, and interactive card boundaries (4.59:1 on white) |
| **Primary Text (Ink)** | `--customer-ink`: `#172137`<br>`--tutor-ink`: `#263244` | High-contrast body text, headings, and primary card labels (>= 12:1 on white) |
| **Secondary Text (Muted)** | `--customer-muted`: `#455a76`<br>`--tutor-muted`: `#58697f` | Timestamps, metadata, labels (>= 4.5:1 on white and canvas) |
| **Primary Action (CTA)** | `--customer-orange` / `--tutor-orange`: `#f47736`<br>Hover: `#a43e14`<br>Border: `#d96123` | Refresh and navigation action buttons; paired strictly with dark ink `#172137` text (never low-contrast white text on orange) |
| **Focus Indicator** | `--customer-focus` / `--tutor-focus`: `#aa4519` | `3px solid #aa4519` with `outline-offset: 3px`; visible and unobstructed on all interactive elements |
| **Status Badge: Booked** | `background: #eef2f7; color: #172137; border: 1px solid #c6d2e3` | Active / upcoming reservation badge; label **ยืนยันแล้ว** (Customer) or **มีนัดหมาย (Booked)** (Tutor) |
| **Status Badge: Past** | `background: #f1f3f6; color: #58697f; border: 1px solid #d4dbe4` | Elapsed appointment badge; label **สิ้นสุดแล้ว** (Past) |
| **Occupancy Badge: Occupied** | `background: #fff7ed; color: #a43e14; border: 1px solid #f47736` | Tutor agenda slot occupancy; label **มีผู้จองแล้ว (Occupied)** |
| **Occupancy Badge: Unoccupied** | `background: #eef2f7; color: #172137; border: 1px solid #c6d2e3` | Tutor agenda available slot; label **ว่าง (เปิดรับจอง)** |

All text combinations pass WCAG 2.2 AA minimum contrast ratios (>= 4.5:1 for normal text, >= 3:1 for large text and UI borders).

---

### 2. Timezone and Date Presentation Rules (`BR-S1-12`, `Q29`, `NFR-S1-06`)

1. **Mandatory Asia/Bangkok Timezone:**
   - All appointment intervals (`startsAt` to `endsAt`) and creation dates must be formatted explicitly in `Asia/Bangkok` (UTC+7) using `Intl.DateTimeFormat` or equivalent, regardless of the user's operating system or device timezone.
2. **Format Standard:**
   - Date: `d MMM yyyy` in Thai locale (e.g., `10 พ.ย. 2026`).
   - Time: `HH:mm` in 24-hour cycle (e.g., `16:00 – 17:00 น.`).
   - Combined Summary: `10 พ.ย. 2026, 16:00 – 17:00 น.`

---

### 3. Customer Booking Retrieval UI

#### 3.1 Customer Bookings List ( `#customer-bookings-section` )

A Customer navigates to "การจองของฉัน" (My Bookings) within the Customer Portal ( `apps/web/src/customer-availability.tsx` / `apps/web/src/main.tsx` ):

1. **Header & Navigation:**
   - Screen Title: `h1` "การจองของฉัน" (My Bookings).
   - Navigation button/tab to switch between "ตารางติวที่เปิดจอง" (Available Offers) and "การจองของฉัน" (My Bookings).
   - Button "รีเฟรช" (Refresh list).
2. **Booking Card Component ( `.customer-booking-card` ):**
   - **Tutor Reference:** Displays Tutor opaque reference or approved display name (e.g., `ผู้สอน: TUTOR-f7a8b9c0` ).
   - **Appointment Window:** Bangkok time (e.g., `10 พ.ย. 2026, 16:00 – 17:00 น.` ).
   - **Status Badge:**
     - `Booked` (Active/Upcoming): Light navy tint surface with border `#c6d2e3` and text **ยืนยันแล้ว** .
     - `Past` (Elapsed): Neutral gray surface with border `#d4dbe4` and text **สิ้นสุดแล้ว** .
   - **Detail Action Button:** `<button data-testid="view-booking-detail">ดูรายละเอียด</button>` (opens detail modal on `/customer/bookings` ).
3. **Empty State ( `.customer-bookings-empty` ):**
   - Text: "คุณยังไม่มีประวัติการจองติว".
   - Action link/button: "ค้นหาตารางติวเพื่อเริ่มจอง" (navigates back to availability).
4. **Loading State:**
   - Text: "กำลังโหลดรายการจองของคุณ...".
5. **Error State ( `.customer-bookings-error` ):**
   - Text: "ไม่สามารถโหลดข้อมูลการจองได้ในขณะนี้".
   - Action button: "ลองใหม่อีกครั้ง" (retries fetch).

---

#### 3.2 Customer Booking Detail View ( `#customer-booking-detail-modal` / `.booking-detail-view` )

When a Customer clicks "ดูรายละเอียด" on a Booking card:

1. **Header:** Title `h2` "รายละเอียดการจอง".
2. **Field Summary Table / List:**
   - รหัสการจอง **(Booking ID):** Monospaced UUID string (e.g., `e4f8d53b-013d-4c57-891a-7b3c2e1f4001` ) with copy button.
   - ผู้สอน **(Tutor):** `TUTOR-f7a8b9c0` .
   - วันและเวลาติว **(Appointment Time):** `10 พ.ย. 2026, 16:00 – 17:00 น. (Asia/Bangkok)` .
   - สถานะ **(Status):**
     - Upcoming: Badge `ยืนยันแล้ว` ( `Booked` ).
     - Elapsed: Badge `สิ้นสุดแล้ว` ( `Past` ). Notice: "การนัดหมายนี้สิ้นสุดลงแล้ว".
   - วันที่ทำรายการ **(Booked At):** Bangkok formatted timestamp.
3. **Close / Back Action:** `<button data-testid="close-detail-btn">ปิด / กลับสู่รายการ</button>` .
4. **Not Found State ( `404 BOOKING_NOT_FOUND` ):**
   - If user accesses an invalid or foreign Booking ID:
   - Displays "ไม่พบข้อมูลการจองนี้" with button "กลับสู่รายการจอง".
   - Zero private data (no Customer names, IDs, or timestamps) is rendered.

---

### 4. Tutor Schedule Inspection UI

#### 4.1 Integration into Tutor Dashboard ( `apps/web/src/tutor-slots.tsx` )

Fulfills `FR-S1-07` and `FR-S1-15` :

1. **Slots Calendar & Agenda ( `AllSlotsAgenda` & `SlotCalendar` ):**
   - Each Slot card displays its real-time occupancy status:
     - If `occupancy === 'Unoccupied'` : Light navy tint badge `ว่าง (เปิดรับจอง)` ( `#eef2f7` ).
     - If `occupancy === 'Occupied'` : Amber/orange tinted badge `มีผู้จองแล้ว (Occupied)` ( `#fff7ed` with border `#f47736` ).
2. **Schedule Bookings List ( `#tutor-schedule-bookings-section` ):**
   - Section Title: `h2` "รายการนัดหมายบนตารางสอนของคุณ" (Bookings on Your Schedule).
   - Card for each assigned Booking:
     - รหัสการจอง: Booking UUID.
     - ช่วงเวลา: Bangkok formatted time (e.g., `10 พ.ย. 2026, 16:00 – 17:00 น.` ).
     - ผู้จอง: Pseudonymous Customer Reference (e.g., `CUST-e4f8d53b` ); provides data minimization by withholding customer name, email, and phone, and isolating customer UUIDs from the Tutor schedule view.
     - สถานะ:
       - Upcoming: Badge `มีนัดหมาย (Booked)` ( `#eef2f7` ).
       - Elapsed: Badge `สิ้นสุดแล้ว (Past)` ( `#f1f3f6` ).
3. **Empty Schedule State:**
   - If Tutor has no bookings on their schedule:
   - Text: "ยังไม่มีผู้จองในช่วงเวลาที่คุณเปิดสอน".

---

### 5. Viewport and Accessibility Specifications ( `NFR-S1-09` Proposal)

1. **Responsive Viewports:**
   - Small Mobile (320px): Single-column stacked cards, full-width buttons (min 44px touch target).
   - Standard Mobile (375px): Optimized padding (16px), readable typography.
   - Tablet (768px): Two-column card grid or tabular list.
   - Desktop (1280px): Multi-column dashboard with side-by-side agenda and booking details.
2. **Keyboard Navigation:**
   - All interactive elements (refresh buttons, detail triggers, modal dismissals) must be focusable using `Tab` .
   - `Enter` and `Space` activate buttons.
   - `Escape` key closes the Booking Detail modal and returns focus to the triggering element.
3. **Screen Reader Semantics:**
   - Section headings use proper semantic hierarchy ( `h1` -> `h2` -> `h3` ).
   - Badges provide accessible aria-labels (e.g., `aria-label="สถานะการจอง: ยืนยันแล้ว"` ).

---

## E.6.3 F-S1-05 Protected Booking Retrieval API Specification (api-spec.md)

> **Documentation contract only; not implemented yet.**
> Issue #17. This document defines the HTTP endpoints, authorization rules, request/response allowlists, and error mapping for Customer-private Booking retrieval and authorized Tutor schedule inspection.

---

### 1. Authentication and Global Security Protocols

All endpoints specified in this document reuse the shared authentication, session validation, and privacy mechanisms established in `F-S1-01` and `F-S1-02`:

1. **Session Cookie:** Requires HttpOnly session cookie (`nuttiew_session` in production, `nuttiew_session_dev` in local/test). Unauthenticated requests immediately fail with `401 UNAUTHENTICATED`.
2. **Role Enforcement:** Server guards enforce role boundaries before executing business logic:
   - Customer endpoints enforce `requireRole('Customer')`.
   - Tutor endpoints enforce `requireRole('Tutor')`.
   - Any cross-role query returns `403 FORBIDDEN`.
3. **Session Binding Header:** Every successful `200 OK` response returns the `X-NutTiew-Session-Binding` header computed as `SHA-256("nuttiew-ui-binding:v1\0" + userId + "\0" + sessionId)`.
4. **Cache Control:** Every response includes `Cache-Control: no-store` to prevent private Booking records from caching on intermediary proxies or browser caches.
5. **No Query Parameters:** In Sprint 1, no filtering, sorting, or pagination query parameters are supported. If `Object.keys(req.query).length > 0`, the endpoint rejects the request with `400 INVALID_INPUT`.

---

### 2. Customer Endpoints

#### 2.1 List Own Bookings

Retrieves all Bookings owned by the currently authenticated Customer.

- **Method / Path:** `GET /api/v1/customer/bookings`
- **Authorization:** Authenticated Customer only (`role = Customer`).
- **Query Parameters:** None permitted. Any query string produces `400 INVALID_INPUT`.
- **Ordering:** Deterministic ascending order: `startsAt ASC, id ASC`.
- **Evaluation Snapshot Uniformity:** `meta.evaluatedAt` represents a single server evaluation timestamp captured at statement execution (`statement_timestamp()`). This exact timestamp is applied uniformly to compute `displayStatus` across all returned items. Even when no bookings exist (`data: []`), `meta.evaluatedAt` is always populated as an ISO-8601 UTC timestamp.

**Success Response ( `200 OK` )**


```
{
  "data": [
    {
      "id": "e4f8d53b-013d-4c57-891a-7b3c2e1f4001",
      "slotId": "a1b2c3d4-e5f6-7a8b-9c0d-1e2f3a4b5c6d",
      "tutorId": "f7a8b9c0-d1e2-3a4b-5c6d-7e8f9a0b1c2d",
      "tutorRef": "TUTOR-f7a8b9c0",
      "startsAt": "2026-11-10T09:00:00.000Z",
      "endsAt": "2026-11-10T10:00:00.000Z",
      "status": "Booked",
      "displayStatus": "Booked",
      "createdAt": "2026-11-09T08:30:00.000Z"
    },
    {
      "id": "b3c2e1f4-013d-4c57-891a-e4f8d53b0002",
      "slotId": "9c0d1e2f-3a4b-5c6d-a1b2-c3d4e5f67a8b",
      "tutorId": "5c6d7e8f-9a0b-1c2d-f7a8-b9c0d1e23a4b",
      "tutorRef": "TUTOR-5c6d7e8f",
      "startsAt": "2026-11-08T03:00:00.000Z",
      "endsAt": "2026-11-08T04:00:00.000Z",
      "status": "Booked",
      "displayStatus": "Past",
      "createdAt": "2026-11-07T14:15:00.000Z"
    }
  ],
  "meta": {
    "requestId": "9c5a1e2f-3b4c-5d6e-7f8a-9b0c1d2e3f4a",
    "evaluatedAt": "2026-11-09T11:30:00.000Z"
  }
}
```


---

### 2.2 Retrieve Booking Detail

Retrieves full details for a single specific Booking owned by the authenticated Customer.

- **Method / Path:** `GET /api/v1/customer/bookings/:id`
- **Authorization:** Authenticated Customer only ( `role = Customer` ).
- **Path Parameter:**
  - `id` (string, required): A standard 36-character UUID format.
- **Privacy Refusal Invariant:**
  - If the requested `:id` does not exist in the database, OR if it exists but belongs to a different Customer, the server returns `404 BOOKING_NOT_FOUND`.
  - The server **MUST NOT** return `403 FORBIDDEN` for another user's valid Booking ID, as returning `403` leaks the existence of that record to an unauthorized prober.

**Success Response ( `200 OK` )**


```
{
  "data": {
    "id": "e4f8d53b-013d-4c57-891a-7b3c2e1f4001",
    "slotId": "a1b2c3d4-e5f6-7a8b-9c0d-1e2f3a4b5c6d",
    "tutorId": "f7a8b9c0-d1e2-3a4b-5c6d-7e8f9a0b1c2d",
    "tutorRef": "TUTOR-f7a8b9c0",
    "startsAt": "2026-11-10T09:00:00.000Z",
    "endsAt": "2026-11-10T10:00:00.000Z",
    "status": "Booked",
    "displayStatus": "Booked",
    "createdAt": "2026-11-09T08:30:00.000Z",
    "updatedAt": "2026-11-09T08:30:00.000Z"
  },
  "meta": {
    "requestId": "8a7b6c5d-4e3f-2a1b-0c9d-8e7f6a5b4c3d",
    "evaluatedAt": "2026-11-09T11:30:00.000Z"
  }
}
```


---

### 3. Tutor Endpoints

#### 3.1 List Tutor Own Slots (Updated with Dynamic Occupancy)

Fulfills `FR-S1-07` : A Tutor must be able to view their own Slots including whether each is `Unoccupied` or `Occupied` .

- **Method / Path:** `GET /api/v1/tutor/slots`
- **Authorization:** Authenticated Tutor only ( `role = Tutor` ).
- **Query Parameters:** None permitted ( `Object.keys(req.query).length === 0` ).
- **Behavior Update:** In `apps/api/src/slots.ts` , `occupancy` is derived via left-join or subquery against active `Booking` records ( `status = 'Booked' AND currentSlotId = Slot.id` ). If an active booking exists, `occupancy: 'Occupied'` ; otherwise `occupancy: 'Unoccupied'` .

**Success Response ( `200 OK` )**


```
{
  "data": [
    {
      "id": "a1b2c3d4-e5f6-7a8b-9c0d-1e2f3a4b5c6d",
      "startsAt": "2026-11-10T09:00:00.000Z",
      "endsAt": "2026-11-10T10:00:00.000Z",
      "lifecycle": "Offered",
      "occupancy": "Occupied"
    },
    {
      "id": "f6e5d4c3-b2a1-0f9e-8d7c-6b5a4f3e2d1c",
      "startsAt": "2026-11-10T11:00:00.000Z",
      "endsAt": "2026-11-10T12:00:00.000Z",
      "lifecycle": "Offered",
      "occupancy": "Unoccupied"
    }
  ],
  "meta": {
    "requestId": "7e6d5c4b-3a2f-1e0d-9c8b-7a6f5e4d3c2b"
  }
}
```


---

#### 3.2 List Tutor Schedule Bookings

Fulfills `FR-S1-15` & `AC-S1-32` : An authorized Tutor inspects Bookings on their own schedule.

- **Method / Path:** `GET /api/v1/tutor/bookings`
- **Authorization:** Authenticated Tutor only ( `role = Tutor` ).

- **Query Parameters:** None permitted. Any query parameters produce `400 INVALID_INPUT`.
- **Query Predicate:** Filters strictly by `Slot.tutorId = principal.userId` and `Booking.status = 'Booked'`.
- **Privacy Guarantee:** Excludes other Tutors' bookings. Represents Customer identity as a pseudonymous truncated reference (`customerRef: "CUST-" + customerId.slice(0, 8)`), omitting Customer PII (name, email, phone) and isolating internal customer UUIDs from the Tutor wire DTO. Note: this is pseudonymous data minimization, not an irreversible cryptographic anonymization. Never returns password hashes, session cookies, or foreign contact details.

**Success Response (`200 OK`)**

```
{
  "data": [
    {
      "id": "e4f8d53b-013d-4c57-891a-7b3c2e1f4001",
      "slotId": "a1b2c3d4-e5f6-7a8b-9c0d-1e2f3a4b5c6d",
      "tutorId": "f7a8b9c0-d1e2-3a4b-5c6d-7e8f9a0b1c2d",
      "customerRef": "CUST-e4f8d53b",
      "startsAt": "2026-11-10T09:00:00.000Z",
      "endsAt": "2026-11-10T10:00:00.000Z",
      "status": "Booked",
      "displayStatus": "Booked",
      "createdAt": "2026-11-09T08:30:00.000Z"
    }
  ],
  "meta": {
    "requestId": "1a2b3c4d-5e6f-7a8b-9c0d-1e2f3a4b5c6d",
    "evaluatedAt": "2026-11-09T11:30:00.000Z"
  }
}
```

---

### 4. Status and Display Classification (`Q30`, `FR-S1-17`, `BR-S1-22`)

The API explicitly returns two separate status fields to cleanly distinguish database business status from time-derived display status:

| Field | Possible Values | Semantics | |
|---|---|---|---|
| `status` | `'Booked'` (or `'Cancelled'` in future sprints) | Authoritative database status persisted in the `Booking.status` column. | |
| `displayStatus` | `'Booked'` \ | `'Past'` | Time-derived presentation status computed relative to the single statement evaluation snapshot `meta.evaluatedAt`. If `endsAt <= meta.evaluatedAt`, `displayStatus` is `'Past'`; if `endsAt > meta.evaluatedAt`, `displayStatus` is `'Booked'`. |

**Rule:** `displayStatus = 'Past'` is an informative presentation label. It **never** causes the row in PostgreSQL to be marked as `Completed`, nor does it release the Slot from occupancy. Both list endpoints and single-detail endpoints evaluate `displayStatus` using this single snapshot mechanism, and empty lists still return a valid ISO-8601 UTC `meta.evaluatedAt`.

---

### 5. Structured Error Responses

All error responses adhere to the standard error envelope `{ error: { code, message }, requestId }`:

| HTTP Status | Error Code | Trigger Condition |
|---|---|---|
| `400 Bad Request` | `INVALID_INPUT` | Unrecognized query parameters, malformed `:id` (non-UUID), or invalid payload. |
| `401 Unauthorized` | `UNAUTHENTICATED` | Missing, expired, revoked, or invalid session cookie. |
| `403 Forbidden` | `FORBIDDEN` | Authenticated user lacks required role (e.g. Tutor requesting Customer endpoint, or Customer requesting Tutor endpoint). |

| HTTP Status | Error Code | Trigger Condition |
| --- | --- | --- |
| `404 Not Found` | `BOOKING_NOT_FOUND` | Booking ID does not exist, or exists but belongs to a different Customer. |
| `503 Service Unavailable` | `SERVICE_UNAVAILABLE` | Database connection failure or transient pool exhaustion. |

```
{
  "error": {
    "code": "BOOKING_NOT_FOUND",
    "message": "Booking not found"
  },
  "requestId": "3d4e5f6a-7b8c-9d0e-1f2a-3b4c5d6e7f8a"
}
```

---

### E.6.4 F-S1-05 Protected Booking Retrieval Data Contract (data-spec.md)

> **Documentation contract only; not implemented yet.**
> Issue #17. This document defines the read-only database queries, data projection models, privacy transformations, and consistency guarantees for F-S1-05.

---

#### 1. Schema Authority and Read-Only Boundary

F-S1-05 introduces **zero database schema modifications**, zero new tables, zero new columns, and zero migrations. It reads from the existing canonical tables established in `F-S1-01` (Auth), `F-S1-02` (Slots), and `D1-08A/B` (Booking Data Foundation):

- `"User"` : Authentication identity, roles ( `Customer` , `Tutor` ), account status ( `isActive` ).
- `"Slot"` : 60-minute appointment windows ( `startsAt` , `endsAt` ), owner reference ( `tutorId` ), lifecycle ( `Offered` , `Withdrawn` ).
- `"Booking"` : Committed reservations ( `id` , `customerId` , `currentSlotId` , `startsAt` , `endsAt` , `status` , `createdAt` , `updatedAt` ).

All database access in F-S1-05 consists of pure `SELECT` queries executed at PostgreSQL's default `READ COMMITTED` isolation level against the committed MVCC state. No transaction locks ( `FOR UPDATE` or `FOR SHARE` ) are acquired.

---

#### 2. Server-Authoritative Queries and Projections

##### 2.1 Customer: List Own Bookings

Retrieves all Bookings belonging strictly to the authenticated Customer ( `customerId = principal.userId` ). All rows in the query share a single uniform evaluation snapshot derived via `statement_timestamp()` , preserved as `timestamptz` throughout SQL comparison to prevent session timezone drift:

```
WITH eval_snapshot AS (
  SELECT statement_timestamp() AS evaluated_at
)
SELECT
  b."id",
  b."currentSlotId" AS "slotId",
  s."tutorId",
  to_char(b."startsAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "startsAt",
  to_char(b."endsAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "endsAt",
  b."status",
  to_char(b."createdAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "createdAt",
  CASE
    WHEN b."endsAt" <= s_clock.evaluated_at THEN 'Past'
    ELSE 'Booked'
  END AS "displayStatus",
  to_char(s_clock.evaluated_at AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "evaluatedAt"
FROM eval_snapshot AS s_clock
CROSS JOIN "Booking" AS b
INNER JOIN "Slot" AS s ON s."id" = b."currentSlotId"
WHERE b."customerId" = $1
ORDER BY b."startsAt" ASC, b."id" ASC;
```

**Data Mapping Rules:**

- `tutorRef`: Generated as `"TUTOR-" + row.tutorId.slice(0, 8)`.
- `displayStatus`: Derived conditionally in SQL relative to `s_clock.evaluated_at`. If `endsAt <= evaluated_at`, `displayStatus = 'Past'`; otherwise `'Booked'`. Database `status` remains strictly `'Booked'`.
- `timestamptz` Integrity: `s_clock.evaluated_at` is preserved as `timestamptz` throughout SQL comparison against `b."endsAt"`. Converting `statement_timestamp()` via `AT TIME ZONE 'UTC'` in the CTE would strip timezone information into a naive timestamp (`timestamp without time zone`), causing PostgreSQL to interpret it using the session's active `TimeZone` (e.g. `Asia/Bangkok`), skewing comparisons by 7 hours. Preserving `timestamptz` guarantees absolute, timezone-independent comparison.
- `meta.evaluatedAt`: In multi-row results, the uniform `evaluatedAt` string (formatted explicitly `AT TIME ZONE 'UTC'`) is extracted for `meta.evaluatedAt`. When the query returns 0 rows (`data: []`), the application service captures `statement_timestamp()` so that `meta.evaluatedAt` is always populated as a valid ISO-8601 UTC timestamp.

---

### 2.2 Customer: Get Single Booking Detail

Retrieves one specific Booking by ID, strictly verifying ownership (`b."id" = $1 AND b."customerId" = $2`), using the same single statement evaluation timestamp preserved as `timestamptz`:

```
WITH eval_snapshot AS (
  SELECT statement_timestamp() AS evaluated_at
)
SELECT
  b."id",
  b."currentSlotId" AS "slotId",
  s."tutorId",
  to_char(b."startsAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "startsAt",
  to_char(b."endsAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "endsAt",
  b."status",
  to_char(b."createdAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "createdAt",
  to_char(b."updatedAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "updatedAt",
  CASE
    WHEN b."endsAt" <= s_clock.evaluated_at THEN 'Past'
    ELSE 'Booked'
  END AS "displayStatus",
  to_char(s_clock.evaluated_at AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "evaluatedAt"
FROM eval_snapshot AS s_clock
CROSS JOIN "Booking" AS b
INNER JOIN "Slot" AS s ON s."id" = b."currentSlotId"
WHERE b."id" = $1 AND b."customerId" = $2;
```

**Refusal Policy:**

If the query returns 0 rows, the application throws `BookingError(404, 'BOOKING_NOT_FOUND')`. This completely prevents an attacker from guessing Booking UUIDs to verify their existence.

---

#### 2.3 Tutor: List Own Slots with Dynamic Occupancy

Replaces the hardcoded `'Unoccupied'` in `listOwnSlots` with an active `Booking` lookup:

```
SELECT
  s."id",
  to_char(s."startsAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "startsAt",
  to_char(s."endsAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "endsAt",
  s."lifecycle",
  CASE
    WHEN b."id" IS NOT NULL THEN 'Occupied'
    ELSE 'Unoccupied'
  END AS "occupancy"
FROM "Slot" AS s
LEFT JOIN "Booking" AS b
  ON b."currentSlotId" = s."id" AND b."status" = 'Booked'
WHERE s."tutorId" = $1
ORDER BY s."startsAt" ASC, s."id" ASC;
```

---

#### 2.4 Tutor: List Schedule Bookings

Retrieves all Bookings scheduled on Slots owned by the authenticated Tutor ( `s."tutorId" = $1` ), evaluated against a single statement evaluation timestamp preserved as `timestamptz`:

```
WITH eval_snapshot AS (
  SELECT statement_timestamp() AS evaluated_at
)
SELECT
  b."id",
  b."currentSlotId" AS "slotId",
  s."tutorId",
  b."customerId",
  to_char(b."startsAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "startsAt",
  to_char(b."endsAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "endsAt",
  b."status",
  to_char(b."createdAt" AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "createdAt",
  CASE
    WHEN b."endsAt" <= s_clock.evaluated_at THEN 'Past'
    ELSE 'Booked'
  END AS "displayStatus",
  to_char(s_clock.evaluated_at AT TIME ZONE 'UTC', 'YYYY-MM-DD"T"HH24:MI:SS.MS"Z"') AS "evaluatedAt"
FROM eval_snapshot AS s_clock
CROSS JOIN "Booking" AS b
INNER JOIN "Slot" AS s ON s."id" = b."currentSlotId"
WHERE s."tutorId" = $1 AND b."status" = 'Booked'
ORDER BY b."startsAt" ASC, b."id" ASC;
```

**Privacy Masking and Pseudonymity:**

- The raw `customerId` column is projected in backend SQL only to construct the pseudonymous truncated reference `customerRef: "CUST-" + row.customerId.slice(0, 8)`.
- This truncated pseudonymous reference provides data minimization for the Tutor schedule view by withholding customer personal identifiers (name, email, phone) and isolating customer UUIDs from the Tutor wire DTO. It is not an irreversible cryptographic anonymization.
- The raw `customerId` UUID is **strictly excluded** from the serialized HTTP JSON response DTO.

---

### 3. Data Integrity and Privacy Invariants

| Invariant | Description |
|---|---|
| **No Schema Drift** | The canonical database schema remains untouched. |
| **No Cross-Customer Leaks** | Customer queries use `WHERE b."customerId" = $1` with parameterized SQL; cross-customer access is physically impossible. |
| **No Cross-Tutor Leaks** | Tutor queries use `WHERE s."tutorId" = $1`; one Tutor can never inspect another Tutor's schedule. |
| **No Secret Columns in DTO** | The fields `passwordHash`, `tokenDigest`, `csrfNonce`, and internal error traces are never selected. |
| **Immutable Past Records** | Elapsed appointments are computed dynamically via `endsAt <= evaluatedAt`; no database mutation occurs. |

---

## E.6.5 F-S1-05 Software Test Specification (tests.md)

> **Documentation contract only; tests are planned and not executed yet.**
> Issue #17. This document details the test strategy, test fixtures, execution steps, expected outcomes, and traceability mapping for the `RET-01..RET-17` test suite covering Protected Booking Retrieval and Authorized Tutor Schedule Inspection.

---

### 1. Traceability and Test Case Index

| Test ID | Requirement / Rule Trace | Acceptance Criteria | Validation Anchor | Target Layer & File | Summary of Verification |
|---|---|---|---|---|---|
| **RET-01** | `FR-S1-14`, `FR-S1-16`, `BR-S1-01` | **AC-S1-30** | `VC/TEST-S1-28` | API / Database (`retrieval.db.test.ts`) | Customer retrieves own committed Bookings list with Bangkok interval and `Booked` status. |
| **RET-02** | `FR-S1-14`, `FR-S1-16`, `BR-S1-15` | **AC-S1-30** | `VC/TEST-S1-28` | API / Database (`retrieval.db.test.ts`) | Customer retrieves own single Booking detail by valid UUID. |
| **RET-03** | `FR-S1-04`, `FR-S1-14`, `BR-S1-15`, `NFR-S1-01` | **AC-S1-31** | `VC/TEST-S1-29` | API / Database (`retrieval.db.test.ts`) | Cross-Customer probe: Customer B requests Customer A's Booking ID; returns safe `404 BOOKING_NOT_FOUND`. |
| **RET-04** | `FR-S1-15`, `BR-S1-16` | **AC-S1-32** | `VC/TEST-S1-30` | API / Database (`retrieval.db.test.ts`) | Tutor retrieves Bookings scheduled on their own Slots; pseudonymous `customerRef` rendered without PII leakage. |
| **RET-05** | `FR-S1-07` | **AC-S1-32** | `VC/TEST-S1-30` | API / Database (`retrieval.db.test.ts`) | Tutor own-slots list (`/tutor/slots`) projects dynamic `occupancy: 'Occupied'` for booked Slot, `'Unoccupied'` for unbooked. |
| **RET-06** | `FR-S1-04`, `FR-S1-15`, `BR-S1-16`, `NFR-S1-01` | **AC-S1-33** | `VC/TEST-S1-31` | API / Database (`retrieval.db.test.ts`) | Cross-Tutor schedule isolation: Tutor B cannot inspect Tutor A's schedule bookings. |
| **RET-07** | `FR-S1-17`, `BR-S1-14`, `BR-S1-22`, `Q30`, `BR-S1-12`, `NFR-S1-06` | **AC-S1-34** | `VC/TEST-S1-32` | API / Database (`retrieval.db.test.ts`) | Elapsed appointment displays `displayStatus: 'Past'`, while database `status` remains `'Booked'`, never `'Completed'`. |

| Test ID | Requirement / Rule Trace | Acceptance Criteria | Validation Anchor | Target Layer & File | Summary of Verification |
|---|---|---|---|---|---|
| **RET-08** | `FR-S1-04`, `AC-S1-05` | — | `VC/TEST-S1-05` | API Guard (`retrieval.db.test.ts`) | Anonymous callers receive `401 UNAUTHENTICATED` on all customer and tutor retrieval endpoints. |
| **RET-09** | `FR-S1-04`, `AC-S1-06` | — | `VC/TEST-S1-06` | API Guard (`retrieval.db.test.ts`) | Role boundary: Authenticated Tutor calling Customer booking endpoints receives `403 FORBIDDEN`. |
| **RET-10** | `FR-S1-04`, `AC-S1-06` | — | `VC/TEST-S1-06` | API Guard (`retrieval.db.test.ts`) | Role boundary: Authenticated Customer calling Tutor booking endpoints receives `403 FORBIDDEN`. |
| **RET-11** | `NFR-S1-08` | — | — | API Input (`retrieval.db.test.ts`) | Malformed non-UUID in path parameter (`/api/v1/customer/bookings/invalid-id`) returns `400 INVALID_INPUT`. |
| **RET-12** | `NFR-S1-08` | — | — | API Input (`retrieval.db.test.ts`) | Unexpected query parameters on list and detail endpoints return `400 INVALID_INPUT`. |
| **RET-13** | `NFR-S1-01`, `NFR-S1-08` | — | `VC/TEST-S1-35` | Security / Privacy (`retrieval.db.test.ts`) | Full JSON response inspection: Zero leakage of password hashes, session tokens, or unapproved contact data. |
| **RET-14** | `FR-S1-16`, `NFR-S1-03` | **AC-S1-30** | `VC/TEST-S1-28` | Persistence / Process Lifecycle (`retrieval.db.test.ts`) | Server restart persistence: Process termination + new DB connection pool reading persistent DB returns identical committed Bookings. |
| **RET-15** | `FR-S1-14`, `FR-S1-17`, `BR-S1-12`, `Q29`, `NFR-S1-06`, `NFR-S1-09` | **AC-S1-30**, **AC-S1-34** | `VC/TEST-S1-28`, `VC/TEST-S1-32` | Playwright E2E (`e2e/retrieval.spec.ts`) | Customer browser UI: Navigates to My Bookings, views upcoming & past badges, checks Bangkok time, opens detail modal. |
| **RET-16** | `FR-S1-04`, `FR-S1-07`, `FR-S1-15`, `BR-S1-16`, `NFR-S1-01` | **AC-S1-31**, **AC-S1-32** | `VC/TEST-S1-29`, `VC/TEST-S1-30` | Playwright E2E (`e2e/retrieval.spec.ts`) | Tutor browser UI: Inspects schedule bookings; Customer B cannot see Customer A's booking in UI list/modal; direct API probe returns safe 404. |
| **RET-17** | `FR-S1-17`, `BR-S1-22`, `Q30`, `NFR-S1-06` | **AC-S1-34** | `VC/TEST-S1-32` | API / Evaluator (`retrieval.db.test.ts`) | Statement snapshot uniformity, empty list metadata, exact Q30 boundary, and session TimeZone independence (`SET LOCAL TIME ZONE 'UTC'` vs `'Asia/Bangkok'`). |

---

### 2. Detailed Test Specifications

#### RET-01: Customer Lists Own Committed Bookings

- **Goal:** Verify that an authenticated Customer can retrieve their own list of committed Bookings in deterministic ascending order.
- **Setup:**
  - Create Customer A and two Tutors (Tutor 1, Tutor 2).
  - Create two Slots (Slot 1 at +2h, Slot 2 at +5h).
  - Insert two committed Bookings for Customer A.
  - Create Customer B with a separate Booking on Slot 3.
- **Execution:** Customer A calls `GET /api/v1/customer/bookings`.

- **Expected Outcome:**
  - HTTP `200 OK`.
  - Response array contains exactly 2 items belonging to Customer A.
  - Customer B's Booking is completely omitted.
  - Response headers include `X-NutTiew-Session-Binding` and `Cache-Control: no-store`.

---

**RET-02: Customer Retrieves Single Booking Detail**

- **Goal:** Verify that an authenticated Customer can fetch complete details of their own Booking by ID.
- **Execution:** Customer A calls `GET /api/v1/customer/bookings/:id` with Customer A's Booking ID.
- **Expected Outcome:**
  - HTTP `200 OK`.
  - Body contains `data.id`, `data.slotId`, `data.tutorId`, `data.tutorRef`, `data.startsAt`, `data.endsAt`, `data.status = 'Booked'`, and `data.createdAt`.

---

**RET-03: Cross-Customer Access Refusal (Safe 404)**

- **Goal:** Prove that Customer B cannot inspect Customer A's Booking even if the exact UUID is known (`AC-S1-31`).
- **Setup:** Customer A owns Booking `UUID-A`. Customer B is authenticated.
- **Execution:** Customer B calls `GET /api/v1/customer/bookings/UUID-A`.
- **Expected Outcome:**
  - HTTP `404 Not Found` with `{ error: { code: 'BOOKING_NOT_FOUND', message: 'Booking not found' } }`.
  - Server does **NOT** return `403 FORBIDDEN` (which would confirm existence).
  - Zero private data is returned in the response body.

---

**RET-04: Tutor Lists Schedule Bookings**

- **Goal:** Verify that a Tutor can retrieve Bookings scheduled on their own Slots (`AC-S1-32`).
- **Setup:**
  - Tutor 1 has Slot 1 with a committed Booking by Customer A.
  - Tutor 2 has Slot 2 with a committed Booking by Customer B.
- **Execution:** Tutor 1 calls `GET /api/v1/tutor/bookings`.
- **Expected Outcome:**
  - HTTP `200 OK`.
  - Response contains Slot 1's Booking.
  - Customer identity is represented as pseudonymous `customerRef: "CUST-" + customerAId.slice(0, 8)` for data minimization; customer name, email, and phone are never disclosed, and raw `customerId` UUID is excluded.
  - Slot 2's Booking (Tutor 2) is completely absent.

---

**RET-05: Tutor Own-Slots Dynamic Occupancy**

- **Goal:** Verify that `GET /api/v1/tutor/slots` dynamically reports `occupancy: 'Occupied'` when booked, and `'Unoccupied'` when not booked (`FR-S1-07`).
- **Setup:** Tutor 1 creates two Slots: Slot 1 (booked by Customer A) and Slot 2 (unbooked).
- **Execution:** Tutor 1 calls `GET /api/v1/tutor/slots`.
- **Expected Outcome:**
  - HTTP `200 OK`.

- Slot 1 has `occupancy: 'Occupied'`.
- Slot 2 has `occupancy: 'Unoccupied'`.

---

**RET-06: Cross-Tutor Schedule Isolation**

- **Goal:** Verify that Tutor B cannot read or discover Tutor A's schedule bookings (`AC-S1-33`).
- **Execution:** Tutor B calls `GET /api/v1/tutor/bookings`.
- **Expected Outcome:**
  - Response array contains zero items from Tutor A.
  - API accepts no query parameters (e.g. `?tutorId=...` produces `400 INVALID_INPUT`).

---

**RET-07: Time-Derived "Past" Appointment Display (`Q30`, `AC-S1-34`, `BR-S1-14/22`, `NFR-S1-06`)**

- **Goal:** Verify that an elapsed Booking displays as `Past` without modifying database state or asserting `Completed`.
- **Historical Fixture Feasibility Protocol:**
  - In canonical database schemas, DB triggers prevent creating past slots (`slot_overlap_s1`) or booking with lead time <60m (`booking_guard_s1()` with `P0B02`). The test suite in Part F must NOT alter or disable triggers in the shared public schema.
  - **Authorized Test Strategy for Part F:**
    - **Method A (Query Evaluation Snapshot / Injected Clock):** Seed a valid future Slot and Booking (>60m notice) passing all canonical guards. Execute the retrieval evaluation specifying an evaluation snapshot `evaluatedAt >= endsAt`. Assert that `displayStatus: 'Past'`, `meta.evaluatedAt` reflects the evaluation time, and database `Booking.status` remains strictly `'Booked'` without database mutation.
    - **Method B (Isolated Disposable Ephemeral DB Seed):** In an ephemeral, disposable test container (never in shared/production schema), seed historical rows under a localized seed script with triggers re-enabled before test execution, without ever touching shared/canonical database schemas.
- **Execution:** Customer opens `GET /api/v1/customer/bookings/:id`.
- **Expected Outcome:**
  - Response body contains `displayStatus: 'Past'`, but `status: 'Booked'`.
  - Direct database inspection via `ownerPool.query`: `Booking.status` column is strictly `'Booked'`.
  - Associated Slot remains occupied and is not automatically released.

---

**RET-08..RET-10: Authentication and Role Boundaries**

- **RET-08:** Anonymous call to `/api/v1/customer/bookings` or `/api/v1/tutor/bookings` -> `401 UNAUTHENTICATED`.
- **RET-09:** Tutor session calling `/api/v1/customer/bookings` -> `403 FORBIDDEN`.
- **RET-10:** Customer session calling `/api/v1/tutor/bookings` or `/api/v1/tutor/slots` -> `403 FORBIDDEN`.

---

**RET-11..RET-13: Input Validation and Privacy Leak Checks**

- **RET-11:** `GET /api/v1/customer/bookings/12345-invalid` -> `400 INVALID_INPUT`.
- **RET-12:** `GET /api/v1/customer/bookings?filter=all` -> `400 INVALID_INPUT`.
- **RET-13:** Stringify full response bodies across all endpoints; assert absence of substring `"passwordHash"`, `"tokenDigest"`, `"csrfNonce"`, or unmasked private emails.

---

**RET-14: Persistence Across Application Process Restart and Pool Reconnection (`FR-S1-16`, `NFR-S1-03`)**

- **Goal:** Prove that committed Bookings survive complete application process shutdown, connection pool termination, and restart against the persistent database.
- **Execution:**

1. Commit a valid Slot and Booking on running API instance 1.
2. Explicitly disconnect and terminate active database connection pool ( `prisma.$disconnect()` / `pool.end()` ).
3. Spawn an entirely separate Node.js process / fresh connection pool against the same persistent PostgreSQL database.
4. Call `GET /api/v1/customer/bookings` from the newly spawned process/pool.

- **Expected Outcome:** Returns the exact committed Booking with identical IDs, timestamps, and status, proving durable persistence across process lifecycles.

---

**RET-15 & RET-16: Playwright Edge Browser E2E Tests**

- **RET-15 (Customer E2E):** Customer logs in, navigates to "การจองของฉัน", verifies Bangkok time formatting ( `d MMM yyyy, HH:mm – HH:mm น.` ), verifies upcoming badge ( `ยืนยันแล้ว` , `#eef2f7` ) and elapsed badge ( `สิ้นสุดแล้ว` , `#f1f3f6` ), clicks "ดูรายละเอียด" to open modal, verifies Booking UUID and details, and presses `Escape` or close button to dismiss modal.
- **RET-16 (Tutor E2E & Negative Privacy Isolation):**
  - Tutor logs in, views schedule agenda with "มีผู้จองแล้ว (Occupied)" amber badge ( `#fff7ed` / `#f47736` ) and unbooked slots with "ว่าง (เปิดรับจอง)", and verifies schedule bookings list displaying pseudonymous `customerRef` .
  - Customer B logs in to their own account; Customer A's booking is absent from the list. Customer B cannot open Customer A's booking modal.
  - Direct API probe: Customer B issues `GET /api/v1/customer/bookings/<CustomerA_BookingId>` and verifies safe `404 BOOKING_NOT_FOUND` response with zero data disclosure.

---

**RET-17: Single Statement Evaluation Snapshot Uniformity, Empty List Metadata, and Q30 Exact Boundary ( `Q30` , `FR-S1-17` , `BR-S1-22` , `NFR-S1-06` )**

- **Goal:** Verify that `meta.evaluatedAt` is a single uniform evaluation snapshot, is present on empty responses, and cleanly governs the Q30 boundary.
- **Scenarios:**
  1. **Empty List Metadata:** An authenticated Customer with 0 bookings calls `GET /api/v1/customer/bookings` . Expected: `200 OK` with `data: []` and a valid ISO-8601 UTC `meta.evaluatedAt` timestamp.
  2. **Multi-Row Snapshot Uniformity:** A Customer with multiple bookings calls `GET /api/v1/customer/bookings` . Expected: all rows project `displayStatus` based on the exact single evaluation timestamp that matches `meta.evaluatedAt` .
  3. **Q30 Exact Boundary:** For an appointment ending at $T$:
     - When evaluated at $T - 1\text{s}$: `displayStatus: 'Booked'` , `status: 'Booked'` .
     - When evaluated at $T$: `displayStatus: 'Past'` , `status: 'Booked'` .
     - When evaluated at $T + 1\text{s}$: `displayStatus: 'Past'` , `status: 'Booked'` .
     - Database row check: in all three states, `Booking.status` remains `'Booked'` , never mutating to `'Completed'` .
  4. **Session TimeZone Independence ( `SET LOCAL TIME ZONE` ):** Execute retrieval evaluation query with `SET LOCAL TIME ZONE 'UTC'` and `SET LOCAL TIME ZONE 'Asia/Bangkok'` . Verify that because `s_clock.evaluated_at` is preserved as `timestamptz` throughout SQL comparison ( `endsAt <= s_clock.evaluated_at` ), the computed `displayStatus` ('Booked' vs 'Past') is strictly identical across different session timezones, completely avoiding naive timestamp interpretation bugs.

---

### 3. Part F Execution Status

All 17 test cases ( `RET-01..RET-17` ) are fully implemented and verified **PASS (100%)**. Complete execution logs, observed command outcomes, and TDD evidence are documented in `verification-ledger.md` .

---

# Part F: Sprint 1 Implementation, Verification & Release Evidence

## 1. Truthful Automated Test Execution & CI Record

Automated verification was executed across both local Windows 11 (Node v24.14.0, PostgreSQL 17.2 + `btree_gist` 1.7, Microsoft Edge / Chromium) and GitHub Actions Ubuntu 24.04 runners (Node 24, PostgreSQL 18, Microsoft Edge). All domain code (`apps/api/`, `apps/web/`) and Playwright journey tests (`e2e/`) have remained unchanged since verified snapshot `e591f72` (application logic from `sprint1@9d24fca`, plus `e2e/sprint1.journey.spec.ts` added in `e591f72`).

| Verification Gate / Suite | Execution Command | Environment | Passed | Failed | Skipped | Distinct Total |
|---|---|---|---|---|---|---|
| **Pure Domain Unit & Contract Tests** | `npm test` | Local + CI (Node 24) | **29** | 0 | 0 | **29** |
| **Real PostgreSQL DB Integration & Concurrency** | `npm run test:db -w @nuttiew/api` | Local (PG 17.2) + CI (PG 18) | **106** | 0 | 0 | **106** |
| **Browser End-to-End Suite (incl. Sprint 1 Journey)** | `npx playwright test` | Local + CI (MS Edge) | **64** | 0 | 0 | **64** |
| **TypeScript Static Typecheck** | `npm run typecheck` | Local + CI | 0 errors | 0 | - | **Clean** |
| **Production Build** | `npm run build` | Local + CI | Clean | 0 | - | **Clean** |
| **Git Whitespace & Patch Check** | `git diff --check` | Local | Clean | 0 | - | **Clean** |

> **Total Distinct Automated Tests:** `29` (Unit) + `106` (DB) + `64` (E2E) = `199` **Distinct Tests (`199` Passed, `0` Failed, `0` Skipped)**

> **Accounting & CI Incident Transparency Notes:**
> 1. **No Double-Counting:** The 64-test browser suite (`npx playwright test`) already executes `e2e/sprint1.journey.spec.ts` as test `[39/64]`. The true count of unique automated tests is **199** (29 + 106 + 64).
> 2. **CI Workflow Run Diagnosis (#42672763881):** On commit `0efa30b`, GitHub Actions Run #42672763881 Attempt 1 concluded `failure` because GitHub Actions transiently failed to dispatch the `PostgreSQL 18 / Auth / Slot / Race A` job (0 job entries/logs created, while `Unit / types / build` and `Microsoft Edge E2E` passed). Re-running the exact same workflow without file edits on Attempt 2 dispatched all 3 jobs and passed **3/3 GREEN**.
> 3. **Exact Verified Baseline Recorded:** The table above reflects local execution (Unit 29/29, PG 17.2 DB 106/106, typecheck, build) and verified GitHub Actions CI (Run 42783770373 on SHA `808b906`, **3/3 jobs PASS**). The subsequent metadata-sync commit on PR #43 updates only the cited verified baseline SHA/CI-Run fields and regenerated Deliverable 1 Markdown/PDF without modifying `apps/`, `e2e/`, migrations, Part A–E contracts, or `README.md`, and is independently gated on 3/3 GREEN CI.

## 2. Complete Stakeholder Traceability Matrices

### 2.1 Acceptance Criteria Coverage (AC-S1-01..35 → VC/TEST-S1 → Actual Executed Tests)

| AC ID | Scenario & Acceptance Requirement | Anchor ID | Executed Test File & Case | Result |
|---|---|---|---|---|
| **AC-S1-01** | Valid Customer credentials authenticate with Customer role | `VC-01/03` | `apps/api/test/auth.db.test.ts` | **PASS** |

| AC ID | Scenario & Acceptance Requirement | Anchor ID | Executed Test File & Case | Result |
|---|---|---|---|---|
| **AC-S1-02** | Valid Tutor credentials authenticate with Tutor role | `VC-01/03` | `apps/api/test/auth.db.test.ts` | **PASS** |
| **AC-S1-03** | Invalid password or unknown credentials return generic 401 | `VC-02` | `apps/api/test/auth.extended.db.test.ts` ( `AUTH-02` ) | **PASS** |
| **AC-S1-04** | Logout revokes presented Session in DB; replay rejected 401 | `VC-04` | `apps/api/test/auth.db.test.ts` | **PASS** |
| **AC-S1-05** | Anonymous request to protected routes rejected 401 | `VC-05` | `apps/api/test/guards.db.test.ts` , `retrieval.db.test.ts` ( `RET-08` ) | **PASS** |
| **AC-S1-06** | Customer forging Tutor action denied 403; schedule unchanged | `VC-06` | `apps/api/test/guards.db.test.ts` , `slots.db.test.ts` | **PASS** |
| **AC-S1-07** | Tutor A cannot inspect or mutate Tutor B's private schedule | `VC-07/31` | `apps/api/test/slots.db.test.ts` , `retrieval.db.test.ts` ( `RET-06` ) | **PASS** |
| **AC-S1-08** | Tutor creates 60-minute future Slot; persisted on own schedule | `VC-08/14` | `apps/api/test/slots.db.test.ts` | **PASS** |
| **AC-S1-09** | Same Tutor creating overlapping Offered Slot rejected ( `23P01` → 409) | `VC-09` | `apps/api/test/slots.race.db.test.ts` | **PASS** |
| **AC-S1-10** | Same Tutor creating adjacent 60-minute Slot permitted | `VC-10` | `apps/api/test/slots.db.test.ts` | **PASS** |
| **AC-S1-11** | Different Tutors offering identical interval permitted | `VC-11` | `apps/api/test/slots.db.test.ts` | **PASS** |
| **AC-S1-12** | Past or invalid Slot start rejected without persistence | `VC-12` | `apps/api/test/slots.db.test.ts` | **PASS** |
| **AC-S1-13** | Race A: Concurrent overlapping Slot writes serialize to 1 commit | `VC-37` | `apps/api/test/slots.race.db.test.ts` ( `SLOT-10/11` ) | **PASS** |
| **AC-S1-14** | Non-Bangkok browser timezone displays accurate Bangkok hours | `VC-13` | `e2e/slots.spec.ts` , `e2e/availability.spec.ts` | **PASS** |
| **AC-S1-15** | Customer browses eligible Offered Slots with Tutor ref and Bangkok time | `VC-15` | `apps/api/test/availability.db.test.ts` | **PASS** |
| **AC-S1-16** | Occupied Slots and Q05 <60m Slots excluded without Customer leakage | `VC-15/22` | `apps/api/test/availability.db.test.ts` | **PASS** |
| **AC-S1-17** | Submitting stale offer rechecks DB eligibility and rejects if taken | `VC-22` | `apps/api/test/bookings.db.test.ts` ( `BOOK-07` ), `e2e/booking.spec.ts` | **PASS** |

| AC ID | Scenario & Acceptance Requirement | Anchor ID | Executed Test File & Case | Result |
|---|---|---|---|---|
| **AC-S1-18** | Device locale outside Bangkok does not shift schedule semantics | `VC-13/15` | `e2e/availability.spec.ts` | **PASS** |
| **AC-S1-19** | Customer books eligible Offered Slot; commits `Booked` row | `VC-16` | `apps/api/test/bookings.db.test.ts` ( `BOOK-01` ) | **PASS** |
| **AC-S1-20** | Slot at 15:00 with DB `T_elig` = 14:00:00 (exact 60:00) accepted | `VC-17` | `apps/api/test/bookings.db.test.ts` ( `BOOK-02` ), `BDF-21` | **PASS** |
| **AC-S1-21** | Slot at 15:00 with DB `T_elig` = 14:00:01 (59:59) rejected ( `P0B02` → 422) | `VC-18` | `apps/api/test/bookings.db.test.ts` ( `BOOK-03` ) | **PASS** |
| **AC-S1-22** | Customer B attempting to book Slot held by Customer A rejected 409 | `VC-19` | `apps/api/test/bookings.db.test.ts` ( `BOOK-04` ) | **PASS** |
| **AC-S1-23** | Customer with Tutor A Booking rejected from overlapping Tutor B Slot (409) | `VC-20` | `apps/api/test/bookings.db.test.ts` ( `BOOK-05` ) | **PASS** |
| **AC-S1-24** | Adjacent cross-Tutor interval permitted for same Customer (201) | `VC-21` | `apps/api/test/bookings.db.test.ts` ( `BOOK-06` ) | **PASS** |
| **AC-S1-25** | Race B: Two Customers racing for one Slot serialize to <=1 commit | `VC-25` | `apps/api/test/bookings.db.test.ts` ( `BOOK-10` ) | **PASS** |
| **AC-S1-26** | Race C: Customer concurrently booking overlapping Slots across Tutors serializes | `VC-26` | `apps/api/test/bookings.db.test.ts` ( `BOOK-11` ) | **PASS** |
| **AC-S1-27** | Injected DB fault before COMMIT rolls back cleanly with 0 phantom rows | `VC-22/27/33` | `apps/api/test/bookings.db.test.ts` ( `BOOK-12` ), `booking.foundation.db.test.ts` | **PASS** |
| **AC-S1-28** | Client-forged `customerId` / `tutorId` rejected; owner derived from Session | `VC-24` | `apps/api/test/bookings.db.test.ts` ( `BOOK-09` ) | **PASS** |
| **AC-S1-29** | Same-pair natural-key retry returns 200 replay with 1 committed row | `VC-38` | `apps/api/test/bookings.db.test.ts` ( `BOOK-13..16` ), `e2e/booking.spec.ts` | **PASS** |
| **AC-S1-30** | Customer retrieves persisted private Bookings across reload & process restart | `VC-28` | `apps/api/test/retrieval.db.test.ts` ( `RET-01/02/14` ) | **PASS** |
| **AC-S1-31** | Cross-Customer probe returns safe `404 BOOKING_NOT_FOUND` | `VC-29` | `apps/api/test/retrieval.db.test.ts` ( `RET-03` ), `e2e/retrieval.spec.ts` | **PASS** |
| **AC-S1-32** | Tutor retrieves own schedule Bookings with `customerRef` and zero PII | `VC-30` | `apps/api/test/retrieval.db.test.ts` ( `RET-04/05` ) | **PASS** |
| **AC-S1-33** | Cross-Tutor schedule query blocked; Tutor B sees zero Tutor A records | `VC-31` | `apps/api/test/retrieval.db.test.ts` ( `RET-06` , `RET-16` ) | **PASS** |

| AC ID | Scenario & Acceptance Requirement | Anchor ID | Executed Test File & Case | Result |
|---|---|---|---|---|
| **AC-S1-34** | Elapsed interval projects `displayStatus: 'Past'` with `status: 'Booked'` | `VC-32` | `apps/api/test/retrieval.db.test.ts` ( `RET-07/17` ) | **PASS** |
| **AC-S1-35** | Pre-cutoff request waiting across 60:00 lock wait rejected at post-wait `T_elig` | `VC-39` | `apps/api/test/bookings.db.test.ts` ( `BOOK-17` ) | **PASS** |

### 2.2 Complete Cross-Cutting Verification Cases ( `VC-S1-34..39` )

| VC / TEST ID | Scope | Executed Verification & Honest Gate Status | Observed Result |
|---|---|---|---|
| **VC-S1-34 / TEST-S1-34** | Full UI→API→DB Sprint 1 Journey | `e2e/sprint1.journey.spec.ts` ( `[39/64]` in `npx playwright test` ) + 8 screenshots | **PASS** |
| **VC-S1-35 / TEST-S1-35** | No stored secrets/plaintext/PII leaks | `auth.db.test.ts` , `config.test.ts` , `retrieval.db.test.ts` ( `RET-13` ), `git grep` clean | **PASS** |
| **VC-S1-36 / TEST-S1-36** | Performance p95 (NFR-010) & Keyboard/WCAG (NFR-009) | `AVA-14` ( `availability.db.test.ts` ) p95 < 2.0s: **PASS**; Playwright focus/reflow checks: **PASS**; Formal manual WCAG 2.2 human assistive-tech sign-off: **NOT RUN (Manual Gate)** | **PARTIAL (Auto PASS / Manual NOT RUN)** |
| **VC-S1-37 / TEST-S1-37** | Race A (concurrent same-Tutor overlapping Slots) | `apps/api/test/slots.race.db.test.ts` ( `SLOT-10/11` ) | **PASS** |
| **VC-S1-38 / TEST-S1-38** | Same-Customer natural-key duplicate/retry | `apps/api/test/bookings.db.test.ts` ( `BOOK-13..16` ) & `e2e/booking.spec.ts` | **PASS** |
| **VC-S1-39 / TEST-S1-39** | Post-wait `T_elig` cutoff drift & Option 1 lock proof | `apps/api/test/bookings.db.test.ts` ( `BOOK-17` , `BOOK-19 / BDF-23` ) | **PASS** |

*(Also note: `AUTH-22` deterministic multi-instance Argon2 barrier stress test covers single-process barrier in `auth.barrier.db.test.ts` [PASS] while full external multi-instance mixed stress remains transparently documented as PARTIAL in `F-S1-01/tests.md` .)*

---

## 3. Concurrency Invariants & Real Database Race Verification

The NutTiew platform enforces three distinct concurrency invariants at the PostgreSQL layer, verified with independent `pg.Pool` connections, `pg_backend_pid()` , and `pg_blocking_pids()` assertions:

### 3.1 Race A: Concurrent Slot Creation by Same Tutor ( `SLOT-10/11` / `SQLSTATE 23P01` )

- **Constraint:** `offered_slot_no_overlap_per_tutor EXCLUDE USING gist ("tutorId" WITH =, tstzrange("startsAt", "endsAt", '[)') WITH &&) WHERE ("lifecycle" = 'Offered')` .
- **Observed Local Output ( `apps/api/test/slots.race.db.test.ts` on PG 17.2):**

```
  RACE_A_OBSERVED {"first":"A","holderPid":26720,"aPid":25556,"bPid":5156,"statuses":[201,409],"committed":["524d65df-c698-47f9-bc4b-902fdda60205"]}
  RACE_A_DIRECT_SQL_OBSERVED {"aPid":26720,"bPid":27588,"loserSQLSTATE":"23P01"}
```

Exactly one conflicting `Offered` slot commits ( `201 Created` ); the competing transaction blocks on GiST, raises PostgreSQL `23P01` ( `exclusion_violation` ), and returns safe `409 Conflict` .

### 3.2 Race B: Concurrent Booking on Same Offered Slot ( `BOOK-10` / `SLOT_UNAVAILABLE` )

- **Mechanism:** Ordered row lock `SELECT "id" FROM "Slot" WHERE "id" = $1 FOR UPDATE` followed by `booking_guard_s1()` and partial unique index `booking_one_active_per_slot`.
- **Observed Output ( `apps/api/test/bookings.db.test.ts` ):** Winner locks Slot, validates `Offered` and Q05, and commits `201 Created`; blocked waiter wakes after commit, sees `Slot` is occupied, and cleanly receives `409 SLOT_UNAVAILABLE`. Zero duplicate active Bookings.

### 3.3 Race C & Option 1 Interleaving Proof: Same-Customer Overlapping Cross-Tutor Bookings ( `BOOK-11` , `BOOK-19 / BDF-23` )

- **Mechanism:** Remediation migration `20261109000000_booking_guard_user_lock` replaces `booking_guard_s1()` ( `SECURITY DEFINER` ) to lock `User(customerId) FOR UPDATE` inside the `BEFORE ROW` trigger *before* locking `Slot` and *before* inserting into `booked_customer_no_overlap` GiST index.
- **Observed Local Output ( `apps/api/test/bookings.db.test.ts` on PG 17.2):**


```
  BDF23_BOOK19_EVIDENCE {"canonicalPart1A":{"slotId":"a3d9ce7f-f5dc-40e7-804a-
229c2c4c208a","roguePid":1980,"adapterUserPid":26260,"userBlockers":
[1980],"outcome":"BOOKING_NOT_ELIGIBLE"},"canonicalPart1B":{"slotId":"1b4fae3b-35f5-4961-8ab4-
073824aff944","roguePid":1980,"adapterSlotPid":26260,"slotBlockers":
[1980],"outcome":"BOOKING_NOT_ELIGIBLE"},"canonicalPart1C":{"slotId":"92d8c642-2a77-403e-a247-
941d369cd371","roguePid":1980,"adapterPid1C":26260,"rogueBlockers1C":[26260],"adapterReverseBlockers":
[],"outcome":"23P01"},"canonicalPart1C2NoStaleCommit":{"slotId":"d9f200e3-1a5d-49be-af97-
e8b884aaac38","roguePid":1980,"adapterPid1C2":26260,"adapterReverseBlockers":
[],"commitNoticeMs":3599166,"outcome":201},"canonicalPart1D":{"slotId":"a4a9ccd6-97f2-44b9-a3d1-
32004ee4b920","roguePid":1980,"adapterPid1D":26260,"rogueBlockers1D":[26260],"outcome":"23505"}}
```


Notice `adapterReverseBlockers: []` in both Part 1C and Part 1C2 — proving zero reverse GiST waits and zero `40P01` deadlocks across both adapter-initiated and direct-SQL writers. Under 10 parallel overlapping Customer requests in `BOOK-11` , exactly 1 booking commits and 9 fail safely with `409 CUSTOMER_OVERLAP` .

---

## 4. Verbatim Executable Test Excerpts (Instructor §4.2)

### 4.1 Domain-Rule Test Excerpt: Q05 60-Minute Cutoff Post-Lock Drift ( `BOOK-17` )

**Source File:** `apps/api/test/bookings.db.test.ts` , lines `855–918` (reproduced verbatim below).

**Rule Proven ( `AC-S1-35 / Q05` ):** When an eligible HTTP booking request arrives before the 60-minute cutoff ( `60m + 1.8s` ) but blocks on an active `Slot` `FOR UPDATE` lock until PostgreSQL `clock_timestamp()` crosses cutoff, `booking_guard_s1()` samples authoritative DB time *post-wait*, rejects with SQLSTATE `P0B02` ( `422 BOOKING_NOT_ELIGIBLE` ), and commits `0` rows.

```
// Verbatim excerpt from apps/api/test/bookings.db.test.ts (lines 855-918)
  it('BOOK-17 enforces Q05 at post-wait DB T_elig when HTTP arrives before cutoff and lock wait crosses cutoff', async () => {
    const tempCustomerEmail = `book-c17-${marker}@example.test`;
    const tempCustomerId = await createUser(tempCustomerEmail, 'Customer');
    const tempCustomerAuth = await loginBundle(tempCustomerEmail, tempCustomerId);
    const tempTutor = await createUser(`book-t17-${marker}@example.test`, 'Tutor');
    const nowRes = await ownerPool.query<{ now: Date }>('SELECT clock_timestamp() AS now');
    // Slot starts in 60m + 1.8s (eligible at arrival, ineligible after 2.1s lock wait)
    const slot = await createSlot(
      tempTutor,
      new Date(nowRes.rows[0].now.getTime() + 60 * 60_000 + 1_800),
    );
    const cutoff = new Date(slot.startsAt.getTime() - 60 * 60_000);

    const holder = await ownerPool.connect();
    try {
      await holder.query('BEGIN');
      await holder.query('SELECT "id" FROM "Slot" WHERE "id"=$1 FOR UPDATE', [slot.id]);
      const holderPid = await getPid(holder);

      let waiterPid = 0;
      const pendingBooking = createCustomerBooking(
        runtimePool,
        { userId: tempCustomerAuth.userId, sessionId: tempCustomerAuth.sessionId },
        slot.id,
        {
          onLockStep: async event => {
            if (event.phase === 'slot' && waiterPid === 0) {
              waiterPid = event.backendPid;
            }
          },
        },
      ).then(
        res => ({ ok: true as const, res }),
        (err: BookingError) => ({ ok: false as const, err }),
      );

      await expect.poll(() => waiterPid, { timeout: 5_000 }).toBeGreaterThan(0);
      await waitForBlockedBy(waiterPid, holderPid);

      // Hold the Slot lock until DB clock crosses cutoff
      while (true) {
        const c = await ownerPool.query<{ now: Date }>('SELECT clock_timestamp() AS now');
        if (c.rows[0].now.getTime() >= cutoff.getTime() + 150) break;
        await new Promise(resolve => setTimeout(resolve, 40));
      }

      await holder.query('COMMIT');
      const outcome = await pendingBooking;
      expect(outcome.ok).toBe(false);
      if (!outcome.ok) {
        expect(outcome.err.status).toBe(422);
        expect(outcome.err.errorCode).toBe('BOOKING_NOT_ELIGIBLE');
      }

      const persisted = await ownerPool.query<{ n: number }>(
        'SELECT count(*)::int AS n FROM "Booking" WHERE "currentSlotId"=$1',
        [slot.id],
      );
      expect(persisted.rows[0].n).toBe(0);
    } finally {
      await holder.query('ROLLBACK').catch(() => {});
      holder.release();
    }
  }, 15_000);
```

### 4.2 Authorization Test Excerpt: Cross-Customer Safe 404 & Cross-Tutor Schedule Isolation ( `RET-03` & `RET-06` )

**Source File:** `apps/api/test/retrieval.db.test.ts` , fixture setup lines `128–149` and assertions lines `214–224` ( `RET-03` ) and `278–297` ( `RET-06` ) (reproduced verbatim below).

**Rules Proven ( `AC-S1-31 / AC-S1-33 / NFR-S1-01` ):** Cross-Customer reads against another Customer's Booking ID return safe `404 BOOKING_NOT_FOUND` (preventing existence confirmation via 403), and Tutor B cannot inspect Tutor A's bookings or override ownership via query parameters ( `400 INVALID_INPUT` ).

```
// Verbatim setup excerpt from apps/api/test/retrieval.db.test.ts (lines 128-149)
    // Create 3 slots for Tutor A
    const s1 = await createSlot(tutorAId);
    slotA1Id = s1.id;
    const s2 = await createSlot(tutorAId);
    slotA2Id = s2.id;
    const s3 = await createSlot(tutorAId);
    slotA3UnbookedId = s3.id;

    // Create 1 slot for Tutor B
    const sb1 = await createSlot(tutorBId);
    slotB1Id = sb1.id;

    // Book slotA1 and slotA2 for Customer A using canonical createCustomerBooking
    const b1 = await createCustomerBooking(runtimePool, { userId: customerAId, sessionId: authCustomerA.sessionId },
slotA1Id);
    customerABooking1Id = b1.data.id;
    const b2 = await createCustomerBooking(runtimePool, { userId: customerAId, sessionId: authCustomerA.sessionId },
slotA2Id);
    customerABooking2Id = b2.data.id;

    // Book slotB1 for Customer B
    const bb = await createCustomerBooking(runtimePool, { userId: customerBId, sessionId: authCustomerB.sessionId },
slotB1Id);
    customerBBookingId = bb.data.id;
  }, 30_000);

// Verbatim RET-03 excerpt (lines 214-224)
  // RET-03: Cross-Customer Access Refusal (Safe 404)
  it('RET-03: Cross-Customer probe returns safe 404 BOOKING_NOT_FOUND (no 403 confirmation)', async () => {
    const res = await request(app)
      .get(`/api/v1/customer/bookings/${customerABooking1Id}`)
      .set('Cookie', authCustomerB.cookie);

    expect(res.status).toBe(404);
    expect(res.body.error?.code).toBe('BOOKING_NOT_FOUND');
    expect(res.body.error?.message).toBe('Booking not found');
    expect(res.body.data).toBeUndefined();
  });

// Verbatim RET-06 excerpt (lines 278-297)
  // RET-06: Cross-Tutor Schedule Isolation
  it('RET-06: Cross-Tutor schedule isolation: Tutor B cannot inspect Tutor A schedule bookings', async () => {
    const res = await request(app)
      .get('/api/v1/tutor/bookings')
      .set('Cookie', authTutorB.cookie);

    expect(res.status).toBe(200);
    const data = res.body.data;
    expect(Array.isArray(data)).toBe(true);
    expect(data.length).toBe(1);
    expect(data[0].id).toBe(customerBBookingId);
    expect(data[0].tutorId).toBe(tutorBId);

    // Any query parameters fail closed
    const queryRes = await request(app)
      .get(`/api/v1/tutor/bookings?tutorId=${tutorAId}`)
      .set('Cookie', authTutorB.cookie);
    expect(queryRes.status).toBe(400);
    expect(queryRes.body.error?.code).toBe('INVALID_INPUT');
  });
```

## 5. Verifiable TDD RED-to-Green Commit History

Every critical domain and security fix followed observable **failing proof (RED) → remediation commit (GREEN)** recorded in Git history and feature verification ledgers:


1. **Case 1: `BDF-28 / BDF-23` Option 1 Lock-Order Remediation (Issue #39 / PR #40):**
   - **RED Observation (PR #38 commit `c8ebc4a`):** Under the initial `#33` `booking_guard_s1()` trigger (locking only `Slot`), PostgreSQL's deferred `AFTER ROW` FK trigger allowed a direct-SQL writer to enter the `booked_customer_no_overlap` GiST index before locking `User`. In `BOOK-19` Part 1C, Adapter hit reverse wait `adapterReverseBlockers: [roguePid]` and SQLSTATE `40P01` deadlock, triggering the documented Option 1 Stop Gate.
   - **GREEN Fix (PR #40 commits `6bd92a8` & `da17acf`, merged `1ff4c2b`; `#16` verified commit `5dd02b9`):** Added forward-only migration `20261109000000_booking_guard_user_lock` redefining `booking_guard_s1()` (`SECURITY DEFINER`) to lock `User(customerId) FOR UPDATE` in `BEFORE ROW` before `Slot` and before index insertion. `BDF-28` reproduces legacy failure in an isolated schema (Part 1) and proves zero reverse wait (`adapterReverseBlockers: []`) on canonical schema (Part 2).
2. **Case 2: `BOOK-17` & Trigger `T_elig` Authority vs Application Heuristic (Issue #16 / PR #38):**
   - **RED / Review Finding (between commits `222b5d3` and `2e59b89`):** Application-layer heuristic `statementDurationMs >= 150` conflicted with `transaction-spec.md` §5 ("a valid 60:00 guard may still commit later"), and fixture reuse caused early overlap failure in `BOOK-17` (`docs/features/F-S1-04/verification-ledger.md`).
   - **GREEN Fix (commits `2e59b89` & `865114a`):** Removed the app duration heuristic, restored exclusive `booking_guard_s1()` post-lock `clock_timestamp()` authority, and verified `BOOK-17` rejecting cross-cutoff contention at `422 BOOKING_NOT_ELIGIBLE`.
3. **Case 3: Error Status Precedence Before Session-Binding Check (Issue #17 / PR #42):**
   - **RED Review Finding (on commit `e6d9cac`):** `apps/web/src/customer-availability.tsx` inspected `X-NutTiew-Session-Binding` before `!res.ok`, risking false session-mismatch logouts on injected/transient `404` and `503` error envelopes that omit binding headers.
   - **GREEN Fix (commit `4c60267`):** Reordered HTTP status handling before session-binding validation and added deterministic E2E regression tests `RET-15-ERR-503` and `RET-15-ERR-404` in `e2e/retrieval.spec.ts`.

---

## 6. End-to-End Vertical Journey Walkthrough & Screenshots


Executed against real React 19 UI, Express 5 API, and PostgreSQL persistence via `e2e/sprint1.journey.spec.ts`:

### Milestone 1: Tutor Logs In & Creates 60-Minute Slot





*01 Tutor Slot Created*

## Milestone 2: Customer Browses Available Tutoring Offers





*02 Customer Availability Browse*

## Milestone 3: Customer Confirms Booking





*03 Customer Booking Confirmed*

## Milestone 4: Customer Private Booking List





*04 Customer Private Bookings*

## Milestone 5: Customer Booking Detail Modal





*05 Customer Detail Modal*

## Milestone 6: Tutor Schedule View (Occupied & Pseudonymous `CUST-...`)





*06 Tutor Schedule Occupied*

## Milestone 7: Negative Business Rule Rejection (409 Conflict)




*07 Negative Conflict 409*

## Milestone 8: Negative Cross-Customer Access Refusal (Safe 404)




*08 Negative Cross Customer 404*

## 7. Substantive Teammate Peer Review Evidence

1. **Pull Request #38 — F-S1-04 Customer Exclusive Booking (`feature/16-exclusive-booking` → `sprint1`):**
   - Author: @Chxtamos | Reviewer: @Tanaboonnnnn | Issue: #16
   - Substantive interventions resolved: decoupled CSRF retry UX, session-binding rebootstrap without kicking valid Customer sessions, removed duration heuristic, discovered Part 1C FK reverse-wait deadlock leading to Issue #39 / PR #40, merged into `sprint1` at `ed78bba`.
2. **Pull Request #42 — F-S1-05 Protected Booking Retrieval (`feature/17-booking-retrieval` → `sprint1`):**
   - Author: @Chxtamos | Reviewer: @Tanaboonnnnn | Issue: #17
   - Substantive interventions resolved: decoupled Tutor slot vs booking AbortControllers, eliminated trigger tampering in E2E fixtures, fixed `!res.ok` precedence before `X-NutTiew-Session-Binding` with `RET-15-ERR-404/503`, merged into `sprint1` at `9d24fca`.
3. **Pull Request #43 — D1-10 Deliverable 1 Integration (`docs/18-deliverable-1-integration` → `sprint1`):**
   - Author: @Chxtamos | Reviewer: @Tanaboonnnnn | Issue: #18
   - Multiple rigorous review rounds resolving README least-privilege bootstrap order & seed envs, Express 5 / React 19 fidelity, canonical AC/VC mapping, complete embedded Parts A–E contracts, verbatim test excerpts, Mermaid vector verification, and computed PDF page ranges.

## 8. Team Contribution Matrix

| Contributor | Contribution | Primary Responsibilities & Deliverables |
|---|---|---|
| **Tanboon Teawsawat** (@Tanaboonnnnn) | **50%** | Requirements discovery (Q01–Q32), Whole-product SRS & Traceability Matrix, System SDS, Three-Sprint Delivery Plan, Project #6 Kanban governance, and substantive peer reviews across PRs #25–#43 |
| **Chxtamos** (@Chxtamos) | **50%** | Express 5 REST API, PostgreSQL schema/GiST constraints/triggers, Option 1 concurrency lock ordering, React 19 UI, automated Unit/DB/Playwright tests, and Deliverable 1 markdown/PDF packaging |

## 9. Academic Integrity & AI Usage Declaration

- **AI Assistant Declared:** Google Antigravity / Gemini agentic coding assistant.
- **Usage Scope:** Drafting boilerplate TypeScript interfaces, structuring `pg_blocking_pids()` concurrency test harnesses, automating Markdown/PDF compilation, and verifying cross-references.
- **Human Accountability:** All product business rules (Q01–Q32), lock-ordering architecture decisions, security trust boundaries, and peer reviews were evaluated and accepted by human team members. Zero test results or deliverables were fabricated or accepted without real execution against PostgreSQL and browser suites.

## 10. Definition of Done (DoD) Checklist (Truthful Status)

| Quality Gate / Requirement | Verification Evidence | DoD Status |
|---|---|---|
| **Whole-product Parts A–D embedded verbatim** | Complete SRS, Inventory, Traceability, System SDS & 3-Sprint Plan inside PDF | **Complete** |
| **All Sprint 1 Part E contracts embedded verbatim** | Full F-S1-01..05 + Shared Booking Data specs/UI/API/Data/Transaction/STS inside PDF | **Complete** |

| Quality Gate / Requirement | Verification Evidence | DoD Status |
| --- | --- | --- |
| **Real working UI → API → PostgreSQL vertical slice** | Verified on React 19, Express 5, PostgreSQL 17.2 (local) & 18 (CI) | **Complete** |
| **Automated verification suite** | 199 distinct tests (29 Unit + 106 DB + 64 E2E) PASS; typecheck & build clean | **Complete** |
| **Formal manual WCAG 2.2 human audit** | Automated checks PASS; manual assistive-tech sign-off remains separate manual gate | **Not Run (Manual Gate)** |
| **Reproducible README setup** | Owner DB + post-migration grants + seed env vars smoke-tested on PG 17.2 | **Complete** |
| **Staging PR #43 review & `sprint1 -> main` release PR** | PR #43 merged into sprint1 on 10 Nov 2026; reviewed sprint1-to-main release PR and tag remain outstanding | **Pending Release** |
| **Private Student IDs & LEB2 External Submission** | Student IDs withheld from public repo; team supplies IDs & final PDF to LEB2 | **Pending Release & LEB2 Handoff** |

---

*End of original Parts A-F baseline. See the following verified 10 November addendum.*

# Part F: ผลตรวจสอบเพิ่มเติมจากโค้ดล่าสุด (10 พฤศจิกายน 2569)

> ส่วนนี้เป็นหลักฐานที่ตรวจซ้ำจากโค้ดล่าสุดหลังมีการปรับหน้าปฏิทินของลูกค้า โดยเก็บเนื้อหา Parts A-E และหลักฐาน Sprint 1 เดิมไว้ครบถ้วน รายการทดสอบเก่าที่ยืนยันไว้คนละ Commit แยกจากผลทดสอบรอบนี้ชัดเจน เพื่อไม่ให้เข้าใจว่ารันทดสอบทุกชุดใหม่ทั้งหมด

## 11. เวอร์ชันที่ตรวจสอบและสถานะการส่งงาน

| รายการ | ผลที่ตรวจสอบได้ ณ วันที่ 10 พฤศจิกายน 2569 |
|---|---|
| โครงการ | NutTiew (นัตติว), Theme 1: Appointment & Scheduling |
| Repository | https://github.com/Tanaboonnnnn/CPE334-NutTiew |
| โค้ดที่เปิดและทดสอบจริง | `sprint1` Commit `9aa37c0f0acbb35b43eb4bd099f8bfac9faa18bc` |
| งาน UI ล่าสุด | Pull Request #47 เพิ่มปฏิทินรายเดือนให้ Customer, Merge เข้า `sprint1` วันที่ 10 พฤศจิกายน 2569 เวลา 20:30 น. (เวลาไทย) |
| รายงาน Deliverable 1 เดิม | PR #43 ได้ Merge เข้า `sprint1` แล้ววันที่ 10 พฤศจิกายน 2569 เวลา 16:38 น. |
| สถานะ `main` ที่ตรวจสอบ | ยังเป็น Commit `b501c18` ซึ่งไม่ใช่รุ่น `sprint1` ที่ทดสอบครั้งนี้ |
| สถานะ Release | ยังไม่ได้ยืนยัน Pull Request สำหรับ `sprint1` ไป `main` หรือ Release Tag ที่ผ่านการอนุมัติ |
| ข้อกำหนดกำหนดส่ง | เอกสาร Project Deliverable 1 v1 ระบุ 8 พฤศจิกายน 2569 เวลา 23:59 น. ผลตรวจรอบนี้อยู่หลังวันดังกล่าว จึงไม่อ้างว่าเป็นหลักฐานการส่งทันกำหนด |

สเปกที่ใช้เปรียบเทียบคือ `group_work_specs_v1.pdf` และ `project_deliverable_1_v1.pdf` ซึ่งเป็นไฟล์ v1 ที่มีอยู่ในโครงการ การอนุมัติ Theme จากอาจารย์และ Master Specification ฉบับสุดท้ายยังไม่มีหลักฐานยืนยัน จึงคงสถานะเป็นประเด็นที่ต้องตรวจสอบก่อนส่งฉบับสมบูรณ์

## 12. สภาพแวดล้อมที่รันทดสอบจริง

ครั้งนี้ดึง Commit ล่าสุดลงเครื่องแล้วเปิดใช้งานผ่าน Windows, Node.js 24.14.0, React 19, Express 5 และ PostgreSQL 18 โดยตั้งฐานข้อมูลทดสอบขึ้นใหม่แยกจากฐานข้อมูลเดิม ใช้ข้อมูลบัญชีสมมติ 1 Tutor และ 1 Customer สำหรับตรวจการทำงาน ไม่ใช้ข้อมูลส่วนตัวจริง และไม่บันทึกรหัสผ่านไว้ใน PDF หรือ Repository

การตั้งค่าฐานข้อมูลใหม่ใช้บทบาทเจ้าของ Schema และบทบาท Runtime แยกกัน จากนั้นรัน Prisma migrations ทั้งสี่รายการครบ ผลการสร้างตารางและ Constraint ผ่านทั้งหมด การทดสอบเส้นทางใช้งานทำกับ API และฐานข้อมูลจริง โดย Browser E2E เปิดหน้าเว็บจากโค้ด `9aa37c0` ไม่ใช่ภาพ Mockup

| สิ่งที่ทำในรอบนี้ | คำสั่งหรือหลักฐาน | ผล |
|---|---|---|
| ตรวจชนิดข้อมูล TypeScript | `npm run typecheck` | ผ่านทั้ง API และ Web |
| สร้างไฟล์สำหรับใช้งานจริง | `npm run build` | ผ่านทั้ง API และ Web |
| Unit/Contract Tests | `npm test` | 34 ผ่าน / 0 ไม่ผ่าน (API 29, Web Calendar 5) |
| สร้างฐานข้อมูลทดสอบ | `npm run db:generate` , `npm run db:migrate` | ผ่าน 4 migrations |
| ทดสอบเส้นทางจองครบวงจร | `npx playwright test e2e/sprint1.journey.spec.ts --reporter=line` | 1 ผ่าน / 0 ไม่ผ่าน |
| ทดสอบปฏิทินใหม่ | `npx playwright test e2e/availability.calendar.spec.ts --reporter=line` | 4 ผ่าน / 0 ไม่ผ่าน |
| ทดสอบ DB Suite ทั้งหมดรอบใหม่ | `npm run test:db -w @nuttiew/api` | ยังไม่ได้รันครบในรอบนี้; อ้างหลักฐานเดิมพร้อม SHA ใน Part F |
| ทดสอบ Browser Suite ทั้งหมดรอบใหม่ | `npx playwright test` | ยังไม่ได้รันครบในรอบนี้; รันเฉพาะ 5 กรณีข้างต้น |

| สิ่งที่ทำในรอบนี้ | คำสั่งหรือหลักฐาน | ผล |
|---|---|---|
| ตรวจ WCAG ด้วยผู้ใช้จริง/โปรแกรมอ่านหน้าจอ | การตรวจด้วยมนุษย์ | ยังไม่ได้ทำ |


ตัวเลข 199 tests ใน Part F เดิมเป็นบันทึกผลการทดสอบของ Snapshot ก่อนหน้า ไม่ใช่ผลใหม่ที่อ้างว่าได้รันครบ 199 กรณี ณ `9aa37c0` สำหรับรอบนี้ตรวจสอบผลโดยตรง 34 Unit Tests และ 5 Browser E2E Tests ซึ่งไม่ได้หมายความว่า 39 กรณีครอบคลุมชุดทดสอบทั้งหมด

## 13. ภาพจากการใช้งานจริงหลังอัปเดตหน้าปฏิทิน

ภาพเส้นทางใช้งานหลักลำดับ 01-08 ในหัวข้อ Part F ก่อนหน้านี้ ได้ถ่ายใหม่จาก `e2e/sprint1.journey.spec.ts` บนโค้ด `9aa37c0` แล้ว ได้แก่ Tutor เพิ่ม Slot, Customer ค้นหา Slot, ยืนยันการจอง, เปิดรายการจองของตน, ดูรายละเอียด, Tutor ตรวจสถานะ Occupied, การปฏิเสธ 409 และการปฏิเสธการเข้าถึงข้ามลูกค้า 404

### 13.1 หน้าปฏิทิน Customer บน Desktop (1280px)


หลังล็อกอิน Customer เห็นปฏิทินรายเดือนที่เลือกวันที่มี Slot ได้ วันว่างและวันไม่มีช่วงเวลาต่างกันอย่างชัดเจน เมื่อเลือกวันแล้วระบบแสดงกลุ่มช่วงเวลาทางด้านขวา วันที่และเวลาแสดงตาม Asia/Bangkok




*ภาพหน้าปฏิทินรายเดือนบน Desktop จาก Playwright E2E และ PostgreSQL 18 จริง*

### 13.2 แสดงจำนวนช่วงเวลาเมื่อมีข้อมูลหนาแน่น


กรณี `UX-CAL-01/03` สร้าง Slot ทดสอบมากกว่า 520 รายการใน PostgreSQL จริง จากนั้นตรวจการแสดงผลแบบค่อยเปิดเผยข้อมูล โดยเริ่มต้นเห็นไม่เกิน 6 กลุ่มช่วงเวลา มีปุ่มดูเพิ่มเติม และไม่ส่งคำขอจองจากการเลื่อนดูปฏิทิน




*ภาพทดสอบปฏิทินเมื่อมี Slot มากกว่า 520 รายการ*

### 13.3 เลือกช่วงเวลาในวันที่ต้องการ


ปฏิทินเก็บรายการเวลาตามช่วงจริง ไม่บังคับให้เป็นต้นชั่วโมง และเมื่อเปิดกลุ่มเวลาแล้วจึงแสดง Tutor ที่มี Slot ในช่วงนั้น การเลือก Slot เป็นเพียงขั้นตอนก่อนยืนยันการจอง ยังไม่ถือว่าจองสำเร็จ




*ภาพแสดงกลุ่มเวลาและตัวเลือก Tutor หลังเปิดรายละเอียด*

### 13.4 ภาพ Responsive บน Mobile (375px)

บนหน้าจอขนาดเล็กปฏิทินและรายการเวลาเรียงตามแนวตั้ง ผล Automated Test ผ่านการตรวจความกว้างและการแสดงเนื้อหาที่ 320, 375, 768, 800, 801 และ 1280 CSS pixels ทั้งนี้ยังต้องให้มนุษย์ตรวจการอ่านจอและความสะดวกในการใช้งานเพิ่มเติม




*ภาพปฏิทิน Responsive บนจอ 375px — Top-viewport excerpt (375×431 px) cropped for PDF readability from full-page capture (375×2449 px) at ../evidence/sprint1/09-after-calendar-375.png*

## 14. บันทึกการเปลี่ยนแปลงที่มีผลต่อเอกสาร

- **Part E:** เพิ่มฉบับเต็มของ `docs/features/F-S1-03/ui-decision-2026-11-10.md` สำหรับ Option A Monthly Calendar UX รวมเงื่อนไขการแสดงผล, ข้อกำหนดสิทธิ์, Timezone, Accessibility และขอบเขต API ตาม PR #45 ที่ Merge แล้ว
- **Part F:** เปลี่ยนภาพประกอบเส้นทาง 01-08 ให้เป็นภาพทดสอบจาก Commit ล่าสุด พร้อมเพิ่มการทดสอบหน้า Calendar และภาพ Responsive ในหัวข้อ 11-14
- **การติดตามหลักฐาน:** PR #47 เป็นการเปลี่ยนแปลงที่ Merge เข้า `sprint1` แล้ว แต่การส่งอาจารย์กำหนดให้มี Release ที่ได้รับการ Review บน `main` จึงยังมีงานปิด Release Gate
- **สิ่งที่ยังต้องยืนยัน:** ชื่อและรหัสนักศึกษาทั้งสองคนในไฟล์ส่ง LEB2, Master Specification ฉบับสุดท้าย, การยืนยัน Theme 1 และผลการ Merge Release ไปยัง `main`

**ขอบเขตของรายงานนี้:** ส่วนที่เป็นคำอธิบายเพิ่มเติมเขียนเป็นภาษาไทย ส่วนข้อความรายละเอียดสเปก API, Business Rules, Acceptance Criteria, Code และ Test IDs จาก Repository คงชื่อเดิมไว้เพื่อให้ตรวจสอบย้อนกลับได้ โดยไม่ปรับความหมายของข้อกำหนดที่ทีมทำไว้