A Simplified Multi-Floor Classification-Based Indoor Positioning System Study

Optimizing Grid Size and Feature Selection for ML-Based IPS

Burin Intachuen[1]   Mhadhanagul Charoenphon[1]   Tanakorn Mankhetwit[1]
Charnon Pattiyanon[2]

November 3, 2025

[1]Department of Computer Engineering, Mahidol University (International College), Thailand
[2]Department of AI and Computer Engineering, CMKL University, Thailand

Table of contents

Problem & Contributions

Problem, Approach & Contributions

Challenge: GPS fails indoors, need ML-based IPS using Wi-Fi fingerprinting

Research Gap: Limited understanding of grid size and feature selection impact

Our Contributions:

1. New evaluation metrics: AGT and ADT
2. Grid size vs. precision trade-off analysis ($1{\times}1$m to $15{\times}15$m)
3. Feature filtering impact ($1{,}799 \rightarrow 378$ BSSIDs)
4. Verified local optimal grid size can be identified ($7{\times}7$m)

Methodology

Figure 1: Four-part research methodology

Environmental Factors

Key factors identified:

1. **Grid Size**
   - Larger grids $\rightarrow$ easier classification, lower precision
   - Smaller grids $\rightarrow$ higher precision, more data collection effort

2. **Low-Relevance BSSIDs**
   - Signals from distant access points
   - Introduce noise and increase computational cost
   - Need systematic filtering approach

New Evaluation Metrics

Average Grid from Target (AGT):

$$AGT = \sqrt{(x_{target} - x_{estimate})^2 + (y_{target} - y_{estimate})^2}$$

Average Distance from Target (ADT):

$$ADT = \sqrt{[w_g \times (x_{target} - x_{estimate})]^2 + [h_g \times (y_{target} - y_{estimate})]^2}$$

- AGT: Grid-based distance (adaptable to any grid size)
- ADT: Converts AGT to physical distance in meters using grid dimensions

Grid Interpolation Approach

Figure 2: Grid aggregation visualization

Benefits:

- Avoid re-taping entire area
- Generate multiple grid sizes from 1×1m base
- Reduce human measurement errors

Method:

- Average RSSI from 5 sampling points
- Test 8 grid sizes: 1×1m to 15×15m

Dataset Overview

Table 1: Dataset metadata by grid size

Floor	Grid Size	# Grids	# Data Points
1st	1×1m	309	8,086
1st	7×7m	17	445
1st	15×15m	5	130
2nd	1×1m	174	4,554
2nd	7×7m	12	314
2nd	15×15m	4	105

- Total: 12,640 RSSI samples
- Filtered: 378 BSSIDs (from 1,799)

RSSI Heatmap Analysis

Figure 3: Heatmap showing RSSI values from different access points in a sample grid

- Darker colors = lower signal strength

Machine Learning Models

Models evaluated:

- k-Nearest Neighbor (kNN)
- Random Forest (RF)
- Support Vector Machine (SVM)
- Multi-Layer Perceptron (MLP)
- XGBoost
- XGBoost + Random Forest hybrid

Training approach:

- Standard process with hyperparameter tuning
- Consistent dataset across all models
- Comparison of filtered vs. unfiltered BSSIDs

Results

Accuracy by Grid Size

**Figure 4:** Model accuracy across different grid sizes (Filtered)

**Figure 5:** Average Grid from Target (Filtered)

Figure 6: Average Distance from Target in meters (Filtered)

Feature Filtering Impact

**Figure 7:** Filtered (378 BSSIDs)   **Figure 8:** Unfiltered (1,799 BSSIDs)

Key Findings & Implications

Key Findings

1. **Optimal Grid Size: 7×7m**
   - Best balance between accuracy and spatial resolution
   - 80% accuracy with lowest AGT/ADT values

2. **Feature Filtering Works**
   - 79% reduction in features (1,799 → 378)
   - Maintained performance, improved stability
   - Significantly reduced training time

3. **Best Models: RF and XGBoost**
   - Consistently outperformed other models
   - Well-suited for fingerprint-matching tasks
   - Better than complex deep learning in this setting

Practical Implications

For IPS Implementation:

- Don't assume bigger grids imply better accuracy - accuracy diminishes beyond optimal point
- Moderate grid sizes can be optimal
- Simple feature filtering is effective

Limitations:

- Site-specific results (university campus)
- Intensive data collection required (can be automated but still daunting)
- May need recalibration for different environments
- Architecture and materials affect performance

Conclusion

Summary

What we achieved:

- Verified local optimal grid size can be identified (7×7m in this case)
- Introduced AGT and ADT metrics for standardized evaluation
- Demonstrated effective BSSID filtering approach
- Showed RF and XGBoost performed best among models tested

Future directions:

- Advanced deep learning models (attention-based, GNN-MLP)
- Real-time adaptive grid configurations
- Synthetic data augmentation and sensor fusion
- Transfer learning across buildings

Implementation Challenges

Floor tiling variations:

- Different elevations and angles
- Addressed by reference-point-based grid construction

Edge grid effects:

- Corner vs. center RSSI variations
- Minimal impact on overall performance
- Misclassifications typically involve adjacent grids

Hardware constraints:

- RTX 3080 Ti struggled with unfiltered dataset
- Filtering made training feasible across all grid sizes

Questions?