Contrastive Pretraining for Natural Language Inference

Mei Lin, Tomas Varga

Abstract

We pretrain a sentence encoder with a contrastive objective and fine-tune it on MNLI, where it reaches 88.0% matched accuracy, 1.9 points above RoBERTa.

1 Introduction

Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise.

2 Approach

Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise.

3 Results

Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise.

Model	Acc. (%)	F1
BERT-base	84.6	0.812
RoBERTa	86.1	0.829
Ours	**88.0**	**0.851**

Table 2: Accuracy on the MNLI matched dev set.

Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise.

4 Conclusion

Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise.
Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise.

References

Devlin, J., Chang, M., Lee, K., and Toutanova, K. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In NAACL.