Sparse Routing Improves Low-Resource Translation

Asha Rao[1], Daniel Okafor[2]
[1]Institute of Language Technology [2]City University

Abstract

We introduce SparseRoute, a mixture-of-experts layer that routes each token to a single expert. On the FLORES-200 benchmark SparseRoute improves BLEU by 2.1 points over a dense Transformer baseline while using 30% fewer training FLOPs. Code is available at https://github.com/example/sparseroute.

1 Introduction

Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise.

Our contributions are threefold. First, we propose a routing rule that needs no auxiliary load-balancing loss. Second, we evaluate it on FLORES-200 and WMT 2014 English-German. Third, we release code and trained checkpoints.

2 Related Work

Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise.

3 Method

Each token representation x is sent to the expert with the highest router score, and the layer output is the expert output scaled by the router probability:

$$y = p_k(x)\, E_k(x), \quad k = \mathrm{argmax}_i\, W_r\, x \qquad (1)$$

Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather than to noise. Recent work has shown that careful design of the training objective matters as much as model size. We study this question under a controlled compute budget and report results averaged over several random seeds so that differences can be attributed to the method rather