OPEN SOURCE SOFTWARE LAB (15B17CI575)

Lab Assignment 4

Topic Coverage: Python-Numpy package

Basic commands of Numpy

- 1. Import the numpy package under the name np: import numpy as np
- 2. Create a vector with values ranging from 10 to 49.
 - a. Z = np.arange(10,50)
- 3. Reverse a vector (first element becomes last
 - a. Z = np.arange(50)
 - b. Z = Z[::-1]
- 4. Create a 3x3 matrix with values ranging from 0 to 8.
 - a. Z = np.arange(9).reshape(3,3)
- 5. Find indices of non-zero elements from [1,2,0,0,4,0]
 - a. nz = np.nonzero([1,2,0,0,4,0])
- 6. Create a 3x3 identity matrix
 - a. Z = np.eye(3)
- 7. Create a 3x3x3 array with random values
 - a. Z = np.random.random((3,3,3))
- 8. Create a 10x10 array with random values and find the minimum and maximum values
 - a. Z = np.random.random((10,10))
 - b. Zmin, Zmax = Z.min(), Z.max()
 - c. print(Zmin, Zmax)
- 9. Create a random vector of size 30 and find the mean value
 - a. Z = np.random.random(30)
 - b. m = Z.mean()
 - c. print(m)
- 10. Create a 2d array with 1 on the border and 0 inside.
 - a. Z = np.ones((10,10))
 - b. Z[1:-1,1:-1] = 0
 - c. print(Z)
- 11. How to add a border (filled with 0's) around an existing array?
 - a. Z = np.ones((5,5))
 - b. Z = np.pad(Z, pad width=1, mode='constant', constant values=0)
 - c. print(Z)
- 12. Multiply a 5x3 matrix by a 3x2 matrix
 - a. Z = np.dot(np.ones((5,3)), np.ones((3,2)))
 - b. print(Z)
- 13. Given a 1D array, negate all elements which are between 3 and 8, in place.

- a. Z = np.arange(11)
- b. Z[(3 < Z) & (Z <= 8)] *= -1
- c. print(Z)
- 14. How to find common values between two arrays?
 - a. Z1 = np.random.randint(0,10,10)
 - b. Z2 = np.random.randint(0,10,10)
 - c. print(np.intersect1d(Z1,Z2))
- 15. How to get the dates of yesterday, today and tomorrow?
 - a. yesterday = np.datetime64('today', 'D') np.timedelta64(1,'D')
 - b. today = np.datetime64('today', 'D')
 - c. tomorrow = np.datetime64('today', 'D') +
 - d. np.timedelta64(1, 'D')
- 16. How to get all the dates corresponding to the month of July 2016?
 - a. Z = np.arange(2016-07', 2016-08', dtype='datetime64[D]')
 - b. print(Z)
- 17. Consider two random array A and B, check if they are equal
 - a. A = np.random.randint(0,2,5)
 - b. B = np.random.randint(0,2,5)
 - c. # Assuming identical shape of the arrays and a tolerance for the comparison of values equal = np.allclose(A,B)
 - d. print(equal)
 - e. # Checking both the shape and the element values, no tolerance
 - f. (values have to be exactly equal)
 - g. $equal = np.array_equal(A,B)$
 - h. print(equal)
- 18. Create random vector of size 10 and replace the maximum value by 0.
 - a. Z = np.random.random(10)
 - b. Z[Z.argmax()] = 0

You can refer following link for more information:

https://www.w3schools.com/python/numpy/default.asp

https://www.geeksforgeeks.org/python-numpy/

https://www.edureka.co/blog/python-numpy-tutorial/

Exercise Questions:

- 1. Using numpy, WAP that takes an input from the user in the form of a list and calculate the frequency of occurrence of each character/integer in that list (count the number of characters).
- 2. Take a binary input from user and segregate all 1's to left side and 0's to right side.

Ex: Input: 1010011 Output: 111100

- 3. Write a Python program to remove the nth index character from a nonempty string.
- 4. Write a Python program to test whether each element of a 1-D array is also present in a second array.

Expected Output:

Array1: [0 10 20 40 60]

Array2: [0, 40]

Compare each element of array1 and array2

[True False False True False]

5. Write a Python program to find the set exclusive-or of two arrays. Set exclusive-or will return the sorted, unique values that are in only one (not both) of the input arrays.

Array1: [0 10 20 40 60 80] Array2: [10, 30, 40, 50, 70]

Unique values that are in only one (not both) of the input arrays:

[0 20 30 50 60 70 80]

6. Take an input matrix from the user and find the rank, trace, determinant of the input matrix.