



Piping in Unix or Linux

A pipe is a form of redirection (transfer of standard output to some other destination) that is used in Linux and other Unix-like operating systems to send the output of one command/program/process to another command/program/process for further processing. The Unix/Linux systems allow stdout of a command to be connected to stdin of another command. You can make it do so by using the pipe character '|'.

Pipe is used to combine two or more commands, and in this, the output of one command acts as input to another command, and this command's output may act as input to the next command and so on. It can also be visualized as a temporary connection between two or more commands/ programs/ processes. The command line programs that do the further processing are referred to as filters.

This direct connection between commands/ programs/ processes allows them to operate simultaneously and permits data to be transferred between them continuously rather than having to pass it through temporary text files or through the display screen.

Pipes are unidirectional i.e data flows from left to right through the pipeline.

Syntax :

```
command_1 | command_2 | command_3 | .... | command_N
```

Example :

1. Listing all files and directories and give it as input to more command.

```
$ ls -l | more
```

Output :


```
rishabh@rishabh: ~/GFG
rishabh@rishabh:~/GFG$ ls -l | more
total 28
drwxrwxr-x 2 rishabh rishabh 4096 Jan 29 21:11 demo1
-rw-rw-r-- 1 rishabh rishabh 26 Jan 25 23:03 demo1.txt
drwxrwxr-x 2 rishabh rishabh 4096 Jan 29 21:11 demo2
-rw-rw-r-- 1 rishabh rishabh 0 Jan 25 23:04 demo2.txt
drwxrwxr-x 2 rishabh rishabh 4096 Jan 29 21:11 demo3
-rw-rw-r-- 1 rishabh rishabh 0 Jan 25 23:04 demo.txt
-rw-rw-r-- 1 rishabh rishabh 123 Jan 26 16:02 sample1.txt
-rw-rw-r-- 1 rishabh rishabh 44 Jan 26 15:52 sample2.txt
-rw-rw-r-- 1 rishabh rishabh 0 Jan 26 00:12 sample3.txt
-rw-rw-r-- 1 rishabh rishabh 26 Jan 25 23:03 sample.txt
rishabh@rishabh:~/GFG$
```

The more command takes the output of \$ ls -l as its input. The net effect of this command is that the output of ls -l is displayed one screen at a time. The pipe acts as a container which takes the output of ls -l and gives it to more as input. This command does not use a disk to connect standard output of ls -l to the standard input of more because pipe is implemented in the main memory.

In terms of I/O redirection operators, the above command is equivalent to the following command sequence.

```
$ ls -l -> temp
more -> temp (or more temp)
[contents of temp]
rm temp
```

Output :



```
rishabh@rishabh: ~/GFG
rishabh@rishabh:~/GFG$ ls -l > temp
rishabh@rishabh:~/GFG$ more < temp
total 28
drwxrwxr-x 2 rishabh rishabh 4096 Jan 29 21:11 demo1
-rw-rw-r-- 1 rishabh rishabh 26 Jan 25 23:03 demo1.txt
drwxrwxr-x 2 rishabh rishabh 4096 Jan 29 21:11 demo2
-rw-rw-r-- 1 rishabh rishabh 0 Jan 25 23:04 demo2.txt
drwxrwxr-x 2 rishabh rishabh 4096 Jan 29 21:11 demo3
-rw-rw-r-- 1 rishabh rishabh 0 Jan 25 23:04 demo.txt
-rw-rw-r-- 1 rishabh rishabh 123 Jan 26 16:02 sample1.txt
-rw-rw-r-- 1 rishabh rishabh 44 Jan 26 15:52 sample2.txt
-rw-rw-r-- 1 rishabh rishabh 0 Jan 26 00:12 sample3.txt
-rw-rw-r-- 1 rishabh rishabh 26 Jan 25 23:03 sample.txt
-rw-rw-r-- 1 rishabh rishabh 0 Jan 29 21:53 temp
rishabh@rishabh:~/GFG$ rm temp
rishabh@rishabh:~/GFG$
```


Output of the above two commands is same.

2. Use sort and uniq command to sort a file and print unique values.

```
$ sort record.txt | uniq
```

This will sort the given file and print the unique values only.

Output :



```
rishabh@rishabh: ~/GFG
rishabh@rishabh:~/GFG$ cat result.txt
Rajat Dua      ECE    9.1
Rishabh Gupta  CSE    8.4
Prakhar Agrawal CSE    9.7
Aman Singh    ME     7.9
Rajat Dua      ECE    9.1
Rishabh Gupta  CSE    8.4
Aman Singh    ME     7.9
Naman Garg     CSE    9.4
rishabh@rishabh:~/GFG$ sort result.txt | uniq
Aman Singh    ME     7.9
Naman Garg     CSE    9.4
Prakhar Agrawal CSE    9.7
Rajat Dua      ECE    9.1
Rishabh Gupta  CSE    8.4
rishabh@rishabh:~/GFG$
```

3. Use head and tail to print lines in a particular range in a file.

```
$ cat sample2.txt | head -7 | tail -5
```

This command select first 7 lines and last 5 lines from the file and print those lines which are common to both of them.

Output :



```
rishabh@rishabh: ~/GFG
rishabh@rishabh:~/GFG$ cat sample2.txt | head -7 | tail -5

This is a sample program.
Hello Prakhar!
rishabh@rishabh:~/GFG$
```

4. Use ls and find to list and print all lines matching a particular pattern in matching files.

```
$ ls -l | find ./ -type f -name "*.txt" -exec grep "program" {} \;
```

This command select files with **.txt** extension in the given directory and search for pattern like "program" in the above example and print those line which have program in them.

Output :

```
rishabh@rishabh: ~/GFG
rishabh@rishabh:~/GFG$ ls -l | find ./ -type f -name "*.txt" -exec grep "program" {} \;
This is a sample program.
This is a sample program.
This is a sample program.
This is a sample program.
This is a sample program.
rishabh@rishabh:~/GFG$
```

5. Use cat, grep, tee and wc command to read the particular entry from user and store in a file and print line count.

```
$ cat result.txt | grep "Rajat Dua" | tee file2.txt | wc -l
```

This command select **Rajat Dua** and store them in file2.txt and print total number of lines matching **Rajat Dua**

Output :



```
rishabh@rishabh: ~/GFG
rishabh@rishabh:~/GFG$ cat result.txt | grep "Rajat Dua" | tee file2.txt | wc -l
2
rishabh@rishabh:~/GFG$ cat file2.txt
Rajat Dua      ECE    9.1
Rajat Dua      ECE    9.1
rishabh@rishabh:~/GFG$
```

Recommended Posts:

[Linux vs Unix](#)

[Sed Command in Linux/Unix with examples](#)

[grep command in Unix/Linux](#)

[Essential Linux/Unix Commands](#)

[Wget command in Linux/Unix](#)

[Environment Variables in Linux/Unix](#)

[AWK command in Unix/Linux with examples](#)

[tr command in Unix/Linux with examples](#)

[Soft and Hard links in Unix/Linux](#)

[SORT command in Linux/Unix with examples](#)

[vi Editor in UNIX](#)

[systemctl in Unix](#)

[Introduction to UNIX System](#)

[Data Analysis with Unix - Part 1](#)

[Data Analysis with Unix - Part 2](#)



[rishabh1322](#)

Check out this Author's [contributed articles](#).

If you like GeeksforGeeks and would like to contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please Improve this article if you find anything incorrect by clicking on the "Improve Article" button below.

Improved By : [KevinWalther](#), [rtrnachiket](#)

Article Tags : [Linux-Unix](#) [linux-command](#)





1

☐ To-do ☐ Done

2

Based on 1 vote(s)

Feedback/ Suggest Improvement

Add Notes

Improve Article

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

[Load Comments](#)

A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

About Us
Careers
Privacy Policy
Contact Us

PRACTICE

Courses
Company-wise
Topic-wise
How to begin?

LEARN

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

CONTRIBUTE

Write an Article
Write Interview Experience
Internships
Videos

@geeksforgeeks, Some rights reserved

