

the following **Modify** menu is displayed:

[illegible]

The choices on this menu are: **Delete**, **Insert**, and **Rename**. The following sections discuss what happens when you choose each of these commands.

4.5.1 Adding Commands to Menus

You can add commands by using the **Modify** menu. First, press the **MODIFY** key. Choose the **Insert** option. Fill in the command fields with the following:

1. The name of the command as you want it to appear on the menu.
2. The location of that command (you must give the command's full path-name) Refer to the *XENIX User's Guide* for information on filesystems and the pathnames of commands. Refer to Appendix A, "Command Mapping," for appropriate command names.
3. Where you want the command to appear on the menu.

When you press the RETURN key, the command will be added to the main command menu.

Example

Visual Shell

Assume that you want to add a **Look** command to the main command menu. This command will perform the same function as the XENIX **ls** (for “list”) command. You want the command menu to contain 12 commands: **Copy**, **Delete**, **Help**, **Look**, **Mail**, **Name**, **Options**, **Print**, **Quit**, **Run**, **View**, and **Window**. To add the **Look** command, follow these steps:

1. When the main command menu is displayed, press the MODIFY (@) key. The **Modify** menu will appear.
2. Choose the **Insert** option.
3. The **Modify Insert** menu command will appear. This menu asks you what name you want to add to the main command menu and the command pathname that is associated with that name. The following figure illustrates what your screen should look like:

```
+-----/usr/diane-----+
| [..]          [forms]          |
| temp1         [letters]        |
| temp2         [mnt]           |
|               [myfile]        |
|-----|
|-----temp1-----41 bytes-----modified--date--|
|-----|
|
| Copy File (1) temp1 (2) temp2
|
| INSERT menu item:             for command:
|       before item: Copy
| Enter text of new menu item
| /usr/diane
|
| date time XENIX
```

4. Type “**Look**” in the “menu item:” field.
5. Go to the “command:” field. Type the full pathname of the XENIX command for the value of the **Look** command (**/bin/ls**).
6. Go to the “before item:” field. This asks you which command you want **Look** to come before on the menu. The Visual Shell automatically suggests **Mail**, the next item in the alphabetical list.

7. Press RETURN. The main command menu will include the new **Look** command between **Help** and **Mail**.
8. If you want to insert **Look** in a different place, press a direction key. The list of commands will appear at the top of the screen. Use direction keys to select the command you wish **Look** to precede.

Note

You must name your commands with unique first letters. Do not name your commands with letters that have already been used on the main command menu. If you choose a letter that is already taken, the Visual Shell will ask you to specify a different name for that command.

The Visual Shell recognizes all XENIX operating system commands and creates a submenu for each one you add to a command menu. To illustrate this, let's use the new **Look** command. In the command menu, go to the **Look** command and press RETURN. A special default command menu for your **Look** command will appear on the screen. This menu asks you to specify the parameters for the **Look** command. Type the name of the directory you want to view in the "parameters:" command field. When you press RETURN, you will be returned to the command screen and the directory you specified will appear in the window.

Note

If the directory you want to view is not a subdirectory of your working directory, you must type the *pathname* of the directory in the "parameters:" command field.

4.5.2 Deleting Commands from Menus

To delete a command from the main command menu, press the MODIFY key while in the command menu. (You do not have to go to the command you want to delete.) The **Modify** menu will appear. Press RETURN to select the **Delete** option. The **Modify Delete** menu simply asks you which command you want to delete. Type the name of the command you want to delete in the "menu item:" field. You can also use the direction keys to enumerate which com-

Visual Shell

mand you want to delete. When you press RETURN, the main command menu will be displayed. It will no longer contain the command you just deleted.

Example

To delete the **Look** command you just added to the main command menu, follow these steps:

1. Press the **MODIFY** key when the main command menu is displayed.
2. Choose the **Delete** option from the **Modify** menu.
3. Type the word “**Look**” in the “menu item” field.
4. Press the **RETURN** key.

The Visual Shell will redisplay the main command menu without the **Look** command.

Note

You cannot delete the **Help** command or any of the commands in the **Help** menu.

4.6 Renaming Commands

You can add and delete many commands with the Visual Shell. You can also change the name of any command on the menu. To do this, use the **Rename** command in the **Modify** menu.

For example, you may want to rename the **View** command to “see.” (You might want to do this if you want to add a command that starts with the letter “V”, which conflicts with the **View** command.) To rename a command, choose the **Rename** option in the **Modify** menu. The **Modify Rename** menu asks you which command to rename. Fill in the three command fields and press the **RETURN** key. The main command menu will be redisplayed and will include the new command name.

Example

The following steps illustrate how to rename the **View** command to **See**.

1. While in the command menu, press the **MODIFY** key. The **Modify**

menu will appear on the screen.

2. Go to the **Rename** command and press RETURN. Your screen should look like this:

```

+---/usr/diane-----+
|  [.]                  [...]          .profile      [forms]      |
|  temp1                [letters]      [mnt]          myfile      |
|  temp2                                                         |
|                                                                |
|                                                                |
|                                                                |
+---temp1-----41 bytes-----modified---date-----+

RENAME menu item from: Copy      to:
                        place before item: Delete
Enter name of menu item or select from list
/usr/diane                                date    time    XENIX

```

3. There are three fields: “from:”, “to:”, and “place before item:”. Type “View” in the “from:” field, and “See” in the “to:” field. The Visual Shell will check to see if there are any commands in the main command menu that begin with the letter “S”.
4. Go to the “place before item:” field. The Visual Shell automatically suggests placing the renamed command in alphabetical order. Press RETURN to insert “See” in alphabetical order.
5. The **View** command is now renamed **See**.

If you have chosen a letter that is already used on the menu, the Visual Shell prompts you to choose a different letter.

4.7 Creating and Modifying Submenus

Creating and modifying submenus is easy with the Visual Shell. You must first decide what to name the main menu item. The command and its associated submenu must have the same name. Use the **MODIFY** (@) key to display the **Modify** menu and choose the **Insert** menu.

There are three fields in the **Modify Insert** menu: “menu item:”, “for command:” and “before item:”. To add a submenu, type the name of the command in the “menu item:” field. Next, go to the “for command:” field. Instead of typing a filename, type the word “menu”. This tells the Visual Shell that you are planning to add a submenu to the system. When you press the RETURN key, the Visual Shell will display the main command menu with the new top-level command.

So far, you have created a command with a submenu, but there are no commands for the submenu. To add commands to your new submenu, choose the top-level command and press RETURN. You should see the name of your submenu displayed on the screen. You can use the MODIFY (@) key to call up the **Menu Modify** menu to add some commands to your submenu. Follow the steps described in Section 4.5.1 to add commands to the submenu. A copy of the special file containing Visual Shell menu instructions—*menu.def*—is automatically copied to your directory when you use **Modify Insert** command. This is an executable file and appears in your directory with an asterisk (*) in front of the filename.

Commands are deleted from a submenu the same way they are deleted from the main command menu. Refer to Section 4.5.2 for more information. You cannot delete a submenu until each command has been deleted from it.

Example

Assume that you want to be able to access several editors by using a submenu under a **Text** main command. These editors are named **word**, **ed**, and **vi**.

You must first add the main level command to the command screen using the MODIFY (@) key and the **Insert** option. Follow these steps:

1. When the main command menu is displayed, press the MODIFY (@) key. The **Modify** menu will appear.
2. Choose the **Insert** menu.
3. Type “Text” in response to the “menu item:” field, and “Menu” in response to the “for command:” field.
4. Press RETURN. The main command menu is now displayed. The **Text** command has been added to this menu.
5. Choose the **Text** command. The screen will display “TEXT”. Press the MODIFY (@) key to display the **Modify** menu. Choose the **Insert** menu.
6. Add the first editor by typing the name of the editor (for example,

“Word”) in the “menu item:” field and the location of the editor or disk (for example, */bin/word*) in the “for command:” field.

7. Press RETURN to display the main command screen.
8. Repeat steps 4, 5, and 6 to add **ed** and **vi** subcommands to the **Text** submenu.

To delete the submenu, select **Text** command, then use the **Modify** menu to delete the commands **word**, **ed**, and **vi**. Next, return to the command screen and use the **MODIFY** key to display the **Modify** menu. Choose the **Delete** menu and type “text” in response to the “command:” field. When you press RETURN, both the submenu (named **Text**) and the top level **Text** command will be deleted.

4.8 Changing Command Menus

In the previous section, you learned how to add, delete, and rename commands. You also learned how to create and delete submenus. This section describes how to change and create command menus. Command menus are the menus that you fill in once you have selected a command.

4.9 .mnu Files

All XENIX commands are actually executable files on disk. You can see the files when you do a directory listing for the directory that contains XENIX commands on your system (usually */bin*). The instructions for Visual Shell command menus are found in a special file, */usr/bin/menu.def*. When you add your own Visual Shell commands, a copy of this special file is automatically placed in your current directory and a default menu is assigned your command. However, you can create your own command menus by placing instructions in a *.mnu* file. For example, the instruction menu for your **See** command would be in *see.mnu*. An *.mnu* file contains the information necessary for the Visual Shell to create a command submenu and is stored in the */usr/bin* directory. An *.mnu* file describes the following:

1. The submenu(s) for one operating system command.
2. The defaults and possible values of the fields within the submenu(s).
3. The actual command line arguments to be used once you press RETURN. These arguments act as a template into which values from the submenu are inserted.
4. **Help** text. This text appears on the screen if you press the **HELP** key (the **?** key) while the command submenu is being displayed.

If you add commands to the Visual Shell using the **MODIFY** key, you do not

Visual Shell

have to add a corresponding command menu. When you choose the new command, the Visual Shell first searches in the `/bin` directory to find a `.mnu` file that corresponds to the command. (For example, a **finger** command might have an associated `finger.mnu` file.) If there is no associated `.mnu` file for the command, the Visual Shell displays a default command menu. The default command menu looks like this:

```
+---/usr/diane-----+
|  [.]                [..]          .profile    [forms]      |
|  temp1              [letters]      [mnt]        myfile      |
|  temp2                                                     |
|                                                              |
|                                                              |
|                                                              |
+---temp1-----41 bytes-----modified---date---+

SEE file:           parameters:

Enter a filename or select from list
/usr/diane                                     date   time   XENIX
```

You can create your own command menus by writing a `.mnu` file that corresponds to a command that you have added to the Visual Shell. Refer to Appendix B, “Making Your Own Menu Files,” for information on how to create a `.mnu` file.

Chapter 5

Key Directory

5.1 Introduction 5-1

5.2 Key Chart 5-1



5.1 Introduction

In this manual, the keys are referred to by their functional names (by what they do), rather than by what may be written on the key.

The following are the basic key assignments provided with your operating system. Depending on the keyboard you use, you may have additional function keys or different key assignments. An extended chart, which lists terminal-specific keys, is available in the Visual Shell by pressing the letter “H” (for **Help**) and then “K” (for **Keyboard**). (Press “N”, for **Next**, to view more of the chart.)

Note

These keys perform the following functions only in conjunction with Visual Shell menus. They may not work in the same manner if used during application programs or during operating system commands.

5.2 Key Chart

Key Sequences	Function
CTRL-E	UP DIRECTION. Moves the cursor up one line.
CTRL-X	DOWN DIRECTION. Moves the cursor down one line.
CTRL-S	LEFT DIRECTION. Moves the cursor left one character.
CTRL-D	RIGHT DIRECTION. Moves the cursor right one character.
CTRL-R-E	PAGE UP. Moves the cursor up one page.
CTRL-R-X	PAGE DOWN. Moves the cursor down one page.
CTRL-Q	HOME. Moves the cursor to the beginning of the file or directory listing.
CTRL-Z	END. Moves the cursor to the end of the file or directory listing.

Visual Shell

CTRL-C	CANCEL. Cancels present operation and returns to main command menu.
RETURN	RETURN. Starts a command selected from a menu or carries out a completed command.
SPACEBAR	Selects the next item on a menu.
BACKSPACE, CTRL-H	Selects the previous item on a menu. When editing responses in command fields, deletes selected characters.
TAB, CTRL-I, CTRL-A	TAB. Moves to and selects the entire contents of the next field in the command line.
CTRL-Y, DELETE	DELETE. Deletes selected characters.
CTRL-L	CHARACTER RIGHT. Selects the character to the right of the current character.
CTRL-K	CHARACTER LEFT. Selects the character to the left of the current character.
CTRL-P	WORD RIGHT. Selects the word to the right of the current word.
CTRL-O	WORD LEFT. Selects the word to the left of the current word.
?	HELP. Requests information about the selected command or the command in progress at the time of the request.
=	SHOW. Displays directories and text files; displays sub-menus for commands in window.
-	GOAWAY. Returns window display to parent or current directory.
@	MODIFY. Displays the Modify menu.
!	REDRAW. Redraws the screen.
	BAR. Displays the Filter menu.

Chapter 6

Command Directory

6.1 Introduction 6-1

6.2 Copy 6-2

6.2.1 Copy Directory 6-3

6.2.2 Copy File 6-4

6.3 Delete 6-5

6.4 Edit 6-6

6.5 Help 6-7

6.6 Mail 6-8

6.6.1 Mail Read 6-8

6.6.2 Mail Send 6-8

6.7 Name 6-9

6.8 Options 6-10

6.9 Options Directory 6-11

6.9.1 Options Directory Make 6-11

6.9.2 Options Directory Usage 6-11

6.10 Options Filesystem 6-12

6.10.1 Options Filesystem Create 6-12

6.10.2 Options Filesystem Filescheck 6-13

6.10.3 Options Filesystem Mount 6-14

6.10.4 Options Filesystem Spacefree 6-15

6.10.5 Options Filesystem Unmount 6-15

6.11 Options Output 6-16

6.12 OptionsPermissions 6-17

6.13 Print 6-18

6.14 Quit 6-18

6.15 Run 6-19

6.16 View 6-20

6.17 Window 6-21

6.1 Introduction

This chapter describes the Microsoft Visual Shell commands. They are:

- Copy Directory
- Copy File
- Delete
- Edit
- Help
- Mail Read
- Mail Send
- Name
- Options Directory Make
- Options Directory Usage
- Options Filesystem Create
- Options Filesystem Filescheck
- Options Filesystem Mount
- Options Filesystem Spacefree
- Options Filesystem Unmount
- Options Output
- Options Permissions
- Print
- Quit
- Run
- View
- Window

The command descriptions explain the action of each command, the purpose of the command fields, and the meaning of the messages displayed by a command.

The two following definitions, which you will be using later on in this chapter, describe the required syntax for filenames and pathnames.

Filename	A filename is a string of up to 14 characters. Characters such as period (.) and hyphen (-) are allowed so you may create filename extensions that are used to identify types of files. An example of a filename with an extension is <i>newfile.mnu</i> . Refer to your <i>XENIX User's Guide</i> for more information on naming files.
Pathname	A pathname is a sequence of directory names followed by a simple filename, each separated from the previous one by a forward slash (/). Pathnames are used to uniquely identify files that may have the same name or that are not

in your current directory. An example of a pathname is */usr/joe/testfile*.

Device	A device is a special filename that refers to a peripheral device such as a hard or a floppy disk drive. These names are required in commands to specify the device containing the file system you are mounting, checking, or searching. For example, the filename <i>/dev/fd0</i> refers to the floppy disk drive 0 on your computer.
--------	--

6.2 Copy

COPY: File Directory

Purpose

The **Copy** command offers a choice of subcommands that perform the following tasks:

- Copy the contents of a file to a new file.
- Copy the contents of a directory to a new directory.

The **Copy** subcommands are described individually on the following pages.

6.2.1 Copy Directory

COPY DIRECTORY from: to: recursive: Yes (No)

Purpose

To copy the contents of the *source* directory to the *destination* directory.

Command Fields

- from: Enter a directory name. The directory name must have the syntax described at the beginning of this chapter. If the directory specified in this field is not the working directory, make sure you supply an appropriate path-name.
- to: Enter a directory name. The directory name must have the syntax described at the beginning of this chapter.
- recursive: If you select “Yes” the Visual Shell will copy all sub-directories under the directory specified.

6.2.2 Copy File

COPY FILE from: to:

Purpose

To copy the contents of the specified *source* file to the specified *destination* file.

Remarks

You may copy the contents of any existing file to the destination file. If the destination file already exists, the old contents are deleted before the new contents are copied to it.

If you copy the source file to another directory, you may give the destination file the same name as the source. Otherwise, you must use a different name.

Command Fields

from: Enter a filename. The filename must have the syntax described at the beginning of this chapter. If the file is not in the working directory, make sure you supply an appropriate pathname.

to: Enter a filename. The filename must have the syntax described at the beginning of this chapter. If the file is not in the working directory, make sure you supply an appropriate pathname.

6.3 Delete

DELETE name:

Purpose

To perform the following delete operations:

- Delete a file from a directory
- Delete a subdirectory from a directory

Remarks

The command deletes a file from the current or specified directory, or deletes the directory specified by the pathname.

Command Fields

name: Choose one of the following:

1. Enter a filename. The filename must have the syntax described at the beginning of this chapter. If the file is not in the working directory, make sure you supply an appropriate pathname.
2. Enter a directory name. It must have the syntax described at the beginning of this chapter. If the subdirectory is not in the working directory, make sure you supply an appropriate pathname.

6.4 Edit

EDIT filename:

Purpose

To load the system's interactive editor and edit the text file named after "filename:".

Remarks

The command relinquishes control to the system's interactive editor, so the command menu is erased from the screen and is replaced by the editor's own screen. The command menu is restored when you exit the editor.

Command Fields

filename:	Enter a filename. The filename must have the syntax described at the beginning of this chapter. If the file is not in the working directory, make sure you supply an appropriate pathname.
-----------	--

6.5 Help

HELP: Resume Next Previous Introduction Commands Filters
Keyboard Menus

Purpose

To display information about the Visual Shell and its commands.

Remarks

The commands in the **Help** menu provide the following **Help** information:

Resume	Exits Help and returns you to your previous screen.
Next	Scrolls Help text one screenful ahead.
Previous	Scrolls Help text one screenful backward.
Introduction	Displays the beginning of Visual Shell Help text.
Commands	Displays Visual Shell command information.
Keyboard	Displays information about the keyboard.
Filters	Displays information on the Visual Shell filters More , Sort , Head , Tail , Get and Count .
Menus	Displays information on how to change the Visual Shell menus.

6.6 Mail

Mail has two commands: **Read** and **Send**. These two commands are described in the following text.

6.6.1 Mail Read

Purpose

To read mail sent by other users of the system.

Remarks

Once you have selected **Mail Read**, you begin using the XENIX mail system to read your mail. Refer to the *XENIX User's Guide* for more information on the **XENIX Mail** command.

Command Fields

There are no command fields.

6.6.2 Mail Send

MAIL SEND to:

Purpose

To send mail to other users on the system.

Remarks

After you have filled in the "to:" command field, you begin using the **XENIX Mail** command. Refer to the *XENIX User's Guide* for more information on the **Mail** command.

Command Fields

to: Type one or more user names in this command field and press RETURN. If more than one user name is specified, separate the names with a space.

6.7 Name

NAME from: to:

Purpose

To rename a directory or file.

Remarks

The new name must not be the same name of a file or directory already in the same directory.

Command Fields

from:	Enter a file or directory name. The file or directory name must have the syntax described at the beginning of this chapter. If the file or directory is not in the working directory, make sure you supply an appropriate pathname.
to:	Enter a file or directory name. The file or directory name must have the syntax described at the beginning of this chapter. If the file or directory is not in the working directory, make sure you supply an appropriate pathname.

6.8 Options

OPTIONS: Directory Filesystem Output Permissions

Purpose

To offer a choice of subcommands to perform the following operations:

- Make a directory (under **Directory**).
- Determine disk usage (under **Directory**).
- Create a file system (under **Filesystem**).
- Check a file system (under **Filesystem**).
- Determine free space (under **Filesystem**).
- Mount a floppy disk (under **Filesystem**).
- Unmount a floppy disk (under **Filesystem**).
- Set permissions for directories and files (under **Permissions**).
- Change Visual Shell command output on the screen (under **Output**).

The commands are described individually on the following pages.

6.9 Options Directory

The **Options Directory** menu has two commands: **Make** and **Usage**. They are described below.

6.9.1 Options Directory Make

OPTIONS DIRECTORY MAKE directory:

Purpose

To make a new directory.

Command Fields

directory: Enter a directory name. The directory name must have the syntax described at the beginning of this chapter. The directory that you create will become a *subdirectory* of your working directory.

6.9.2 Options Directory Usage

OPTIONS DIRECTORY USAGE pathname:

Purpose

To determine the number of blocks contained in all files and directories within each directory and file specified by "name:".

Remarks

This command does not count directories that cannot be read or files that cannot be opened. Files with holes in them will result in an incorrect block count.

Command Fields

pathname: Specify the pathname of a directory. The directory name must have the syntax described at the beginning of this chapter.

6.10 Options Filesystem

The Options Filesystem menu contains 5 commands:

Command	Purpose
Create	Creates a file system.
Filesystemcheck	Checks and repairs files systems.
Spacefree	Reports number of free disk blocks.
Mount	Mounts a file structure.
Unmount	Dismounts a file structure.

These commands are described in the following pages.

6.10.1 Options Filesystem Create

OPTIONS FILESYSTEM CREATE device name: block number:
 gap number: block number:

Purpose

To create a file system.

Remarks

The block size, gap number, and block number command fields require numbers that are given in the *XENIX Operations Guide*.

Command Fields

- device name: Specify a device name, such as */dev/fd0*. The device name must have the syntax described at the beginning of this chapter.
- block number: Specify a block size or the size of the created system.
- gap number: Specify a gap number.
- block number: Specify a block number.

6.10.2 Options Filesystem Filescheck

OPTIONS FILESYSTEM FILESCHECK device:

Purpose

This command is usually run when you have problems mounting a floppy disk on a machine. **Options Filesystem Filescheck** audits and repairs inconsistent conditions for file systems. If the file system is consistent, the number of files, number of blocks used, and number of blocks free are reported.

Remarks

Most corrective actions of this command result in some loss of data.

Command Fields

device:	Specify a device name. The device name must have the syntax described at the beginning of this chapter.
---------	---

6.10.3 Options Filesystem Mount

OPTIONS FILESYSTEM MOUNT: device: directory:

Purpose

To mount a floppy disk on the machine.

Remarks

This command tells the system that a removable file structure (i.e., a floppy disk) is present. The file structure is mounted on a directory. The directory must already exist; it becomes the name of the root of the newly mounted file structure. Refer to the **Options Directory Make** command for information on how to create a directory.

If you have problems mounting a floppy disk, refer to the **Options Filesystem Filecheck** command.

Command Fields

- | | |
|------------|---|
| device: | Specify the name of the device you are mounting, such as <i>/dev/fd0</i> . The device name must have the syntax described at the beginning of this chapter. |
| directory: | Specify the name of the directory in which the mounted file system will reside. The directory name must have the syntax described at the beginning of this chapter. |
| read only: | Select “Yes” or “No”. The default is “No”. |

6.10.4 Options Filesystem Spacefree

OPTIONS FILESYSTEM SPACEFREE device:

Purpose

Reports the number of free disk blocks.

Remarks

If the “device:” command field is not specified, **Spacefree** reports free space on all mounted file systems.

Command Fields

device: Specify a device name. The device name must have the syntax described at the beginning of this chapter.

6.10.5 Options Filesystem Unmount

OPTIONS FILESYSTEM UNMOUNT device:

Purpose

Dismounts a mounted file system (floppy disk).

Remarks

Busy file structures cannot be dismounted with **Unmount**.

Command Fields

device: Specify the mounted device name. The device name must have the syntax described at the beginning of this chapter.

6.11 Options Output

OPTIONS OUTPUT commands like: VShell XENIX

Purpose

To set how the Visual Shell will display command syntax when a command has run.

Remarks

Normally, the Visual Shell will display its commands in the command output area of the screen. For example, when you have run **Options Directory Make** to create a directory, the Visual Shell will display, “Options Directory Make...” when the command has processed. If you want to see which XENIX command is running, select the “XENIX” field. The Visual Shell will display “mkdir ...” instead of **Options Directory Make**.

Command Fields

commands like: VShell XENIX

Choose “XENIX” to see actual XENIX commands displayed. The default is Visual Shell commands (“VShell”).

6.12 Options Permissions

OPTIONS PERMISSIONS name: who: (All) Me Group Others
 read: (Yes) No write: (Yes) No execute: (Yes) No

Purpose

To change permissions on a file or directory.

Remarks

The following permissions groups are established:

All	All users
Me	One user
Group	All users in a specified group
Others	All users other than group and me

Command Fields

name:	Type the name of a file or directory. The filename or directory name must have the syntax described at the beginning of this chapter.
who:	Enable the permissions group by selecting All, Me, Group, or Others.
read:	Select "Yes" or "No". "Yes" is the default.
write:	Select "Yes" or "No". "Yes" is the default.
execute:	Select "Yes" or "No". "Yes" is the default.

6.13 Print

PRINT filename:

Purpose

To print a file or files on the system's lineprinter.

Remarks

The command adds the specified file or files to the end of the printer queue. The file is printed when it reaches the top of the queue.

The specified file(s) must be text files.

Command Fields

filename:	Enter a filename. The filename must have the syntax described at the beginning of this chapter. If the file is not in the working directory, make sure you supply an appropriate pathname.
-----------	--

6.14 Quit

QUIT:

Enter Y to confirm:

Purpose

To leave the Visual Shell and return to the XENIX command shell.

Remarks

You must type the letter "Y" to confirm that you want to leave the Visual Shell. On exit from the shell, the system saves the current environment so you may return to the same point when you start the shell again.

6.15 Run

RUN file: parameters: output:

Purpose

To run the program or command specified by “name:”.

Remarks

The specified file must be one of the following:

- An application program
- A XENIX file that is executable
- The name of a XENIX command

If you specify a filename, the filename must have the syntax described at the beginning of this chapter. If the file is not in the working directory, make sure you supply an appropriate pathname.

Command Fields

file:	Enter a filename, program name, or command name.
parameters:	Enter any arguments to the program or command, including switches.
output:	Specify a filename or device name to redirect output from the program or command. Specify a bar (!) symbol to access the Filter menu.

6.16 View

VIEW name:

Purpose

This command loads a file or directory into the window.

Remarks

If a file is loaded in the window, you can view the file by using the scrolling keys. If a directory is loaded in the window, you can travel around the directory by using the SHOW (=) and GOAWAY (–) keys. Refer to Chapter 5, “Key Directory,” for more information.

Command Fields

name:	Enter a file or directory name. The file or directory name must have the syntax described at the beginning of this chapter. If the file or directory is not in the current directory, make sure you supply an appropriate pathname.
-------	---

6.17 Window

WINDOW redraw: (Yes) No height in lines:

Purpose

To turn the window display on or off and set the window height.

Remarks

When the window redraw is “Yes”, a permanent window appears at the top of your screen. The window contains the output from the **View** command and the **SHOW** and **GOAWAY** keys. When redraw is “No”, a window only appears when specifically requested with a **View** command or by pressing a direction key. The window “redraw:” command field is initially “Yes”.

You may use the “height in lines:” field to set the window height in lines. Initially, the height is 15 lines (the maximum height).

Command Fields

redraw:	Choose an option. “Yes” turns the window display on. “No” turns it off.
height in lines:	Enter a number. It may be any number from 1 to 15.



Appendix A

Command Mapping

A.1 Command Map A-1



A.1 Command Map

The following table maps all Visual Shell commands to XENIX commands.

XENIX Command	Visual Shell Command
cp	Copy File
copy	Copy Directory
rm, rmdir	Delete
vi	Edit
--	Help
mail	Mail Read
mail	Mail Send
mv	Name
mkdir	Options Directory Make
du	Options Directory Usage
mkfs	Options Filesystem Create
fsck	Options Filesystem Filescheck
df	Options Filesystem Spacefree
mount	Options Filesystem Mount
umount	Options Filesystem Unmount
chmod	Options Permissions
--	Options Output
pr lp	Print
CTRL-D	Quit
--	Run
cat, cd	View
--	Window



Appendix B

Making Your Own Menu Files

B.1 Introduction B-1

B.2 Command Menus B-2

B.3 .mnu Files B-2

B.4 Command Menu Prompts B-3

B.5 Command Menu Fields B-3

B.6 Command Lines B-4

B.7 Help Text B-4

B.8 Examples B-5



B.1 Introduction

When you use the Visual Shell, you select commands at the bottom of the screen. Each time you select a command, another screen appears. This screen is called a “command menu.” For example, when you select the **Copy** command, a screen similar to the following appears:

```

+---/usr/diane-----+
|  [.]                [...]      .profile  |
|                                           |
|                                           |
|                                           |
|                                           |
|                                           |
|                                           |
|                                           |
|                                           |
|                                           |
+---.-----modified---date-----+

COPY FILE from:          to:

Enter a filename or select from list
/usr/diane                                date   time      XENIX
  
```

A command menu contains fields that give information, such as a filename, to the command. To run the **Copy** command, you fill in the “from:” and “to:” fields and then press the RETURN key.

Visual Shell

If the Visual Shell does not recognize the command you run (for example, if you have added a command to the menu), a default command menu appears for you to fill in. The default command menu looks like this:

+---/usr/diane-----+ [.] [..] .profile		
+-----modified---date-----+		
TEXT file:	parameters:	output:
Enter a filename or select from list		
/usr/diane	date	time XENIX

B.2 Command Menus

Each Visual Shell command calls up a different command menu. Some command menus are defined in a special file named */usr/bin/menu.def*. The command menus for user-added commands are stored in individual files with *.mnu* extensions, one for each command. For example, if you add a command named **Spread** (for Spreadsheet), you can define your own command menu with a file named *spread.mnu*. If the Visual Shell does not find a corresponding *.mnu* file for a command, it displays the default command menu.

B.3 .mnu Files

A *.mnu* file describes:

1. Prompts that will be displayed on command menus.
2. Fields within command menus.
3. Operating system command-line arguments.

4. **Help** text for a command (optional).

You create a *.mnu* file by using an editor in XENIX such as **vi**, or by using the XENIX **cat** command. (See **cat(C)** in the *XENIX Reference Manual* for more information on the **cat** command.) All *.mnu* files should be stored in the */bin* directory. The */bin* directory must be a defined search path.

B.4 Command Menu Prompts

If you want the command menu to contain prompts, they should be inserted in the *.mnu* file just as they will appear on the screen. You may need to insert special characters to delimit fields. See the example *.mnu* files at the end of this appendix for more information.

B.5 Command Menu Fields

There are two types of fields in a command menu:

1. **Menu fields:** Field selection is with a menu and you choose one of the options. Example:

who: Me All Group Others

2. **Fill-in fields:** The response is text and you type a response, such as a filename. Example:

filename:

A *.mnu* file contains a description for each field, whether it is a menu field or a fill-in field. Each field description describes the field's type, default value, and any other type-specific information. The following is a list of field types:

Field type	Description
SELECT	Selection is from a menu.
FILENAME	Allows directory window selection and text.
FILENAMELIST	Allows directory window selection and text.
PARAMETERS	This is a text field.
OUTPUT*	This field is for output information.
NUMBER	This is an integer field (number).
DIRECTORY	Allows directory window selection and text.

OUTPUT* fields determine redirection of I/O. If used, the Visual Shell adds the necessary symbols, commands, and file names to the command line that is processed by XENIX. SELECT field types must always be followed by a series of text strings, one for each option in the field. These are generally used

Visual Shell

to specify switches.

Each field type has a fixed prompt that will appear at the bottom of the menu when the field is selected; for example, "Enter a filename."

You can include a default response for each field type. That is, the Visual Shell can automatically display a response to a field when the command menu first appears. There are several different kinds of defaults for fields:

Default Value	Description
POINT	File or directory from directory window (if open).
<number>	Indicates option in menu-type selection.
'any string'	A string for a fill-in field. Quotation marks will be stripped. For example, note that a <number> field is a fill-in field, so its default is a quoted string.

B.6 Command Lines

After you have described the command menu prompts and fields, the *.mnu* file must contain a description of the command line. The Visual Shell uses this information to build the line that will be executed by XENIX. The command line description is a line with placeholders for variables that the Visual Shell will provide. The placeholders take the form ^x, where "x" is an integer that indicates the command menu field that supplies the value. The line appears as "exec = template" in the *.mnu* file, where "template" stands for the executable command line. See the *.mnu* files at the end of this appendix for examples of the "exec=" line.

B.7 Help Text

Help text appears whenever you press the HELP key or use the Help command. This text will only be displayed if you ask the Visual Shell for help when choosing the top-level command or while in the command menu. You can type any text after the command argument line (exec=) in the *.mnu* file. Your text should begin after this line.

Help text must be separated from the *.mnu* file description by a line consisting of five hyphens.

B.8 Examples

The following examples show two typical *.mnu* files. The first *.mnu* file is named */bin/get.mnu*, and provides a unique command menu for the XENIX command **get** that a user has added to the top-level Visual Shell menu. The second *.mnu* file is named */bin/spread.mnu*, and provides a unique command menu for a spreadsheet application that a user wishes to select from the top-level menu. Each *.mnu* file contains **Help** text.

Note

Both of these examples assume that the user has already added the commands **Get** and **Spread** to the top-level menu. See Section 4.5 in Chapter 4, “Using Advanced Features,” for details on adding user commands to the Visual Shell.

Example 1: *get.mnu*

```
GET string:^^ filename:^^ linenumbers:^Yes No^
  casesensitive:^Yes No^ output:^^
fields
1 parameters
2 filename
3 select=2
"-n"
""
4 select=1
""
"-y"
5 output OPT
exec="fgrep ^3 ^4 ^1 ^2"
-----
```

GET finds a string in a file. If the “linenumbers:” command field is set to “Yes”, GET reports the line numbers that contain the string. If the “casesensitive:” command field is set to “Yes”, GET reports strings that exactly match the string and does not ignore case. You can direct output to a file or printer by specifying a filename or device name in the “output:” command field.

Typing a bar symbol (|) in the “output:” command field brings up the **Filter** menu.

Visual Shell

Example 2: spread.mnu

```
SPREAD filename:^^  
fields  
  1 filename OPT  
  exec="/bin/mp /bin/mp ^1"  
-----
```

SPREAD runs the electronic spreadsheet named Multiplan. Specify the filename of the worksheet in the field. If no worksheet is specified, Multiplan starts with a blank spreadsheet.

Appendix C

Message Directory

C.1 Messages C-1



C.1 Messages

The Visual Shell displays the following messages on the message line:

Already at bottom of directory
 Already at top of directory
 At first character in field
 At last character in field
 Bad Help file
 Cannot write to Help pointer file
 Command is too long
 Command not found
 Default specifier not recognized
 Enter Y to confirm
 Enter Y to retry access to
 Enter a filename or press | to view filter menu
 Enter a filename or select from list
 Enter an integer
 Enter name of command
 Enter name of menu item or select from list
 Enter new path
 Enter one or more filenames or select from list
 Enter options
 Enter text of new menu item
 Error changing directories
 Field has too many words
 Field not optional
 Field number greater than limit
 Field number less than one
 Field type not defined
 File is empty
 File not found
 First letter conflict with existing menu item
 Help file not available
 Inappropriate field type for fill-in field
 Inappropriate field type for menu field
 Insufficient memory
 Menu item not on current menu
 Menu must be empty to be deleted
 Missing "="
 Missing command field type
 Missing default specifier
 Missing end quote
 Missing field number
 Missing quoted menu value descriptions
 Missing sheet name in property sheet
 Multiple responses are not allowed
 Name list is empty

Visual Shell

No character to delete
No character to delete
Not a valid character
Not a valid default for a menu
Not a valid default function
Not a valid integer
Not a valid key
Not a valid option
Not a valid path name
Path is too long
Permission denied
Select option
Select option or type command letter
Too few command field definitions
Too many command field definitions
Trailing characters not valid in
Unexpected end-of-file
Unexpected end of line
Unknown internal function
Word not recognized
Wrong command field number
Wrong number of field type
You cannot modify this menu

Index - Visual Shell User's Guide

- Adding commands to menus 4-7
- Appending responses 2-2
- Applications, running 3-21
- Arguments 3-22
- Asterisk (*) 1-4

- BACKSPACE key 2-1
- Bar (|) symbol 1-5, 3-22
- Batch files 3-21

- CANCEL key 2-1, 2-2
- Canceling a Mail message 3-28
- Changing command menus 4-13
- Changing the menus 4-6
- Closing the window 4-4
- Command screen 1-1
- Command
 - line 1-1, B-4
 - mapping A-1
 - menus, changing 4-13
 - output 1-2
- Copy command 6-2
- Copy Directory command 3-13, 6-3
- Copy File command 3-5, 6-4
- Copy File menu 3-6
- Copying directories 3-13
- Copying files 3-5
- Count 3-23
- Creating files 3-1

- Date 1-3
- Definitions 1-4
- Delete command 3-6, 3-14, 6-5
- Deleting a Mail message 3-27
- Deleting commands from menus 4-9
- Deleting directories 3-14
- Deleting files 3-6
- Deleting responses 2-2
- Deleting text 2-2
- Directories 1-4
 - copying 3-13
 - deleting 3-14
 - Managing 3-9
 - Showing 4-1
 - transferring to other 3-12
- Directory Make Menu 3-11
- Directory tree 3-9

- Edit command 3-1, 6-6
- Edit cursor 2-2
- Editing a Mail message 3-28
- Editing responses 2-1
- Equal sign (=) key 4-2
- Error messages 1-3, C-1
- Expanding the window 4-3

- Filenames 1-4
- Files 1-4
 - copying 3-5
 - Creating 3-1
 - deleting 3-6
 - managing 3-3
 - printing 3-7
 - renaming 3-4
 - Showing 4-2
 - viewing 3-3
- Filter menu 1-5, 3-22, 3-26
- Filters 1-5, 3-22
 - Count 3-26
 - custom 3-23
 - Get 1-5, 3-26
 - Head 3-26
 - More 1-5, 3-26
 - Sort 1-5, 3-26
- Floppy disks

Floppy disks (*continued*)
managing 3-16

Get 3-23
Getting Help 3-30
GOAWAY key 4-2, 4-3

Head 3-23
Help Next 3-31
Help
 command 1-1, 3-30, 6-7
 Introduction 3-31
 Keyboard 3-31
 menu 3-30
 Menus 3-31
 Previous 3-31
 Resume 3-31
How to choose commands 2-1
Hyphen (-) key 4-2

Illegal option 2-1
Increasing size of window 4-3
Inserting text 2-2

Key directory 5-1

Mail 1-3
 canceling a message 3-28
 deleting a message 3-27
 editing a message 3-28
 reading 3-27
 saving a message 3-28
 sending 3-28
Main command menu 1-2
Managing directories 3-9
Managing disks 3-16
Managing files 3-3
Menu
 adding commands 4-7
 deleting commands 4-9

Message directory C-1
Message line 1-3
.mnu files 4-13
mnu files
 Help text B-4
 OUTPUT fields B-3
MODIFY (@) key 4-7, 4-9
Modify Delete menu 4-9
Modify Insert menu 4-8
Modify menu 4-7
Modify Rename menu 4-11
More 3-23

Name command 3-4, 6-9
Name menu 3-5

Options command 6-10
Options Directory Make command 6-11
Options Directory Usage command 6-11
Options Filesystem Create command 6-12
Options Output command 1-2, 6-16
Output: command field 1-5, 3-22

Pathnames 1-4
Piping 1-5, 3-23
Print command 3-7, 6-18
Print menu 3-8
Printer 3-7
Printing files 3-7

Question mark (?) key 3-31
Question mark (?) special character 1-4
Quit command 3-33, 6-18
Quit screen 3-33

Reading mail 3-27
REDRAW key 2-2
Renaming commands 4-10
Renaming files 3-4

Visual Shell User's Guide

Replacing text 2-2
RETURN key 2-1
Run command 3-21, 3-23, 6-19
Run menu 3-24
Running applications 3-21

RETURN key 2-2
SPACEBAR 2-1
Saving a Mail message 3-28
Sending mail 3-28
SHOW key 4-2, 4-3
Showing a directory 4-1
Sort 3-23
Special characters 1-4
Status line 1-2, 1-3
Submenus
 creating 4-11
 modifying 4-11
Switches 1-5, 3-22, B-4

Tail 3-23
Text files, showing 4-2
Time 1-3
Transferring directories 3-12

View command 3-3, 3-12, 6-20
View menu 3-4
View 3-13
Viewing files 3-3

Window
 closing 4-4
 command 6-21
 expanding 4-3
 menu 4-4
 permanent 4-3
 temporary 4-3
 using 3-3, 4-1
Working directory 1-4

