



Boosting


CS229: Machine Learning

Carlos Guestrin


Stanford University

Slides include content developed by and co-developed with Emily Fox


Simple (weak) classifiers are good!



Logistic regression w.
simple features



Shallow
decision trees




Decision
stumps

Low variance. Learning is fast!

But high bias...

Finding a classifier that's just right



Option 1: add more features or depth
Option 2: ?????

Boosting question

“Can a set of weak learners be combined to create a stronger learner?” *Kearns and Valiant (1988)*



Yes! *Schapire (1990)*




Boosting




Amazing impact: • simple approach • widely used in industry • wins most Kaggle competitions • great systems (e.g., XGBoost)

Ensemble classifier

A single classifier



Ensemble methods: Each classifier “votes” on prediction



Ensemble classifier in general

- Goal:
 - Predict output y
 - Either +1 or -1
 - From input x
- Learn ensemble model:
 - Classifiers: $f_1(x), f_2(x), \dots, f_T(x)$
 - Coefficients: $\hat{w}_1, \hat{w}_2, \dots, \hat{w}_T$
- Prediction:


$$\hat{y} = \text{sign} \left(\sum_{t=1}^T \hat{w}_t f_t(\mathbf{x}) \right)$$

Boosting


Training a classifier



Learning decision stump



Boosting = Focus learning on “hard” points



Learning on weighted data:


More weight on “hard” or more important points

- Weighted dataset:
 - Each x_i, y_i weighted by α_i
 - More important point = higher weight α_i
- Learning:
 - Data point i counts as α_i data points
 - E.g., $\alpha_i = 2 \rightarrow$ count point twice


Learning a decision stump on weighted data

Increase weight α of harder/misclassified points

Credit	Income	y	Weight α
A	\$130K	Safe	0.5
B	\$80K	Risky	1.5
C	\$110K	Risky	1.2
A	\$110K	Safe	0.8
A	\$90K	Safe	0.6
B	\$120K	Safe	0.7
C	\$30K	Risky	3
C	\$60K	Risky	2
B	\$95K	Safe	0.8
A	\$60K	Safe	0.7
A	\$98K	Safe	0.9



Boosting = Greedy learning ensembles from data



AdaBoost algorithm

AdaBoost: learning ensemble


[Freund & Schapire 1999]

- Start with same weight for all points: $\alpha_i = 1/N$
- For $t = 1, \dots, T$
 - Learn $f_t(\mathbf{x})$ with data weights α_i
 - Compute coefficient \hat{w}_t
 - Recompute weights α_i
- Final model predicts by:

$$\hat{y} = \text{sign} \left(\sum_{t=1}^T \hat{w}_t f_t(\mathbf{x}) \right)$$

Computing coefficient \hat{w}_t

AdaBoost: Computing coefficient \hat{w}_t of classifier $f_t(x)$




- $f_t(x)$ is good $\rightarrow f_t$ has low training error
- Measuring error in weighted data?
 - Just weighted # of misclassified points

AdaBoost:

Formula for computing coefficient \hat{w}_t of classifier $f_t(x)$

$$\hat{w}_t = \frac{1}{2} \ln \left(\frac{1 - \text{weighted_error}(f_t)}{\text{weighted_error}(f_t)} \right)$$



AdaBoost: learning ensemble


- Start with same weight for all points: $\alpha_i = 1/N$

- For $t = 1, \dots, T$

- Learn $f_t(\mathbf{x})$ with data weights α_i

- Compute coefficient $\hat{\mathbf{w}}_t$

- Recompute weights α_i

$$\hat{\mathbf{w}}_t = \frac{1}{2} \ln \left(\frac{1 - \text{weighted_error}(f_t)}{\text{weighted_error}(f_t)} \right)$$



- Final model predicts by:

$$\hat{y} = \text{sign} \left(\sum_{t=1}^T \hat{\mathbf{w}}_t f_t(\mathbf{x}) \right)$$



Recompute weights α_i

AdaBoost: Updating weights α_i based on where classifier $f_t(x)$ makes mistakes



AdaBoost: Formula for updating weights α_i

$$\alpha_i \leftarrow \begin{cases} \alpha_i e^{-\hat{w}_t}, & \text{if } f_t(x_i) = y_i \\ \alpha_i e^{\hat{w}_t}, & \text{if } f_t(x_i) \neq y_i \end{cases}$$

Did f_t get x_i right?	$f_t(x_i) = y_i$?	\hat{w}_t	Multiply α_i by	Implication
	Yes			
	No			

AdaBoost: learning ensemble

- Start with same weight for all points: $\alpha_i = 1/N$

- For $t = 1, \dots, T$

- Learn $f_t(x)$ with data weights α_i

- Compute coefficient \hat{w}_t

- Recompute weights α_i

$$\hat{w}_t = \frac{1}{2} \ln \left(\frac{1 - \text{weighted_error}(f_t)}{\text{weighted_error}(f_t)} \right)$$

$$\alpha_i \leftarrow \begin{cases} \alpha_i e^{-\hat{w}_t}, & \text{if } f_t(x_i) = y_i \\ \alpha_i e^{\hat{w}_t}, & \text{if } f_t(x_i) \neq y_i \end{cases}$$

- Final model predicts by:

$$\hat{y} = \text{sign} \left(\sum_{t=1}^T \hat{w}_t f_t(\mathbf{x}) \right)$$

AdaBoost: Normalizing weights α_i

If x_i often mistake,
weight α_i gets very
large

If x_i often correct,
weight α_i gets very
small

Can cause numerical instability
after many iterations

Normalize weights to
add up to 1 after every iteration

$$\alpha_i \leftarrow \frac{\alpha_i}{\sum_{j=1}^N \alpha_j}$$

AdaBoost: learning ensemble

- Start with same weight for all points: $\alpha_i = 1/N$

- For $t = 1, \dots, T$

- Learn $f_t(\mathbf{x})$ with data weights α_i

- Compute coefficient \hat{w}_t

- Recompute weights α_i

- Normalize weights α_i


- Final model predicts by:

$$\hat{y} = \text{sign} \left(\sum_{t=1}^T \hat{w}_t f_t(\mathbf{x}) \right)$$


$$\hat{w}_t = \frac{1}{2} \ln \left(\frac{1 - \text{weighted_error}(f_t)}{\text{weighted_error}(f_t)} \right)$$

$$\alpha_i \leftarrow \begin{cases} \alpha_i e^{-\hat{w}_t}, & \text{if } f_t(x_i) = y_i \\ \alpha_i e^{\hat{w}_t}, & \text{if } f_t(x_i) \neq y_i \end{cases}$$



$$\alpha_i \leftarrow \frac{\alpha_i}{\sum_{j=1}^N \alpha_j}$$



AdaBoost example: A visualization




t=1: Just learn a classifier on original data




Updating weights α_i

Increase weight α_i
of misclassified points


Learned decision stump $f_1(x)$




New data weights α_i




t=2: Learn classifier on weighted data




Weighted data: using α_i
chosen in previous iteration




Learned decision stump $f_2(x)$
on weighted data



Ensemble becomes weighted sum of learned classifiers



Decision boundary of ensemble classifier after 30 iterations



training_error = 0

Boosting convergence & overfitting

Boosting question revisited

“Can a set of weak learners be combined to create a stronger learner?” *Kearns and Valiant (1988)*




Yes! *Schapire (1990)*



Boosting

After some iterations,
training error of boosting goes to zero!!!




AdaBoost Theorem

Under some technical conditions...



Training error of
boosted classifier $\rightarrow 0$
as $T \rightarrow \infty$



Condition of AdaBoost Theorem

Under some technical conditions...



Training error of
boosted classifier $\rightarrow 0$
as $T \rightarrow \infty$

Condition = At every t ,
can find a weak learner with
 $\text{weighted_error}(f_t) < 0.5$



Not always possible




Nonetheless, boosting often
yields great training error


Extreme example:
No classifier can
separate a +1
on top of -1




Decision trees on loan data




Boosted decision stumps on loan data



Boosting tends to be robust to overfitting



But boosting will eventually overfit,
so must choose max number of components T



Summary of boosting

Variants of boosting and related algorithms

There are hundreds of variants of boosting, most important:

Gradient boosting

- Like AdaBoost, but useful beyond basic classification
- Great implementations available (e.g., XGBoost)

Many other approaches to learn ensembles, most important:

Random forests

- Bagging: Pick random subsets of the data
 - Learn a tree in each subset
 - Average predictions
- Simpler than boosting & easier to parallelize
- Typically higher error than boosting for same # of trees (# iterations T)

Impact of boosting (*spoiler alert... HUGE IMPACT*)

Amongst most useful ML methods ever created

Extremely useful in
computer vision

- Standard approach for face detection, for example

Used by most winners of
ML competitions
(Kaggle, KDD Cup,...)

- Malware classification, credit fraud detection, ads click through rate estimation, sales forecasting, ranking webpages for search, Higgs boson detection,...

Most deployed ML systems use model
ensembles

- Coefficients chosen manually, with boosting, with bagging, or others

What you can do now...

- Identify notion ensemble classifiers
- Formalize ensembles as weighted combination of simpler classifiers
- Outline the boosting framework – sequentially learn classifiers on weighted data
- Describe the AdaBoost algorithm
 - Learn each classifier on weighted data
 - Compute coefficient of classifier
 - Recompute data weights
 - Normalize weights
- Implement AdaBoost to create an ensemble of decision stumps