

# Analysis of the Triboro line

## Requirements

### Libraries

```
library(tidyverse)
library(igraph)
library(sf)
```

### Files

```
nys_od <- readr::read_csv('data/ny_od_main_JT00_2019.csv')
nyc_nta_borders <- sf::st_read('data/nyc_2010_nta_borders.geojson')

## Reading layer `nyc_2010_nta_borders' from data source
##   `/home/miller/GeoI/fall-2022/gtech_705-spatial_anlysis/triboro-line/brooklyn-lodes/data/nyc_2010_n
##   using driver `GeoJSON'
## Simple feature collection with 195 features and 8 fields
## Geometry type: MULTIPOLYGON
## Dimension:      XY
## Bounding box:   xmin: -74.25559 ymin: 40.49614 xmax: -73.70001 ymax: 40.91554
## Geodetic CRS:   WGS 84

nyc_nta_tract_equiv <- readxl::read_xlsx('data/nyc_2010_census_tract_nta_equiv.xlsx')

subway_lines <- readr::read_csv('data/nta-subway-lines.csv')
subway_times <- readr::read_csv('data/nta-subway-times.csv')
driving_times <- readr::read_csv('data/nta-driving-times.csv')
walking_times <- readr::read_csv('data/nta-walking-times.csv')
```

### Data

```
bk_name <- "Brooklyn"
bk_county_code <- "047"
bk_parks <- "BK99"

bk_nta_border <- nyc_nta_borders %>%
  dplyr::filter(BoroName == bk_name) %>%
  dplyr::filter(NTACode != bk_parks) %>%
  dplyr::select("NTACode")

bk_nta_tract_equiv <- nyc_nta_tract_equiv %>%
  dplyr::filter(borough_name == bk_name) %>%
  dplyr::filter(nta_code != bk_parks) %>%
  dplyr::rename(tract = census_tract) %>%
  dplyr::select("tract", "nta_code")

od <- nys_od %>%
  dplyr::filter(
    stringr::str_sub(as.character(w_geocode), 3, 5) == bk_county_code &
    stringr::str_sub(as.character(h_geocode), 3, 5) == bk_county_code
  ) %>%
  dplyr::mutate(
```

```

  w_tract = stringr::str_sub(as.character(w_geocode), 6, 11)
) %>%
dplyr::mutate(
  h_tract = stringr::str_sub(as.character(h_geocode), 6, 11)
) %>%
dplyr::select("w_tract", "h_tract", "S000") %>%
dplyr::left_join(bk_nta_tract_equiv, c("w_tract" = "tract")) %>%
dplyr::rename(w_nta_code = nta_code) %>%
dplyr::left_join(bk_nta_tract_equiv, c("h_tract" = "tract")) %>%
dplyr::rename(h_nta_code = nta_code) %>%
dplyr::select("h_nta_code", "w_nta_code", "S000") %>%
dplyr::filter(w_nta_code != bk_parks & h_nta_code != bk_parks)

```

## Exploratory data analysis

### Distribution of job counts

```

job_counts <- od %>%
  dplyr::group_by(w_nta_code) %>%
  dplyr::summarise(
    S000 = sum(S000)
  ) %>%
  unique() %>%
  mutate(
    log_S000 = log(S000)
  )


```

Original

```


ggplot(job_counts) +
  geom_histogram(aes(x = S000), fill = "steelblue", color = "grey", bins = "30")

```



Natural log

```
ggplot(job_counts) +  
  geom_histogram(aes(x = log_S000), fill = "steelblue", color = "grey", bins = "30")
```




### Distribution of commute counts

```
commute_counts <- subway_lines %>%  
  dplyr::select(trip, S000) %>%  
  dplyr::mutate(  
    log_S000 = log(S000)  
  )
```


Original

```
ggplot(commute_counts) +  
  geom_histogram(aes(x = S000), fill = "steelblue", color = "grey", binwidth = 30)
```



Natural log

```
ggplot(data = commute_counts) +  
  geom_histogram(aes(x = log_S000), bins = 30, fill = "steelblue", color = "grey")
```




### Number of subway lines and commute count

```
subway_lines <- subway_lines %>%  
  dplyr::mutate(  
    line_count_ordinal = as.character(line_count),  
    log_S000 = log(S000)  
  )
```


Original

```
ggplot(data = subway_lines, aes(x = line_count_ordinal, y = S000)) +  
  geom_boxplot()
```



Transformed

```
ggplot(data = subway_lines, aes(x = line_count_ordinal, y = log_S000)) +  
  geom_boxplot()
```




### Subway Transit time and commute count

```
subway_times <- subway_times %>%
  dplyr::mutate(
    log_S000 = log(S000),
    i_seconds_in_transit = 1 / seconds_in_transit^(1/8)
  )
subway_times_connected <- subway_times %>%
  dplyr::filter(
    subway_lines$line_count > 0
  )
```

Original


```
ggplot(data = subway_times_connected, aes(x = seconds_in_transit, y = S000)) +
  geom_point() +
  stat_smooth()
```





Transformed

```
ggplot(data = subway_times_connected, aes(x = i_seconds_in_transit, y = log_S000)) +  
  geom_point() +  
  stat_smooth()
```




### Driving in traffic time and commute count

```
driving_times <- driving_times %>%
  dplyr::mutate(
    log_S000 = log(S000),
    i_seconds_in_traffic = 1 / seconds_in_traffic^(1/8)
  )
```


Original

```
ggplot(data = driving_times, aes(x = seconds_in_traffic, y = S000)) +
  geom_point() +
  stat_smooth()
```



Transformed

```
ggplot(data = driving_times, aes(x = i_seconds_in_traffic, y = log_S000)) +  
  geom_point() +  
  stat_smooth()
```




### Walking time and commute count

```
walking_times <- walking_times %>%
  dplyr::mutate(
    log_S000 = log(S000),
    i_seconds_of_walking = 1 / seconds_of_walking^(1/8)
  )
```


### Original

```
ggplot(data = walking_times, aes(x = seconds_of_walking, y = S000)) +
  geom_point() +
  stat_smooth()
```



Transformed

```
ggplot(data = walking_times, aes(x = i_seconds_of_walking, y = log_S000)) +  
  geom_point() +  
  stat_smooth()
```



## Regression of Subway, Driving, and walking


### Subway model

```
subway_connected_model <- lm(subway_times_connected$log_S000 ~ subway_times_connected$i_seconds_in_transit)
summary(subway_connected_model)
```


```
##
## Call:
## lm(formula = subway_times_connected$log_S000 ~ subway_times_connected$i_seconds_in_transit)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.96244 -0.61708  0.03841  0.63741  2.59935
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    -3.0033     0.5352  -5.612 2.51e-08 ***
## subway_times_connected$i_seconds_in_transit  22.1264     1.4434  15.330 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.8933 on 1146 degrees of freedom
## Multiple R-squared:  0.1702, Adjusted R-squared:  0.1694
```

```
## F-statistic: 235 on 1 and 1146 DF, p-value: < 2.2e-16
```


```
plot(subway_connected_model)
```




Fitted values  
lm(subway\_times\_connected\$log\_S000 ~ subway\_times\_connected\$i\_seconds\_in\_tr  
Normal Q-Q



Theoretical Quantiles  
lm(subway\_times\_connected\$log\_S000 ~ subway\_times\_connected\$i\_seconds\_in\_tr



lm(subway\_times\_connected\$log\_S000 ~ subway\_times\_connected\$i\_seconds\_in\_tr  
Residuals vs Leverage



Leverage  
lm(subway\_times\_connected\$log\_S000 ~ subway\_times\_connected\$i\_seconds\_in\_tr

Driving


```
driving_model <- lm(driving_times$log_S000 ~ driving_times$i_seconds_in_traffic)
summary(driving_model)
```



##




```
## Call:
## lm(formula = driving_times$log_S000 ~ driving_times$i_seconds_in_traffic)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -3.14840 -0.56631  0.01954  0.60172  2.82033
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      -1.9856     0.4438  -4.474 8.39e-06 ***
## driving_times$i_seconds_in_traffic  17.9177     1.0974  16.327 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.9051 on 1223 degrees of freedom
## Multiple R-squared:  0.179, Adjusted R-squared:  0.1783
## F-statistic: 266.6 on 1 and 1223 DF, p-value: < 2.2e-16
```

```
plot(driving_model)
```











### Walking

```
walking_model <- lm(walking_times$log_S000 ~ walking_times$i_seconds_of_walking)
summary(walking_model)
```

```
##
## Call:
## lm(formula = walking_times$log_S000 ~ walking_times$i_seconds_of_walking)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -3.01771 -0.56471  0.02807  0.58272  2.80456
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    -1.9091     0.3532  -5.406 7.76e-08 ***
## walking_times$i_seconds_of_walking  20.8372     1.0257  20.315 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.8637 on 1223 degrees of freedom
## Multiple R-squared:  0.2523, Adjusted R-squared:  0.2517
## F-statistic: 412.7 on 1 and 1223 DF, p-value: < 2.2e-16
plot(driving_model)
```





Multiple linear regression for all three factors

Equations plotted for all factors

```
subway_connected_eq <- function(t) exp(-3.0033 + 22.1264 / t^(1/8))
driving_eq <- function(t) exp(-1.9856 + 17.9177 / t^(1 / 8))
```

```
walking_eq <- function(t) exp(-1.9091 + 20.8372 / t^(1 / 8))
```

```
summary(subway_times_connected$seconds_in_transit)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      645   2274   2984   3061   3821   6924
```

```
summary(driving_times$seconds_in_traffic)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      276   1076   1547   1576   2053   3122
```


```
summary(walking_times$seconds_of_walking)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      702   3755   5725   5991   7974   15171
```

```
ggplot(
  dplyr::data_frame(
    seconds = seq(from = 301, to = 15200, by = 14.9)
  ), aes(seconds)) +
  stat_function(fun = subway_connected_eq, color = "steelblue", xlim = c(645, 6924)) +
  stat_function(fun = driving_eq, color = "seagreen", xlim = c(276, 3122)) +
  stat_function(fun = walking_eq, color = "goldenrod", xlim = c(702, 15171))
```

```
## Warning: `data_frame()` was deprecated in tibble 1.1.0.
```


```
## i Please use `tibble()` instead.
```



Along all axis

Cut to most pivotal times (10 to 50 minutes) Table of values at 10, 25, 50

```
ggplot(  
  dplyr::data_frame(  
    seconds = seq(from = 720, to = 3000, by = 2.28)  
  ), aes(seconds)) +  
  stat_function(fun = subway_connected_eq, color = "steelblue") +  
  stat_function(fun = driving_eq, color = "seagreen") +  
  stat_function(fun = walking_eq, color = "goldenrod")
```



## Auto Correlation of Subway, Driving, and Walking

### Global Moran's I

```
subway_times <- subway_times %>%  
  dplyr::mutate(  
    i_c_seconds_in_transit = ifelse(subway_lines$line_count > 0, i_seconds_in_transit, 0),  
  )  
  
subway_graph <- subway_times %>%  
  dplyr::select(  
    c(  
      nta_one,  
      nta_two,  
      i_c_seconds_in_transit  
    )  
  ) %>%  
  dplyr::rename(  
    nta_one = nta_one,  
    nta_two = nta_two,  
    i_c_seconds_in_transit = i_c_seconds_in_transit  
  )
```

```

    from = nta_one,
    to = nta_two,
    weight = i_c_seconds_in_transit,
  ) %>%
  igraph::graph.data.frame(
    directed = FALSE
  )

subway_weights <- subway_graph %>%
  igraph::as_adjacency_matrix(attr = "weight") %>%
  spdep::mat2listw()

driving_weights <- driving_times %>%
  dplyr::mutate(
    i_u_seconds_in_traffic = 1 / seconds_in_traffic
  ) %>%
  dplyr::select(
    c(
      nta_one,
      nta_two,
      i_seconds_in_traffic
    )
  ) %>%
  dplyr::rename(
    from = nta_one,
    to = nta_two,
    weight = i_seconds_in_traffic
  ) %>%
  igraph::graph.data.frame(
    directed = FALSE
  ) %>%
  igraph::as_adjacency_matrix(attr = "weight") %>%
  spdep::mat2listw()

walking_weights <- walking_times %>%
  dplyr::select(
    c(
      nta_one,
      nta_two,
      i_seconds_of_walking
    )
  ) %>%
  dplyr::rename(
    from = nta_one,
    to = nta_two,
    weight = i_seconds_of_walking
  ) %>%
  igraph::graph.data.frame(
    directed = FALSE
  ) %>%
  igraph::as_adjacency_matrix(attr = "weight") %>%
  spdep::mat2listw()


```



```
subway_global_morans <- spdep::moran.test(
  job_counts$log_S000,
  subway_weights,
  zero.policy = TRUE,
)
print(subway_global_morans)
```

### Subway

```
##
## Moran I test under randomisation
##
## data: job_counts$log_S000
## weights: subway_weights
##
## Moran I statistic standard deviate = -0.63359, p-value = 0.7368
## alternative hypothesis: greater
## sample estimates:
## Moran I statistic      Expectation      Variance
## -2.477782e-02      -2.040816e-02      4.756382e-05
spdep::moran.plot(
  job_counts$log_S000,
  subway_weights,
  zero.policy = TRUE,
  xlab = "Job count",
  ylab = "Lagged job count"
)
```



#### Driving


```
driving_global_morans <- spdep::moran.test(
  job_counts$log_S000,
  driving_weights,
```

```

    zero.policy = TRUE,
  )
print(driving_global_morans)

##
## Moran I test under randomisation
##
## data:  job_counts$log_S000
## weights: driving_weights
##
## Moran I statistic standard deviate = 1.9231, p-value = 0.02724
## alternative hypothesis: greater
## sample estimates:
## Moran I statistic      Expectation      Variance
##    -1.736419e-02    -2.040816e-02    2.505457e-06
spdep::moran.plot(
  job_counts$log_S000,
  driving_weights,
  zero.policy = TRUE,
  xlab = "Job count",
  ylab = "Lagged job count"
)

```



```


walking_global_morans <- spdep::moran.test(
  job_counts$log_S000,
  walking_weights,
  zero.policy = TRUE,
)
print(walking_global_morans)

```

Walking

```
##
## Moran I test under randomisation
##
## data: job_counts$log_S000
## weights: walking_weights
##
## Moran I statistic standard deviate = 1.7419, p-value = 0.04077
## alternative hypothesis: greater
## sample estimates:
## Moran I statistic      Expectation      Variance
## -1.722520e-02    -2.040816e-02    3.339181e-06
```

```
spdep::moran.plot(
  job_counts$log_S000,
  walking_weights,
  zero.policy = TRUE,
  xlab = "Job count",
  ylab = "Lagged job count"
)
```



## LISA

```
avg_jobs <- mean(job_counts$log_S000)

classify_co_types <- function(mode_lisa, l_job_counts, avg_job_count) {
  mode_lisa %>%
    tibble::as_tibble() %>%
    magrittr::set_colnames(
      c("Ii", "E.Ii", "Var.Ii", "Z.Ii", "Pr(z > 0)")
    ) %>%
    dplyr::mutate(
      co_type = dplyr::case_when(
        `Pr(z > 0)` <= 0.05 &
```

```

      Ii >= 0 &
      l_job_counts >= avg_job_count ~ "HH",
    `Pr(z > 0)` <= 0.05 &
      Ii >= 0 &
      l_job_counts < avg_job_count ~ "LL",
    `Pr(z > 0)` <= 0.05 &
      Ii < 0 &
      l_job_counts >= avg_job_count ~ "HL",
    `Pr(z > 0)` <= 0.05 &
      Ii < 0 &
      l_job_counts < avg_job_count ~ "LH"
  )
)
}

subway_lisa <- spdep::localmoran(
  job_counts$log_S000,
  subway_weights,
  zero.policy = TRUE,
  na.action = na.omit
)

driving_lisa <- spdep::localmoran(
  job_counts$log_S000,
  driving_weights,
  zero.policy = TRUE,
  na.action = na.omit
)

walking_lisa <- spdep::localmoran(
  job_counts$log_S000,
  walking_weights,
  zero.policy = TRUE,
  na.action = na.omit
)

subway_classes <- classify_co_types(subway_lisa, job_counts$log_S000, avg_jobs)
driving_classes <- classify_co_types(driving_lisa, job_counts$log_S000, avg_jobs)
walking_classes <- classify_co_types(walking_lisa, job_counts$log_S000, avg_jobs)

subway_bk_nta_border <- bk_nta_border %>%
  dplyr::mutate(
    co_type = ifelse(is.na(subway_classes$co_type), "Insignificant", subway_classes$co_type)
  )

driving_bk_nta_border <- bk_nta_border %>%
  dplyr::mutate(
    co_type = ifelse(is.na(driving_classes$co_type), "Insignificant", driving_classes$co_type)
  )


walking_bk_nta_border <- bk_nta_border %>%
  dplyr::mutate(
    co_type = ifelse(is.na(walking_classes$co_type), "Insignificant", walking_classes$co_type)
  )

```

```
)
```


**Subway** Statistic Plot with subway lines

```
ggplot(subway_bk_nta_border) +  
  geom_sf(aes(fill = co_type), col = 'lightgrey') +  
  scale_fill_manual(  
    values = c("red", "goldenrod", "NA", "steelblue"),  
    name = "Clusters & \nOutliers"  
  ) +  
  labs(  
    title = "Neighboring job counts"  
  )  
)
```



```
ggplot(driving_bk_nta_border) +  
  geom_sf(aes(fill = co_type), col = 'lightgrey') +  
  scale_fill_manual(  
    values = c("red", "goldenrod", "NA", "steelblue", "seagreen"),  
    name = "Clusters & \nOutliers"  
  ) +  
  labs(  
    title = "Neighboring job counts by driving"  
  )  
)
```


## Neighboring job counts by driving



Statistic Plot with major

```
ggplot(walking_bk_nta_border) +
  geom_sf(aes(fill = co_type), col = 'lightgrey') +
  scale_fill_manual(
    values = c("red", "goldenrod", "NA", "seagreen"),
    name = "Clusters & \nOutliers"
  ) +
  labs(
    title = "Neighboring job counts"
  )
)
```

## Neighboring job counts



## Visualization of network

## Visualization of network's complement

## Global Moran's I

## LISA Plot by coloring desire lines