

## hw2\_code

February 1, 2026

```
[1]: import numpy as np
import matplotlib.pyplot as plt
```

**1 2**

```
[2]: # total 25 samples
# 16 positive (filled)
# 9 negative (empty)

c1_tp = 16
c1_tn = 0
c1_fp = 9
c1_fn = 0

c2_tp = 16
c2_tn = 4
c2_fp = 5
c2_fn = 0

c3_tp = 13
c3_tn = 6
c3_fp = 3
c3_fn = 3

c4_tp = 10
c4_tn = 7
c4_fp = 2
c4_fn = 6


c5_tp = 4
c5_tn = 9
c5_fp = 0
c5_fn = 12

c6_tp = 0
c6_tn = 9
c6_fp = 0
```

```
c6_fn = 16
```

## 1.1 a

```
[9]: plt.figure(figsize=(8, 8))
plt.plot([0, c1_fp/(c1_fp + c1_tn), 1], [0, c1_tp/(c1_tp + c1_fn), 1],
        label='Classifier 1')
plt.plot([0, c2_fp/(c2_fp + c2_tn), 1], [0, c2_tp/(c2_tp + c2_fn), 1],
        label='Classifier 2')
plt.plot([0, c3_fp/(c3_fp + c3_tn), 1], [0, c3_tp/(c3_tp + c3_fn), 1],
        label='Classifier 3')
plt.plot([0, c4_fp/(c4_fp + c4_tn), 1], [0, c4_tp/(c4_tp + c4_fn), 1],
        label='Classifier 4')
plt.plot([0, c5_fp/(c5_fp + c5_tn), 1], [0, c5_tp/(c5_tp + c5_fn), 1],
        label='Classifier 5')
plt.plot([0, c6_fp/(c6_fp + c6_tn), 1], [0, c6_tp/(c6_tp + c6_fn), 1],
        label='Classifier 6')
plt.plot([0, 1], [0, 1], 'k--', label='Random Guess')
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive Rate')
plt.title('ROC Curves for Classifiers')
plt.legend()
plt.grid()
plt.show()
```



## 1.2 b

```
[5]: acc_c1 = (c1_tp + c1_tn) / 25
acc_c2 = (c2_tp + c2_tn) / 25
acc_c3 = (c3_tp + c3_tn) / 25
acc_c4 = (c4_tp + c4_tn) / 25
acc_c5 = (c5_tp + c5_tn) / 25
acc_c6 = (c6_tp + c6_tn) / 25

print(f'Classifier 1 Accuracy: {acc_c1:.2f}')
print(f'Classifier 2 Accuracy: {acc_c2:.2f}')
print(f'Classifier 3 Accuracy: {acc_c3:.2f}')
```

```

print(f'Classifier 4 Accuracy: {acc_c4:.2f}')
print(f'Classifier 5 Accuracy: {acc_c5:.2f}')
print(f'Classifier 6 Accuracy: {acc_c6:.2f}')

```

```

Classifier 1 Accuracy: 0.64
Classifier 2 Accuracy: 0.80
Classifier 3 Accuracy: 0.76
Classifier 4 Accuracy: 0.68
Classifier 5 Accuracy: 0.52
Classifier 6 Accuracy: 0.36

```

### 1.3 c

```

[ ]: prec_c1 = c1_tp / (c1_tp + c1_fp)
prec_c2 = c2_tp / (c2_tp + c2_fp)
prec_c3 = c3_tp / (c3_tp + c3_fp)
prec_c4 = c4_tp / (c4_tp + c4_fp)
prec_c5 = c5_tp / (c5_tp + c5_fp)
prec_c6 = 0 # undefined

print(f'Classifier 1 Precision: {prec_c1:.2f}')
print(f'Classifier 2 Precision: {prec_c2:.2f}')
print(f'Classifier 3 Precision: {prec_c3:.2f}')
print(f'Classifier 4 Precision: {prec_c4:.2f}')
print(f'Classifier 5 Precision: {prec_c5:.2f}')
print(f'Classifier 6 Precision: Undefined')

```

```

Classifier 1 Precision: 0.64
Classifier 2 Precision: 0.76
Classifier 3 Precision: 0.81
Classifier 4 Precision: 0.83
Classifier 5 Precision: 1.00
Classifier 6 Precision: Undefined

```

### 1.4 d

```

[7]: f1_c1 = 2 * (prec_c1 * (c1_tp / (c1_tp + c1_fn))) / (prec_c1 + (c1_tp / (c1_tp_
    ↪ c1_fn)))
f1_c2 = 2 * (prec_c2 * (c2_tp / (c2_tp + c2_fn))) / (prec_c2 + (c2_tp / (c2_tp_
    ↪ c2_fn)))
f1_c3 = 2 * (prec_c3 * (c3_tp / (c3_tp + c3_fn))) / (prec_c3 + (c3_tp / (c3_tp_
    ↪ c3_fn)))
f1_c4 = 2 * (prec_c4 * (c4_tp / (c4_tp + c4_fn))) / (prec_c4 + (c4_tp / (c4_tp_
    ↪ c4_fn)))
f1_c5 = 2 * (prec_c5 * (c5_tp / (c5_tp + c5_fn))) / (prec_c5 + (c5_tp / (c5_tp_
    ↪ c5_fn)))
f1_c6 = 0 # undefined since precision is undefined

```

```

print(f'Classifier 1 F1 Score: {f1_c1:.2f}')
print(f'Classifier 2 F1 Score: {f1_c2:.2f}')
print(f'Classifier 3 F1 Score: {f1_c3:.2f}')
print(f'Classifier 4 F1 Score: {f1_c4:.2f}')
print(f'Classifier 5 F1 Score: {f1_c5:.2f}')
print(f'Classifier 6 F1 Score: Undefined')

```

```

Classifier 1 F1 Score: 0.78
Classifier 2 F1 Score: 0.86
Classifier 3 F1 Score: 0.81
Classifier 4 F1 Score: 0.71
Classifier 5 F1 Score: 0.40
Classifier 6 F1 Score: Undefined

```

## 2 3

```

[3]: data = [
    (2, 2, 3),
    (3, 3, 2),
    (1, 2, 3),
    (1, 4, 1),
    (4, 4, 4),
    (2, 2, 2),
    (3, 3, 1),
    (1, 1, 1),
    (3, 2, 2),
    (0, 4, 2),
    (4, 0, 0),
    (0, 0, 3)
]

labels = [
    1,
    1,
    1,
    1,
    1,
    1,
    -1,
    -1,
    -1,
    -1,
    -1,
    -1
]

```

## 2.1 a

```
[4]: print("Margins for each data point:")
     for point, label in zip(data, labels):
         x1, x2, x3 = point
         decision_value = 3*x1 + 2*x2 + 4*x3
         margin = label * (decision_value - 18) / np.sqrt(3**2 + 2**2 + 4**2)
         print(f'Point {point} with label {label}: {margin:.2f}')
```

Margins for each data point:

```
Point (2, 2, 3) with label 1: 0.74
Point (3, 3, 2) with label 1: 0.93
Point (1, 2, 3) with label 1: 0.19
Point (1, 4, 1) with label 1: -0.56
Point (4, 4, 4) with label 1: 3.34
Point (2, 2, 2) with label 1: 0.00
Point (3, 3, 1) with label -1: -0.19
Point (1, 1, 1) with label -1: 1.67
Point (3, 2, 2) with label -1: -0.56
Point (0, 4, 2) with label -1: 0.37
Point (4, 0, 0) with label -1: 1.11
Point (0, 0, 3) with label -1: 1.11
```

## 2.2 b

```
[5]: print("0-1 Loss for each data point:")
     for point, label in zip(data, labels):
         x1, x2, x3 = point
         decision_value = 3*x1 + 2*x2 + 4*x3
         prediction = 1 if decision_value >= 18 else -1
         loss = 0 if prediction == label else 1
         print(f'Point {point} with label {label}: {loss}')
```

0-1 Loss for each data point:

```
Point (2, 2, 3) with label 1: 0
Point (3, 3, 2) with label 1: 0
Point (1, 2, 3) with label 1: 0
Point (1, 4, 1) with label 1: 1
Point (4, 4, 4) with label 1: 0
Point (2, 2, 2) with label 1: 0
Point (3, 3, 1) with label -1: 1
Point (1, 1, 1) with label -1: 0
Point (3, 2, 2) with label -1: 1
Point (0, 4, 2) with label -1: 0
Point (4, 0, 0) with label -1: 0
Point (0, 0, 3) with label -1: 0
```

## 2.3 c

```
[7]: print("Hinge Loss for each data point:")
    for point, label in zip(data, labels):
        x1, x2, x3 = point
        decision_value = 3*x1 + 2*x2 + 4*x3
        hinge_loss = max(0, 1 - label * (decision_value - 18))
        print(f'Point {point} with label {label}: {hinge_loss}')
```

```
Hinge Loss for each data point:
Point (2, 2, 3) with label 1: 0
Point (3, 3, 2) with label 1: 0
Point (1, 2, 3) with label 1: 0
Point (1, 4, 1) with label 1: 4
Point (4, 4, 4) with label 1: 0
Point (2, 2, 2) with label 1: 1
Point (3, 3, 1) with label -1: 2
Point (1, 1, 1) with label -1: 0
Point (3, 2, 2) with label -1: 4
Point (0, 4, 2) with label -1: 0
Point (4, 0, 0) with label -1: 0
Point (0, 0, 3) with label -1: 0
```

## 2.4 d

```
[8]: print("Squared Loss for each data point:")
    for point, label in zip(data, labels):
        x1, x2, x3 = point
        decision_value = 3*x1 + 2*x2 + 4*x3
        squared_loss = (label - (decision_value - 18))**2
        print(f'Point {point} with label {label}: {squared_loss}')
```

```
Squared Loss for each data point:
Point (2, 2, 3) with label 1: 9
Point (3, 3, 2) with label 1: 16
Point (1, 2, 3) with label 1: 0
Point (1, 4, 1) with label 1: 16
Point (4, 4, 4) with label 1: 289
Point (2, 2, 2) with label 1: 1
Point (3, 3, 1) with label -1: 4
Point (1, 1, 1) with label -1: 64
Point (3, 2, 2) with label -1: 16
Point (0, 4, 2) with label -1: 1
Point (4, 0, 0) with label -1: 25
Point (0, 0, 3) with label -1: 25
```

### 3 5

```
[11]: import time

def gradient_descent(X, y, learning_rate=0.1, epochs=1000, regularization=1e-6):
    start_time = time.time()
    m, n = X.shape
    weights = np.zeros(n)
    obj_values = []
    for epoch in range(epochs):
        predictions = X @ weights
        errors = predictions - y
        gradient = (2/m) * (X.T @ errors) + 2 * regularization * weights
        if np.linalg.norm(gradient) < 1e-6:
            if regularization > 0:
                print("Completed GD w/ regularization in epoch:", epoch, "in",
↪time.time() - start_time, "seconds")
            else:
                print("Completed GD w/o regularization in epoch:", epoch, "in",
↪time.time() - start_time, "seconds")
            return weights, obj_values
        weights -= learning_rate * gradient
        obj_values.append((errors @ errors) / m + regularization * (weights @
↪weights))
    if regularization > 0:
        print("Completed GD w/ regularization in epoch:", epoch, "in", time.
↪time() - start_time, "seconds")
    else:
        print("Completed GD w/o regularization in epoch:", epoch, "in", time.
↪time() - start_time, "seconds")
    return weights, obj_values

def stochastic_gradient_descent(X, y, learning_rate=0.1, epochs=1000,
↪regularization=1e-6):
    start_time = time.time()
    m, n = X.shape
    weights = np.zeros(n)
    obj_values = []
    for epoch in range(epochs):
        for i in range(m):
            xi = X[i]
            yi = y[i]
            prediction = xi @ weights
            error = prediction - yi
            gradient = (2/m) * xi * error + 2 * regularization * weights
            weights -= learning_rate * gradient
        predictions = X @ weights
```



```

        errors = predictions - y
        obj_values.append((errors @ errors) / m + regularization * (weights @
↪weights))
        if regularization > 0:
            print("Completed SGD w/ regularization in epoch:", epoch, "in", time.
↪time() - start_time, "seconds")
        else:
            print("Completed SGD w/o regularization in epoch:", epoch, "in", time.
↪time() - start_time, "seconds")
        return weights, obj_values

def closed_form_solution(X, y, regularization=1e-6):
    n = X.shape[1]
    return np.linalg.inv(X.T @ X + regularization * np.eye(n)) @ X.T @ y

X = np.load('data_X_Q5Q6.npy')
y = np.load('data_y_Q5Q6.npy').reshape(-1)

weights_gd, obj_gd = gradient_descent(X, y)
weights_sgd, obj_sgd = stochastic_gradient_descent(X, y)
weights_closed_form = closed_form_solution(X, y)

weights_gd_noReg, obj_gd_noReg = gradient_descent(X, y, regularization=0)
weights_sgd_noReg, obj_sgd_noReg = stochastic_gradient_descent(X, y,
↪regularization=0)
weights_closed_form_noReg = closed_form_solution(X, y, regularization=0)

def l2_norm_diff(w1, w2):
    return np.linalg.norm(w1 - w2)

print("L2 Norm Differences of Least Squares Regression:")
print("With Regularization:")
print("GD vs SGD:", l2_norm_diff(weights_gd, weights_sgd))
print("GD vs Closed Form:", l2_norm_diff(weights_gd, weights_closed_form))
print("SGD vs Closed Form:", l2_norm_diff(weights_sgd, weights_closed_form))
print("Without Regularization:")
print("GD vs SGD:", l2_norm_diff(weights_gd_noReg, weights_sgd_noReg))
print("GD vs Closed Form:", l2_norm_diff(weights_gd_noReg,
↪weights_closed_form_noReg))
print("SGD vs Closed Form:", l2_norm_diff(weights_sgd_noReg,
↪weights_closed_form_noReg))

```





Completed GD w/ regularization in epoch: 999 in 0.24744129180908203 seconds  
 Completed SGD w/ regularization in epoch: 999 in 79.89985132217407 seconds  
 Completed GD w/o regularization in epoch: 999 in 0.25933051109313965 seconds  
 Completed SGD w/o regularization in epoch: 999 in 87.29134202003479 seconds  
 L2 Norm Differences of Least Squares Regression:

With Regularization:  
 GD vs SGD: 1.3603089942927995  
 GD vs Closed Form: 5.191738520295133  
 SGD vs Closed Form: 5.998876146468824  
 Without Regularization:  
 GD vs SGD: 0.0009529716509423173  
 GD vs Closed Form: 5.191620708668827  
 SGD vs Closed Form: 5.191819050801421

## 4 6

```
[12]: plt.figure(figsize=(12, 5))
plt.subplot(1, 2, 1)
plt.plot(obj_gd, label='With Regularization', linestyle='-', marker='o')
plt.xlabel('Epochs')
plt.ylabel('Objective Value')
plt.title('Gradient Descent Objective Values\nwith Regularization')
plt.subplot(1, 2, 2)
plt.plot(obj_gd_noReg, label='Without Regularization', color='orange',
        linestyle='-', marker='o')
plt.xlabel('Epochs')
plt.ylabel('Objective Value')
plt.title('Gradient Descent Objective Values\nwithout Regularization')
plt.show()

plt.figure(figsize=(12, 5))
plt.subplot(1, 2, 1)
plt.plot(obj_sgd, label='With Regularization', linestyle='-', marker='o')
plt.xlabel('Epochs')
plt.ylabel('Objective Value')
plt.title('Stochastic Gradient Descent Objective Values\nwith Regularization')
plt.subplot(1, 2, 2)
plt.plot(obj_sgd_noReg, label='Without Regularization', color='orange',
        linestyle='-', marker='o')
plt.xlabel('Epochs')
plt.ylabel('Objective Value')
plt.title('Stochastic Gradient Descent Objective Values\nwithout
        Regularization')
plt.show()
```



5 7

```
[17]: def batch_stochastic_gradient_descent(X, y, learning_rate=0.1, epochs=1000,
      ↪ batch_size=32, regularization=1e-6):
    start_time = time.time()
    m, n = X.shape
    weights = np.zeros(n)
    obj_values = []
    for epoch in range(epochs):
        perm = np.random.permutation(m)
```

```

X_shuffled = X[perm]
y_shuffled = y[perm]
for i in range(0, m, batch_size):
    xi = X_shuffled[i:i+batch_size]
    yi = y_shuffled[i:i+batch_size]
    prediction = xi @ weights
    error = prediction - yi
    gradient = (2/m) * (xi.T @ error) + 2 * regularization * weights
    weights -= learning_rate * gradient
predictions = X @ weights
errors = predictions - y
obj_values.append((errors @ errors) / m + regularization * (weights @
↪weights))
    print(f"Completed Batch {batch_size} SGD w/ regularization in epoch:↵
↪{epoch} in {time.time() - start_time} seconds")
    return weights, obj_values

X = np.load('data_X_Q7.npy')
y = np.load('data_y_Q7.npy').reshape(-1)
batch_sgd_1, batch_obj_1 = batch_stochastic_gradient_descent(X, y, batch_size=1)
batch_sgd_10, batch_obj_10 = batch_stochastic_gradient_descent(X, y,↵
↪batch_size=10)
batch_sgd_100, batch_obj_100 = batch_stochastic_gradient_descent(X, y,↵
↪batch_size=100)

```

Completed Batch 1 SGD w/ regularization in epoch: 999 in 78.41542434692383 seconds

Completed Batch 10 SGD w/ regularization in epoch: 999 in 24.432676076889038 seconds

Completed Batch 100 SGD w/ regularization in epoch: 999 in 20.637977838516235 seconds

```

[19]: plt.figure(figsize=(12, 15))
plt.subplot(3, 1, 1)
plt.plot(batch_obj_1, linestyle='--', marker='o')
plt.xlabel('Epochs')
plt.ylabel('Objective Value')
plt.title('Batch Size 1 SGD Objective Values')
plt.subplot(3, 1, 2)
plt.plot(batch_obj_10, color='orange', linestyle='--', marker='o')
plt.xlabel('Epochs')
plt.ylabel('Objective Value')
plt.title('Batch Size 10 SGD Objective Values')
plt.subplot(3, 1, 3)
plt.plot(batch_obj_100, color='green', linestyle='--', marker='o')
plt.xlabel('Epochs')
plt.ylabel('Objective Value')

```

```
plt.title('Batch Size 100 SGD Objective Values')
plt.show()
```

