HW 4

Kevin Lin

10/22/2026

1

(a) By the cone condition (0.1) $\|\Delta_{S^c}\|_1 \leq 3\|\Delta_S\|_1$. Since S and S^c partition the coordinates of Δ, we have:

$$\begin{aligned}\|\Delta\|_1 &= \|\Delta_S\|_1 + \|\Delta_{S^c}\|_1 \\ &\leq \|\Delta_S\|_1 + 3\|\Delta_S\|_1 \\ &= 4\|\Delta_S\|_1\end{aligned}$$

Because $|S| = k$, applying the Cauchy-Schwarz inequality gives:

$$\begin{aligned}\|\Delta_S\|_1 &\leq \sum_{i\in S} |\Delta_i| \\ &\leq \sqrt{k}\sqrt{\sum_{i\in S} |\Delta_i|^2} \\ &= \sqrt{k}\|\Delta_S\|_2\end{aligned}$$

Combining the two inequalities gives us $\|\Delta\|_1 \leq 4\sqrt{k}\|\Delta_S\|_2$. Substituting the ℓ_2 bound (0.2) gives us:

$$\begin{aligned}\|\Delta\|_1 &\leq 4\sqrt{k}\left(\frac{3\lambda\sqrt{k}}{\kappa}\right) \\ &= \frac{12\lambda k}{\kappa}\end{aligned}$$

Thus, $\|\Delta\|_1 \leq \frac{12\lambda k}{\kappa}$.

(b) For any $q \in [1, 2]$, we can define the Holder conjugates $a = \frac{1}{2-q}$ and $b = \frac{1}{q-1}$ such that $\frac{1}{a} + \frac{1}{b} = 1$. By the definition of the ℓ_q norm, we have $\|v\|_q^q = \sum_{i=1}^p |v_i|^q$. We can rewrite each term $|v_i|^q = |v_i|^{2-q}|v_i|^{2(q-1)}$ and

apply Holder's inequality to get:

$$\begin{aligned}
\sum_{i=1}^{p} |v_i|^q &= \sum_{i=1}^{p} |v_i|^{2-q} |v_i|^{2(q-1)} \\
&\leq \left(\sum_{i=1}^{p} |v_i|^{(2-q)a} \right)^{\frac{1}{a}} \left(\sum_{i=1}^{p} |v_i|^{2(q-1)b} \right)^{\frac{1}{b}} \\
\|v\|_q^q &= \left(\sum_{i=1}^{p} |v_i| \right)^{2-q} \left(\sum_{i=1}^{p} |v_i|^2 \right)^{q-1} \\
&= \|v\|_1^{2-q} \|v\|_2^{2(q-1)} \\
\|v\|_q &\leq \|v\|_1^{\frac{2-q}{q}} \|v\|_2^{\frac{2(q-1)}{q}} \\
&= \|v\|_1^{2/q-1} \|v\|_2^{2-2/q}
\end{aligned}$$

For $q = 1, 2$, the inequality holds with equality, thus $\|v\|_q \leq \|v\|_1^{2/q-1} \|v\|_2^{2-2/q}$ for all $q \in [1, 2]$. Using the bounds from (a) and (0.2), $\|\Delta\|_1 \leq \frac{12\lambda k}{\kappa}$ and $\|\Delta\|_2 \leq \frac{3\lambda\sqrt{k}}{\kappa}$. We can substitue these bounds into the inequality to get:

$$\begin{aligned}
\|\Delta\|_q &\leq \left(\frac{12\lambda k}{\kappa} \right)^{2/q-1} \left(\frac{3\lambda\sqrt{k}}{\kappa} \right)^{2-2/q} \\
&= \left(\frac{\lambda}{\kappa} \right)^{\frac{2}{q}-1+2-\frac{2}{q}} \cdot k^{\frac{2}{q}-1+\frac{2-2/q}{2}} \cdot 12^{\frac{2}{q}-1} \cdot 3^{2-\frac{2}{q}} \\
&= \left(\frac{\lambda}{\kappa} \right) \cdot k^{1/q} \cdot 4^{2/q-1} \cdot 3 \\
&= 3 \cdot 4^{2/q-1} \frac{k^{1/q}\lambda}{\kappa}
\end{aligned}$$

For $q = 1$, the constant is $3 \cdot 4^{2-1} = 12$, and for $q = 2$, the constant is $3 \cdot 4^{1-1} = 3$, so both are always ≤ 12. Thus, we have $\|\Delta\|_q \leq \frac{12k^{1/q}\lambda}{\kappa}$ for all $q \in [1, 2]$. When $q = 1$, we have $\|\Delta\|_1 \leq \frac{12k\lambda}{\kappa}$ which recovers (a), and when $q = 2$, we have $\|\Delta\|_2 \leq \frac{3\sqrt{k}\lambda}{\kappa}$ which recovers (0.2).

(c) Utilize (0.1) $\frac{1}{2n}\|X\Delta\|_2^2 \leq \frac{3\lambda}{2}\|\Delta_S\|_1 - \frac{\lambda}{2}\|\Delta_{S^c}\|_1$. Because $\|Delta_{S^c}\|_1 \geq 0$, we can drop the second term on the right-hand side to get:

$$\begin{aligned}
\frac{1}{2n}\|X\Delta\|_2^2 &\leq \frac{3\lambda}{2}\|\Delta_S\|_1 \\
\frac{1}{n}\|X\Delta\|_2^2 &\leq 3\lambda\|\Delta_S\|_1
\end{aligned}$$

By Cauchy-Schwarz, since $|S| = k$, $\|Delta_S\|_1 \leq \sqrt{k}\|\Delta_S\|_2 \leq \sqrt{k}\|\Delta\|_2$. Substituting this into the inequality gives $\frac{1}{n}\|X\Delta\|_2^2 \leq 3\lambda\sqrt{k}\|\Delta\|_2$. We

can then apply the ℓ_2 bound (0.2) to get:

$$\begin{aligned}\frac{1}{n}\|X\Delta\|_2^2 &\leq 3\lambda\sqrt{k}\left(\frac{3\lambda\sqrt{k}}{\kappa}\right)\\ &= \frac{9k\lambda^2}{\kappa}\end{aligned}$$

Thus, $\frac{1}{n}\|X\Delta\|_2^2 \leq \frac{9k\lambda^2}{\kappa}$.

(d) With the assumptions, by the optimality of the LASSO estimator, the objective value is no larger than the objective value β^*:

$$\frac{1}{2n}\|y - X\hat{\beta}\|_2^2 + \lambda\|\hat{\beta}\|_1 \leq \frac{1}{2n}\|y - X\beta^*\|_2^2 + \lambda\|\beta^*\|_1$$

We know that $y = X\beta^* + \epsilon$, $\hat{\beta} = \beta^* + \Delta$, thus $y - X\hat{\beta} = \epsilon - X\Delta$ and $y - X\beta^* = \epsilon$. Substituting these into the inequality gives:

$$\begin{aligned}\frac{1}{2n}\|\epsilon - X\Delta\|_2^2 + \lambda\|\beta^* + \Delta\|_1 &\leq \frac{1}{2n}\|\epsilon\|_2^2 + \lambda\|\beta^*\|_1\\ \|\epsilon - X\Delta\|_2^2 &= \|\epsilon\|_2^2 - 2\epsilon^\top X\Delta + \|X\Delta\|_2^2\\ \frac{1}{2n}\|X\Delta\|_2^2 + \lambda\|\hat{\beta}\|_1 &\leq \frac{1}{n}\epsilon^\top X\Delta + \lambda\|\beta^*\|_1\end{aligned}$$

Using Holder's inequality and the noise condition:

$$\begin{aligned}\frac{1}{n}\epsilon^T X\Delta &\leq \left(\frac{1}{n}X^\top\epsilon\right)^\top\Delta\\ &\leq \|\frac{1}{n}X^\top\epsilon\|_\infty\|\Delta\|_1\\ &\leq \frac{\lambda}{2}\|\Delta\|_1\end{aligned}$$

Thus, $\frac{1}{2n}\|X\Delta\|_2^2 + \lambda\|\hat{\beta}\|_1 \leq \frac{\lambda}{2}\|\Delta\|_1 + \lambda\|\beta^*\|_1$. By the triangle inequality, $\|\Delta\|_1 = \|\hat{\beta} - \beta^*\|_1 \leq \|\hat{\beta}\|_1 + \|\beta^*\|_1$, so we can substitute this into the inequality to get:

$$\begin{aligned}\frac{1}{2n}\|X\Delta\|_2^2 + \lambda\|\hat{\beta}\|_1 &\leq \frac{\lambda}{2}(\|\hat{\beta}\|_1 + \|\beta^*\|_1) + \lambda\|\beta^*\|_1\\ &= \frac{\lambda}{2}\|\hat{\beta}\|_1 + \frac{3\lambda}{2}\|\beta^*\|_1\\ \frac{1}{2n}\|X\Delta\|_2^2 + \frac{\lambda}{2}\|\hat{\beta}\|_1 &\leq \frac{3\lambda}{2}\|\beta^*\|_1\\ \frac{1}{n}\|X\Delta\|_2^2 + \lambda\|\hat{\beta}\|_1 &\leq 3\lambda\|\beta^*\|_1\end{aligned}$$

Because $\lambda\|\hat{\beta}\|_1 \geq 0$, we can drop this term to get $\frac{1}{n}\|X\Delta\|_2^2 \leq 3\lambda\|\beta^*\|_1$. Because the prediction error is nonnegative, $\frac{1}{n}\|X\Delta\|_2^2 \geq 0$, we can drop

this term to get $\lambda\|\hat{\beta}\|_1 \leq 3\lambda\|\beta^*\|_1$. We know $\lambda > 0$, so we can get $\|\hat{\beta}\|_1 \leq 3\|\beta^*\|_1$.

Now, taking $\lambda \asymp \sigma\sqrt{\frac{\log p}{n}}$ and assuming β^* has k nonzero entries, each equal to ± 1, $\|\beta^*\|_1 = \sum i = 1^p|\beta_i^*| = k$. Then the fast rate from (c):

$$\begin{aligned}\frac{1}{n}\|X\Delta\|_2^2 &\leq \frac{9k\lambda^2}{\kappa} \\ &\lesssim \frac{9k\sigma^2\log p}{\kappa n}\end{aligned}$$

For fixed k, p, σ, κ, this is $\mathcal{O}(1/n)$.
The slow rate from (d):

$$\begin{aligned}\frac{1}{n}\|X\Delta\|_2^2 &\leq 3\lambda\|\beta^*\|_1 = 3k\lambda \\ &\lesssim 3k\sigma\sqrt{\frac{\log p}{n}}\end{aligned}$$

For fixed k, p, σ, this is $\mathcal{O}(1/\sqrt{n})$.
Comparing the bounds:

$$\begin{aligned}\frac{9k\lambda^2}{\kappa} &\leq 3k\lambda \\ \frac{3\lambda}{\kappa} &\leq 1 \\ \lambda &\leq \frac{\kappa}{3}\end{aligned}$$

We know $\lambda \asymp \sigma\sqrt{\frac{\log p}{n}}$, so $\sigma\sqrt{\frac{\log p}{n}} \leq \frac{\kappa}{3}$. Rearrange for n gives $n \geq \frac{9\sigma^2\log p}{\kappa^2}$. Thus, the fast rate is better than the slow rate when $n \gtrsim \frac{9\sigma^2\log p}{\kappa^2}$.

2

(a) Let $u \in \mathbb{R}^p$ such that $\|u\|_2 = 1$, $\|u\|_0 \leq k$. Let $T = \text{supp}(u)$, then $|T| \leq k$. Then, by the triangle inequality and definitions of $\delta_1(A)$ and

$\mu(A)$:

$$\begin{aligned}
\|Au\|_2^2 - 1 &= u^\top (A^\top A - I)u \\
&= \sum_{j \in T} u_j^2 (\|A_j\|_2^2 - 1) + \sum_{i,j \in T, i \neq j} u_i u_j A_i^\top A_j \\
&\leq \delta_1(A) \sum_{j \in T} u_j^2 + \mu(A) \sum_{i,j \in T, i \neq j} |u_i||u_j| \\
&= \delta_1(A) + \mu(A) \left[\left(\sum_{j \in T} |u_j| \right)^2 - \sum_{j \in T} u_j^2 \right] \\
&= \delta_1(A) + \mu(A) \left[\|u\|_1^2 - 1 \right]
\end{aligned}$$

Since u has at most k nonzero coordinates, by Cauchy-Schwarz, $\|u\|_1 \leq \sqrt{k}\|u\|_2 = \sqrt{k}$. Therefore, $\|u\|_1^2 - 1 \leq k - 1$, and we have $|\|Au\|_2^2 - 1| \leq \delta_1(A) + (k-1)\mu(A)$. Taking the supremum over every k-sparse unit vector u gives us $\delta_k(A) \leq \delta_1(A) + (k-1)\mu(A)$.

(b) We start by bounding $\delta_1(A)$. For every column j, $\|A_j\|_2^2 - 1 = \frac{1}{n}\sum_{i=1}^n (X_{ij}^2 - 1)$. Since $X_{ij} \sim \mathcal{N}(0,1)$, $E[X_{ij}^2 - 1] = 0$, and the centered squares are sub-exponential. If we apply Bernstein's inequality, there then exists an absolute constant $c > 0$ such that:

$$P(|\|A_j\|_2^2 - 1| \geq t) \leq 2\exp(-cnt^2) \quad \forall 0 < t \leq 1$$

Applying the union bound over all p columns gives:

$$\begin{aligned}
P(\delta_1(A) \geq t) &= P\left(\max_{j=1,\ldots,p} |\|A_j\|_2^2 - 1| \geq t \right) \\
&\leq \sum_{j=1}^p P(|\|A_j\|_2^2 - 1| \geq t) \\
&\leq 2p\exp(-cnt^2)
\end{aligned}$$

Now we bound $\mu(A)$. For distinct columns $i \neq j$, $A_i^\top A_j = \frac{1}{n}\sum_{k=1}^n X_{ki}X_{kj}$. Because each entry is independent and nonzero, $E[X_{ki}X_{kj}] = 0$, and the product of independent Gaussians is sub-exponential. Thus, again with Bernstein's inequality, we have $P(|A_i^\top A_j| \geq t) \leq 2\exp(-cnt^2)$ for some absolute constant $c > 0$ and $0 < t \leq 1$. There are $\binom{p}{2}$ distinct pairs of

columns, thus applying the union bound gives:

$$\begin{aligned} P(\mu(A) \geq t) &= P\left(\max_{i,j=1,\ldots,p,i\neq j} |A_i^\top A_j| \geq t\right) \\ &\leq \sum_{i,j=1,\ldots,p,i\neq j} P(|A_i^\top A_j| \geq t) \\ &\leq 2\binom{p}{2}\exp(-cnt^2) \\ &\leq p^2\exp(-cnt^2) \end{aligned}$$

Now we combine the two bounds:

$$\begin{aligned} P(\delta_1(A) \geq t \text{ or } \mu(A) \geq t) &\leq 2p\exp(-cnt^2) + p^2\exp(-cnt^2) \\ &\leq 2p^2\exp(-cnt^2), \quad p \geq 2 \end{aligned}$$

Choose $t = C\sqrt{\frac{\log p}{n}}$ with $C = \sqrt{3/c}$. Then $cnt^2 = 3\log p$, and we have:

$$\begin{aligned} P(\delta_1(A) \geq C\sqrt{\frac{\log p}{n}} \text{ or } \mu(A) \geq C\sqrt{\frac{\log p}{n}}) &\leq 2p^2\exp(-3\log p) \\ &= 2p^2p^{-3} = 2/p \end{aligned}$$

For $n \geq C'\log p$, with $C' \geq C^2$, we have $t \leq 1$, and thus with probability at least $1 - 2/p$, $\delta_1(A) \leq C\sqrt{\frac{\log p}{n}}$ and $\mu(A) \leq C\sqrt{\frac{\log p}{n}}$.

(c) From (a), we have $\delta_k(A) \leq \delta_1(A) + (k-1)\mu(A)$. From (b), with probability at least $1 - 2/p$, $\delta_1(A) \leq C\sqrt{\frac{\log p}{n}}$ and $\mu(A) \leq C\sqrt{\frac{\log p}{n}}$. Thus, with probability at least $1 - 2/p$:

$$\begin{aligned} \delta_k(A) &\leq C\sqrt{\frac{\log p}{n}} + (k-1)C\sqrt{\frac{\log p}{n}} \\ &= kC\sqrt{\frac{\log p}{n}} \end{aligned}$$

To guarantee k-RIP with constant δ, we require $kC\sqrt{\frac{\log p}{n}} \leq \delta$, which rearranges to $n \geq C^2\delta^{-2}k^2\log p$. Taking $C'' = C^2$, or a larger absolute constant as necessary, gives $n \geq C''\delta^{-2}k^2\log p$. Thus, for $0 < \delta < 1$, this sample size guarantees k-RIP with probability at least $1 - 2/p$.
k is lost in (a) when we bound all off diagonal entires using the worst case coherence: $\sum_{i\neq j} |u_i||u_j|| \langle A_i, A_j\rangle | \leq (k-1)\mu(A)$. Since $\mu(A) \lesssim \sqrt{\frac{\log p}{n}}$, we need to multiply by k to account for the k nonzero entries in u. This is a loose bound because taking the absolute value ignores cancellation among the off diagonal entries, and thus we get $\delta_k(A) \lesssim$

$k\sqrt{\frac{\log p}{n}}$. Squaring the resulting sample size condition introduces the k^2 term.

For a fixed k-sparse unit vector u, Bernstein's inequality gives:

$$P(|\|Au\|_2^2 - 1| \geq \delta) \leq 2\exp(-cn\delta^2)$$

for $0 < \delta < 1$. A 1/4-net for the k-spare unit sphere has size at most $|\mathcal{N}| \leq 9^k\binom{p}{k} \leq \left(\frac{9ep}{k}\right)^k$. Applying the union bound and the net-to-sphere argument after adjusting absolute constants gives $P(\delta_k(A) \geq \delta) \leq 2\exp\left(-cn\delta^2 + k\log(9ep/k)\right)$. Thus, k-RIP holds with high probability when $n \gtrsim \delta^{-2}k\log(ep/k)$. Unlike the coherence argument, the net argument controls all sparse directions instead of summing over the worst case coherence, and thus avoids the loose k factor.

3

(a) The matrix exponential of a square matrix A is defined by the convergent power series $e^A = \sum_{n=0}^{\infty}\frac{A^n}{n!}$. Therefore, $e^{X+Y} = \sum_{n=0}^{\infty}\frac{(X+Y)^n}{n!}$. Since $XY = YX$, we can apply the binomial theorem $(X+Y)^n = \sum_{k=0}^{n}\binom{n}{k}X^kY^{n-k}$. Substituting this into the exponential series gives:

$$\begin{aligned} e^{X+Y} &= \sum_{n=0}^{\infty}\frac{(X+Y)^n}{n!} \\ &= \sum_{n=0}^{\infty}\frac{1}{n!}\sum_{k=0}^{n}\binom{n}{k}X^kY^{n-k} \\ &= \sum_{n=0}^{\infty}\sum_{k=0}^{n}\frac{X^kY^{n-k}}{k!(n-k)!} \end{aligned}$$

Let $m = n - k$. Since $k, m \geq 0$, we can rearrange the absolutely convergent series:

$$\begin{aligned} e^{X+Y} &= \sum_{k=0}^{\infty}\sum_{m=0}^{\infty}\frac{X^kY^m}{k!m!} \\ &= \left(\sum_{k=0}^{\infty}\frac{X^k}{k!}\right)\left(\sum_{m=0}^{\infty}\frac{Y^m}{m!}\right) \\ &= e^Xe^Y \end{aligned}$$

Thus, for commuting matrices X and Y, we have $e^{X+Y} = e^Xe^Y$.

(b) Consider the symmetric matrices:

$$X = \begin{bmatrix}1 & 0\\ 0 & 0\end{bmatrix}, \quad Y = \begin{bmatrix}0 & 1\\ 1 & 0\end{bmatrix}$$

Since X is diagonal, its matrix exponential is $e^X = \begin{bmatrix} e & 0 \\ 0 & 1 \end{bmatrix}$. Note that $Y^2 = I$, so $Y^{2m} = I$ and $Y^{2m+1} = Y$. Therefore, using the matrix exponential series, we get:

$$\begin{aligned}
e^Y &= \sum_{m=0}^{\infty} \frac{Y^m}{m!} \\
&= \sum_{m=0}^{\infty} \frac{Y^{2m}}{(2m)!} + \sum_{m=0}^{\infty} \frac{Y^{2m+1}}{(2m+1)!} \\
&= \sum_{m=0}^{\infty} \frac{I}{(2m)!} + \sum_{m=0}^{\infty} \frac{Y}{(2m+1)!} \\
&= \left(\sum_{m=0}^{\infty} \frac{1}{(2m)!} \right) I + \left(\sum_{m=0}^{\infty} \frac{1}{(2m+1)!} \right) Y \\
&= \cosh(1) I + \sinh(1) Y \\
&= \begin{bmatrix} \cosh(1) & \sinh(1) \\ \sinh(1) & \cosh(1) \end{bmatrix}
\end{aligned}$$

Therefore,

$$\begin{aligned}
e^X e^Y &= \begin{bmatrix} e & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} \cosh(1) & \sinh(1) \\ \sinh(1) & \cosh(1) \end{bmatrix} \\
&= \begin{bmatrix} e\cosh(1) & e\sinh(1) \\ \sinh(1) & \cosh(1) \end{bmatrix}
\end{aligned}$$

Note that this matrix is not symmetric since $e\sinh(1) \neq \sinh(1)$. However, $X + Y$ is symmetric, and the exponential of a symmetric matrix is also symmetric because $(e^{X+Y})^\top = e^{(X+Y)^\top} = e^{X+Y}$. Thus, e^{X+Y} is symmetric while $e^X e^Y$ is not, therefore they can't be equal.

HW4_P4

October 29, 2026

1 4

1.1 (a)

[ ]:
```
from itertools import combinations
from math import comb

import numpy as np
import matplotlib.pyplot as plt

from joblib import Parallel, delayed
from threadpoolctl import threadpool_limits

p = 64
k_values = [1, 2, 3, 4]
n_values = np.array([20, 40, 80, 160, 320, 640])
T = 10
rho = 0.5

designs = ["Gaussian", "Laplace", "AR(1)", "Equicorrelated", "Heavy-tailed"]

supports = {}

for k in k_values:
    count = comb(p, k)
    indices = np.fromiter(
        (j for support in combinations(range(p), k) for j in support),
        dtype=np.uint8,
        count=count * k
    )
    supports[k] = indices.reshape(count, k)
    print(f"k={k}: {count:,} supports")
```

```
k=1: 64 supports
k=2: 2,016 supports
k=3: 41,664 supports
k=4: 635,376 supports
```

[3]:
```python
def generate_design(design, n, p, rng, rho=0.5):
    if design == "Gaussian":
        return rng.standard_normal((n, p))
    elif design == "Laplace":
        return rng.laplace(
            loc=0.0,
            scale=1 / np.sqrt(2),
            size=(n, p)
        )
    elif design == "AR(1)":
        z = rng.standard_normal((n, p))
        X = np.empty((n, p))

        X[:, 0] = z[:, 0]

        for j in range(1, p):
            X[:, j] = (
                rho * X[:, j - 1]
                + np.sqrt(1 - rho**2) * z[:, j]
            )

        return X
    elif design == "Equicorrelated":
        z = rng.standard_normal((n, p))
        g = rng.standard_normal((n, 1))

        return (
            np.sqrt(1 - rho) * z
            + np.sqrt(rho) * g
        )
    elif design == "Heavy-tailed":
        return rng.standard_t(
            df=2.2, size=(n, p)
        ) / np.sqrt(11)

def compute_all_delta(X, supports, batch_size=20000):
    n, p = X.shape
    G = (X.T @ X) / n

    deltas = np.empty(4, dtype=float)

    deltas[0] = np.max(np.abs(np.diag(G) - 1))

    pairs = supports[2]
    a = G[pairs[:, 0], pairs[:, 0]]
    b = G[pairs[:, 1], pairs[:, 1]]
    c = G[pairs[:, 0], pairs[:, 1]]
```

```
    center = (a + b) / 2
    radius = np.sqrt(((a - b) / 2)**2 + c**2)

    deltas[1] = np.max(np.abs(center - 1) + radius)

    for k in [3, 4]:
        indices = supports[k]
        maximum = 0.0

        for start in range(0, len(indices), batch_size):
            batch = indices[start:start + batch_size]

            gram_blocks = G[
                batch[:, :, None],
                batch[:, None, :]
            ]

            eigenvalues = np.linalg.eigvalsh(gram_blocks)

            deviations = np.maximum(
                np.abs(eigenvalues[:, 0] - 1),
                np.abs(eigenvalues[:, -1] - 1)
            )

            maximum = max(maximum, float(deviations.max()))

        deltas[k - 1] = maximum

    return deltas

def run_trial(design_idx, n_idx, trial_idx, seed):
    design = designs[design_idx]
    n = int(n_values[n_idx])
    rng = np.random.default_rng(seed)

    with threadpool_limits(limits=1):
        X = generate_design(design, n, p, rng, rho)
        delta_values = compute_all_delta(
            X, supports, 20000
        )

    return design_idx, n_idx, trial_idx, delta_values

configs = [
    (d, ni, t)
    for d in range(len(designs))
```

```
    for ni in range(len(n_values))
    for t in range(T)
]

seeds = np.random.SeedSequence(0).spawn(len(configs))

trial_results = Parallel(
    n_jobs=8,
    backend="loky",
    verbose=10
)(
    delayed(run_trial)(d, ni, t, seeds[i])
    for i, (d, ni, t) in enumerate(configs)
)

delta = np.zeros(
    (len(designs), len(k_values), len(n_values), T)
)

for d, ni, t, delta_values in trial_results:
    delta[d, :, ni, t] = delta_values

means = delta.mean(axis=3)
sems = delta.std(axis=3, ddof=1) / np.sqrt(T)

np.savez(
    "results_4a.npz",
    delta=delta,
    means=means,
    sems=sems,
    n_values=n_values,
    k_values=k_values,
    designs=np.array(designs),
    T=T
)
```

```
[Parallel(n_jobs=8)]: Using backend LokyBackend with 8 concurrent workers.
[Parallel(n_jobs=8)]: Done   2 tasks      | elapsed:    1.2s
[Parallel(n_jobs=8)]: Done   9 tasks      | elapsed:    1.9s
[Parallel(n_jobs=8)]: Done  16 tasks      | elapsed:    2.0s
[Parallel(n_jobs=8)]: Done  25 tasks      | elapsed:    3.3s
[Parallel(n_jobs=8)]: Done  34 tasks      | elapsed:    4.0s
[Parallel(n_jobs=8)]: Done  45 tasks      | elapsed:    4.7s
[Parallel(n_jobs=8)]: Done  56 tasks      | elapsed:    5.6s
[Parallel(n_jobs=8)]: Done  69 tasks      | elapsed:    6.9s
[Parallel(n_jobs=8)]: Done  82 tasks      | elapsed:    8.3s
[Parallel(n_jobs=8)]: Done  97 tasks      | elapsed:    9.8s
[Parallel(n_jobs=8)]: Done 112 tasks      | elapsed:   10.8s
```

```
[Parallel(n_jobs=8)]: Done 129 tasks      | elapsed:   12.8s
[Parallel(n_jobs=8)]: Done 146 tasks      | elapsed:   14.3s
[Parallel(n_jobs=8)]: Done 165 tasks      | elapsed:   15.8s
[Parallel(n_jobs=8)]: Done 184 tasks      | elapsed:   17.3s
[Parallel(n_jobs=8)]: Done 205 tasks      | elapsed:   19.2s
[Parallel(n_jobs=8)]: Done 226 tasks      | elapsed:   21.1s
[Parallel(n_jobs=8)]: Done 249 tasks      | elapsed:   23.1s
[Parallel(n_jobs=8)]: Done 272 tasks      | elapsed:   25.9s
[Parallel(n_jobs=8)]: Done 300 out of 300 | elapsed:   32.3s finished
```

[10]:
```python
fig, axes = plt.subplots(
    2, 2,
    figsize=(12, 9),
    layout="constrained"
)

markers = ["o", "s", "^", "v", "D"]

design_labels = ["(A) Gaussian", "(B) Laplace", r"(C) AR(1), $\rho$=0.5", "(D) Equicorrelated", r"(E) $t_{2.2}$"]

for ki, k in enumerate(k_values):
    ax = axes.flat[ki]

    for d, design_label in enumerate(design_labels):
        ax.plot(
            n_values,
            means[d, ki, :],
            marker=markers[d],
            linewidth=1.5,
            markersize=5,
            label=design_label
        )

    reference = means[0, ki, 2] * (n_values / 80)**(-0.5)

    ax.plot(
        n_values,
        reference,
        "k--",
        linewidth=1.3,
        label=r"slope $-1/2$"
    )

    ax.set_xscale("log")
    ax.set_yscale("log")
```

```
    ax.set_title(f"k = {k}")
    ax.set_xlabel("n")
    ax.set_ylabel(r"$\delta_k(X/\sqrt{n})$")

    ax.set_xticks(n_values)
    ax.set_xticklabels(n_values)


    ax.grid(True, which="both", alpha=0.25)

handles, labels = axes[0, 0].get_legend_handles_labels()

fig.legend(
    handles, labels,
    loc="outside lower center",
    ncol=3,
    fontsize=9
)

fig.suptitle(
    f"restricted isometry constants, p={p} ({T} trials)",
    fontsize=14
)

plt.show()
```



[11]:
```
means[3, :, -1]
```

[11]:
```
array([0.14057132, 0.7134392 , 1.29582759, 1.86817295])
```

i. δ_k decays like $n^{-1/2}$ for designs (A) and (B). Despite being not sub-Gaussian, design (B) is consistent with its finite moments and exponetial tails. The entries of the sample Gram matrix still concentrate at approximately $n^{-1/2}$ rate for fixed p and k.

ii. For both (C) and (D), the rows have covariance matrix Σ. By the law of large numbers, $\frac{1}{n}X^\top X \xrightarrow{\Sigma}$. Therefore, for fixed p and k, $\lim_{n\to\infty}\delta_k = \max_{|T|=k}\|\Sigma_{TT} - I_k\|_{\text{op}}$. For design (C), $\Sigma_{ij} = \rho^{|i-j|}$, $\rho = 0.5$. Since the off diagonal correlations do not vanish, δ_k approaches a positive limit for $k \geq 2$, which we see in the simulations as the curve begins to flatten for larger k and n. For design (D), $\Sigma = (1-\rho)I_p + \rho\mathbf{1}\mathbf{1}^\top$. For a support T with $|T| = k$, we have $\Sigma_{TT} - I_k = \rho(\mathbf{1}_k\mathbf{1}_k^\top - I_k)$, and thus the eigenvalues are $\rho(k-1), -\rho, \cdots, -\rho$. Then, the limiting restricted isometry constant is $\lim_{n\to\infty}\delta_k = \begin{cases} 0, & k = 1 \\ \rho(k-1), & k \geq 2 \end{cases}$ For $\rho = 0.5$, the theoretical limit of $k = 1, 2, 3, 4$ is respectively $0, 0.5, 1, 1.5$, which the simulated values approach but remain slightly above them at $n = 640$. Then, a correlated design can satisfy k-RIP with a small constant if its population covariance is sufficiently close to the identity on every k-sparse support. However, increasing n cannot eliminate the underlying correlations.

For design (D), $\rho(k-1)$ sets the limiting RIP constant, so strong correlations prevent a small RIP constant as $n \to \infty$.

iii. Design (E) is significantly different from the rest of the designs. Its restricted isometry constant does not consistently decrease as n grows. For $k = 1$, the column norms ($\delta_1 = \max_j \left|\frac{1}{n}\sum_{i=1}^{n} X_{ij}^2 - 1\right|$) are highly unstable because the fourth moment $E[X_{ij}^4] = \infty$, therefore X_{ij}^2 has infinite variance leading to large fluctuations which we see in the graphs, especially for larger n. The RIP proof from Lecture 9 assumes a sub-Gaussian condition, which requires $(x_i^\top u)^2 - 1$ to be sub-exponential so that Bernstein's inequality provides exponential concentration. However, the Student's $t_{2.2}$ design does not satisfy this requirement.

1.2 (b)

[ ]:
```
from sklearn.linear_model import Lasso

P = 512
K = 10
N_VALUES = np.array([200, 400, 800, 1600, 3200])
DESIGNS = ["(A) Gaussian", r"(D) equicorrelated $\rho$=0.5", r"(E) $t_{2.2}$",
           "(F) duplicated column", "(G) factor model, r=5"]
TRIALS = 20
SEED = 0
RHO = 0.5
FACTOR_RANK = 5

def generate_data(design_index, n, rng):
    beta = np.zeros(P)
    if design_index == 3:
        available = np.arange(2, P)
        support = np.r_[1, rng.choice(available, size=K - 1, replace=False)]
    else:
        support = rng.choice(P, size=K, replace=False)
    beta[support] = rng.choice(np.array([-1.0, 1.0]), size=K)

    # A, F
    if design_index == 0 or design_index == 3:
        X = rng.standard_normal((n, P))
        if design_index == 3:
            X[:, 0] = X[:, 1]
    # D
    elif design_index == 1:
        z = rng.standard_normal((n, P))
        g = rng.standard_normal((n, 1))
        X = np.sqrt(1 - RHO) * z + np.sqrt(RHO) * g
    # E
    elif design_index == 2:
        X = rng.standard_t(df=2.2, size=(n, P)) / np.sqrt(11)
```

```
    # G
    else:
        V = rng.standard_normal((P, FACTOR_RANK))
        V = V / np.linalg.norm(V, axis=1, keepdims=True)
        latent = rng.standard_normal((n, FACTOR_RANK))
        X = latent @ V.T

    eps = rng.standard_normal(n)
    y = X @ beta + eps
    return X, beta, eps, y

def run_trial(design_index, n_index, trial_index, seed):
    n = int(N_VALUES[n_index])
    rng = np.random.default_rng(seed)
    X, beta, eps, y = generate_data(design_index, n, rng)
    lambda0 = np.sqrt(2 * np.log(P) / n)
    lam = 0.5 * lambda0

    with threadpool_limits(limits=1):
        solver = Lasso(alpha=lam, fit_intercept=False,
                       max_iter=50000, tol=1e-8, selection="cyclic")
        solver.fit(X, y)
    delta = solver.coef_ - beta
    estimation = float(delta @ delta)
    residual = X @ delta
    prediction = float((residual @ residual) / n)
    noise_ratio = float(np.max(np.abs(X.T @ eps / n)) / lambda0)
    if design_index == 3:
        beta_hat_1 = float(solver.coef_[0])
        beta_hat_2 = float(solver.coef_[1])
    else:
        beta_hat_1 = np.nan
        beta_hat_2 = np.nan
    return (design_index, n_index, trial_index, estimation, prediction,
            noise_ratio, beta_hat_1, beta_hat_2, bool(solver.n_iter_ >= solver.
 ↪max_iter))

configs = [(d, ni, t) for d in range(len(DESIGNS))
           for ni in range(len(N_VALUES)) for t in range(TRIALS)]
seeds = np.random.SeedSequence(0).spawn(len(configs))
result_rows = Parallel(n_jobs=8, backend="loky", verbose=10)(
    delayed(run_trial)(d, ni, t, seeds[index])
    for index, (d, ni, t) in enumerate(configs)
)
```

```
[Parallel(n_jobs=8)]: Using backend LokyBackend with 8 concurrent workers.
[Parallel(n_jobs=8)]: Done   2 tasks      | elapsed:    2.5s
[Parallel(n_jobs=8)]: Done   9 tasks      | elapsed:    2.5s
```

```
[Parallel(n_jobs=8)]: Done  16 tasks      | elapsed:    2.6s
[Parallel(n_jobs=8)]: Done  25 tasks      | elapsed:    2.6s
[Parallel(n_jobs=8)]: Batch computation too fast (0.19974150234096363s.) Setting
batch_size=2.
[Parallel(n_jobs=8)]: Done  34 tasks      | elapsed:    2.6s
[Parallel(n_jobs=8)]: Done  45 tasks      | elapsed:    2.6s
[Parallel(n_jobs=8)]: Batch computation too fast (0.06576704978942871s.) Setting
batch_size=4.
[Parallel(n_jobs=8)]: Done  64 tasks      | elapsed:    2.7s
[Parallel(n_jobs=8)]: Done 100 tasks      | elapsed:    3.0s
[Parallel(n_jobs=8)]: Done 152 tasks      | elapsed:    3.3s
[Parallel(n_jobs=8)]: Done 212 tasks      | elapsed:    4.5s
[Parallel(n_jobs=8)]: Done 272 tasks      | elapsed:    5.7s
[Parallel(n_jobs=8)]: Done 340 tasks      | elapsed:    6.2s
[Parallel(n_jobs=8)]: Done 408 tasks      | elapsed:    6.8s
[Parallel(n_jobs=8)]: Done 500 out of 500 | elapsed:   36.9s finished
```

[28]:
```
est = np.empty((len(DESIGNS), len(N_VALUES), TRIALS))
pred = np.empty_like(est)
noise = np.empty_like(est)
duplicates = np.full((len(N_VALUES), TRIALS, 2), np.nan)
n_nonconverged = 0
for d, ni, t, a, b, c, b1, b2, warn in result_rows:
    est[d, ni, t] = a
    pred[d, ni, t] = b
    noise[d, ni, t] = c
    if d == 3:
        duplicates[ni, t] = [b1, b2]
    n_nonconverged += int(warn)

def summarize(data):
    return data.mean(axis=2), data.std(axis=2, ddof=1) / np.sqrt(TRIALS)

est_mean, est_sem = summarize(est)
pred_mean, pred_sem = summarize(pred)
noise_mean, noise_sem = summarize(noise)
np.savez("results_4b.npz", est=est, pred=pred, noise=noise,
            duplicates=duplicates, est_mean=est_mean, est_sem=est_sem,
            pred_mean=pred_mean, pred_sem=pred_sem,
            noise_mean=noise_mean, noise_sem=noise_sem, n_values=N_VALUES,
            designs=np.array(DESIGNS), trials=TRIALS, seed=0)

styles = [
    {"color": "tab:blue",    "marker": "D"},
    {"color": "red",     "marker": "v"},
    {"color": "purple",  "marker": "D"},
    {"color": "brown",   "marker": "x"},
```

```
    {"color": "hotpink", "marker": "D"}
]


fig, axes = plt.subplots(1, 2, figsize=(13, 5.3), layout="constrained")
for ax, mean, sem, title, ylabel in (
    (axes[0], est_mean, est_sem, r"estimation error, p=512, k=10, $\lambda =␣
 ↪\frac{1}{n}\lambda_0$", r"$\|\hat\beta-\beta^*\|_2^2$"),
    (axes[1], pred_mean, pred_sem, r"prediction error p=512, k=10, $\lambda =␣
 ↪\frac{1}{n}\lambda_0$", r"$\frac{1}{n}\|X(\hat\beta-\beta^*)\|_2^2$")
):
    for d, name in enumerate(DESIGNS):
        style = styles[d]

        ax.errorbar(
            N_VALUES,
            mean[d],
            yerr=sem[d],
            fmt="-",
            color=style["color"],
            marker=style["marker"],
            markersize=7,
            capsize=3,
            linewidth=1.5,
            label=name
        )
    anchor = mean[0, 2]
    ref = anchor * (N_VALUES / N_VALUES[2]) ** (-1)
    ax.plot(N_VALUES, ref, "k--", linewidth=1.3, label="slope -1")
    ax.set_xscale("log")
    ax.set_yscale("log")
    ax.set_xticks(N_VALUES)
    ax.set_xticklabels([str(x) for x in N_VALUES])
    ax.set_title(title)
    ax.set_xlabel("n")
    ax.set_ylabel(ylabel)
    ax.grid(which="both", alpha=0.25)
handles, labels = axes[0].get_legend_handles_labels()
fig.legend(handles, labels, loc="outside lower center", ncol=3)
plt.show()

print("\nNoise ratio E[||X.T eps/n||_inf] / lambda0")
print("n       Gaussian mean  Gaussian SEM  t(2.2) mean  t(2.2) SEM")
for ni, n in enumerate(N_VALUES):
    print(f"{n:<7d} {noise_mean[0,ni]:13.4f} {noise_sem[0,ni]:13.4f} "
          f"{noise_mean[2,ni]:13.4f} {noise_sem[2,ni]:13.4f}")

print("\nDuplicated-column solver behavior (F):")
```

```
for ni, n in enumerate(N_VALUES):
    print(f"n={n}: average beta_hat[0]={duplicates[ni,:,0].mean():.5f}, "
          f"beta_hat[1]={duplicates[ni,:,1].mean():.5f}, "
          f"fraction |beta_hat[0]|>1e-6={np.mean(np.abs(duplicates[ni,:
 ↪,0])>1e-6):.2f}")
```




```
Noise ratio E[||X.T eps/n||_inf] / lambda0
n       Gaussian mean  Gaussian SEM  t(2.2) mean  t(2.2) SEM
200            0.9263        0.0178       2.4265       0.3740
400            0.9335        0.0219       2.2622       0.4071
800            0.9110        0.0319       2.5482       0.4971
1600           0.8937        0.0240       1.9249       0.3607
3200           0.9554        0.0235       1.5739       0.1641

Duplicated-column solver behavior (F):
n=200: average beta_hat[0]=-0.11785, beta_hat[1]=0.00000, fraction
|beta_hat[0]|>1e-6=1.00
n=400: average beta_hat[0]=0.38528, beta_hat[1]=0.00000, fraction
|beta_hat[0]|>1e-6=1.00
n=800: average beta_hat[0]=0.09976, beta_hat[1]=-0.00000, fraction
|beta_hat[0]|>1e-6=1.00
n=1600: average beta_hat[0]=-0.18843, beta_hat[1]=-0.00000, fraction
|beta_hat[0]|>1e-6=1.00
n=3200: average beta_hat[0]=0.19527, beta_hat[1]=0.00000, fraction
|beta_hat[0]|>1e-6=1.00
```

i. From part (a), design (D) does not satisfy k-RIP with a small constant when k is large, since its population covariance is $\Sigma = (1-\rho)I_p + \rho\mathbf{1}\mathbf{1}^\top$. However, LASSO only requires the RE condition, which is weaker than RIP. So, for any $u \in \mathbb{R}^p$, $u^\top\Sigma u = (1-\rho)\|u\|_2^2 + \rho(\mathbf{1}^\top u)^2 \geq (1-\rho)\|u\|_2^2$, since $\rho(\mathbf{1}\top u)^2 \geq 0$. Thus, $u^\top\Sigma u \geq \lambda_{\min}(\Sigma)\|u\|_2^2$. The eigenvalues of Σ are $1-\rho$ (multiplicity $p-1$), and $1+(p-1)\rho$ (multiplicity 1). Therefore, for any $\rho = 0.5$,

$\lambda_{\min}(\Sigma) = 1 - \rho = 0.5$, and $u^\top \Sigma u \geq 0.5\|u\|_2^2$. This establishes the RE condition with $\kappa = 0.5$, even for all vectors u. According to the LASSO bound, $\|\widehat{\beta} - \beta^*\|_2 \leq \frac{3\lambda\sqrt{k}}{\kappa}$. Since $\lambda^2 \asymp \log(p)/n$, the squared estimation error is expected to decrease at approximately fast rate $1/n$ when the sample RE condition is sufficiently controlled. The LASSO analysis then uses the lower side of the restricted isometric inequality $\frac{1}{n}\|Xu\|_2^2 \geq \kappa\|u\|_2^2$, allowing a correlated design to violate small constant RIP and still permit accurate LASSO estimation.

ii. Design (E) generally has larger estimation errors than design (A), but both estimation and prediction errors decrease as the sample size increases. However, (E) has less stable recovery due to its larger observations. We can see that the Gaussian noise levels remain around 0.9, while the heavy tailed ratios are consistently larger, ranging from 1.5 to 2.5, almost a 2x increase. Since $\lambda = \frac{1}{2}\lambda_0$, the noise condition requires $\|\frac{1}{n}X^\top \epsilon\|_\infty \leq \frac{\lambda_0}{4}$. The reported noise ratios are much greater than 0.25, thus chosen regularization levels do not reliably enforce (N). Heavy tails also affect the design condition, since extreme observations make the sample Gram matrix less stable, which we can see with the irregular restriced isometry constants. Thus, from the reported table and panels, we can see t hat heavy tails affects both conditions.

iii. In (F), since column 1 is a duplicate of column 2, $X_1 = X_2$, and the true support S will always contain coordinate 2 but never coordinate 1. Consider the nonzero vector $\Delta = e_1 - e_2$. Because the columns are identical, $X\Delta = X_1 - X_2 = 0$. Also, $\|\Delta_{S^c}\|_1 = 1$ and $\|\Delta_S\|_1 = 1$. Therefore, Δ satisfies the cone condition, but $\frac{1}{n}\|X\Delta\|_2^2 = 0$ and $\|\Delta\|_2^2 = 2$, thus the restricted eigenvalue identity $\frac{1}{n}\|X\Delta\|_2^2 \geq \kappa\|\Delta\|_2^2$ can't hold for any $\kappa > 0$. Therefore, the RE condition fails for design (F). For design (G), the factor model is $X = GV^\top$. Since both matrices have 5 columns and are full column rank almost surely, the rank of X is 5. The true support has size $|S| = 10$, therefore $rank(X_s) \leq 5 \leq 10$. Thus, the 10 columns of X_S are linearly dependent, meaning there exists a nonzero vector Δ supported on S such that $X\Delta = 0$. Since Δ is supported entirely on S, $\|\Delta_{S^c}\|_1 = 0 \leq 3\|\Delta_S\|_1$, but again, $\frac{1}{n}\|X\Delta\|_2^2 = 0 < \kappa\|\Delta\|_2^2$, for every $\kappa > 0$, and hence, the RE condition also fails for design (G). Because both designs have nonzero vectors in the null space of X, different coefficient vectors can produce the same response. Therefore, the true coefficient vector is not uniquely identifiable, even as $n \to \infty$. Consequently, the squared estimation error doesn't need to converge to 0, but the prediction error can approach 0 because the estimator can accurately recover $X\beta^*$ without recovering the exact coefficients. We can see this in the simulation, as designs (F) and (G) exhibit decrease prediction errors but persistent estimation errors. For design (F), I used `sklearn.linear_model.Lasso` with cyclic coordinate descent (`selection='cyclic'`). Across all 100 trials, the solver assigned the nonzero duplicated-column coefficient to coordinate 1, while coordinate 2 remained approximately zero. Since $X_1 = X_2$, $X_1\widehat{\beta}_1 + X_2\widehat{\beta}_2 = X_2(\widehat{\beta}_1 + \widehat{\beta}_2)$. Therefore, the fitted response only depends on the sum of the two coefficients. When this sum is nonzero, multiple allocations with the same sign and total magnitude produce the same fitted response and ℓ_1 penalty, so the LASSO minimizer is not unique. The cyclic coordinate-descent solver updates coordinate 1 first, allowing it to absorb the shared coefficient while coordinate 2 remains zero. The reported average of $\widehat{\beta}_1$ changes sign because the true coefficient is randomly ± 1 across trials. Thus, the solver can produce accurate predictions while assigning the coefficient to the wrong variable.

1.3 (c)

[30]:
```
P, K, N = 512, 10, 800
RHOS = np.array([0, 0.5, 0.8, 0.9, 0.95, 0.98, 0.99])
TRIALS = 20
SEED = 0

LAMBDA0 = np.sqrt(2 * np.log(P) / N)
LAM = 0.5 * LAMBDA0

def run_trial(rho_index, trial_index, seed):
    rho = float(RHOS[rho_index])
    rng = np.random.default_rng(seed)

    # True k-sparse coefficient vector
    beta = np.zeros(P)
    support = rng.choice(P, size=K, replace=False)
    beta[support] = rng.choice([-1.0, 1.0], size=K)

    # Equicorrelated Gaussian design
    z = rng.standard_normal((N, P))
    common = rng.standard_normal((N, 1))
    X = np.sqrt(1 - rho) * z + np.sqrt(rho) * common

    # Response
    eps = rng.standard_normal(N)
    y = X @ beta + eps

    # LASSO fit
    with threadpool_limits(limits=1):
        solver = Lasso(
            alpha=LAM,
            fit_intercept=False,
            max_iter=50000,
            tol=1e-8,
            selection="cyclic"
        )
        solver.fit(X, y)

    delta = solver.coef_ - beta

    estimation = float(delta @ delta)
    Xdelta = X @ delta
    prediction = float(Xdelta @ Xdelta / N)

    noise_ratio = float(
        np.max(np.abs(X.T @ eps / N)) / LAMBDA0
```

```
    )

    nonconverged = solver.n_iter_ >= solver.max_iter

    return (
        rho_index,
        trial_index,
        estimation,
        prediction,
        noise_ratio,
        nonconverged
    )

configs = [
    (i, t)
    for i in range(len(RHOS))
    for t in range(TRIALS)
]

seeds = np.random.SeedSequence(0).spawn(
    len(configs)
)

results = Parallel(
    n_jobs=8,
    backend="loky",
    verbose=5
)(
    delayed(run_trial)(i, t, seeds[index])
    for index, (i, t) in enumerate(configs)
)

estimation = np.empty((len(RHOS), TRIALS))
prediction = np.empty_like(estimation)
noise_ratio = np.empty_like(estimation)

nonconverged = 0

for i, t, e, q, r, warning in results:
    estimation[i, t] = e
    prediction[i, t] = q
    noise_ratio[i, t] = r
    nonconverged += int(warning)

mean_est = estimation.mean(axis=1)
mean_pred = prediction.mean(axis=1)
```

```
sem_est = (
    estimation.std(axis=1, ddof=1) / np.sqrt(TRIALS)
)
sem_pred = (
    prediction.std(axis=1, ddof=1) / np.sqrt(TRIALS)
)

fast = 9 * K * LAM**2 / (1 - RHOS)
slow = 3 * LAM * K

np.savez(
    "results_4c.npz",
    rhos=RHOS,
    estimation=estimation,
    prediction=prediction,
    noise_ratio=noise_ratio,
    mean_est=mean_est,
    mean_pred=mean_pred,
    sem_est=sem_est,
    sem_pred=sem_pred,
    bound_fast=fast,
    bound_slow=slow,
    seed=SEED,
    trials=TRIALS
)
```

```
[Parallel(n_jobs=8)]: Using backend LokyBackend with 8 concurrent workers.
[Parallel(n_jobs=8)]: Done   2 tasks      | elapsed:    2.7s
[Parallel(n_jobs=8)]: Done  64 tasks      | elapsed:    3.5s
[Parallel(n_jobs=8)]: Done 125 out of 140 | elapsed:   10.1s remaining:    1.1s
[Parallel(n_jobs=8)]: Done 140 out of 140 | elapsed:   15.5s finished
```

[37]:
```
fig, ax = plt.subplots(figsize=(10, 6.2))

x = 1 - RHOS

ax.errorbar(
    x, mean_est,
    yerr=sem_est,
    fmt="D-",
    color="red",
    capsize=3,
    linewidth=1.7,
    markersize=6,
    label=r"estimation $\|\hat{\beta} - \beta^*\|_2^2$"
)
```

```
ax.errorbar(
    x, mean_pred,
    yerr=sem_pred,
    fmt="s-",
    color="tab:blue",
    capsize=3,
    linewidth=1.7,
    markersize=6,
    label=r"prediction $\frac{1}{n}\|X\hat{\beta} - X\beta^*\|_2^2$"
)

ax.plot(
    x, fast,
    "--",
    color="red",
    linewidth=2,
    label=r"prediction bound of 1(c): $9k\lambda^2/\kappa$, $\kappa = 1 - \rho$"
)

ax.plot(
    x, np.full_like(x, slow),
    "--",
    color="tab:blue",
    linewidth=2,
    label=r"prediction bound of 1(d): $3\lambda\|\beta^*\|_1$"
)

ax.set_xscale("log")
ax.set_yscale("log")

ax.set_xticks(x)
ax.set_xticklabels([f"{rho:g}" for rho in RHOS])

ax.invert_xaxis()


ax.set_xlabel(r"$\rho$ (axis is $1-\rho$, log scale)")
ax.set_ylabel("squared error")
ax.set_title("equicorrelated design, p=512, k=10, n=800")

ax.grid(True, which="both", alpha=0.25)
ax.legend()
fig.tight_layout()
plt.show()

print(
    "rho    est mean   est SEM  "
    "pred mean  pred SEM  fast bound  slow bound"
```

```
)

for i, rho in enumerate(RHOS):
    print(
        f"{rho:4.2f}  "
        f"{mean_est[i]:9.4f} {sem_est[i]:9.4f}  "
        f"{mean_pred[i]:9.4f} {sem_pred[i]:9.4f} "
        f"{fast[i]:11.4f} {slow:11.4f}"
    )
```



rho	est mean	est SEM	pred mean	pred SEM	fast bound	slow bound
0.00	0.0649	0.0039	0.0614	0.0032	0.3509	1.8732
0.50	0.1977	0.0138	0.0951	0.0056	0.7018	1.8732
0.80	0.9523	0.0304	0.1892	0.0055	1.7545	1.8732
0.90	3.8665	0.1191	0.3724	0.0082	3.5091	1.8732
0.95	6.7022	0.3943	0.3310	0.0200	7.0181	1.8732
0.98	7.5633	0.4128	0.1542	0.0095	17.5453	1.8732
0.99	8.0551	0.3727	0.0837	0.0037	35.0906	1.8732

As $\rho \to 1$, the estimatino error increases, while the prediction error initially increases then decreases. This occurs because, as $\rho \to 1$, the columns of X become nearly identical. Consequently, it becomes increasingly difficult to distinguish individual coefficients, even though the model can still accurately predict the response. Therefore, high correlation substantially worsens coefficient estimation but doesn't necessarily worsen prediction accuracy. Both bounds are respected by the empirical mean prediction error at every tested ρ. However, this does not guarantee that every individual trial satisfies the bounds, since the theoretical guarantees require the noise condition (N), and the fast-

rate bound additionally requires the sample restricted eigenvalue condition (RE). As $\rho \to 1$, the fast bound diverges to ∞, while the slow bound remains constant. Thus, the slow bound is more informative for ρ close to 1. When ρ is close to 1, the columns of X become nearly identical, making it difficult to recover the true coefficients. Thus, the estimation error can remain large even when the prediction error is small. Consider $\Delta = e_1 - e_2$. The squared estimation error is $\|\Delta\|_2^2 = 2$, but the expected prediction error is $E[\frac{1}{n}\|X\Delta\|2_2] = \Delta^\top \Sigma \Delta = 2(1-\rho)$. As $\rho \to 1$, the prediction error approaches zero, while the estimation error remains 2, which we can see in the plot at $\rho = 0.99$, the estimation error is high at 8.0551 but the prediction error is only 0.0837. High correlation can prevent accurate coefficient recovery while still allowing accurate predictions.

AI Usage: All homework problems were written in VSCode and compiled using LaTeX (Problem 4 utilized Jupyter notebook), with assistance from ChatGPT and Github Copilot inline suggestions.