

15. Challenges Faced and Resolution

15.1 Base URL Configuration Issue

◆ Challenge:

Initially, APIs were not executing correctly because the **base URL was hardcoded** in multiple requests instead of using environment variables.

Example issue:

```
https://fakestoreapi.com/products
```

Instead of:

```
{{baseUrl}}/products
```

◆ Impact:

- If base URL changed, all requests failed
 - Difficult to maintain collection
 - Not suitable for automation
-

◆ Resolution:

- Created environment variable:

```
baseUrl = https://fakestoreapi.com
```

- Updated all endpoints to use:

```
{{baseUrl}}/products
```

◆ Result:

- Improved reusability
 - Easy environment switching (QA/Dev/Prod)
 - Collection became automation-ready
-

15.2 Environment Variable Export Issue

◆ Challenge:

While running Newman, environment variables like:

- authToken
- productId

were not being passed correctly.

◆ Impact:

- APIs failed in Newman execution
 - Token-dependent APIs returned 401 Unauthorized
-

◆ Resolution:

- Properly exported environment file from Postman
- Ensured variables were initialized before execution
- Used scripts to store values:

```
pm.environment.set("authToken", pm.response.json().token);
```

◆ Result:

- Variables successfully passed to Newman
 - End-to-end flow worked smoothly
-

15.3 Invalid URI Issue in Newman

◆ Challenge:

Newman showed error:

```
Invalid URI
```

◆ Cause:

- Incorrect baseURL formatting
 - Missing protocol (http/https)
 - Extra spaces in environment variable
-

◆ Example mistake:

```
baseURL = fakestoreapi.com ✕
```

◆ Resolution:

Corrected to:

```
baseURL = https://fakestoreapi.com ✓
```

Also:

- Removed trailing spaces
 - Verified variable syntax
-

◆ Result:

- All API endpoints executed successfully in Newman CLI
-

15.4 Collection Execution Issue

◆ Challenge:

Some APIs failed when running via Collection Runner:

- Order of execution was incorrect
 - Dependent APIs ran before token generation
-

◆ Impact:

- Cart and Product APIs failed
 - Authentication dependency broken
-

◆ Resolution:

- Reordered collection execution flow:
 1. Authentication
 2. Products
 3. Cart
 4. Users
 - Used Postman folder structure to maintain sequence
-

◆ Result:

- Smooth end-to-end execution
 - No dependency failure
-

15.5 Newman Report Generation Issue

◆ Challenge:

HTML reports were not generating properly in Newman.

Errors included:

- Reporter not found
 - Blank report output
 - Missing plugin errors
-

◆ Cause:

- Reporter plugin not installed
 - Incorrect command syntax
-

◆ Resolution:

Installed correct reporter:

```
npm install -g newman-reporter-htmlextra
```

Correct execution command:

```
newman run collection.json -e environment.json -r htmlextra
```

◆ Result:

- Proper HTML reports generated
 - Visual dashboards available
 - Easy test analysis achieved
-