

Paper and board finishing process

Laminating, varnishing, hot foil blocking, embossing

Link Link

Laminating



Laminating is a versatile manufacturing process that involves bonding two or more layers of material together to form a composite with improved properties, such as enhanced strength, durability, or aesthetics. This process can be achieved using various methods, including heat, pressure, or adhesives. Laminating is widely used across different industries, from protecting everyday documents to creating durable kitchen worktops and engineered wood products.

Everyday Desktop Lamination

This method uses a desktop laminator and pre-made pouches to protect documents, photos, or create graphic products like puzzles, tags, and labels.

- Preparation: The item to be laminated is placed inside a laminating pouch (which comes in various thicknesses).
- Application: The pouch is fed through a heated desktop laminator.
- Bonding: The heat and pressure from the machine melt the adhesive within the pouch, sealing it around the document and bonding the layers together for durability.



Industrial and DT Lamination (e.g., Formica, Veneer)

This process is used in Design and Technology to create durable surfaces and engineered boards like plywood, often involving contact adhesives or PVA glue and mechanical presses.

- Preparation: The substrate (e.g., MDF, chipboard, plywood) and the laminate material (e.g., Formica, real wood veneer) are prepared.
- Adhesive Application: A suitable adhesive (contact adhesive for Formica, PVA for veneer) is applied to the surfaces being joined.
- Bonding/Pressing: The layers are aligned and then pressed together. For veneers, a press is used until the PVA adhesive dries to ensure a strong, flat bond.
- Shaping (Optional): In some applications, like cold moulding plywood, the layers are pressed around a curved former to create specific shapes.

Link Link

Laminating

Key Aspects and Applications

- Enhanced Properties: Lamination improves material properties, such as creating smooth, easy-to-clean surfaces (kitchen worktops), adding durability to decoupage, or increasing the strength and stability of manufactured boards (plywood).
- Material Types: Common substrates include chipboard, MDF, and plywood, which are often faced with laminates like Formica or real wood veneer.
- Adhesives: The choice of adhesive is crucial, with heat-activated adhesives used in pouches, contact adhesives for Formica, and PVA for wood veneers.





Varnishing

Varnishing is the application of a transparent liquid coat to a printed surface to enhance its appearance (aesthetics) and provide protection (functionality) against dirt, moisture, and general handling.

Traditional Varnishing (Water/Oil-based)

- Process: Varnish is applied as a clear, liquid ink using a printing press (often offset lithography). It can cover the whole surface (flood varnish) or specific areas (spot varnish).
- Drying Time: Traditional varnishes contain solvents (water or oil-based) that must evaporate to dry and cure the coating. This process is slow, often taking two hours or more during which the printed sheets must be carefully handled and stacked to prevent smudging or sticking. This slows down the overall production cycle.
- Finish: Available in gloss, silk, and matte finishes, offering moderate protection and enhancing colours.

UV varnishing



Advantages

- Speed: Instant drying allows the product to move immediately to the next stage of production (e.g., cutting, folding, binding), significantly speeding up the manufacturing process.
- High Gloss & Aesthetics: UV varnish produces the highest possible gloss finish, making images and colours "pop" and creating a premium, eye-catching look.
- Durability: The cured coating forms a hard, abrasion-resistant, and chemically resistant layer, offering superior protection compared to traditional varnish.
- Eco-friendliness: UV coatings are often 100% solid and contain few or no Volatile Organic Compounds (VOCs), reducing harmful emissions.

Disadvantages

- Cost: The initial machinery is more expensive than traditional systems.
- Material Limitations: Not suitable for all paper types (porous or uncoated papers absorb the varnish) and the hard coating may crack when scored or folded.
- Safety: UV light exposure requires safety precautions and ventilation systems to protect workers.

Spot UV Varnishing

This is where the UV varnish is applied only to specific, targeted areas of the print design rather than the entire surface.
It creates a striking contrast between the glossy highlighted elements (e.g., a logo, text, or pattern) and the surrounding surface, which is often a matte or soft-touch laminate.



Other special finishes


UV Sparkle Finish
- A variation of UV varnishing where metallic or glitter particles are mixed into the clear UV polymer before application. This creates a shimmering, highly decorative finish, popular on greeting cards or premium packaging.


Fragrance Burst Inks (Scented Inks)
- These are printing inks containing microencapsulated fragrances.
- The ink is applied during the printing process. The scent is released when the coating is scratched or rubbed, breaking the tiny capsules.
- Use: Often used on magazine inserts, scratch-and-sniff stickers, or promotional materials to add an interactive, multi-sensory element.

Silver Latex Scratch-offs
- A functional finish widely used for lottery tickets, phone cards, or promotional campaigns.
- Process: A layer of opaque, metallic silver (or sometimes gold) latex ink is screen printed over pre-printed information (e.g., a prize-winning code).
- Function: The latex is designed to be easily scratched off by the user to reveal the information underneath, while remaining durable enough to withstand normal handling prior to use.

Hot foil blocking

- Foil blocking is a specialty printing process where a thin layer of metallic foil is applied to the print surface.
- It has the effect of creating a shiny, eye-catching surface that imparts a high-quality, luxury feel to the product.
- Foils come in a variety of colours, not just gold or silver, giving designers a wide range of options for visual effects.








Embossing/Debossing

- Embossing and debossing are processes that create raised or recessed designs respectively on a paper or board surface.
- These processes can be executed with or without ink to create a more tactile experience, adding depth and dimension to the print.
- Embossing is a process that creates a raised pattern on the paper or card and is made using a stamping process. Embossing adds texture and depth to a product and is often found on greetings cards or on perfume and aftershave boxes to raise the logo and make it eye-catching.






EMBOSS