



**INSTITUTE OF TECHNOLOGY AND MANAGEMENT
SKILLS UNIVERSITY,
KHARGHAR, NAVI MUMBAI**

**DATA STRUCTURES & ALGORITHMS
PROGRAMMING LAB**



Prepared by:

Name of Student : Tanish

Roll No: 32

Batch: 2023-27

Dept. of CSE

DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING



**INSTITUTE OF TECHNOLOGY AND MANAGEMENT
SKILLS UNIVERSITY,
KHARGHAR, NAVI MUMBAI**

CERTIFICATE

This is to certify that Mr. / Ms. _____
Roll No. _____ Semester _____ of B.Tech Computer Science &
Engineering, ITM Skills University, Kharghar, Navi Mumbai , has completed the term
work satisfactorily in subject _____ for the
academic year 20____ - 20____ as prescribed in the curriculum.

Place: _____

Date: _____

Subject I/C

HOD

Exp. No	List of Experiment	Date of Submission	Sign
1	Implement Array and write a menu driven program to perform all the operation on array elements		
2	Implement Stack ADT using array.		
3	Convert an Infix expression to Postfix expression using stack ADT.		
4	Evaluate Postfix Expression using Stack ADT.		
5	Implement Linear Queue ADT using array.		
6	Implement Circular Queue ADT using array.		
7	Implement Singly Linked List ADT.		
8	Implement Circular Linked List ADT.		
9	Implement Stack ADT using Linked List		
10	Implement Linear Queue ADT using Linked List		
11	Implement Binary Search Tree ADT using Linked List.		
12	Implement Graph Traversal techniques: a) Depth First Search b) Breadth First Search		
13	Implement Binary Search algorithm to search an element in an array		
14	Implement Bubble sort algorithm to sort elements of an array in ascending and descending order		

Name of Student: Tanish

Roll Number: 32

Experiment No: 1

Title: Implement Array and write a menu driven program to perform all the operation on array elements

Theory: Array is a collection of elements of similar data types and has a fixed size. We can access an element of the array through it's index. Indexing starts from 0 till n-1(where n=size of array). An element can be inserted in the array by shifting all the elements of the array to the right and making space for the element. Similarly, to delete an element, we need to shift all the elements from the right of the deleted element to the left side in order to overwrite the deleted element. In order to search for an element, we need to traverse through the array and print the appropriate message if the element is found or not.

Code:

```
// menu driven array operations program - 1.display array 2.insert
at beginning 3.insert at end 4.insert before an element 5.insert
after an element 6.delete at beginning 7.delete at end 8.delete
before an element 9.delete after an element 10.search an element
11.number of elements
#include <iostream>
#include <algorithm>
using namespace std;

void displayArray(int &a, int arr[]) // function to display array
and number of elements in array
{
    int count = 0;
    cout << "Array: ";
    for (int i = 0; i < a; i++)
    {
        if (arr[i] != -1)
        {
            cout << arr[i] << " ";
            count++;
        }
    }
}
```

```

        else
        {
            break;
        }
    }
    cout << endl;
    << "Number of elements: " << count << endl;
}

```

```

void insertAtBegin(int &a, int arr[]) // function to insert element
at the beginning of the array
{

```

```

    if (a >= 45)
    {
        cout << "Array is full. Cannot insert at the beginning." <<
endl;
        return;
    }
    int b, count = 0;
    cout << "Enter beginning detail: ";
    cin >> b;
    for (int i = a - 1; i >= 0; i--)
    {
        arr[i + 1] = arr[i];
    }
    arr[0] = b;
    a++;
    for (int i = 0; i < a; i++)
    {
        if (arr[i] == -1)
        {
            break;
        }
        else
        {
            count++;
        }
    }
    for (int i = 0; i < count; i++)
    {
        cout << arr[i] << " ";
    }
}

```

```

void insertAtEnd(int &a, int arr[]) // function to insert element
at the end of the array
{

```

```

    if (a >= 45)
    {

```

```

        cout << "Array is full. Cannot insert at the end." << endl;
        return;
    }
    int b, count = 0;
    cout << "Enter end detail: ";
    cin >> b;
    for (int i = 0; i < a; i++)
    {
        if (arr[i] == -1)
        {
            break;
        }
        else
        {
            count++;
        }
    }
    arr[count] = b;
    count++;
    cout << "Size of array: " << count << endl;
    a = count;
    for (int i = 0; i < count; i++)
    {
        cout << arr[i] << " ";
    }
}

void insertAtIndexLocation(int &c, int arr[]) // function to insert
element at specified index location in the array
{
    int a, b;
    cout << "Enter updated detail: ";
    cin >> b;
    cout << "Enter index location: ";
    cin >> a;
    int i = c - 1;
    while (i >= a)
    {
        arr[i + 1] = arr[i];
        i--;
    }
    c++;
    arr[a] = b;
    for (int i = 0; i < c; i++)
    {
        cout << arr[i] << " ";
    }
}

```

```
void insertBeforeElement(int &c, int arr[]) // function to insert
element before specified element in the array
```

```
{
    int b, a, pos;
    cout << "Enter updated detail: ";
    cin >> b;
    cout << "Enter element to insert before: ";
    cin >> a;
    for (int i = 0; i < c; i++)
    {
        if (arr[i] == a)
        {
            pos = i;
        }
    }
    for (int i = c - 1; i >= pos; i--)
    {
        arr[i + 1] = arr[i];
    }
    c++;
    arr[pos] = b;
    for (int i = 0; i < c; i++)
    {
        cout << arr[i] << " ";
    }
}
```

```
void insertAfterElement(int &c, int arr[]) // function to insert
element after specified element in the array
```

```
{
    int b, a, pos;
    cout << "Enter updated detail: ";
    cin >> b;
    cout << "Enter element to insert after: ";
    cin >> a;
    for (int i = 0; i < c; i++)
    {
        if (arr[i] == a)
        {
            pos = i;
        }
    }
    for (int i = c - 1; i > pos; i--)
    {
        arr[i + 1] = arr[i];
    }
    c++;
    arr[pos + 1] = b;
    for (int i = 0; i < c; i++)
```

```

    {
        cout << arr[i] << " ";
    }
}

void deleteFromBegin(int &c, int arr[]) // function to delete
element from beginning of the array
{
    for (int i = 0; i < c; i++)
    {
        arr[i] = arr[i + 1];
    }
    c--;
    for (int i = 0; i < c; i++)
    {
        cout << arr[i] << " ";
    }
}

void deleteFromEnd(int &c, int arr[]) // function to delete element
from end of the array
{
    if (c <= 0)
    {
        cout << "Array is empty. Cannot delete from the end." <<
endl;
        return;
    }
    arr[c - 1] = arr[c];
    c--;
    for (int i = 0; i < c; i++)
    {
        cout << arr[i] << " ";
    }
}

void deleteBeforeElement(int &c, int arr[]) // function to delete
element before specified element in the array
{
    int b, pos;
    cout << "Enter element to delete after it: ";
    cin >> b;
    for (int i = 0; i < c; i++)
    {
        if (arr[i] == b)
        {
            pos = i;
        }
    }
}

```



```

    for (int i = pos - 1; i < c; i++)
    {
        arr[i] = arr[i + 1];
    }
    c--;
    for (int i = 0; i < c; i++)
    {
        cout << arr[i] << " ";
    }
}

```

```

void deleteAfterElement(int &c, int arr[]) // function to delete
element after specified element in the array
{

```

```

    int b, pos;
    cout << "Enter element to delete after it: ";
    cin >> b;
    for (int i = 0; i < c; i++)
    {
        if (arr[i] == b)
        {
            pos = i;
        }
    }
    for (int i = pos + 1; i < c; i++)
    {
        arr[i] = arr[i + 1];
    }
    c--;
    for (int i = 0; i < c; i++)
    {
        cout << arr[i] << " ";
    }
}

```

```

void deleteFromArray(int &a, int arr[]) // function to delete
elements from array
{

```

```

    int b, pos;
    cout << "Enter element to delete: ";
    cin >> b;
    for (int i = 0; i < a; i++)
    {
        if (arr[i] == b)
        {
            pos = i;
        }
    }
    for (int i = pos; i < a; i++)

```

```

    {
        arr[i] = arr[i + 1];
    }
    a--;
    for (int i = 0; i < a; i++)
    {
        cout << arr[i] << " ";
    }
}

```

```

void searchElement(int &a, int arr[]) // function to search an
element in the array

```

```

{
    int b, count = 0;
    cout << "Enter element to search: ";
    cin >> b;
    for (int i = 0; i < a; i++)
    {
        if (arr[i] == b)
        {
            cout << "Element found at index " << i << endl;
            count++;
        }
    }
    if (count == 0)
    {
        cout << "Element not found" << endl;
    }
}

```

```

int main()
{
    int arr[32], n, choice;
    fill_n(arr, 32, -1);
    cout << "Enter number of details you want to enter (less than
45): ";
    cin >> n;
    while (n >= 45 || n <= 0)
    {
        cout << "Invalid size. Enter a valid size" << endl;
        cin >> n;
    }
    for (int i = 0; i < n; i++)
    {
        cout << "Enter detail: ";
        cin >> arr[i];
    }
    char ans = 'y';
    while (ans == 'y')

```

```

    {
        cout << "Enter your choice:\n1. Insert element at
beginning\n2. Insert element at end\n3. Insert element at a
particular index position\n4. Insert element before an element\n5.
Insert element after an element\n6. Delete element from
beginning\n7. Delete element from end\n8. Delete element before a
particular element\n9. Delete element after a particular
element\n10. Search an element\n11. Delete element from array\n12.
Display array\n13. Exit\n";
        cin >> choice;

        switch (choice)
        {
            case 1:
                insertAtBegin(n, arr);
                break;
            case 2:
                insertAtEnd(n, arr);
                break;
            case 3:
                insertAtIndexLocation(n, arr);
                break;
            case 4:
                insertBeforeElement(n, arr);
                break;
            case 5:
                insertAfterElement(n, arr);
                break;
            case 6:
                deleteFromBegin(n, arr);
                break;
            case 7:
                deleteFromEnd(n, arr);
                break;
            case 8:
                deleteBeforeElement(n, arr);
                break;
            case 9:
                deleteAfterElement(n, arr);
                break;
            case 10:
                searchElement(n, arr);
                break;
            case 11:
                deleteFromArray(n, arr);
                break;
            case 12:
                displayArray(n, arr);
                break;
        }
    }
}

```

```

        case 13:
            cout << "Exiting..." << endl;
            return 0;
        default:
            cout << "Invalid choice\n";
    }
    cout << "Want to perform another operation? (y/n): ";
    cin >> ans;
}
return 0;
}

```

Output: (screenshot)

```

ishsingh/Desktop/DSA_labmanual/1_array_operations
Enter number of details you want to enter (less than 45): 5
Enter detail: 1
Enter detail: 2
Enter detail: 3
Enter detail: 4
Enter detail: 5
Enter your choice:
1. Insert element at beginning
2. Insert element at end
3. Insert element at a particular index position
4. Insert element before an element
5. Insert element after an element
6. Delete element from beginning
7. Delete element from end
8. Delete element before a particular element
9. Delete element after a particular element
10. Search an element
11. Delete element from array
12. Display array
13. Exit
1
Enter beginning detail: 9
9 1 2 3 4 5 Want to perform another operation? (y/n): y
Enter your choice:
1. Insert element at beginning
2. Insert element at end
3. Insert element at a particular index position
4. Insert element before an element
5. Insert element after an element
6. Delete element from beginning
7. Delete element from end
8. Delete element before a particular element
9. Delete element after a particular element
10. Search an element
11. Delete element from array
12. Display array
13. Exit
12
Array: 9 1 2 3 4 5
Number of elements: 6
Want to perform another operation? (y/n):

```

Test Case: Any two (screenshot)

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ l_array_operations.cpp -o l_array_operations
tanishsingh/Desktop/DSA_labmanual/"l_array_operations
Enter number of details you want to enter (less than 45): 5
Enter detail: 1
Enter detail: 2
Enter detail: 3
Enter detail: 4
Enter detail: 5
Enter your choice:
1. Insert element at beginning
2. Insert element at end
3. Insert element at a particular index position
4. Insert element before an element
5. Insert element after an element
6. Delete element from beginning
7. Delete element from end
8. Delete element before a particular element
9. Delete element after a particular element
10. Search an element
11. Delete element from array
12. Display array
13. Exit
2
Enter end detail: 6
Size of array: 6
1 2 3 4 5 6 Want to perform another operation? (y/n):
```

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ l_array_operations.cpp -o l_array_operations
tanishsingh/Desktop/DSA_labmanual/"l_array_operations
Enter number of details you want to enter (less than 45): 5
Enter detail: 1
Enter detail: 2
Enter detail: 3
Enter detail: 4
Enter detail: 5
Enter your choice:
1. Insert element at beginning
2. Insert element at end
3. Insert element at a particular index position
4. Insert element before an element
5. Insert element after an element
6. Delete element from beginning
7. Delete element from end
8. Delete element before a particular element
9. Delete element after a particular element
10. Search an element
11. Delete element from array
12. Display array
13. Exit
3
Enter updated detail: 8
Enter index location: 0
8 1 2 3 4 5 Want to perform another operation? (y/n):
```

Conclusion: Therefore, using switch cases, we can perform multiple operations like insertion, deletion, and searching for an element in an array through traversal using index.

Name of Student: Tanish

Roll Number: 32

Experiment No: 2

Title: Implement Stack ADT using Array.

Theory: Array is a collection of elements of similar data types and has a fixed size. We can access an element of the array through its index. Indexing starts from 0 till n-1 (where n=size of array).

Stack is an Abstract Data Type which can be implemented using Linked List or Array. It consists of a variable named Top which points to the topmost element of the stack. Stack follows LIFO principle (Last In, First Out) which means that the element which is inserted last will be deleted first. There are three operations in Stack: Push- insertion from top, Pop- deletion from top, Peek- returning the topmost element from the stack.

Code:

```
// stack operations(array)
#include <iostream>
using namespace std;

int main()
{
    int top = -1, element, op, n;
    cout << "Enter size of stack: ";
    cin >> n;
    int stack[n];
    while (true)
    {
        cout << "\nStack operation:
\n1.Push\n2.Pop\n3.Peek\n4.Exit\n";
        cin >> op;
        switch (op)
        {
            case 1:
                if (top == n - 1)
                {
                    cout << "Stack is full. Cannot add more elements.
\n";
                    break;
                }
            case 2:
            case 3:
            case 4:
                break;
        }
    }
}
```

```

    }
    else
    {
        cout << "Enter element: ";
        cin >> element;
        top++;
        stack[top] = element;
        cout << "Element added in stack\n";
    }
    break;
case 2:
    if (top == -1)
    {
        cout << "Stack is empty.\n";
        break;
    }
    else
    {
        cout << stack[top] << " is popped from stack\n";
        top--;
    }
    break;
case 3:
    if (top == -1)
    {
        cout << "Stack is empty.\n";
        break;
    }
    else
    {
        cout << "Top element: " << stack[top] << "\n";
    }
    break;
case 4:
    cout << "Exiting...\n";
    return 0;
default:
    cout << "Wrong choice\n";
    break;
}
}
return 0;
}

```

Output: (screenshot)

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 2_stack_array.cpp -o 2_stack_array && "/Users/tanishsingh/Desktop/DSA_labmanual/"2_stack_array
Enter size of stack: 5

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
2
Stack is empty.

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
1
Enter element: 2
Element added in stack

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
1
Enter element: 3
Element added in stack

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
3
Top element: 3

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
4
Exiting...
```

Test Case: Any two (screenshot)

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 2_stack_array.cpp -o 2_stack_array && "/Users/tanishsingh/Desktop/DSA_labmanual/"2_stack_array
Enter size of stack: 5

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
1
Enter element: 2
Element added in stack

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
3
Top element: 2

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
4
Exiting...
```



```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 2_stack_array.cpp -o 2_stack_array
Enter size of stack: 5

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
1
Enter element: 2
Element added in stack

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
3
Top element: 2

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
4
Exiting...
```

Conclusion: Therefore, using switch cases, we can perform multiple operations like push, pop, and peek in a stack using array.

Name of Student: Tanish

Roll Number: 32

Experiment No: 3

Title: Convert an Infix expression to Postfix expression using Stack ADT.

Theory: Stack is an Abstract Data Type which can be implemented using Linked List or Array. It consists of a variable named Top which points to the topmost element of the stack. Stack follows LIFO principle (Last In, First Out) which means that the element which is inserted last will be deleted first. There are three operations in Stack: Push- insertion from top, Pop- deletion from top, Peek- returning the topmost element from the stack. Using stack, we can convert an infix expression to postfix expression by pushing the operators and brackets in the stack and the operands to the expression and popping the elements to the expression through operator precedence after encountering a closing bracket.

Code:

```
// conversion of infix to postfix expression using stack(array)
#include <iostream>
using namespace std;

int precedence(char op)
{
    if (op == '+' || op == '-')
    {
        return 1;
    }
    else if (op == '*' || op == '/' || op == '%')
    {
        return 2;
    }
    else
    {
        return 0;
    }
}

int main()
{
    string exp, result = "";
```

```

char stack[100];
int top = -1;
cout << "Enter infix expression: ";
getline(cin, exp);
int n = exp.length();
char express[n + 2];
express[0] = '(';
for (int i = 0; i < n; i++)
{
    express[i + 1] = exp[i];
}
express[n + 1] = ')';
for (int i = 0; i < n + 2; i++)
{
    if (express[i] == '(')
    {
        top++;
        stack[top] = express[i];
    }
    else if (express[i] == ')')
    {
        while (stack[top] != '(' && top > -1)
        {
            result += stack[top];
            top--;
        }
        top--;
    }
    else if ((express[i] >= 'a' && express[i] <= 'z') ||
(express[i] >= 'A' && express[i] <= 'Z') || (express[i] >= '0' &&
express[i] <= '9'))
    {
        result += express[i];
    }
    else
    {
        while (top > -1 && precedence(stack[top]) >=
precedence(express[i]))
        {
            result += stack[top];
            top--;
        }
        top++;
        stack[top] = express[i];
    }
}
while (top > -1)
{
    result += stack[top];
}

```

```

        top--;
    }
    cout << "Postfix Result: " << result << endl;
    return 0;
}

```

Output: (screenshot)

```

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 3_infix_postfix_conversion_stack.cpp -o 3_infix_postfix_conversion_stack && "/Users/tanishsingh/Desktop/DSA_labmanual/"3_infix_postfix_conversion_stack
Enter infix expression: (a+b)*c-d
Postfix Result: ab+c*d-
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 3_infix_postfix_conversion_stack.cpp -o 3_infix_postfix_conversion_stack && "/Users/tanishsingh/Desktop/DSA_labmanual/"3_infix_postfix_conversion_stack
Enter infix expression: (a/b+c)-(d*e/f)
Postfix Result: ab/c+de*f/-

```

Test Case: Any two (screenshot)

```

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 3_infix_postfix_conversion_stack.cpp -o 3_infix_postfix_conversion_stack && "/Users/tanishsingh/Desktop/DSA_labmanual/"3_infix_postfix_conversion_stack
Enter infix expression: (a+b)*c-d
Postfix Result: ab+c*d-

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 3_infix_postfix_conversion_stack.cpp -o 3_infix_postfix_conversion_stack && "/Users/tanishsingh/Desktop/DSA_labmanual/"3_infix_postfix_conversion_stack
Enter infix expression: (a/b+c)-(d*e/f)
Postfix Result: ab/c+de*f/-

```

Conclusion: Therefore, using stack ADT, we can convert infix expression to postfix expression by operations like Push and Pop.

Name of Student: Tanish

Roll Number: 32

Experiment No: 4

Title: Evaluate Postfix expression using Stack ADT.

Theory: Stack is an Abstract Data Type which can be implemented using Linked List or Array. It consists of a variable named Top which points to the topmost element of the stack. Stack follows LIFO principle (Last In, First Out) which means that the element which is inserted last will be deleted first. There are three operations in Stack: Push- insertion from top, Pop- deletion from top, Peek- returning the topmost element from the stack. Using stack, we can evaluate a postfix expression by pushing the operands in the stack and popping them and evaluating them when an operator is encountered and popping the result back in the stack and printing the topmost element after the whole expression is evaluated.

Code:

```
// evaluating postfix expression using stack(array)
#include <iostream>
#include <string>
using namespace std;
int main()
{
    string expression;
    char stack[100];
    int stack1[100];
    int top = -1, a, b, result = 0;
    cout << "Enter postfix expression: ";
    getline(cin, expression);
    for (int i = 0; i < expression.length(); i++)
    {
        stack[i] = expression[i];
    }
    stack[expression.length()] = '\0';
    int i = 0;
    while (stack[i] != '\0')
    {
        if (stack[i] == '*' || stack[i] == '/' || stack[i] == '%' ||
            stack[i] == '-' || stack[i] == '+')
        {
            // Operator encountered, pop two operands and perform operation
            // This part is commented out in the original code
        }
        else
        {
            // Operand, push to stack
            // This part is commented out in the original code
        }
        i++;
    }
    // Print the result
    // This part is commented out in the original code
}
```

```

{
    a = stack1[top];
    top--;
    b = stack1[top];
    top--;
    if (stack[i] == '*')
    {
        result = b * a;
    }
    else if (stack[i] == '/')
    {
        if (a != 0)
        {
            result = b / a;
        }
        else
        {
            cout << "Error: Division by zero." << endl;
            return 1;
        }
    }
    else if (stack[i] == '%')
    {
        result = b % a;
    }
    else if (stack[i] == '+')
    {
        result = b + a;
    }
    else
    {
        result = b - a;
    }
    top++;
    stack1[top] = result;
}
else
{
    top++;
    stack1[top] = int(stack[i]) - 48;
}
i++;
}
cout << "Result: " << stack1[top] << endl;
return 0;
}

```

Output: (screenshot)

```

• lakshyaduhoon@Lakshyas-MacBook-Air dsa % cd "/Users/lakshyaduhoon/Desktop/lab_manuals/dsa/" && g++ eval_postfix_stack.cpp -o
eval_postfix_stack && "/Users/lakshyaduhoon/Desktop/lab_manuals/dsa/"eval_postfix_stack
Enter postfix expression: 12+4*8-
Result: 4
• lakshyaduhoon@Lakshyas-MacBook-Air dsa % cd "/Users/lakshyaduhoon/Desktop/lab_manuals/dsa/" && g++ eval_postfix_stack.cpp -o
eval_postfix_stack && "/Users/lakshyaduhoon/Desktop/lab_manuals/dsa/"eval_postfix_stack
Enter postfix expression: 45*2/1-
Result: 9

```

Test Case: Any two (screenshot)

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 4_eval_postfix_stack.cpp  
l_postfix_stack && "/Users/tanishsingh/Desktop/DSA_labmanual/"4_eval_postfix_stack  
Enter postfix expression: 12+4*8-  
Result: 4
```

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 4_eval_postfix_stack.cpp  
l_postfix_stack && "/Users/tanishsingh/Desktop/DSA_labmanual/"4_eval_postfix_stack  
Enter postfix expression: 12+4*8-  
Result: 4
```

Conclusion: Therefore, using stack ADT, we can evaluate a postfix expression by operations like Push and Pop.

Name of Student: Tanish

Roll Number: 32

Experiment No: 5

Title: Implement Linear Queue ADT using array.

Theory: Array is a collection of elements of similar data types and has a fixed size. We can access an element of the array through its index. Indexing starts from 0 till n-1 (where n=size of array).

Queue is an Abstract Data Type which can be implemented using Linked List or Array. It consists of two variables named Front and Rear which point to the first and last elements of the queue, respectively. Queue follows FIFO principle (First In, First Out) which means that the element which is inserted first will be deleted first. There are three operations in Queue: Enqueue- insertion from rear, Dequeue- deletion from front, Peek- returning the frontmost element from the queue.

Code:

```
// queue menu driven program(array)
#include <iostream>
using namespace std;
int main()
{
    int front = -1, rear = -1, choice, element, n;
    cout << "Enter size of queue: ";
    cin >> n;
    int queue[n];
    while (true)
    {
        cout << "\nQueue Operation:
\n1.Enqueue\n2.Dequeue\n3.Peek\n4.Exit\n";
        cin >> choice;
        switch (choice)
        {
            case 1:
                if (rear == n - 1)
                {
                    cout << "Queue is full. Cannot add more elements.
\n";
```



```

    }
    else
    {
        cout << "Enter element: ";
        cin >> element;
        if (front == -1 && rear == -1)
        {
            front = 0, rear = 0;
        }
        else
        {
            rear++;
        }
        queue[rear] = element;
        cout << "Element added successfully.\n";
    }
    break;
case 2:
    if (front == -1 || front > rear)
    {
        cout << "Queue is empty. Cannot delete more
elements.\n";
    }
    else
    {
        element = queue[front];
        front++;
        cout << "Element " << element << " removed
successfully.\n";
    }
    break;
case 3:
    if (front == -1)
    {
        cout << "Queue is empty.\n";
    }
    else
    {
        cout << "Front element: " << queue[front] << endl;
    }
    break;
case 4:
    cout << "Exiting...\n";
    return 0;
default:
    cout << "Wrong choice.\n";
    break;
}
}

```

```
}  
    return 0;  
}
```

Output: (screenshot)

```
lakshyaduhoon@Lakshyas-MacBook-Air dsa % cd "/Users/lakshyaduhoon/Desktop/lab manuals/dsa/" && g++ queue_array.cpp -o queue_array && ./queue_array  
Enter size of queue: 5  
  
Queue Operation:  
1.Enqueue  
2.Dequeue  
3.Peek  
4.Exit  
3  
Queue is empty.  
  
Queue Operation:  
1.Enqueue  
2.Dequeue  
3.Peek  
4.Exit  
2  
Queue is empty. Cannot delete more elements.  
  
Queue Operation:  
1.Enqueue  
2.Dequeue  
3.Peek  
4.Exit  
4  
Exiting...
```

Test Case: Any two (screenshot)

```
tanishsingh2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 5_queue_array.cpp -o 5_queue_array && ./5_queue_array  
Enter size of queue: 5  
  
Queue Operation:  
1.Enqueue  
2.Dequeue  
3.Peek  
4.Exit  
1  
Enter element: 2  
Element added successfully.  
  
Queue Operation:  
1.Enqueue  
2.Dequeue  
3.Peek  
4.Exit  
2  
Element 2 removed successfully.  
  
Queue Operation:  
1.Enqueue  
2.Dequeue  
3.Peek  
4.Exit  
4  
Exiting...  
tanishsingh2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 5_queue_array.cpp -o 5_queue_array && ./5_queue_array  
Enter size of queue: 5  
  
Queue Operation:  
1.Enqueue  
2.Dequeue  
3.Peek  
4.Exit  
1  
Enter element: 5  
Element added successfully.  
  
Queue Operation:  
1.Enqueue  
2.Dequeue  
3.Peek  
4.Exit  
3  
Front element: 5  
  
Queue Operation:  
1.Enqueue  
2.Dequeue  
3.Peek  
4.Exit  
4  
Exiting...
```

Conclusion: Therefore, using array, we can implement a linear queue and perform operations like Enqueue, Dequeue and Peek.

Name of Student: Tanish

Roll Number: 32

Experiment No: 6

Title: Implement Circular Queue ADT using array.

Theory: Array is a collection of elements of similar data types and has a fixed size. We can access an element of the array through its index. Indexing starts from 0 till n-1 (where n=size of array).

Queue is an Abstract Data Type which can be implemented using Linked List or Array. It consists of two variables named Front and Rear which point to the first and last elements of the queue, respectively. Queue follows FIFO principle (First In, First Out) which means that the element which is inserted first will be deleted first. There are three operations in Queue: Enqueue- insertion from rear, Dequeue- deletion from front, Peek- returning the frontmost element from the queue. As size of array is fixed, in order to overcome the challenges, we can move the rear pointer to the start of the array if rear=n-1 and front is not at first index, so we can continue to insert elements.

Code:

```
// circular queue menu driven operations(array)
#include <iostream>
using namespace std;
int main()
{
    int element, front = -1, rear = -1, n, choice;
    cout << "Enter size of queue: ";
    cin >> n;
    int queue[n];
    while (true)
    {
        cout << "\nCircular queue operations:\n1.Enqueue\n2.Dequeue\n3.Peek\n4.Exit\n";
        cin >> choice;
        switch (choice)
        {
            case 1:
                if ((front == 0 && rear == n - 1) || rear == front - 1)
                {
```

```

        cout << "Queue is full. Cannot add more elements.
\n";
    }
    else
    {
        if (rear == n - 1 && front != 0)
        {
            rear = (rear + 1) % n;
        }
        else if (front == -1 && rear == -1)
        {
            front++;
            rear++;
        }
        else
        {
            rear++;
        }
        cout << "Enter element: ";
        cin >> element;
        queue[rear] = element;
        cout << "Element added successfully.\n";
    }
    break;
case 2:
    if (front == -1)
    {
        cout << "Queue is empty. Cannot delete elements.
\n";
    }
    else
    {
        element = queue[front];
        if (front == rear)
        {
            front = -1;
            rear = -1;
        }
        else if (front == n - 1)
        {
            front = (front + 1) % n;
        }
        else
        {
            front++;
        }
        cout << "Element " << element << " is popped from
the queue.\n";
    }
}

```

```

        break;
    case 3:
        if (front == -1)
        {
            cout << "Queue is empty.\n";
        }
        else
        {
            cout << "Top element: " << queue[front] << endl;
        }
        break;
    case 4:
        cout << "Exiting...\n";
        return 0;
    default:
        cout << "Wrong input\n";
        break;
    }
}
return 0;
}

```

Output: (screenshot)

```

1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Enter element: 4
Element added successfully.

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
2
Element 1 is popped from the queue.

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Enter element: 6
Element added successfully.

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
3
Top element: 2

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Queue is full. Cannot add more elements.

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
4
Exiting...

```

Test Case: Any two (screenshot)

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" &&
Desktop/DSA_labmanual/"6_circular_queue_array
Enter size of queue: 2

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Enter element: 9
Element added successfully.

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Enter element: 4
Element added successfully.

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Queue is full. Cannot add more elements.
```

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 6_circular_queue_array.cpp
Desktop/DSA_labmanual/"6_circular_queue_array
Enter size of queue: 2

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Enter element: 5
Element added successfully.

Circular queue operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
2
Element 5 is popped from the queue.
```

Conclusion: Therefore, using array, we can implement a circular queue and perform operations like Enqueue, Dequeue and Peek without being constrained by the limitation of the fixed size of the array.

Name of Student: Tanish

Roll Number: 32

Experiment No: 7

Title: Implement Singly Linked List ADT.

Theory: Linked List is a data type which consists of nodes which contain data and a next pointer which points to the next node in the list. It stores the address of the next node. There is a start pointer in stack memory which points to the first node in the heap memory. It utilises dynamic memory and allocates heap memory to the nodes in the list. The last node's next pointer has NULL value to indicate it's the last node in the list.

Code:

```
// menu driven linked list
#include <iostream>
using namespace std;

class Node
{
public:
    int data;
    Node *next;
    Node()
    {
        cout << "Enter data: ";
        cin >> data;
        next = NULL;
    }
};

Node *createList(int n) // function to create a linked list
{
    Node *start = NULL;
    Node *ptr = NULL;
    for (int i = 0; i < n; i++)
    {
        Node *new_node = new Node();
        if (start == NULL)
        {
            start = new_node;
        }
    }
}
```



```

        ptr = start;
    }
    else
    {
        ptr->next = new_node;
        ptr = new_node;
    }
}
return start;
}

```

```

void insertAtStart(Node *&a) // function to insert a node at the
start of list
{

```

```

    Node *new_node = new Node();
    if (new_node == NULL)
    {
        cout << "Overflow";
        return;
    }
    else
    {
        new_node->next = a;
        a = new_node;
    }
}

```

```

void insertAtEnd(Node *&a) // function to insert a node at the end
of list
{

```

```

    Node *new_node = new Node();
    Node *ptr = a;
    while (ptr->next != NULL)
    {
        ptr = ptr->next;
    }
    ptr->next = new_node;
    new_node->next = NULL;
}

```

```

void insertAfterElement(Node *&a) // function to insert a node
after a particular element in the list
{

```

```

    int n;
    cout << "Enter element after which to add a node: ";
    cin >> n;
    Node *new_node = new Node();
    Node *ptr = a;
    Node *preptr = ptr;

```

```

    if (new_node == NULL)
    {
        cout << "Overflow" << endl;
        return;
    }
    else
    {
        while (preptr->data != n)
        {
            preptr = ptr;
            ptr = ptr->next;
        }
        if (ptr == NULL)
        {
            cout << "No element found" << endl;
        }
        else if (ptr == a)
        {
            new_node->next = ptr->next;
            a->next = new_node;
        }
        else
        {
            new_node->next = ptr;
            preptr->next = new_node;
        }
    }
}

```

```

void insertBeforeElement(Node *&a) // function to insert a node
before a particular element in the list
{
    Node *ptr = a;
    Node *preptr = ptr;
    int b;
    cout << "Enter element to add a node before it: ";
    cin >> b;
    Node *new_node = new Node();
    if (new_node == NULL)
    {
        cout << "Overflow" << endl;
        return;
    }
    else
    {
        while (ptr->data != b)
        {
            preptr = ptr;
            ptr = ptr->next;
        }
    }
}

```

```

    }
    if (ptr == NULL)
    {
        cout << "No element found" << endl;
    }
    else if (ptr == a)
    {
        new_node->next = ptr;
        a = new_node;
    }
    else
    {
        preptr->next = new_node;
        new_node->next = ptr;
    }
}
}

```

```

void deleteFirstNode(Node *&a) // function to delete the first node
in the list
{

```

```

    Node *ptr = a;
    if (a == NULL)
    {
        cout << "Underflow" << endl;
        return;
    }
    else
    {
        a = ptr->next;
        delete ptr;
    }
}

```

```

void deleteLastNode(Node *&a) // function to delete the last node
in the list
{

```

```

    Node *ptr = a;
    Node *preptr = ptr;
    if (a == NULL)
    {
        cout << "Underflow" << endl;
        return;
    }
    else
    {
        while (ptr->next != NULL)
        {
            preptr = ptr;

```

```

        ptr = ptr->next;
    }
    if (preptr == ptr) // if there is only one node, delete it
and make the start pointer NULL
    {
        delete ptr;
        a = NULL;
    }
    else
    {
        preptr->next = NULL;
        delete ptr;
    }
}
}

```

```

void deleteBeforeElement(Node *&a) // function to delete the node
before a particular element in the list
{
    Node *ptr = a;
    Node *preptr = NULL;
    Node *temp = a;
    int b;
    cout << "Enter element to delete a node before it: ";
    cin >> b;
    if (a == NULL)
    {
        cout << "Underflow" << endl;
        return;
    }
    else
    {
        while (ptr->data != b)
        {
            temp = preptr;
            preptr = ptr;
            ptr = ptr->next;
            if (ptr == NULL)
            {
                cout << "Element not found" << endl;
                return;
            }
        }
        if (preptr == NULL) // if first node is selected, print
error message
        {
            cout << "Element not found" << endl;
        }
        else
    }
}

```

```

    {
        if (preptr == a)
        {
            a = ptr;
        }
        else
        {
            temp->next = ptr;
        }
        delete preptr;
    }
}

```

```

void deleteAfterElement(Node *&a) // function to delete the node
after a particular element in the list
{

```

```

    Node *ptr = a;
    Node *preptr = a;
    Node *temp = NULL;
    int b;
    cout << "Enter element to delete node after: ";
    cin >> b;
    ptr = a;
    if (a == NULL)
    {
        cout << "Underflow" << endl;
        return;
    }
    else
    {
        while (ptr->data != b)
        {
            preptr = ptr;
            ptr = ptr->next;
            if (ptr == NULL)
            {
                cout << "Element not found" << endl;
                return;
            }
        }
        if (ptr == NULL)
        {
            cout << "Element not found" << endl;
        }
        else
        {
            if (ptr->next == NULL)
            {

```

```

        cout << "No element to delete" << endl;
    }
    else
    {
        preptr = ptr;
        temp = ptr->next;
        preptr->next = temp->next;
        delete temp;
    }
}

void searchElement(Node *a, int b) // function to search for a
particular element in the list
{
    Node *ptr = a;
    Node *pos = NULL;
    while (ptr != NULL)
    {
        if (ptr->data == b)
        {
            pos = ptr;
            break;
        }
        else
        {
            ptr = ptr->next;
        }
    }
    if (pos == NULL)
    {
        cout << "Element not found" << endl;
    }
    else
    {
        cout << "Element " << pos->data << " found at " << pos <<
endl;
    }
}

void showList(Node *a) // function to display the list and print
number of nodes in the list
{
    int count = 0;
    Node *ptr = a;
    while (ptr != NULL)
    {
        cout << ptr->data << " ";
    }
}

```

```

        ptr = ptr->next;
        count++;
    }
    cout << endl
        << "Number of nodes: " << count << endl;
}

```

```

void deleteList(Node *&a) // function to delete the list
{
    Node *ptr = a;
    Node *temp = NULL;
    while (ptr != NULL)
    {
        temp = ptr;
        ptr = ptr->next;
        delete temp;
    }
    a = NULL;
}

```

```

int main()
{
    int n;
    cout << "Enter number of nodes: ";
    cin >> n;
    Node *start = createList(n);
    int choice;
    char ans = 'y';
    do
    {
        cout << "Enter your choice: \n1.Insert a node at
beginning\n2.Insert a node at end\n3.Search the list for an
element\n4.Insert a node after an element\n5.Insert a node before
an element\n6.Delete first node\n7.Delete last node\n8.Delete a
node after a particular element\n9.Delete a node before a
particular element\n10.Show list\n11.Exit\n";
        cin >> choice;
        switch (choice)
        {
            case 1:
                insertAtStart(start);
                break;
            case 2:
                insertAtEnd(start);
                break;
            case 3:
                int element;
                cout << "Enter the element to search for: ";
                cin >> element;

```

```

        searchElement(start, element);
        break;
    case 4:
        insertAfterElement(start);
        break;
    case 5:
        insertBeforeElement(start);
        break;
    case 6:
        deleteFirstNode(start);
        break;
    case 7:
        deleteLastNode(start);
        break;
    case 8:
        deleteAfterElement(start);
        break;
    case 9:
        deleteBeforeElement(start);
        break;
    case 10:
        showList(start);
        break;
    case 11:
        cout << "Exiting...\n";
        return 0;
    default:
        cout << "Wrong choice" << endl;
    }
    cout << "Do you want to continue? (y/n): ";
    cin >> ans;
} while (ans == 'y');
deleteList(start);
return 0;
}

```

Output: (screenshot)

```

tanishsingh@2023_tanishk_isu_ac_in_DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 7_menu_linked_list.cpp -o
DSA_labmanual/7_menu_linked_list
Enter number of nodes: 5
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
Enter data: 5
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
10
1 2 3 4 5
Number of nodes: 5

```


Test Case: Any two (screenshot)

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 7_menu_linked_list.cpp -o DSA_labmanual/"7_menu_linked_list"
Enter number of nodes: 5
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
Enter data: 5
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
1
Enter data: 6
Do you want to continue? (y/n): y
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
10
6 1 2 3 4 5
Number of nodes: 6
```

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 7_menu_linked_list.cpp -o DSA_labmanual/"7_menu_linked_list"
Enter number of nodes: 5
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
Enter data: 5
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
6
Do you want to continue? (y/n): y
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
10
2 3 4 5
Number of nodes: 4
```

Conclusion: Therefore, we can implement a linked list by using class or structure and allocate heap memory for the node by using new operator or malloc function. We can deallocate memory for the node by using free function or delete operator.

Name of Student: Tanish

Roll Number: 32

Experiment No: 8

Title: Implement Circular Linked List ADT.

Theory: Linked List is a data type which consists of nodes which contain data and a next pointer which points to the next node in the list. It stores the address of the next node. There is a start pointer in stack memory which points to the first node in the heap memory. It utilises dynamic memory and allocates heap memory to the nodes in the list. The last node's next pointer has the address of first node, hence it's called circular linked list.

Code:

```
// circular linked list menu
#include <iostream>
using namespace std;

class Node
{
public:
    int data;
    Node *next;
    Node()
    {
        cout << "Enter data: ";
        cin >> data;
        next = NULL;
    }
};

Node *createList(int n)
{
    Node *start = NULL;
    Node *ptr = start;
    for (int i = 0; i < n; i++)
    {
        Node *newNode = new Node();
        if (start == NULL)
        {
            start = newNode;
        }
    }
}
```

```

        ptr = newNode;
    }
    else
    {
        ptr->next = newNode;
        ptr = ptr->next;
    }
}
ptr->next = start;
return start;
}

void searchElement(Node *&a)
{
    int element;
    cout << "Enter element to search: ";
    cin >> element;
    Node *ptr = a;
    Node *preptr = ptr;
    Node *temp = NULL;
    while (preptr->next != a)
    {
        if (ptr->data == element)
        {
            cout << "Element " << ptr->data << " found in node " <<
ptr << endl;
            temp = ptr;
            break;
        }
        preptr = ptr;
        ptr = ptr->next;
    }
    if (temp == NULL)
    {
        cout << "No element found" << endl;
    }
}

void traverseList(Node *&a)
{
    int count = 0;
    Node *ptr = a;
    Node *preptr = ptr;
    cout << "Circular Linked List: " << endl;
    while (preptr->next != a)
    {
        cout << ptr->data << endl;
        preptr = ptr;
        ptr = ptr->next;
    }
}

```

```

        count++;
    }
    cout << "Number of nodes: " << count << endl;
}

```

```

void insertAtBegin(Node *&a)
{
    Node *ptr = a;
    Node *newNode = new Node();
    if (newNode == NULL)
    {
        cout << "Overflow" << endl;
        return;
    }
    newNode->next = a;
    while (ptr->next != a)
    {
        ptr = ptr->next;
    }
    ptr->next = newNode;
    a = newNode;
}

```

```

void insertAtEnd(Node *&a)
{
    Node *ptr = a;
    Node *newNode = new Node();
    if (newNode == NULL)
    {
        cout << "Overflow" << endl;
        return;
    }
    newNode->next = a;
    while (ptr->next != a)
    {
        ptr = ptr->next;
    }
    ptr->next = newNode;
}

```

```

void insertBeforeElement(Node *&a)
{
    Node *ptr = a;
    Node *preptr = a;
    Node *newNode = new Node();
    if (newNode == NULL)
    {
        cout << "Overflow" << endl;
        return;
    }
}

```

```

    }
    else
    {
        int element;
        cout << "Enter element to insert a node before it: ";
        cin >> element;
        if (ptr->data == element)
        {
            newNode->next = a;
            while (ptr->next != a)
            {
                ptr = ptr->next;
            }
            ptr->next = newNode;
            a = newNode;
            return;
        }
        else
        {
            do
            {
                if (ptr->data == element)
                {
                    preptr->next = newNode;
                    newNode->next = ptr;
                    return;
                }
                preptr = ptr;
                ptr = ptr->next;
            } while (ptr != a);
            if (ptr == a)
            {
                cout << "Element not found" << endl;
                return;
            }
        }
    }
}

void insertAfterElement(Node *&a)
{
    Node *ptr = a;
    Node *preptr = ptr;
    Node *newNode = new Node();
    if (newNode == NULL)
    {
        cout << "Overflow" << endl;
        return;
    }
}

```

```

else
{
    int element;
    cout << "Enter element to insert a node after it: ";
    cin >> element;
    do
    {
        if (preptr->data == element)
        {
            if (preptr == a)
            {
                newNode->next = a->next;
                a->next = newNode;
                return;
            }
            if (preptr->next == a)
            {
                preptr->next = newNode;
                newNode->next = a;
                a = newNode;
                return;
            }
            preptr->next = newNode;
            newNode->next = ptr;
            return;
        }
        preptr = ptr;
        ptr = ptr->next;
    } while (ptr != a);
    if (ptr == a)
    {
        cout << "Element not found" << endl;
        return;
    }
}
}

void deleteAtBegin(Node *&a)
{
    Node *ptr = a;
    if (a == NULL)
    {
        cout << "Underflow" << endl;
        return;
    }
    while (ptr->next != a)
    {
        ptr = ptr->next;
    }
}

```

```

    Node *temp = a;
    ptr->next = temp->next;
    a = temp->next;
    delete temp;
}

void deleteAtEnd(Node *&a)
{
    Node *ptr = a;
    Node *preptr = ptr;
    if (a == NULL)
    {
        cout << "Underflow" << endl;
        return;
    }
    while (ptr->next != a)
    {
        preptr = ptr;
        ptr = ptr->next;
    }
    preptr->next = a;
    delete ptr;
}

void deleteBeforeElement(Node *&a)
{
    int element;
    cout << "Enter element to delete node before it: ";
    cin >> element;
    Node *ptr = a;
    Node *preptr = NULL;
    Node *temp = NULL;
    if (a == NULL)
    {
        cout << "Underflow" << endl;
        return;
    }
    else
    {
        if (element == a->data)
        {
            cout << "Cannot delete before first element" << endl;
            return;
        }
        else
        {
            do
            {
                if (ptr->data == element)

```



```

    {
        if (temp == NULL)
        {
            ptr = a;
            while (ptr->next != a)
            {
                ptr = ptr->next;
            }
            temp = a;
            ptr->next = temp->next;
            a = temp->next;
            delete temp;
            return;
        }
        temp->next = ptr;
        delete preptr;
    }
    temp = preptr;
    preptr = ptr;
    ptr = ptr->next;
} while (ptr != a);
return;
if (ptr == a)
{
    cout << "Element not found" << endl;
    return;
}
}
}
}

```

```

void deleteAfterElement(Node *&a)
{
    int element;
    cout << "Enter element to delete node after it: ";
    cin >> element;
    if (a == NULL)
    {
        cout << "Underflow" << endl;
        return;
    }
    Node *ptr = a;
    Node *preptr = NULL;
    do
    {
        if (ptr->data == element)
        {
            if (ptr->next == a)
            {

```

```

        Node *temp = ptr->next;
        ptr->next = temp->next;
        delete temp;
        a = ptr->next;
        return;
    }
    else
    {
        preptr = ptr;
        ptr = ptr->next;
        preptr->next = ptr->next;
        delete ptr;
        return;
    }
}
preptr = ptr;
ptr = ptr->next;
} while (ptr != a);
return;
cout << "Element not found" << endl;
}

```

```

void deleteList(Node *&a)
{
    Node *ptr = a;
    Node *preptr = ptr;
    while (ptr->next != a)
    {
        preptr = ptr;
        ptr = ptr->next;
        delete preptr;
    }
    a = NULL;
}

```

```

int main()
{
    int n;
    cout << "Enter number of nodes: ";
    cin >> n;
    Node *start = createList(n);
    int choice;
    char ans = 'y';
    do
    {
        cout << "Enter your choice: \n1.Insert a node at
beginning\n2.Insert a node at end\n3.Search the list for an
element\n4.Insert a node after an element\n5.Insert a node before
an element\n6.Delete first node\n7.Delete last node\n8.Delete a

```

node after a particular element\n9.Delete a node before a particular element\n10.Show list\n11.Exit\n";

```
    cin >> choice;
    switch (choice)
    {
    case 1:
        insertAtBegin(start);
        break;
    case 2:
        insertAtEnd(start);
        break;
    case 3:
        searchElement(start);
        break;
    case 4:
        insertAfterElement(start);
        break;
    case 5:
        insertBeforeElement(start);
        break;
    case 6:
        deleteAtBegin(start);
        break;
    case 7:
        deleteAtEnd(start);
        break;
    case 8:
        deleteAfterElement(start);
        break;
    case 9:
        deleteBeforeElement(start);
        break;
    case 10:
        traverseList(start);
        break;
    case 11:
        cout << "Exiting...\n";
        return 0;
    default:
        cout << "Wrong choice" << endl;
    }
    cout << "Do you want to continue? (y/n): ";
    cin >> ans;
} while (ans == 'y');
deleteList(start);
return 0;
}
```

Output: (screenshot)

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 8_menu_circular_list.cpp -
top/DSA_labmanual/"8_menu_circular_list
Enter number of nodes: 5
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
Enter data: 5
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
10
Circular Linked List:
1
2
3
4
5
Number of nodes: 5
```

Test Case: Any two (screenshot)

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 8_menu_circular_list.cpp -
top/DSA_labmanual/"8_menu_circular_list
Enter number of nodes: 5
Enter data: 12
Enter data: 2
Enter data: 3
Enter data: 4
Enter data: 5
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
2
Enter data: 6
Do you want to continue? (y/n): y
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
10
Circular Linked List:
12
2
3
4
5
6
Number of nodes: 6
```

```

tanishsingh2023@tanishk_isu_ac_in:DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 8_menu_circular_list.cpp -c
top/DSA_labmanual/"8_menu_circular_list
Enter number of nodes: 5
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
Enter data: 5
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
7
Do you want to continue? (y/n): y
Enter your choice:
1.Insert a node at beginning
2.Insert a node at end
3.Search the list for an element
4.Insert a node after an element
5.Insert a node before an element
6.Delete first node
7.Delete last node
8.Delete a node after a particular element
9.Delete a node before a particular element
10.Show list
11.Exit
10
Circular Linked List:
1
2
3
4
Number of nodes: 4
Do you want to continue? (y/n):

```

Conclusion: Therefore, we can implement a circular linked list by using class or structure and allocate heap memory for the node by using new operator or malloc function. We can deallocate memory for the node by using free function or delete operator.

Name of Student: Tanish

Roll Number: 32

Experiment No: 9

Title: Implement Stack ADT using Linked List.

Theory: Stack is an Abstract Data Type which can be implemented using Linked List or Array. It consists of a variable named Top which points to the topmost element of the stack. Stack follows LIFO principle (Last In, First Out) which means that the element which is inserted last will be deleted first. There are three operations in Stack: Push- insertion from top, Pop- deletion from top, Peek- returning the topmost element from the stack. We can implement insertion at beginning, deletion from beginning algorithms to implement Stack using Linked List.

Linked List is a data type which consists of nodes which contain data and a next pointer which points to the next node in the list. It stores the address of the next node. There is a start pointer in stack memory which points to the first node in the heap memory. It utilises dynamic memory and allocates heap memory to the nodes in the list. The last node's next pointer has the address of first node, hence it's called circular linked list.

Code:

```
// stack operations(linked list)
#include <iostream>
using namespace std;

class Node
{
public:
    int element;
    Node *next;
    Node()
    {
        cout << "Enter element: ";
        cin >> element;
        next = NULL;
    }
};
```

```
void pushList(Node *&a)
{
    Node *newnode = new Node();
    if (a == NULL)
    {
        a = newnode;
    }
    else
    {
        newnode->next = a;
        a = newnode;
    }
    cout << "Element pushed successfully\n";
}
```

```
void popList(Node *&a)
{
    Node *ptr = a;
    if (a == NULL)
    {
        cout << "Stack is empty\n";
    }
    else
    {
        cout << "Element " << a->element << " popped successfully\n";
        a = a->next;
        delete ptr;
    }
}
```

```
void peekList(Node *&a)
{
    if (a == NULL)
    {
        cout << "Stack is empty\n";
    }
    else
    {
        cout << "Top element: " << a->element << endl;
    }
}
```

```
void deleteList(Node *&a)
{
    Node *ptr = a;
    Node *temp = ptr;
    if (a == NULL)
```

```

    {
        return;
    }
    else
    {
        while (ptr)
        {
            temp = ptr;
            ptr = ptr->next;
            delete temp;
        }
        a = NULL;
    }
}

void seeList(Node *&a)
{
    Node *ptr = a;
    if (a == NULL)
    {
        cout << "Empty stack\n";
    }
    else
    {
        while (ptr)
        {
            cout << ptr->element << endl;
            ptr = ptr->next;
        }
    }
}

int main()
{
    Node *top = NULL;
    int choice;
    while (true)
    {
        cout << "\nStack operation:
\n1.Push\n2.Pop\n3.Peek\n4.Exit\n";
        cin >> choice;
        switch (choice)
        {
            case 1:
                pushList(top);
                break;
            case 2:
                popList(top);
                break;

```



```

        case 3:
            peekList(top);
            break;
        case 4:
            cout << "Exiting...\n";
            return 0;
        default:
            cout << "Wrong choice\n";
            break;
    }
}
deletelist(top);
return 0;
}

```

Output: (screenshot)

```

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 9_stack_list.cpp -o 9_stack_list

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
1
Enter element: 2
Element pushed successfully

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
2
Element 2 popped successfully

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
3
Stack is empty

Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
4
Exiting...

```

Test Case: Any two (screenshot)

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 9_stack_list.cpp -o 9_stack_list
Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
1
Enter element: 3
Element pushed successfully
Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
3
Top element: 3
Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
4
Exiting...
```

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 9_stack_list.cpp -o 9_stack_list
Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
3
Stack is empty
Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
2
Stack is empty
Stack operation:
1.Push
2.Pop
3.Peek
4.Exit
4
Exiting...
```

Conclusion: Therefore, we can implement Stack by linked list by using class or structure and allocate heap memory for the node by using new operator or malloc function. We can deallocate memory for the node by using free function or delete operator. We can implement push and pop operations through insertion at beginning and deletion from beginning algorithms.

Name of Student: Tanish

Roll Number: 32

Experiment No: 10

Title: Implement Linear Queue ADT using Linked List.

Theory: Queue is an Abstract Data Type which can be implemented using Linked List or Array. It consists of two variables named Front and Rear which point to the first and last elements of the stack, respectively. Queue follows FIFO principle(First In, First Out) which means that the element which is inserted first will be deleted first. There are three operations in Stack: Enqueue- insertion from rear, Dequeue- deletion from front, Peek- returning the frontmost element from the queue. It can be implemented by insertion at end and deletion from beginning algorithms.

Linked List is a data type which consists of nodes which contain data and a next pointer which points to the next node in the list. It stores the address of the next node. There is a start pointer in stack memory which points to the first node in the heap memory. It utilises dynamic memory and allocates heap memory to the nodes in the list. The last node's next pointer has the address of first node, hence it's called circular linked list.

Code:

```
// queue menu driven program(linked list)
#include <iostream>
using namespace std;

class Node
{
public:
    int data;
    Node *next;
    Node()
    {
        cout << "Enter data: ";
        cin >> data;
        next = NULL;
    }
};
```

```

void enqueue(Node *&start, Node *&end)
{
    Node *newnode = new Node();
    if (start == NULL)
    {
        start = newnode;
        end = newnode;
    }
    else
    {
        end->next = newnode;
        end = newnode;
    }
    cout << "Element added successfully.\n";
}

```

```

void dequeue(Node *&start, Node *&end)
{
    Node *ptr = NULL;
    if (start == NULL)
    {
        cout << "Queue is empty.\n";
        return;
    }
    else
    {
        ptr = start;
        start = start->next;
        cout << "Element " << ptr->data << " deleted successfully.\n";
        delete ptr;
    }
}

```

```

void peek(Node *&start)
{
    if (start == NULL)
    {
        cout << "Queue is empty.\n";
        return;
    }
    else
    {
        cout << "Top element: " << start->data << endl;
    }
}

```

```

void deleteQueue(Node *&start)

```

```

{
    Node *ptr = start;
    Node *temp = NULL;
    if (start == NULL)
    {
        return;
    }
    else
    {
        while (ptr != NULL)
        {
            temp = ptr;
            ptr = ptr->next;
            delete temp;
        }
        start = NULL;
    }
}

void showQueue(Node *start)
{
    Node *ptr = start;
    while (ptr != NULL)
    {
        cout << ptr->data << endl;
        ptr = ptr->next;
    }
}

int main()
{
    Node *front = NULL;
    Node *rear = NULL;
    int choice;
    while (true)
    {
        cout << "\nQueue Operations:
\n1.Enqueue\n2.Dequeue\n3.Peek\n4.Exit\n";
        cin >> choice;
        switch (choice)
        {
            case 1:
                enqueue(front, rear);
                break;
            case 2:
                dequeue(front, rear);
                break;
            case 3:
                peek(front);

```

```

        break;
    case 4:
        cout << "Exiting...\n";
        return 0;
    default:
        cout << "Wrong choice.\n";
        break;
    }
}
return 0;
}

```

Output: (screenshot)

```

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 10_queue_u
ual/"10_queue_list

Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Enter data: 2
Element added successfully.

Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
3
Top element: 2

Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
4
Exiting...

```

Test Case: Any two (screenshot)

```

tanishsingh@2023 tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 10_queue_list.cpp -o 10_queue_list
Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Enter data: 9
Element added successfully.

Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
2
Element 9 deleted successfully.

Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
4
Exiting...

```

```

tanishsingh@2023 tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 10_queue_list.cpp -o 10_queue_list
Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
1
Enter data: 3
Element added successfully.

Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
3
Top element: 3

Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
2
Element 3 deleted successfully.

Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
3
Queue is empty.

Queue Operations:
1.Enqueue
2.Dequeue
3.Peek
4.Exit
4
Exiting...

```

Conclusion: Therefore, we can implement Linear Queue by linked list by using class or structure and allocate heap memory for the node by using new operator or malloc function. We can deallocate memory for the node by using free function or delete operator. We can implement enqueue and dequeue operations through insertion at end and deletion from beginning algorithms.

Name of Student: Tanish

Roll Number: 32

Experiment No: 11

Title: Implement Binary Search Tree ADT using Linked List.

Theory:

A binary tree is a non-linear data structure in which there is a root node and each parent node has 0,1 or 2 child nodes at most. In binary search tree, all the nodes having values less than that of the root node are present in the left subtree of the root node and all the nodes having values greater than or equal to that of the root node are present in the right subtree of the root node.

Code:

```
// Binary Search Tree using Linked List
#include <iostream>
using namespace std;

class Node
{
public:
    int data;
    Node *left;
    Node *right;
    Node()
    {
        cout << "Enter data: ";
        cin >> data;
        left = right = NULL;
    }
};

class BST
{
public:
    Node *root;
    BST()
    {
        root = NULL;
    }
    void insert(Node *node)
    {

```



```

    if (root == NULL)
    {
        root = node;
        return;
    }
    Node *temp = root;
    while (temp != NULL)
    {
        if (node->data < temp->data)
        {
            if (temp->left == NULL)
            {
                temp->left = node;
                return;
            }
            temp = temp->left;
        }
        else
        {
            if (temp->right == NULL)
            {
                temp->right = node;
                return;
            }
            temp = temp->right;
        }
    }
}

void inorder(Node *node)
{
    if (node == NULL)
        return;
    inorder(node->left);
    cout << node->data << " ";
    inorder(node->right);
}

void preorder(Node *node)
{
    if (node == NULL)
        return;
    cout << node->data << " ";
    preorder(node->left);
    preorder(node->right);
}

void postorder(Node *node)
{
    if (node == NULL)
        return;
    postorder(node->left);
}

```

```

        postorder(node->right);
        cout << node->data << " ";
    }
};

int main()
{
    BST bst;
    int n;
    cout << "Enter number of nodes: ";
    cin >> n;
    for (int i = 0; i < n; i++)
    {
        Node *node = new Node();
        bst.insert(node);
    }
    cout << "Inorder: ";
    bst.inorder(bst.root);
    cout << endl;
    cout << "Preorder: ";
    bst.preorder(bst.root);
    cout << endl;
    cout << "Postorder: ";
    bst.postorder(bst.root);
    cout << endl;
    return 0;
}

```

Output: (screenshot)

```

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 11_binarysearchtree_list.cpp -o 11_binarysearchtree_list
Enter number of nodes: 5
Enter data: 12
Enter data: 10
Enter data: 12
Enter data: 15
Enter data: 17
Inorder: 10 12 12 15 17
Preorder: 12 10 12 15 17
Postorder: 10 17 15 12 12

```

Test Case: Any two (screenshot)

```

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 11_binarysearchtree_list.cpp -o 11_binarysearchtree_list
Enter number of nodes: 5
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
Enter data: 5
Inorder: 1 2 3 4 5
Preorder: 1 2 3 4 5
Postorder: 5 4 3 2 1

```

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 11_binarysearchtree_list.cpp -o 11_binarysearchtree_list
Enter number of nodes: 5
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
Enter data: 5
Inorder: 1 2 3 4 5
Preorder: 1 2 3 4 5
Postorder: 5 4 3 2 1
```

Conclusion: Therefore, we can implement Binary Search Tree ADT using Linked List.

Name of Student: Tanish

Roll Number: 32

Experiment No: 12

Title: Implement Graph Traversal techniques: a) Depth First Search b) Breadth First Search

Theory: A Graph is a non-linear data structure which can have parent-child as well as other complex relationships between the nodes. It is a set of edges and vertices, where vertices are the nodes, and the edges are the links connecting the nodes. We can implement a graph using adjacency matrix or adjacency list.

Code:

```
// Graph Traversal techniques: a) Depth First Search b) Breadth First Search
#include <iostream>
#include <queue>

using namespace std;

const int MAXN = 100;

// Depth First Search (DFS)
void dfs(int graph[][MAXN], bool visited[], int n, int node)
{
    visited[node] = true;
    cout << node << " ";

    for (int i = 0; i < n; ++i)
    {
        if (graph[node][i] == 1 && !visited[i])
        {
            dfs(graph, visited, n, i);
        }
    }
}

// Breadth First Search (BFS)
void bfs(int graph[][MAXN], bool visited[], int n, int start)
{

```

```

queue<int> q;
q.push(start);
visited[start] = true;

while (!q.empty())
{
    int node = q.front();
    q.pop();
    cout << node << " ";

    for (int i = 0; i < n; ++i)
    {
        if (graph[node][i] == 1 && !visited[i])
        {
            q.push(i);
            visited[i] = true;
        }
    }
}

int main()
{
    int n;
    cout << "Enter the number of vertices: ";
    cin >> n;

    int graph[MAXN][MAXN]; // Adjacency matrix
    cout << "Enter the adjacency matrix:" << endl;
    for (int i = 0; i < n; ++i)
    {
        for (int j = 0; j < n; ++j)
        {
            cin >> graph[i][j];
        }
    }

    bool visited[MAXN] = {false}; // Visited array to keep track of
visited nodes

    cout << "Depth First Search (DFS): ";
    for (int i = 0; i < n; ++i)
    {
        if (!visited[i])
        {
            dfs(graph, visited, n, i);
        }
    }
    cout << endl;
}

```

```
// Resetting visited array for BFS
fill(visited, visited + n, false);
```

```
cout << "Breadth First Search (BFS): ";
for (int i = 0; i < n; ++i)
{
    if (!visited[i])
    {
        bfs(graph, visited, n, i);
    }
}
cout << endl;
```

```
return 0;
```

Output: (screenshot)

```
tanishsingh@2023 tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 12_graphtraversal.cpp -o 12_graphtraversal
A_labmanual/"12_graphtraversal
Enter the number of vertices: 4
Enter the adjacency matrix:
1
0
1
1
0
1
1
0
1
1
1
2
0
1
1
0
0
Depth First Search (DFS): 0 2 1 3
Breadth First Search (BFS): 0 2 3 1
```

Test Case: Any two (screenshot)

```
tanishsingh@2023 tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 12_graphtraversal.cpp -o 12_graphtraversal
A_labmanual/"12_graphtraversal
Enter the number of vertices: 3
Enter the adjacency matrix:
1
0
1
1
0
0
1
1
1
Depth First Search (DFS): 0 2 1
Breadth First Search (BFS): 0 2 1
```

```
tanishsingh@2023 tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 12_graphtraversal.cpp -o 12_graphtraversal
A_labmanual/"12_graphtraversal
Enter the number of vertices: 2
Enter the adjacency matrix:
1
1
0
0
Depth First Search (DFS): 0 1
Breadth First Search (BFS): 0 1
```

Conclusion: Therefore, we can implement Graph Traversal techniques by Depth First and Breadth First using adjacency matrix.

Name of Student: Tanish

Roll Number: 32

Experiment No: 13

Title: Implement Binary Search algorithm to search an element in the array.

Theory:

Binary Search is a searching algorithm which is used in a sorted array by repeatedly dividing the search interval in half. The idea of binary search is to use the information that the array is sorted and reduce the time complexity to $O(\log N)$.

Code:

```
// Binary Search algorithm to search an element in an array
#include <iostream>
using namespace std;

int binarySearch(int arr[], int n, int a)
{
    int l = 0, r = n - 1;
    while (l <= r)
    {
        int m = l + (r - l) / 2;
        if (arr[m] == a)
        {
            return m;
        }
        if (arr[m] < a)
        {
            l = m + 1;
        }
        else
        {
            r = m - 1;
        }
    }
    return -1;
}

int main()
{
    int n, a;
```



```

cout << "Enter size of array: ";
cin >> n;
int arr[n];
for (int i = 0; i < n; i++)
{
    cout << "Enter " << i + 1 << " element: ";
    cin >> arr[i];
}
cout << "Enter element to search for: ";
cin >> a;
int b = binarySearch(arr, n, a);
if (b == -1)
{
    cout << "Element not found." << endl;
}
else
{
    cout << "Element found at index " << b << endl;
}
return 0;
}

```

Output: (screenshot)

```

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 13_binarysearch.cpp -o 13_bin
bmanual/"13_binarysearch
Enter size of array: 5
Enter 1 element: 1
Enter 2 element: 2
Enter 3 element: 3
Enter 4 element: 4
Enter 5 element: 5
Enter element to search for: 4
Element found at index 3

```

Test Case: Any two (screenshot)

```

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 13_binarysearch.cpp -o 13_bin
bmanual/"13_binarysearch
Enter size of array: 5
Enter 1 element: 2
Enter 2 element: 5
Enter 3 element: 3
Enter 4 element: 9
Enter 5 element: 1
Enter element to search for: 6
Element not found.

```

```

tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 13_binarysearch.cpp -o 13_bin
bmanual/"13_binarysearch
Enter size of array: 5
Enter 1 element: 4
Enter 2 element: 5
Enter 3 element: 3
Enter 4 element: 2
Enter 5 element: 1
Enter element to search for: 8
Element not found.

```

Conclusion: Therefore, we can implement Binary Search algorithm in a sorted array to search the index location of an element present in the array in an efficient manner.

Name of Student: Tanish

Roll Number: 32

Experiment No: 14

Title: Implement Bubble Sort algorithm to sort elements of an array in ascending and descending order.

Theory:

In Bubble Sort algorithm, we traverse from left and compare adjacent elements and the higher one is placed at right side. In this way, the largest element is moved to the rightmost end at first. This process is then continued to find the second largest and place it and so on until the data is sorted.

Code:

```
// bubble sort algorithm to sort array in ascending and descending
order
#include <iostream>
using namespace std;

int main()
{
    int n;
    cout << "Enter number of elements: ";
    cin >> n;
    int arr[n];
    for (int i = 0; i < n; i++)
    {
        cout << "Enter " << i + 1 << " element: ";
        cin >> arr[i];
    }
    cout << "Array: ";
    for (int i = 0; i < n; i++)
    {
        cout << arr[i] << " ";
    }

    // ascending order
    for (int i = 0; i < n - 1; i++)
    {
        for (int j = 0; j < n - 1; j++)
        {
            if (arr[j] > arr[j + 1])
```

```

        {
            int temp = arr[j];
            arr[j] = arr[j + 1];
            arr[j + 1] = temp;
        }
    }
}

cout << "\nArray in ascending order: ";
for (int i = 0; i < n; i++)
{
    cout << arr[i] << " ";
}

// descending order
for (int i = 0; i < n - 1; i++)
{
    for (int j = 0; j < n - 1 - i; j++)
    {
        if (arr[j] < arr[j + 1])
        {
            int temp = arr[j];
            arr[j] = arr[j + 1];
            arr[j + 1] = temp;
        }
    }
}

cout << "\nArray in descending order: ";
for (int i = 0; i < n; i++)
{
    cout << arr[i] << " ";
}

cout << endl;
return 0;
}

```

Output: (screenshot)

```

tanishsingh2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 14_bubble_sort.cpp -o 14_bubb
anual/"14_bubble_sort
Enter number of elements: 5
Enter 1 element: 3
Enter 2 element: 1
Enter 3 element: 7
Enter 4 element: 4
Enter 5 element: 6
Array: 3 1 7 4 6
Array in ascending order: 1 3 4 6 7
Array in descending order: 7 6 4 3 1

```

Test Case: Any two (screenshot)

```

tanishsingh2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 14_bubble_sort.cpp -o 14_bubb
anual/"14_bubble_sort
Enter number of elements: 5
Enter 1 element: 5
Enter 2 element: 3
Enter 3 element: 2
Enter 4 element: 9
Enter 5 element: 7
Array: 5 3 2 9 7
Array in ascending order: 2 3 5 7 9
Array in descending order: 9 7 5 3 2

```

```
tanishsingh@2023_tanishk_isu_ac_in DSA_labmanual % cd "/Users/tanishsingh/Desktop/DSA_labmanual/" && g++ 14_bubble_sort.cpp -o 14_bubble_sort
Enter number of elements: 4
Enter 1 element: 7
Enter 2 element: 2
Enter 3 element: 1
Enter 4 element: 5
Array: 7 2 1 5
Array in ascending order: 1 2 5 7
Array in descending order: 7 5 2 1
```

Conclusion: Therefore, we can implement Bubble Sort algorithm to sort the array in ascending or descending order by traversing through the array and comparing the elements to the adjacent elements.