
Algorithm 2 Rebuilding NCBI-Tree Denovo with Custom Taxonomy

Input: Custom taxonomy table with capacity \mathcal{C} with column taxa as List \mathcal{L}_{taxa7}

Output: NCBI-TREE nodes.dmp and names.dmp for custom taxonomy

```
    Initializing NCBI-Tree as Directed Acyclic Graph(DAG) with Dict  $\mathcal{D}_{dag}$ 
2: Initializing vertices and edges in DAG with List  $\mathcal{L}_{vertices}$  and  $\mathcal{L}_{edges}$ 
    Initializing taxa node ever seen with Dict  $\mathcal{D}_{taxa_{seen}}$ 
4: Initializing taxa node ID with Dict  $\mathcal{D}_{taxid_{node}}$ 

6: for  $genome = 1, \mathcal{C}$  do
    for  $\varepsilon, taxon$  in enumerate( $\mathcal{L}_{taxa7}$ ) do
8:     Adding Vertex  $taxon$  into  $\mathcal{D}_{dag}$  when not in  $\mathcal{D}_{dag}$ , or nothing to do
    if  $taxon$  NOT in  $\mathcal{D}_{dag}$  then
10:          $\mathcal{D}_{dag}[taxon] = []$ 
        Updating Taxa Node ID with occurrence order of incrementing by 1
12:          $\mathcal{D}_{taxid_{node}}[taxon] = \text{len}(\mathcal{D}_{taxid_{node}}) + 1$ 
    end if

14:     Updating Edges from root to leaf(RTL) in Linked List
16:     if  $\varepsilon = 0$  then
        Adding Edge  $taxon$  from root of  $\mathcal{D}_{dag}$ 
18:          $\mathcal{D}_{dag}[root] = [taxon]$ 
    else
20:         Adding Edge  $taxon$  to  $taxon_{before}$  denoted with  $\mathcal{L}_{taxa7}[\varepsilon - 1]$  of  $\mathcal{D}_{dag}$ 
         $\mathcal{D}_{dag}[taxon_{before}] = [taxon]$ 
22:     end if
    end for
24: end for

26: Recursive DFS to generate node.dmp and names.dmp
    Initializing nodes and names as List  $\mathcal{L}_{name}$  and  $\mathcal{L}_{node}$ 
28: DFS( $taxon, \mathcal{L}_{name}, \mathcal{L}_{node}$ )
    for  $taxon_{child}$  in  $\mathcal{D}_{dag}[taxon]$  do
30:     if  $taxon_{child}$  in  $\mathcal{D}_{taxa_{seen}}$  then
        Continue
32:     end if
     $\mathcal{D}_{taxa_{seen}}[taxon_{child}] = flag$ 
34:
    Appending nodes with  $taxid, parent_id, rank, \dots$  format
36:      $\mathcal{L}_{node}.append(\mathcal{D}_{taxid_{node}}[taxon_{child}], \mathcal{D}_{taxid_{node}}[taxon], \mathcal{D}_{rank}[taxon_{child}], \dots)$ 

38:     Appending names with  $taxid, name, 'scientificname'$  format
     $\mathcal{L}_{name}.append(\mathcal{D}_{taxid_{node}}[taxon_{child}], taxon_{child}, 'scientific name')$ 
40:     DFS( $taxon_{child}, \mathcal{L}_{name}, \mathcal{L}_{node}$ )
    end for
42:
```
