
Algorithm 1 Ensemble Voting of User Genome from GTDB to NCBI

Input: Initialize parsing genome GTDB-NCBI-r203 mapping metadata with training genome capacity \mathcal{N}

Input: Initialize reading user genome Q and tree T classified with GTDB-Tk

```
1: Fixed ensemble weights  $\theta, \theta'$  to constant 0.5
2:
3: for  $genome = 1, N$  do
4:   Associating genome accession ID  $gid$  with NCBI taxonomy in Dict  $\mathcal{D}_{ncbi\_taxa}$ 
5:   Associating representative genome ID  $rid$  with GTDB taxonomy in Dict  $\mathcal{D}_{gtdb\_taxa}$ 
6:   Clustering genome  $gid$  into representative genome  $rid$  in Dict  $\mathcal{D}_{cluster}$ 
7:   Associating specific  $taxon$  with NCBI taxonomy lineage in Dict  $\mathcal{D}_{ncbi\_lineage}$ 
8:   Storing  $\mathcal{D}_{ncbi\_taxa}, \mathcal{D}_{gtdb\_taxa}, \mathcal{D}_{cluster}$  and  $\mathcal{D}_{ncbi\_lineage}$ 
9: end for
10:
11: Initializing GTDB cluster with NCBI-type taxonomy in Dict  $\mathcal{N}4\mathcal{G}_{cluster}$ 
12: for  $rid, gids$  in  $\mathcal{D}_{ncbi\_taxa}.items()$  do
13:   for  $rank = r_{species}, r_{kindom}$  do
14:     Initializing hit list for  $\mathcal{D}_{ncbi\_taxa}$  with  $\mathcal{L}_{hit}$ 
15:     for  $\varepsilon$  in  $gids$  do
16:       if  $\varepsilon$  in  $\mathcal{D}_{ncbi\_taxa}$  then
17:         appending  $\mathcal{D}_{ncbi\_taxa}[\varepsilon][rank]$  into  $\mathcal{L}_{hit}$ 
18:       end if
19:     end for
20:     if  $\mathcal{L}_{hit}$  is NOT empty then
21:       Counting element occurrence in  $\mathcal{L}_{hit}$ 
22:       Applying heapsort to  $\mathcal{L}_{hit}$  and finding top 1 element
23:        $tax_{top}, count_{top} = \mathcal{HEAPSORT}(\mathcal{L}_{hit})$ 
24:       if  $count_{top} \geq \theta * \mathcal{L}_{hit}.size()$  &&  $tax_{top}$  is NOT unassigned then
25:          $\mathcal{N}4\mathcal{G}_{cluster}[rid] = \mathcal{D}_{ncbi\_lineage}[tax_{top}]$ 
26:       break
27:     end if
28:   end if
29:   if  $\mathcal{N}4\mathcal{G}_{cluster}[rid]$  is NOT unassigned then
30:     Reporting representative genome cannot be converted to NCBI tax-
31:     onomy
32:   end if
33: end for
34:   Storing  $\mathcal{N}4\mathcal{G}_{cluster}[rid]$ 
35: end for
```

```

36: Mapping training genome or user genome from GTDB taxonomy to NCBI
    taxonomy
37: Initializing final hit list as  $\mathcal{L}_{hit_{final}}$ 
38: for  $rank = r_{species}, r_{kingdom}$  do
39:   if  $\mathcal{D}_{gtdb\_taxa}[rank]$  is unassigned then
40:     Continue
41:   end if
42:   Initializing hit list for  $\mathcal{D}_{ncbi\_taxa}$  with  $\mathcal{L}_{hit_{genome}}$ 
43:   Mapping genome accession gid to tree leaf node  $\mathcal{NODE}_{map}$ 
44:   traversing leaf nodes  $\mathcal{NODE}_{map}$  to find NCBI decendants with
     $\mathcal{N4G}_{cluster}[rid]$ 
45:   Storing  $\mathcal{N4G}_{cluster_{hit}}$  as list  $\mathcal{L}_{cluster_{hit}}$ 
46:   for  $rid$  in  $\mathcal{L}_{cluster_{hit}}$  do
47:     appending  $\mathcal{N4G}_{cluster}[rid][rank]$  into  $\mathcal{L}_{hit_{genome}}$ 
48:     Counting element occurence in  $\mathcal{L}_{hit_{genome}}$ 
49:     Applying heapsort to  $\mathcal{L}_{hit_{genome}}$  and finding top 1 element
50:      $tax_{top}, count_{top} = \mathcal{HEAPSORT}(\mathcal{L}_{hit_{genome}})$ 
51:     if  $count_{top} \geq \theta' * \mathcal{L}_{hit_{genome}}.size()$  &&  $tax_{top}$  is NOT unassigned
    then
52:        $\mathcal{L}_{hit_{final}} = \mathcal{D}_{ncbi\_lineage}[tax_{top}]$ 
53:       break
54:     end if
55:   end for
56:   Storing  $\mathcal{L}_{hit_{final}}$ 
57: end for

```

Algorithm 2 Rebuilding NCBI-Tree Denovo with Custom Taxonomy

Input: Custom taxonomy table with capacity \mathcal{C} with column taxa as List \mathcal{L}_{taxa7}

Output: NCBI-TREE nodes.dmp and names.dmp for custom taxonomy

```
    Initializing NCBI-Tree as Directed Acyclic Graph(DAG) with Dict  $\mathcal{D}_{dag}$ 
2: Initializing vertices and edges in DAG with List  $\mathcal{L}_{vertices}$  and  $\mathcal{L}_{edges}$ 
    Initializing taxa node ever seen with Dict  $\mathcal{D}_{taxa_{seen}}$ 
4: Initializing taxa node ID with Dict  $\mathcal{D}_{taxid_{node}}$ 

6: for  $genome = 1, \mathcal{C}$  do
    for  $\varepsilon, taxon$  in enumerate( $\mathcal{L}_{taxa7}$ ) do
8:     Adding Vertex  $taxon$  into  $\mathcal{D}_{dag}$  when not in  $\mathcal{D}_{dag}$ , or nothing to do
    if  $taxon$  NOT in  $\mathcal{D}_{dag}$  then
10:          $\mathcal{D}_{dag}[taxon] = []$ 
        Updating Taxa Node ID with occurrence order of incrementing by 1
12:          $\mathcal{D}_{taxid_{node}}[taxon] = \text{len}(\mathcal{D}_{taxid_{node}}) + 1$ 
    end if

14:     Updating Edges from root to leaf(RTL) in Linked List
16:     if  $\varepsilon = 0$  then
        Adding Edge  $taxon$  from root of  $\mathcal{D}_{dag}$ 
18:          $\mathcal{D}_{dag}[root] = [taxon]$ 
    else
20:         Adding Edge  $taxon$  to  $taxon_{before}$  denoted with  $\mathcal{L}_{taxa7}[\varepsilon - 1]$  of  $\mathcal{D}_{dag}$ 
         $\mathcal{D}_{dag}[taxon_{before}] = [taxon]$ 
22:     end if
    end for
24: end for

26: Recursive DFS to generate node.dmp and names.dmp
    Initializing nodes and names as List  $\mathcal{L}_{name}$  and  $\mathcal{L}_{node}$ 
28: DFS( $taxon, \mathcal{L}_{name}, \mathcal{L}_{node}$ )
    for  $taxon_{child}$  in  $\mathcal{D}_{dag}[taxon]$  do
30:     if  $taxon_{child}$  in  $\mathcal{D}_{taxa_{seen}}$  then
        Continue
32:     end if
     $\mathcal{D}_{taxa_{seen}}[taxon_{child}] = flag$ 
34:
    Appending nodes with  $taxid, parent_id, rank, \dots$  format
36:      $\mathcal{L}_{node}.append(\mathcal{D}_{taxid_{node}}[taxon_{child}], \mathcal{D}_{taxid_{node}}[taxon], \mathcal{D}_{rank}[taxon_{child}], \dots)$ 

38:     Appending names with  $taxid, name, 'scientificname'$  format
     $\mathcal{L}_{name}.append(\mathcal{D}_{taxid_{node}}[taxon_{child}], taxon_{child}, 'scientific name')$ 
40:     DFS( $taxon_{child}, \mathcal{L}_{name}, \mathcal{L}_{node}$ )
    end for
42:
```
