SENSOR FUSION

LiDAR (Light Detection and Ranging)

Functions:

- Uses laser light to measure distances and create highly accurate 3D representations of objects and environments
- Emits laser pulses and measures the time it takes for those pulses to bounce off objects and return to the sensor.
- By knowing the speed of light and the time it takes for the laser pulse to return, the LiDAR system can calculate the distance to the object.

Lidars can measure depths from about 0.9 to 40 m (3 to 131 ft), with vertical accuracy in the order of 15 cm (6 in). (We are using rpLiDAR A1m8 which had diameter range from 3m-12m)

Applications:

- Positioning containers in a loading bridge
- Autonomous Vehicles
- Position detection of moving objects
- Road management system

Why LiDAR and why not other sensors? Because,
- RADAR has less spatial resolution and less accurate 3D data
- Ultrasonic sensor works for shorter ranges
- GPS lacks detailed information about the immediate environment and cannot detect obstacles or terrain changes

Some drawbacks of Lidar include

- Ensuring proper alignment, calibration, and maintenance of the sensor can be challenging and time-consuming.
- Lidar sensors generate large amounts of data that need to be processed and interpreted accurately. This requires lots of complexity and energy consumption
- Many lidar sensors have a limited field of view compared to other sensor types like cameras. This can require additional sensors or scanning mechanisms to cover a broader area

- In situations where multiple lidar sensors are used in close proximity, interference between the emitted laser pulses can occur, leading to inaccurate readings. Proper synchronization and interference mitigation strategies are needed.

ULTRASONIC SENSORS

- Ultrasonic sensors are devices that use ultrasonic waves, which are sound waves with frequencies higher than the upper audible limit of human hearing, above 20,000 hertz (Hz).
- These sensors emit ultrasonic waves and then measure the time it takes for the waves to bounce back after hitting an object.
- With this we can find the distance between the sensor and the object.

It's better than other sensors like:

- **Infrared (IR) Sensors**: Ultrasonic sensors can be better than IR sensors in environments where there are things that can interfere with IR sensor readings. Ultrasonic sensors, on the other hand, use sound waves and are less affected by these environmental factors.

- **Proximity Sensors**: In situations where the sensor needs to detect objects at a distance without requiring direct line-of-sight, ultrasonic sensors can outperform some proximity sensors, which might get disturbed by certain materials or shapes.

But ultrasonic sensors have many drawbacks like:

- Limited Accuracy and Precision: Ultrasonic sensors might not provide the same level of accuracy and precision as some other sensors, such as laser-based sensors. Factors like air temperature, humidity, interference can affect the accuracy of distance measurements.

- Beam Angle and Detection Area: The ultrasonic sensor's beam angle can result in a cone-shaped detection area. This can make it challenging to detect objects accurately if they are not positioned directly in front of the sensor. Objects located outside the beam angle might not be detected at all.

- Limited Range: Ultrasonic sensors typically have a limited maximum range. They work best at shorter to moderate distances and can become less effective or even fail at longer distances.

- Power Consumption: Depending on the design and application, ultrasonic sensors might consume more power compared to some other types of sensors, impacting the overall power efficiency of a system.

- Limited Resolution: Ultrasonic sensors might not provide high-resolution data, making them unsuitable for applications that require detailed spatial information.

- Reflection Issues: Ultrasonic sensors rely on the reflection of sound waves to measure distances. In environments with reflective surfaces or echoing, the sensor might have difficulty distinguishing between multiple reflections, leading to inaccurate measurements.

FUSION

Sensor fusion of LiDAR and Ultrasonic sensors are useful in ways like:

- Accurate data as ultrasonic works for short range and LiDAR for long
- Ultrasonic sensors can be more effective in environments with poor lighting or where LiDAR might struggle
- LiDAR can sometimes struggle to differentiate between static and dynamic objects. Ultrasonic sensors can help detect moving objects like vehicles, improving the understanding of the environment.

Drawbacks:
- Ultrasonic sensors are typically used for short-range obstacle detection and lack the precision and range of LIDAR sensors. This limitation can affect the overall performance of the sensor fusion system, especially when trying to detect objects at longer distances.

- LIDAR and ultrasonic sensors provide data in different formats, such as point clouds from LIDAR and distance measurements from ultrasonic sensors. Integrating and interpreting these different types of data can be complex and require specialized software.

- LIDAR sensors tend to be more expensive and complex than ultrasonic sensors. Integrating both types of sensors increases the overall cost and complexity of the system, which could be a limiting factor in applications.