22.01.2024

Singly Linked List

Insertion and Deletion of a node at first position, at end of list.

```
#include <stdio.h>
#include<stdlib.h>
#include<conio.h>
struct node {
    int data;
    struct node *next;};

struct node *start = NULL;
struct node *insert_beg(struct node*);
struct node *insert_end(struct node*); struct node *insert_at_pos(struct no
struct node *delete_beg(struct node*);
struct node *delete_end(struct node*); struct node *delete_at_pos(struct
struct node *display(struct node*);

int main()
{ int option;
  do {
   printf("\n *** MENU ***");
   printf("\n 1: Insert at beginning");
   printf("\n 2: Insert at the end"); printf("\n 3: Insert at a specific po
   printf("\n 4: Delete at beginning");
   printf("\n 5: Delete at the end"); printf("\n 6: Delete from a specific p
   printf("\n 7: Display");
   printf("\n 8: Exit");
   printf("Enter your option:");
   scanf("%d", &option);
   switch(option)
  { case 1: start = insert_beg(start);
            break;
   case 2: start = insert-end(start);
            break;
   case 3: start = insert_at-pos(start);
            break;
```

```
case 4: start = delete_beg(start);
        break;
case 5: start = delete_end(start);
        break;
case 6: start = delete_at_pos
        (start);
        break;
case 7: start = display(start);
        break;
}
}while(option != 8);
getch();
return 0; }
```

```
Struct node *temp;
while (start != NULL){
    temp = start;
    start = start -> next;
    free(temp); }
```

```
struct node* insert_beg (struct node *start)
{ struct node *new_node;
  int num;
  printf ("Enter the data:");
  scanf ("%d", &num);
  new_node = (struct node *) malloc (sizeof(struct node));
  new_node -> data = num;
  new_node -> next = start;
  start = new_node;
  printf ("Inserted at the beginning\n");
  return start; }
```

```
Struct node * insert_end (struct node *start)
{ Struct node *ptr, *new_node;
  int num;
  printf ("Enter the data:");
  scanf ("%d", &num);
  new_node = (struct node *) malloc (sizeof (struct node));
  new_node -> data = num;
  new_node -> next = NULL;
  ptr = start;
  while (ptr -> next != NULL)
      ptr = ptr -> next;
  ptr -> next = new_node;
  printf ("Inserted at the end\n");
  return start; }
```

```
Struct node *delete_beg (struct node * start)
{ struct node *ptr;
  ptr = start;
  if (ptr -> next == NULL)
  { printf (" Empty List. Can't be deleted");
    return start; }
  else { start = start -> next;
         free(ptr);
         printf (" Deleted at beginning");
         return start; }
}
Struct node *delete_end (struct node *start)
{ Struct node *ptr, *ptr1;
  ptr = start;
  if (ptr -> next == NULL)
  { printf(" Empty List. Can't be deleted");
    return start; }
  else { while (ptr -> next != NULL)
         { ptr1 = ptr;
         ptr = ptr -> next; }
          ptr1 -> next = NULL;
          free(ptr);
          printf (" Deleted at the end");
          return start; }
}

Struct node * display (struct node * start)
{   Struct node * ptr;
    ptr = start;
    if (ptr -> next == NULL)
    { printf (" Empty List.");
      return start; }
    else { while(ptr -> next != NULL)
           { printf (" %d", ptr -> data);
             ptr = ptr -> next;
           } return start; }
}
```

```
Struct node * insert_at_pos (struct node * start)
{  Struct node * new_node, * ptr, * preptr;
   int pos, num;
   printf (" Enter the position to insert at:");
   Scanf (" %d", &pos);
   printf (" Enter the data: ");
   Scanf ("%d", &num);
   new_node = (Struct node *) malloc (sizeof (Struct node));
   new_node → data = num;
   new_node → next = NULL;
   if (pos == 1) {
      new_node → next = start;
      start = new_node;
      printf (" Inserted at position %d \n", pos);
      return start; }
  else {  ptr = start;
      int i;
      for (int i = 1; i< pos && ptr != NULL; i++)
      {  preptr = ptr;
         ptr = ptr → next; }
      if (ptr == NULL && pos > i)
      {  printf (" Invalid position. \n");
         return start; }
      preptr → next = new_node;
      new_node → next = ptr;
      printf (" Inserted at position %d", pos);
      return start; }
}


Struct node * delete_at_pos (Struct node * start)
{ Struct node *ptr, *preptr;
  int pos;
  printf (" Enter the position to delete");
  Scanf (" %d", &pos);
  if (start == NULL)
  {  printf (" Empty list. Can't be deleted\n");
     return start; }
}
```

```
    ptr = start;
    if (pos == 1)
    { start = start -> next;
      free(ptr);
      printf (" Deleted at position %d \n", pos);
      return start;
    }
    else {
      for (int i=1; i<pos && ptr != NULL; i++)
      { preptr = ptr;
        ptr = ptr -> next; }
      if (ptr == NULL)
      { printf (" Invalid position \n");
        retun start;
      }
      preptr -> next = ptr -> next;
      free (ptr);
      printf (" Deleted at position %d \n", pos);
      return start;
    }
}
```

OUTPUT:

```
***Main Menu***
1: Add a node at the beginning.
2: Add a node at the end.
3: Add a node at a specific position.
4: Delete a node from the beginning.
5: Delete a node from the end.
6: Delete a node from a specific position.
7: Display the list.
8: EXIT.
Enter your option: 1
Enter the data: 10
Inserted at the beginning.
```

```
C:\Users\tanma\OneDrive\Do

 *****MAIN MENU *****
 1: Add a node at the beginning
 2: Add a node at the end
 3: Add a node at a specific position
 4: Delete a node from the beginning
 5: Delete a node from the end
 6: Delete a node from a specific position
 7: Display the list
 8: EXIT

 Enter your option :1
Enter the data: 10
Inserted at the beginning.


 *****MAIN MENU *****
 1: Add a node at the beginning
 2: Add a node at the end
 3: Add a node at a specific position
 4: Delete a node from the beginning
 5: Delete a node from the end
 6: Delete a node from a specific position
 7: Display the list
 8: EXIT

 Enter your option :2
Enter the data: 30
Inserted at the end.


 *****MAIN MENU *****
 1: Add a node at the beginning
 2: Add a node at the end
 3: Add a node at a specific position
 4: Delete a node from the beginning
 5: Delete a node from the end
 6: Delete a node from a specific position
 7: Display the list
```

```
C:\Users\tanma\OneDrive\Do
 7: Display the list
 8: EXIT

 Enter your option :3
Enter the position to insert at: 2
Enter the data: 20
Inserted at position 2.


 *****MAIN MENU *****
 1: Add a node at the beginning
 2: Add a node at the end
 3: Add a node at a specific position
 4: Delete a node from the beginning
 5: Delete a node from the end
 6: Delete a node from a specific position
 7: Display the list
 8: EXIT

 Enter your option :7
Linked list elements: 10        20      30


 *****MAIN MENU *****
 1: Add a node at the beginning
 2: Add a node at the end
 3: Add a node at a specific position
 4: Delete a node from the beginning
 5: Delete a node from the end
 6: Delete a node from a specific position
 7: Display the list
 8: EXIT

 Enter your option :4
Deleted at the beginning.


 *****MAIN MENU *****
 1: Add a node at the beginning
 2: Add a node at the end
```

```
 2: Add a node at the end
 3: Add a node at a specific position
 4: Delete a node from the beginning
 5: Delete a node from the end
 6: Delete a node from a specific position
 7: Display the list
 8: EXIT

 Enter your option :6
Enter the position to delete: 2
Deleted at position 2.


 *****MAIN MENU *****
 1: Add a node at the beginning
 2: Add a node at the end
 3: Add a node at a specific position
 4: Delete a node from the beginning
 5: Delete a node from the end
 6: Delete a node from a specific position
 7: Display the list
 8: EXIT

 Enter your option :7
Linked list elements: 20


 *****MAIN MENU *****
 1: Add a node at the beginning
 2: Add a node at the end
 3: Add a node at a specific position
 4: Delete a node from the beginning
 5: Delete a node from the end
 6: Delete a node from a specific position
 7: Display the list
 8: EXIT

 Enter your option :8

Process returned 0 (0x0)   execution time : 67.518 s
```