

# OBJECT ORIENTED PROGRAMMING LAB

Submitted By: Tanmay Vig

Roll No.: 19BCS061

Batch: B. Tech 3<sup>rd</sup> year

Submitted to: -

Dr. Mumtaz Ahmed

Mr. Shamim Ahmad

Department Of Computer Engineering

S no.	Program title	Date Submitted
1	Enter some Students data like Name, Roll no, Class, subject code, sub name, marks obtained, max marks etc.	10/08/21
2	Implement Program p1 using Default Constructor and Parameterized Constructor	17/08/21
3	Implement Array of Objects in given problem	24/08/21
4	Implement Bank Account	31/08/21
5	Implement Friend Function	07/9/21
6	Implement Book Store	14/9/21
7	Implement Employee	21/9/21
8	Implement Operator Overloading: String Operations	5/10/21
9	Implement Stack using classes and objects	26/10/21
10	Implement Inheritance in given problem	16/11/21
11	Implement Inheritance in given problem	23/11/21
12	Templates-Write a program in C++ to implement a generic Stack.	30/11/21
13	Templates-Write a program in C++ to implement a generic Stack.	7/12/21

**P1:** Enter some Students data like Name, roll no, Class, subject code, subname, marks obtained, max marks etc. Print their Grades according to following rule Grade A if marks obtained are in range 75-100. Grade B if marks obtained are in range 60-74. Grade C if marks obtained are in range 45-59 Grade D if marks obtained are in range 35-44 Grade F if marks obtained are in range 0-34.

### Source Code:

```
#include<iostream>

#include<vector>

#include<string>

#include <iomanip>

#include<vector>


using namespace std;


class Student{
    private:
        string name;
        string _class;
        string roll_num;
        int num;
        string *subject_code;
        string *subject_name;
```

```
float *marks;

float max_marks;

public:

Student() {}

Student(string na,string cl,string r_n,int n, string s_c[],string s_n[], float m[]){

    name=na;
    _class=cl;
    roll_num=r_n;
    num=n;
    subject_code=s_c;
    subject_name=s_n;
    marks=m;
    max_marks=-1;
    for(int i=0;i<num;i++){
        if(max_marks<marks[i]) max_marks=marks[i];
    }
}

void marksheet(){

    cout<<"Name: "<<name<<"\nRoll Number: "<<roll_num<<"\nClass: "<<_class<<endl;
    cout<<"-----\n";

    cout<<"| Subject code| Subject Name| Marks| Grade|\n";
    cout<<"-----\n";

    for(int i=0;i<num;i++){

        cout<<"| "<<setw(12)<<subject_code[i]<<"| "<<setw(12)<<subject_name[i]<<"|
"<<setw(5)<<marks[i]<<"| "<<setw(5)<<grade(marks[i])<<"|\n";
```

```
    }

    cout<<"-----\n";

    cout<<"Max_marks: "<<max_marks<<endl;

    cout<<"Net Grade: "<<grade(total(marks,num)/num)<<endl;

}

float total(float m[],int n){

    float sum=0;

    for(int i=0;i<n;i++) sum+=m[i];

    return sum;

}

string grade(float m){

    if(m>=75) return "A";

    else if(m<75 && m>=60) return "B";

    else if(m<60 && m>=45) return "C";

    else if(m<45 && m>=35) return "D";

    return "F";

}

};

int main(){

    int n;

    cout<<"Enter Number of students:\t";

    cin>>n;

    Student arr[100];

    for(int i=0;i<n;i++){
```

```
    string name,clas,r_n,s_c[20],s_n[20]; int num; float m[20];  
    cout<<"Enter Name and Roll Number of student:\t";  
    cin>>name>>r_n;  
    cout<<"Enter Class of student:\t";  
    cin>>clas;  
    cout<<"Enter Number of subjects:\t";  
    cin>>num;  
    cout<<"Enter the Subject codes, Subject Name, marks obtained\n";  
    for(int j=0;j<num;j++) cin>>s_c[j]>>s_n[j]>>m[j];  
    Student s(name,clas,r_n,num,s_c,s_n,m);  
    cout<<endl;  
    s.marksheet();  
}  
return 0;  
}
```

## Output:

D:\sem-5\opp\_Lab\1.exe

```
Enter Number of students:      2
Enter Name and Roll Number of student:  Ruben 19BCS061
Enter Class of student: 3rd
Enter Number of subjects:      4
Enter the Subject codes, Subject Name, marks obtained
CEN501 SE 80
CEN502 CI 23
CEN503 CN 60
CEN504 ML 54
```

```
Name: Ruben
Roll Number: 19BCS061
Class: 3rd
```

Subject code	Subject Name	Marks	Grade
CEN501	SE	80	A
CEN502	CI	23	F
CEN503	CN	60	B
CEN504	ML	54	C

Max\_marks: 80

Net Grade: C

```
Enter Name and Roll Number of student:  Bedi 20BCS010
Enter Class of student: 2nd
Enter Number of subjects:      3
Enter the Subject codes, Subject Name, marks obtained
CEN301 DS 90
CEN302 DLD 51
CEN OOP 80
```

```
Name: Bedi
Roll Number: 20BCS010
Class: 2nd
```

Subject code	Subject Name	Marks	Grade
CEN301	DS	90	A
CEN302	DLD	51	C
CEN	OOP	80	A

Max\_marks: 90

Net Grade: B

```
-----
Process exited after 168.8 seconds with return value 0
Press any key to continue . . .
```

## **P2**: implement Program P1 using Default Constructor and Parameterized constructor.

### **Source Code:**

```
#include <bits/stdc++.h>

using namespace std;

class Student {

    public:

        string name;

        int _class, rollNum, totalSubjects;

        string subjectNames[100], subjectCodes[100];

        int marks[100], maxMarks[100];

// Default Constructor

    Student() {

        this->name="";

        this->_class=0;

        this->rollNum=0;

    }

// Parameterized Constructor

    Student(string name, int _class, int rollNum) {

        this->name=name;

        this->_class=_class;

        this->rollNum=rollNum;
```

```
}
```

```
// Student data setter, in case of default constructor
```

```
void setStudentData(string name, int _class, int rollNum) {
```

```
    this->name=name;
```

```
    this->_class=_class;
```

```
    this->rollNum=rollNum;
```

```
}
```

```
void setData() {
```

```
    int n;
```

```
    cout << "Enter the number of subjects" << endl;
```

```
    cin >> n;
```

```
    this->totalSubjects = n;
```

```
    for(int i=0;i<n;i++) {
```

```
        string subName, subCode;
```

```
        int marks, maxMarks;
```

```
        cout << "Enter the name, code, marks and max marks for subject " << i+1 << endl;
```

```
        cin >> subName;
```

```
        cin >> subCode;
```

```
        cin >> marks;
```

```
        cin >> maxMarks;
```

```
        this->subjectNames[i] = subName;
```

```
        this->subjectCodes[i] = subCode;
```

```
        this->marks[i] = marks;
```



```
        this->maxMarks[i] = maxMarks;

    }

}

void getData() {

    cout << "Subject wise marks of " << this->name << " are" << endl;

    cout << "Name\t\t" << "Code\t\t" << "Max Marks\t\t" << "Marks Obtained" << endl;

    int totalMarks = 0, totalMaxMarks = 0;

    double avg;

    for(int i=0;i<this->totalSubjects;i++) {

        cout << this->subjectNames[i] << "\t\t" << this->subjectCodes[i] << "\t\t" << this->
        maxMarks[i] << "\t\t\t" << this->marks[i] << endl;

        totalMarks += this->marks[i];

        totalMaxMarks += this->maxMarks[i];

    }

    avg = ((double)totalMarks/(double)totalMaxMarks)*100.0;

    cout << endl << "Grade of student " << this->name << " is: ";

    if(avg >= 75.0) cout << "A" << endl << endl;

    else if(avg >= 60.0) cout << "B" << endl << endl;

    else if(avg >= 45.0) cout << "C" << endl << endl;

    else if(avg >= 35.0) cout << "D" << endl << endl;

    else cout << "F" << endl << endl;


}

};
```

```
int main() {  
  
    cout << "Enter the number of students" << endl;  
  
    int n;  
  
    cin >> n;  
  
    for(int i=1;i<=n;i++) {  
  
        string name;  
  
        int _class, rollNum;  
  
        cout << "Enter the name, class and roll number of student " << i << endl;  
  
        cin >> name;  
  
        cin >> _class;  
  
        cin >> rollNum;  
  
        int choice;  
  
        cout << "Enter 0 to use default constructor, 1 to use parameterized constructor" << endl;  
  
        cin >> choice;  
  
        if(choice == 0) {  
  
            Student* student = new Student();  
  
            student->setStudentData(name, _class, rollNum);  
  
            student->setData();  
  
            student->getData();  
  
        } else {  
  
            Student* student = new Student(name, _class, rollNum);  
  
            student->setData();  
  
            student->getData();  
  
        }  
    }  
}
```

```
    }  
  
    }  
  
    return 0;  
  
}
```

## Output:

 D:\sem-5\oop\_Lab\2.exe

```
Enter the name, code, marks and max marks for subject 2  
Sub2 102 96 100  
Subject wise marks of Tanmay are  
Name           Code           Max Marks           Marks Obtained  
Sub1            101            89                  89  
Sub2            102            100                 96  
  
Grade of student Tanmay is: A  
  
Enter the name, class and roll number of student 2  
Ruben 12 34  
Enter 0 to use default constructor, 1 to use parameterized constructor  
1  
Enter the number of subjects  
2  
Enter the name, code, marks and max marks for subject 1  
Sub1 121 20 60  
Enter the name, code, marks and max marks for subject 2  
Sub2 122 89 90  
Subject wise marks of Ruben are  
Name           Code           Max Marks           Marks Obtained  
Sub1            121            60                  20  
Sub2            122            90                  89  
  
Grade of student Ruben is: B  
  
-----  
Process exited after 138.4 seconds with return value 0  
Press any key to continue . . . █
```

**P3 a:** Create a class called Employee that contains employee number (type long), name (an object of class string) and salary (integer). Include a member function called getData() to get data from the user for insertion into the object, and another function called putData() to display the data. Define both the functions outside the class. Assume the name has embedded blanks (like Rakesh Kumar Mehta). Write a main() program to execute this class. It should create an array of type Employee, and then invite the user to input data for up to 10 employees. Finally, it should print out the data for all the employees in proper format.

**Source code:**

```
#include<iostream>

#include<string>

#include <iomanip>

using namespace std;

class Employee{
    public:
        long long int employee_number;
        string name;
        int salary;
        void getData();
        void putData();
```

```
};
```

```
void Employee::getData(){  
    cout<<"Enter employee number\t";  
    cin>>employee_number;  
    cin.clear();  
    cin.sync();  
    cout<<"Enter Name of employee"<<endl;  
    getline(cin,name);  
    cout<<"Enter Salary\t";  
    cin>>salary;  
}
```

```
void Employee::putData(){  
  
    cout<<left<<" | "<<setw(15)<<employee_number<<" | "<<setw(15)<<name<<" | "<<setw(15)<<salary<<endl;  
}
```

```
int main(){  
    Employee arr[10];  
    cout<<"Enter details:\n";  
    for(int i=0;i<10;i++){  
        cout<<"Enter data for employee "<<i+1<<endl;  
        arr[i].getData();  
    }  
    cout<<"Employee Details:\n"<<
```

```
    " _____\n | Employee Number | Name  
 | Salary      | \n _____\n";  
    for(int i=0;i<10;i++){  
        arr[i].putData();  
        cout<<" _____\n";  
    }  
    return 0;  
}
```

## Output:

```
D:\sem-5\oop_Lab\3a.exe
Enter data for employee 9
Enter employee number 9
Enter Name of employee
Garvit Ahuja
Enter Salary 88000
Enter data for employee 10
Enter employee number 10
Enter Name of employee
Bhargav Bajaj
Enter Salary 60000
Employee Details:

Employee Number | Name | Salary |
1 | Paras Dang | 80000 |
2 | Prabhmeet Singh | 75000 |
3 | Parmeesh Singh | 89000 |
4 | Ruben Singh | 89000 |
5 | Naman Sachdeva | 60000 |
6 | Mridul Bhatia | 50000 |
7 | Aryan Bedi | 89000 |
8 | Tanmay Vig | 1000000 |
9 | Garvit Ahuja | 88000 |
10 | Bhargav Bajaj | 60000 |

-----
Process exited after 229.1 seconds with return value 0
Press any key to continue . . .
```

```
D:\sem-5\oop_Lab\3a.exe
Enter details:
Enter data for employee 1
Enter employee number 1
Enter Name of employee
Paras Dang
Enter Salary 80000
Enter data for employee 2
Enter employee number 2
Enter Name of employee
Prabhmeet Singh
Enter Salary 75000
Enter data for employee 3
Enter employee number 3
Enter Name of employee
Parmeesh Singh
Enter Salary 89000
Enter data for employee 4
Enter employee number 4
Enter Name of employee
Ruben Singh
Enter Salary 89000
Enter data for employee 5
Enter employee number 5
Enter Name of employee
Naman Sachdeva
Enter Salary 60000
Enter data for employee 6
Enter employee number 6
Enter Name of employee
Mridul Bhatia
Enter Salary 50000
Enter data for employee 7
Enter employee number 7
Enter Name of employee
Aryan Bedi
Enter Salary 89000
Enter data for employee 8
Enter employee number 8
Enter Name of employee
Tanmay Vig
Enter Salary 1000000
Enter data for employee 9
Enter employee number 9
Enter Name of employee
Garvit Ahuja
Enter Salary 88000
Enter data for employee 10
Enter employee number 10
Enter Name of employee
Bhargav Bajaj
```

**P3 b:** Create a class called Student that contains a Student id (type int), name (char array ) and marks (integer). Include a member function called getStudent() to get data from the user for insertion into the object, and another function called printStudent() to display the data. Define both the functions inside the class. Assume the name has no embedded blanks. Write a main() program to execute this class. It should create an array of type Student, and then invite the user to input data for up to 10 students. Finally, it should print out the data for all the students in proper format.

**Source Code:**

```
#include<iostream>

#include<string>

#include <iomanip>

#define M 10

using namespace std;

class Student{

    public:

        int student_id;
```



```
        char name[30];
        int marks;
        void getData(){
            cout<<"Enter student number\t";
            cin>>student_id;
            cin.clear();
            cin.sync();
            cout<<"Enter Name of student"<<endl;
            cin.getline(name,30);
            cout<<"Enter Marks\t";
            cin>>marks;
        }
        void putData(){

        cout<<left<<"|"<<setw(15)<<student_id<<"|"<<setw(15)<<name<<"|"<<setw(15)<<marks<<"|
        "<<endl;

        }

};

int main(){
    Student arr[M];
    cout<<"Enter details:\n";
    for(int i=0;i<M;i++){
        cout<<"Enter data for student "<<i+1<<endl;
        arr[i].getData();
    }
    cout<<"Student Details:\n"<<
```

output:

```
D:\C++\oop\lab13.exe
Enter details:
Enter data for student 1
Enter student number 1
Enter Name of student
Ruben
Enter Marks 99
Enter data for student 2
Enter student number 2
Enter Name of student
Bhargav
Enter Marks 38
Enter data for student 3
Enter student number 3
Enter Name of student
Paras
Enter Marks 89
Enter data for student 4
Enter student number 4
Enter Name of student
Boby
Enter Marks 76
Enter data for student 5
Enter student number 5
Enter Name of student
Prabmeet
Enter Marks 88
Enter data for student 6
Enter student number 6
Enter Name of student
Garvit
Enter Marks 84
Enter data for student 7
Enter student number 7
Enter Name of student
Vojkeet
Enter Marks 92
Enter data for student 8
Enter student number 8
Enter Name of student
Parmeesh
Enter Marks 91
Enter data for student 9
Enter student number 9
Enter Name of student
Tanmay
Enter Marks 100
Enter data for student 10
Enter student number 10
Enter Name of student
Aridul
```

```
D:\sem-5\oop_lab\3b.exe
Enter student number 8
Enter Name of student
Parmeesh
Enter Marks 91
Enter data for student 9
Enter student number 9
Enter Name of student
Tanmay
Enter Marks 100
Enter data for student 10
Enter student number 10
Enter Name of student
Mridul
Enter Marks 33
Student Details:
|Student Number|Name|Marks|
|1|Ruben|99|
|2|Bhargav|38|
|3|Paras|89|
|4|Boby|76|
|5|Prabhmeet|88|
|6|Garvit|84|
|7|Malkeet|92|
|8|Parmeesh|91|
|9|Tanmay|100|
|10|Mridul|33|
-----
Process exited after 179.2 seconds with return value 0
Press any key to continue . . .
```

**P4:** Write a program in C++ to represent a Bank Account.

Data members:

- Account number
- Name of the depositor
- Type of account
- Balance amount in the account

Member functions:

- To assign initial values
- To deposit an amount
- To withdraw an amount after checking the balance
- To display name and balance of a single customer if account number is entered through
- the keyboard
- To display the details of all customers
- Sort the customers according to their balance

Write a main program to test the class. Your program must be able to handle at least 10 customers.

**Source Code:**

```
#include<iostream>
#include<string>
#define M 10
```

```
using namespace std;
```

```
class Account{
```

```
private:
```

```
    long long int account_number;
```

```
    string name;
```

```
    string account_type;
```

```
    int balance;
```

```
public:
```

```
    void putDetails(){
```

```
        cout<<"Enter Account Number:\t";
```

```
        cin>>account_number;
```

```
        cin.ignore();
```

```
        cout<<"Enter Name of depositor:\t";
```

```
        getline(cin, name);
```

```
        cout<<"Enter Type of Account(Current, Saving, Salary):\t";
```

```
        getline(cin, account_type);
```

```
        cout<<"Enter Balance amount in the account:\t";
```

```
        cin>>balance;
```

```
    }
```

```
    void deposit(int amt){
```

```
        balance=balance+amt;
```

```
        cout<<"Amount deposited: "<<amt<<". Total balance: "<<balance<<endl;
```

```
    }
```

```
void withdraw(int amt){
    if(balance<amt) cout<<"Error: please input Valid amount.\nYour current balance is:
"<<balance<<endl;
    else{
        balance=balance-amt;
        cout<<"Amount withdraw: "<<amt<<". Total balance: "<<balance<<endl;
    }
}

void display(){
    cout<<"Name: "<<name<<".\nAccount Type: "<<account_type<<".\nBalance:
"<<balance<<endl;
}

int getbalance(){
    return balance;
}

long long int getAccNum(){
    return account_number;
}

};

int findAcc(Account arr[],long long int num) {
    for(int i=0;i<M;i++) {
        if(arr[i].getAccNum()==num) return i;
    }
    return -1;
}
```

```
int main(){  
    Account arr[M];  
    int n;  
    long long int accNum;  
    for(int i=0;i<M;i++){  
        cout<<"Enter Details of Account "<<i+1<<endl;  
        arr[i].putDetails();  
    }  
    do{  
        cout<<"Enter 1 to Deposit. \nEnter 2 to Withdraw. \nEnter 3 to see your Details.\nEnter 0  
to exit.\n";  
        cin>>n;  
        if(n){  
            cout<<"Enter Account Number:\t";  
            cin>>accNum;  
        }  
        int index=findAcc(arr,accNum),amt;  
        if(index!=-1){  
            switch (n)  
            {  
            case 1:  
                cout<<"Enter Amount to Deposit:\t";  
                cin>>amt;  
                cout<<endl;  
                arr[index].deposite(amt);  
                break;  
            case 2:
```

```
        cout<<"Enter Amount to withdraw:\t";

        cin>>amt;

        cout<<endl;

        arr[index].withdraw(amt);

        break;

    case 3:

        cout<<endl;

        arr[index].display();

        break;

    default:

        cout<<"Enter valid input or 0 to Exit\n";

        break;

    }

}

else if(index==-1){

    cout<<"\nError: no account found.\n";

}

}while(n!=0);

cout<<"Enter 1 to see all account details in sorted order\nEnter 2 to see all details in
unsorted order\n";

cin>>n;

if(n==1){

    int i,j;

    for(i=0;i<M-1;i++){

        for(j=0;j<M-i-1;j++){

            if(arr[j].getbalance()>arr[j+1].getbalance()){

                Account temp=arr[j];

                arr[j]=arr[j+1];

                arr[j+1]=temp;

            }

        }

    }

}
```



```
        arr[j+1]=temp;
    }
}
}
cout<<"Showing Details in unsorted order:\n";
cout<<"_____ "<<endl;
for(int i=0;i<M;i++){
    arr[i].display();
    cout<<"_____ "<<endl;
}
}else{
    cout<<"Showing Details in unsorted order:\n";
    cout<<"_____ "<<endl;
    for(int i=0;i<M;i++){
        arr[i].display();
        cout<<"_____ "<<endl;
    }
}
return 0;
}
```

## Output:

```
D:\sem-5\oop_Lab\4.exe
Enter Details of Account 1
Enter Account Number: 1001
Enter Name of depositor: Tanmay Vig
Enter Type of Account(Current, Saving, Salary): Current
Enter Balance amount in the account: 123123123
Enter Details of Account 2
Enter Account Number: 1002
Enter Name of depositor: Ruben Singh
Enter Type of Account(Current, Saving, Salary): Saving
Enter Balance amount in the account: 12312312
Enter Details of Account 3
Enter Account Number: 1003
Enter Name of depositor: Parmeesh Singh
Enter Type of Account(Current, Saving, Salary): Salary
Enter Balance amount in the account: 1231231
Enter Details of Account 4
Enter Account Number: 1004
Enter Name of depositor: Paras Dang
Enter Type of Account(Current, Saving, Salary): Current
Enter Balance amount in the account: 123123
Enter Details of Account 5
Enter Account Number: 1005
Enter Name of depositor: Bhargav Bajaj
Enter Type of Account(Current, Saving, Salary): Saving
Enter Balance amount in the account: 12312
Enter Details of Account 6
Enter Account Number: 1006
Enter Name of depositor: Aryan Bedi
Enter Type of Account(Current, Saving, Salary): Salary
Enter Balance amount in the account: 1231
Enter Details of Account 7
Enter Account Number: 1007
Enter Name of depositor: Bobby Sachdeva
Enter Type of Account(Current, Saving, Salary): Current
Enter Balance amount in the account: 123
Enter Details of Account 8
Enter Account Number: 1008
Enter Name of depositor: Mridul Bhatia
Enter Type of Account(Current, Saving, Salary): Saving
Enter Balance amount in the account: 10000
Enter Details of Account 9
Enter Account Number: 1009
Enter Name of depositor: Prabhmeet Singh
Enter Type of Account(Current, Saving, Salary): Salary
Enter Balance amount in the account: 12122
Enter Details of Account 10
Enter Account Number: 1010
Enter Name of depositor: Garvit Ahuja
Enter Type of Account(Current, Saving, Salary): Current
Enter Balance amount in the account: 102031
```

```
D:\sem-5\oop_Lab\4.exe
Enter Name of depositor: Garvit Ahuja
Enter Type of Account(Current, Saving, Salary): Current
Enter Balance amount in the account: 102031
Enter 1 to Deposit.
Enter 2 to Withdraw.
Enter 3 to see your Details.
Enter 0 to exit.
1
Enter Account Number: 1001
Enter Amount to Deposite: 500000
Amount deposited: 500000. Total balance: 123623123
Enter 1 to Deposit.
Enter 2 to Withdraw.
Enter 3 to see your Details.
Enter 0 to exit.
2
Enter Account Number: 1010
Enter Amount to withdraw: 1000
Amount withdraw: 1000. Total balance: 101031
Enter 1 to Deposit.
Enter 2 to Withdraw.
Enter 3 to see your Details.
Enter 0 to exit.
3
Enter Account Number: 1008
Name: Mridul Bhatia.
Account Type: Saving.
Balance: 10000
Enter 1 to Deposit.
Enter 2 to Withdraw.
Enter 3 to see your Details.
Enter 0 to exit.
0
Enter valid input or 0 to Exit
Enter 1 to see all account details in sorted order
Enter 2 to see all details in unsorted order
1
Showing Details in unsorted order:
Name: Bobby Sachdeva.
Account Type: Current.
Balance: 123
Name: Aryan Bedi.
Account Type: Salary.
Balance: 1231
```

Name: Tanmay Vig  
Roll No.: 19BCS061

OOPS Lab Practical File

```
D:\sem-5\oop_Lab\4.exe
Showing Details in unsorted order:

Name: Bobby Sachdeva.
Account Type: Current.
Balance: 123

Name: Aryan Bedi.
Account Type: Salary.
Balance: 1231

Name: Mridul Bhatia.
Account Type: Saving.
Balance: 10000

Name: Prabhmeet Singh.
Account Type: Salary.
Balance: 12122

Name: Bhargav Bajaj.
Account Type: Saving.
Balance: 12312

Name: Garvit Ahuja.
Account Type: Current.
Balance: 101031

Name: Paras Dang.
Account Type: Current.
Balance: 123123

Name: Parmeesh Singh.
Account Type: Salary.
Balance: 1231231

Name: Ruben Singh.
Account Type: Saving.
Balance: 12312312

Name: Tanmay Vig.
Account Type: Current.
Balance: 123623123

-----
Process exited after 359.6 seconds with return value 0
Press any key to continue . . .
```

**P5 a:** Write the definition for a class called Rectangle that has floating point data members length and width. The class has the following member functions:

void setlength(float) to set the length data member

void setwidth(float) to set the width data member

float perimeter() to calculate and return the perimeter of the rectangle

float area() to calculate and return the area of the rectangle

void show() to display the length and width of the rectangle

int sameArea(Rectangle) that has one parameter of type Rectangle. sameArea() returns 1 if the two Rectangles have the same area, and returns 0 if they don't.

Write the definitions for each of the above member functions.

Write main function to create two rectangle objects. Set the length and width of the first rectangle to 5 and 2.5. Set the length and width of the second rectangle to 5 and 18.9. Display each rectangle and its area and perimeter.

3. Check whether the two Rectangles have the same area and print a message indicating the result. Set the length and width of the first rectangle to 15 and 6.3. Display each Rectangle and its area and perimeter again. Again, check whether the two Rectangles have the same area and print a message indicating the result.

### Source Code:

```
#include<iostream>

using namespace std;

class Rectangle{
    private:
        float length;
        float width;
    public:
        void setLength(float);
        void setWidth(float);
        float perimeter();
        float area();
        void show();
        int sameArea(Rectangle);
};

void Rectangle::setLength(float l){
    length=l;
```

```
        cout<<"Length of rectangle is set to "<<l<<endl;
    }

    void Rectangle::setWidth(float w){
        width=w;
        cout<<"Width of rectangle is set to"<<w<<endl;
    }

    float Rectangle::perimeter(){
        return 2*(length+width);
    }

    float Rectangle::area(){
        return length*width;
    }

    void Rectangle::show(){
        cout<<"Length of Rectangle: "<<length<<"\nWidth of Rectangle: "<<width<<endl;
    }

    int Rectangle::sameArea(Rectangle r){
        return area()==r.area() ? 1 : 0;
    }

    int main(){
        Rectangle r1,r2;
        cout<<"Setting dimentions of Rectangle 1.\n";
```

```
r1.setLength(5); r1.setWidth(2.5);  
cout<<endl;  
  
cout<<"Setting dimentions of Rectangle 2.\n";  
r2.setLength(5); r2.setWidth(18.9);  
cout<<endl;  
  
cout<<"Showing details of Rectangles\n\n";  
cout<<"Rectangle 1:\n";  
r1.show();  
cout<<"Area: "<<r1.area()<<endl;  
cout<<"Perimeter: "<<r1.perimeter()<<endl;  
cout<<endl;  
cout<<"Rectangle 2:\n";  
r2.show();  
cout<<"Area: "<<r1.area()<<endl;  
cout<<"Perimeter: "<<r1.perimeter()<<endl;  
cout<<endl;  
  
if(r1.sameArea(r2)) cout<<"Both Rectangles have the same area.\n\n";  
else cout<<"Both Rectangles have different area.\n\n";  
  
cout<<"Changing dimentions of Rectangle 1.\n";  
r1.setLength(15);  
r1.setWidth(6.3);  
cout<<endl;
```

```
    cout<<"Showing details of Rectangles\n\n";  
    cout<<"Rectangle 1:\n";  
    r1.show();  
    cout<<"Area: "<<r1.area()<<endl;  
    cout<<"Perimeter: "<<r1.perimeter()<<endl;  
    cout<<endl;  
    cout<<"Rectangle 2:\n";  
    r2.show();  
    cout<<"Area: "<<r1.area()<<endl;  
    cout<<"Perimeter: "<<r1.perimeter()<<endl;  
    cout<<endl;  
  
    if(r1.sameArea(r2)) cout<<"Both Rectangles have the same area.\n\n";  
    else cout<<"Both Rectangles have different area.\n\n";  
  
    return 0;  
}
```

**Output:**



```
D:\sem-5\oop_lab\5a.exe
Setting dimentions of Rectangle 1.
Length of rectangle is set to 5
Width of rectangle is set to2.5

Setting dimentions of Rectangle 2.
Length of rectangle is set to 5
Width of rectangle is set to18.9

Showing details of Rectangles

Rectangle 1:
Length of Rectangle: 5
Width of Rectangle: 2.5
Area: 12.5
Perimeter: 15

Rectangle 2:
Length of Rectangle: 5
Width of Rectangle: 18.9
Area: 12.5
Perimeter: 15

Both Rectangles have different area.

Changing dimentions of Rectangle 1.
Length of rectangle is set to 15
Width of rectangle is set to6.3

Showing details of Rectangles

Rectangle 1:
Length of Rectangle: 15
Width of Rectangle: 6.3
Area: 94.5
Perimeter: 42.6

Rectangle 2:
Length of Rectangle: 5
Width of Rectangle: 18.9
Area: 94.5
Perimeter: 42.6

Both Rectangles have the same area.

-----
Process exited after 0.08414 seconds with return value 0
Press any key to continue . . .
```

**P5 b:** Write the definition for a class called complex that has floating point data members for storing real and imaginary parts. The class has the following member functions:

- void set(float, float) to set the specified value in object
- void disp() to display complex number object
- complex sum(complex) to sum two complex numbers & return complex number

1. Write the definitions for each of the above member functions.
2. Write main function to create three complex number objects. Set the value in two objects and call sum() to calculate sum and assign it in third object. Display all complex numbers.

Source code:

```
#include<iostream>


using namespace std;

class Complex{
    private:
        float real;
        float imag;
        Complex friend sum(Complex,Complex);
    public:
        void set(float r,float i){
            real = r; imag = i;
        }
        void display(){
            cout<<real<<" + "<<imag<<"i\n";
        }
};
```

```
Complex sum(Complex x,Complex y){  
    Complex c;  
    c.real = x.real+y.real; c.imag = x.imag+y.imag;  
    return c;  
}  
  
int main(){  
    Complex a,b,c;  
    float r,i;  
    cout<<"Enter value of complex number 1.\nreal part:\t";  
    cin>>r;  
    cout<<"imaginary part:\t"; cin>>i;  
    a.set(r,i);  
  
    cout<<"Enter value of complex number 2.\nreal part:\t";  
    cin>>r;  
    cout<<"imaginary part:\t"; cin>>i;  
    b.set(r,i);  
  
    c = sum(a,b);  
    cout<<"Displaying values of complex numbers:\n";  
    cout<<"number 1:\n";  
    a.display();  
    cout<<"number 2:\n";  
    b.display();  
    cout<<"number 3:\n";  
    c.display();
```

```
    return 0;  
}
```

## Output:



```
D:\sem-5\oop_Lab\5b.exe  
Enter value of complex number 1.  
real part:    3.5  
imaginary part: 2  
Enter value of complex number 2.  
real part:    2  
imaginary part: 3.5  
Displaying values of complex numbers:  
number 1:  
3.5 + 2i  
number 2:  
2 + 3.5i  
number 3:  
5.5 + 5.5i  
  
-----  
Process exited after 17.97 seconds with return value 0  
Press any key to continue . . .
```

**P5 c:** Write the definition for a class called Distance that has data member feet as integer and inches as float. The class has the following member functions:

void set(int, float) to give value to object

void disp() to display distance in feet and inches

Distance add(Distance) to sum two distances & return distance

1. Write the definitions for each of the above member functions.
2. Write main function to create three Distance objects. Set the value in two objects and call add() to calculate sum and assign it in third object. Display all distances.

### Source Code:

```
#include <iostream>

#include <cmath>

using namespace std;

class Distance
{
    private:
        int feet;
        int inch;
        Distance friend add(Distance,Distance);
    public:
        void set ();
        void disp ();
};

void Distance:: set()
{
    cout << "Enter Value of feets : "; cin >> feet;
    cout << "Enter value of inches : "; cin >> inch;
```

```
}
```

```
void Distance:: disp()
```

```
{
```

```
    cout << endl << "\tFeets : " << feet;
```

```
    cout << endl << "\tInches: " << inch;
```

```
}
```

```
Distance add(Distance d1,Distance d2){
```

```
    Distance temp;
```

```
    int totdist = d2.inch+ d1.inch;
```

```
    temp.feet = totdist/12+ d2.feet + d1.feet;
```

```
    temp.inch = totdist%12;
```

```
    return temp;
```

```
}
```

```
int main()
```

```
{
```

```
    Distance d1;
```

```
    Distance d2;
```

```
    Distance d3;
```

```
    Distance d4;
```

```
    cout << "Enter Distance1 : " << endl;
```

```
d1.set();

cout << "Enter Distance2 : " << endl;
d2.set();

d3 = add(d1,d2);


cout << endl << "Distance1 : " ;
d1.disp();

cout << endl << "Distance2 : " ;
d2.disp();

cout << endl << "Distance3 : " ;
d3.disp();

cout << endl;
return 0;
}
```

Output:



```
Select D:\sem-5\oop_Lab\5c.exe
Enter Distance1 :
Enter Value of feets : 5
Enter value of inches : 11
Enter Distance2 :
Enter Value of feets : 4
Enter value of inches : 5

Distance1 :
    Feets : 5
    Inches: 11
Distance2 :
    Feets : 4
    Inches: 5
Distance3 :
    Feets : 10
    Inches: 4

-----
Process exited after 13.21 seconds with return value 0
Press any key to continue . . .
```

**P5 d.** Write the definition for a class called time that has hours and minutes as integer. The class has the following member functions:

void settime(int, int) to set the specified value in object

void showtime() to display time object

time sum(time &,time &) to sum two time object &  
return time

1. Write the definitions for each of the above member functions.



2. Write main function to create three time objects. Set the value in two objects and call sum() to calculate sum and assign it in third object. Display all time objects.

### Source Code:

```
#include<iostream>

using namespace std;

class Time{
private:
    int hrs,min;
    Time friend sum(Time&,Time&);
public:
    void setTime(int h,int m){
        hrs=h%24;min=m;
    }
    void showTime(){
        cout<<"hrs: "<<hrs<<"min: "<<min<<endl;
    }
};

Time sum(Time &t1, Time &t2){
    Time t;
    t.hrs = (t1.hrs + t2.hrs + (t1.min + t2.min)/60)%24;
    t.min = (t1.min + t2.min)%60;
```

```
        return t;
    }

int main(){
    Time t1,t2,t3;
    int hrs,min;
    cout<<"Enter time 1\nEnter hrs:\t";
    cin>>hrs;
    cout<<"Enter min:\t";
    cin>>min;
    t1.setTime(hrs,min);

    cout<<"Enter time 2\nEnter hrs:\t";
    cin>>hrs;
    cout<<"Enter min:\t";
    cin>>min;
    t2.setTime(hrs,min);


    t3 = sum(t1,t2);

    cout<<"Displaying times:\n";
    cout<<"Time 1 = \t";
    t1.showTime();

    cout<<"Time 2 = \t";
    t2.showTime();
```

```
        cout<<"Time 3 = \t";  
  
        t3.showTime();  
  
        return 0;  
    }
```

## Output:



```
D:\sem-5\oop_Lab\5d.exe  
Enter time 1  
Enter hrs:      3  
Enter min:      54  
Enter time 2  
Enter hrs:      6  
Enter min:      12  
Displaying times:  
Time 1 =        3hrs: 54min  
Time 2 =        6hrs: 12min  
Time 3 =       10hrs: 6min  
  
-----  
Process exited after 14.7 seconds with return value 0  
Press any key to continue . . .
```

**P6:** A book shop maintains the inventory of books that are being sold at the shop. The list includes details such as author, title, price, publisher and stock position. Whenever a customer wants a book, the sales person inputs the title and author and the system searches the list and displays whether it is available or not. If it is not, an appropriate message is displayed. If it is, then the system displays the book details and requests for the number of copies required. If the requested copies book details and requests for the number of copies required. If the requested copies are available, the total cost of the requested copies is displayed; otherwise the message "Required copies not in stock" is displayed. Design a system using a class called Books with suitable member functions and Constructors. Implement C++ program for the system.

### Source Code:

```
#include<iostream>

#include<string>

#include<iomanip>

#define M 5

using namespace std;

class Books{

    private:
```

```
    string author;
    string title;
    float price;
    string publisher;
    int stock_position;
    void friend add_to_array(Books &,Books,int);
    void friend bill(Books arr[],int);
    void friend search_by_author(Books arr[],string);
    void friend search_by_title(Books arr[],string);
    void friend show_all_books(Books arr[]);
public:
    Books(){}
    Books(string a, string t, float pr, string pub, int st){
        author = a;
        title=t;
        price=pr;
        publisher=pub;
        stock_position = st;
    }
    bool match(string,string);
    void details();
    float query(int);
    void update_price(float);
};

bool Books::match(string t, string auth){
    if(title==t && auth==author) return true;
```

```
        return false;
    }

void Books::details(){
    cout<<"Title: "<<title<<endl<<"Author: "<<author<<endl;
    cout<<"Publisher: "<<publisher<<endl<<"Price: "<<price<<endl;
}

float Books::query(int q){
    if(q<=stock_position){
        stock_position-=q;
        return q*price;
    }
    return 0.0;
}

void Books::update_price( float p){
    price=p;
}

void add_to_array(Books &a,Books b,int q){
    a=b;
    a.stock_position = q;
}

void bill(Books arr[],int n){
    float total=0;
```

```
        for(int i=0;i<n;i++){
            total+=arr[i].price * arr[i].stock_position;
            cout<<"Item: "<<i+1<<endl;
            cout<<"Title: "<<arr[i].title<<endl;
            cout<<"Author: "<<arr[i].author<<endl;
            cout<<"Price: "<<arr[i].price<<endl;
            cout<<"Quantity: "<<arr[i].stock_position<<endl;
        }
        cout<<"-----\nTotal: "<<total<<endl;
    }

void show_all_books(Books arr[]){

    cout<<" _____
    _____\n";

    cout<<" |Title          | Author          | Publisher          | Price    | Stock Position |\n";

    cout<<" _____
    _____\n";

    for(int i=0;i<M;i++){

        cout<<left<<" | "<<setw(18)<<arr[i].title<<" | "<<setw(17)<<arr[i].author<<" | "<<setw(18)<<arr[i].
        publisher<<" | "<<setw(10)<<arr[i].price<<" | "<<setw(14)<<arr[i].stock_position<<" |\n";

        cout<<" _____
        _____\n";

    }
}

void search_by_author(Books arr[],string a){
```

```
        cout<<"_____ \n";
        cout<<" |Title      | Publisher    | Price    | Stock Position | \n";
        cout<<"_____ \n";
        for(int i=0;i<M;i++){
            if(arr[i].author==a){

                cout<<left<<" | "<<setw(18)<<arr[i].title<<" | "<<setw(18)<<arr[i].publisher<<" | "<<setw(10)<<arr
                [i].price<<" | "<<setw(14)<<arr[i].stock_position<<" | \n";

                cout<<"_____ \n";
            }
        }
    }

    void search_by_title(Books arr[],string a){
        cout<<"_____ \n";
        cout<<" | Author      | Publisher    | Price    | Stock Position | \n";
        cout<<"_____ \n";
        for(int i=0;i<M;i++){
            if(arr[i].title==a){

                cout<<left<<" | "<<setw(18)<<arr[i].title<<" | "<<setw(18)<<arr[i].publisher<<" | "<<setw(10)<<arr
                [i].price<<" | "<<setw(14)<<arr[i].stock_position<<" | \n";

                cout<<"_____ \n";
            }
        }
    }
```



```
int main(){  
    Books arr[M],bought[M];  
    string author,title,publisher;  
    float price;  
    int stock,n=0;  
    bool flag;  
    cout<<"Enter Details of books in stock.\n";  
    for(int i=0;i<M;i++){  
        cout<<"Details of book "<<i+1<<endl;  
        cout<<"Enter Title\n";  
        cin.clear();  
        cin.sync();  
        getline(cin,title);  
        cout<<"Enter Author's name\n";  
        getline(cin,author);  
        cout<<"Enter Publisher\n";  
        getline(cin,publisher);  
        cout<<"Enter Price\n";  
        cin>>price;  
        cout<<"Enter Stock Position\n";  
        cin>>stock;  
        arr[i]=Books(author,title,price,publisher,stock);  
    }  
    while(1){  
        int choice=0;
```

```
cout<<"Enter 1 to buy Book\nEnter 2 to see all book details\nEnter 3 to update price of a  
book\nEnter 4 to search all books by an author\nEnter 5 to search books by Title\nEnter 0 to  
exit.\n";
```

```
cin>>choice;
```

```
switch(choice){
```

```
case 1:
```

```
cout<<"Enter the Title and Author of the book\n";
```

```
cin.clear();
```

```
cin.sync();
```

```
getline(cin,title);
```

```
getline(cin,author);
```

```
for(int i=0;i<M;i++){
```

```
flag = arr[i].match(title,author);
```

```
if(flag){
```

```
int q,amt;
```

```
cout<<"Congratulations!! We have the required book in stock.\n";
```

```
arr[i].details();
```

```
cout<<"Enter the Number of Books you want? \t";
```

```
cin>>q;
```

```
amt=arr[i].query(q);
```

```
if(amt!=0){
```

```
add_to_array(bought[n],arr[i],q);
```

```
cout<<"Cost of books: "<<amt<<endl;
```

```
n++;
```

```
}else{
```

```
cout<<"Stock Unavailable.\n";
```

```
flag=false;
```

```
}
```


```
        break;
    }
}

if(!flag) cout<<"We Do not have the book you require\n";
break;
case 2:
    show_all_books(arr);
    break;
case 3:
    cout<<"Enter the Title and Author of Book\n";
    cin.clear();
    cin.sync();
    getline(cin,title);
    getline(cin,author);
    flag=false;
    for(int i=0;i<M;i++){
        if(arr[i].match(title,author)){
            float price=0;
            flag=true;
            cout<<"Enter new price: ";
            cin>>price;
            arr[i].update_price(price);
            break;
        }
    }
}

if(!flag){
    cout<<"Book not found"<<endl;
```

```
    }  
    break;  
case 4:  
    cout<<"Enter Name of Author: ";  
    cin.clear();  
    cin.sync();  
    getline(cin,author);  
    search_by_author(arr,author);  
    break;  
case 5:  
    cout<<"Enter Title of Book: ";  
    cin.clear();  
    cin.sync();  
    getline(cin,title);  
    search_by_title(arr,title);  
    break;  
default:  
    cout<<"Enter valid input\n";  
    break;  
}  
if(choice==0) break;  
}  
bill(bought,n);  
return 0;  
}
```

**Output:**

 D:\sem-5\oop\_Lab\6.exe

Enter Details of books in stock.

Details of book 1

Enter Title

DS and Algo

Enter Author's name

Tanmay Vig

Enter Publisher

TV Corp

Enter Price

1000

Enter Stock Position

30

Details of book 2

Enter Title

Basics of ML

Enter Author's name

Tanmay Vig

Enter Publisher

bmp

Enter Price

550

Enter Stock Position

15

Details of book 3

Enter Title

DS and Algo

Enter Author's name

Chandu

Enter Publisher

Carl

Enter Price

300

Enter Stock Position

20

Details of book 4

Enter Title

Atomic Habits

Enter Author's name

James Clear

Enter Publisher

rh

Enter Price

500

Enter Stock Position

10

Details of book 5

Enter Title

Harry Potter

Enter Author's name

JK



D:\sem-5\oop\_Lab\6.exe

Enter Stock Position

10

Details of book 5

Enter Title

Harry Potter

Enter Author's name

JK

Enter Publisher

Rowling

Enter Price

250

Enter Stock Position

9

Enter 1 to buy Book

Enter 2 to see all book details

Enter 3 to update price of a book

Enter 4 to search all books by an author

Enter 5 to search books by Title

Enter 0 to exit.

2

Title	Author	Publisher	Price	Stock Position
DS and Algo	Tanmay Vig	TV Corp	1000	30
Basics of ML	Tanmay Vig	bmp	550	15
DS and Algo	Chandu	Carl	300	20
Atomic Habits	James Clear	rh	500	10
Harry Potter	JK	Rowling	250	9

Enter 1 to buy Book

Enter 2 to see all book details

Enter 3 to update price of a book

Enter 4 to search all books by an author

Enter 5 to search books by Title

Enter 0 to exit.

3

Enter the Title and Author of Book

Harry Potter

JK

Enter new price: 500

Enter 1 to buy Book

Enter 2 to see all book details

Enter 3 to update price of a book

Enter 4 to search all books by an author

Enter 5 to search books by Title

Enter 0 to exit.



D:\sem-5\oop\_Lab\6.exe

Enter the Title and Author of Book

Harry Potter

JK

Enter new price: 500

Enter 1 to buy Book

Enter 2 to see all book details

Enter 3 to update price of a book

Enter 4 to search all books by an author

Enter 5 to search books by Title

Enter 0 to exit.

2

Title	Author	Publisher	Price	Stock Position
DS and Algo	Tanmay Vig	TV Corp	1000	30
Basics of ML	Tanmay Vig	bmp	550	15
DS and Algo	Chandu	Carl	300	20
Atomic Habits	James Clear	rh	500	10
Harry Potter	JK	Rowling	500	9

Enter 1 to buy Book

Enter 2 to see all book details

Enter 3 to update price of a book

Enter 4 to search all books by an author

Enter 5 to search books by Title

Enter 0 to exit.

1

Enter the Title and Author of the book

DS and Algo

Tanmay Vig

Congratulations!! We have the required book in stock.

Title: DS and Algo

Author: Tanmay Vig

Publisher: TV Corp

Price: 1000

Enter the Number of Books you want? 10

Cost of books: 10000

Enter 1 to buy Book

Enter 2 to see all book details

Enter 3 to update price of a book

Enter 4 to search all books by an author

Enter 5 to search books by Title

Enter 0 to exit.

1

Enter the Title and Author of the book

Atomic Habits



D:\sem-5\oop\_Lab\6.exe

```
Enter the Title and Author of the book
Atomic Habits
James Clear
Congratulations!! We have the required book in stock.
Title: Atomic Habits
Author: James Clear
Publisher: rh
Price: 500
Enter the Number of Books you want?    9
Cost of books: 4500
Enter 1 to buy Book
Enter 2 to see all book details
Enter 3 to update price of a book
Enter 4 to search all books by an author
Enter 5 to search books by Title
Enter 0 to exit.
```

2

Title	Author	Publisher	Price	Stock Position
DS and Algo	Tanmay Vig	TV Corp	1000	20
Basics of ML	Tanmay Vig	bmp	550	15
DS and Algo	Chandu	Carl	300	20
Atomic Habits	James Clear	rh	500	1
Harry Potter	JK	Rowling	500	9

```
Enter 1 to buy Book
Enter 2 to see all book details
Enter 3 to update price of a book
Enter 4 to search all books by an author
Enter 5 to search books by Title
Enter 0 to exit.
```

4

Enter Name of Author: Tanmay Vig

Title	Publisher	Price	Stock Position
DS and Algo	TV Corp	1000	20
Basics of ML	bmp	550	15

```
Enter 1 to buy Book
Enter 2 to see all book details
Enter 3 to update price of a book
Enter 4 to search all books by an author
Enter 5 to search books by Title
```





D:\sem-5\oop\_Lab\6.exe

```
|DS and Algo      |TV Corp          |1000    |20      |
|Basics of ML     |bmp              |550     |15      |
+-----+-----+
Enter 1 to buy Book
Enter 2 to see all book details
Enter 3 to update price of a book
Enter 4 to search all books by an author
Enter 5 to search books by Title
Enter 0 to exit.
5
Enter Title of Book: DS and Algo
+-----+-----+
|Author          |Publisher        |Price    |Stock Position|
+-----+-----+
|DS and Algo     |TV Corp         |1000     |20            |
+-----+-----+
|DS and Algo     |Carl            |300      |20            |
+-----+-----+
Enter 1 to buy Book
Enter 2 to see all book details
Enter 3 to update price of a book
Enter 4 to search all books by an author
Enter 5 to search books by Title
Enter 0 to exit.
0
Enter valid input
Item: 1
Title: DS and Algo
Author: Tanmay Vig
Price: 1000
Quantity: 10
Item: 2
Title: Atomic Habits
Author: James Clear
Price: 500
Quantity: 9
-----
Total: 14500
-----
Process exited after 339.5 seconds with return value 0
Press any key to continue . . .
```

**P7:** Write a program in C++ to implement a class Employee using following concepts:

Pointer to Objects, Dynamic Memory Allocation using new and delete, Dynamic constructors, Destructors

**Source Code:**

```
#include<iostream>
#include<string>
#include<iomanip>
using namespace std;

class Employee{
    private:
        // int holidays;
        long long int id,salary;
        string name;
        int friend find(Employee *arr[], int n, string name,long long int id, bool mode_id, bool print)
;
        void friend display(Employee *arr[],int , bool );
        void friend sort(Employee *arr[],int n,int form);
        void friend del(Employee *arr[], int n,int pos);
    public:
        Employee(){}
        Employee(int i, string n,long long int s){
            id = i;
            name = n;
            salary = s;
```

```
        // holidays = h;
    }
};

int find(Employee *arr[],int n,string name,long long int id,bool mode_id, bool print){
    bool found=false;
    for(int i=0;i<n;i++){
        if((!mode_id && arr[i]->name==name) || (mode_id && arr[i]->id == id)){
            found = true;
            if(print)display(arr,i,found);
            return i;
            break;
        }
    }
    if(!found) cout<<"No related data found.\n";
    return -1;
}

void display(Employee *arr[],int n, bool single){
    cout<<"-----\n";
    cout<<"|id      |Name      |Salary  |\n";
    cout<<"-----\n";
    if(single){
        cout<<left<<"| "<<setw(10)<<(*arr[n]).id<<"| "<<setw(15)<<(*arr[n]).name<<"| "<<setw(10)
<<(*arr[n]).salary<<"|\n";
        cout<<"-----\n";
    }else{
```

```
        for(int i=0;i<n;i++){  
            cout<<left<<" | "<<setw(10)<<(*arr[i]).id<<" | "<<setw(15)<<(*arr[i]).name<<" | "<<setw(10)  
)<<(*arr[i]).salary<<" | \n";  
            cout<<"-----\n";  
        }  
    }  
}
```

```
void sort(Employee *arr[],int n,int form){  
    for(int i=0;i<n-1;i++){  
        for(int j=0;j<n-i-1;j++){  
            if((form == 1 && arr[j]->id>arr[j+1]->id) || (form==2 && arr[j]->name.compare(arr[j+1]-  
>name)>0) || (form==3 && arr[j]->salary>arr[j+1]->salary)){  
                Employee temp = *arr[j];  
                *arr[j] = *arr[j+1];  
                *arr[j+1] = temp;  
            }  
        }  
    }  
    display(arr,n,false);  
}
```

```
void del(Employee *arr[],int n,int pos){  
    for(int i=pos;i<n-1;i++){  
        Employee temp = *arr[i];  
        *arr[i] = *arr[i+1];
```

```
        *arr[i+1] = temp;
    }
    cout<<"Deleted\n";
}

int main(){
    int n=5;
    Employee *arr[100];
    cout<<"Enter the employee Details:\n";
    for(int i=0;i<n;i++){
        long long int id, salary; string name;
        cout<<"Enter the details of employee "<<(i+1)<<endl;
        cout<<"Enter id, name salary\n";
        cin>>id;
        cin.ignore();
        getline(cin,name);
        cin>>salary;
        arr[i] = new Employee(id,name,salary);
    }
    while(true){
        int choice=0,s=0;
        long long int id,salary;
        string name;
        cout<<"to display data of all employees Enter 1\nto display data of one employee Enter 2\nto sort data Enter 3\nto delete Enter 4\nto insert new employee Enter 5\nto exit Enter 0\n";
        cin>>choice;
        switch (choice)
```

```
{
case 2:
    cout<<"to search by name Enter 1\nto search by id Enter 2\n";
    cin>>s;
    if(s==1){
        cout<<"Enter name: ";
        cin.clear();
        cin.sync();
        getline(cin,name);
        find(arr,n,name,-1,false,true);
    }else{
        cout<<"Enter id: ";
        cin>>s;
        find(arr,n,"",s,true,true);
    }
    break;
case 1:
    display(arr,n,false);
    break;
case 3:
    cout<<"to sort by id Enter 1\nto sort by name Enter 2\nto sort by salary Enter 3\n";
    cin>>s;
    sort(arr,n,s);
    break;
case 4:
    cout<<"to find by id Enter 1\nto find by name Enter 2\n";
    cin>>s;
```

```
        if(s==1){
            cout<<"Enter id: ";cin>>s;
            s=find(arr,n,"",s,true,false);
        }else{
            cin.clear();
            cin.sync();
            getline(cin,name);
            s=find(arr,n,name,-1,false,false);
        }
        if(s!=-1){
            del(arr,n,s);
            n--;
        }
        break;
case 5:
    cout<<"Enter id, name, salary\n";
    cin>>id;
    cin.ignore();
    getline(cin,name);
    cin>>salary;
    arr[n++] = new Employee(id,name,salary);
    break;
default:
    choice =0;
    break;
}
if(!choice) break;
```

```
}  
  
return 0;  
  
}
```

## Output:

```
123112  
Enter the details of employee 5  
Enter id, name salary  
104  
faisal ahmed  
11121  
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
1
```

id	Name	Salary
100	tanmay vig	100000
101	almas	1020203
102	amir javed	120030
103	surya	123112

```
PS D:\sem-5\oop_Lab> cd "d:\sem-5\oop_Lab\" ; if ($?) { g++ 7.cpp -o 7 } ; if ($?) { .\7 }  
Enter the employee Details:  
Enter the details of employee 1  
Enter id, name salary  
100  
tanmay vig  
100000  
Enter the details of employee 2  
Enter id, name salary  
101  
almas  
1020203  
Enter the details of employee 3  
Enter id, name salary  
102  
amir javed  
120030  
Enter the details of employee 4  
Enter id, name salary  
103  
surya  
123112  
Enter the details of employee 5  
Enter id, name salary
```



```
-----  
|id      |Name      |Salary  |  
-----  
|100     |tanmay vig|100000  |  
-----  
|101     |almas     |1020203 |  
-----  
|102     |amir javed|120030  |  
-----  
|103     |surya     |123112  |  
-----  
|104     |faisal ahmed|11121  |  
-----
```

```
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
2  
to search by name Enter 1  
to search by id Enter 2  
1  
Enter name: almas
```

```
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
2  
to search by name Enter 1  
to search by id Enter 2  
1  
Enter name: almas
```

```
-----  
|id      |Name      |Salary  |  
-----  
|101     |almas     |1020203 |  
-----
```

```
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
2  
to search by name Enter 1
```

```
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
2  
to search by name Enter 1  
to search by id Enter 2  
103  
Enter id: 103
```

```
-----  
|id      |Name      |Salary  |  
-----  
|103     |surya     |123112  |  
-----
```

```
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
3  
to sort by id Enter 1  
to sort by name Enter 2  
to sort by salary Enter 3
```

```
to display data of one employee Enter 2
to sort data Enter 3
to delete Enter 4
to insert new employee Enter 5
to exit Enter 0
3
to sort by id Enter 1
to sort by name Enter 2
to sort by salary Enter 3
2
-----
|id      |Name      |Salary  |
-----
|101     |almas     |1020203|
-----
|102     |amir javed|120030  |
-----
|104     |faisal ahmed|11121  |
-----
|103     |surya     |123112  |
-----
|100     |tanmay vig |100000  |
-----
to display data of all employees Enter 1
```

```
to display data of all employees Enter 1
to display data of one employee Enter 2
to sort data Enter 3
to delete Enter 4
to insert new employee Enter 5
to exit Enter 0
3
to sort by id Enter 1
to sort by name Enter 2
to sort by salary Enter 3
3
-----
|id      |Name      |Salary  |
-----
|104     |faisal ahmed|11121  |
-----
|100     |tanmay vig |100000  |
-----
|102     |amir javed|120030  |
-----
|103     |surya     |123112  |
-----
|101     |almas     |1020203|
-----
```

```
to display data of all employees Enter 1
to display data of one employee Enter 2
to sort data Enter 3
to delete Enter 4
to insert new employee Enter 5
to exit Enter 0
3
to sort by id Enter 1
to sort by name Enter 2
to sort by salary Enter 3
1
-----
|id      |Name      |Salary  |
-----
|100     |tanmay vig |100000  |
-----
|101     |almas     |1020203|
-----
|102     |amir javed|120030  |
-----
|103     |surya     |123112  |
-----
|104     |faisal ahmed|11121  |
-----
```

```
-----  
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
4
```

```
to find by id Enter 1  
to find by name Enter 2  
1
```

Enter id: 103

Deleted

```
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
1
```

```
-----  
|id      |Name      |Salary  |  
-----  
|100     |tanmay vig|100000  |
```

```
-----  
|id      |Name      |Salary  |  
-----  
|100     |tanmay vig|100000  |  
-----  
|101     |almas     |1020203 |  
-----  
|102     |amir javed|120030  |  
-----  
|104     |faisal ahmed|11121  |  
-----
```

```
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
4
```

```
to find by id Enter 1  
to find by name Enter 2  
2
```

almas

Deleted

```
to display data of all employees Enter 1
```

```
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
1
```

```
-----  
|id      |Name      |Salary  |  
-----  
|100     |tanmay vig|100000  |  
-----  
|102     |amir javed|120030  |  
-----  
|104     |faisal ahmed|11121  |  
-----
```

```
to display data of all employees Enter 1  
to display data of one employee Enter 2  
to sort data Enter 3  
to delete Enter 4  
to insert new employee Enter 5  
to exit Enter 0  
5
```

```
Enter id, name, salary
```

```
5
Enter id, name, salary
105
almas
10020
to display data of all employees Enter 1
to display data of one employee Enter 2
to sort data Enter 3
to delete Enter 4
to insert new employee Enter 5
to exit Enter 0
1
-----
|id      |Name      |Salary   |
-----
|100     |tanmay vig|100000   |
-----
|102     |amir javed|120030   |
-----
|104     |faisal ahmed|11121   |
-----
|105     |almas     |10020    |
-----
to display data of all employees Enter 1
```

```
to delete Enter 4
to insert new employee Enter 5
to exit Enter 0
1
-----
|id      |Name      |Salary   |
-----
|100     |tanmay vig|100000   |
-----
|102     |amir javed|120030   |
-----
|104     |faisal ahmed|11121   |
-----
|105     |almas     |10020    |
-----
to display data of all employees Enter 1
to display data of one employee Enter 2
to sort data Enter 3
to delete Enter 4
to insert new employee Enter 5
to exit Enter 0
0
```

## **P8:** Use operator overloading to do complete the following functions:

```
Main Menu
    1.Equality
    2.String Copy
    3.Concat
    4.Show
    5.Reverse
    6.Palindrome
    7.Sub String
    8.Exit

Please Enter your choice:
```

### **Source Code:**

```
#include<iostream>

#include<cstring>

using namespace std;

class String{
    private:
        char str[30];
    public:
        void input();
        void show();
        void operator==(String s);
        void operator=(String s);
        void operator+(String s);
        void operator<<(String s);
        void operator>>(String s);
        void operator~();
```

```
        int operator/(String s);
    };

void String::input(){
    cout<<"Enter String: ";
    cin.clear();
    cin.sync();
    cin.getline(str,30);
}

void String::show(){
    for(int i=0;str[i]!='\0';i++){
        cout<<str[i];
    }
}

void String::operator==(String s){
    int i=0;
    bool equal=true;
    while(*(str+i]!='\0' && *(s.str + i]!='\0' )){
        if(*(str+i)!=*(s.str+i)){
            equal=false;
            break;
        }
        i++;
    }

    if(equal && *(str+i]!='\0' && *(s.str+i]!='\0') cout<<"Both String are equal\n";
```

```
        else cout<<"Strings are not equal\n";  
    }
```

```
void String::operator=(String s){  
    int i=0,len= sizeof(s.str)/sizeof(char);  
    for(int i=0;i<len;i++){  
        *(str+i)= *(s.str+i);  
        // str[i]=s.str[i];  
    }  
    *(str+len )='\0';  
}
```

```
void String::operator+(String s){  
    int len=0;  
    while(this->str[len]!='\0') len++;  
    for(int i=0;s.str[i]!='\0';++i,++len){  
        this->str[len] = s.str[i];  
    }  
    this->str[len] = '\0';  
}
```

```
void String::operator<<(String s){  
    cout<<"String:\t";  
    s.show();  
    cout<<"\n";  
}
```

```
void String::operator>>(String s){  
    cout<<"Reverse String:\t";  
    for(int i=strlen(s.str);i>=0;i--){  
        cout<<s.str[i];  
    }  
    cout<<"\n";  
}
```

```
void String::operator~(){  
    bool ans=true;  
    int len = strlen(str)-1;  
    for(int i=0;i<=len/2;i++){  
        // cout<<str[i]<<" "<<str[len-i]<<endl;  
        if(str[i]!=str[len-i]){  
            ans=false;  
            break;  
        }  
    }  
    if(ans) cout<<"Yes It is palindrome\n";  
    else cout<<"No it is not palindrome\n";  
}
```

```
int String::operator/(String s)  
{  
    int flag=0,k,i,j,len=strlen(str),len1=strlen(s.str)-1;  
    for(i=0;i<len;i++){  
        {
```



```
        if(str[i]==s.str[0])
        {
            if(str[i+len1]==s.str[len1])
            {
                for(j=i,k=0;j<i+len1+1,k<len1;j++,k++)
                {
                    if(str[j]==s.str[k])
                        flag=1;
                    else
                    {
                        flag=0;
                        break;
                    }
                }
            }
        }
    }
    if(flag==0)
        return 0; //not a substring

    return 1; //it is a substring
}

int main(){
    while(true){
        int choice=8,br=0,c;
        String a,b;
```

```
a.input();  
b.input();  
  
cout<<"Main Menu\n\t1. Equality\n\t2. String copy\n\t3. Concat\n\t4. Show\n\t5.  
Reverse\n\t6. Palindrome\n\t7. Sub String\n\t8. Exit\nPlease enter your choice\t";  
  
cin>>choice;  
  
switch (choice)  
{  
case 1:  
    a==b;  
    break;  
case 2:  
    b=a;  
    cout<<"The String is copied: ";  
    b.show();  
    cout<<endl;  
    break;  
case 3:  
    a+b;  
    a.show();  
    cout<<"\n";  
    break;  
case 4:  
    b<<a;  
    break;  
case 5:  
    b>>a;  
    break;
```

```
        case 6:
            ~a;
            break;
        case 7:
            c=a/b;
            if(c){
                cout<<"YES\n";
            }else cout<<"NO\n";
            break;
        case 8:
            br=1;
            break;
        default:
            cout<<"Enter Valid option\n";
            break;
    }
    if(br) break;
}
return 0;
}
```

**Output:**

```
PS D:\sem-5\oop_Lab> cd "d:\sem-5\oop_Lab\" ; if ($?) { g++ 8.cpp -o 8 } ; if ($?) { .\8 }
Enter String: level
Enter String: q
Main Menu
    1. Equality
    2. String copy
    3. Concat
    4. Show
    5. Reverse
    6. Palindrome
    7. Sub String
    8. Exit
Please enter your choice      6
Yes It is palindrome
Enter String: tanmay
Enter String: a
Main Menu
    1. Equality
    2. String copy
    3. Concat
    4. Show
    5. Reverse
    6. Palindrome
    7. Sub String
    8. Exit
Please enter your choice      6
No it is not palindrome
```

## **P9:** Write a program to implement a class Stack using Linked List.

### **Source code:**

```
#include <iostream>

using namespace std;

class Stak_Node {
private:
    int data;
    Stak_Node* next;
public:
    Stak_Node* newNode(int);
    void push(Stak_Node**, int);
    int pop(Stak_Node**);
    int isempty(Stak_Node*);
    int front(Stak_Node*);
    void print(Stak_Node*);
};

Stak_Node* Stak_Node::newNode(int data){
    Stak_Node* stackNode = new Stak_Node();
    stackNode->data = data;
    stackNode->next = NULL;
    return stackNode;
}
```

```
void Stak_Node::push(Stak_Node** root, int data){  
    Stak_Node* stackNode = newNode(data);  
    stackNode->next = *root;  
    *root = stackNode;  
    cout<<data<<" pushed to the stack";  
}
```

```
int Stak_Node::pop(Stak_Node** root){  
    if (isempty(*root))  
        return INT_MIN;  
  
    Stak_Node* temp = *root;  
    *root = (*root)->next;  
    int popped = temp->data;  
    return popped;  
}
```

```
int Stak_Node::isempty(Stak_Node* root){  
    return !root;  
}
```

```
int Stak_Node::front(Stak_Node* root){  
    if (isempty(root))  
        return INT_MIN;  
    return root->data;  
}
```

```
void Stak_Node::print(Stak_Node* root){
    cout<<"Elements present in stack are (top to bottom) : ";
    while(!isempty(root)) {
        cout<<front(root)<<"\t";
        pop(&root);
    }
}

int main(){
    Stak_Node* root = NULL;
    int choice,item;

    while(1){
        cout<<"\n\n1.To Push\n2.To Pop\n3.To Display the top element\n4.To Display all stack
elements\n5.To Quit\n\nEnter your choice : ";
        cin>>choice;
        switch(choice){
            case 1 :
                cout<<"\nEnter data for the stack element: ";
                cin>>item;
                root->push(&root, item);
                break;
            case 2:
                cout<<root->pop(&root)<<" is popped from stack\n";
                break;
            case 3:
```

```
        cout<<"\n"<<root->front(root)<<" is on the top\n"<<endl;
        break;
    case 4:
        root->print(root);
        break;
    case 5:
        exit(1);
    default:
        cout<<"\nINCORRECT INPUT\n";
    }
}

return 0;
}
```

Output:



D:\sem-5\oop\_Lab\9.exe

```
1.To Push
2.To Pop
3.To Display the top element
4.To Display all stack elements
5.To Quit

Enter your choice : 1

Enter data for the stack element: 1
1 pushed to the stack

1.To Push
2.To Pop
3.To Display the top element
4.To Display all stack elements
5.To Quit

Enter your choice : 1

Enter data for the stack element: 2
2 pushed to the stack

1.To Push
2.To Pop
3.To Display the top element
4.To Display all stack elements
5.To Quit

Enter your choice : 1

Enter data for the stack element: 3
3 pushed to the stack

1.To Push
2.To Pop
3.To Display the top element
4.To Display all stack elements
5.To Quit

Enter your choice : 1

Enter data for the stack element: 4
4 pushed to the stack

1.To Push
2.To Pop
3.To Display the top element
4.To Display all stack elements
```

```
D:\sem-5\oop_Lab\9.exe
5.To Quit

Enter your choice : 1

Enter data for the stack element: 4
4 pushed to the stack

1.To Push
2.To Pop
3.To Display the top element
4.To Display all stack elements
5.To Quit

Enter your choice : 3
4 is on the top

1.To Push
2.To Pop
3.To Display the top element
4.To Display all stack elements
5.To Quit

Enter your choice : 2
4 is popped from stack

1.To Push
2.To Pop
3.To Display the top element
4.To Display all stack elements
5.To Quit

Enter your choice : 4
Elements present in stack are (top to bottom) : 3      2      1

1.To Push
2.To Pop
3.To Display the top element
4.To Display all stack elements
5.To Quit

Enter your choice : 5

-----
Process exited after 36.85 seconds with return value 1
Press any key to continue . . . █
```

## **P10:** Implementation of Inheritance

### **Source Code**

```
#include <iostream>

#include <string>

using namespace std;

class Employee{
private:
    string name;
    string id;
    int salary;

public:
    Employee() {}
    Employee(string n, string i, int s){
        id=i;
        name=n;
        salary = s;
    }
    ~Employee(){
    }
    void getEmployee(){
        cout<<"Employee id: "<<id<<"\nEmployee Name: "<<name<<"\nEmployee salary:
"<<salary<<endl;
    }
};
```

```
class Scientist: protected Employee{
private:
    int num_publications;
    int num_awards;
    string *publications;
    string *awards;
public:
    Scientist() {}

    Scientist(int num_pub, string *pub, string *aw,int n_a, string name, string id, int
salary):Employee(name,id,salary){
        num_publications = num_pub;
        num_awards = n_a;
        publications = new string[num_publications];
        for(int i=0;i<num_publications;i++){
            publications[i] =pub[i];
        }
        awards = new string[n_a];
        for(int i=0;i<n_a;i++){
            awards[i] =aw[i];
        }
    }
    ~Scientist(){
        delete[] publications;
        delete[] awards;
    }
    void getScientist(){
```

```
        cout<<"\nScientist Details:\n";
        getEmployee();
        cout<<"\nTotal publications: "<<num_publications<<endl;
        cout<<"Publications:\n";
        for(int i=0;i<num_publications;i++){
            cout<<" "<<publications[i]<<endl;
        }
        cout<<"\nTotal Awards: "<<num_awards<<endl;
        cout<<"Awards:\n";
        for(int i=0;i<num_awards;i++){
            cout<<" "<<awards[i]<<endl;
        }cout<<"\n";
    }

};

class Manager : protected Employee{
private:
    string title;
    int yrs_of_exp;
    int teams;
public:
    Manager(){}
    Manager(string t, int yrs, int tm,string name, string id, int salary):Employee(name,id,salary){
        title=t;
        yrs_of_exp=yrs;
        teams = tm;
    }
};
```

```
    }  
    ~Manager(){  
    }  
    void getManager(){  
        cout<<"\nManager Details: \n";  
        getEmployee();  
        cout<<"Title as Manager: "<<title<<endl;  
        cout<<"Years of Experience: "<<yrs_of_exp<<endl;  
        cout<<"Teams Managed: "<<teams<<endl;  
    }  
};
```

```
class Laborer : protected Employee{  
private:  
    int overtime;  
    int wage_over;  
    int leaves;  
public:  
    Laborer(){}  
    Laborer(int o, int w_o, int l,string name, string id, int salary) :Employee(name,id,salary){  
        overtime = o;  
        wage_over = w_o;  
        leaves = l;  
    }  
    ~Laborer(){  
    }  
    void getLaborer(){
```

```
        cout<<"\nLabourer Details: \n"<<endl;
        getEmployee();
        cout<<"Overtime: "<<overtime<<endl;
        cout<<"Wage in overtime: "<<wage_over<<endl;
        cout<<"Total leaves: "<<leaves<<endl;
    }
};

int main(){

    int sci_num=0,man_num=0, lab_num=0;
    Scientist *arr_s[100];
    Manager *arr_m[100];
    Laborer *arr_l[100];

    while(true){
        int choice=0,c, yrs, teams;
        int salary;
        int n_p,n_a,n_o, wage, leaves;
        string name, id,title;

        cout<<"\nEnter:\n 1 to add Scientist\n 2 to add Manager\n 3 to add Laborer\n 4 to show
all Scientists\n 5 to show all Managers\n 6 to show all Laborer\n any num to exit\n";
        cin>>choice;
        switch(choice){
            case 1:
            {
                sci_num++;
```

```
cout<<"Enter Employee ID, Name and Salary\n";  
cin.clear();  
cin.sync();  
getline(cin, id);  
getline(cin, name);  
cin>>salary;  
cout<<"Enter number of publications\t";  
cin>>n_p;  
string *a_p = new string[n_p];  
cout<<"Enter publications name\n";  
for(int i=0;i<n_p;i++){  
    string s;  
    cin.clear();  
    cin.sync();  
    getline(cin, s);  
    a_p[i]=s;  
}  
cout<<"Enter number of awards\t";  
cin>>n_a;  
string *a_a = new string[n_a];  
cout<<"Enter awards name\n";  
for(int i=0;i<n_a;i++){  
    string s;  
    cin.clear();  
    cin.sync();  
    getline(cin, s);  
    a_a[i] = s;
```



```
    }  
    arr_s[sci_num-1] = new Scientist(n_p,a_p,a_a, n_a,name,id, salary);  
    break;  
}  
case 4:  
{  
    for(int i=0;i<sci_num;i++){  
        (*arr_s[i]).getScientist();  
    }  
    break;  
}  
case 2:  
{  
    man_num++;  
    cout<<"Enter Employee ID, Name and Salary\n";  
    cin.clear();  
    cin.sync();  
    getline(cin, id);  
    getline(cin, name);  
    cin>>salary;  
    cout<<"Choose any position:\n 1. General Manager\n 2. Assistant Manager\n 3.  
Production Manager\n";  
    cin>>c;  
    // cin.clear();  
    // cin.sync();  
    switch(c){  
        case 1:
```

```
        title = "General Manager";  
        break;  
    case 2:  
        title = "Assistant Manager";  
        break;  
    case 3:  
        title="Production Manager";  
        break;  
    default:  
        title="Unknown Manager";  
        break;  
    }  
    cout<<"Enter number of teams managed\t";  
    cin>>teams;  
    cout<<"Enter numbers of years of experience\t";  
    cin>>yrs;  
    arr_m[man_num-1] = new Manager(title,yrs,teams, name,id,salary);  
    break;  
}  
case 5:  
{  
    for(int i=0;i<man_num;i++){  
        (*arr_m[i]).getManager();  
    }  
    break;  
}  
case 3:
```

```
{
    lab_num++;
    cout<<"Enter Employee ID, Name and Salary\n";
    cin.clear();
    cin.sync();
    getline(cin, id);
    getline(cin, name);
    cin>>salary;
    cout<<"Enter overtime hours\t";
    cin>>n_o;
    cout<<"Enter wage in overtime\t";
    cin>>wage;
    cout<<"Enter number of leaves\t";
    cin>>leaves;
    arr_l[lab_num-1] = new Laborer(n_o,wage,leaves,name, id, salary);
    break;
}

case 6:
{
    for(int i=0;i<lab_num;i++){
        (*arr_l[i]).getLaborer();
    }
    break;
}

default:
{
    choice = 0;
```

Name: Tanmay Vig  
Roll No.: 19BCS061

OOPS Lab Practical File

```
        break;
    }
}
if(choice == 0) break;
}

return 0;
}
```

Output:

```
Enter:
 1 to add Scientist
 2 to add Manager
 3 to add Laborer
 4 to show all Scientists
 5 to show all Managers
 6 to show all Laborer
any num to exit
1
Enter Employee ID, Name and Salary
100
Mudit Malhotra
20000
Enter number of publications    1
Enter publications name
one
Enter number of awards  1
Enter awards name
alpha

Enter:
 1 to add Scientist
 2 to add Manager
 3 to add Laborer
 4 to show all Scientists
 5 to show all Managers
 6 to show all Laborer
any num to exit
1
Enter Employee ID, Name and Salary
101
Karan Kapoor
3000
Enter number of publications    0
Enter publications name
Enter number of awards  1
Enter awards name
theta

Enter:
 1 to add Scientist
 2 to add Manager
 3 to add Laborer
 4 to show all Scientists
 5 to show all Managers
 6 to show all Laborer
any num to exit
2
```

```
Enter:
1 to add Scientist
2 to add Manager
3 to add Laborer
4 to show all Scientists
5 to show all Managers
6 to show all Laborer
any num to exit
2
Enter Employee ID, Name and Salary
102
Tanmay Vig
1000000
Choose any position:
1. General Manager
2. Assistant Manager
3. Production Manager
1
Enter number of teams managed    8
Enter numbers of years of experience    5

Enter:
1 to add Scientist
2 to add Manager
3 to add Laborer
4 to show all Scientists
5 to show all Managers
6 to show all Laborer
any num to exit
6

Enter:
1 to add Scientist
2 to add Manager
3 to add Laborer
4 to show all Scientists
5 to show all Managers
6 to show all Laborer
any num to exit
3
Enter Employee ID, Name and Salary
103
Paras
10000
Enter overtime hours    6
Enter wage in overtime    100
Enter number of leaves    4
```

D:\sem-5\oop\_Lab\10.exe

```
10000
Enter overtime hours    6
Enter wage in overtime 100
Enter number of leaves  4

Enter:
 1 to add Scientist
 2 to add Manager
 3 to add Laborer
 4 to show all Scientists
 5 to show all Managers
 6 to show all Laborer
any num to exit
2
Enter Employee ID, Name and Salary
104
Manuj Monga
100000
Choose any position:
 1. General Manager
 2. Assistant Manager
 3. Production Manager
2
Enter number of teams managed    5
Enter numbers of years of experience    4

Enter:
 1 to add Scientist
 2 to add Manager
 3 to add Laborer
 4 to show all Scientists
 5 to show all Managers
 6 to show all Laborer
any num to exit
4

Scientist Details:
Employee id: 100
Employee Name: Mudit Malhotra
Employee salary: 20000

Total publications: 1
Publications:
one

Total Awards: 1
Awards:
alpha
```

D:\sem-5\oop\_Lab\10.exe

Total Awards: 1

Awards:

alpha

Scientist Details:

Employee id: 101

Employee Name: Karan Kapoor

Employee salary: 3000

Total publications: 0

Publications:

Total Awards: 1

Awards:

theta

Enter:

1 to add Scientist

2 to add Manager

3 to add Laborer

4 to show all Scientists

5 to show all Managers

6 to show all Laborer

any num to exit

5

Manager Details:

Employee id: 102

Employee Name: Tanmay Vig

Employee salary: 1000000

Title as Manager: General Manager

Years of Experience: 5

Teams Managed: 8

Manager Details:

Employee id: 104

Employee Name: Manuj Monga

Employee salary: 100000

Title as Manager: Assistant Manager

Years of Experience: 4

Teams Managed: 5

Enter:


1 to add Scientist

2 to add Manager

3 to add Laborer

4 to show all Scientists



 D:\sem-5\oop\_Lab\10.exe

Teams Managed: 8

Manager Details:

Employee id: 104

Employee Name: Manuj Monga

Employee salary: 100000

Title as Manager: Assistant Manager

Years of Experience: 4

Teams Managed: 5

Enter:

1 to add Scientist

2 to add Manager

3 to add Laborer

4 to show all Scientists

5 to show all Managers

6 to show all Laborer

any num to exit

6

Labourer Details:

Employee id: 103

Employee Name: Paras

Employee salary: 10000

Overtime: 6

Wage in overtime: 100

Total leaves: 4

Enter:

1 to add Scientist

2 to add Manager

3 to add Laborer

4 to show all Scientists

5 to show all Managers

6 to show all Laborer

any num to exit

0

-----  
Process exited after 224.7 seconds with return value 0

Press any key to continue . . .

**P11:** A company pays its employees on a weekly basis. The employees are of four types: Salaried employees are paid a fixed weekly salary regardless of the number of hours worked, hourly employees are paid by the hour and receive overtime pay (i.e., 1.5 times their hourly salary rate) for all hours worked in excess of 40 hours, commission employees are paid a percentage of their sales and base-salaried commission employees receive a base salary plus a percentage of their sales. For the current pay period, the company has decided to reward salaried commission employees by adding 10% to their base salaries. Write a c++ program that performs payroll calculations of the company polymorphically.

**Source Code:**

```
#include<iostream>

#include<string>

using namespace std;

class Employee {
    protected:
        string name;
        float salary;
    public:
        Employee(){ }
```

```
Employee(string n, float s){
    name=n;salary=s;
}
virtual void getDetail(){
    cout<<"\nEmployee Name: "<<name<<"\nSalary: "<<salary<<"\n\n";
}
virtual float getSalary(){
    return salary;
}
};

class SalariedEmployee : public Employee {
public:
    SalariedEmployee(string name, float salary): Employee(name, salary){ }
    void getDetail(){
        cout<<"\nEmployee Name: "<<name<<"\nType: "<<"Salaried\nSalary:
"<<salary<<"\n\n";
    }
};

class HourlyEmployee : public Employee
{
protected:
    int hours;
public:
    HourlyEmployee(string name, float salary, int hrs): Employee(name, salary){
        hours=hrs;
    }
};
```

```
    }

    float getsalary(){
        if(hours<=40) return salary*hours;
        else return salary*40 +1.5*salary*(hours-40);
    }

    void getDetail(){
        cout<<"\nEmployee Name: "<<name<<"\nType: "<<"Hourly\nSalary:
"<<getsalary()<<"\n\n";
    }
};

class CommissionEmployee : public Employee {
protected:
    float commission;
public:
    CommissionEmployee(string name,float salary,float c):Employee(name, salary){
        commission = c;
    }
    virtual float getSalary(){
        return salary*commission/100;
    }
    virtual void getDetail(){
        cout<<"\nEmployee Name: "<<name<<"\nType: Commissioned\nSalary:
"<<getSalary()<<"\n\n";
    }
};
```

```
class BasePlusCommissionEmployee : public CommissionEmployee{
    protected:
        float base_amount;
        float increment;
    public:
        BasePlusCommissionEmployee(string name, float salary, float base, float c, float
incr):CommissionEmployee(name, salary,c){
            base_amount = base;
            increment = incr;
        }
        float getSalary(){
            return base_amount + base_amount*increment/100 + salary*commission/100;
        }
        void getDetail(){
            cout<<"\nEmployee Name: "<<name<<"\nType: Commissioned\nSalary: "<<
getSalary()<<"\n\n";
        }
};

int main(){
    Employee* arr[100];
    int count=0;
    while(true){
        int choice = 0;

        cout<<"Enter:\n 1. to create a Salaried Employee\n 2. to create a Hourly Employee\n 3. to
create a Comission Employee\n 4. to create a Base Plus Commission Employee\n 5. to get
payroll of all employees\n any other number to exit\n";
```

```
cin>>choice;

string name;

float salary;

switch(choice){

    case 1:{

        count++;

        cout<<"Enter name: ";

        cin.clear();

        cin.sync();

        getline(cin,name);

        cout<<"Enter salary: ";

        cin>>salary;

        arr[count-1]=new SalariedEmployee(name, salary);

        cout<<"Employee Details:\n";

        arr[count-1]->getDetail();

        break;

    }

    case 2: {

        count++;

        int hrs;

        cout<<"Enter name: ";

        cin.clear();

        cin.sync();

        getline(cin,name);

        cout<<"Enter Hourly salary: ";

        cin>>salary;

        cout<<"Enter Hours worked: ";
```

```
        cin>>hrs;

        arr[count-1]=new HourlyEmployee(name, salary,hrs);

        cout<<"Employee Details:\n";

        arr[count-1]->getDetail();

        break;
    }

    case 3: {

        count++;

        float com;

        cout<<"Enter name: ";

        cin.clear();

        cin.sync();

        getline(cin,name);

        cout<<"Enter sales made: ";

        cin>>salary;

        cout<<"Enter commission: ";

        cin>>com;

        arr[count-1]=new CommissionEmployee(name, salary,com);

        cout<<"Employee Details:\n";

        arr[count-1]->getDetail();

        break;
    }

    case 4: {

        count++;

        float com, base;

        cout<<"Ente name: ";

        cin.clear();
```

```
        cin.sync();
        getline(cin,name);
        cout<<"Enter sales made: ";
        cin>>salary;
        cout<<"Enter commission: ";
        cin>>com;
        cout<<"Enter base salary: ";
        cin>>base;
        arr[count-1]=new BasePlusCommissionEmployee(name, salary,base, com, 10.0);
        cout<<"Employee Details:\n";
        arr[count-1]->getDetail();
        break;
    }
    case 5:{
        float sum=0;
        for(int i=0;i<count;i++){
            arr[i]->getDetail();
            sum+=arr[i]->getSalary();
        }
        cout<<"Total spenditure: "<<sum<<endl;
        break;
    }
    default:{
        choice=0;
        break;
    }
}
```



Name: Tanmay Vig  
Roll No.: 19BCS061

OOPS Lab Practical File

```
        if(choice==0) break;
    }

    return 0;
}
```

Output:

D:\sem-5\oop\_Lab\11.exe

Enter:

1. to create a Salaried Employee
2. to create a Hourly Employee
3. to create a Comission Employee
4. to create a Base Plus Commission Employee
5. to get payroll of all employees
- any other number to exit

1

Enter name: Tanmay Vig

Enter salary: 100000

Employee Details:

Employee Name: Tanmay Vig

Type: Salaried

Salary: 100000

Enter:

1. to create a Salaried Employee
2. to create a Hourly Employee
3. to create a Comission Employee
4. to create a Base Plus Commission Employee
5. to get payroll of all employees
- any other number to exit

2

Enter name: Mudit Malhotra

Enter Hourly salary: 4000

Enter Hours worked: 44

Employee Details:

Employee Name: Mudit Malhotra

Type: Hourly

Salary: 184000

Enter:

1. to create a Salaried Employee
2. to create a Hourly Employee
3. to create a Comission Employee
4. to create a Base Plus Commission Employee
5. to get payroll of all employees
- any other number to exit

3

Enter name: Mukul Monga

Enter sales made: 1000000


Enter commission: 20

Employee Details:

Employee Name: Mukul Monga

Type: Commissioned

Salary: 200000

 D:\sem-5\oop\_Lab\11.exe

```
Employee Name: Mukul Monga
Type: Commissioned
Salary: 200000
```

```
Enter:
```

1. to create a Salaried Employee
  2. to create a Hourly Employee
  3. to create a Commission Employee
  4. to create a Base Plus Commission Employee
  5. to get payroll of all employees
- any other number to exit

```
4
```

```
Enter name: Manuj Monga
Enter sales made: 200000
Enter commission: 25
Enter base salary: 10000
Employee Details:
```

```
Employee Name: Manuj Monga
Type: Commissioned
Salary: 61000
```

```
Enter:
```

1. to create a Salaried Employee
  2. to create a Hourly Employee
  3. to create a Commission Employee
  4. to create a Base Plus Commission Employee
  5. to get payroll of all employees
- any other number to exit


```
5
```

```
Employee Name: Tanmay Vig
Type: Salaried
Salary: 100000
```

```
Employee Name: Mudit Malhotra
Type: Hourly
Salary: 184000
```

```
Employee Name: Mukul Monga
Type: Commissioned
Salary: 200000
```

```
Employee Name: Manuj Monga
Type: Commissioned
```

 D:\sem-5\oop\_Lab\11.exe

```
2. to create a Hourly Employee
3. to create a Comission Employee
4. to create a Base Plus Commission Employee
5. to get payroll of all employees
any other number to exit
```

5

```
Employee Name: Tanmay Vig
Type: Salaried
Salary: 100000
```

```
Employee Name: Mudit Malhotra
Type: Hourly
Salary: 184000
```

```
Employee Name: Mukul Monga
Type: Commissioned
Salary: 200000
```

```
Employee Name: Manuj Monga
Type: Commissioned
Salary: 61000
```

```
Total spenditure: 365000
```

```
Enter:
```

```
1. to create a Salaried Employee
2. to create a Hourly Employee
3. to create a Comission Employee
4. to create a Base Plus Commission Employee
5. to get payroll of all employees
any other number to exit
```

8

```
-----
Process exited after 99.35 seconds with return value 0
Press any key to continue . . .
```

## **P12:** Templates-Write a program in C++ to implement a generic Stack.

### **Source code:**

```
#include<iostream>

#include<string>

#define SIZE 5

using namespace std;

template <class T>

class Stack{

    private:

        int top, capacity;

        T* arr;

    public:

        Stack(int size=SIZE);

        void push(T k);

        T pop();

        T peek();

        int size();

        bool isEmpty();

        bool isFull();
```

```
        ~Stack(){  
            delete[] arr;  
        }  
};  
  
template <class T>  
Stack<T>::Stack(int size){  
    arr = new T[size];  
    capacity = size;  
    top = -1;  
}  
  
template <class T>  
void Stack<T>::push(T k){  
    if(isFull()){  
        cout<<"Stack is Full!"<<endl;  
    }else{  
        cout<<"Pushing "<<k<<" to the stack\n";  
        arr[++top]=k;  
    }  
}  
  
template <class T>  
T Stack<T>::pop(){
```

```
    T top_ele;

    if(isEmpty()){

        cout<<"Stack is Empty!"<<endl;

    }else{

        top_ele = arr[top--];

        cout<<"removing "<<top_ele<<" from Stack\n";

    }

    return top_ele;

}
```

```
template<class T>

T Stack<T>::peek(){

    return arr[top];

}
```

```
template<class T>

int Stack<T>::size(){

    return top+1;

}
```

```
template<class T>

bool Stack<T>::isEmpty(){

    return top==-1;
```

```
}
```

```
template<class T>
```

```
bool Stack<T>::isFull(){
```

```
    return top==capacity-1;
```

```
}
```

```
int main(){
```

```
    Stack<string> st;
```

```
    st.pop();
```

```
    st.push("Hey");
```

```
    st.push("two");
```

```
    cout<<st.pop()<<endl;
```

```
    cout<<"size of stack: "<<st.size()<<endl;
```

```
    st.push("three");
```

```
    st.push("four");
```

```
    st.push("five");
```

```
    cout<<"size of stack: "<<st.size()<<endl;
```

```
    st.push("six");
```

```
    if(st.isFull()){
```

```
        cout<<"Stack is full\n";
```

```
    }
```

```
    st.push("seven");
```



```
        st.pop();  
  
    return 0;  
  
}
```

## Output:

```
Stack is Empty!  
Pushing Hey to the stack  
Pushing two to the stack  
removing two from Stack  
two  
size of stack: 1  
Pushing three to the stack  
Pushing four to the stack  
Pushing five to the stack  
size of stack: 4  
Pushing six to the stack  
Stack is full  
Stack is Full!  
removing six from Stack  
  
-----  
Process exited after 0.05603 seconds with return value 0  
Press any key to continue . . .
```

**P13:** Inheritance in Java: Implement a manager class that inherits from the Employee class in Java. Implement the relevant constructors also.

**Source Code:**

```
import java.util.*;

class Employee{

    int sNo;

    String name;

    long salary;

    public Employee(int sNo, String name, long salary) {

        this.sNo = sNo;

        this.name = name;

        this.salary = salary;

    }

}

class Manager extends Employee{

    String position;

    public Manager(int sNo, String name, long salary, String position){
```

```
        super(sNo,name,salary);

        this.position = position;
    }

    public void getData(){

        System.out.println("Emoplyee Details:\nSerial Number: "+ this.sNo+"\nName: "+
this.name+"\nPosition: "+ this.position + "\nSalary "+this.salary);

    }

}

public class inherit{

    public static void main(String[] args){

        Manager m = new Manager(100,"Tanmay Vig",1000000,"General Manager");

        m.getData();

    }

}
```

Output:

```
Employee Details:  
Serial Number: 100  
Name: Tanmay Vig  
Position: General Manager  
Salary 1000000  
PS D:\sem-5\oop_Lab>
```