

DIGITAL TDS METERS

MODEL NO. ALE - 885



Digital TDS Meters are reliable and accurate test instruments for measurement of TDS of aqueous solutions. They measure TDS in five ranges. The Resolution is 0.1 ppm respectively, in the lowest range. The cell constant is flashed on a digital display & can be adjusted. The instruments have the "Check" facility to calibrate the instrument.

These instruments are ideal for monitoring salt contents in water and soluble salts in soils. They are extremely useful instruments for agriculture and soil analysis labs, swimming pools, fertilizer plants, petroleum refineries, textile plants etc.



Features

- Rugged, reliable & easy to operate.
- Highly Stable & Accurate
- User friendly
- Cell Constant adjustable
- 3 ½ Digit LED
- Platinum DIP type measuring cell
- Resolution is 0.1 ppm respectively

Accessories

- TDS Cell
- Cell Stand
- Operation Manual
- Dust Cover

SPECIFICATION

★ Five Stages of Quality Checking Before Dispatch.

Parameter	Specification
Display	3 ½ Digit LED
Measurement	TDS
Range	0 To 200 ppm
	0 to 2000 ppm
	0 to 20.00 ppt (20,000 ppm)
	0 to 200.0 ppt (2,00,000 ppm)
	0 to 1000 ppt (10,00,000 ppm)
Resolution	0.1 ppm
Accuracy	±2% FS ±1 Digit
Temperature Compensation	Manual : 0° to 50°C
Cell Constant	Adjustable on Digital Display
Measuring Cell	Platinum DIP Type
Power	230V ±10% AC, 50 Hz
Dimensions	280x180x88 mm (L x B x H)
Weight	3kg

Note: Technical Specifications, Appearance & Model number are subject to change without prior notice.