



DIGITAL CONDUCTIVITY METER

MODEL NO. ALE - 874/875



DIGITAL CONDUCTIVITY METER

MODEL NO. ALE - 874/875

Digital Conductivity Meters are reliable and accurate test instruments for measurement of Electrical Conductivity (EC) of aqueous solutions. They measure Conductivity and TDS in five ranges. The resolution is 0.1 μ /cm and 0.1 ppm respectively, in the lowest range. The cell constant is flashed on a digital display and can be adjusted from the front panel. The instruments have the “check” facility to calibrate the instrument.



Conductivity Meters are ideal for monitoring salt contents in water and soluble salts in soils. They are extremely useful instruments for agriculture and soil analysis labs, swimming pools, fertilizer plants, petroleum refineries, textile plants etc.

Features

- Highly Stable & Accurate
- Cell Constant Adjustment Facility
- 3½ Digit Display
- Easy to operate & user friendly
- ATC Facility available in Model 875

Accessories

- Conductivity Cell
- Cell Stand
- Operation Manual
- Dust Cover

SPECIFICATION

★ Five Stages of Quality Checking Before Dispatch.

Model	ALE - 874	ALE - 875
Display	3½ digit LED	3½ digit LED
Range	0-200 μ S 0-2.0,20.0,200 & 0-1000mS	0-200 μ S 0-2.0,20.0,200 & 0-1000mS
Temperature Compensation	Manual 0-50°C	ATC 0-50°C
Cell Constant Adjustment	Adjustable	Adjustable
Conductivity Cell	Platinum DIP Type	Platinum DIP Type
Resolution	0.1 μ S	0.1 μ S
Accuracy	± 1% FS ±1Digit	± 1% FS ±1Digit
Power Supply	230V ±10% AC, 50 Hz	230V ±10% AC, 50 Hz
Dimension	280x180x88 (LxBxH)	280x180x88 (LxBxH)
Weight	3 kg	3 kg

Note: Technical Specifications, Appearance & Model number are subject to change without prior notice.