

MICROPROCESSOR SINGLE BEAM VISIBLE SPECTROPHOTOMETER MODEL NO. ALE-650



MICROPROCESSOR SINGLE BEAM VISIBLE SPECTROPHOTOMETER

MODEL NO. ALE-650

Spectrophotometer models are designed for reliable continuous operation. It is easy to use, thoroughly reliable and above all low cost.

Applications

- Medical/pharmaceutical
- Industry environmental Monitoring
- Commodity Inspection
- Food Inspection
- Agricultural Chemistry
- Teaching in Colleges & Universities
- Metallurgy
- Geology
- Machine Manufacturing
- Petrochemical Industries
- Water and Waste water Labs
- Food and Beverage Labs

Characteristics

- The Monochromator with a holographic flashing grating is used.
- It has the advantage of high wavelength precision, good monochromatic and low stray light.
- A sample compartment is equipped with 50 mm cell holder.
- Direct concentration read-out and concentration factor setting function.

Standard Configuration

- Main Instrument : 1 Unit
- Operational Manual : 1 No.
- Power cable : 1 No.
- Glass Cell 10 mm : 4 no.



SPECIFICATION

★ FIVE STAGES OF QUALITY CHECKING BEFORE DISPATCH.

Parameter	Specification
Optical System	C-T Single Beam, Grating 1200 lines/mm
Wavelength Range	320–1020 nm
Spectral Bandwidth	2 nm
Wavelength Interval	1 nm
Wavelength Accuracy	±2 nm
Wavelength Repeatability	≤1 nm
Photometric Accuracy	±1%T
Photometric Repeatability	0.5%T
Photometric Range	0 – 1.999A, 0 – 199.9%T
Stray Light	≤0.3%T @ 340 nm
Stability	±0.004A/h @ 500 nm
Display	4 LCD
Photometric Mode	T, A, C
Detector	Si Photodiode
Light Source	Tungsten lamp
Power Requirement	AC (220V/50Hz)
Dimensions (W × D × H)	450 × 520 × 320 mm
Weight	10 kg

Note: Technical Specifications, Appearance & Model number are subject to change without prior notice.