

DIGITAL VISCOMETER MODEL NO - ALE-1205





Digital viscometers operate on the principle of how a fluid's internal friction affects its flow behavior. They typically measure the time it takes for a given amount of fluid to flow through a specific geometry (usually a capillary tube or rotating spindle) under controlled conditions. The measurement is then used to calculate the fluid's viscosity.

Advantages of Digital Viscometers

- High precision and accuracy in viscosity measurement.
- Quick and repeatable measurements.
- Can be used for a wide range of fluid types, from low to high viscosities.
- Some models can measure at different shear rates, providing valuable information about the fluid's behavior under different conditions.

Applications

- Medical/pharmaceutical
- Industry Environmental Monitoring
- Commodity Inspection
- Food Inspection Agricultural Chemistry
- Teaching in Colleges & Universities
- Metallurgy, Petrochemical Industries
- Geology, Machine Manufacturing
- Water and Wastewater Labs
- Food and Beverage Labs

Features

- Stepping Motor means Accurate , reliable operation
- Direct readout of all measurement parameters
- Auto Range Showing
- Time Function for measurement
- Sound alarm at under 20% Torque
- Linear calibration
- Wide range power supply:100V-240V

MODEL NO.	ALE-1205
RPM	0.3, 0.6, 1.5, 3, 6, 12, 30, 60
Measuring Range(mPa.s)	20-2,000,000 m.pas
No of Standard Spindles	#1,#2,#3,#4 is standard configuration ,(#0 is for option)
Measurement Accuracy	±1.0% of range
Repeatability	±0.5%
Display	LCD
Temperature RTD Monitoring Sensor Probe	Yes
Output	RS 232 Interface
Power Supply	AC 220V/50Hz
Environment	Temperature 5-35 C Relative Humidity Not Larger Than 80%
Dimension	LxWxH (mm) 370 x 325 x 280
Weight	6.8 Kg

Note: Technical Specifications, Appearance & Model number are subject to change without prior notice.