

DIGITAL VISCOMETER MODEL NO - ALE-1210



DIGITAL VISCOMETER

MODEL NO –ALE-1210

A digital viscometer is a device used to measure the viscosity of a fluid, which is a measure of the fluid's resistance to flow. Viscosity is important in various industries, such as pharmaceuticals, food and beverages, cosmetics, and lubricants. Digital viscometers provide accurate and reliable measurements, often displaying results on a digital readout for easy interpretation.

Advantages of Digital Viscometers

- High precision and accuracy in viscosity measurement.
- Quick and repeatable measurements.
- Can be used for a wide range of fluid types, from low to high viscosities.
- Some models can measure at different shear rates, providing valuable information about the fluid's behavior under different conditions.

Applications

- Medical/pharmaceutical
- Industry Environmental Monitoring
- Commodity Inspection
- Food Inspection Agricultural Chemistry
- Teaching in Colleges & Universities
- Metallurgy, Petrochemical Industries
- Geology, Machine Manufacturing
- Water and Wastewater Labs
- Food and Beverage Labs

Features

- Stepping Motor means Accurate , reliable operation
- Direct readout of all measurement parameters
- Auto Range Showing
- Time Function for measurement
- Direct Viscosity reading and Temperature Display
- Choice of 3 Pin Power Cord
- Sound alarm at under 20% Torque
- Linear calibration
- Wide range power supply:100V-240V



MODEL NO.	ALE-1210
RPM	0.3, 0.6, 1.5, 3, 6, 12, 30, 60
Measuring Range(mPa.s)	10-2,000,000 m.pas
No of Standard Spindles	#1,#2,#3,#4 is standard configuration ,(#0 is for option)
Measurement Accuracy	±1.0% of range
Repeatability	±0.5%
Display	LCD
Temperature RTD Monitoring Sensor Probe	Yes
Output	RS 232 Interface
Power Supply	AC 220V/50Hz
Environment	Temperature 5-35 C Relative Humidity Not Larger Than 80%
Dimension	LxWxH (mm) 370 x 325 x 280
Weight	6.8 Kg

Note: Technical Specifications, Appearance & Model number are subject to change without prior notice.