



TOUCH SCREEN VISCOMETER MODEL NO - ALE-1220



TOUCH SCREEN VISCOMETER

MODEL NO –ALE-1220



Viscometer is an instrument used to measure the viscosity, or the resistance to flow, of a fluid. Viscometer is a precision instrument used to measure the viscosity of liquids across a broad range (10 to 2,000,000 mPa·s). It features a digital LCD display for direct viscosity and temperature readings, with an RTD sensor for accurate temperature monitoring. The device includes multiple speed settings (0.3–60 RPM) and supports four standard spindles for versatile applications. With an accuracy of $\pm 1\%$ and repeatability of $\pm 0.5\%$, it ensures reliable results. It is widely applied in industries like pharmaceuticals, paints, polymers, and food quality control

Advantages of Digital Viscometers

- High precision and accuracy in viscosity measurement.
- Quick and repeatable measurements.
- Can be used for a wide range of fluid types, from low to high viscosities.
- Some models can measure at different shear rates, providing valuable information about the fluid's behavior under different conditions.

Applications

- Medical/pharmaceutical
- Industry Environmental Monitoring
- Commodity Inspection
- Food Inspection Agricultural Chemistry
- Teaching in Colleges & Universities
- Metallurgy, Petrochemical Industries
- Geology, Machine Manufacturing
- Water and Wastewater Labs
- Food and Beverage Labs

Features

- Stepping Motor means Accurate , reliable operation
- Direct readout of all measurement parameters
- Auto Range Showing
- Time Function for measurement
- Direct Viscosity reading and Temperature Display
- Choice of 3 Pin Power Cord
- Sound alarm at under 20% Torque
- Linear calibration
- Wide range power supply:100V-240V

MODEL NO.	ALE-1220 (TOUCH SCREEN)
RPM	0.3, 0.6, 1.5, 3, 6, 12, 30, 60
Measuring Range(mPa.s)	10-2,000,000 m.pas
No of Standard Spindles	#1,#2,#3,#4 is standard configuration ,(#0 is for option)
Measurement Accuracy	$\pm 1.0\%$ of range
Repeatability	$\pm 0.5\%$
Display	LCD TOUCHSCREEN
Temperature RTD Monitoring Sensor Probe	Yes
Output	RS 232 Interface
Power Supply	AC 220V/50Hz
Environment	Temperature 5-35 C Relative Humidity Not Larger Than 80%
Dimension	LxWxH (mm) 400 x 350 x 360
Weight	10 Kg

Note: Technical Specifications, Appearance & Model number are subject to change without prior notice.