Geosteering Under Structural Uncertainty

Project: GeoSteering Structural Uncertainty
Synthetic replay run and simplified causal comparison. Training and portfolio tool; not validated for live operations.
Run ID: 1cb485ce-f24f-49ee-b75e-c877c6423f8c
Status: COMPLETE; revealed MD (ft): 7000.0
scenario_version: structural_dip_01-v1
seed: 123
code_revision: 9176b26a74972cdcaa8d0b41d1737bfa2c3fe8a3
dirty_working_tree: True
coordinate_reference: LOCAL_EAST_NORTH_FT; shared declared vertical datum; TVD positive down

Data summary and QC

Well	Curves	QC valid	Warnings
active_01	GR, RES	True	
offset_01	GR, RES	True	
offset_02	GR, RES	True	
offset_03	GR, RES	True	

Input provenance (SHA-256)


inputs/wells/0e86d9b2-5d0a-4e29-b076-440069245276/logs.parquet:
f125ec0bf7c247f09aca8dc52577693d7ba47f8d56d9412635bb9dc612127778
inputs/wells/0e86d9b2-5d0a-4e29-b076-440069245276/markers.json:
9013e130534da8976f160da6bafa675e9fa1311d9e6474f83b2d1e9ee1bf1c16
inputs/wells/0e86d9b2-5d0a-4e29-b076-440069245276/survey.parquet:
e0db2f667e87a5dd24d1a9649b94eb756d82bbbaa66fa71886da8f8ee2c35c27
inputs/wells/0e86d9b2-5d0a-4e29-b076-440069245276/trajectory.parquet:
7da6dc9e7bf5e94b5935573b74a444f2c5b8b5af008c519ab8ccb6864faefb7a
inputs/wells/0e86d9b2-5d0a-4e29-b076-440069245276/well.json:
f8d3b7603ae0bee715c47f2e4aac026bad44149b98ce94344de517bbabe652f0
inputs/wells/443627b6-d8e9-45da-8fe7-98f3ffce1eb6/logs.parquet:
e2973880c1d5f78d36e7d3679a9a54756943d7f0645a7cb26e282d2d216f19f3
inputs/wells/443627b6-d8e9-45da-8fe7-98f3ffce1eb6/markers.json:
cacc5e421907fa12c134ab2b50c4d4739c4d175560489ebdf2587c1199de017e
inputs/wells/443627b6-d8e9-45da-8fe7-98f3ffce1eb6/survey.parquet:
e0db2f667e87a5dd24d1a9649b94eb756d82bbbaa66fa71886da8f8ee2c35c27
inputs/wells/443627b6-d8e9-45da-8fe7-98f3ffce1eb6/trajectory.parquet:
336f3feba4cd8e4c7e2f0d8a44603a4e9ca79c1b7c10e62ac3f8b98345790686
inputs/wells/443627b6-d8e9-45da-8fe7-98f3ffce1eb6/well.json:
db58327001106750e96f279d408b4f93d3fd28ee42f49ea82520867d04184f2c
inputs/wells/eb087bdc-d83d-4778-a8f5-e8aa1f700a5d/logs.parquet:
7c0011908cffb95663cd5d7d9af5082bf5dd0496a4890bdd6224adc8e4b33e24
inputs/wells/eb087bdc-d83d-4778-a8f5-e8aa1f700a5d/markers.json:
34d11f1abea35b690a51dc8e44f2f793d79fdd57e4cb715200a8fd8cf6a887a8
inputs/wells/eb087bdc-d83d-4778-a8f5-e8aa1f700a5d/survey.parquet:
e0db2f667e87a5dd24d1a9649b94eb756d82bbbaa66fa71886da8f8ee2c35c27
inputs/wells/eb087bdc-d83d-4778-a8f5-e8aa1f700a5d/trajectory.parquet:
83eb9415f19fb7228a389f81e29900918bb89a01c402ba3bf87fffd5cc3070d9
inputs/wells/eb087bdc-d83d-4778-a8f5-e8aa1f700a5d/well.json:
ca8ddcb4a8ca90d661f03752f5454af23bf24b038db35a7071c6442aa14c1951
inputs/wells/ee8e11dc-092c-4c0e-91eb-a49ce1ffbb0e/logs.parquet:
602cc1af88d1af8d02fdc6fe2aa6ced71a4e657a8dc78fc78bab98c1d986a5ef
inputs/wells/ee8e11dc-092c-4c0e-91eb-a49ce1ffbb0e/markers.json:
4f53cda18c2baa0c0354bb5f9a3ecbe5ed12ab4d8e11ba873c2f11161202b945

inputs/wells/ee8e11dc-092c-4c0e-91eb-a49ce1ffbb0e/survey.parquet:
704f1be34125cf143bf05c880f3a8fe44b7614ebea936c6764fff8b222d3ab22
inputs/wells/ee8e11dc-092c-4c0e-91eb-a49ce1ffbb0e/trajectory.parquet:
e25744bb68e586f6e81d7cd29b19c0af4631d4e5128b90c366b95bf2a33f721d
inputs/wells/ee8e11dc-092c-4c0e-91eb-a49ce1ffbb0e/well.json:
a2cc403dc32b53b8a0dc42052b32524553d4c742a2e7e9baa95faaae2ac29dea

Correlation and markers


Offset formation picks constrain a regional estimate in shared along-track x and local TVD. Active observations and markers are limited to the saved revealed depth.


Well	Marker	MD (ft)
offset_01	Top_A	1438.16
offset_01	Mid_A	1450.16
offset_01	Base_A	1462.16
offset_02	Top_A	1440.66
offset_02	Mid_A	1452.66
offset_02	Base_A	1464.66
offset_03	Top_A	1442.66
offset_03	Mid_A	1454.66
offset_03	Base_A	1466.66



Pre-spud plan and DLS

Plan name: Browser QA Landing; Plan ID: 9165372a-7057-45c1-a2f6-6b968d30dfca
Max DLS constraint: 6.0 degrees/100 ft; exceedance count: 0







Steering decisions and KPI results

Replay recommendations do not change the recorded trajectory. Estimated metrics are frozen at each reveal using the cited interpretation, and exclude the build/landing interval.

Step	MD interval (ft)	Action	Evidence / interpretation version
1	2000-7000	HOLD	Acquired landing measurements recorded; HOLD reveals the full fixed lateral for completed-unevaluated report QA, not a policy-performance trial.; version d67b57ad-ab43-4672-ae12-ee161247205e


Step	Revealed MD (ft)	Estimated in-zone (%)	Mean center distance (ft)
1	7000	48.000	12.500





Final interpretation

Interpretation version: d67b57ad-ab43-4672-ae12-ee161247205e; rationale: Carry forward current interpretation: Acquired landing measurements recorded; HOLD reveals the full fixed lateral for completed-unevaluated report QA, not a policy-performance trial. Assumed uncertainty band (ft): 10.0. This scenario-assumed range is not a calibrated statistical confidence interval.



Independent evaluation

Run complete; independent withheld-truth evaluation has not been saved for the selected run. Its final truth-scored performance is unavailable.

Assumptions and limitations

Synthetic calibration: GR = 80 + 2*(TVD - target center) API, clipped to 20-160 API, with 0.6 API Gaussian noise. This deliberately signed layer signal is known to the synthetic operator; real gamma-ray inversion does not generally provide this information. Saturation cannot identify an exact center and is logged as unresolved evidence.
Scoring: estimated zones use exact piecewise-linear MD interval integration. Nonlinear withheld geology uses at most 1-ft intervals with boundary-crossing interpolation; reference refinement to 0.1 ft changes in-zone results by less than 0.001 percentage points. The final-point indicator is not an interval-length percentage.
Coordinates: feet; MD along the well, local TVD positive down, along-track x eastward. Minimum-curvature integration uses survey inclination and azimuth. Layer metrics are length weighted over the lateral interval with an explicit evaluated-length denominator.
The operator baseline uses offset picks only. Subsequent interpretations may use only revealed active measurements. Geological truth remains fixed and is isolated from live interpretations and recommendations.
Causal trials share geology, initial state, seed and trajectory constraints. HOLD/BUILD/DROP use a simplified bounded kinematic response. Report measured outcomes, including failure; no production drilling, sensor physics or operational safety claims are made.
Idealized 2D geology and synthetic GR/resistivity response; sparse offsets and assumed uncertainty. No real-time telemetry or WITSML support. Numerical summaries are reproducible; PDF timestamps and run identifiers can differ.