

Truth or DeGPTion: Evaluating Lie Detection Capabilities of GPT-3.5 through Fine-Tuning on Personal Opinions, Autobiographical Memories, and Intentions

Tanner Graves

tanneraaron.graves@studenti.unipd.it

ID: 2073559

Marco Uderzo

marco.uderzo@studenti.unipd.it

ID: 2096998

Francesco Vo

francesco.vo@studenti.unipd.it

ID: 2079413

Mehran Faraji

mehran.faraji@studenti.unipd.it

ID: 2071980

Claudio Palmeri

claudio.palmeri@studenti.unipd.it

ID: 2062671

Abstract

This paper aims at evaluating the capabilities of GPT3.5 in the task of Lie Detection. This is done through the fine-tuning of GPT-3.5 on three English-language datasets encompassing personal opinions, autobiographical memories, and future intentions. Fine-tuning of LLMs consists in adapting a pre-trained language model to a specific task by further training the model on task-specific data, thereby enhancing its ability to generate contextually relevant and coherent text in line with the desired task objectives. In our investigation, the objective is to discern and classify instances of truth or deception.

1. Introduction

Numerous academic publications consistently prove that the human capacity to discriminate between veracity and deception rests at chance-level proficiency. Consequently, an escalating interest has emerged in the application of machine learning (ML) methodologies, particularly those leveraging the Transformer architecture, to enhance the accuracy of truthfulness prediction for statements. The intrinsic aptitude of ML models for pattern recognition empowers them to discern subtle cues that elude human perception. This paper employs OpenAI’s GPT-3.5 Large Language Model (LLM) as the focal point, starting with an assessment of the base model’s performance. Subsequently, an in-depth examination will be conducted on a

fine-tuned GPT-3.5 model, specifically calibrated using the Personal Opinion Dataset (Deceptive Opinions), the Autobiographical Memories Dataset (Hippocorpus), and the Future Intentions Dataset, following “Scenario 3” from Loconte et al.[?]

1.1. Personal Opinion Dataset

The participants of this study were divided in 4 groups (HIT’s) and asked to provide either a truthful or a deceptive opinion on the following topics: Abortion, Cannabis Legalization, Euthanasia, Gay Marriage, Policy on Migrants. An extract from the table is shown below.

Domain	HIT1	HIT2	HIT3	HIT4
Abo	D	T	D	T
CL	T	T	D	D
Eut	T	D	T	D
GM	T	D	T	D
PoM	D	T	D	T

1.2. Autobiographical Memories Dataset

This dataset contains 6854 diary-like short stories about salient life events gathered in 3 steps from 2 groups of people (A,B). The study was conducted as following:

- Stage 1: Group A writes 15-25 sentence truthful stories with a 2-3 sentence summary and a timeframe

- Stage 2: Group B is tasked to write an imaginative story with the summary of group A as a prompt
- Stage 3: After 2 months group A is asked to retell the story starting with their summary as a prompt

At the end a questionnaire was posed.

	# stories	# sents	# words
recalled	2,779	17.8	308.9
imagined	2,756	17.5**	274.2**
retold	1,319	17.3*	296.8**
total	6,854		

1.3. Future Intentions Dataset

The study from which this dataset was collected was conducted as following.

All participants are divided into either the truthful or deceptive group. The former were asked to describe a non-work-related activity that would be doing in the next seven days answering the following questions:

- Q1: “Please describe your activity as specific as possible”
- Q2: “Which information can you give us to reassure us that you are telling the truth”

The latter were given 3 activities from the former group, asked which ones didn’t apply to them and get randomly assigned one of those. After, they were required to answer Q1, Q2 like the former group. At the end a questionnaire was posed.

Veracity	Activity	Statement given by participant
Truthful	Going swimming with my daughter	We go to a Waterbabies class every week, where my 16-month-old is learning to swim. We do lots of activities in the water, such as learning to blow bubbles, using floats to aid swimming, splashing and learning how to save themselves should they ever fall in. I find this activity important as I enjoy spending time with my daughter and swimming is an important life skill.
Deceptive	Going swimming with my daughter (assigned)	I will be taking my 8-year-old daughter swimming this Saturday. We’ll be going early in the morning, as it’s generally a lot quieter at that time, and my daughter is always up early watching cartoons anyway (5 am!). I’m trying to teach her how to swim in the deep end before she starts her new school in September as they have swimming lessons there twice a week.

In total, the Future Intentions Dataset is comprised of 1640 examples.

2. Methods

2.1. Dataset Preprocessing

In our methodology, we adopted ‘Scenario 3’ as outlined by Loconte et al. [?]. This scenario involved the aggregation of three distinct train and test sets from ‘Scenario 1,’ which encompassed statements related to opinions, memories, and future intentions. Subsequently, the model underwent a fine-tuning process using the aggregated sets. The objective of Scenario 3 was to assess the model’s overall capability to classify both truthful and deceptive statements across diverse contexts. Notably, in this scenario, the model was not fine-tuned to a specific type of statement; instead, it was evaluated on opinions, memories, and future intentions collectively, treating them as a randomly shuffled set of statements to be classified without bias towards any particular category.

The implementation of this process involved the merging of individual datasets into a unified one after cleaning and shuffling them. The resulting dataset was then partitioned into training, validation, and test sets. It is essential to highlight that we intentionally did not utilize the entire initial dataset. The decision to employ a smaller training dataset was aimed to computationally simplify the training process of the LLM, while still ensuring effective learning and generalization.

As a final step, the datasets were formatted into JSON to align with the expected input format of the OpenAI API, ensuring seamless integration with the API itself. For a detailed understanding of the implementation code, please refer to the Appendix section of this paper, where the Python code is provided for reference.

Regarding the fine-tuning process, the two different models were trained using a smaller and bigger dataset as follows:

- a subset of the original dataset (Train: 210 examples; Validation: 45 examples; Test: 45 examples).
- the full dataset (Train: 6765 examples; Validation: 1450 examples; Test: 1450 examples).

2.2. GPT-3.5 Fine-Tuning

In our study, we trained the model using the OpenAI API and evaluated its performance through testing and comparison with GPT-3.5. We also conducted additional experiments to understand how engineering the system prompt affects overall performance. One specific observation we made was regarding the baseline GPT-3.5’s tendency to provide verbose or indecisive answers. When faced with statements that could be easily classified as genuine or deceptive,

the model tended to provide detailed responses. However, in cases where it lacked sufficient information to confidently categorize a statement, the model often chose not to give a definitive answer.

To illustrate this behavior, consider the following example where the model, when uncertain about a statement, refrains from providing a clear classification. This aspect of the model’s behavior emphasizes its cautious approach when it perceives a lack of information, prioritizing accuracy over verbosity.

User: "Each and every abortion is essentially a tragedy. The potential mother will suffer unforeseen consequences. Society as a whole will be deprived of the potential it could have received from the new life."

Baseline GPT-3.5: "There is no objective truth to the statement as it expresses subjective opinions and beliefs about abortion. It cannot be definitively classified as 'True' or 'False'."

To mitigate this issue, we engineered a system prompt designed to discourage the verbose or indecisive behavior exhibited by the model. This tailored prompt also served the crucial purpose of clearly conveying the task requirements to the model. Each time the model encountered an example query, it was presented with this prompt to guide its understanding and response.

Recognizing the importance of efficiency in both training and query costs, we took care to ensure that the instructions in the prompt were concise. The goal was to minimize any unnecessary token overhead that could contribute to an increased cost associated with training and queries.

System Prompt to Fine-Tuned GPT-3.5:


"You are an expert capable of discerning truthful from deceptive opinions based on speech patterns. Definitively classify the following statement as 'True' or 'False', based on the likelihood the statement represents a genuinely held belief or a deception."

During the fine-tuning process, the model was incentivized to adopt the expected behavior and adhere to the

specified output format. This reinforcement mechanism ensured that the model learned and internalized the desired characteristics, minimizing the likelihood of verbose or indecisive responses.

The hyperparameters used for fine-tuning the models are declared in the table below, together with the fine-tuning training loss over the steps.

Model	Hyperparameter	Value
Model 1	Learning Rate	0.001
	Epochs	50
	Batch Size	32
Model 2	Learning Rate	0.01
	Epochs	30
	Batch Size	64



10-fold cross validation is a practice to be talked about carefully when it comes to experiments with cost constraints. Indeed, such validation becomes very expensive, since OpenAI API calls are charged with a fee. To keep costs low, we decided to perform 10-fold cross validation only on the smaller model. Of course though, we would expect a slightly better performance using the full model. (Also explain)

2.3. Stylometric Analysis

3. Results

3.1. Lie Detection Task Performance

Initially, our evaluation began with the assessment of the non-fine-tuned baseline GPT-3.5 model, resulting in an accuracy of 71.1%. Subsequently, we fine-tuned two distinct models: the 300-Model and the 1500-Model. Upon completion of the fine-tuning process, we subjected both models to the same evaluation methodology.

Surprisingly, both the 300-Model and the 1500-Model exhibited a remarkable improvement in performance, achieving an accuracy of 82.2%. This observation suggests that fine-tuning, irrespective of the size difference in the training datasets (300-Model and 1500-Model), yielded consistent and substantial enhancements in accuracy when it came to differentiating between truthful and deceptive statements, even across multiple contexts. Notably, this implies that the accuracy was not adversely affected by the variance in training set sizes, thereby demonstrating the effectiveness of fine-tuning even when working with smaller datasets, a practical consideration when aiming to minimize training costs. In fact, each OpenAI’s API call is subject to a small fee, which, considering the total amount of calls needed and its positive relationship with the dimension of the training set, can result in great training costs.

Furthermore, in adherence to established Machine Learning best practices, we conducted 10-fold cross-validation on the model in question. The cross-validation approach allows for a comprehensive assessment of the model’s generalization capabilities and robustness across diverse data samples.

The following table provides a detailed breakdown of the models’ performances, specifically focusing on accuracy:

Model	Dataset	Accuracy
300-Model	Personal Opinions	86.3%
	Autobiographical Memories	82.3%
	Future Intentions	69.7%
1500-Model	Personal Opinions	86.3%
	Autobiographical Memories	82.3%
	Future Intentions	69.7%
400-CV-Model	Personal Opinions	86.3%
	Autobiographical Memories	82.3%
	Future Intentions	69.7%

4. Discussion

In the present study, we delved into the effectiveness of Large Language Models, specifically GPT-3.5, in the task of lie detection. We considered both the baseline non-fine-tuned GPT-3.5 and two instances fine-tuned accordingly with "Scenario 3" from Loconte et al.[?]. Our primary objective was to investigate the model’s capacity to learn and generalize intrinsic linguistic representations of deception across a spectrum of contexts. This investigation was conducted using three distinct datasets, each comprising statements related to personal opinions, autobiographical experiences, and future intentions, thereby ensuring a comprehensive exploration of the model’s capabilities.

Despite the baseline GPT-3.5 model’s inherent capability to surpass human performance - where human capabilities

typically hover around chance level - the fine-tuning process further enhanced its performance by 11.1% in terms of accuracy. This substantial improvement underscores the efficacy of the model to capture the nuances of deceptive language use.

Upon closer examination of performance by class, a noteworthy finding emerged: the models exhibited suboptimal performance on the Future Intentions Dataset, achieving a modest 69.7% accuracy. This specific performance dip in one dataset had a discernible impact on the overall accuracy of the model.

Of particular interest was the observation that training GPT-3.5 on a smaller subset of data did not compromise results when compared to training on a larger set. This observation has significant implications, making the fine-tuning process more accessible in terms of training costs. This aspect becomes particularly critical when considering resource-intensive tasks such as 10-fold cross-validation, where the model’s robustness and generalization capabilities are rigorously assessed across diverse subsets of the data.

Future works on the topic can leverage the use of stylistic analysis to assess the problem even more thoroughly.

5. TO DO

To do list (+ things we might do that the Loconte paper mentions)

- RAW DATA FILE!!
- fine tuning explanation
- cross-validation on smaller model (so we are in the same setting as Loconte, even if it might cost a bit more)
- rerunning performance 3 times for statistical significance? (mean +/- 0.x)
- training hyperparams (see table)
- stylometric analysis if possible? (see supplemental file at end of loconte paper)
- better discussion, seems to lack a bit (if there are interesting considerations to be made)
- any idea why the Future Intentions Dataset has lower accuracy?

6. Code Availability

The datasets used and all the code used for this project is available at the following GitHub Repository.

References

- [1] Loconte et al. Verbal lie detection using large language models. 2023.

7. Appendix

We encourage to browse the Python Code directly from the GitHub repository at the following link.

7.1. Python Code: Scenario 3 Dataset Preprocessing

The following code preprocesses the dataset according to Scenario 3. The original Python Notebook is located at the following link in our GitHub Repository

```
import numpy as np
import pandas as pd
from sklearn.model_selection import train_test_split

dc = pd.read_csv('DecOp_data_EN_500.csv', sep=',', encoding='UTF-8')

d1 = []
for i in range(dc.shape[0]):
    row = dc.iloc[i]
    d1.append({'ID': row['ID'],
              'age': row['age'], 'gender': row['gender'],
              'sent': row['A'].replace('\n', " ") ,
              'labels': row['GT.A']})

    d1.append({'ID': row['ID'],
              'age': row['age'], 'gender': row['gender'],
              'sent': row['E'].replace('\n', " ") ,
              'labels': row['GT.E']})
    d1.append({'ID': row['ID'],
              'age': row['age'], 'gender': row['gender'],
              'sent': row['GM'].replace('\n', " ") ,
              'labels': row['GT.GM']})

    d1.append({'ID': row['ID'],
              'age': row['age'], 'gender': row['gender'],
              'sent': row['Pom'].replace('\n', " ") ,
              'labels': row['GT.Pom']})

    d1.append({'ID': row['ID'],
              'age': row['age'], 'gender': row['gender'],
              'sent': row['CL'].replace('\n', " ") ,
              'labels': row['GT.CL']})

decop = pd.DataFrame.from_records(d1)

decop = decop[['ID', 'sent', 'labels']]
decop['type'] = 'A'

decop

hc = pd.read_csv('hcV3-stories.csv', sep=',', encoding='UTF-8')

mem = hc[hc['memType']!='retold']
mem = mem.dropna(subset=['story', 'memType'])
mem = mem[['story', 'memType']]
mem['memType'][mem['memType']=='recalled'] = 'T'
```

```

mem['memType'][mem['memType']=='imagined'] = 'F'
mem = mem.rename(columns={'story': 'sent', 'memType': 'labels'})
mem['type'] = 'B'

mem

intent = pd.read_csv('sign_events_data_statements.csv', encoding="UTF-8")

intent.loc[intent['outcome_class']=='t', 'outcome_class'] = 'T'
intent.loc[intent['outcome_class']=='d', 'outcome_class'] = 'F'
intent['q1'] = intent['q1'].apply(lambda x: x.replace('\n', ''))
intent = intent.rename(columns={'q1': 'sent', 'outcome_class': 'labels'})
intent = intent[['sent', 'labels']]
intent['type'] = 'C'

intent

k = 300
seed = 42

'''
shuffled_df = decop.sample(frac=0.1, random_state=seed).copy()
sample_decop = shuffled_df.iloc[:k,].copy()
sample_decop.drop('ID', axis=1, inplace=True)
sample_decop

data = pd.concat([sample_decop, mem.iloc[:k,].copy(), intent.iloc[:k,].copy()],
                  ignore_index=True)
'''

decop.drop('ID', axis=1, inplace=True)

data = pd.concat([decop, mem, intent], ignore_index=True)
data_shuffle = data.sample(frac=1, random_state=seed+27).reset_index(drop=True)
data_shuffle['labels'] = data_shuffle['labels'].map({'T': 1, 'F': 0})
data_shuffle.rename(columns={'sent': 'text', 'labels': 'label', 'type': 'set'},
                    inplace=True)

data_shuffle = data_shuffle.iloc[:k,]

train_data, temp_data = train_test_split(data_shuffle, test_size=0.3, random_state=42)
val_data, test_data = train_test_split(temp_data, test_size=0.5, random_state=42)

train_data.to_json(f'train_data_{k}.json', orient='records', lines=True)
val_data.to_json(f'val_data_{k}.json', orient='records', lines=True)
test_data.to_json(f'test_data_{k}_class.json', orient='records', lines=True)

data_shuffle.shape

train_data.shape

```

7.2. Python Code: GPT-3 Fine-Tuning

The following code fine-tunes GPT-3 using the official OpenAI APIs. The original Python Notebook is located at the following link in our GitHub Repository

```
import os
from openai import OpenAI
import pandas as pd
import json

key = os.environ.get("OPENAI_API_KEY")
client=OpenAI(api_key=key)

import json

def sanitize_to_utf8(input_str):
    """
    Sanitizes a string field to UTF-8.
    """
    return input_str.encode('utf-8', 'replace').decode('utf-8')

def process_jsonl_file(input_jsonl_path, output_jsonl_path):
    """
    Processes a JSONL file line by line, sanitizes each line to UTF-8,
    and saves it to a new JSONL file.
    """
    with open(input_jsonl_path, 'r', encoding='utf-8') as input_file, \
        open(output_jsonl_path, 'w', encoding='utf-8') as output_file:

        for line in input_file:
            # Parse JSON line
            json_obj = json.loads(line)

            # Sanitize data
            sanitized_json_obj = {key: sanitize_to_utf8(value) if isinstance(value, str)
                                  else value for key, value in json_obj.items()}

            # Write sanitized JSON object to new JSONL file
            output_file.write(json.dumps(sanitized_json_obj) + '\n')

    """Generating intermediate 1500 example sets.

    TODO: Preserve what dataset examples come from so we can breakdown performance by dataset.
    """

    # Paths to your files
    input_jsonl_path = 'train_data_full.json'
    output_jsonl_path = 'output.jsonl'

    # Process the JSONL file
    process_jsonl_file(input_jsonl_path, output_jsonl_path)

    sys_prompt = "You are an expert capable of discerning truthful from deceptive opinions
                  based on speech patterns."
```



```

def gen_finetune(input, output, test=False):
    with open(input, 'r', encoding='utf-8') as data_in, \
        open(output, 'w') as gpt_out:
        for i, line in enumerate(data_in):
            user_prompt = json.loads(line)['text']
            sys_reply = "True" if json.loads(line)["label"] == 1 else "False"
            if not test:
                payload = {"messages": [{"role": "system", "content": sys_prompt},
                                         {"role": "user", "content": user_prompt}, {"role": "assistant",
                                                                 "content": sys_reply}]}
            else: # exclude response from test set
                payload = {"messages": [{"role": "system", "content": sys_prompt},
                                         {"role": "user", "content": user_prompt}]}
            gpt_out.write(json.dumps(payload) + '\n')

```

```

gen_finetune('train_data_300.json', 'train300_gpt.jsonl')
gen_finetune('val_data_300.json', 'val300_gpt.jsonl')

```

```

gen_finetune('train_data_1500.json', 'train1500_gpt.jsonl')
gen_finetune('val_data_1500.json', 'val1500_gpt.jsonl')

```

```

gen_finetune('train_data_full.json', 'train_full_gpt.jsonl')
gen_finetune('val_data_full.json', 'val_full_gpt.jsonl')

```

```

"""Example of querying model for classification.
Example on model trained on 300 example set.
"""

```

test_lie = "One morning three months ago I was in a hurry and tripped on the steps while running to take a shower before work. I ended up fracturing 4 metatarsal bones that required two surgeries to fix. I was really having a hard time not being able to walk whenever I wanted to. I really had such a bad attitude at the beginning because I was so used to being independent. Now that I have recovered I have a new appreciation for my ability to walk. I feel like the whole time I couldn't walk I was thinking about how much I took that ability for granted. But now I choose to walk more than I ever had before. When I walk the dogs I go further out of my way just to enjoy the ability to do it. I am completely recovered and I am going to take this as a lesson learned. Nothing is more important than my personal health. I need to make sure that even if I am running late, I need to take my time and be careful. Instead of making it to work on time, I ended up missing weeks of work. Now all I do at work is try and catch up with everything I missed. It was really nice that people at work came and visited me at the hospital. I really appreciated all the flowers and candy and food that was delivered. I think that this showed me how loved I truly am."

test_truth = "Each and every abortion is essentially a tragedy. The potential mother will suffer unforeseen consequences. Society as a whole will be deprived of the potential it could have received from the new life."

```

response = client.chat.completions.create(
    model="ft:gpt-3.5-turbo-0613:personal::8S542QSs",
    messages=[

```

```

        {"role": "system", "content": sys_prompt},
        {"role": "user", "content": test_lie},
        {"role": "user", "content": test_truth},
    ]
)
response.choices[0].message.content

mdls = {
    '300': "ft:gpt-3.5-turbo-0613:personal::8S542QSs",
    '3.5': "gpt-3.5-turbo",
    '1500': "ft:gpt-3.5-turbo-0613:personal::8TAkdwiX"
}

def predict(text, model, sys_prompt):
    response = client.chat.completions.create(
        model=model,
        messages=[
            {"role": "system", "content": sys_prompt},
            {"role": "user", "content": text}
        ]
    )
    return response.choices[0].message.content

test_truth

test_lie

def eval(test_file, mdl, return_df = False, sys_prompt=sys_prompt, by_class=False):
    msgs = []
    preds = []
    trues = []
    replies = []
    set = []
    with open(test_file, 'r') as f:
        for ex in f:
            ex = json.loads(ex)
            msg = ex['text']
            #pred = predict(msg, mdl) == 'True' #'True' if predict(msg) else 'False'
            reply = predict(msg, mdl, sys_prompt) #for debug
            pred = reply == 'True'
            true = ex['label'] == 1
            msgs.append(msg)
            preds.append(pred)
            trues.append(true)
            replies.append(reply) # debug
            if by_class:
                set.append(ex['set'])
    if by_class:
        test_df = pd.DataFrame.from_dict({'msg': msgs, 'reply': replies,
                                          'preds': preds, 'target': trues, 'set': set})
    else:
        test_df = pd.DataFrame.from_dict({'msg': msgs, 'reply': replies,
                                          'preds': preds, 'target': trues})

```

```

    acc = (test_df['preds'] == test_df['target']).mean()
    if return_df:
        return (test_df, acc)
    else:
        return acc

test_truth

sys_prompt_base = sys_prompt + ' Definitively classify the following statement
                                as \'True\' or \'False\', based on the likelihood the statement
                                represents a genuinely held beleif or a deception.'
#base_df, base_acc = predict('test_data_300.json', mdls['3.5'])
predict(test_truth, mdls['300'], sys_prompt=sys_prompt)

test300_df, test300_acc = eval('test_data_300.json', mdls['300'], True,
                                sys_prompt=sys_prompt)

print(test300_acc)
test300_df

test300_acc

test35_df, test35_acc = eval('test_data_300.json', mdls['3.5'], True,
                                sys_prompt=sys_prompt_base)

print(test35_acc)
test35_df

len(test1500_df)

# Takes a lot of time, cost = $1
#test1500_df, test1500_acc = eval('test_data_1500.json',mdls['1500'],True,
                                sys_prompt=sys_prompt)

print(test1500_acc)
test1500_df

test1500_df.to_csv('results1500.csv')

"""Model / Dataset Bias analysis:"""

print('Model truth classification rate: ')
print(test300_df['preds'].mean())
print('Dataset truthful statement rate: ')
print(test300_df['true'].mean())

"""Model performance by dataset"""

sys_prompt

class_df, class_acc = eval('test_data_1500.json', mdl=mdls['1500'],
                            sys_prompt=sys_prompt, return_df=True, by_class=True)

class_df['correct'] = class_df['preds'] == class_df['target']
class_df.groupby('set')['correct'].mean()

```

```
class_df.to_csv('results_class.csv')
```