

# Lecture Notes:

## Python Data Science Libraries

### NumPy Arrays

#### Key Definitions & Concepts

**ndarray:** A multi-dimensional array object with homogeneous data type, the core of NumPy.

**Axis:** Indicates the dimension along which an operation is applied. For 2D arrays:

- `axis=0`: down columns
- `axis=1`: across rows

**Vectorised Operations:** Operations applied directly to entire arrays without the need for explicit loops. These are optimised for performance and are a key feature of NumPy.

**Universal Functions (ufuncs):** Element-wise operations that are vectorised across arrays — e.g., `np.exp()`, `np.sqrt()`

**Broadcasting:** Allows arrays of different shapes to be combined in arithmetic operations without explicit looping.

**Copy vs View:** Slices often return views (not copies), meaning modifying the slice may alter the original array.

#### Core Ideas & Theoretical Intuition

- NumPy leverages **vectorisation** and **memory-efficient storage** to outperform Python lists in numerical tasks.
- Think of **broadcasting** as an implicit replication mechanism. NumPy aligns shapes without needing loops or `.repeat()`.
- Reshaping and transposition are **non-destructive operations** that offer powerful ways to prepare arrays for computation.

- Images and tabular data can be treated as **2D or 3D tensors**, making NumPy the go-to tool for low-level data prep.

## Mathematical Foundation

Let:

$$A = \begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix}, \quad B = \begin{bmatrix} 10 & 20 \end{bmatrix}$$

- **Broadcasted Addition:**

$$A + B = \begin{bmatrix} 1 + 10 & 2 + 20 \\ 3 + 10 & 4 + 20 \end{bmatrix} = \begin{bmatrix} 11 & 22 \\ 13 & 24 \end{bmatrix}$$

- **Dot Product:**

$$\text{If } x = [1, 2], \quad y = [3, 4], \quad \text{then } x \cdot y = 1 * 3 + 2 * 4 = 11$$

## Implementation

### Array Creation

Python

```
np.array([1, 2, 3])           # From list
np.zeros((2, 3))              # 2x3 zeros
np.ones((3,))                 # 1D ones
np.arange(0, 10, 2)           # [0, 2, 4, 6, 8]
np.linspace(0, 1, 5)          # [0. , 0.25, ..., 1.]
np.eye(3)                     # 3x3 identity matrix
```

## Indexing and Slicing

Python

```
a = np.array([[10, 20, 30], [40, 50, 60]])  
  
a[1, 2]          # 60  
  
a[:, 1]          # [20, 50]  
  
a[0:2, 0:2]      # subarray  
  
a[-1, :]         # last row
```

## Reshaping & Flattening

Python

```
a = np.arange(12)  
  
a.reshape(3, 4)      # new shape  
  
a.flatten()          # copy as 1D  
  
a.ravel()            # view as 1D
```

## Aggregations

Python

```
a = np.array([[1, 2], [3, 4]])  
  
a.sum(), a.mean(), a.std()  
  
a.sum(axis=0)         # column-wise  
  
a.max(axis=1)         # row-wise
```

## Array Manipulations

**np.append()**: Add elements to an array

Adds values to the end along the specified axis or flattens if **axis=None**

Python

```
a = np.array([[1, 2], [3, 4]])

np.append(a, [[5, 6]], axis=0) # Append row → shape (3, 2)

np.append(a, [[7], [8]], axis=1) # Append column → shape (2, 3)
```

Returns a **new array**, and the original is not modified.

**np.delete()**: Remove elements along an axis

Removes rows/columns by index

Python

```
a = np.array([[1, 2, 3], [4, 5, 6]])

# Remove 2nd row → shape (1, 3)

np.delete(a, 1, axis=0)

# Remove 1st and 3rd columns → shape (2, 1)

np.delete(a, [0, 2], axis=1)
```

Like **append**, it returns a **copy**, not in-place modification.

**.T** or **np.transpose()**: Transpose array dimensions

Python

```
a = np.array([[1, 2], [3, 4]])  
  
a.T                # [[1, 3], [2, 4]]  
  
np.transpose(a)    # Same as a.T for 2D
```

For 3D+, use the **axes** argument:

Python

```
a = np.ones((2, 3, 4))  
  
np.transpose(a, (1, 0, 2)) # Rearranges axes
```

**np.concatenate()**: Join arrays along an axis

Concatenates arrays with compatible dimensions

Python

```
a = np.array([[1, 2], [3, 4]])  
  
b = np.array([[5, 6]])  
  
np.concatenate((a, b), axis=0) # Vertical → shape (3, 2)  
  
np.concatenate((a, a), axis=1) # Horizontal → shape (2, 4)
```

Dimensions must **match on all axes except the one concatenated**.

## Axis Swapping

Python

```
a = np.array([[1, 2], [3, 4]])

a.T                                # transpose: [[1, 3], [2, 4]]

a.swapaxes(0, 1)                  # swap dimensions
```

## Stacking & Splitting

Python

```
a = np.array([1, 2, 3])
b = np.array([4, 5, 6])

np.stack((a, b))                  # shape: (2, 3)
np.hstack((a, b))                # shape: (6,)
np.vstack((a, b))                # shape: (2, 3)

c = np.arange(9).reshape(3, 3)
np.hsplit(c, 3)                  # three column arrays
```

## Element-wise Operations (Broadcasting)

Python

```
a = np.array([1, 2, 3])

a + 10                            # [11, 12, 13]

a * 2                             # [2, 4, 6]

a ** 2                           # [1, 4, 9]

np.exp(a)                        # [2.71, 7.39, 20.09]
```

## Logical Operations & Boolean Indexing

Python

```
a = np.array([1, 2, 3, 4, 5])  
a[a > 3] # [4, 5]  
np.where(a % 2 == 0, 0, 1) # Replace even with 0
```

## Image Manipulation

Python

```
from PIL import Image  
img = Image.open("image.jpg").convert("L")  
arr = np.array(img)  
  
# Invert grayscale  
inverted = 255 - arr  
  
# Brighten image  
bright = np.clip(arr + 30, 0, 255)
```

## Real-world Use Cases

- **Data Preprocessing:** Clean and transform numeric datasets before modelling
- **Scientific Computation:** Perform fast simulations, e.g., particle systems, numerical integration
- **Image Analysis:** Pixel-wise filters, transformations, masks
- **Feature Engineering:** Compute means, deltas, differences, or normalisations across axes

## Pitfalls and Misconceptions

- **Shape mismatch in broadcasting:** Ensure trailing dimensions are compatible
- **Slicing returns views, not copies:** Use `.copy()` if needed
- **reshape()** errors: Total size must remain constant
- **Misuse of axis:** Confusing axis 0 vs 1 is a common source of bugs

## NumPy Functions and Operations

NumPy Functions	Description
<code>np.array([1,2,3])</code>	Creates a 1D array of shape <b>1x3</b> with values 1, 2, 3
<code>np.array([(1,2,3), (4,5,6)])</code>	Creates 2D array of shape <b>2x3</b> with values 1,2,3,4,5,6
<code>np.array([[(1,2,3), (4,5,6)], [(7,8,9), (10,11,12)]])</code>	Creates a 3D array with shape <b>2x2x3</b>
<code>np.zeros(3,4)</code>	Creates a <b>3x4</b> array of zeros
<code>np.arange(1,60,5)</code>	Creates a 1D array of values 1 through 60 at steps of 5
<code>arr.reshape(2,3,4)</code>	Reshapes array <b>arr</b> into an array of shape <b>2x3x4</b>
<code>arr.shape</code>	To get the shape of the array <b>arr</b>

NumPy Operations	Description
<code>a[0]</code>	Gets the 0th element in 1D array
<code>b[0,0]</code>	Gets the 0th element in 2D array
<code>c[0,0,0]</code>	Gets the 0th element in 3D array
<code>c[9,0,0]</code>	Gets the element which is the 0th element in the 0th row in the 9th depth
<b>1D Arrays</b>	
<code>a[:]</code>	Selects everything
<code>a[2:5]</code>	Selects the 2nd through the 4th rows (does not include the 5th row)
<b>2D Arrays</b>	

NumPy Operations	Description
<code>b[:, :]</code>	Selects all rows and all columns
<code>b[:, 0]</code>	Selects all rows, and the zeroth column
<code>b[0, :]</code>	Selects the zeroth row, and all columns in that row
<code>b[0:2, :]</code>	Selects the zeroth and first row, but NOT the second row
<code>b[0:2, 0:2]</code>	Selects the zeroth and first row, and the zeroth and first column
3D Arrays	
<code>c[:, :, :]</code>	Selects all rows and columns on all depths
<code>c[0, :, :]</code>	Selects the everything in the first depth
<code>c[:, 0, :]</code>	Selects the first row of each depth
<code>c[:, :, 0]</code>	Selects the first column of each depth

## Try this out

1. Write NumPy code to create a 5×5 matrix with values 1 to 25.
2. Given `a = np.array([1, 2, 3])`, what is `a[:, np.newaxis] + a`?
3. How do you extract the diagonal of a 2D array?
4. How would you stack two 1D arrays column-wise?
5. What is the difference between `flatten()` and `ravel()`?

## Additional Reading

- [Official NumPy Docs](#)
- [Visual Guide to Broadcasting](#)
- [NumPy 100 Practice Problems](#)

# Pandas Series

## Key Definitions & Concepts

**Series:** A one-dimensional labelled array, capable of holding any data type (int, float, str, datetime, etc.). Think of it as a hybrid of a list and a dictionary.

**Index:** The labels associated with each element in a Series. Allows fast access and alignment.

**Vectorised Operations:** Just like NumPy arrays, Series supports element-wise operations (addition, comparison, logical operations).

**Method Chaining:** The practice of applying multiple Series/DataFrame methods in a single statement. Promotes readable, fluent code.

**.str accessor:** Enables vectorised string methods.

**.dt accessor:** Provides datetime-specific operations after converting a Series to a datetime format.

## Core Ideas

- A Pandas Series behaves like a **dictionary-backed vector**: values are like a NumPy array; labels (index) are like dictionary keys.
- Operations respect the index: this makes Pandas ideal for labelled time series or named features.
- **Method chaining** encourages writing "pipelines", stepwise transformations applied in sequence.
- Series enables **clean, readable, high-level operations** without the verbosity of loops.

## Implementation

### Creating Series

```
Python
import pandas as pd

# From a list
pd.Series([10, 20, 30])

# With custom index
pd.Series([10, 20, 30], index=['a', 'b', 'c'])

# From a dictionary
pd.Series({'x': 1, 'y': 2, 'z': 3})
```

### Indexing and Slicing

```
Python
s = pd.Series([10, 20, 30], index=['a', 'b', 'c'])

s['a']          # 10
s[0:2]          # First two elements
s[['a', 'c']]   # Specific labels
s.loc['b']      # Access by label
s.iloc[1]       # Access by position
```

## Operations on Series

```
Python
s = pd.Series([1, 2, 3, 4])

s + 10          # [11, 12, 13, 14]
s * 2           # [2, 4, 6, 8]
s.mean(), s.max(), s.std()

# Method chaining
s.add(1).mul(10).clip(0, 25)

# Remove duplicates
pd.Series([1, 2, 2, 3]).drop_duplicates()

# Apply/map
s.apply(lambda x: x**2)
s.map({1: 'A', 2: 'B', 3: 'C'}) # Mapping values
```

## Working with Series (Boolean Logic & Filtering)

```
Python
s = pd.Series([100, 200, 300, 400], index=['a', 'b', 'c', 'd'])

s[s > 200]          # Filter by value
s.isnull()           # Check for missing values
s.fillna(0)          # Fill missing values
```

## String Operations with `.str`

Python

```
names = pd.Series(['alice', 'BOB', 'Charlie'])
```

```
names.str.upper()           # ['ALICE', 'BOB', 'CHARLIE']
names.str.len()             # [5, 3, 7]
names.str.contains('li')    # [True, False, True]
names.str.split('a')        # [['', 'lice'], ['BOB'], ['Ch',
                                'rlie']]
```

## Datetime Operations with `.dt`

Python

```
dates = pd.Series(['2023-01-01', '2023-05-15'])
```

```
dates = pd.to_datetime(dates)
```

```
dates.dt.year               # [2023, 2023]
dates.dt.month              # [1, 5]
dates.dt.weekday            # [6, 0]
```

## Summary

Operation	Method	Description
Create Series	<code>pd.Series(data)</code>	From list, dict, array
Indexing	<code>s['a'],</code> <code>s.iloc[0]</code>	By label or position
Math ops	<code>s + 10,</code> <code>s * 2</code>	Element-wise operations
Filtering	<code>s[s &gt; 100]</code>	Boolean condition
Map/Apply	<code>s.map(),</code> <code>s.apply()</code>	Transform values
String ops	<code>s.str.upper(),</code> <code>s.str.len()</code>	Vectorised string handling
Datetime ops	<code>s.dt.year,</code> <code>s.dt.month</code>	Extract date components

## Real-world Use Cases

- **Feature Engineering:** Extract year/month from timestamps
- **Data Cleaning:** Lowercase names, split strings, remove duplicates
- **Time Series Analysis:** Weekly sales, monthly trends
- **Categorical Encoding:** Mapping string values to codes

## Pitfalls and Misconceptions

- `.apply()` vs `.map()`:  
`map()` is for value substitution; `apply()` is more general (can apply any function)
- `.str` accessor only works on string-typed Series; convert if needed
- `to_datetime()` is required before using `.dt` accessor

## Try this out

1. Create a Series of 5 cities with population values.
2. Convert `[ '2022-01-01 ', '2023-01-01 ' ]` into a datetime Series and extract the year.
3. How would you replace all lowercase names in a Series with uppercase versions?
4. Filter a Series of integers to only keep even numbers.
5. Explain the difference between `.apply()` and `.map()` with a small example.

# Pandas DataFrames

## Key Definitions & Concepts

**DataFrame:** A two-dimensional, size-mutable, labelled data structure with columns of potentially different types.

**Indexing:** Refers to selecting rows and columns using position (`iloc`) or labels (`loc`).

**Fancy Indexing:** Supplying a list or array of labels/positions to select specific rows or columns.

**Method Chaining:** Writing successive operations on a DataFrame in one statement.

**Grouping:** The act of splitting data into groups and applying an aggregation function.

**Wrangling:** The process of cleaning, transforming, and reshaping raw data into a usable format.

## Core Ideas & Theoretical Intuition

- A DataFrame is like a **spreadsheet with labelled rows and columns**, built for high-performance operations.
- Think of `.iloc` as NumPy-style **position-based access**, and `.loc` as dictionary-style **label-based access**.
- Merging is analogous to SQL joins – critical for combining datasets from multiple sources.
- Grouping and pivoting allow **multilevel summarisation**, ideal for exploratory data analysis.
- Most DataFrame operations are **non-destructive**, enabling method chaining and functional transformations.

## Implementation

### Creating DataFrames

```
Python
import pandas as pd

# From dictionary
data = {'Name': ['Alice', 'Bob'], 'Age': [25, 30]}
df = pd.DataFrame(data)

# From list of lists
df2 = pd.DataFrame([[1, 2], [3, 4]], columns=['A', 'B'])

# With custom index
pd.DataFrame(data, index=['a', 'b'])
```

### Attributes

```
Python

df.dtypes      # Data type of each column
df.ndim        # Number of dimensions
df.shape       # Rows × Columns
df.size        # Total elements
df.index       # Row index object
df.columns     # Column names
df.values      # Underlying NumPy array
```

## Info & Summary Functions

Python

```
df.info()           # Structure summary  
  
df.head(3)         # First 3 rows; similarly for df.tail(3)  
  
df.describe()      # Stats for numeric columns
```

## Reading Data (CSV Example)

Python

```
pd.read_csv('data.csv', header=0, index_col='ID',  
            usecols=['ID', 'Name', 'Score'],  
            nrows=100, skiprows=1)
```

## Indexing and Slicing

### **iloc** (position-based)

Python

```
df.iloc[0]          # First row  
  
df.iloc[:, 1]       # All rows, second column  
  
df.iloc[0:2, 1:3]   # Rows 0-1, Columns 1-2
```

## loc (label-based)

Python

```
df.loc['a'] # Row with label 'a'

df.loc[:, 'Age'] # Entire 'Age' column

df.loc['a':'b', ['Name']] # Slice rows and specific col
```

## Fancy Indexing

Python

```
# Rows with labels 'a' and 'c' and columns 'Name' and 'Age'

df.loc[['a', 'c'], ['Name', 'Age']]

# Rows at positions 0 and 2 and columns at positions 0 and 1

df.iloc[[0, 2], [0, 1]]
```

## Operations on DataFrames

Python

```
df * 10 # Multiply numeric values

df['Bonus'] = df['Age'] * 0.1 # Add new column

df.sum(), df.mean() # Aggregations

df.sort_values('Age') # Sort rows

df.apply(len) # Apply function to columns
```

```
df['Name'].map(str.upper) # Element-wise string map

# Method chaining

df.dropna().query("Age > 20").sort_values('Age')
```

## Working with DataFrames

```
Python

df.columns = df.columns.str.lower() # Rename cols

df.rename(columns={'age': 'year'}) # Rename

df.fillna(0) # Fill missing
```

## Merging DataFrames

```
Python

pd.merge(df1, df2, how='inner', on='ID')

# SQL-style merge

pd.concat([df1, df2], axis=0)

# Stack rows
```

- `how=` options: 'inner', 'left', 'right', 'outer'
- `on=` specifies column key; `axis=1` for column-wise merge

## Analysing DataFrames

Python

```
df.reset_index()                # Move index to column

df['Score'].quantile(0.75)       # 75th percentile
```

## Grouping and Aggregation

Python

```
df.groupby('Department')['Salary'].sum()

df.groupby(['Gender', 'Department']).agg({'Age': 'mean', 'Salary':
    'max'})
# Group the DataFrame by both 'Gender' and 'Department',
# then compute the mean age and max salary for each group
```

## Pivoting

Python

```
df.pivot(index='Date', columns='Region', values='Sales')
```

## Sample Output:

```
# Region      North  South
# Date
# 2023-01-01    100    150
# 2023-01-02    200    180
```

## Wrangling a DataFrame

Python

```
df.drop_duplicates()           # drop duplicate rows

df.dropna()                   # drop rows with null values

df['City'] = df['City'].str.strip().str.title()

df['Date'] = pd.to_datetime(df['Date'])
```

## Summary

Task	Example Code	Output Description
Row by label	<code>df.loc['a']</code>	Row with index label 'a'
Col by position	<code>df.iloc[:, 1]</code>	Second column
Filter	<code>df[df['Age'] &gt; 25]</code>	Rows with Age > 25
Merge	<code>pd.merge(df1, df2, on='ID')</code>	Combine tables
Groupby	<code>df.groupby('Team')['Score'].mean()</code>	Aggregated stats
Pivot	<code>df.pivot(index, columns, values)</code>	Reshaped table

## Pitfalls and Misconceptions

- `.iloc` vs `.loc`: Position vs Label: using the wrong one may raise errors
- Modifying views: `.loc` may return a view, not a copy: use `.copy()` if needed
- `map()` vs `apply()`: `map` works on Series elements; `apply` can be column-wise on DataFrame
- Be cautious when chaining inplace operations (e.g., `df.dropna(inplace=True)` followed by `df.sort_values()`)

## Common Interview Questions

### 1. What are the key differences between a NumPy array and a Python list?

Topic: NumPy Basics

Expected Points:

- Fixed-size, homogeneous vs dynamic, heterogeneous
- Vectorised operations in NumPy
- Memory efficiency and performance benefits

### 2. Explain broadcasting in NumPy. Give an example of a valid and an invalid broadcast operation.

Topic: NumPy Broadcasting

Expected Points:

- Rules for shape compatibility
- Example:  $(3, 1) + (1, 4) \rightarrow (3, 4)$
- Invalid example where trailing dimensions don't match

3. What does `.reshape()` do in NumPy? How is it different from `.ravel()` and `.flatten()`?

Topic: Array Reshaping & Views

Expected Points:

- `reshape` changes shape without changing data
- `flatten` returns a copy; `ravel` returns a view (if possible)

4. How would you remove duplicate values from a Pandas Series or DataFrame?

Topic: Data Cleaning in Pandas

Expected Points:

- `Series.drop_duplicates()`
- `DataFrame.drop_duplicates(subset=['col1', ...])`

5. How are `.loc[]` and `.iloc[]` different? When would you use each?

Topic: Pandas Indexing

Expected Points:

- `.loc[]` uses label-based indexing
- `.iloc[]` uses integer position indexing
- Edge cases (e.g., mixed-type index)

6. What is method chaining in Pandas? Why is it useful?

Topic: Code Style and Efficiency

Expected Points:

- Writing operations like: `df.dropna().query(...).sort_values(...)`
- Benefits: readable, compact, avoids intermediate variables

7. Explain the difference between `map()`, `apply()`, and `applymap()` in Pandas.

Topic: Functional Programming with Pandas

Expected Points:

- `map()` → element-wise on Series
- `apply()` → row/column-wise on DataFrame
- `applymap()` → element-wise on DataFrame

8. Describe how you would merge two DataFrames in Pandas. What types of joins are supported?

Topic: Combining DataFrames

Expected Points:

- `pd.merge(left, right, how='inner', on='key')`
- `how=` supports: 'inner', 'left', 'right', 'outer'
- Can also join on the index or use `concat()` for stacking

9. You read a CSV file and find some columns are not needed, and the headers are in the second row. How would you load only the relevant data?

Topic: Data Import & Preprocessing

Expected Points:

- Use `usecols=`, `skiprows=`, `header=` in `read_csv()`

10. How would you calculate the average sales per product category in a DataFrame? How would you reshape the result into a pivot table?

**Topic:** Grouping and Pivoting

**Expected Points:**

- `df.groupby('Category')['Sales'].mean()`
- `df.pivot(index='Date', columns='Category', values='Sales')`