

Contents

Java – First Problem Statement

- Question 2
- Solution 3
- Testcase 4

Java – Second Problem Statement

- Question 5
- Solution 10
- Testcase 14

Solutions for TCS Xplore iPA held on 29-Jan-23

Java – First Problem Statement

Question

Write main method in **Solution** class.

In the main method, read a String value and print the count of lower case characters present in the input String value. If no lower case characters are present in the String value then it should print "No lower case characters present" as a String.

Sample input1:

XpLore

Output:

4

Sample input2:

XPLORE

Output:

No lower case characters present

Sample code snippet for reference:

Please use below code to build your MyClass.

```
public class MyClass
{

    public static void main(String[] args)
```

Restricted for circulation outside TCS Xplore

2

```
{  
    //code to read values  
    //code to display the result  
}  
  
}
```

Java – First Problem Statement Solution

```
public class Solution {  
    public static void main(String args[]){  
        int lower=0;  
        Scanner sc=new Scanner(System.in);  
        String s1 = sc.nextLine();  
        for(int i=0; i<s1.length(); i++){  
            char ch=s1.charAt(i);  
            if(ch>='a' && ch<='z') {  
                lower++;  
            }  
        }  
        if(lower>0)  
            System.out.println(lower);  
        else  
            System.out.println("No lower case characters present");  
    }  
}
```

Test Cases- First Problem Statement

Test Case1

XpLore

Output:

4

Test Case2:

XPLORE

Output:

No lower case characters present

Test Case3:

Morning

Output:

6

Test Case4:

MORNING

Output:

1

Restricted for circulation outside TCS Xplore

4

Java- Second Problem Statement

Question

Create a class HeadSets with below attributes:

headsetName - String

brand-String

price - int

available- boolean

The above attributes should be private, write getters, setters and parameterized constructor as required.

Create class Solution with main method.

Implement two static methods - `findTotalPriceForGivenBrand` and `findAvailableHeadsetWithSecondMinPrice` in Solution class.

findTotalPriceForGivenBrand method:

The method will return the total price of Headsets from array of Headset objects for the given brand(String parameter passed).

If no Headsets with the given brand is present in the array of Headsets objects, then the method should return 0.

findAvailableHeadsetWithSecondMinPrice method:

This method will take array of Headset objects as an input parameter and returns the available Headset object with the second lowest/minimum price from the given array of objects.

If no Headsets with the above condition is present in the array of Headsets objects, then the method should return null.

Restricted for circulation outside TCS Xplore

5

Note : No two Headsets will have the same price.

All the searches should be case insensitive.

The above mentioned static methods should be called from the main method.

For findTotalPriceForGivenBrand method - The main method should print the returned total price as it is if the returned value is greater than 0 or it should print "No Headsets available with the given brand".

Eg: 4500

where 4500 is the total Headsets price

For findAvailableHeadsetWithSecondMinPrice method - The main method should print the headsetsName and price from the returned Headsets object if the returned value is not null.

If the returned value is null then it should print "No Headsets available".

Eg:Logitech Wired

1500

where Logitech Wired is the headsetName and 1500 is the price

Before calling these static methods in main, use Scanner object to read the values of four Headset objects referring attributes in the above mentioned attribute sequence.

Next, read the value of String parameter for capturing brand.

Consider below sample input and output:

Input1:

boAt BassHeads

boAt

1220

Restricted for circulation outside TCS Xplore

6

true

Over Ear Wired

boAt

549

true

In Ear with Mic

JBL

450

true

Buds 2 Neo

RealMe

500

true

boAt

Output:

1769

Buds 2 Neo

500

Input2:

boAt BassHeads

boAt

1220

false

Over Ear Wired

boAt

1549

false

Restricted for circulation outside TCS Xplore

7

In Ear with Mic

JBL

450

false

Buds 2 Neo

RealMe

500

false

boAt

Output:

2769

No Headsets available

Sample code snippet for reference:

Please use below code to build your solution.

import java.util.Scanner;
public class MyClass
{

public static void main(String[] args)
{
//code to read values
//code to call required method
//code to display the result
}

public static int findTotalPriceForGivenBrand (/* required parameters to be added */)
{

Restricted for circulation outside TCS Xplore

8


```
//method logic
}

public static HeadSets findAvailableHeadsetWithSecondMinPrice (/* required parameters to be
added */)

//method logic
}
}

class HeadSets
{
//code to build the class
}
```

Note on using Scanner object:

Sometimes scanner does not read the new line character while invoking methods like nextInt(), nextDouble() etc.

Usually, this is not an issue, but this may be visible while calling nextLine() immediately after those methods.

Consider below input values:

1001

Savings

Referring below code:

```
Scanner sc = new Scanner(System.in);
```

```
int x = sc.nextInt();
```

```
String str = sc.nextLine(); -> here we expect str to have value Savings. Instead it may be "".
```

If above issue is observed, then it is suggested to add one more explicit call to nextLine() after reading numeric value.

Restricted for circulation outside TCS Xplore

9

Java – Second Problem Statement Solution

```
import java.util.Scanner;
```

```
public class Solution{
```

```
    public static void main(String[] args) {
```

```
        Headsets[] hs = new Headsets[4];
```

```
        Scanner sc = new Scanner(System.in);
```

```
        for (int i = 0; i < hs.length; i++) {
```

```
            String headsetName = sc.nextLine();
```

```
            String brand = sc.nextLine();
```

```
            int price = sc.nextInt();
```

```
            boolean available = sc.nextBoolean();
```

```
        sc.nextLine();
```

```
        hs[i] = new Headsets(headsetName, brand, price, available);
```

```
        }
```

```
        String new_brand = sc.nextLine();
```

```
        int sum = findTotalPriceForGivenBrand (hs,new_brand);
```

```
        if (sum>0) {
```

```
            System.out.println(sum);
```

```
        } else {
```

```
            System.out.println("No Headsets available with the given brand");
```

```
        }
```

```
        Headsets res1 = findAvailableHeadsetWithSecondMinPrice(hs);
```

```
        if (res1 != null) {
```

```
            System.out.println(res1.getHeadsetName());
```

```
            System.out.println(res1.getPrice());
```

```
        } else{
```

Restricted for circulation outside TCS Xplore

10

```
        System.out.println("No Headsets available");
    }

}

public static int findTotalPriceForGivenBrand (Headsets[] hs, String brand) {

    int sum=0;
    for(int i=0;i<hs.length;i++) {
        if( hs[i].getBrand().equalsIgnoreCase(brand)) {
            sum = sum + hs[i].getPrice();
        }
    }
    return sum;
}

public static Headsets findAvailableHeadsetWithSecondMinPrice (Headsets[] hs) {
    int count = 0;
    Headsets temp = null;

    for (int i = 0; i < hs.length; i++) {

        if (hs[i].isAvailable()) {
            count++;
        }
    }

    Headsets[] newheadset = new Headsets[count];
    int k=0;
```

```

        for (int i = 0; i < hs.length; i++) {
            if (hs[i].isAvailable()) {
                newheadset[k] = hs[i];
                k++;
            }
        }
        for (int i = 0; i < newheadset.length; i++) {
            for (int j = i + 1; j < newheadset.length; j++) {
                if (newheadset[i].getPrice() > newheadset[j].getPrice()) {
                    temp = newheadset[i];
                    newheadset[i] = newheadset[j];
                    newheadset[j] = temp;
                }
            }
        }
        if(count>0){
            return newheadset[1];
        }
        else{
            return null;
        }
    }
}

```

```

class Headsets{

```

```

    private String headsetName;

```

```

    private String brand;

```

Restricted for circulation outside TCS Xplore

12

```
private int price;

private boolean available;

public String getHeadsetName() {
    return headsetName;
}

public void setHeadsetName(String headsetName) {
    this.headsetName = headsetName;
}

public String getBrand() {
    return brand;
}

public void setBrand(String brand) {
    this.brand = brand;
}

public int getPrice() {
    return price;
}

public void setPrice(int price) {
    this.price = price;
}

public boolean isAvailable() {
    return available;
}

public void setAvailable(boolean available) {
    this.available = available;
}

public Headsets(String headsetName, String brand, int price,
    boolean available) {
    super();
    this.headsetName = headsetName;
    this.brand = brand;
```

```
        this.price = price;  
        this.available = available;  
    }  
  
}
```

Test Cases – Second Problem Statement

Test Case1:

boAt BassHeads

boAt

1220

true

Over Ear Wired

boAt

549

true

In Ear with Mic

JBL

450

true

Buds 2 Neo

RealMe

500

true

boAt

Output:

1769

Buds 2 Neo

500

Restricted for circulation outside TCS Xplore

14

Test Case2:

boAt BassHeads

boAt

1220

false

Over Ear Wired

boAt

1549

false

In Ear with Mic

JBL

450

false

Buds 2 Neo

RealMe

500

false

boAt

Output:

2769

No Headsets available

Testcase 3:

Bluetooth Wireless

Sony

2690

true

Wired InEar with Mic

Philips

Restricted for circulation outside TCS Xplore

15

455

false

Wireless In Ear

Sony

2799

true

Live Over Ear with Mic

JBL

5999

true

sony

Output:

5489

Wireless In Ear

2799

Testcase 4:

Bluetooth Wireless

Sony

2890

true

Wired InEar with Mic

Philips

455

false

Wireless In Ear

Sony

2799

true

Live Over Ear with Mic

JBL

Restricted for circulation outside TCS Xplore

16

5999

true

apple

Output:

No Headsets available with the given brand

Bluetooth Wireless

2890

Restricted for circulation outside TCS Xplore

17