

NUDURA 6" (152mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

HAUNCHED SLAB
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

NUDURA FLOOR
TECHNOLOGY OR EQUIVALENT
RIGID INSULATION AS
SPECIFIED

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

INSTALL SLOPED INSULATION
TO SUIT FROST PENETRATION
DEPTH AS SPECIFIED BY
LOCAL CODES

$\frac{1}{2}$ " (13mm) GYPSUM BOARD

STEEL DOWELS TO MATCH
VERTICAL REINFORCEMENT IN
SLAB (EMBED 40x BAR
DIAMETER) INSTALLED AS
PER CODE OR AS SPECIFIED

FOAM FILL INTERLOCK GAPS
CONTINUOUS WITH NUDURA
LOW EXPANSION
POLYURETHANE SPRAY FOAM
BOTH INTERIOR AND
EXTERIOR

SLAB ON GRADE

NUDURA FLOOR
TECHNOLOGY

COMPACTED
GRANULAR FILL

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
HAUNCHED SLAB DETAIL
EXTERIOR FINISH AS SPECIFIED
INSULATED

REV. NO.
003 KS

REV. DATE:
FEB 2010

DRAWN BY:
J. NEILON

DWG NO.

B6D01

SCALE:
1 : 8