

BRICK VENEER c/w 1"
(25mm) AIR SPACE
AND BRICK TIES

FORM PANELS c/w INSERT
WEBS-CUT TO SUIT FLOOR
CONNECTION—
ADDITIONAL FORM SUPPORT
AS REQUIRED

WET SET DOWELS FIELD
BENT INTO SLAB AS
SPECIFIED

U BRACKET ANCHOR
INSERT

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT
BETWEEN POUR OR AS
SPECIFIED

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

NUDURA 6" (152mm)
STANDARD FORM
UNIT

GYPSUM BOARD
FINISHED/FIRE STOP
INSTALLED AT JOISTS
AS PER CODE

COMPOSITE STEEL
DECK-SLAB AND
REINFORCEMENT AS
SPECIFIED

OWSJ

INTERIOR INSULATION
REMOVED AT JOIST
LOCATIONS

½" (13mm) GYPSUM
BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY
Building Value.

NUDURA 6" (152mm) FORM UNIT
COMPOSITE STEEL DECK-SLAB
STEEL JOIST ON EXT. BEARING WALL
INTERMEDIATE FLOOR CONNECTION
BRICK VENEER FINISH

REV. NO.
007 KS

DWG NO.

D6C09

REV. DATE:
MAR 2010

DRAWN BY:
T. VAN CLIEAF

SCALE:
1 : 8