

NUDURA 8" (203mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

WET SET DOWELS
TO MATCH VERTICAL
REINFORCEMENT
BETWEEN POUR OR
AS SPECIFIED

THROUGH WALL
FLASHING AND
WEEP HOLES AS
PER CODE OR AS
SPECIFIED

FINISHED GRADE
MINIMUM 6"
(152mm) OR AS
PER CODE (SEE
NOTE)

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

NUDURA
WATERPROOFING MEMBRANE

4 1/2" [114mm]
BEVEL TOP
& BOTTOM
OF OPENING
45 DEG.

ANCHOR BOLT(S)

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

SUB FLOOR

FLOOR
JOISTS/TRUSSES
AS SPECIFIED

JOIST HANGER
LEDGER BOARD

FORMS TO BE
CUT AND FOAM
REMOVED
AS NOTED

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

NUDURA 8"
(203mm) BRICK
LEDGE FORM UNIT

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER

NOTE: FINISHED GRADE LEVEL SPECIFIED FOR
FROST PRONE AREAS. FOR ALTERNATIVE GRADE
LEVEL SEE DETAIL C6A29



NUDURA
INTEGRATED BUILDING TECHNOLOGY
Building Value

NUDURA 8" (203mm) FORM UNIT
LEDGER BOARD CONNECTION
BRICK VENEER FINISH

REV. NO.
001 KS

DWG. NO.

C8A05

REV. DATE:
AUGUST 2010

SCALE:
1 : 8

DRAWN BY:
J. N / N. L