

NUDURA 8" (203mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

LINTEL REINFORCEMENT
AS PER CODE OR AS
SPECIFIED

ALUMINUM DRIP CAP
FLASHING INSTALLED BELOW
FINISH FOR FULL FRAME
WIDTH INSTALLED AS PER
CODE OR AS SPECIFIED

EXTENDED DOOR
FRAME SCREWED
DIRECTLY INTO
NUDURA CONCRETE
CORE

DOOR THRESHOLD

EXTERIOR CONCRETE
SLAB AND SLOPE AS
PER CODE

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

NUDURA 8" (203mm)
TAPER TOP FORM UNIT OR
HAND CUT TAPER BELOW
DOOR OPENING ONLY

NUDURA WATERPROOFING
MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

VAPOR BARRIER
LAPPED AND SEALED
TO DOOR FRAME

$1\frac{1}{2}$ "
(38mm) MIN.
COVER

OPENING
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

BLOCKING BETWEEN
JOISTS

FLOOR FINISH
AS SPECIFIED

PROPRIETARY
EMBEDDED JOIST
ANCHORAGE SYSTEM
OR EQUIVALENT

FLOOR
JOISTS/TRUSSES
AS SPECIFIED

LAP VAPOR BARRIER
TO CONTACT DOOR
THRESHOLD

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
DOOR HEAD/THRESHOLD DETAIL
EXTERIOR FINISH AS SPECIFIED

REV. NO.
000

DATE:
SEPT 2010

DRAWN BY:
K. STILL

DWG NO.

E8G08

SCALE:

1 : 8