

NUDURA 10" (254mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WET SET DOWELS
TO MATCH VERTICAL
REINFORCEMENT
BETWEEN POUR OR
AS SPECIFIED

THROUGH WALL
FLASHING AND
WEEP HOLES AS
PER CODE OR AS
SPECIFIED

FINISHED GRADE
MINIMUM 6"
(152mm) OR AS
PER CODE (SEE
NOTE)

$\frac{3}{16}$ " (5mm) ACRYLIC
PRIME COAT WHERE
EXTENDED ABOVE
GRADE

NUDURA
WATERPROOFING MEMBRANE

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

SUB FLOOR

FLOOR
JOISTS/TRUSSES
AS SPECIFIED

PROPRIETARY
EMBEDDED JOIST
ANCHORAGE SYSTEM
OR EQUIVALENT

NUDURA 10"
(254mm) BRICK
LEDGE FORM UNIT

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER

NOTE: FINISHED GRADE LEVEL SPECIFIED FOR
FROST PRONE AREAS. FOR ALTERNATIVE GRADE
LEVEL SEE DETAIL C6A30



NUDURA

INTEGRATED BUILDING TECHNOLOGY
Building Value.

NUDURA 10" (254mm) FORM UNIT
MULTI-PURPOSE HANGER
BRICK VENEER FINISH

REV. NO.
004 KS
REV. DATE:
AUGUST 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
C10A10
SCALE:
1 : 8