

NUDURA 10" (254mm)  
STANDARD FORM UNIT

BRICK VENEER c/w  
1" (25mm) AIR  
SPACE AND BRICK  
TIES

WET SET DOWELS  
TO MATCH VERTICAL  
REINFORCEMENT  
BETWEEN POUR OR  
AS SPECIFIED

HORIZ/VERT  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

THROUGH WALL  
FLASHING AND  
WEEP HOLES AS  
PER CODE OR AS  
SPECIFIED

FINISHED GRADE  
MINIMUM 6"  
(152mm) OR AS  
PER CODE (SEE  
NOTE)

$\frac{3}{16}$ " (5mm) ACRYLIC  
PARGE COAT

NUDURA  
WATERPROOFING MEMBRANE

BEVEL TOP &  
BOTTOM OF  
OPENING 45°

ANCHOR  
BOLT(S)

$\frac{1}{2}$ " (13mm)  
GYPSUM BOARD

SUB FLOOR

FLOOR  
JOISTS/TRUSSES  
AS SPECIFIED

JOIST HANGER  
LEDGER BOARD

FORMS TO BE  
CUT AND FOAM  
REMOVED  
AS NOTED

$\frac{1}{2}$ " (13mm)  
GYPSUM BOARD

NUDURA 10"  
(254mm) BRICK  
LEDGE FORM UNIT

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER

NOTE: FINISHED GRADE LEVEL SPECIFIED FOR  
FROST PRONE AREAS. FOR ALTERNATIVE GRADE  
LEVEL SEE DETAIL C6A29



**NUDURA**  
INTEGRATED BUILDING TECHNOLOGY  
*Building Value.*

NUDURA 10" (254mm) FORM UNIT  
LEDGER BOARD CONNECTION  
BRICK VENEER FINISH

REV. NO.  
001 KS

DWG. NO.

C10A03

REV. DATE:  
AUGUST 2010

DRAWN BY:  
J. N / N. L

SCALE:  
1 1/2"=1'-0"