Date of Submission:

## Vidyavardhini's College of Engineering and Technology Department of Artificial Intelligence & Data Science

| Experiment No.9                   |
|-----------------------------------|
| Demonstrate Database connectivity |
| Date of Performance:              |



### Vidyavardhini's College of Engineering and Technology Department of Artificial Intelligence & Data Science

Aim :- Write a java program to connect Java application with the MySQL database

**Objective :-** To learn database connectivity

#### **Theory:**

Database used: MySql

- 1. Driver class: The driver class for the mysql database is com.mysql.jdbc.Driver.
- 2. Connection URL: The connection URL for the mysql database is jdbc:mysql://localhost:3306/loan management where jdbc is the API, mysql is the database, localhost is the server name on which mysql is running, can also use IP address, 3306 is the port number and loan management is the database name.
- 3. Username: The default username for the mysql database is Hiren.
- 4. Password: It is the password given by the user at the time of installing the mysql database. Password used is "".

To connect a Java application with the MySQL database, follow the following steps.

- First create a database and then create a table in the mysql database.
- To connect java application with the mysql database, mysqlconnector.jar file is required to be loaded.
- download the jar file mysql-connector.jar

Statement stmt=con.createStatement();

- add the jar file to the same folder as the java program.
- Compile and run the java program to retrieve data from the database.

#### **Implementation:**

#### **JAVA APPLICATION:-**



# Vidyavardhini's College of Engineering and Technology Department of Artificial Intelligence & Data Science

```
ResultSet rs=stmt.executeQuery("select * from customer");

while(rs.next())

System.out.println(rs.getInt(1)+" "+rs.getString(2)+" "+rs.getString(3));

con.close();

}catch(Exception e){ System.out.println(e);}

}
```

```
C:\Users\ts395\.jdks\openjdk-22.0.1\bin\java.exe "-javaagent:C:\Program Files\JetBrains\IntelliJ IDEA 2024.1\lib\idea_rt.jar=60829:C:\Program Files\JetBrain
```

**Conclusion:** Data has been retrieved successfully from a table by establishing database connectivity of java program with mysql database.

#### 1. Explain steps to connect a java application with the MySQL database

Sure, here are the steps to connect a Java application with a MySQL database:

#### 1. Import JDBC Library:

- Ensure that you have the MySQL JDBC driver JAR file included in your Java project's build path. You can download the MySQL Connector/J driver from the MySQL website or use a dependency management tool like Maven or Gradle.

#### 2. \*\*Load the JDBC Driver:

- Use the 'Class.forName()' method to dynamically load the MySQL JDBC driver class. For example:

Class.forName("com.mysql.cj.jdbc.Driver");

#### 3. Establish Connection:

- Use the `DriverManager.getConnection()` method to establish a connection to the MySQL database. Provide the database URL, username, and password as parameters. For example:

```
String url = "jdbc:mysql://localhost:3306/mydatabase";

String username = "root";

String password = "password";

Connection connection = DriverManager.getConnection(url, username, password);
```

#### 4. Create Statement:



## Vidyavardhini's College of Engineering and Technology Department of Artificial Intelligence & Data Science

- Create a Statement or PreparedStatement object to execute SQL queries against the database. For example:

Statement statement = connection.createStatement();

#### 5. Execute SQL Queries:

- Use the 'executeQuery()' method to execute SELECT queries or 'executeUpdate()' method to execute INSERT, UPDATE, DELETE queries. For example:

ResultSet resultSet = statement.executeQuery("SELECT \* FROM mytable");

#### 6. Process Results:

- Iterate through the ResultSet object to retrieve and process the query results. For example:

```
while (resultSet.next()) {
   String name = resultSet.getString("name");
   int age = resultSet.getInt("age");
   // Process data...
}
```

#### 7. Close Resources:

- Close the ResultSet, Statement, and Connection objects when done to release database resources and prevent memory leaks. For example:

```
resultSet.close();
statement.close();
connection.close();
```