



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Experiment No.10
Implementation and demonstration of Transaction and Concurrency control techniques using locks
Date of Performance:
Date of Submission:



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Aim :- Write a query to lock and unlock a table for transaction and concurrency control.

Objective :- To learn locking of tables for transaction processing and concurrency control.

Theory:

A lock is a mechanism associated with a table used to restrict the unauthorized access of the data in a table. MySQL allows a client session to acquire a table lock explicitly to cooperate with other sessions to access the table's data. MySQL also allows table locking to prevent unauthorized modification into the same table during a specific period.

Table Locking in MySQL is mainly used to solve concurrency problems. It will be used while running a transaction, i.e., first read a value from a table (database) and then write it into the table (database).

MySQL provides two types of locks onto the table, which are:

READ LOCK: This lock allows a user to only read the data from a table.

WRITE LOCK: This lock allows a user to do both reading and writing into a table.

The following is the syntax that allows us to acquire a table lock explicitly:

LOCK TABLES table_name [READ | WRITE];

The following is the syntax that allows us to release a lock for a table in MySQL:

UNLOCK TABLES;

Implementation:

LOCK:-

```
1 • Create database Hotel_Management;
2 • use Hotel_Management;
3 • LOCK TABLES customer WRITE;
4 • select * from customer;
```

✓	32 02:45:56	LOCK TABLES customer WRITE	0 row(s) affected	0.032 sec
✓	33 02:47:11	select * from customer LIMIT 0, 1000	3 row(s) returned	0.000 sec / 0.000 sec

UNLOCK:-

```
1 • Create database Hotel_Management;
2 • use Hotel_Management;
3 • UNLOCK TABLES;
4 • select * from customer;
```

✓	34 02:50:28	UNLOCK TABLES	0 row(s) affected	0.000 sec
✓	35 02:50:34	select * from customer LIMIT 0, 1000	3 row(s) returned	0.000 sec / 0.000 sec



Conclusion:

Locking and unlocking of tables is achieved and verified using insert command in the same table of a database system.

1. Explain Transaction and Concurrency control techniques using locks.

here's a brief explanation of transactions and concurrency control techniques using locks:

1. Transaction:

- A transaction is a logical unit of work that consists of one or more database operations, such as INSERT, UPDATE, DELETE, or SELECT.
- Transactions ensure that all operations within them are executed atomically, meaning they either all succeed or all fail, maintaining data consistency.
- The ACID properties (Atomicity, Consistency, Isolation, Durability) define the characteristics of a transaction, ensuring reliability and data integrity.

2. Concurrency Control Techniques Using Locks:

- Locking: Locks are used to control access to shared resources (e.g., database records) to prevent conflicts and maintain data consistency in a multi-user environment.

- Types of Locks:

- ****Shared Locks (Read Locks):** Allow multiple transactions to read data simultaneously but prevent write operations until all shared locks are released.

- **Exclusive Locks (Write Locks)**:** Prevent other transactions from reading or writing to a resource until the exclusive lock is released.

- Concurrency Control Protocols:

- **Two-Phase Locking (2PL):** Transactions acquire locks in two phases (growing phase and shrinking phase) and hold them until the end of the transaction. This ensures serializability but may lead to deadlocks.

- **Timestamp Ordering:** Assigns a unique timestamp to each transaction and uses these timestamps to order conflicting operations, ensuring serializability without explicit locking. Conflicts are resolved by comparing transaction timestamps.

- **Optimistic Concurrency Control (OCC):** Transactions operate without acquiring locks initially. Conflicts are detected at commit time, and if conflicts occur, the transaction is rolled back and retried.

- **Multi-Version Concurrency Control (MVCC):** Maintains multiple versions of a data item to allow concurrent read and write operations without blocking. Each transaction sees a consistent snapshot of the database at its start time.

These concurrency control techniques using locks ensure that transactions execute safely and



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

efficiently in a multi-user database environment, preventing data inconsistencies and ACID properties. Different techniques may be suitable depending on the specific requirements and characteristics of the application.