

<u>Index</u>		
Useful Tips	2	
Fast I/O	2	
Random algorithm	2	
Policy Based Data Structure	2	
1 Formula	2	
1.1 Area Formulas	2	
1.2 Perimeter Formulas	2	
1.3 Volume Formulas	2	
1.4 Surface Area Formulas	2	
1.5 Trigonometry	3	
1.6 Sum	3	
2 Number Theory	3	
2.1 Prime number under 1000	3	
2.2 Divisor Count	3	
2.3 Leap year	3	
2.4 Num of Leap year in between	3	
2.5 Power	3	
2.6 BINARY EXPONENTIATION: (a^b)	3	
2.7 BINARY EXPONENTIATION: $(a^b)^c$	4	
2.8 Check is prime number- $O(\sqrt{n})$	4	
2.9 Prime factorization- $O(\sqrt{n})$	4	
2.10 Seive	4	
2.11 smallest number in Seive	4	
2.12 Bitwise Seive(memory efficient)	4	
2.12 nth prime number	5	
2.13 Modular Operation	5	
2.16 Factorial mod	5	
2.14 nCr (more space, less time)	5	
2.15 nCr (less space, more time)	5	
2.17 Generate combinations	6	
2.18 Binomial coefficient	6	
2.19 10-ary to m-ary	6	
2.20 m-ary to 10-ary	6	
2.21 Catalan numbers	6	
2.22 Euler's totient function	6	
2.23 EXT_GCD	6	
2.24 Power Set	6	
2.25 Bitset DS	7	
3 Algorithms	7	
3.1 Big Interger Operation	7	
3.2 Find rank k in array	8	
3.3 InfixToPostFix	8	
3.4 Postfix calculation	8	
3.5 2D prefix sum	9	
3.6 KMP Algorithm- $O(n+m)$	9	
3.7 Kadane's Algorithm $O(n)$	9	
4 Data Structure	10	
		4.1 SEGMENT TREE 10
		4.2 FENWICK TREE 10
		4.3 SEGMENT TREE LAZY 10
		4.5 TRIE 11
		4.6 DSU 12
		5 Dynamic Programming 12
		5.1 LCS $O(n*m)$ 12
		5.2 MCM $O(n^3)$ 12
		5.3 LIS $O(n^2)$ 13
		5.4 LCIS $O(n * m)$ 13
		5.5 Maximum submatrix 13
		5.6 SOS DP 14
		5.7 Depth and width of tree 14
		6 Graph Theory 14
		6.1 SPFA – Optimal BF $O(V * E)$ 14
		6.2 Dijkstra $O(V + E \log V)$ 15
		6.3 BellmanFord $O(V.E)$ 15
		6.4 Floyd-Warshall algorithm $O(n^3)$ 15
		6.5 Topological sort 15
		6.6 Kruskal $O(E \log E)$ 16
		6.7 Prim – MST $O(E \log V)$ 16
		6.8 Eulerian circuit $O(V+E)$ 16
		6.9 LCA 17
		6.10 Min cost max flow 17
		6.11 SCC 18
		6.12 Bipartite 19
		6.13 Two farthest node 19
		7 Random Staff 19
		7.1 HASHING 19
		7.2 when $\phi(1)$ to $\phi(n)$ is needed 21
		7.3 when only $\phi(n)$ is needed 21
		7.4 Knight Moves 21
		7.5 bit count in $O(1)$ 21
		7.6 Matrix Exponentiation 21
		7.8 sqrt decomposition(MO's Algo) 22
		7.9 Meet in the middle 22
		7.10 PIE(inclusion - exclusion) 23
		7.11 LARGEST POWER OF K IN N! 23
		7.12 Binary Search 24
		7.13 Generating Permutations 24
		7.14 N Queen optimal 24

Modified By YUSUF REZA HASNAT**→ Useful Tips****→ Fast I/O**

```
C++:
ios_base::sync_with_stdio(false),
cin.tie(nullptr), cout.tie(nullptr);
```

Python:

```
import sys
input = sys.stdin.readline
sys.stdout.write("-----")
```

→ Random algorithm

```
#define accuracy
chrono::steady_clock::now().time_since_epoch(
).count()
```

```
mt19937 rng(accuracy);
int rand(int l, int r) {
    uniform_int_distribution<int> ludo(l, r);
    return ludo(rng);
}
```

→ Policy Based Data Structure

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
```

```
template <typename T> using o_set = tree<T,
null_type, less<T>, rb_tree_tag,
tree_order_statistics_node_update>;
```

```
// find_by_order(k) - returns an iterator to
// the k-th largest element (0 indexed);
// order_of_key(k)-the number of elements in
// the set that are strictly smaller than k;
```

1 Formula**1.1 Area Formulas**

Rectangle: $Area = length \times width$

Square: $Area = side \times side$

Triangle: $Area = \frac{1}{2} \times base \times height$

Circle: $Area = \pi \times radius^2$

Parallelogram: $Area = base \times height$

Pyramid Base: $Area = \frac{1}{2} \times base \times slant\ height$

Polygon :

$$(a) \quad Area = \frac{1}{2} \left| \sum_{i=1}^{n-1} (x_i y_{i+1} - x_{i+1} y_i) \right|$$

$$(b) \quad Area = a + \frac{b}{2} - 1 \quad (\text{for int coordinates})$$

here, a=#int points inside polygon
b=#int points outside polygon

1.2 Perimeter Formulas

Rectangle: $Perimeter = 2 \times (length + width)$

Square: $Perimeter = 4 \times side$

Triangle: $Perimeter = \text{sum of all sides}$

Circle: $Circumference = 2 \times \pi \times radius$

1.3 Volume Formulas

Cube: $Volume = side^3$

Rect Prism: $Volume = length \times width \times height$

Cylinder: $Volume = \pi \times radius^2 \times height$

Sphere: $Volume = \frac{4}{3} \times \pi \times radius^3$

Pyramid: $Volume = \frac{1}{3} \times base\ area \times height$

1.4 Surface Area Formulas

Cube: $Surface\ Area = 6 \times side^2$

Rectangular Prism:

$Surface\ Area = 2 \times (length \times width + length \times height + width \times height)$

Cylinder:

$Surface\ Area = 2 \times \pi \times radius \times (radius + height)$

Sphere: $Surface\ Area = 4 \times \pi \times radius^2$

Pyramid:

$Surface\ Area = base\ area +$

$\frac{1}{2} \times perimeter\ of\ base \times slant\ height$

Triangles

Side lengths: a, b, c

Semiperimeter: $p = \frac{a+b+c}{2}$

Area: $A = \sqrt{p(p-a)(p-b)(p-c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles):

$$ma = \frac{1}{2} * \sqrt{2b^2 + 2c^2 - a^2}$$

Length of bisector (divides angles in two):

$$sa = \sqrt{\frac{bc}{1 - \left(\frac{a}{b+c}\right)^2}}$$

1.5 Trigonometry

Law of sines: $\sin \frac{\alpha}{a} = \sin \frac{\beta}{b} = \sin \frac{\gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc \cos \alpha$

Law of tangents: $\frac{a+b}{a-b} = \frac{\tan \frac{\alpha+\beta}{2}}{\tan \frac{\alpha-\beta}{2}}$

$$\sin(A + B) = \sin A \cos B + \cos A \sin B$$

$$\cos(A + B) = \cos A \cos B - \sin A \sin B$$

$$\sin(A - B) = \sin A \cos B - \cos A \sin B$$

$$\cos(A - B) = \cos A \cos B + \sin A \sin B$$

$$\tan(A + B) = \frac{(\tan A + \tan B)}{(1 - \tan A \tan B)}$$

$$\tan(A - B) = \frac{(\tan A - \tan B)}{(1 + \tan A \tan B)}$$

Double Angle and Half Angle Formulas:

$$\sin 2\theta = 2 \sin \theta \cos \theta$$

$$\cos 2\theta = \cos^2 \theta - \sin^2 \theta$$

$$\tan 2\theta = \frac{(2 \tan \theta)}{(1 - \tan^2 \theta)}$$

$$\sin\left(\frac{\theta}{2}\right) = \pm \sqrt{\frac{1 - \cos \theta}{2}}$$

$$\cos\left(\frac{\theta}{2}\right) = \pm \sqrt{\frac{1 + \cos \theta}{2}}$$

$$\tan\left(\frac{\theta}{2}\right) = \frac{(1 - \cos \theta)}{\sin \theta}$$

$$\sin(r + w) = \sin r \cos w + \cos r \sin w$$

$$\cos(r + w) = \cos r \cos w - \sin r \sin w$$

$$\tan(r + w) = \frac{(\tan r + \tan w)}{(1 - \tan r \tan w)}$$

$$\sin r + \sin w = 2 \sin\left(\frac{r+w}{2}\right) \cos\left(\frac{r-w}{2}\right)$$

$$\cos r + \cos w = 2 \cos\left(\frac{r+w}{2}\right) \cos\left(\frac{r-w}{2}\right)$$

$$(V + W) \tan\left(\frac{r-w}{2}\right) = (V - W) \tan\left(\frac{r+w}{2}\right)$$

where V, W are lengths of sides opposite angles r, w.

$$a \cos x + b \sin x = r \cos(x - \phi)$$

$$a \sin x - b \cos x = r \sin(x - \phi)$$

where $r = \sqrt{a^2 + b^2}$, $\phi = \text{atan2}(b, a)$

1.6 Sum

$$c^k + c^{k+1} + \dots + c^n = c^{n+1} - c^k$$

// (c - 1) for c ≠ 1

$$1 + 2 + 3 + \dots + n = \frac{n * (n+1)}{2}$$

$$1^2 + 2^2 + \dots + n^2 = \frac{n * (n+1) * (2n+1)}{6}$$

$$1^3 + 2^3 + \dots + n^3 = \frac{n^2 * (n+1)^2}{4}$$

$$1^4 + 2^4 + \dots + n^4 = \frac{n * (n+1) * (2n+1) * (3n^2 + 3n - 1)}{30}$$

2 Number Theory

2.1 Prime number under 1000

2	3	5	7	11	13	17	19	23	29	31	37
41	43	47	53	59	61	67	71	73	79	83	89
97	101	103	107	109	113	127	131	137	139	149	
151	157	163	167	173	179	181	191	193	197	199	
211	223	227	229	233	239	241	251	257	263	269	
271	277	281	283	293	307	311	313	317	331	337	
347	349	353	359	367	373	379	383	389	397	401	
409	419	421	431	433	439	443	449	457	461	463	
467	479	487	491	499	503	509	521	523	541	547	
557	563	569	571	577	587	593	599	601	607	613	
617	619	631	641	643	647	653	659	661	673	677	
683	691	701	709	719	727	733	739	743	751	757	
761	769	773	787	797	809	811	821	823	827	829	
839	853	857	859	863	877	881	883	887	907	911	
919	929	937	941	947	953	967	971	977	983	991	
997											

2.2 Divisor Count

```
int maxVal = 1e6 + 1;
vector<int> countDivisor(maxVal, 0);
void countingDivisor(){
    for (int i = 1; i < maxVal; i++)
        for(int j= i; j<maxVal;j+= i)
            countDivisor[j]++;
}
```

// count the number of divisors of a number.

2.3 Leap year

```
bool isLeap(int n){
    if (n%100==0)
        if (n%400==0) return true;
        else return false;
    if (n%4==0) return true;
    else return false;
}
```

2.4 Num of Leap year in between

```
int calNum(int year) {
    return (year / 4) - (year / 100) +
        (year / 400);
}
int leapNum(int l, int r) {
    l--;
    return calNum(r) - calNum(l);
}
```

2.5 Power

```
int x = (int)(pow(base, power) + 1e-18);
```

2.6 BINARY EXPONENTIATION: (a^b)

```
int binaryExp(int base, int power, int MOD =
mod) {
    int res = 1;
    while (power) {
        if (power & 1)
            res = (res * base) % MOD;
        base = ((base%MOD) * (base%MOD)) %MOD;
        power /= 2;
    }
    return res;
}
```

2.7 BINARY EXPONENTIATION: (a^b^c)

```
int binaryExp(int base, int power, int
modulo){
    int ans = 1;
    while (power){
        if (power % 2 == 1)
            ans = (ans * base) % modulo;
        base = (base * base) % modulo;
        power /= 2;
    }
    return ans;
}
//function call:
binaryExp(a, binaryExp(b, c, mod-1), mod)
```

2.8 Check is prime number-O(sqrt(n))

```
bool prime(int n){
    if (n<2) return false;
    if (n<=3) return true;
    if (!(n%2) || !(n%3)) return false;
    for (int i=5; i*i<=n; i+=6){
        if (!(n%i) || !(n%(i+2)))
            return false;
    }
    return true;
}
```

2.9 Prime factorization-O(sqrt(n))

```
// smallest prime factor of a number.
```

```
int factor(int n){
    int a;
    if (n%2==0)
        return 2;
    for (a=3; a<=sqrt(n); a+=2){
        if (n%a==0)
            return a;
    }
    return n;
}
```

```
// complete factorization
```

```
int r;
while (n>1){
    r = factor(n);
    printf("%d", r);
    n /= r;
}
```

2.10 Seive

```
int prime[2e7 + 5];
void sieve(int n) {
    for (int i = 2; i <= n; i++) {
        prime[i] = 1;
    }
    for (int i = 4; i <= n; i += 2) {
        prime[i] = 0;
    }
    for (int i = 3; i * i <= n; i++) {
        if (prime[i]) {
            for (int j=i*i;j<=n;j+=i*2)
                prime[j] = 0;
        }
    }
}
```

2.11 smallest number in Seive

```
int factor[1000005];
// It will store the smallest prime factor of
a number.
void primeFactorSeive(int n) {
    for (int i = 2; i <= n; i++) {
        if (factor[i] == 0) {
            for (int j=i; j<=n; j+=i) {
                if (factor[j] == 0)
                    factor[j] = i;
            }
        }
    }
}
```

2.12 Bitwise Seive(memory efficient)

```
const int N = 3125005;
int prime[3125005];
bool is_set(int n, int pos) {
    if (n & (1 << pos))
        return true;
    return false;
}
int set_bit(int n, int pos) {
    return (n | (1 << pos));
}
void sieve() {
    for (int i = 0; i < 3125005; i++)
        prime[i] = 0;
    prime[0] = set_bit(0, 0);
    prime[0] = set_bit(prime[0], 1);
    for (int i = 4; i <= N; i += 2) {
        prime[i/32]=set_bit(prime[i/32],i%32);
    }
    for (int i = 3; i * i <= N; i += 2) {
        if (!is_set(prime[i/32],i%32)) {
            for (int j=i*i; j<=N; j+=2*i) {
                prime[j / 32] =
                    set_bit(prime[j / 32], j % 32);
            }
        }
    }
}
bool isPrime(int n) {
    if (!is_set(prime[n / 32], n % 32))
        return true;
    return false;
}
void solve() {
    for (int i = 2; i < 100; i++) {
        if (isPrime(i)) {
            cout << i << " -> OK!" << endl;
        }
    }
}
```

2.12 nth prime number

```
// Time complexity O(log(logn))
vector<int> nth_prime;
const int MX = 86200005;
bitset<MX> visited;
void optimized_prime() {
    nth_prime.push_back(2);
    for(int i=3; i<MX; i+=2){
        if(visited[i])
            continue;
        nth_prime.push_back(i);
        if(1ll*i*i > MX)
            continue;
        for(int j = i*i; j< MX; j+= i+i)
            visited[j] = true;
    }
}
```

2.13 Modular Operation**Addition:**

```
int mod_add(int a, int b, int MOD = mod){
    a = a % MOD, b = b % MOD;
    return ((a + b) % MOD) + MOD) % MOD;
}
```

Subtraction:

```
int mod_sub(int a, int b, int MOD = mod){
    a = a % MOD, b = b % MOD;
    return ((a - b) % MOD) + MOD) % MOD;
}
```

Multiplication:

```
int mod_mul(int a, int b, int MOD = mod){
    a = a % MOD, b = b % MOD;
    return ((a * b) % MOD) + MOD) % MOD;
}
```

Division:

```
//call binary Exponential Function here.
```

```
int mminvprime(int a, int b) { return
binaryExp(a, b - 2, b); }
```

```
//call modular multiplication here.
```

```
int mod_div(int a, int b, int MOD = mod) {
    a = a % MOD, b = b % MOD;
    return (mod_mul(a, mminvprime(b, MOD),
MOD) + MOD) % MOD;
}
```

```
//only for prime MOD
```

2.16 Factorial mod

```
//n! mod p : Here P is mod value
```

```
//For binaryExp we call 1.6 function
```

```
int factmod (int n, int p)
{
    int res = 1;
    while (n > 1){
        res=(res*binaryExp(p-1,n/p,p))%p;
        for (int i=2; i<=n%p; ++i)
            res=(res*i) %p;
        n /= p;
    }
    return int (res % p);
}
```

2.14 nCr(more space, less time)

```
int mod = 1e9 + 7;
const int MAX = 1e7 + 5;
vector<int> fact(MAX), ifact(MAX), inv(MAX);
void factorial() {
    inv[1] = fact[0] = ifact[0] = 1;
    for (int i = 2; i < MAX; i++)
        inv[i]=inv[mod%i]*(mod-mod/i)%mod;
    for (int i = 1; i < MAX; i++)
        fact[i] = (fact[i - 1] * i) % mod;
    for (int i = 1; i < MAX; i++)
        ifact[i]=ifact[i-1]*inv[i] % mod;
}

int nCr(int n, int r) {
    if (r < 0 || r > n)
        return 0;
    return (int)fact[n] * ifact[r] % mod *
ifact[n - r] % mod;
}
```

```
// first call factorial() function
// then for nCr just call nCr(n,r)
```

2.15 nCr(less space, more time)

```
const int MOD = 1e9 + 7;
const int MAX = 1e7+10;
vector<int> fact(MAX), inv(MAX);
void factorial(){
    fact[0] = 1;
    for (int i = 1; i < MAX; i++)
        fact[i] = (i * fact[i - 1]) % MOD;
}
```

```
int bigmod(int a, int n, int M = MOD){
    int res = 1;
    while (n){
        if (n & 1)
            res = (res * a) % M;
        a = (a * a) % M, n /= 2;
    }
    return res;
}
```

```
void inverse(){
    for (int i = 0; i < MAX; ++i)
        inv[i] = bigmod(fact[i], MOD - 2);
}
```

```
int nCr(int a, int b){
    if (a < b or a < 0 or b < 0)
        return 0;
    int de = (inv[b] * inv[a - b]) % MOD;
    return (fact[a] * de) % MOD;
}
```

```
// nCr ends here
```

```
int ModInv(int a, int M){
    return bigmod(a, M - 2, M);
}
```

2.17 Generate combinations

// n>=m, choose M numbers from 1 to N.

```
void combination(int n, int m){
    if (n<m) return ;
    int a[50]= {0};
    int k=0;
    for (int i=1; i<=m; i++) a[i]=i;
    while (true){
        for (int i=1; i<=m; i++)
            cout << a[i] << " ";
        cout << endl;
        k=m;
        while ((k>0) && (n-a[k]==m-k)) k--;
        if (k==0) break;
        a[k]++;
        for (int i=k+1; i<=m; i++)
            a[i]=a[i-1]+1;
    }
}
```

2.18 Binomial coefficient

#define MAXN 100 // largest n or m

long binomial_coefficient(n,m)

// compute n choose m

```
{
    int i,j;
    long bc[MAXN][MAXN];
    for (i=0; i<=n; i++) bc[i][0] = 1;
    for (j=0; j<=n; j++) bc[j][j] = 1;
    for (i=1; i<=n; i++)
        for (j=1; j<i; j++)
            bc[i][j]=bc[i-1][j-1]+ bc[i-1][j];
    return bc[n][m];
}
```

2.19 10-ary to m-ary

```
char a[16]={'0','1','2','3','4','5','6','7',
           '8','9','A','B','C','D','E','F'};
```

```
string tenToM(int n, int m){
    int temp=n;
    string result="";
    while (temp!=0){
        result=a[temp%m]+result;
        temp/=m;
    }
    return result;
}
```

2.20 m-ary to 10-ary

```
string num = "0123456789ABCDE";
int mToTen(string n, int m){
    int multi=1;
    int result=0;
    for (int i=n.size()-1; i>=0; i--) {
        result += num.find(n[i])*multi;
        multi*=m;
    }
    return result;
}
```

2.21 Catalan numbers

Cn =

$$\frac{nX-1}{k=0} \frac{CkCn-1-k}{1} \frac{n+1}{n} \frac{n}{k} (1)$$

The first terms of this sequence are 2, 5, 14, 42, 132, 429, 1430 when C0 = 1. This is the number of ways to build a balanced

formula from n sets of left and right parentheses. It is also the number of triangulations of a convex polygon, the number of

rooted binary trees on n + 1 leaves and the number of paths across a lattice which do not rise above the main diagonal.

2.22 Euler's totient function

// the positive integers less than or equal to n that are relatively prime to n.

```
int phi (int n){
    int result = n;
    for (int i=2; i*i<=n; ++i)
        if(n%i==0){
            while(n%i==0)
                n /= i;
            result -= result / i;
        }
    if (n > 1)
        result -= result / n;
    return result;
}
```

2.23 EXT_GCD

// return {x,y} such that ax+by=gcd(a,b)

```
pair<int,int>ext_gcd(int a, int b){
    if (b == 0)
        return {1, 0};
    else{
        pair<int,int> tmp=ext_gcd(b, a % b);
        return {tmp.second,
                tmp.first - (a / b) * tmp.second};
    }
}
```

2.24 Power Set

```
void printPowerSet(char* set, int setSz) {
    // Setsize of power set of a set with
    // setsize. n is (2^n-1)
    unsigned int powSetSz = pow(2, setSz);
    int i, j; // i as counter
    // Run from i 000..0 to 111..1
    for (i = 0; i < powSetSz; i++) {
        for (j = 0; j < setSz; j++) {
            //Check if jth bit in the counter is set
            //If set then print jth element from set
        }
    }
}
```

```

        if (i & (1 << j))
            cout << set[j];
    }
    cout << endl;
}
}

2.25 Bitset DS
    bitset<2>arr;
    arr[0]=1, arr[1]=0;
    cout<<arr<<endl<<endl; ///<01
    /// int to binary/bitset and vise-versa
    bitset<4>a(8) ;
    cout<<a<<endl;    ///<1000
    int n=(int)a.to_ulong();
    cout<<n<<endl<<endl;    ///<8 (back into
int)
    /// string to bitset
    string str="1010110100";
    bitset<10>b(str); cout<<b[0]<<"
    "<<b[2]<<endl;    ///<0 1
    string new_str=b.to_string();
    cout<<new_str<<endl;    ///<1010110100
    ///count the no of Ones
    cout<<b.count()<<endl<<endl;
    ///basic operations
    bitset<4>a1(string("0101"));
    bitset<4>b1(string("1010"));
    cout<<(a1 & b1)<<endl;
    cout<<(b1<<1)<<endl<<endl;
    /// streams in bitset
    string str1="10 101101 10";
    istringstream stream(str1);
    bitset<2>s1; bitset<6>s2;
    stream>>s1; cout<<s1<<endl;    ///<10
    stream>>s2; cout<<s2<<endl<<endl;
    ///<101101

    ///check if any bit is set
    bitset<4>a2(string("1101"));
    cout<<a2.any()<<endl;    ///

```

3 Algorithms

3.1 Big Integer Operation

```

struct BigInteger {
    string str;
    /// Constructor to initialize
    /// BigInteger with a string
    BigInteger(string s) { str = s; }
    /// Overload + operator to add
    /// two BigInteger objects
    BigInteger operator+(const BigInteger& b)
    {
        string a = str, c = b.str;
        int alen=a.length(), clen=c.length();
        int n = max(alen, clen);
        if (alen > clen)
            c.insert(0, alen - clen, '0');
        else if (alen < clen)
            a.insert(0, clen - alen, '0');
        string res(n + 1, '0');
        int carry = 0;
        for (int i = n - 1; i >= 0; i--) {
            int digit=(a[i]-'0')+(c[i]-'0')
                +carry;
            carry = digit / 10;
            res[i + 1] = digit % 10 + '0';
        }
        if (carry == 1) {
            res[0] = '1';
            return BigInteger(res);
        }
        else
            return BigInteger(res.substr(1));
    }

    /// Overload - operator to subtract
    /// first check which number is greater
    and then subtract
    BigInteger operator-(const BigInteger& b)
    {
        string a = str;
        string c = b.str;
        int alen=a.length(), clen=c.length();
        int n = max(alen, clen);
        if (alen > clen)
            c.insert(0, alen - clen, '0');
        else if (alen < clen)
            a.insert(0, clen - alen, '0');
        if (a < c) {
            swap(a, c);
            swap(alen, clen);
        }
        string res(n, '0');
        int carry = 0;
        for (int i = n - 1; i >= 0; i--) {
            int digit =(a[i]-'0')-(c[i]-'0')
                - carry;
            if (digit < 0) {
                digit += 10;
                carry = 1;
            }
            else {
                carry = 0;
            }
            res[i] = digit + '0';
        }
        /// remove leading zeros
        int i = 0;

```

```

    while (i < n && res[i] == '0')
        i++;
    if (i == n)
        return BigInteger("0");
    return BigInteger(res.substr(i));
}

// Overload * operator to multiply
// two BigInteger objects
BigInteger operator*(const BigInteger& b)
{
    string a = str, c = b.str;
    int alen=a.length(), clen=c.length();
    int n = alen + clen;
    string res(n, '0');
    for (int i = alen - 1; i >= 0; i--) {
        int carry = 0;
        for(int j=clen-1; j>=0; j--) {
            int digit = (a[i] - '0') *
            (c[j-'0'])+(res[i+j+1]-'0')+carry;
            carry = digit / 10;
            res[i+j+1]=digit % 10 + '0';
        }
        res[i] += carry;
    }
    int i = 0;
    while (i < n && res[i] == '0')
        i++;
    if (i == n)
        return BigInteger("0");
    return BigInteger(res.substr(i));
}

// Overload << operator to output
// BigInteger object
friend ostream& operator<<(ostream& out,
const BigInteger& b) {
    out << b.str;
    return out;
}
};

3.2 Find rank k in array
int find(int l, int r, int k){
    int i=0,j=0,x=0,t=0;
    if (l==r) return a[l];
    x=a[(l+r)/2];
    t=a[x];
    a[x]=a[r];
    a[r]=t;
    i=l-1;
    for (int j=l; j<=r-1; j++)
        if (a[j]<=a[r]){
            i++;
            t=a[i];
            a[i]=a[j];
            a[j]=t;
        }
    i++;
    t=a[i];
    a[i]=a[r];
    a[r]=t;
    if (i==k) return a[i];
    if (i<k) return find(i+1, r,k);
    return find(l, i-1, k);
}

```

3.3 InfixToPostFix

```

int prec(char c) {
    if (c == '^')
        return 3;
    else if (c == '*' || c == '/')
        return 2;
    else if (c == '+' || c == '-')
        return 1;
    else
        return -1;
    // for open brackets. coz we have to pop
    // until we find an opening bracket.
}

string infixtopostfix(string s) {
    stack<char> st;
    string res = "";
    for (int i = 0; i < s.length(); i++) {
        if ((s[i] >= 'a' && s[i] <= 'z') ||
            (s[i] >= 'A' && s[i] <= 'Z')){
            res = res + s[i];
        }
        else if (s[i] == '(')
            st.push(s[i]);
        else if (s[i] == ')') {
            while(st.size()&&st.top() != '('){
                res = res + st.top();
                st.pop();
            }
            if (!st.empty())
                st.pop();
        }
        else {
            while (!st.empty() &&
                prec(st.top()) > prec(s[i])) {
                res = res + st.top();
                st.pop();
            }
            st.push(s[i]);
        }
    }
    while (!st.empty()) {
        res = res + st.top();
        st.pop();
    }
    return res;
}

```

3.4 Postfix calculation

```

float scanNum(char ch) {
    int value = ch;
    return float(value - '0');
    // return float from character
}

int isOperator(char ch) {
    // Check for operator
    if (ch == '+' || ch == '-' || ch == '*'
        || ch == '/' || ch == '^')
        return 1;
    return -1;
}

int isOperand(char ch) {
    // Check for operand
    if (ch >= '0' && ch <= '9')
        return 1;
    return -1;
}

```



```

float operation(int a, int b, char op) {
    // Perform operation
    if (op == '+')
        return b + a;
    else if (op == '-')
        return b - a;
    else if (op == '*')
        return b * a;
    else if (op == '/')
        return b / a;
    else if (op == '^')
        return pow(b, a); // find b^a
    else
        return INT_MIN;
}

float postfixEval(string postfix) {
    int a, b;
    stack<float> stk;
    string::iterator it;
    for (it = postfix.begin(); it !=
        postfix.end(); it++) {
        if (isOperator(*it) != -1) {
            a = stk.top();
            stk.pop();
            b = stk.top();
            stk.pop();
            stk.push(operation(a, b, *it));
        }
        else if (isOperand(*it) > 0) {
            stk.push(scanNum(*it));
        }
    }
    return stk.top();
}

```

3.5 2D prefix sum

```

class NumMatrix {
    int row, col;
    vector<vector<int>> sums;
public:
    NumMatrix(vector<vector<int>> &matrix) {
        row = matrix.size();
        col = row > 0 ? matrix[0].size() : 0;
        sums = vector<vector<int>>(row+1,
            vector<int>(col+1, 0));
        for(int i=1; i<=row; i++) {
            for(int j=1; j<=col; j++) {
                sums[i][j] =
                    matrix[i-1][j-1] +
                    sums[i-1][j] +
                    sums[i][j-1] -
                    sums[i-1][j-1] ;
            }
        }

        int sumRegion(int row1, int col1,
            int row2, int col2) {
            return sums[row2+1][col2+1] -
                sums[row2+1][col1] -
                sums[row1][col2+1] +
                sums[row1][col1];
        }
    };
}

```

3.6 KMP Algorithm-O(n+m)

```

vector<int> createLPS(string pattern) {
    int n = pattern.length(), idx = 0;
    vector<int> lps(n);
    for (int i = 1; i < n; i++) {
        if (pattern[idx] == pattern[i]) {
            lps[i] = idx + 1;
            idx++;
        }
        else {
            if (idx != 0)
                idx = lps[idx - 1];
            else
                lps[i] = idx, i++;
        }
    }
    return lps;
}

int kmp(string text, string pattern) {
    int cnt_of_match = 0, i = 0, j = 0;
    vector<int> lps = createLPS(pattern);
    while (i < text.length()) {
        if (text[i] == pattern[j])
            i++, j++; // i->text, j->pattern
        else {
            if (j != 0)
                j = lps[j - 1];
            else
                i++;
        }
        if (j == pattern.length()) {
            cnt_of_match++;
            // the index where match found ->
            (i - pattern.length());
            j = lps[j - 1];
        }
    }
    return cnt_of_match;
}

3.7 Kadane's Algorithm O(n)
// return maximum subarray sum.
int maxSubArraySum(vector<int> &a) {
    int size = a.size();
    int maxTill = INT_MIN, maxEnd = 0;
    for (int i = 0; i < size; i++) {
        maxEnd = maxEnd + a[i];
        if (maxTill < maxEnd)
            maxTill = maxEnd;
        if (maxEnd < 0)
            maxEnd = 0;
    }
    return maxTill;
}

```

4 Data Structure

4.1 SEGMENT TREE

```
class SEGMENT_TREE {
public:
    vector<int> v;
    vector<int> seg;
    SEGMENT_TREE(int n) {
        v.resize(n + 5);
        seg.resize(4 * n + 5);
    }
    //! initially: ti = 1, low = 1, high = n
    (number of elements in the array);
    void build(int ti, int low, int high) {
        if (low == high) {
            seg[ti] = v[low];
            return;
        }
        int mid = (low + high) / 2;
        build(2 * ti, low, mid);
        build(2 * ti + 1, mid + 1, high);
        seg[ti] = (seg[2*ti] + seg[2*ti+1]);
    }
    //! initially: ti = 1, low = 1, high = n
    (number of elements in the array),
    (ql & qr)=user input in 1 based index;
    int find(int ti, int tl, int tr, int ql,
             int qr) {
        if (tl > qr || tr < ql) {
            return 0;
        }
        if (tl >= ql and tr <= qr)
            return seg[ti];
        int mid = (tl + tr) / 2;
        int l = find(2*ti, tl, mid, ql, qr);
        int r = find(2*ti+1, mid+1, tr, ql, qr);
        return (l + r);
    }
    //! initially: ti = 1, tl = 1, tr = n
    (number of elements in the array),
    id = user input in 1 based indexing,
    val = updated value;
    void update(int ti, int tl, int tr, int
               id, int val) {
        if (id > tr or id < tl)
            return;
        if (id == tr and id == tl) {
            seg[ti] = val;
            return;
        }
        int mid = (tl + tr) / 2;
        update(2 * ti, tl, mid, id, val);
        update(2*ti+1, mid + 1, tr, id, val);
        seg[ti] = (seg[2*ti] + seg[2*ti + 1]);
    }
};
// use 1 based indexing for input and queries
and update;
```

4.2 FENWICK TREE

```
// Sum
struct FenwickTree {
    vector<int> bit; // binary indexed tree
    int n;
    FenwickTree(int n) {
        this->n = n;
        bit.assign(n, 0);
    }
    FenwickTree(vector<int> a):
        FenwickTree(a.size()) {
        for (size_t i=0; i < a.size(); i++)
            add(i, a[i]);
    }
    int sum(int r) {
        int ret = 0;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            ret += bit[r];
        return ret;
    }
    int sum(int l, int r) {
        return sum(r) - sum(l - 1);
    }
    void add(int idx, int delta) {
        for (; idx < n; idx = idx | (idx + 1))
            bit[idx] += delta;
    }
};

// minimum
struct FenwickTreeMin {
    vector<int> bit;
    int n;
    const int INF = (int)1e9;
    FenwickTreeMin(int n) {
        this->n = n;
        bit.assign(n, INF);
    }
    FenwickTreeMin(vector<int> a) :
        FenwickTreeMin(a.size()) {
        for (size_t i=0; i < a.size(); i++)
            update(i, a[i]);
    }
    int getmin(int r) {
        int ret = INF;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            ret = min(ret, bit[r]);
        return ret;
    }
    void update(int idx, int val) {
        for (; idx < n; idx = idx | (idx + 1))
            bit[idx] = min(bit[idx], val);
    }
};



### 4.3 SEGMENT TREE LAZY


const int N = 1e5 + 100;
int tree[N << 2], lz[N << 2];
void propagate(int u, int st, int en) {
    if (!lz[u])
        return;
    tree[u] += lz[u] * (en - st + 1);
    if (st != en) {
        lz[2 * u] += lz[u];
        lz[2 * u + 1] += lz[u];
    }
    lz[u] = 0;
}
```

```

void update(int u, int st, int en, int l,
            int r, int x) {
    propagate(u, st, en);
    if (r < st or en < l)
        return;
    else if (st >= l and en <= r) {
        lz[u] += x;
        propagate(u, st, en);
    }
    else {
        int mid = (st + en) >> 1;
        update(2 * u, st, mid, l, r, x);
        update(2 * u + 1, mid + 1, en, l, r, x);
        tree[u] = tree[2 * u] + tree[2 * u + 1];
    }
}

int query(int u, int st, int en, int l, int r) {
    propagate(u, st, en);
    if (r < st or en < l)
        return 0;
    else if (st >= l and en <= r)
        return tree[u];
    else {
        int mid = (st + en) >> 1;
        int left = query(2 * u, st, mid, l, r);
        int right = query(2 * u + 1, mid + 1, en, l, r);
        return left + right;
    }
}

```

4.5 TRIE

```

class TrieNode {
public:
    int isEnd;
    TrieNode *child[26];
    TrieNode() {
        isEnd = 0;
        for (int i = 0; i < 26; i++)
            child[i] = NULL;
    }
};

class Trie {
    TrieNode *root;

public:
    Trie() : root(new TrieNode()) {}
    void insert(string word) {
        TrieNode *curr = root;
        for (char ch : word) {
            if (curr->child[ch - 'a'] == NULL)
                curr->child[ch - 'a'] =
                    new TrieNode();
            curr = curr->child[ch - 'a'];
        }
        curr->isEnd++;
    }
    bool search(string word) {
        TrieNode *curr = root;
        for (char ch : word) {
            if (curr->child[ch - 'a'] == NULL)
                return false;
            curr = curr->child[ch - 'a'];
        }
        return curr->isEnd;
    }
    bool startsWith(string prefix) {
        TrieNode *curr = root;

```

```

        for (char ch : prefix) {
            if (curr->child[ch - 'a'] == NULL)
                return false;
            curr = curr->child[ch - 'a'];
        }
        return true;
    }
    bool isJunc(TrieNode *curr) {
        for (int i = 0; i < 26; i++) {
            if (curr->child[i] != NULL)
                return true;
        }
        return false;
    }
    // 1 means junction delete kore asche
    bool dlt(string s, int idx,
             TrieNode *curr) {
        if (idx >= s.size())
            return 0;
        if (idx == s.size() - 1) {
            if (isJunc(curr->child[s[idx] -
                                   'a'])) {
                curr->child[s[idx] -
                           'a']->isEnd = 0;
                return false;
            }
            else {
                delete curr->child[s[idx] - 'a'];
                curr->child[s[idx] - 'a'] = NULL;
                return true;
            }
        }
        bool res = dlt(s, idx + 1,
                       curr->child[s[idx] - 'a']);
        if (res) {
            if (isJunc(curr->child[s[idx] - 'a']))
                return false;
            else if (!curr->child[s[idx] -
                                   'a']->isEnd) {
                delete curr->child[s[idx] - 'a'];
                curr->child[s[idx] - 'a'] = NULL;
                return true;
            }
        }
        return false;
    }
    bool dlt(string s) {
        if (search(s)) {
            dlt(s, 0, root);
            return true;
        }
        return false;
    }
    void print(string start, TrieNode *curr) {
        if (curr->isEnd)
            cout << start << endl;
        for (int i = 0; i < 26; i++) {
            if (curr->child[i] != NULL) {
                start.push_back(i + 'a');
                print(start, curr->child[i]);
                start.pop_back();
            }
        }
    }
    void print() { print("", root); }
};

```

4.6 DSU

```

class DisjointSet{
    vector<int> par, sz, minElmt, maxElmt,
    cntElmt;

public:
    DisjointSet(int n){
        par.resize(n + 1);
        sz.resize(n + 1, 1);
        minElmt.resize(n + 1);
        maxElmt.resize(n + 1);
        cntElmt.resize(n + 1, 1);
        for (int i = 1; i <= n; i++)
            par[i]=minElmt[i]=maxElmt[i]=i;
    }
    int findUPar(int u) {
        if (u == par[u])
            return u;
        return par[u] = findUPar(par[u]);
    }
    void unionBySize(int u, int v){
        int pU = findUPar(u);
        int pV = findUPar(v);
        if (pU == pV)
            return;
        if (sz[pU] < sz[pV])
            swap(pU, pV);
        par[pV] = pU;
        sz[pU] += sz[pV];
        cntElmt[pU] += cntElmt[pV];
        minElmt[pU] = min(minElmt[pU],
                           minElmt[pV]);
        maxElmt[pU] = max(maxElmt[pU],
                           maxElmt[pV]);
    }
    int getMinElementIntheSet(int u){
        return minElmt[findUPar(u)];
    }
    int getMaxElementIntheSet(int u){
        return maxElmt[findUPar(u)];
    }
    int getNumofElementIntheSet(int u){
        return cntElmt[findUPar(u)];
    }
};

```

5 Dynamic Programming**5.1 LCS $O(n*m)$**

```

int dp[1001][1001];
int lcs(const string &s, const string &t){
    int m = s.size(), n = t.size();
    if (m == 0 || n == 0) return 0;
    for (int i=0; i<=m; ++i)
        dp[i][0] = 0;
    for (int j=1; j<=n; ++j)
        dp[0][j] = 0;
    for (int i=0; i<m; ++i)
        for (int j=0; j<n; ++j)
            if (s[i] == t[j])
                dp[i+1][j+1] = dp[i][j]+1;
            else
                dp[i+1][j+1]=
                    max(dp[i+1][j], dp[i][j+1]);
    return dp[m][n];
}

```

5.2 MCM $O(n^3)$

```

const int N = 1005;
vector<int> v;
int dp[N][N], mark[N][N];
int MCM(int i, int j) {
    if (i == j)
        return dp[i][j] = 0;
    if (dp[i][j] != -1)
        return dp[i][j];
    int mn = INT_MAX;
    for (int k = i; k < j; k++) {
        int x = mn;
        mn = min(mn, MCM(i, k) + MCM(k + 1,
j) + v[i - 1] * v[k] * v[j]);
        if (x != mn)
            mark[i][j] = k;
    }
    return dp[i][j] = mn;
}

void print_order(int i, int j) {
    if (i == j)
        cout << "X" << i;
    else {
        cout << "(";
        print_order(i, mark[i][j]);
        print_order(mark[i][j] + 1, j);
        cout << ")";
    }
}

// memset(dp, -1, sizeof dp);
// print_order(1, n);

```

5.3 LIS $O(n^2)$

```

int n=0;
int a[100]={0},f[100]= {0},x[100]={0};
int main(void){
    cin >> n;
    for (int i=1; i<=n; i++){
        cin >> a[i];
        x[i]=INT_MAX;
    }
    f[0]=0;
    int ans=0;
    for(int i=1; i<=n; i++){
        int l=0, r=i;
        while (l+1<r){
            int m=(l+r)/2;
            if (x[m]<a[i]) l=m;
            else r=m;
        }
        // change to x[m]<=a[i] for non-decre case
        f[i]=l+1;
        x[l+1]=a[i];
        if (f[i]>ans) ans=f[i];
    }
    cout << ans << endl;
    return 0;
}

vector<int> findLIS(){
    vector<int> result;
    result.push_back(0);
    vector<int> sequence(n, -1);
    for (int i = 1; i < n; i++){
        if (arr[i] > arr[result.back()]){
            sequence[i] = result.back();
            result.push_back(i);
        }
        else{
            int l = 0, h=result.size() - 1;
            int optimal = 0;
            while (l <= h){
                int mid = (l + h) / 2;
                if(arr[result[mid]]<= arr[i])
                    l = mid + 1;
                else
                    optimal=mid,h=mid-1;
            }
            if (optimal > 0){
                sequence[i]=result[optimal-1];
            }
            result[optimal] = i;
        }
    }
    vector<int> lis;
    int last = result.back();
    while (last != -1){
        lis.push_back(arr[last]);
        last = sequence[last];
    }
    reverse(lis.begin(), lis.end());
    return lis;
}

```

5.4 LCIS $O(n * m)$

```

int a[100]= {0}, b[100]= {0}, f[100]= {0};
int n=0, m=0;
int main(void){
    cin >> n;
    for (int i=1; i<=n; i++) cin >> a[i];
    cin >> m;
    for (int i=1; i<=m; i++) cin >> b[i];
    for (int i=1; i<=n; i++){
        int k=0;
        for (int j=1; j<=m; j++){
            if (a[i]>b[j] && f[j]>k)
                k=f[j];
            else if (a[i]==b[j] && k+1>f[j])
                f[j]=k+1;
        }
    }
    int ans=0;
    for (int i=1; i<=m; i++)
        if (f[i]>ans) ans=f[i];
    cout << ans << endl;
    return 0;
}

```

5.5 Maximum submatrix

```

int a[150][150]= {0};
int c[200]= {0};
int maxarray(int n){
    int b=0, sum=-100000000;
    for (int i=1; i<=n; i++){
        if (b>0) b+=c[i];
        else b=c[i];
        if (b>sum) sum=b;
    }
    return sum;
}

int maxmatrix(int n){
    int sum=-100000000, max=0;
    for (int i=1; i<=n; i++){
        for (int j=1; j<=n; j++){
            c[j]=0;
            for (int j=i; j<=n; j++){
                for (int k=1; k<=n; k++){
                    c[k]+=a[j][k];
                    max=maxarray(n);
                    if (max>sum) sum=max;
                }
            }
        }
    }
    return sum;
}

int main(void){
    int n=0;
    cin >> n;
    for (int i=1; i<=n; i++)
        for (int j=1; j<=n; j++)
            cin >> a[i][j];
    cout << maxmatrix(n);
    return 0;
}

```

5.6 SOS DP

```
// # of elements in the list for which you //
want to find the sum over all subsets
int n = 20;
// the list for which you want to find the //
sum over all subsets
vector<int> a(1 << n);

//answer for sum over subsets of each subset
vector<int> sos(1 << n);

for (int i = 0; i < (1 << n); i++) {
    // iterate over all other sets and
    checks whether they're a subset of i
    for (int j = 0; j < (1 << n); j++) {
        if ((i & j) == j) {
            sos[i] += a[j];
        }
    }
}
```

5.7 Depth and width of tree

```
int l[100]= {0}, int r[100]= {0};
stack<int> mystack;
int n = 0, w = 0, d = 0;
int depth(int n){
    if (l[n]==0 && r[n]==0)
        return 1;
    int depthl=depth(l[n]);
    int depthr=depth(r[n]);
    int dep=depthl>depthr ? depthl:depthr;
    return dep+1;
}
void width(int n){
    if (n<=d){
        int t=0,x;
        stack<int> tmpstack;
        while (!mystack.empty()){
            x=mystack.top();
            mystack.pop();
            if (x!=0){
                t++;
                tmpstack.push(l[x]);
                tmpstack.push(r[x]);
            }
        }
        w=w>t?w:t;
        mystack=tmpstack;
        width(n+1);
    }
}
int main(void){
    cin >> n;
    for (int i=1; i<=n; i++){
        cin >> l[i] >> r[i];
    }
    d=depth(1);
    mystack.push(1);
    width(1);
    cout << w << " " << d << endl;
    return 0;
}
```

6 Graph Theory**6.1 SPFA – Optimal BF $O(V * E)$**

```
int q[3001]= {0}; // queue for node
int d[1001]= {0}; // record shortest path
from start to ith node
bool f[1001]= {0};
int a[1001][1001]= {0}; // adjacency list
int w[1001][1001]= {0}; // adjacency matrix
int main(void) {
    int n=0, m=0;
    cin >> n >> m;
    for (int i=1; i<=m; i++){
        int x=0, y=0, z=0;
        cin >> x >> y >> z;
        // node x to node y has weight z
        a[x][0]++;
        a[x][a[x][0]]=y;
        w[x][y]=z;
    }
    /*
    // for undirected graph
    a[x][0]++;
    a[y][a[y][0]]=x;
    w[y][x]=z;
    */
}
int s=0, e=0;
cin >> s >> e; // s: start, e: end
SPFA(s);
cout << d[e] << endl;
return 0;
}
void SPFA(int v0){
    int t,h,u,v;
    for (int i=0; i<1001; i++) d[i]=INT_MAX;
    for (int i=0; i<1001; i++) f[i]=false;
    d[v0]=0;
    h=0;
    t=1;
    q[1]=v0;
    f[v0]=true;
    while (h!=t){
        h++;
        if (h>3000) h=1;
        u=q[h];
        for (int j=1; j<=a[u][0]; j++){
            v=a[u][j];
            if (d[u]+w[u][v]<d[v]) // change
            to > if calculating longest path
            {
                d[v]=d[u]+w[u][v];
                if (!f[v]){
                    t++;
                    if (t>3000) t=1;
                    q[t]=v;
                    f[v]=true;
                }
            }
        }
        f[u]=false;
    }
}
```

6.2 Dijkstra $O(V + E \log V)$

```

map<int, vector<pair<int, int>>> m;
map<int, int> dist;
#define pairi pair<int, int>

void dijkstra(int src, int n) {
    priority_queue<pairi, vector<pairi>,
greater<pairi>> pq;
    pq.push({0, src});
    dist[src] = 0;
    vector<int> dis(n, inf);
    dis[src] = 0;
    while (!pq.empty()) {
        int u = pq.top().second;
        pq.pop();
        for (int i=0; i<m[u].size(); i++) {
            int wt = m[u][i].second;
            int v = m[u][i].first;
            if (dis[v] > dis[u] + wt) {
                dis[v] = dis[u] + wt;
                pq.push({dis[v], v});
                dist[v] = dis[u] + wt;
            }
        }
    }
}

```

6.3 BellmanFord $O(V.E)$

```

vector<int> dist;
vector<int> parent;
vector<vector<pair<int, int>>> adj;
// resize the vectors from main function

void bellmanFord(int num_of_nd, int src) {
    dist[src] = 0;
    for (int step=0; step<num_of_nd; step++) {
        for (int i = 1; i<=num_of_nd; i++) {
            for (auto it : adj[i]) {
                int u = i;
                int v = it.first;
                int wt = it.second;
                if (dist[u] != inf &&
((dist[u] + wt) < dist[v])) {
                    if (step==num_of_nd - 1){
                        cout << "Negative
cycle found\n";
                        return;
                    }
                    dist[v] = dist[u] + wt;
                    parent[v] = u;
                }
            }
        }
    }
    for (int i = 1; i <= num_of_nd; i++)
        cout << dist[i] << " ";
    cout << endl;
}

```

6.4 Floyd-Warshall algorithm $O(n^3)$

```

typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;

typedef vector<int> VI;
typedef vector<VI> VVI;

bool FloydWarshall (VVT &w, VVI &prev){
    int n = w.size();
    prev = VVI (n, VI(n, -1));

    for (int k = 0; k < n; k++){
        for (int i = 0; i < n; i++){
            for (int j = 0; j < n; j++){
                if (w[i][j] > w[i][k] + w[k][j]){
                    w[i][j] = w[i][k] + w[k][j];
                    prev[i][j] = k;
                }
            }
        }
    }

    // check for negative weight cycles
    for(int i=0;i<n;i++)
        if (w[i][i] < 0) return false;
    return true;
}

```

6.5 Topological sort

```

map<string, vector<string>> adj;
map<string, int> degree;
set<string> nodes;
vector<string> ans;
// adj: graph input, degree: cnt indegree,
// node: unique nodes, ans: path

int c = 0;
void topo_sort() {
    queue<string> qu;
    // traverse all the nodes and check if its
    degree is 0 or not..
    for (string i : nodes) {
        if (degree[i] == 0) {
            qu.push(i);
        }
    }
    while (!qu.empty()) {
        string top = qu.front();
        qu.pop();
        ans.push_back(top);
        for (string i : adj[top]) {
            degree[i]--;
            if (degree[i] == 0) {
                qu.push(i);
            }
        }
    }
}

```

6.6 Kruskal $O(E \log E)$

```

typedef pair<int, int> edge;

class Graph {
    vector<pair<int, edge>> G, T;
    vector<int> parent;
    int cost = 0;

public:
    Graph(int n) {
        for (int i = 0; i < n; i++)
            parent.push_back(i);
    }

    void add_edges(int u, int v, int wt) {
        G.push_back({wt, {u, v}});
    }

    int find_set(int n) {
        if (n == parent[n])
            return n;
        else
            return find_set(parent[n]);
    }

    void union_set(int u, int v) {
        parent[u] = parent[v];
    }

    void kruskal() {
        sort(G.begin(), G.end());
        for (auto it : G) {
            int uRep = find_set(it.second.first);
            int vRep = find_set(it.second.second);
            if (uRep != vRep) {
                cost += it.first;
                T.push_back(it);
                union_set(uRep, vRep);
            }
        }

        int get_cost() { return cost; }
        void print() {
            for (auto it : T)
                cout << it.second.first << " "
                    << it.second.second << "->"
                    << it.first << endl;
        }
    };

    // g.add_edges(u, v, wt);
    // g.kruskal();

```

6.7 Prim – MST $O(E \log V)$

```

typedef pair<int, int> pii;

class Prims {
    map<int, vector<pii>> graph;
    map<int, int> visited;

public:
    void addEdge(int u, int v, int w) {
        graph[u].push_back({v, w});
        graph[v].push_back({u, w});
    }

    vector<int> path(pii start) {
        vector<int> ans;
        priority_queue<pii, vector<pii>,
            greater<pii>> pq;
        // cost vs node
        pq.push({start.second, start.first});
        while (!pq.empty()) {
            pair<int, int> curr = pq.top();
            pq.pop();
            if (visited[curr.second])
                continue;
            visited[curr.second] = 1;
            ans.push_back(curr.second);
            for (auto i : graph[curr.second]) {
                if (visited[i.first])
                    continue;
                pq.push({i.second, i.first});
            }
        }
        return ans;
    }
};

```

6.8 Eulerian circuit $O(V+E)$

```

unordered_map<int, int> Start, End, Val;
unordered_map<int, pair<int, int>> Range;
int start = 0;
void dfs(int node) {
    visited[node] = true;
    Start[node] = start++;
    for (auto child : adj[node]) {
        if (!visited[child])
            dfs(child);
    }
    End[node] = start - 1;
}
dfs(1);
vector<int> FlatArray(start + 5);
for (auto i : Start) {
    FlatArray[i.second] = Val[i.first];
    Range[i.first] =
        {i.second, End[i.first]};
}

```


6.9 LCA

```

struct LCA {
    vector<int> height, euler;
    vector<int> first, segtree;
    vector<bool> visited;
    int n;
    LCA(vector<vector<int>> &adj, int root=0) {
        n = adj.size();
        height.resize(n), first.resize(n);
        euler.reserve(n * 2);
        visited.assign(n, false);
        dfs(adj, root);
        int m = euler.size();
        segtree.resize(m * 4);
        build(1, 0, m - 1);
    }
    void dfs(vector<vector<int>> &adj,
            int node, int h = 0) {
        visited[node] = true;
        height[node] = h;
        first[node] = euler.size();
        euler.push_back(node);
        for (auto to : adj[node]) {
            if (!visited[to]) {
                dfs(adj, to, h + 1);
                euler.push_back(node);
            }
        }
    }
    void build(int node, int b, int e) {
        if (b == e)
            segtree[node] = euler[b];
        else {
            int mid = (b + e) / 2;
            build(node << 1, b, mid);
            build(node << 1 | 1, mid + 1, e);
            int l = segtree[node << 1];
            int r = segtree[node << 1 | 1];
            segtree[node] =
                (height[l] < height[r]) ? l : r;
        }
    }
    int query(int node, int b, int e, int L, int R) {
        if (b > R || e < L) return -1;
        if (b >= L && e <= R)
            return segtree[node];
        int mid = (b + e) >> 1;
        int lf = query(node << 1, b, mid, L, R);
        int rg = query(node << 1 | 1,
            mid + 1, e, L, R);
        if (lf == -1) return rg;
        if (rg == -1) return lf;
        return height[lf] < height[rg] ? lf : rg;
    }
    int lca(int u, int v) {
        int left = first[u], right = first[v];
        if (left > right) swap(left, right);
        return query(1, 0, euler.size() - 1,
            left, right);
    }
};

```

6.10 Min cost max flow

```

struct Edge {
    int from, to, capacity, cost;
};
vector<vector<int>> adj, cost, capacity;
const int INF = 1e9;
void shortest_paths(int n, int v0,
    vector<int> &d, vector<int> &p) {
    d.assign(n, INF);
    d[v0] = 0;
    vector<bool> inq(n, false);
    queue<int> q;
    q.push(v0);
    p.assign(n, -1);
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        inq[u] = false;
        for (int v : adj[u]) {
            if (capacity[u][v] > 0 && d[v] >
                d[u] + cost[u][v]) {
                d[v] = d[u] + cost[u][v];
                p[v] = u;
                if (!inq[v]) {
                    inq[v] = true;
                    q.push(v);
                }
            }
        }
    }
}

int min_cost_flow(int N, vector<Edge> edges,
    int K, int s, int t) {
    adj.assign(N, vector<int>());
    cost.assign(N, vector<int>(N, 0));
    capacity.assign(N, vector<int>(N, 0));
    for (Edge e : edges) {
        adj[e.from].push_back(e.to);
        adj[e.to].push_back(e.from);
        cost[e.from][e.to] = e.cost;
        cost[e.to][e.from] = -e.cost;
        capacity[e.from][e.to] = e.capacity;
    }
    int flow = 0;
    int cost = 0;
    vector<int> d, p;
    while (flow < K) {
        shortest_paths(N, s, d, p);
        if (d[t] == INF)
            break;
        // find max flow on that path
        int f = K - flow;
        int cur = t;
        while (cur != s) {
            f = min(f,
                capacity[p[cur]][cur]);
            cur = p[cur];
        }
        // apply flow
        flow += f;
        cost += f * d[t];
    }
}

```

```

    cur = t;
    while (cur != s) {
        capacity[p[cur]][cur] -= f;
        capacity[cur][p[cur]] += f;
        cur = p[cur];
    }
}

if (flow < K)
    return -1;
else
    return cost;
}

```

6.11 SCC

```

unordered_map<int, vector<int>> adj, InvAdj;
stack<int> order;
unordered_map<int, bool> visited;
unordered_map<int, vector<int>> all_scc;
unordered_map<int, int> compId;
void dfs_for_start(int curr){
    visited[curr] = 1;
    for (auto i : adj[curr])
        if (!visited[i])
            dfs_for_start(i);
    order.push(curr);
}
vector<int> curr_comp;
void dfs_for_scc(int curr){
    visited[curr] = 1;
    for (auto i : InvAdj[curr])
        if (!visited[i])
            dfs_for_scc(i);
    curr_comp.push_back(curr);
}
inline void scc(){
    int n, e, u, v;
    cin >> n >> e;
    for (int i = 0; i < e; i++){
        cin >> u >> v;
        adj[u].push_back(v);
        InvAdj[v].push_back(u);
    }
    for (int i = 1; i <= n; i++)
        if (!visited[i])
            dfs_for_start(i);
    visited.clear();
    while (!order.empty()){
        if (!visited[order.top()]){
            curr_comp.clear();
            dfs_for_scc(order.top());
            int sz = all_scc.size() + 1;
            all_scc[sz] = curr_comp;
            for (auto i : curr_comp)
                compId[i] = sz;
        }
        order.pop();
    }
}

no. of ways and min cost of connecting the
sccs

```

```

const int MOD = 1e9 + 7, N = 1e5 + 2, INF =
1e18 + 2;
int n, m, comp[N];
vector<int> adj[N], rev[N];
bitset<N> vis;
void DFS1(int u, stack<int> &TS){
    vis[u] = true;
    for (int v : adj[u])
        if (!vis[v])
            DFS1(v, TS);
    TS.push(u);
}
void DFS2(int u, const int scc_no, int
&min_cost, int &ways, vector<int> &cost){
    vis[u] = true;
    comp[u] = scc_no;
    for (int v : rev[u])
        if (!vis[v]){
            if (min_cost == cost[v])
                ++ways;
            else if (min_cost > cost[v]){
                ways = 1;
                min_cost = cost[v];
            }
            DFS2(v, scc_no, min_cost, ways,
                cost);
        }
}
signed main(){
    FIO cin >> n;
    vector<int> cost(n + 1);
    for (int i = 1; i <= n; ++i)
        cin >> cost[i];
    cin >> m;
    while (m--){
        int u, v;
        cin >> u >> v;
        adj[u].push_back(v);
        rev[v].push_back(u);
    }
    int tot = 0, ways = 1;
    stack<int> TS;
    for (int i = 1; i <= n; ++i)
        if (!vis[i])
            DFS1(i, TS);
    vis.reset();
    int scc_no = 0;
    while (!TS.empty()){
        int u = TS.top();
        TS.pop();
        if (!vis[u]){
            int tmp_cst = cost[u], tmp_ways =
1;

            DFS2(u, ++scc_no, tmp_cst,
                tmp_ways, cost);
            tot += tmp_cst;
            ways = (ways * tmp_ways) % MOD;
        }
    }
    cout << tot << ' ' << ways;
}
//TC: O(V+E)

```

6.12 Bipartite

```

const int N=1000;
int adj[N][N];
int n,e;
bool isBicolored(int s){
    int colorArray[n];
    for(int i=0;i<n;i++){
        colorArray[i]=-1; //init no color;
    }
    queue<int>q;
    q.push(s);
    colorArray[s]=1; //assigning first color
    while(!q.empty()){
        int senior = q.front();
        q.pop();
        if(adj[senior][senior]==1)
            return false;
        for(int i=0;i<n;i++){
            int junior=i;
            if(adj[senior][junior]==1){
                if(colorArray[junior]==colorArray[senior])
                    //successor(child/junior) having same color
                    return false;
                ///if(colorArray[junior]!=-1)
                continue;    ///not same color but have a
                             color
                else
                if(colorArray[junior]==-1){          ///No
                    color assigned
                    q.push(junior);
                }
            }
        }
        colorArray[junior]=!colorArray[senior];
        ///assigning diff color
    }
}
}
}
}
return true;
}

```

6.13 Two farthest node

```

vector<int>adj[30001];
map<pair<int,int>,int>weight;
map<int,int>vis,dis;
void dfs(int node)
{
    vis[node]=1;
    for(int i=0;i<adj[node].size();i++){
        int child=adj[node][i];
        if(vis[child]==1) continue;
        dis[child]=dis[node]+weight[{node,child}];
        dfs(child);
    }
}
void reset()
{
    for(int i=0;i<30001;i++){
        adj[i].clear();
    }
    dis.clear(),weight.clear(),vis.clear();
}

```

```

int main()
{
    int t; cin>>t;
    for(int p=1;p<=t;p++){
        int n,u,v,w; cin>>n;
        for(int i=0;i<n-1;i++){
            cin>>u>>v>>w;
            adj[u].push_back(v);
            adj[v].push_back(u);

            weight[{u,v}]=w;
            weight[{v,u}]=w;
        }
        dfs(0);
        int max_dis=0,farthestVertex;
        map<int,int>::iterator i;
        for(i=dis.begin();i!=dis.end();i++){
            if(i->second>max_dis){
                max_dis=i->second;
                farthestVertex=i->first;
            }
        }
        vis.clear();
        dis.clear();

        dfs(farthestVertex);
        max_dis=0;
        for(i=dis.begin();i!=dis.end();i++){
            if(i->second>max_dis){
                max_dis=i->second;
            }
        }
        cout<<"Case "<<p<<" :
        "<<max_dis<<"\n";
        reset();
    }
}

```

7 Random Staff**7.1 HASHING**

```

#define mp make_pair
typedef long long LL;
typedef pair<LL, LL> PLL;
const PLL M = mp(1e9 + 7, 1e9 + 9); // Should
be large primes
const LL base = 347;    // Should be a prime
larger than highest value
const int N = 1e6 + 7; // Highest length of
string
ostream& operator<<(ostream& os, PLL hash) {
    return os << "(" << hash.first << ", " <<
hash.second << ")";
}
PLL operator+(PLL a, LL x) {
    return mp(a.first + x, a.second + x);
}
PLL operator-(PLL a, LL x) {
    return mp(a.first - x, a.second - x);
}
PLL operator*(PLL a, LL x) {

```

```

    return mp(a.first * x, a.second * x);
}
PLL operator+(PLL a, PLL x) {
    return mp(a.first + x.first, a.second + x.second);
}
PLL operator-(PLL a, PLL x) {
    return mp(a.first - x.first, a.second - x.second);
}
PLL operator*(PLL a, PLL x) {
    return mp(a.first * x.first, a.second * x.second);
}
PLL operator%(PLL a, PLL m) {
    return mp(a.first % m.first, a.second % m.second);
}

PLL power(PLL a, LL p) {
    if (p == 0)
        return mp(1, 1);
    PLL ans = power(a, p / 2);
    ans = (ans * ans) % M;
    if (p % 2)
        ans = (ans * a) % M;
    return ans;
}
// Magic!!!!!!
PLL inverse(PLL a) {
    return power(a, (M.first - 1) * (M.second - 1) - 1);
}
PLL pb[N]; // powers of base mod M
PLL invb;
// Call pre before everything
void hashPre() {
    pb[0] = mp(1, 1);
    for (int i = 1; i < N; i++)
        pb[i] = (pb[i - 1] * base) % M;
    invb = inverse(pb[1]);
}
// Calculates Hash of a string
PLL Hash(string s) {
    PLL ans = mp(0, 0);
    for (int i = 0; i < s.size(); i++)
        ans = (ans * base + s[i]) % M;
    return ans;
}
// appends c to string
PLL append(PLL cur, char c) {
    return (cur * base + c) % M;
}
// prepends c to string with size k
PLL prepend(PLL cur, int k, char c) {
    return (pb[k] * c + cur) % M;
}
// replaces the i-th (0-indexed) character from right from a to b;
PLL replace(PLL cur, int i, char a, char b) {
    cur = (cur + pb[i] * (b - a)) % M;

```

```

    return (cur + M) % M;
}
// Erases c from the back of the string
PLL pop_back(PLL hash, char c) {
    return ((hash - c) * invb) % M + M) % M;
}
// Erases c from front of the string with size len
PLL pop_front(PLL hash, int len, char c) {
    return ((hash - pb[len - 1] * c) % M + M) % M;
}
// concatenates two strings where length of the right is k
PLL concat(PLL left, PLL right, int k) {
    return (left * pb[k] + right) % M;
}
// Calculates hash of string with size len repeated cnt times
// This is O(log n). For O(1), pre-calculate inverses
PLL repeat(PLL hash, int len, LL cnt) {
    PLL mul = (pb[len * cnt] - 1) * inverse(pb[len] - 1);
    mul = (mul % M + M) % M;
    PLL ans = (hash * mul) % M;
    if (pb[len].first == 1)
        ans.first = hash.first * cnt;
    if (pb[len].second == 1)
        ans.second = hash.second * cnt;
    return ans;
}
// Calculates hashes of all prefixes of s including empty prefix
vector<PLL> hashList(string s) {
    int n = s.size();
    vector<PLL> ans(n + 1);
    ans[0] = mp(0, 0);
    for (int i = 1; i <= n; i++)
        ans[i] = (ans[i - 1] * base + s[i - 1]) % M;
    return ans;
}
// Calculates hash of substring s[l..r] (1 indexed)
PLL substringHash(const vector<PLL>& hashlist, int l, int r) {
    int len = (r - l + 1);
    return ((hashlist[r] - hashlist[l - 1] * pb[len]) % M + M) % M;
}
// Solves LightOJ 1255-Substring Frequency
// You are given two strings A and B. You have to find
// the number of times B occurs as a substring of A.
char buffer[N];
int main() {
    hashPre();
    int t;
    scanf("%d", &t);

```

```

    for (int cs = 1; cs <= t; ++cs) {
        string a, b;
        scanf("%s", buffer);
        a = buffer;
        scanf("%s", buffer);
        b = buffer;
        int na = a.size(), nb = b.size();
        PLL hb = Hash(b);
        vector<PLL> ha = hashList(a);
        int ans = 0;
        for (int i = 1; i + nb - 1 <= na;
i++)
            if (substringHash(ha, i, i + nb -
1) == hb)
                ans++;
        printf("Case %d: %d\n", cs, ans);
    }
}

```

7.2 when phi(1) to phi(n) is needed

```

int phi[MX];
//bitset<MX> visited;// declared before in
optimized SIEVE
void sieve_phi(){
    for(int i=1; i<MX; ++i) phi[i] = i;
    visited[1] = 1;
    for(int i=2; i<MX; ++i){
        if(!visited[i]){
            for(int j = i; j<MX; j+=i){
                visited[j] = 1;
                phi[j] = phi[j]/i*(i-1);
            }
        }
    }
}
}///O(log(logn))

```

7.3 when only phi(n) is needed

```

int phi(int n){ //O(sqrt(n))
    int res = n;
    for(int p=2; p*p<=n; ++p){
        if(n%p== 0){
            while(n%p == 0)
                n /= p;
            res -= res/p;
        }
    }
    if(n>1) res -= res/n;
    return res;
}

```

7.4 Knight Moves

```

int X[8]={2,1,-1,-2,-2,-1,1,2};
int Y[8]={1,2,2,1,-1,-2,-2,-1};

```

7.5 bit count in O(1)

```

int BitCount(unsigned int u){
    unsigned int uCount;
    uCount = u - ((u >> 1) & 033333333333) -
((u >> 2) & 011111111111);
    return ((uCount + (uCount >> 3)) &
030707070707) % 63;
}

```

```

}

```

7.6 Matrix Exponentiation

```

// A technique of computing a number raised
to a square matrix in a fast and efficient
manner.
// Uses properties of exponentiation and
binary numbers for fast computation.
//
// Running time:
// O(m^3*log(n)) where m is the size of the
matrix and n is the power the matrix is being
raised to.
//
// INPUT:
// - size of matrix m
// - the matrix A
// - the power n
// - modulo value mod
//
// OUTPUT:
// - the matrix A^n (all values mod m)
//

```

```

#include<bits/stdc++.h>
using namespace std;
typedef long long LL;

LL arr[60][60],res[60][60],tmp[60][60],m;

void matMul (LL a[][60], LL b[][60], LL mod)
{
    for(int i=0; i<m; i++)
        for(int j=0; j<m; j++)
        {
            tmp[i][j] = 0;
            for(int k=0; k<m; k++)
            {
                tmp[i][j] +=
(a[i][k]*b[k][j])%mod;
                tmp[i][j] %= mod;
            }
        }
}

void power(LL n, LL mod)
{
    for(int i=0; i<m; i++)
        for(int j=0; j<m; j++)
            if(i==j) res[i][j] = 1;
            else res[i][j] = 0;

    while(n)
    {
        if(n&1)
        {
            matMul(res,arr,mod);
            for(int i=0; i<m; i++)
                for(int j=0; j<m; j++)
                    res[i][j] = tmp[i][j];
            n--;
        }
    }
}

```

```

    }
    else
    {
        matMul(arr, arr, mod);
        for(int i=0; i<m; i++)
            for(int j=0; j<m; j++)
arr[i][j] = tmp[i][j];
        n/=2;
    }
}
}

```

7.8 sqrt decomposition(MO's Algo)

```

// https://www.spoj.com/problems/DQUERY/
#include <bits/stdc++.h>
using namespace std;
const int SIZE_1 = 1e6 + 10, SIZE_2 = 3e4 + 10;
class query{
public:
    int l, r, indx;
};

int block_size, cnt = 0;
int frequency[SIZE_1], a[SIZE_2];
void add(int indx){
    ++frequency[a[indx]];
    if (frequency[a[indx]] == 1)
        ++cnt;
}
void sub(int indx){
    --frequency[a[indx]];
    if (frequency[a[indx]] == 0)
        --cnt;
}
bool comp(query a, query b){
    if (a.l / block_size == b.l / block_size)
        return a.r < b.r;
    return a.l / block_size < b.l / block_size;
}
signed main(){
    int n; cin >> n;
    for(int i = 0; i < n; ++i) cin>>a[i];

    int q; cin >> q;
    int ans[q] = {};
    query Qur[q];
    for (int i = 0; i < q; ++i){
        int l, r; cin>>l>>r;

        Qur[i].l = l - 1;
        Qur[i].r = r - 1;
        Qur[i].indx = i;
    }
    block_size = sqrt(n); // sqrt(q) dileo
    hobe, but n is more accurate
    sort(Qur, Qur + q, comp);

    int ML = 0, MR = -1;

```

```

    for(int i = 0; i < q; ++i) {
        int L = Qur[i].l;
        int R = Qur[i].r;

        // fixing right pointer
        while (MR < R) add(++MR);
        while (MR > R) sub(MR--);
        // fixing left pointer
        while (ML < L) sub(ML++);
        while (ML > L) add(--ML);

        ans[Qur[i].indx] = cnt;
    }
    for (int i = 0; i < q; ++i)
        cout << ans[i] << '\n';
} //sqrt(n)

```

7.9 Meet in the middle

```

#include <bits/stdc++.h>
using namespace std;
int les_equal(vector<int> &s, int key){
    int siz = s.size();
    int lo = 0, hi = siz - 1, ans = 0;

    while (hi >= lo){
        int mid = lo + (hi - lo) / 2;
        if (s[mid] <= key){
            ans = max(ans, mid);
            lo = mid + 1;
        }
        else hi = mid - 1;
    }
    return ans;
}
signed main(){
    FIO int n, n1, n2, t;
    cin >> n >> t;

    n1 = (n + 1) / 2;
    n2 = n / 2;

    int a1[n1]; for(int &i: a1) cin>>i;
    int a2[n2]; for(int &i: a2) cin>>i;

    vector<int> set1, set2;
    for(int mask=0; mask < (1<<n1); ++mask){
        int temp_sum = 0;
        for (int i = 0; i < n1; ++i){
            int f = 1 << i;
            if (f & mask)
                temp_sum += a1[i];
        }
        set1.push_back(temp_sum);
    }
    for(int mask=0; mask < (1<<n2); ++mask){
        int temp_sum = 0;
        for (int i = 0; i < n2; ++i){
            int f = 1 << i;
            if (f & mask)
                temp_sum += a2[i];
        }
    }
}

```

```

    }
    set2.push_back(temp_sum);
}
sort(set2.begin(), set2.end());

// for(auto itr: set2) cout<<itr<<' ';
// cout<<'\n';
// for(auto itr: set1) cout<<itr<<' ';
// cout<<'\n';

int ans = 0;
for (auto it : set1){
    int left = t - it;
    if (left < 0) continue;

    int indx = les_equal(set2, left);
    int temp_sum_set2 = (indx != -1 ? (it
+ set2[indx]) : 0);
    if (temp_sum_set2 <= t)
        ans = max(ans, temp_sum_set2);
}
cout<<ans;
} //TC: O(2^(LK+1))
7.10 PIE(inclusion - exclusion)
#include <bits/stdc++.h>
using namespace std;

inline int LCM(int a, int b){
    return a * b / __gcd(a, b);
}

int PIE(int div[], int n, int num){
    int sum = 0;

    for(int msk=1; msk < (1<<n); ++msk){
        int bit_cnt = 0;
        int cur_lcm = 1;

        for (int i = 0; i < n; ++i){
            if (msk & (1 << i)){
                ++bit_cnt;
                cur_lcm = LCM(cur_lcm,
div[i]);
            }
        }

        int cur = num / cur_lcm;
        if (bit_cnt & 1) sum += cur;
        else sum -= cur;
    }
    return num - sum;
}

signed main(){
    int n, m;
    while (cin >> n >> m){
        int a[m];
        for(int &i : a)cin >> i;

        cout << PIE(a, m, n) << '\n';
    }
}

```

```

}
7.11 LARGEST POWER OF K IN N!
int largestPower(int k, int n){
    int cnt=0;
    lili x=k;
    while(x<=n){
        cnt+=(n/x);
        x*=k;
    }
    return cnt;
}
//Smallest Prime Factor, Greatest Prime
Factor, No of Distinct Prime Factors, No of
Total Prime Factors, No. of Divisors, Sum of
Divisors
const lili N=1e6+5;
lili spf[N];
lili lpf, gpf, tpf, dpf, sum, dv;
void sieve(){
    for(int i=0;i<N;i++){
        spf[i]=0; }
    for(lili
i=2;i<N;i++){if(spf[i]==0){for(lili
j=i*i;j<N;j+=i){if(spf[j]==0)spf[j]=i;}}}
    for(lili i=2;i<N;i++){
        if(spf[i]==0){ spf[i]=i; }}}
    lili power(lili a, lili b){
        if(b==0) return 1;
        lili x=power(a,b/2);
        if(b%2==0) x=x*x;
        else x=x*x*a;
        return x;
    }
    int main(){
        ios_base::sync_with_stdio(false);
        cin.tie(NULL);
        sieve();
        lili m,n; cin>>m;
        while(m--){
            cin>>n;
            lpf=spf[n]; gpf=-1; tpf=0; dpf=0;
dv=1; sum=1;
            while(n>1){
                lili x=spf[n];
                lili cnt=0;
                dpf++;
                while(n%x==0){
                    tpf++;
                    gpf=max(gpf,x);
                    cnt++;
                    n/=x;
                }
                dv*=(cnt+1);
                lili k=(power(x,cnt+1)-1)/(x-1);
                sum*=k;
            }
            cout<<lpf<<" "<<gpf<<" "<<dpf<<"
"<<tpf<<" "<<dv<<" "<<sum<<"\n";}}

```

7.12 Binary Search

```

ll lo=0, hi=mx; ///mx=max possible ans

```

```

while(lo<hi){
    ll mid=(lo+hi+1)>>1;
    if(condition)    ///valid condition->ans
    can be greater than or equal mid
        lo=mid;
    else
        hi=mid-1;    ///ans is less than mid
}
///or
while(lo<hi){
    ll mid=(lo+hi)>>1;
    if(condition)    ///valid condition->ans
    can be less than or equal mid
        hi=mid;
    else
        lo=mid+1;    ///ans is greater than mid
}

ll lo=0, hi=mx, esp=maxError;
while((hi-lo)>esp){
    ll mid=(lo+hi+esp)/2.0;
    if(condition) lo=mid;
    else hi=mid-esp;
}
while((hi-lo)>esp){
    ll mid=(lo+hi)/2.0;
    if(condition) hi=mid;
    else lo=mid+esp;
}

```

7.13 Generating Permutations

```

int length, perm_left_to_print;
bool placed[10000];
vector<char>perm;

void generate_permutations(int curr_length){
    if(perm_left_to_print==0) return;
    if(curr_length==length){
        for(int i=0;i<length;i++){
            cout<<perm[i];
        }
        cout<<"\n";
        perm_left_to_print--;
        return;
    }
    for(char ch='A';ch<('A'+length);ch++){
        if(!placed[ch-'A']){
            perm.push_back(ch);
            placed[ch-'A']=true;
            generate_permutations(curr_length+1);
            perm.pop_back();
            placed[ch-'A']=false;
        }
    }
}

int main(){
    ioi;
    int t; cin>>t;

```

```

    for(int tc=1;tc<=t;tc++){
        cin>>length>>perm_left_to_print;
        cout<<"Case "<<tc<<":\n";
        generate_permutations(0);
    }
}

7.14 N Queen optimal
// It just counts the number of ways to place
the order.
const int N = 32;
int mark[N][N];
char grid[N][N];
int n, cnt;
void fillup(int row, int col) {
    for (int i = 1; i < n - row + 1; i++) {
        mark[row + i][col]++;
        if (col - i >= 0)
            mark[row + i][col - i]++;
        if (col + i < n)
            mark[row + i][col + i]++;
    }
}
void fillout(int row, int col) {
    for (int i = 1; i < n - row + 1; i++) {
        mark[row + i][col]--;
        if (col - i >= 0)
            mark[row + i][col - i]--;
        if (col + i < n)
            mark[row + i][col + i]--;
    }
}
void find_way(int row) {
    if (row == n) {
        cnt++;
        return;
    }
    for (int j = 0; j < n; j++) {
        if (grid[row][j] == '*' or
mark[row][j])
            continue;
        fillup(row, j);
        find_way(row + 1);
        fillout(row, j);
    }
}
// input in grid. call find_way(0);

///N-Queen (different approach)
ll cnt=0,n=15;
bool col[16],diag1[32], diag2[32];
string s[15];    ///if s[i][j]='*',Queen can't
stand there
void backtracking (int i)
{
    if(i==n){
        cnt++; return;
    }
    for(int j=0;j<n;j++){
        if(col[j] or diag1[i+j] or
diag2[i-j+n-1] or s[i][j]=='*') continue;
        col[j]=diag1[i+j]=diag2[i-j+n-1]=1;

```



```
        backtracking(i+1);  
        col[j]=diag1[i+j]=diag2[i-j+n-1]=0;  
    }  
}
```