



# PATUAKHALI SCIENCE AND TECHNOLOGY UNIVERSITY

---

**COURSE CODE CCE 314**  
**Computer Networks Sessional**

---

## **SUBMITTED TO:**

**Prof. Dr. Md Samsuzzaman**

**Department of Computer and Communication Engineering**  
**Faculty of Computer Science and Engineering**

---

## **SUBMITTED BY:**

**Md. Tanvir Islam**

**ID: 2102043,**

**Registration No: 10170**

**Faculty of Computer Science and Engineering**

---

## **Lab 21**

**Assignment title: Test Network Latency with Ping and Traceroute**

**Date of submission: Fri 10, Sep 2025**

# Ping

```
> ping -c 5 www.afrinic.net
```

```
PING www.afrinic.net (196.216.3.4) 56(84) bytes of data.
```

```
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=1 ttl=41 time=433 ms
```

```
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=2 ttl=41 time=402 ms
```

```
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=4 ttl=41 time=396 ms
```

```
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=5 ttl=41 time=396 ms
```

```
--- www.afrinic.net ping statistics ---
```

```
5 packets transmitted, 4 received, 20% packet loss, time 4055ms
```

```
rtt min/avg/max/mdev = 396.191/406.959/433.239/15.365 ms
```

```
> ping -c 5 www.lacnic.net
```

```
PING www.lacnic.net (200.3.14.145) 56(84) bytes of data.
```

```
64 bytes from www.lacnic.net (200.3.14.145): icmp_seq=1 ttl=51 time=383 ms
```

```
64 bytes from www.lacnic.net (200.3.14.145): icmp_seq=3 ttl=51 time=328 ms
```

```
64 bytes from www.lacnic.net (200.3.14.145): icmp_seq=4 ttl=51 time=323 ms
```

```
64 bytes from www.lacnic.net (200.3.14.145): icmp_seq=5 ttl=51 time=322 ms
```

```
--- www.lacnic.net ping statistics ---
```

```
5 packets transmitted, 4 received, 20% packet loss, time 4049ms
```

```
rtt min/avg/max/mdev = 322.285/338.862/382.602/25.337 ms
```

```
> ping -c 5 www.apnic.net
```

```
PING www.apnic.net.cdn.cloudflare.net (104.18.235.68) 56(84) bytes of data.
```

```
64 bytes from 104.18.235.68: icmp_seq=2 ttl=49 time=65.0 ms
```

```
--- www.apnic.net.cdn.cloudflare.net ping statistics ---
```

```
5 packets transmitted, 1 received, 80% packet loss, time 4096ms
```

```
rtt min/avg/max/mdev = 65.025/65.025/65.025/0.000 ms
```

```
> ping -h
```

Usage

```
ping [options] <destination>
```

Options:

```
<destination>    DNS name or IP address
```

```
-3                RTT precision (do not round up the result time)
```

```
-a                use audible ping
```

```
-A                use adaptive ping
```

```
-B                sticky source address
```

```
-c <count>        stop after <count> replies
```

```
-C                call connect() syscall on socket creation
```

```
-D                print timestamps
```

- d use SO\_DEBUG socket option
- e <identifier> define identifier for ping session, default is random for SOCK\_RAW and kernel defined for SOCK\_DGRAM  
Imply using SOCK\_RAW (for IPv4 only for identifier 0)
- f flood ping
- h print help and exit
- H force reverse DNS name resolution (useful for numeric destinations or for -f), override -n
- I <interface> either interface name or address
- i <interval> seconds between sending each packet
- L suppress loopback of multicast packets
- l <preload> send <preload> number of packages while waiting replies
- m <mark> tag the packets going out
- M <pmtud opt> define path MTU discovery, can be one of <do|dont|want|probe>
- n no reverse DNS name resolution, override -H
- O report outstanding replies
- p <pattern> contents of padding byte
- q quiet output
- Q <tclass> use quality of service <tclass> bits
- s <size> use <size> as number of data bytes to be sent
- S <size> use <size> as SO\_SNDBUF socket option value
- t <ttl> define time to live
- U print user-to-user latency
- v verbose output
- V print version and exit
- w <deadline> reply wait <deadline> in seconds
- W <timeout> time to wait for response

#### IPv4 options:

- 4 use IPv4
- b allow pinging broadcast
- R record route
- T <timestamp> define timestamp, can be one of <tsonly|tsandaddr|tsprespec>

#### IPv6 options:

- 6 use IPv6
- F <flowlabel> define flow label, default is random
- N <nodeinfo opt> use IPv6 node info query, try <help> as argument

For more details see ping(8).

> ping -c 25 www.lacnic.net > lacnic.txt  
same for rest 2 \*

```
> ls --file-type *.txt
afrinic.txt apnic.txt lacnic.txt
```

```
> more afrinic.txt
```

```
PING www.afrinic.net (196.216.3.4) 56(84) bytes of data.
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=1 ttl=41 time=469 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=2 ttl=41 time=398 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=3 ttl=41 time=391 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=5 ttl=41 time=439 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=6 ttl=41 time=461 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=7 ttl=41 time=484 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=8 ttl=41 time=395 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=9 ttl=41 time=428 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=10 ttl=41 time=399 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=12 ttl=41 time=450 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=14 ttl=41 time=396 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=15 ttl=41 time=397 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=16 ttl=41 time=393 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=17 ttl=41 time=400 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=18 ttl=41 time=396 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=19 ttl=41 time=477 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=20 ttl=41 time=500 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=21 ttl=41 time=392 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=22 ttl=41 time=444 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=23 ttl=41 time=466 ms
64 bytes from lb.iso.afrinic.net (196.216.3.4): icmp_seq=25 ttl=41 time=394 ms
```

```
--- www.afrinic.net ping statistics ---
25 packets transmitted, 21 received, 16% packet loss, time 24204ms
rtt min/avg/max/mdev = 390.657/427.146/500.292/36.279 ms
```

## Analysis Chart

	Min	Max	Avg
afrinic	391 ms	500 ms	427 ms
apnic	64	71	66
lacnic	322	433	371

# TraceRoute

› **traceroute** www.apnic.net

traceroute to www.apnic.net (104.18.235.68), 30 hops max, 60 byte packets

```
1 _gateway (192.168.10.1) 1.029 ms 2.908 ms 2.890 ms
2 10.140.52.1 (10.140.52.1) 3.658 ms 3.638 ms 3.619 ms
3 10.192.1.1 (10.192.1.1) 4.214 ms 4.197 ms 4.178 ms
4 10.80.19.13 (10.80.19.13) 5.359 ms 5.879 ms 5.978 ms
5 172.16.21.201 (172.16.21.201) 8.632 ms 8.827 ms 8.883 ms
6 103.83.135-244.gmaxbd.com (103.83.135.244) 4.899 ms 4.507 ms 5.994 ms
7 104.18.235.68 (104.18.235.68) 5.351 ms 2.627 ms 3.401 ms
```

› **traceroute** www.apnic.net > apnic\_trace.txt

› **more** apnic\_trace.txt

traceroute to www.apnic.net (104.18.236.68), 30 hops max, 60 byte packets

```
1 _gateway (192.168.10.1) 1.514 ms 1.788 ms 1.781 ms
2 10.140.52.1 (10.140.52.1) 6.170 ms 6.163 ms 6.253 ms
3 10.192.1.1 (10.192.1.1) 6.532 ms 6.525 ms 6.746 ms
4 10.80.19.13 (10.80.19.13) 7.578 ms 8.468 ms 8.564 ms
5 172.16.21.201 (172.16.21.201) 10.664 ms 10.658 ms 10.747 ms
6 103.83.135-244.gmaxbd.com (103.83.135.244) 34.237 ms 32.546 ms 32.682 ms
7 104.18.236.68 (104.18.236.68) 7.133 ms 5.642 ms 5.612 ms
```

Instead of -d, I am using -n in linux.

› **traceroute** -n www.apnic.net

traceroute to www.apnic.net (104.18.235.68), 30 hops max, 60 byte packets

```
1 192.168.10.1 1.475 ms 1.446 ms 1.435 ms
2 10.140.52.1 3.256 ms 3.245 ms 3.235 ms
3 10.192.1.1 3.224 ms 3.210 ms 4.098 ms
4 10.80.19.13 6.841 ms 7.753 ms 7.858 ms
5 172.16.21.201 6.776 ms 6.766 ms 6.757 ms
6 103.83.135.244 5.020 ms 5.231 ms 5.195 ms
7 104.18.235.68 4.194 ms 3.726 ms 3.694 ms
```

# Extra

**1. The tracert and ping results can provide important network latency information. What do you need to do if you want an accurate baseline picture regarding network latency for your network?**

We will need to perform careful delay analysis over successive days and during different periods of the day.

**2. How can you use the baseline information?**

We can compare baseline data against current data to determine if there has been a change in network response times. This analysis may assist with troubleshooting network issues and scheduling of routine data transfer during off-peak hours.

End of document