

Selenium Assignment

Questions

Assignment 1

1. Download and launch the "dropdown.html" file.

Dropdown.html

Objective:

- Open dropdown.html
- Select 05-05-2005
- Validate values
- Validate years in ascending order

```
```java
```

```
WebDriver driver = new ChromeDriver();
driver.get("C:\\Users\\HP\\Downloads\\Dropdown.html");
Select day = new Select(driver.findElement(By.id("day")));
Select month = new Select(driver.findElement(By.id("month")));
Select year = new Select(driver.findElement(By.id("year")));
day.selectByVisibleText("05");
month.selectByVisibleText("May");
year.selectByVisibleText("2005");
assert day.getFirstSelectedOption().getText().equals("05");
assert month.getFirstSelectedOption().getText().equals("May");
assert year.getFirstSelectedOption().getText().equals("2005");
List<WebElement> yearOptions = year.getOptions();
List<String> years =
yearOptions.stream().map(WebElement::getText).collect(Collectors.toList());
List<String> sorted = new ArrayList<>(years);
Collections.sort(sorted);
assert years.equals(sorted);
driver.quit();
```
---
```

2. Select date 05-05-2005 from the dropdown and validate the same.

Objective: Load Assignment.html and extract unique rows.

```
```java
WebDriver driver = new ChromeDriver();
driver.get("C:\\Users\\HP\\Downloads\\Assignment.html");
List<WebElement> rows = driver.findElements(By.xpath("//table/tbody/tr"));
Set<String> uniqueRows = new LinkedHashSet<>();
for (WebElement row : rows) {
 uniqueRows.add(row.getText());
}
for (String row : uniqueRows) {
 System.out.println(row);
}
driver.quit();
```
---
```

3. Fetch the year from the dropdown and validate the year in Ascending Order.

Objective:

- Extract data from state-wise election pages
- Dump into Excel
- Derive metrics

```
```python
from selenium import webdriver
from selenium.webdriver.common.by import By
import pandas as pd
driver = webdriver.Chrome()
data = []
state_urls = {
```

```

 "Goa":
 "https://results.eci.gov.in/ResultAcGenMar2022/ConstituencywiseS0510.htm?ac
 =10",
 }
 for state, url in state_urls.items():
 driver.get(url)
 constituency = driver.find_element(By.XPATH,
 "//span[@id='ctl00_ContentPlaceHolder1_lblACName']").text
 rows = driver.find_elements(By.XPATH, "//table[2]//tr")
 for row in rows[1:]:
 cells = row.find_elements(By.TAG_NAME, "td")
 if len(cells) >= 4:
 data.append({
 "State": state,
 "Constituency": constituency,
 "Candidate": cells[0].text,
 "Party": cells[1].text,
 "Votes": int(cells[2].text.replace(", ", "")),
 "Percentage": float(cells[3].text.replace('%', '')) if cells[3].text else 0.0
 })
 driver.quit()
 df = pd.DataFrame(data)
 df.to_excel("election_data.xlsx", index=False)
 ...

 Post-processing:
    ```python
    max_vote_per_state = df.loc[df.groupby('State')['Votes'].idxmax()]
    max_pct_per_state = df.loc[df.groupby('State')['Percentage'].idxmax()]

```

[Dropdown.html](#)

Assignment 2

1. Download and launch the "Assignment.html" file.
2. Launch the file.
3. Read the table and find the unique rows from the table.

Assignment.html

Objective: Load Assignment.html and extract unique rows.

```
```java
WebDriver driver = new ChromeDriver();
driver.get("file:///C:/Users/Chahat/Desktop/Assignment.html");

List<WebElement> rows = driver.findElements(By.xpath("//table/tbody/tr"));
Set<String> uniqueRows = new LinkedHashSet<>();

for (WebElement row : rows) {
 uniqueRows.add(row.getText());
}

for (String row : uniqueRows) {
 System.out.println(row);
}

driver.quit();
```
```

Assignment 3

2022 Elections

<https://results.eci.gov.in/ResultAcGenMar2022/ConstituencywiseS0510.htm?ac=10>

Each question is state wise

1. Output should be name of constituency, candidate name, and vote number/percentage or whatever is the deciding factor, dump all the data in excel with column (all column+state+constituency name).
2. get the candidate which has got the maximum vote in each state with their constituency name.

3. get the candidate which has got the maximum percentage of vote in each state with their constituency name. (percentage)
4. candidate who won with maximum vote difference.
5. candidate who won with maximum vote percentage difference.
6. candidate who won with the minimum vote.
7. candidate who won with minimum vote percentage.
8. total count of candidate who have got less vote than nota.
9. total count of candidates who have gotten greater than 50% vote.
- 10.name of candidate who has got minimum vote in each state.

Objective:

- Extract data from state-wise election pages
- Dump into Excel
- Derive metrics

```
```python
from selenium import webdriver
from selenium.webdriver.common.by import By
import pandas as pd

driver = webdriver.Chrome()
data = []

state_urls = {
 "Goa":
"https://results.eci.gov.in/ResultAcGenMar2022/ConstituencywiseS0510.htm?ac=10",
}

for state, url in state_urls.items():
 driver.get(url)
 constituency = driver.find_element(By.XPATH,
 "//span[@id='ctl00_ContentPlaceHolder1_lblACName']").text
 rows = driver.find_elements(By.XPATH, "//table[2]/tr")

 for row in rows[1:]:
 cells = row.find_elements(By.TAG_NAME, "td")
 if len(cells) >= 4:
 data.append({
 "State": state,
 "Constituency": constituency,
 "Candidate": cells[0].text,
 "Party": cells[1].text,
```

```

 "Votes": int(cells[2].text.replace(", ", "")),
 "Percentage": float(cells[3].text.replace('%', '')) if cells[3].text else 0.0
 })

driver.quit()
df = pd.DataFrame(data)
df.to_excel("election_data.xlsx", index=False)
...

Post-processing:
```python
max_vote_per_state = df.loc[df.groupby('State')['Votes'].idxmax()]
max_pct_per_state = df.loc[df.groupby('State')['Percentage'].idxmax()]
```

```

## Assignment 4

Please do the following assignment for cucumber framework -

1. Install Cucumber
2. Create a Cucumber project
3. Use the attached feature file and implement the stepDefinitions for all the scenarios in the feature file. (You can use dummy code in the stepDefinition methods)

[Login.feature](#)

4. Execute TestRunner.
5. Assign tags to specific scenarios in the feature file and execute TestRunner for those particular tags.

TestRunner.java

package Runners;

import org.junit.runner.RunWith;

import io.cucumber.junit.Cucumber;

import io.cucumber.junit.CucumberOptions;

```
@RunWith(Cucumber.class)
@cucumberOptions(
 features = "src/test/resources/Features",
 glue = {"StepDefinations"},
 plugin = {"pretty", "html:target/cucumber.html"}
)
public class TestRunner {
}
```

LoginStepDefinitions.java

```
package StepDefinations;
```

```
import io.cucumber.java.en.*;
```

```
public class LoginStepDefinations {
```

```
 @Given("User is on NetBanking landing page")
```

```
 public void user_is_on_net_banking_landing_page() {
```

```
 System.out.println("User navigated to NetBanking landing page");
```

```
 }
```

```
 @When("User login into application with username and password")
```

```
 public void user_login_with_username_and_password() {
```

```
 System.out.println("Logging in with default credentials");
```

```
 }
```

```
 @Then("Home page is populated")
```

```
public void home_page_is_populated() {
 System.out.println("Home page displayed successfully");
}
```

```
@And("Cards are displayed")
public void cards_are_displayed() {
 System.out.println("Cards are visible");
}
```

```
@When("User login into application with {string} and password {string}")
public void user_login_with_username_and_password_param(String username,
String password) {
 System.out.println("Logging in with user: " + username + ", password: " +
password);
}
```

```
@And("Cards displayed are {string}")
public void cards_displayed_are(String status) {
 System.out.println("Cards displayed status: " + status);
}
```

```
@When("^User login in to application with (.+) and password (.+)$")
public void user_login_in_to_application_with_and_password(String username,
String password) {
 System.out.println("Scenario Outline - Username: " + username + ", Password: " +
password);
}
```



}

login.feature

Feature: Application Login

Scenario: Home page default login

Given User is on NetBanking landing page

When User login into application with username and password

Then Home page is populated

And Cards are displayed

Scenario: Home page default login

Given User is on NetBanking landing page

When User login into application with "jin" and password "1234"

Then Home page is populated

And Cards displayed are "true"

Scenario: Home page default login

Given User is on NetBanking landing page

When User login into application with "john" and password "4321"

Then Home page is populated

And Cards displayed are "false"

Scenario Outline: Home page default login

Given User is on NetBanking landing page

When User login in to application with <Username> and password <password>

Then Home page is populated

And Cards displayed are "true"

Examples:


|Username |password|

|user1 |pass1 |

|user2 |pass2 |

|user3 |pass3 |

|user4 |pass4 |




## Assignment 5

Please do the following assignment for TestNG framework -

1. Install TestNG
2. Create a TestNG Project
3. Create 2 test classes (with 3 test cases each).
4. Keep the 2 test classes in 2 different <test> tags in testng.xml
5. Execute the tests above using testng.xml
6. Assign a group to a few test cases and update testng.xml to run test cases belonging to the group.
7. Assign priority to the test cases.

Once completed, please share the below files -

- testng.xml
- 2 test class files created
- Final Console Output (in a .txt file)



The screenshot shows the Run console in IntelliJ IDEA. The left sidebar displays a tree view of the test suite structure: MyTestSuite (21ms), LoginTests (8ms), PaymentTests (13ms), and PaymentTests (13ms). The main console area shows the output of the tests, including 'Login with invalid credentials', 'Logout test', 'Payment with valid card', 'Payment with invalid card', and 'Checking payment history'. The output indicates that all 6 tests passed, with a total of 6 passes, 0 failures, and 0 skips. The process finished with exit code 0.

```
Run C:\Users\dhruv\IdeaProjects\TESTNG_ass\src\test\java\t...
MyTestSuite 21ms ✓ 6 tests passed 6 tests total, 21 ms
 ✓ LoginTests 8 ms Login with invalid credentials
 ✓ PaymentTests 13 ms Logout test
 ✓ PaymentTests 13 ms Payment with valid card
 ✓ validPayment 1 ms Payment with invalid card
 ✓ invalidPayment 1 ms Checking payment history
 ✓ paymentHistory 11 ms
MyTestSuite
Total tests run: 6, Passes: 6, Failures: 0, Skips: 0
Process finished with exit code 0
STNG_ass > src > test > java > </> testng.xml 22:1 CRLF UTF-8 4 spaces
```