



Submitted By :Tanzeela Asghar
Submitted To : Sir Muhammad Shahzad
Roll no :2021-BSE-032
Section : V-A
Course : Software Construction &
Development Lab

"LAB # 04"

1. Constructor Example 1:

```
© Main.java    © Tanzeela.java    © Counter.java ×
2 usages
1  public class Counter {
    6 usages
2  int counterindex;
    1 usage
3  public Counter() {
4      // TODO Auto-generated constructor stub
5      counterindex = 0;
6  }
    3 usages
7  public void increase()
8  {
9      counterindex=counterindex+1;
10 }
    1 usage
11 public void decrease()
12 {
13     counterindex=counterindex-1;
14 }
    3 usages
15 int getcounterindex()
16 {
17     return counterindex;
18 }
```


```
© Main.java    © Tanzeela.java ×    © Counter.java
1  public class Tanzeela {
2  public static void main(String[] args){
3      // TODO Auto-generated method stub
4      Counter c1=new Counter();
5      c1.increase();
6      int a=c1.getcounterindex();
7      c1.increase();
8      int b=c1.getcounterindex();
9      if (a>b)
10         c1.increase();
11     else c1.decrease();
12     System.out.println(c1.getcounterindex());
13 }
14 }
15
```

Output:



```
Run Tanzeela x
C:\Users\92313\.jdk\openjdk-21\bin\java.exe "-javaagent:C:\Program Files\JetBrains\IntelliJ IDEA Community Edition 2023.2.2\bin\idea_rt.jar=53828:C:\Program Files\JetBrains\IntelliJ IDEA Community Edition 2023.2.2\bin" -D
.encoding=UTF-8 -classpath C:\Users\92313\Desktop\lab04\out\production\lab04 Tanzeela
1
Process finished with exit code 0
```

2. Constructor Example 2:



```
Main.java Tanzeela.java Counter.java x
2 usages
1 public class Counter {
    7 usages
2     int counterindex;
    no usages
3     public Counter() {
4         // TODO Auto-generated constructor stub
5         counterindex = 0;}
    no usages
6     public Counter(int x){
7         counterindex=x;
8     }
    3 usages
9     public void increase()
10    {
11        counterindex=counterindex+1;
12    }
    1 usage
13    public void decrease()
14    {
15        counterindex=counterindex-1;}
    3 usages
16    int getcounterindex()
17    {
18        return counterindex;}
19 }
```

```
© Main.java    © Tanzeela.java ×    © Counter.java
1  public class Tanzeela {
2      public static void main(String[] args){
3          // TODO Auto-generated method stub
4          Counter c1=new Counter( 10);
5          c1.increase();
6          int a=c1.getcounterindex();
7          c1.increase();
8          int b=c1.getcounterindex();
9          if (a>b)
10             c1.increase();
11         else
12             c1.decrease();
13         System.out.println(c1.getcounterindex());
14     }
15 }
```

Output:

```
Run    Tanzeela ×
:
C:\Users\92313\.jdk\openjdk-21\bin\java.exe "-javaagent:C:\Program Files\JetBrains\IntelliJ I
.jar=S3856:C:\Program Files\JetBrains\IntelliJ IDEA Community Edition 2023.2.2\bin" -Dfile.en
.encoding=UTF-8 -classpath C:\Users\92313\Desktop\lab04\out\production\lab04 Tanzeela
11
Process finished with exit code 0
```

3. Multiple parameter constructors Example 1:

```
package lab4;

public class Circle {
    public double x,y,r;

    public Circle(double xcentre,double ycentre,double zcentre) {
        // TODO Auto-generated constructor stub
        x=xcentre;
        y=ycentre;
        r=zcentre;
    }

    public double circumference()
    {
        return 2*3.14*r;
    }

    public double area()
    {
        return 3.14*r*r;
    }
}
```

Output:

```
Problems @ Javadoc Declaration Console X
<terminated> saba1 [Java Application] C:\Users\fjwu\p2\pool\plugins\org.
Circumference = 31.400000000000002
Area = 78.5
```

4. Multiple parameter Constructor Examples 2:

```
1 package lab4;
2
3 public class Circle {
4     public double x,y,r;
5
6     public Circle(double xcentre,double ycentre,double zcentre) {
7         // TODO Auto-generated constructor stub
8         x=xcentre;
9         y=ycentre;
10        r=zcentre;
11    }
12    public Circle(double radius)
13    {
14        r=radius;
15    }
16    public Circle() {
17        x=0;y=0;r=0;
18    }
19    public double circumference()
20    {
21        return 2*3.14*r;
22    }
23    public double area()
24    {
25        return 3.14*r*r;
26    }
27 }
28
```

```
1 package lab4;
2
3 public class saba1 {
4
5     public static void main(String[] args) {
6         Circle c1=new Circle(10.0,20.0,5.0);
7         Circle c2=new Circle(2.0);
8         Circle c3=new Circle();
9         // TODO Auto-generated method stub
10
11         System.out.println("Circumference = "+ c1.circumference());
12         System.out.println("Area = "+ c1.area());
13
14         System.out.println("Circumference = "+ c2.circumference());
15         System.out.println("Area = "+ c2.area());
16
17         System.out.println("Circumference = "+ c3.circumference());
18         System.out.println("Area = "+ c3.area());
19     }
20 }
21 }
22
```

Output:

```
<terminated> saba1 [Java Application] C:\Users\fjwu\p2\pool\plugins
Circumference = 31.400000000000002
Area = 78.5
Circumference = 12.56
Area = 12.56
Circumference = 0.0
Area = 0.0
```


5. Method overloading Example 1:

```
Counter.java  Circle.java  Adder.java  TestOverLoa...  X  »_2
1  package labb4;
2
3  class Adder{
4      static int add(int a,int b)
5      {
6          return a+b;
7      }
8      static int add(int a,int b,int c)
9      {
10         return a+b+c;
11     }
12 }
13 class TestOverLoading {
14
15     public static void main(String[] args) {
16
17         System.out.println("Addition of 2 values = "+Adder.add(11,11));
18         System.out.println("Addition of 3 values = "+Adder.add(11,11,11));
19     }
20
21 }
```

Output:


```
Problems  Javadoc  Declaration  Console  X
<terminated> TestOverLoading [Java Application] C:\Users\fjwu\p2\pool\plugins
Addition of 2 values = 22
Addition of 3 values = 33
```

6. Program of the counter without static variable:




```
1 package labbb4;
2
3 public class counter {
4     int count=0;
5     counter()
6     {
7         count++; //incrementing value
8         System.out.println(count);
9     }
10    public static void main(String[] args) {
11        // TODO Auto-generated method stub
12        counter c1=new counter();
13        counter c2=new counter();
14        counter c3=new counter();
15    }
16
17 }
```

Output:




```
<terminated> counter [Java Application] C:\Users\fjwu\p2\po
1
1
1
```

7. Example of counter by static variable:




```
1 package lab4/src/lab4/Counter.java
2
3 public class counter {
4     static int count=0;
5     counter()
6     {
7         count++; //incrementing value
8         System.out.println(count);
9     }
10    public static void main(String[] args) {
11        // TODO Auto-generated method stub
12        counter c1=new counter();
13        counter c2=new counter();
14        counter c3=new counter();
15    }
16
17 }
18
```

Output:




```
<terminated> counter [Java Application] C:\Users\fjwu\p2\poc
1
2
3
```

8. Java Static variable example 1:



```
4 usages
1 public class student {
2     2 usages
3     int rollno;
4     2 usages
5     String name;
6     1 usage
7     static String college="FJWU";
8     2 usages
9     student(int r,String n) {
10        rollno=r;
11        name=n;}
12    2 usages
13    void display()
14    {
15        System.out.println(rollno+" "+name +" "+college);
16    }
17 }
```




```
1 > public class staticvariable1 {
2 >     public static void main(String[] args) {
3         //TODO Auto-generated method stub
4         student s1 = new student( r: 032, n: "Tanzeela Asghar");
5         student s2 = new student( r: 016, n: "Laiba Sohail");
6         s1.display();
7         s2.display();
8     }
9 }
```

Output:


```
Run staticvariable1 x
.jar=53869:C:\Program Files\JetBrains\IntelliJ IDEA Community Edition 2023.2.2\bin" -Dfile.encoding=UTF-8 -classpath C:\Users\92313\Desktop\lab04\out\production\lab04 staticvariable1
26 Tanzeela Asghar FJWU
14 Laiba Sohail FJWU
Process finished with exit code 0
```

9. Static variable example 2:

```
Main.java  Tanzeela.java  student.java x  staticvariable1.java  Counter.java
7 usages
1  public class student {
    2 usages
2      int rollno;
    2 usages
3      String name;
    2 usages
4      static String college="ITS";
    1 usage
5      static void change()
6      { college = "fjwu"; }
    3 usages
7      student(int r,String n) {
8          rollno=r;
9          name=n;}
    3 usages
10     void display()
11     {
12         System.out.println(rollno+" "+name +" "+college);
13     }
14 }
15
```



```
1 public class staticvariable1 {
2     public static void main(String[] args) {
3         //TODO Auto-generated method stub
4         student.change();
5         student s1 = new student(032, "Tanzeela Asghar");
6         student s2 = new student(016, "Laiba Sohail");
7         student s3 = new student(8, "Bisma Ali");
8         s1.display();
9         s2.display();
10        s3.display();
11    }
12 }
```

Output:



```
.encoding=UTF-8 -classpath C:\Users\92513\Desktop\Lab04\out\production\Lab04 staticvariable1
26 Tanzeela Asghar fjwu
14 Laiba Sohail fjwu
8 Bisma Ali fjwu

Process finished with exit code 0

04 > src > staticvariable1 > main
```