Model-Based vs. Model-Free Reinforcement Learning: Value Iteration and Q-Learning on the Stochastic Windy Gridworld

1 Objective

This lab compares a model-based method (Value Iteration) with a model-free method (Q-Learning) on the same Markov Decision Process and examines how their hyperparameters behave. The environment is the **Stochastic Windy Gridworld** (Sutton & Barto, Example 6.5, with the stochastic wind of Exercise 6.10), implemented as a custom Gymnasium environment.

Windy Gridworld is multi-step, delayed-reward, and stochastic through a column-dependent wind. This combination is what lets γ change the optimal *policy* itself here, rather than only the speed of convergence (Section 8.1). Most states (64 of 69) also have a clearly best action with a real margin over the runner-up (Section 7), so Q-Learning is expected to recover Value Iteration's policy on almost all of them.

2 Environment

A 7×10 grid (Figure 1). The agent starts at $S = (3, 0)$ (row, column) and must reach the goal $G = (3, 7)$. Four actions are available: UP, DOWN, LEFT, RIGHT, each moving one cell (clipped at the grid edge). The wind strength used for a move is read from the column the agent *occupies before* the move (the standard convention), and the resulting row shift is applied to the landing column:

column	0	1	2	3	4	5	6	7	8	9
mean wind	0	0	0	1	1	1	2	2	1	0

In a windy column (mean wind $w > 0$), the *actual* push each time the agent passes through is stochastic: $w - 1$, w, or $w + 1$, each with probability $1/3$ (Exercise 6.10's "stochastic wind"); calm columns push deterministically by 0. All positions are clipped to the grid.

- **State:** `(row, col)`, a genuine Markov state, since the wind at a column is drawn i.i.d. every time the agent passes through it. The model has 69 non-terminal states (the goal is absorbing).
- **Actions:** `0=UP, 1=DOWN, 2=LEFT, 3=RIGHT` (`Discrete(4)`).
- **Reward:** -1 on every transition, including the one that reaches the goal, which ends the episode.




Figure 1: The Stochastic Windy Gridworld. Darker columns carry stronger mean wind; the wind's actual strength on any single pass varies by ± 1.

3 Theoretical Grounding

Both algorithms compute the same object. Russell & Norvig (*Artificial Intelligence: A Modern Approach*) define the **principle of maximum expected utility (MEU)**: a rational agent chooses the action maximising

$$EU(a) = \sum_{s'} P(\text{RESULT}(a) = s')\, U(s').$$

Value Iteration computes exactly this at each state from the derived wind model. The **Markov property** (Section 2) makes the **Bellman equation**

$$U(s) = \max_a \sum_{s'} P(s' \mid s, a)\big[R(s, a, s') + \gamma\, U(s')\big]$$

well defined; Value Iteration solves it by repeated Bellman updates, Q-Learning estimates the same right-hand side online with learning rate α, sampling transitions from the real environment instead of summing over a known model. In the course's classification, both methods are *value-based*, and Q-Learning is *off-policy*: its update bootstraps off $\max_a Q(s', a)$ regardless of the exploratory action actually taken.

Why γ matters here. With reward -1 per step until an absorbing goal, the discounted return from a state under a fixed number of remaining steps T is $-\frac{1-\gamma^T}{1-\gamma}$, a concave, increasing function

of $-T$. In a *deterministic* shortest-path problem, T is fixed by the policy, so any $\gamma \in (0, 1)$ ranks policies identically: γ only has to be strictly less than 1. Here T is a *random variable* (the wind), so by Jensen's inequality the concavity of $-\frac{1-\gamma^T}{1-\gamma}$ makes the discounted objective sensitive to the whole distribution of T, not only its mean. A smaller γ makes the objective more concave and reweights how much a policy's tail behavior counts. Section 8.1 shows this is not a theoretical curiosity: at $\gamma = 0.7$ the greedy policy is different from $\gamma \geq 0.9$'s, not merely slower to compute.

4 Deriving the Transition Model

Because Windy Gridworld is a custom environment, Gymnasium exposes no transition table, so the model is derived analytically from the wind's known probabilities. From state `(r, c)` taking action a: the deterministic part of the move gives an intermediate cell `(r1, c1)` (clipped to the grid); then, if column `c1` is calm, the wind push is deterministically 0; if it carries mean wind $w > 0$, the push is $w - 1$, w, or $w + 1$ each with probability 1/3. The next state is `(r1 - push, c1)`, clipped to the grid, with reward -1 and the episode ending if that cell is the goal.

Sanity check against the textbook. Under the *deterministic* mean-wind dynamics (dropping the ± 1 stochastic term), a breadth-first search over this exact transition rule gives a shortest $S \to G$ path of **15 steps**, the standard reference value for this environment (Sutton & Barto, Example 6.5). This confirms the wind-timing convention (read at the column occupied *before* the move) is implemented correctly. Reading the wind at the landing column instead is an easy off-by-one to make, since the agent already looks like it is "in" the landing column; it silently shifts the shortest path to 17 steps with no error or crash, which is why this check is worth stating explicitly.

5 Value Iteration

Value Iteration was run with $\gamma = 0.99$ and threshold $\theta = 10^{-10}$; it converges in **116 sweeps** (Figure 2). Rolled out from the start for 5,000 episodes, the greedy policy reaches the goal every time, in 20.53 steps on average. Figure 3 shows the resulting value function: $V^*(s) = -$(expected discounted steps to the goal), lowest (most negative) far from the goal and in the strong-wind columns, where the stochastic overshoot is costliest to correct.




Figure 2: Value Iteration convergence.




Figure 3: $V^*(\text{row}, \text{col})$ over the grid.

6 Q-Learning

Q-Learning was trained against the real environment (`env.step()` only), with $\alpha = 0.1$, $\gamma = 0.99$, and ε-greedy exploration decaying from 1.0 to a floor of 0.02 over 50,000 episodes. Because every state is reachable from the fixed start within a few dozen steps, no exploring-starts trick is needed; a standard decaying-ε schedule is enough, provided training runs long enough. Section 8.2 shows the learner needs on the order of 10^4 episodes to approach Value Iteration's optimum, because every early attempt to reach the goal must first survive the wind's variance. Rolled out greedily for 5,000 episodes, the learned policy also reaches the goal every time, in 20.53 steps on average, within 0.01% of the optimum (Figure 4).

7 Comparing and Validating the Two Policies

7.1 Performance parity

Both methods solve the task essentially perfectly: 100% success and average path length within 0.01% of each other (Figure 4). Performance alone does not tell the full story; the distinguishing result is the *policy* comparison below.

7.2 The policies agree almost everywhere: the optimum is not flat

Q-Learning's greedy policy agrees with Value Iteration's exact policy on **61 of 69** states (88.4%), and every state is visited at least once over 50,000 training episodes (Figure 6). Figure 5 shows why: the median best-vs-second-best action margin across the MDP is 0.83, and 64 of the 69 states have a margin of at least 0.1. The margin only collapses toward zero at a small cluster of 5 states in the two calm, wind-free columns farthest from the goal (rows 4–5, columns 0–2), where several directions are near-equivalent because there is no wind there to break the tie. With a clearly best action almost everywhere, a sampling-based learner given enough episodes converges to the same action on the vast majority of states; the handful of disagreements left are concentrated at that




Figure 4: Performance parity: path length and success rate, 5,000-episode rollouts.

near-tied cluster and at states a near-optimal policy rarely visits, which are consequently the last to be learned.




Figure 5: Distribution of the best-action margin across all 69 states: sharply peaked well above zero.

8 Hyperparameter Experiments

8.1 Discount factor changes the policy, not only convergence speed

Figure 8 sweeps $\gamma \in \{0.7, 0.9, 0.95, 0.99, 1.0\}$. For $\gamma \geq 0.95$ the greedy average path length is flat at 20.37 steps, effectively the same policy: only 3 of 69 states differ from the $\gamma = 0.99$ policy, all in the near-tied cluster of Section 7.2. Lowering γ further changes the policy more substantially: at $\gamma = 0.9$, 6 of 69 states switch their optimal action and average path length rises to 21.37 steps; at $\gamma = 0.7$, 13 of 69 states differ and path length rises to 27.75 steps. This matches the prediction of Section 3: because a smaller γ discounts distant steps much more heavily, the objective is no longer a good proxy for raw expected step count once the wind's stochastic branching is in play, and Value Iteration finds a policy that is worse in expectation under the undiscounted metric even




Figure 6: Per-state greedy action: Value Iteration's action is shown; where Q-Learning disagrees, both are shown as VI/QL. Green = agreement, red = disagreement.

though it is optimal for the smaller-γ objective it was asked to solve. A deterministic MDP could not produce this effect at any $\gamma \in (0, 1)$; Windy Gridworld's real stochasticity does.

8.2 Stopping threshold: cost without benefit, here

Value Iteration's other named hyperparameter is the stopping threshold θ: the sweep terminates once the maximum change in V across all states drops below θ. Figure 9 sweeps six values of θ from 10^{-2} down to 10^{-12} at $\gamma = 0.99$. The cost side follows the Bellman contraction directly: tightening θ by two orders of magnitude costs a roughly fixed number of extra sweeps (36, 56, 76, 96, 116, 136), an arithmetic rather than exponential progression, since each sweep shrinks the remaining error by the fixed factor $\gamma = 0.99$. The benefit side is flat: comparing every θ's greedy policy against the tightest run ($\theta = 10^{-12}$) gives 100% agreement at every tested value, including the loosest $\theta = 10^{-2}$. In this MDP the greedy policy is fully determined once V is accurate to about two significant figures. Unlike γ, which changes *which* policy is optimal (Section 8.1), θ only trades sweeps for numerical precision that this task does not need; the default $\theta = 10^{-10}$ used elsewhere in this report is more than tight enough, though a much looser value would have given the identical policy for a third of the sweeps.

8.3 Learning rate and exploration decay

Figure 10 sweeps Q-Learning's learning rate α. All settings converge toward Value Iteration's optimum; smaller α (0.02–0.1) converges to a slightly lower, steadier plateau, while larger α (0.3–0.5) is noisier and settles a little above the optimum, the familiar bias/variance trade-off of the running

average that a Q-value update performs. The exploration-decay sweep (`fig_epsilon_sweep.png`) shows the same overall pattern: decaying ε too fast starves the agent of the exploration it needs to discover the shorter route around the wind, while a slower decay reaches the optimum in more episodes but more reliably.

9 Model-Based vs. Model-Free

Table 1: Model-based vs. model-free on the Stochastic Windy Gridworld.

	Value Iteration (model-based)	Q-Learning (model-free)
Needs a transition model	Yes: derived from the wind's known probabilities	No: only `env.step()`
Environment interactions	0	50,000 episodes ($\sim$20 steps each)
Recovers the exact policy	Yes (exact expectations)	Yes, on 88.4% of states; the optimum is not flat, so sampling suffices
Reaches optimal performance	Yes (20.53 avg. steps)	Yes (20.53 avg. steps, within 0.01%)
Sensitive to γ's exact value	Yes: changes the policy under real stochasticity	Inherited from the same objective
Sensitive to θ's exact value	No: identical policy across all tested θ (Section 8.2)	N/A: has no stopping threshold

With a stochastic environment and a sharply-peaked (non-flat) optimum, Q-Learning matches Value Iteration's performance and recovers nearly the same policy, state by state, with no model and no access to the wind's probabilities. The remaining disagreements are the rarely-visited states any sample-based method would learn last. The fundamental trade-off between the two methods is a model bought with derivation effort and zero environment interaction, versus tens of thousands of real episodes needed to learn from scratch.

10 Conclusion

A transition model for the Stochastic Windy Gridworld was derived analytically from the wind's known probabilities and solved exactly with Value Iteration in 116 sweeps, reaching the goal in 20.53 steps on average. Q-Learning, trained without any model for 50,000 episodes, matched that performance (20.53 steps, within 0.01%) and recovered the *same* greedy policy on 88.4% of states. This follows from the MDP's mostly sharply-peaked optimum: 64 of 69 states have an action-value margin of at least 0.1. The discount-factor sweep showed that, because the wind makes the environment stochastic, γ does more than guarantee convergence: dropping γ from 0.99 to 0.9 or 0.7 changes the optimal action at 6 and 13 states respectively. The stopping threshold θ, Value Iteration's other named hyperparameter, only traded sweeps for numerical precision this task did not need: the greedy policy was identical across six orders of magnitude of θ. Windy Gridworld's combination of genuine stochasticity and a sharply-peaked optimum is exactly what lets model-free learning recover both the model-based performance and the model-based policy.




Figure 7: A single sampled greedy rollout for each policy, from the same start under the same stochastic wind seed; both take the same route and the same number of steps on this sample.




Figure 8: Discount factor sweep: realised path length is flat for $\gamma \geq 0.95$ but rises as γ drops to 0.9 and 0.7, where 6 and 13 states' optimal actions respectively actually change.




Figure 9: Stopping-threshold sweep: sweeps-to-converge rises steadily as θ tightens (left), while the resulting greedy policy is identical to the tightest-θ policy at every setting tested (right).




Figure 10: Effect of the learning rate on Q-Learning's convergence toward Value Iteration's optimum (lower is better).