CS101 Algorithms and Data Structures Fall 2023 Homework 5

Due date: November 12, 2023, at 23:59

- 1. Please write your solutions in English.
- 2. Submit your solutions to gradescope.com.
- 3. Set your FULL name to your Chinese name and your STUDENT ID correctly in Account Settings.
- 4. If you want to submit a handwritten version, scan it clearly. CamScanner is recommended.
- 5. When submitting, match your solutions to the problems correctly.
- 6. No late submission will be accepted.
- 7. Violations to any of the above may result in zero points.

1. (12 points) Multiple Choices

Each question has **one or more** correct answer(s). Select all the correct answer(s). For each question, you will get 0 points if you select one or more wrong answers, but you will get 1 point if you select a non-empty subset of the correct answers.


Write your answers in the following table.

(a)	(b)	(c)	(d)	(e)	(f)
F	AC	AD	D	В	В	ABD

- (a) (2') Which of the following statements is/are true about tree?
 - A. A tree with N nodes has N-1 edges.
 - B. The height of a tree is always positive.
 - C. Every node of a tree is either a leaf node or an internal node.
 - D. The degree and the depth of the root node should be 0.
- (b) (2') Which of the following statements is/are true about binary tree?
 - A. In a binary tree, every non-root node has exactly one parent.
 - B. Every full binary tree is also a complete binary tree.
 - C. A full binary tree with n non-leaf nodes contains 2n-1 total nodes.
 - D. A binary tree of height 0 is also perfect.
- (c) (2') Which of the following choices is/are $\Theta(m)$ where m is the maximum length of the queue when traversing a tree with BFS?
 - A. The total number of nodes in the tree.
 - B. The length of the deepest path from a leaf node to the root node.
 - C. The maximum degree of nodes in the tree.
 - D. The maximum number of nodes at a given depth of the tree.
- (d) (2') There exists two paths between any two different nodes in a tree with height more than 3.
 - A. True.
 - B. False.
- (e) (2') The height of a tree is always equal to the maximum depth of nodes in the tree.
 - A. True.
 - B. False.
- (f) (2') Which of the following statements is/are false?
 - A. Nodes with the same depth are siblings.
 - B. Each node in the tree has exactly one parent pointing to it.
 - C. Given any node α within a tree, the collection of α and all of its descendants is a subtree of the tree with root α .
 - D. The root node cannot be the descendent of any nodes.


- 2. (10 points) Generate a binary tree
 - (a) (4') Given the in-order and pre-order traversal of a binary tree T are **ECFBDGA** and **ABCEFDG** respectively.

Draw the tree T.



(b) (4') Given the in-order and post-order traversal of a binary tree T are **EBDAHCGF** and **EDBHFGCA** respectively.


Draw the tree T.



(c) (2') Given the pre-order and post-order traversal of a binary tree T, can you decide the tree T? If yes, please describe an algorithm to construct T; if no, please provide a counterexample.

Solution:

No. Given the pre-order of T is AB, and the post-order of T is BA, then the following two binary trees both match.






3. (10 points) Tree Structure and Traversal


You should solve the below questions following these steps:

- 1. Decide on an appropriate data structure to implement the traversal.
- 2. When doing **Breadth First Traversal**, push children of a node into the data structure in alphabetical order.
- 3. Consider **poping an entry** and **pushing all its children** as one step.


Example: Given a tree with root **A**:




The process of doing Breadth First Traversal is:




(a) (5') Run **Breadth First Traversal** on the tree with root **A** and draw the whole process in the space below.




Solution:



(b) (5') Run **Pre-order Depth First Traversal** on the tree with root **A** and draw the whole process in the space below.



Solution:



4. (10 points) Left Child Right Sibling

- (a) (1') For every ordered tree, there is a unique representation of Left-child right-sibling format.
 - √ True False
- (b) (1') Pre-order traversal of the original tree is identical to the pre-order traversal of the Knuth transform.
 - $\sqrt{\text{True}}$ \bigcirc False
- (c) (1') Post-order traversal of the original tree is identical to the post-order traversal of the Knuth transform.
 - \bigcirc True $\sqrt{\text{False}}$
- (d) (7') Transform the tree below with root 1 (in LCRS format) to N-ary format.

