

Oracle® Sales Intelligence Technical Reference Manual

RELEASE 11*i*

August 2000



Oracle® Sales Intelligence Technical Reference Manual
Release 11i

To order this book, ask for Part No. A86210-01

Copyright © 2000. Oracle Corporation. All rights reserved.

Major Contributors:

Contributors:

This Technical Reference Manual (TRM) in any form, software or printed matter, contains proprietary information of Oracle Corporation; it is provided under an Oracle Corporation agreement containing restrictions on use and disclosure and is also protected by copyright, patent, and other intellectual property law. Restrictions applicable to this TRM include, but are not limited to: (a) exercising either the same degree of care to safeguard the confidentiality of this TRM as you exercise to safeguard the confidentiality of your own most important Confidential Information or a reasonable degree of care, whichever is greater; (b) maintaining agreements with your employees and agents that protect the Confidential Information of third parties such as Oracle Corporation and instructing such employees and agents of these requirements for this TRM; (c) restricting disclosure of this TRM to those of your employees who have a "need to know" consistent with the purposes for which this TRM was disclosed to you; (d) maintaining this TRM at all times on your premises; (e) not removing or destroying any proprietary or confidential legends or markings placed upon this TRM in whatever form, software or printed matter; and (f) not reproducing or transmitting this TRM in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Oracle Corporation. You should not use this TRM in any form, software or printed matter, to create software that performs the same or similar functions as any Oracle Corporation products.

The information in this TRM is subject to change without notice. If you find any problems in the TRM in any form, software or printed matter, please report them to us in writing. Oracle Corporation does not warrant that this TRM is error-free. This TRM is provided to customer "as-is" with no warranty of any kind. This TRM does not constitute Documentation as that term is defined in Oracle's agreements.

Reverse engineering of the Programs (software and documentation) associated with this TRM are prohibited. The Programs associated with this TRM are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be licensee's responsibility to take all appropriate fail-safe, back-up, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and Oracle disclaims liability for any damages caused by such use of the Programs.

Program Documentation is licensed for use solely to support the deployment of the Programs and not for any other purpose.

Restricted Rights Legend

This TRM and the Programs associated with this TRM delivered subject to the DOD FAR Supplement are 'commercial computer software' and use, duplication and disclosure of the TRM and the Programs associated with this TRM shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement. Otherwise, this TRM and the Programs associated with this TRM delivered subject to the Federal Acquisition Regulations are 'restricted computer software' and use, duplication and disclosure of the TRM and the Programs associated with this TRM shall be subject to the restrictions in FAR 52.227-14, Rights in Data — General, including Alternate III (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065.

Oracle is a registered trademark, and Oracle Customer Intelligence, CASE*Exchange, Enabling the Information Age, Hyper*SQL, NLS*Workbench, Oracle7, Oracle8, Oracle 8i, Oracle Access, Oracle Application Object Library, Oracle Discoverer, Oracle Financials, Oracle Quality, Oracle Web Customers, Oracle Web Employees, Oracle Work in Process, Oracle Workflow, PL/SQL, Pro*Ada, Pro*C, Pro*COBOL, Pro*FORTRAN, Pro*Pascal, Pro*PL/I, SmartClient, SQL*Connect, SQL*Forms, SQL*Loader, SQL*Menu, SQL*Net, SQL*Plus, and SQL*Report are trademarks or registered trademarks of Oracle Corporation. Other names may be trademarks of their respective owners.



CAUTION

This Technical Reference Manual in any form -- software or printed matter -- contains proprietary, confidential information that is the exclusive property of Oracle Corporation. If you do not have a valid contract with Oracle for the use of this Technical Reference Manual or have not signed a non-disclosure agreement with Oracle covering this Technical Reference Manual, then you received this document in an unauthorized manner and are not legally entitled to possess or read it.



Contents

	Contents	v
Chapter 1	Introduction	1 – 1
Chapter 2	High-Level Design	2 – 1
	Overview of High-Level Design	2 – 2
	Database Diagrams	2 – 7
	Public Table List	2 – 9
	Public View List	2 – 10
	Internal View List	2 – 11
	Single Organization View List	2 – 12
	Module List	2 – 13
Chapter 3	Detailed Design	3 – 1
	Overview of Detailed Design	3 – 2
	Table and View Definitions	3 – 3
	Index	

Introduction

The *Oracle Sales Intelligence Technical Reference Manual* provides the information you need to understand the underlying structure of Oracle Sales Intelligence. After reading this manual, you should be able to convert your existing applications data, integrate your existing applications with Oracle Sales Intelligence, and write custom reports for Oracle Sales Intelligence, as well as read data that you need to perform other tasks.

This chapter introduces you to the *Oracle Sales Intelligence Technical Reference Manual*, and explains how to use it.

Introduction

At Oracle, we design and build applications using Oracle Designer, our systems design technology that provides a complete environment to support developers through all stages of a systems life cycle. Because we use a repository-based design toolset, all the information regarding the underlying structure and processing of our applications is available to us online. Using Oracle Designer, we can present this information to you in the form of a technical reference manual.

This *Oracle Sales Intelligence Technical Reference Manual* contains detailed, up-to-date information about the underlying structure of Oracle Sales Intelligence. As we design and build new releases of Oracle Sales Intelligence, we update our Oracle Designer repository to reflect our enhancements. As a result, we can always provide you with an *Oracle Sales Intelligence Technical Reference Manual* that contains the latest technical information as of the publication date. Note that after the publication date we may have added new indexes to Oracle Sales Intelligence to improve performance.

About this Manual

This manual describes the Oracle Customer Relationship Management (CRM) Applications Release 11i data model, as used by Oracle Sales Intelligence; it discusses the database we include with a fresh install of Oracle CRM Applications Release 11i. If you have not yet upgraded to Release 11i, your database may differ from the database we document in this book.

You can contact your Oracle representative to confirm that you have the latest technical information for Oracle Sales Intelligence. You can also use Oracle *MetaLink* which is accessible through Oracle's Support Web Center (http://www.oracle.com/support/elec_sup).

Finding the Latest Information

The *Oracle Sales Intelligence Technical Reference Manual* contains the latest information as of the publication date. For the latest information we encourage you to use Oracle *MetaLink* which is accessible through Oracle's Support Web Center (http://www.oracle.com/support/elec_sup).

Audience

The *Oracle Sales Intelligence Technical Reference Manual* provides useful guidance and assistance to:

- Technical End Users
- Consultants
- Systems Analysts
- System Administrators
- Other MIS professionals

This manual assumes that you have a basic understanding of structured analysis and design, and of relational databases. It also assumes that you are familiar with Oracle Application Object Library and Oracle Sales Intelligence. If you are not familiar with the above products, we suggest that you attend one or more of the training classes available through Oracle Education (see: Other Information Sources: page 1 – 7).

How This Manual is Organized

This manual contains two major sections, High-Level Design and Detailed Design.

High-Level Design

This section, Chapter 2, contains database diagrams and lists each database table and view that Oracle Sales Intelligence uses. This chapter also has a list of modules.

Detailed Design

This section, Chapter 3, contains a detailed description of the Oracle Sales Intelligence database design, including information about each database table and view you might need for your custom reporting or other data requirements.

How to Use This Manual

The *Oracle Sales Intelligence Technical Reference Manual* is a single, centralized source for all the information you need to know about the underlying structure and processing of Oracle Sales Intelligence. For example, you can use this manual when you need to:

- Convert existing application data
- Integrate your Oracle Sales Intelligence application with your other applications systems
- Write custom reports
- Define alerts against Oracle Applications tables
- Configure your Oracle Self-Service Web Applications
- Create views for decision support queries using query tools
- Create business views for Oracle Discoverer

You need not read this manual cover to cover. Use the table of contents and index to quickly locate the information you need.

How Not To Use This Manual

Do not use this manual to plan modifications

You should not use this manual to plan modifications to Oracle Sales Intelligence. Modifying Oracle Sales Intelligence limits your ability to upgrade to future releases of your Oracle Sales Intelligence application. In addition, it interferes with our ability to give you the high-quality support you deserve.

We have constructed Oracle Sales Intelligence so that you can customize it to fit your needs without programming, and you can integrate it with your existing applications through interface tables. However, should you require program modifications, you should contact our support team (see: Other Information Sources: page 1 – 7). They can put you in touch with Oracle Services, the professional consulting organization of Oracle. Their team of experienced applications professionals can make the modifications you need while ensuring upward compatibility with future product releases.

Do not write data into non-interface tables

Oracle reserves the right to change the structure of Oracle Applications tables, and to change the meaning of, add, or delete lookup codes and data in future releases. Do not write data directly into or change data in non-interface tables using SQL*Plus or other programming tools because you risk corrupting your database and interfering with our ability to support you.

Moreover, this version of the *Oracle Sales Intelligence Technical Reference Manual* does not contain complete information about the dependencies between Oracle Sales Intelligence applications tables. Therefore, you should write data into only those tables we identify as interface tables. If you write data into other non-interface tables, you risk violating your data integrity since you might not fulfill all the data dependencies in your Oracle Sales Intelligence application.

You are responsible for the support and upgrade of the logic within the procedures that you write, which may be affected by changes between releases of Oracle Applications.

Do not rely on upward compatibility of the data model

Oracle reserves the right to change the structure of Oracle Sales Intelligence tables, and to change the meaning of, add, or delete lookup codes and other data in future releases. We do not guarantee the upward compatibility of the Oracle Sales Intelligence data model. For example, if you write a report that identifies concurrent requests that end in Error status by selecting directly from Oracle Application Object Library tables, we do not guarantee that your report will work properly after an upgrade.

About Oracle Application Object Library

Oracle Application Object Library is a collection of pre-built application components and facilities for building Oracle Applications and extensions to Oracle Applications. Oracle Application Coding Standards use the Oracle Application Object Library and contains shared components including but not limited to -- forms, subroutines, concurrent programs and reports, database tables and objects, messages, menus, responsibilities, flexfield definitions and online help.



Attention: Oracle does not support *any* customization of Oracle Application Object Library tables or modules, not even

by Oracle consultants. (Oracle Application Object Library tables generally have names beginning with FND_%.)

Accordingly, this manual does not contain detailed information about most Oracle Application Object Library tables used by Oracle Sales Intelligence.

A Few Words About Terminology

The following list provides you with definitions for terms that we use throughout this manual:

Relationship

A relationship describes any significant way in which two tables may be associated. For example, rows in the Journal Headers table may have a one-to-many relationship with rows in the Journal Lines table.

Database Diagram

A database diagram is a graphic representation of application tables and the relationships between them.

Module

A module is a program or procedure that implements one or more business functions, or parts of a business function, within an application. Modules include forms, concurrent programs and reports, and subroutines.

Application Building Block

An application building block is a set of tables and modules (forms, reports, and concurrent programs) that implement closely-related database objects and their associated processing. Said another way, an application building block is a logical unit of an application.

QuickCodes

QuickCodes let you define general purpose, static lists of values for window fields. QuickCodes allow you to base your program logic on lookup codes while displaying user-friendly names in a list of values window. QuickCodes simplify name and language changes by letting

you change the names your end users see, while the codes in your underlying programs remain the same.

Form

A form is a module comprised of closely related windows that are used together to perform a task. For example, the Enter Journals form in Oracle General Ledger includes the Enter Journals window, the Batch window, and the More Actions window among others. The Enter Journals window is the main window, and from it, you can use buttons to navigate to other windows in the form. The form name usually corresponds to the main window in the form, and is frequently a window you open directly from the Navigator.

Other Information Sources

Installation and System Administration

Training

Oracle Education offers a complete set of training courses to help you and your staff master Oracle CRM Applications. We can help you develop a training plan that provides thorough training for both your project team and your end users. We will work with you to organize courses appropriate to your job or area of responsibility.

Training professionals can show you how to plan your training throughout the implementation process so that the right amount of information is delivered to key people when they need it the most. You can attend courses at any one of our many Educational Centers, or you can arrange for our trainers to teach at your facility. In addition, we can tailor standard courses or develop custom courses to meet your needs.

Support

From on-site support to central support, our team of experienced professionals provides the help and information you need to keep Oracle Sales Intelligence working for you. This team includes your Technical Representative, Account Manager, and Oracle's large staff of consultants and support specialists with expertise in your business

area, managing an Oracle server, and your hardware and software environment.

About Oracle

Oracle Corporation develops and markets an integrated line of software products for database management, applications development, decision support, and office automation, as well as Oracle Applications, an integrated suite of more than 75 software modules for financial management, supply chain management, manufacturing, project systems, human resources, and sales and service management.

Oracle products are available for mainframes, minicomputers, personal computers, network computers, and personal digital assistants, allowing organizations to integrate different computers, different operating systems, different networks, and even different database management systems, into a single, unified computing and information resource.

Oracle is the world's leading supplier of software for information management, and the world's second largest software company. Oracle offers its database, tools, and applications products, along with related consulting, education, and support services, in over 145 countries around the world.

Thank You

Thanks for using Oracle Sales Intelligence and this technical reference manual!

We appreciate your comments and feedback. After the Table of Contents of this manual is a Reader's Comment Form that you can use to explain what you like or dislike about Oracle Sales Intelligence or this technical reference manual. Mail your comments to the following address or call us directly at (650) 506-7000.

Oracle CRM Applications Content Development Manager
Oracle Corporation
500 Oracle Parkway
Redwood Shores, California 94065
U.S.A.

High-Level Design

This chapter presents a high-level design for Oracle Sales Intelligence that satisfies the business needs we specify during Strategy and Analysis. It contains database diagrams for Oracle Sales Intelligence application building blocks, lists of database tables and views, and a list of modules.

Overview of High-Level Design

During High-Level Design, we define the application components (tables, views, and modules) we need to build our application. We specify what application components should do without specifying the details of *how* they should do it.

You can refer to this High-Level Design chapter to quickly acquaint yourself with the tables, views, and modules that comprise Oracle Sales Intelligence applications. And, you can prepare yourself to understand the detailed design and implementation of Oracle Sales Intelligence.

Database Diagrams

The Database Diagrams section graphically represents all Oracle Sales Intelligence applications tables and the relationships between them, organized by building block.

Use this section to quickly learn what tables each Oracle Sales Intelligence application building block uses, and how those tables interrelate. Then, you can refer to the Table and View Definitions sections of Chapter 3 for more detailed information about each of those tables.

Table Lists

The Table List sections list the Oracle Sales Intelligence applications tables. Because a product might not include at least one table for each type, this Technical Reference Manual might not include each of the following sections.

Public Tables

Use the Public Table List section to quickly identify the tables you are most interested in. Then, you can refer to the Table and View Definitions sections of Chapter 3 for more detailed information about those tables.

In addition, this manual may contain full documentation for one or more of the following Application Object Library tables: FND_DUAL, FND_CURRENCIES, and FND_COMMON_LOOKUPS.

Internal Tables

This section includes a list of private, internal tables used by Oracle Sales Intelligence; we do not provide additional documentation for these tables.

View Lists

The View List sections list the Oracle Sales Intelligence views, with one section for each type of view. Because a product might not include at least one view for each type, this Technical Reference Manual might not include each of the following sections.

Use this section to quickly identify the views you are most interested in. Then, you can refer to the Table and View Definitions sections of Chapter 3 for more detailed information about those views.

Public Views

This section lists views that may be useful for your custom reporting or other data requirements. The list includes a description of the view, and the page in Chapter 3 that gives detailed information about the public view.

Web Views

This section lists views that you may need to configure your Self-Service Web applications. The list includes a description of the view, and the page in Chapter 3 that gives detailed information about the web view.

Internal Views

This section includes each private, internal view that Oracle Sales Intelligence uses.

Multiple Reporting Currency Views

This list includes views that were created to support the Multiple Reporting Currencies feature.

Module List


The Module List section briefly describes each of the Oracle Sales Intelligence applications modules. This section lists forms, reports, and concurrent programs.

A form is a module comprised of closely related windows that are used together to perform a task. For example, the Enter Journals form in Oracle General Ledger includes the Enter Journals window, the Batch window, and the More Actions window. The Enter Journals window is the main window, and from it, you can use buttons to navigate to other windows in the form. The form name usually corresponds to the main window in the form, and is frequently a window you can open directly from the Navigator.

The Reports and Concurrent Programs lists include processes you can submit from the Submit Requests window or other windows, as well as processes that are submitted automatically by Oracle Sales Intelligence. Use your user's guide to learn more about reports and concurrent processes.

Database Diagramming Conventions

Figure 2 – 1
Database Diagram
Conventions



Tables – are the basic unit of storage in the database. A hand symbol preceding the title in the table's title bar indicates that the table is not owned by this application but shared with another.

Foreign key constraint – is a type of referential integrity constraint for checking the integrity of data entered in a specific column or set of columns. This specified column or set of columns is known as the foreign key.

Delete rule indicator – determines the action to be taken when an attempt is made to delete a related row in a join table. A line through the foreign key constraint, as shown on the above diagram, indicates that this action is restricted.

Arcs – specify that, for any given row in a table, a value must be entered in one of the arc columns. The remaining columns within the arc must be null.

Public Table List

This section lists each public database table that Sales Intelligence uses and provides a brief description of each of those tables. The page reference is to the table description in Chapter 3.

Note that "public" tables are not necessarily intended for write access by custom code; Oracle Corporation supports write access using only standard Oracle Applications forms, reports, and programs, or any SQL write access to tables explicitly documented as API tables. For more information, see the How Not To Use This Manual section of this book's Introduction.

Sales Intelligence uses the following Public tables:

Table Name	Description
AK_ATTRIBUTES	Attribute name, properties and the application ID which define an attribute (See page 3 – 7)
AK_ATTRIBUTES_TL	Translations for AK_ATTRIBUTES (See page 3 – 9)
AK_OBJECTS	Defines an object and the application id of the owner of the object (See page 3 – 10)
AK_OBJECTS_TL	Translations for AK_OBJECTS (See page 3 – 12)
AK_OBJECT_ATTRIBUTES	Links an attribute to an object (See page 3 – 13)
AK_OBJECT_ATTRIBUTES_TL	Translations for AK_OBJECT_ATTRIBUTES (See page 3 – 16)
AK_OBJECT_ATTRIBUTE_NAVIGATION	Defines a specific object attribute value which allows access to a region (See page 3 – 17)
AK_OBJECT_VALUES_TEMP	Temporary table for building the LOV of attribute values in the AKDPICKF form (See page 3 – 19)
AK_QUERY_OBJECTS	Defines a query object and the application id of the owner of the query object (See page 3 – 20)
AK_QUERY_OBJECT_LINES	Links a line to a query object (See page 3 – 21)
AK_REGIONS	Defines a region (See page 3 – 22)
AK_REGIONS_TL	Translations for AK_REGIONS (See page 3 – 24)
AK_REGION_ITEMS	Links an item to a region (See page 3 – 25)
AK_REGION_ITEMS_TL	Translations for AK_REGION_ITEMS (See page 3 – 29)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

AK_REGION_LOV_RELATIONS	Defines relationships between LOV regions and regions (See page 3 – 30)
ASO_HEADER_RELATIONSHIPS	ASO_HEADER_RELATIONSHIPS links one quote to another and records the type of relationship. (See page 3 – 31)
ASO_QUOTE_HEADERS_ALL	ASO_QUOTE_HEADERS holds Order Capture quotation information. it has the header data of a quote. For each quote header, there can zero or many quote lines attached to it. (See page 3 – 57)
ASO_QUOTE_LINES_ALL	ASO_QUOTE_LINES_ALL stores information for a typical quote or an order line (See page 3 – 67)
ASO_QUOTE_LINE_DETAILS	ASO_QUOTE_LINE_DETAILS_ALL stores information specific to certain types of quote lines (See page 3 – 77)
ASO_QUOTE_RELATED_OBJECTS	ASO_QUOTE_RELATED_OBJECTS stores the relationship between a quote or a quote line to any entity in the schema and records the type of relationship. (See page 3 – 83)
AS_ACCESSES_ALL	Contains employee access records for accounts and opportunities (See page 3 – 85)
AS_FORECAST_PROB_ALL_B	AS_FORECAST_PROB_ALL defines win probability values for sales (See page 3 – 89)
AS_FORECAST_PROB_ALL_TL	MLS – Translated columns of AS_FORECAST_PROB_ALL_B (See page 3 – 91)
AS_FORECAST_WORKSHEETS	This will store header information for the opportunity and product category worksheet. (See page 3 – 92)
AS_INTERESTS_ALL	Stores product interests, account and opportunity classifications (See page 3 – 94)
AS_INTEREST_CATEGORY_SETS_ALL	Contains interest category sets (See page 3 – 97)
AS_INTEREST_CODES_B	Define Interest code – Base table (See page 3 – 98)
AS_INTEREST_CODES_MC	for recording a price and currency for a product family. (See page 3 – 100)
AS_INTEREST_CODES_TL	For MLS – Translated columns of Interest Codes. (See page 3 – 101)

AS_INTEREST_TYPES_ALL	Defines interest types with multi-org flag columns (See page 3 – 102)
AS_INTEREST_TYPES_B	Define Interest types – base table (See page 3 – 104)
AS_INTEREST_TYPES_TL	For MLS – Translated columns of Interest Types (See page 3 – 106)
AS_INTERNAL_FORECASTS	Table to store the summary forecast information for individual or group (See page 3 – 107)
AS_LEADS_ALL	Holds sales opportunities (See page 3 – 109)
AS_LEADS_LOG	Holds opportunity change history (See page 3 – 113)
AS_LEAD_LINES_ALL	Holds sales opportunity lines (See page 3 – 114)
AS_LEAD_ORDERS	Contains orders resulting from sales opportunities (See page 3 – 117)
AS_SALES_CREDITS	Holds sales credits (See page 3 – 119)
AS_SALES_CREDITS_DENORM	Denormalized table to store opportunity data denormalized from AS_LEADS_ALL, AS_LEAD_LINES_ALL, AS_SALES_CREDITS, AS_SALES_STAGE_ALL, AS_INTEREST_TYPES_ALL, AS_INTEREST_CODES_ALL, HZ_PARTIES, AS_SALES_GROUPS, PER_ALL_PEOPLR_F (See page 3 – 122)
AS_SALES_LEADS	Holds sales leads (See page 3 – 125)
AS_SALES_LEADS_LOG	Holds opportunity change history (See page 3 – 128)
AS_SALES_LEAD_LINES	Holds sales lead lines information (See page 3 – 129)
AS_SALES_LEAD_OPPORTUNITY	Holds the linking information between sales leads and opportunity. Records can not be deleted. (See page 3 – 131)
AS_SALES_LEAD_RANKS_B	Defines the various ranks a lead can have (See page 3 – 133)
AS_SALES_STAGES_ALL_B	Defines sales stages (See page 3 – 134)
AS_SALES_STAGES_ALL_TL	For MLS – Translated columns of AS_SALES_STAGES_ALL_B (See page 3 – 136)
AS_STATUSES_B	Hold three types of status, opportunity, lead and quote (See page 3 – 137)

AS_STATUSES_TL	For MLS, Translated columns of AS_STATUSES_B (See page 3 – 139)
AS_TERRITORY_ACCESSES	Defines territory accesses (See page 3 – 140)
BIL_IMP_CUST_SUMM	Summary measures related to reporting on important customers (See page 3 – 141)
BIL_INV_TERR_INTF	Invoice territory assignment interface table (See page 3 – 143)
BIL_OPTY_PERF_SUMM	Summary measures related to reporting on opportunity performance (See page 3 – 144)
BIL_ORD_TERR_INTF	Order territory assignment interface table (See page 3 – 146)
BIL_PROD_SCT_WL_SUMM	Summary measures related to reporting on product sales cycle time, revenue and wins/losses (See page 3 – 147)
BIL_QUOTE_TERR_INTF	Quote territory assignment interface table (See page 3 – 149)
BIL_REV_CUST_SUMM	Summary measures related to reporting on customer revenue (See page 3 – 150)
BIL_ROC_SUMM	Summary measures related to reporting on return on sales compensation (See page 3 – 152)
BIL_SLS_CHNL_PERF_SUMM	Summary measures related to reporting on sales channel performance (See page 3 – 154)
BIL_SREP_PERF_SUMM	Summary measures related to reporting on salesforce performance (See page 3 – 156)
BIL_SRV_RQST_SUMM	Obsolete (See page 3 – 158)
CN_COMMISSION_HEADERS_ALL	Stores the Direct credit transactions of a salesperson (See page 3 – 159)
CN_COMMISSION_LINES_ALL	Stores all transactions created as part of calculation. (See page 3 – 163)
CN_QUOTAS_ALL	Plan Elements (See page 3 – 166)
CN_QUOTA_ASSIGNS_ALL	Elements assigned to a compensation plan (See page 3 – 169)
CN_SRP_PERIODS_ALL	Salesperson compensation by priod (See page 3 – 170)
CN_SRP_PERIOD_QUOTAS_ALL	Salesperson Plan Elements by Period (See page 3 – 174)
CN_SRP_PER_QUOTA_RC_ALL	Salesperson Revenue Classes by Period (See page 3 – 176)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CN_SRP_PLAN_ASSIGNS_ALL	Salesperson Plan Assignments (See page 3 – 178)
CN_SRP_QUOTA_ASSIGNS_ALL	Salesperson Plan Element Assignments (See page 3 – 180)
CN_SRP_QUOTA_RULES_ALL	Salesperson Revenue Classes (See page 3 – 183)
CS_INCIDENTS_ALL_B	This table stores non-translated information about service requests. (See page 3 – 185)
CS_INCIDENTS_ALL_TL	This table stores translated information about service requests. (See page 3 – 190)
CS_INCIDENT_SEVERITIES_B	This table contains non-translated information about severities. (See page 3 – 191)
CS_INCIDENT_SEVERITIES_TL	This table contains translated information about severities. (See page 3 – 193)
CS_INCIDENT_STATUSES_B	This table contains non-translated information about statuses. (See page 3 – 194)
CS_INCIDENT_STATUSES_TL	This table contains translated information about statuses. (See page 3 – 196)
CS_INCIDENT_TYPES_B	This table contains non-translated information about type codes. (See page 3 – 197)
CS_INCIDENT_TYPES_TL	This table contains translated information about type codes. (See page 3 – 199)
EDW_BIL_COMP_PLANS_M	(See page 3 – 200)
EDW_BIL_COMP_PRF_SUM_F	(See page 3 – 202)
EDW_BIL_CPLNS_A_LTC	(See page 3 – 204)
EDW_BIL_CPLNS_CPLN_LSTG	(See page 3 – 205)
EDW_BIL_CPLNS_CPLN_LTC	(See page 3 – 206)
EDW_BIL_CPLNS_ELMNT_LSTG	(See page 3 – 208)
EDW_BIL_CPLNS_ELMNT_LTC	(See page 3 – 209)
EDW_BIL_CRIT_CUST_SUM_F	(See page 3 – 210)
EDW_BIL_CUST_PRF_SUM_F	(See page 3 – 212)
EDW_BIL_CUST_REQSTS_F	(See page 3 – 214)
EDW_BIL_CUST_REQSTS_FSTG	(See page 3 – 216)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_CUST_RMGT_SUM_F	(See page 3 – 218)
EDW_BIL_CUST_SATFCTN_F	(See page 3 – 220)
EDW_BIL_CUST_SATFCTN_FSTG	(See page 3 – 222)
EDW_BIL_CUST_SATIS_SUM_F	(See page 3 – 224)
EDW_BIL_LEADS_F	(See page 3 – 226)
EDW_BIL_LEADS_FSTG	(See page 3 – 228)
EDW_BIL_LEADS_TER_GRP	(See page 3 – 230)
EDW_BIL_OPTYS_F	(See page 3 – 231)
EDW_BIL_OPTYS_FSTG	(See page 3 – 233)
EDW_BIL_OPTY_PERF_SUM_F	(See page 3 – 235)
EDW_BIL_OPTY_TER_GRP	(See page 3 – 237)
EDW_BIL_OPTY_TGRP_BSTG	(See page 3 – 238)
EDW_BIL_ORDRS_TER_GRP	(See page 3 – 239)
EDW_BIL_ORDRS_TGRP_BSTG	(See page 3 – 240)
EDW_BIL_PROD_PERF_SUM_F	(See page 3 – 241)
EDW_BIL_QUOTES_F	(See page 3 – 243)
EDW_BIL_QUOTES_FSTG	(See page 3 – 245)
EDW_BIL_QUOTE_TER_GRP	(See page 3 – 247)
EDW_BIL_QUOTE_TGRP_BSTG	(See page 3 – 248)
EDW_BIL_ROC_SUM_F	(See page 3 – 249)
EDW_BIL_SCHN_PER_SUM_F	(See page 3 – 251)
EDW_BIL_SF_COMP_F	(See page 3 – 253)
EDW_BIL_SF_COMP_FSTG	(See page 3 – 255)
EDW_BIL_SF_PROFILE_F	(See page 3 – 257)
EDW_BIL_SF_PROFILE_FSTG	(See page 3 – 259)
EDW_BIL_SF_STER_REV_F	(See page 3 – 261)
EDW_BIL_SF_STER_REV_FSTG	(See page 3 – 263)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSFRCE_M	(See page 3 – 265)
EDW_BIL_SLSF_A_LTC	(See page 3 – 269)
EDW_BIL_SLSF_SGRP1_LSTG	(See page 3 – 270)
EDW_BIL_SLSF_SGRP1_LTC	(See page 3 – 271)
EDW_BIL_SLSF_SGRP2_LSTG	(See page 3 – 272)
EDW_BIL_SLSF_SGRP2_LTC	(See page 3 – 273)
EDW_BIL_SLSF_SGRP3_LSTG	(See page 3 – 274)
EDW_BIL_SLSF_SGRP3_LTC	(See page 3 – 275)
EDW_BIL_SLSF_SGRP4_LSTG	(See page 3 – 276)
EDW_BIL_SLSF_SGRP4_LTC	(See page 3 – 277)
EDW_BIL_SLSF_SGRP5_LSTG	(See page 3 – 278)
EDW_BIL_SLSF_SGRP5_LTC	(See page 3 – 279)
EDW_BIL_SLSF_SGRP6_LSTG	(See page 3 – 280)
EDW_BIL_SLSF_SGRP6_LTC	(See page 3 – 281)
EDW_BIL_SLSF_SGRP7_LSTG	(See page 3 – 282)
EDW_BIL_SLSF_SGRP7_LTC	(See page 3 – 283)
EDW_BIL_SLSF_SREP_LSTG	(See page 3 – 284)
EDW_BIL_SLSF_SREP_LTC	(See page 3 – 286)
EDW_BIL_SLSTER_A_LTC	(See page 3 – 287)
EDW_BIL_SLSTER_M	(See page 3 – 288)
EDW_BIL_SLSTER_TERR_LTC	(See page 3 – 292)
EDW_BIL_SLSTER_TER_LSTG	(See page 3 – 293)
EDW_BIL_SLSTER_TGRP1_LSTG	(See page 3 – 294)
EDW_BIL_SLSTER_TGRP1_LTC	(See page 3 – 295)
EDW_BIL_SLSTER_TGRP2_LSTG	(See page 3 – 296)
EDW_BIL_SLSTER_TGRP2_LTC	(See page 3 – 297)
EDW_BIL_SLSTER_TGRP3_LSTG	(See page 3 – 298)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSTER_TGRP3_LTC	(See page 3 – 299)
EDW_BIL_SLSTER_TGRP4_LSTG	(See page 3 – 300)
EDW_BIL_SLSTER_TGRP4_LTC	(See page 3 – 301)
EDW_BIL_SLSTER_TGRP5_LSTG	(See page 3 – 302)
EDW_BIL_SLSTER_TGRP5_LTC	(See page 3 – 303)
EDW_BIL_SLSTER_TGRP6_LSTG	(See page 3 – 304)
EDW_BIL_SLSTER_TGRP6_LTC	(See page 3 – 305)
EDW_BIL_SLSTER_TGRP7_LTC	(See page 3 – 306)
EDW_BIL_SLSTER_TGRP7_LTSG	(See page 3 – 307)
EDW_BIL_SLS_CYCLE_SUM_F	(See page 3 – 308)
EDW_BIL_SREP_PERF_SUM_F	(See page 3 – 310)
EDW_BIL_SREQ_SEV_M	(See page 3 – 312)
EDW_BIL_SRV_REQ_SUM_F	(See page 3 – 313)
EDW_BIL_SR_SV_SRSV_A_LTC	(See page 3 – 315)
EDW_BIL_SR_SV_SRSV_LSTG	(See page 3 – 316)
EDW_BIL_SR_SV_SRSV_LTC	(See page 3 – 317)
EDW_BIL_SR_TER_GRP_B	(See page 3 – 318)
EDW_BIL_SR_TER_GRP_BSTG	(See page 3 – 319)
EDW_BIL_STER_ORDRS_F	(See page 3 – 320)
EDW_BIL_STER_ORDRS_FSTG	(See page 3 – 322)
EDW_BIL_WIN_PROB_A_LTC	(See page 3 – 324)
EDW_BIL_WIN_PROB_LSTG	(See page 3 – 325)
EDW_BIL_WIN_PROB_LTC	(See page 3 – 326)
EDW_BIL_WIN_PROB_M	(See page 3 – 327)
EDW_BIM_LEAD_STATUSES_M	(See page 3 – 328)
EDW_BIM_OPP_STATUSES_M	(See page 3 – 329)
EDW_SOURCE_INSTANCES	(See page 3 – 330)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_SOURCE_INSTANCES_TL	(See page 3 – 331)
JTF_BIS_CHART_FUNCTIONS	CRM BIS 11.5.1 Chart Plug Reports (See page 3 – 332)
JTF_BIS_USER_CHART_PLUGS	This table is for storing Chart report information for each user-defined Chart Plug (See page 3 – 333)
JTF_BIS_USER_FAVORITE_PLUGS	This table is for storing Chart report information for each user-defined Favorite Plug (See page 3 – 334)
JTF_BRM_PARAMETERS	Parameters for the main workflow process of the Business Rule Monitor. (See page 3 – 335)
JTF_RS_GROUPS_B	Base Table JTF_RS_GROUPS_B stores general information about a given Group. (See page 3 – 336)
JTF_RS_GROUPS_DENORM	This is a denormalized table for Group. It stores information about parent group and immediate parent flag. (See page 3 – 338)
JTF_RS_GROUPS_TL	Translation table for JTF_RS_GROUPS_B. It is used to store all columns and data that are needed for Multi-Language Support. (See page 3 – 340)
JTF_RS_GROUP_MEMBERS	This table stores the resources who are assigned to be group members. Primary key is Group_member_id. (See page 3 – 341)
JTF_RS_GROUP_USAGES	This table stores the usages which are assigned to be groups. Primary key is Group_usage_id. Group_id and usage are unique key. (See page 3 – 343)
JTF_RS_GRP_RELATE_AUD	The table that stores audit information for a group relation (See page 3 – 345)
JTF_RS_GRP_RELATIONS	This table stores the relations between Groups. Primary key is Group_relate_id. Ex. for relation_type is 'PARENT_GROUP' (See page 3 – 346)
JTF_RS_JOB_ROLES	This table stores the relations between roles and jobs. Primary key is job_role_id. (See page 3 – 348)
JTF_RS_REP_MANAGERS	Denormalized table that stores the reporting hierarchy of group members (See page 3 – 350)

JTF_RS_RESOURCE_EXTNS	This is table stores all important information about Resources. These Resources are coming from HR or HZ or Vonder table etc. Primary key is resource_id. Resource_number, user_id sre also unique keys. (See page 3 – 352)
JTF_RS_RESOURCE_VALUES	This table stores resource values. Resource_param_value_id is the primary key. (See page 3 – 355)
JTF_RS_ROLES_B	Base Table JTF_RS_ROLES_B stores general information about a given Role. (See page 3 – 357)
JTF_RS_ROLES_TL	Translation table for JTF_RS_ROLES_B. It is used to store all columns and data that are needed for Multi-Language Support. (See page 3 – 359)
JTF_RS_ROLE_RELATE_AUD	Base Table which stores audit information for a Role Relation. (See page 3 – 360)
JTF_RS_ROLE_RELATIONS	This table stores the association between resources and roles. Primary key is Resource_id and Role_id. Each resource can be assigned to multipple roles. (See page 3 – 361)
JTF_RS_SALESREPS	This table stores information about salesreps. Salesrep_id is the primary key. If resource category is 'OTHERS' then salesrep_number and org_id are unique. (See page 3 – 363)
JTF_RS_SRP_TERRITORIES	This table stores information about combination of salesrep and territories. (See page 3 – 365)
JTF_RS_TEAMS_B	Base Table JTF_RS_TEAMS_B stores general information about a given Team. (See page 3 – 367)
JTF_RS_TEAMS_TL	Translation table for JTF_RS_TEAMS_B. It is used to store all columns and data that are needed for Multi-Language Support. (See page 3 – 368)
OE_ORDER_HEADERS_ALL	OE_ORDER_HEADERS_ALL stores header information for orders in Order Management. (See page 3 – 386)
OE_ORDER_LINES_ALL	OE_ORDER_LINES_ALL stores information for all order lines in Oracle Order Management. (See page 3 – 392)

Public View List

This section lists each public database view that Oracle Sales Intelligence uses and provides a brief description of each of those views. These views may be useful for your custom reporting or other data requirements. The page reference is to the detailed view description in Chapter 3.

Oracle Sales Intelligence uses the following public views:

View Name	Description
ASO_HEADER_RELATIONSHIPS_V	view based on aso_header_relationships (See page 3 – 32)
ASO_I_OE_ORDER_HEADERS_V	This view includes all columns from the Oracle Order Management tables and is currently used by Oracle Sales Compensation only. (See page 3 – 33)
ASO_I_OE_ORDER_LINES_V	This view includes all columns from the Oracle Order Management order lines tables and is currently used by Oracle Sales Compensation only. (See page 3 – 38)
ASO_I_OE_SALES_CREDITS_V	view retrieves sales credit information from Order Management (See page 3 – 51)
ASO_I_ORDER_TYPES_V	view gives information regarding valid order types recognized by Order Management (See page 3 – 52)
ASO_I_SALES_CHANNELS_V	view can used as an LOV for the available sales channels (See page 3 – 53)
ASO_I_SALES_CREDITS_V	view gives the salesrep, salescredit information (See page 3 – 54)
ASO_I_SALES_CREDIT_TYPES_V	view used to retrieve all valid sales credit types (See page 3 – 55)
ASO_PARTY_RELATIONSHIPS_V	view based on aso_party_relationships (See page 3 – 56)
ASO_QUOTE_HEADERS_ALL_V	quotations (See page 3 – 59)
ASO_QUOTE_HEADERS_V	quotations (See page 3 – 62)
ASO_QUOTE_LINES_ALL_V	quote lines (See page 3 – 69)
ASO_QUOTE_LINES_V	quote lines (See page 3 – 72)
ASO_QUOTE_LINE_ATTRIBS_V	view based on quote line attribs (See page 3 – 76)
ASO_QUOTE_LINE_DETAILS_V	view based on quote line details (See page 3 – 80)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ASO_QUOTE_RELATED_OBJECTS_V	view based on aso_quote_related_objects (See page 3 – 84)
BIC_CUSTOMER_SUMMARY	(See page NO TAG)
BIL_AK_DUMMY_V	Dummy view used to enable use of AK schema for BIL reports (See page NO TAG)
BIL_DIMV_ACCOUNTS	– Obsolete for version 11.5.2 (See page NO TAG)
BIL_DIMV_COMP_PLANS	Compensation plans view (See page NO TAG)
BIL_DIMV_CREDIT_TYPE	Credit types view (See page NO TAG)
BIL_DIMV_CURRENCIES	Currency codes view (See page NO TAG)
BIL_DIMV_CUSTOMERS	Customers view (See page NO TAG)
BIL_DIMV_EMP_STATUS	Employee statuses view (See page NO TAG)
BIL_DIMV_INTEREST_CODES	Interest codes view (See page NO TAG)
BIL_DIMV_INTEREST_TYPES	Interest types view (See page NO TAG)
BIL_DIMV_JOB_TITLE	Sales representatives job tiles view (See page NO TAG)
BIL_DIMV_OPTY_STATUSES	Opportunity Statuses view (See page NO TAG)
BIL_DIMV_PERIODS	Accounting periods view (See page NO TAG)
BIL_DIMV_PLAN_ELEMENTS	Compensation plan elements view (See page NO TAG)
BIL_DIMV_PRIM_INT_CODES	Primary interest codes view (See page NO TAG)
BIL_DIMV_PROD_LOV	List of values view of product hierarchy (See page NO TAG)
BIL_DIMV_QUALIFICATIONS	Sales representative qualifications view (See page NO TAG)
BIL_DIMV_RATING_FACTORS	Rating factors view (See page NO TAG)
BIL_DIMV_SALESFORCE	Salesforce view (sales reps) (See page NO TAG)
BIL_DIMV_SALES_GROUPS	Sales groups view (See page NO TAG)
BIL_DIMV_SALES_STAGES	Sales Stages view (See page NO TAG)
BIL_DIMV_SEC_INT_CODES	Secondary interest codes view (See page NO TAG)
BIL_DIMV_SKILLS	Sales representative skills view (See page NO TAG)
BIL_DIMV_SLSGRPS_HIER	Obsolete in 11.5.2 (See page NO TAG)
BIL_DIMV_SLSPROD_HIER	Product hierarchy view (See page NO TAG)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

BIL_DIMV_SLS_CHANNELS	Sales channels view (See page NO TAG)
BIL_DIMV_SRV_SVTYS	Service incident severities view (See page NO TAG)
BIL_DIMV_TERRITORIES	Sales territories view (See page NO TAG)
BIL_DIMV_TERR_HIER	Sales territory hierarchy view (See page NO TAG)
BIL_DIMV_TOP_BOTTOM	List of values view (See page NO TAG)
BIL_DIMV_TOT_COMP_PLANS	List of values view (See page NO TAG)
BIL_DIMV_TOT_JOB_TITLES	List of values view (See page NO TAG)
BIL_DIMV_TOT_SLSFORCE	List of values view (See page NO TAG)
BIL_DIMV_TOT_SLSPRODS	List of values view (See page NO TAG)
BIL_DIMV_TOT_TERRITORY	List of values view (See page NO TAG)
BIL_DIMV_UOM	Units of measure view (See page NO TAG)
BIL_FCTV_COMP_AMOUNTS	Quantitative measures related to sales compensation (See page NO TAG)
BIL_FCTV_COMP_REVENUE	Quantitative measure related to revenue return on sales compensation (See page NO TAG)
BIL_FCTV_CS_INCIDENTS	Quantitative measures related to customer service requests (See page NO TAG)
BIL_FCTV_GROSS_MARGIN	Quantitative and descriptive information related to sales orders and sales margin (See page NO TAG)
BIL_FCTV_OPP_SLS_TEAMS	Quantitative measures related to sales opportunities (See page NO TAG)
BIL_FCTV_ORDERS	Quantitative information related to customer sales orders (See page NO TAG)
BIL_FCTV_PIPELINE	Quantitative measures related to sales opportunities (See page NO TAG)
BIL_FCTV_QUOTAS	Quantitative measures related to salesforce quotas (See page NO TAG)
BIL_FCTV_QUOTES	Quantitative measures related to sales quotes (See page NO TAG)

BIL_FCTV_SALES_LEADS	Quantitative measures related to sales leads (See page NO TAG)
BIL_SUMV_IMP_CUST	Quantitative measures related to identifying important customers (See page NO TAG)
BIL_SUMV_OPTY_PERF	Quantitative measures related to reporting on oportunity performance (See page NO TAG)
BIL_SUMV_PROD_SCT_WL	Quantitative measures related to reporting on product sales cycle and won/lost opportunitites (See page NO TAG)
BIL_SUMV_REV_CUST	Quantitative measure related to reporting on customer revenue (See page NO TAG)
BIL_SUMV_ROC	Qunatitative measures related to reporting on return on sales compensation (See page NO TAG)
BIL_SUMV_SLS_CHNL_PERF	(See page NO TAG)
BIL_SUMV_SREP_PERF	Quantitative measure related to reporting on salesforce performance (See page NO TAG)
BIL_SUMV_SRV_RQST	Obsolete (See page NO TAG)
OE_CRM_ORDER_HEADERS_V	Compatible view provoded for CRM usage only. The view is based on oe_order_headers_all table. (See page 3 – 369)
OE_CRM_ORDER_LINES_V	Compatible view provoded for CRM usage only. The view is based on oe_order_lines_all table. (See page 3 – 374)
OE_CRM_SALES_CREDITS_V	Compatible view provoded for CRM usage only. The view is based on oe_sales_credits and ra_salesreps. (See page 3 – 384)

Internal View List

This section lists each private, internal view that Oracle Sales Intelligence uses.



Warning: Oracle Corporation does not support access to Oracle Applications data using these views, except from standard Oracle Applications forms, reports, and programs.

Oracle Sales Intelligence uses the following internal views:

- ASO_I_OPPORTUNITIES_V

Single Organization View List

Multi–Organization Support is a feature that allows you to implement multiple sets of books within a single installation of Oracle Payables, Oracle Receivables, Oracle Purchasing, and Oracle Order Entry/Shipping. Instead of using multiple installations to provide data security, data is secured by operating unit.

In Release 10.7, we added a column, `ORG_ID`, to each base table that requires “partitioning” by operating unit, including all transaction tables and many reference tables, then renamed these tables to end with the suffix `_ALL`. Then, to take the place of the renamed table, we create a view (named like the Release 10.6 or earlier table) containing a `WHERE` clause that automatically restricts data to a single operating unit. The `WHERE` clause relies upon the value of an Oracle global variable to indicate the current organization.

If you want to retrieve all information, regardless of operating unit, query the `_ALL` table. For example, if you are running a cross–organization report, you probably want to query the `_ALL` table.

However, if you want to report against only a single organization or operating unit, query the corresponding cross–organizational view, using the familiar 10.6–style table name. The view definition will automatically retrieve only data for your current operating unit.



Additional Information: *Multiple Organizations in Oracle Applications*

Oracle Sales Intelligence uses the following Single Organization views:

- `ASO_I_ORDER_HEADERS_V`
- `ASO_I_ORDER_LINES_V`
- `ASO_QUOTE_LINES`

Multilingual View List

This section lists each MultiLingual database view that Oracle Sales Intelligence uses. MultiLingual views were created to allow certain seed data to be available in multiple national languages simultaneously.

Oracle Sales Intelligence uses the following Multilingual views:

- ASO_QUOTE_STATUSES_VL

Module List

This section lists each form, report and concurrent program comprising Sales Intelligence.

Detailed Design

This chapter presents a detailed design for implementing Oracle Sales Intelligence. It contains detailed definitions of tables and views that you may need to reference to write custom reports or use for other data extraction.

Overview of Detailed Design

During Detailed Design, we specify in detail how each applications component should work. We prepare detailed definitions of tables and views.

You can refer to this Detailed Design chapter to gain a detailed understanding of the underlying structure and processing of Oracle Sales Intelligence that enables you to:

- Convert existing application data
- Integrate your Oracle Sales Intelligence application with your other applications systems
- Write custom reports
- Define alerts against Oracle Applications tables
- Create views for decision support queries using query tools

Table and View Definitions

The Table and View Definitions section contains a detailed definition of Oracle Sales Intelligence applications tables. For each table, it provides information about primary keys, foreign keys, QuickCodes, indexes, triggers, and sequences. It also gives you a detailed description of each column and its characteristics. In addition, it provides the SQL statement that defines each view. Review this section to get a detailed understanding of what tables your Oracle Sales Intelligence application contains, and how it uses them to hold and access the information it needs.

Table and View Definitions

This section contains a detailed description of each Oracle Sales Intelligence table and view that you may need to reference. For each table, it presents detailed information about:

- Primary keys
- Foreign keys
- Column descriptions
- Indexes
- Oracle sequences
- Triggers
- View derivations

The following sections appear in each table or view description:

Foreign Keys

To help you understand the relationships between tables, we list each foreign key contained in a table. For each foreign key in a table, we list the primary key table name (the table to which a foreign key refers), its corresponding primary key columns, and the foreign key columns that refer to those primary key columns.

When the primary key table has a composite primary key, we list each column of the composite key sequentially.

If a table contains two or more distinct foreign keys that refer to the same primary key table, we repeat the primary key table name and list each of the distinct foreign keys separately.

QuickCodes Columns

When a database column contains a QuickCodes value, which we implement using a foreign key to FND_LOOKUPS, MFG_LOOKUPS, or to some other lookup table, we list the QuickCodes type (lookup type) to which the QuickCodes value must belong and a complete list of QuickCodes values and meanings. Some QuickCodes can be defined by you in the application. These values are designated as User-defined.

Column Descriptions

We list the important characteristics of each column in a table or view. These characteristics include whether the column is part of the table's primary key, whether Oracle8i requires a value for this column, and the data type of the column. We also give you a brief description of how Oracle Sales Intelligence uses the column.

When a column is part of a table's primary key, we append the notation (PK) to the name of that column.

To help you understand which columns Oracle Sales Intelligence uses and which columns it does not use, we alert you to any unused column. When no module uses a database column, we show one of the following legends in the Description column:

Not currently used	Oracle Sales Intelligence does not use this column, although the column might be used in a future release.
No longer used	Oracle Sales Intelligence no longer uses this column. AutoInstall installs this column. Subsequent versions of Oracle Sales Intelligence might not include this column.
No longer installed	Oracle Sales Intelligence no longer uses this column. If you <i>upgraded</i> your software from an earlier version, you may still have this column, depending upon whether you chose to delete it during an upgrade process. If you <i>install</i> Oracle Sales Intelligence, you do not have this column.

Standard Who Columns

Most Oracle Sales Intelligence tables contain standard columns to support \ Row Who. When your program or SQL*Plus command selects a row from a table, use these columns to determine who last updated the row. If your program or SQL*Plus command updates or inserts a row in an interface table, you must populate each of the five standard Who columns:

LAST_UPDATE_DATE	Date when a user last updated this row
LAST_UPDATED_BY	User who last updated this row (foreign key to FND_USER.USER_ID)
CREATION_DATE	Date when this row was created

CREATED_BY	User who created this row (foreign key to FND_USER.USER_ID)
LAST_UPDATE_LOGIN	Operating system login of user who last updated this row (foreign key to FND_LOGINS.LOGIN_ID). You should set this to NULL, or to 0 if NULL is not allowed

Since every table containing Who columns has several foreign keys to the tables FND_USER and FND_LOGINS, we do not include the foreign key columns LAST_UPDATED_BY, CREATED_BY, or LAST_UPDATE_LOGIN in a table's list of foreign keys.

Additional Who Columns for Concurrent Programs

Some Oracle Sales Intelligence tables also contain several additional Who columns to distinguish between changes a user makes with a form and changes a concurrent program makes. When a concurrent program updates or inserts a row in a table, the concurrent program populates the following additional Who columns:

REQUEST_ID	Concurrent request ID of program that last updated this row (foreign key to FND_CONCURRENT_REQUESTS.REQUEST_ID)
PROGRAM_APPLICATION_ID	Application ID of program that last updated this row (foreign key to FND_APPLICATION.APPLICATION_ID)
PROGRAM_ID	Program ID of program that last updated this row (foreign key to FND_CONCURRENT_PROGRAM.CONCURRENT_PROGRAM_ID)
PROGRAM_UPDATE_DATE	Date when a program last updated this row

Since every table containing these additional Who columns has several foreign keys to the tables FND_CONCURRENT_REQUESTS, FND_APPLICATION, and FND_CONCURRENT_PROGRAM, we do not include the foreign key columns REQUEST_ID, PROGRAM_APPLICATION_ID, or PROGRAM_ID in a table's list of foreign keys.

Indexes

If an Oracle Sales Intelligence table uses an Oracle8i index, we list the database columns that comprise that index, in sequential order.

Note: The indexes we document in this manual correspond to unique keys we specified during product development and testing. In some cases, we may add additional indexes during the porting process to fine-tune performance on specific platforms; therefore, there may be minor differences between the indexes documented in this book and the indexes for production versions of Oracle Sales Intelligence.

Sequences

Oracle Sales Intelligence uses Oracle8i sequence generators to generate unique integers. If any table column gets its value from an Oracle8i sequence generator, we list the name of the corresponding sequence generator and the name of the column that stores the unique integer.

Database Triggers

If a table has one or more active database triggers, we provide a brief explanation of each database trigger and when it fires.

View Derivation

For each Oracle Sales Intelligence view you may need to reference, we include important elements from the SQL statement that defines or creates a view. By studying this view definition, you can understand exactly how a view derives its contents.

AK_ATTRIBUTES

AK_ATTRIBUTES contains information about the attributes you define. You need one row for each attribute.

Each attribute has a name, an application that owns the attribute, formatting properties, a default value, a prompt, and a data type (i.e., Number, Varchar2, Date, etc.).

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
DATA_TYPE	DATA_TYPE	AK_LOOKUP_CODES
	BOOLEAN	Boolean
	DATE	Date
	DATETIME	Datetime
	NUMBER	Number
	URL	URL
HORIZONTAL_ALIGNMENT	VARCHAR2	Varchar2
	HORIZONTAL_ALIGNMENT	AK_LOOKUP_CODES
	CENTER	Center
	LEFT	Left
VERTICAL_ALIGNMENT	RIGHT	Right
	VERTICAL_ALIGNMENT	AK_LOOKUP_CODES
	BOTTOM	Bottom
	CENTER	Center
	TOP	Top

Column Descriptions

Name	Null?	Type	Description
ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	Attribute identifier
ATTRIBUTE_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application ID which the attribute belongs to
ATTRIBUTE_LABEL_LENGTH	NULL	NUMBER(15)	Number of characters to be displayed for the attribute label
ATTRIBUTE_VALUE_LENGTH	NULL	NUMBER(15)	Number of characters to be displayed for the attribute value
BOLD	NOT NULL	VARCHAR2(1)	Bold flag ('Y' - Bold the attribute value, 'N' - Do not bold the attribute value)
ITALIC	NOT NULL	VARCHAR2(1)	Italic flag ('Y' - Italicize the attribute value, 'N' - Do not italicize the attribute value)
VERTICAL_ALIGNMENT	NOT NULL	VARCHAR2(30)	Vertical Alignment for attribute
HORIZONTAL_ALIGNMENT	NOT NULL	VARCHAR2(30)	Horizontal alignment for attribute
DATA_TYPE	NOT NULL	VARCHAR2(30)	Data type of attribute
UPPER_CASE_FLAG	NULL	VARCHAR2(1)	Flag to indicate whether the attribute should be in upper case ('Y' - upper case, 'N' - not upper case)

DEFAULT_VALUE_VARCHAR2	NULL	VARCHAR2(240)	Default value of attribute when the data type of the attribute is VARCHAR
DEFAULT_VALUE_NUMBER	NULL	NUMBER(15)	Default value of attribute when the data type of the attribute is NUMBER
DEFAULT_VALUE_DATE	NULL	DATE	Default value of attribute when the data type of the attribute is DATE or DATETIME
LOV_REGION_CODE	NULL	VARCHAR2(30)	LOV Region identifier
LOV_REGION_APPLICATION_ID	NULL	NUMBER(15)	Product team's application ID which the LOV Region belongs to
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column
ITEM_STYLE	NOT NULL	VARCHAR2(30)	
DISPLAY_HEIGHT	NULL	NUMBER	
CSS_CLASS_NAME	NULL	VARCHAR2(80)	
POPLIST_VIEWOBJECT	NULL	VARCHAR2(240)	
POPLIST_DISPLAY_ATTRIBUTE	NULL	VARCHAR2(80)	
POPLIST_VALUE_ATTRIBUTE	NULL	VARCHAR2(80)	
CSS_LABEL_CLASS_NAME	NULL	VARCHAR2(80)	

Indexes

Index Name	Index Type	Sequence	Column Name
AK_ATTRIBUTES_U1	UNIQUE	4	ATTRIBUTE_CODE
		6	ATTRIBUTE_APPLICATION_ID

AK_ATTRIBUTES_TL

AK_ATTRIBUTES_TL stores translated information about the attributes in AK_ATTRIBUTES. Each row includes the language the row is translated to, the name, description, and label of the attribute, and the attribute identifier which uniquely identifies the attribute. You need one row for each attribute in each of the installed languages. Each row includes a language and SOURCE_LANG column which can be used to determine if a value has been translated or defaulted.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AK_ATTRIBUTES	ATTRIBUTE_APPLICATION_ID ATTRIBUTE_CODE	ATTRIBUTE_APPLICATION_ID ATTRIBUTE_CODE

Column Descriptions

Name	Null?	Type	Description
ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	Attribute identifier
ATTRIBUTE_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application ID which the attribute belongs to
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	The language code of the language which the translatable fields are translated to
NAME	NOT NULL	VARCHAR2(80)	Name of the attribute
ATTRIBUTE_LABEL_LONG	NULL	VARCHAR2(80)	Label/Prompt of attribute
ATTRIBUTE_LABEL_SHORT	NULL	VARCHAR2(40)	A short label/prompt of attribute (this column is obsolete, do not use)
DESCRIPTION	NULL	VARCHAR2(2000)	Description of attribute
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language code of the language which the values of the translatable columns were originally entered
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column

Indexes

Index Name	Index Type	Sequence	Column Name
AK_ATTRIBUTES_TL_U1	UNIQUE	4	ATTRIBUTE_CODE
		6	ATTRIBUTE_APPLICATION_ID
		8	LANGUAGE

AK_OBJECTS

AK_OBJECTS contains database object name and the owner (application id) of the database object name. You need one row for each object that you want to define.

An object is a logical representation of a database view. The database object name is the name of a view in the database. Thus, there can only be one AK_OBJECTS per view. This view must exist in FND_VIEW or ALL_VIEWS.

You must specify a unique key name for each database object name.

Column Descriptions

Name	Null?	Type	Description
DATABASE_OBJECT_NAME (PK)	NOT NULL	VARCHAR2(30)	Unique identifier of a database object
PRIMARY_KEY_NAME	NULL	VARCHAR2(30)	Primary key of the database object
DEFAULTING_API_PKG	NULL	VARCHAR2(30)	PL/SQL package name which contains code used to populate default values to the attributes for this object
DEFAULTING_API_PROC	NULL	VARCHAR2(30)	Procedure name in the PL/SQL package which is used to populate default values for the attributes on the object
VALIDATION_API_PKG	NULL	VARCHAR2(30)	PL/SQL package name which contains code used to validate the attributes for this object
VALIDATION_API_PROC	NULL	VARCHAR2(30)	Procedure name in the PL/SQL package which is used to validate the attributes for this object
APPLICATION_ID	NOT NULL	NUMBER(15)	Product team's application id which the database object belong to
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column

Indexes

Index Name	Index Type	Sequence	Column Name
AK_OBJECTS_U1	UNIQUE	2	DATABASE_OBJECT_NAME

AK_OBJECTS_TL

AK_OBJECTS_TL stores translated information about the objects in AK_OBJECTS. Each row includes the language the row is translated to, the translated attributes of the object, and the object identifier which uniquely identifies the object. You need one row for each object in each of the installed languages. Each row includes a language and SOURCE_LANG column which can be used to determine if a value has been translated or defaulted.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AK_OBJECTS	DATABASE_OBJECT_NAME	DATABASE_OBJECT_NAME

Column Descriptions

Name	Null?	Type	Description
DATABASE_OBJECT_NAME (PK)	NOT NULL	VARCHAR2(30)	Unique identifier of database object
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	The language code of the language which the translatable fields are translated to
NAME	NULL	VARCHAR2(30)	User friendly name of database object
DESCRIPTION	NULL	VARCHAR2(2000)	Description of database object
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language code of the language which the values of the translatable columns were originally entered
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column

Indexes

Index Name	Index Type	Sequence	Column Name
AK_OBJECTS_TL_U1	UNIQUE	2 4	DATABASE_OBJECT_NAME LANGUAGE

AK_OBJECT_ATTRIBUTES

AK_OBJECT_ATTRIBUTES defines the attributes on an object. You will need one row for each attribute you want to assign to an object.

You must define formatting properties (i.e., ATTRIBUTE_LABEL_LENGTH, BOLD, ITALIC, VERTICAL_ALIGNMENT, etc.) for each attribute.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AK_ATTRIBUTES	ATTRIBUTE_APPLICATION_ID ATTRIBUTE_CODE	ATTRIBUTE_APPLICATION_ID ATTRIBUTE_CODE
AK_OBJECTS	DATABASE_OBJECT_NAME	DATABASE_OBJECT_NAME

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
DATA_SOURCE_TYPE	DATA_SOURCE_TYPE	AK_LOOKUP_CODES
	3RD NORMAL	3rd Normal
	4TH NORMAL	4th Normal
	VIEW	View
DATA_STORAGE_TYPE	DATA_STORAGE_TYPE	AK_LOOKUP_CODES
	3RD NORMAL	3rd Normal
	4TH NORMAL	4th Normal
HORIZONTAL_ALIGNMENT	HORIZONTAL_ALIGNMENT	AK_LOOKUP_CODES
	CENTER	Center
	LEFT	Left
	RIGHT	Right
VERTICAL_ALIGNMENT	VERTICAL_ALIGNMENT	AK_LOOKUP_CODES
	BOTTOM	Bottom
	CENTER	Center
	TOP	Top

Column Descriptions

Name	Null?	Type	Description
DATABASE_OBJECT_NAME (PK)	NOT NULL	VARCHAR2(30)	Database object identifier
ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	Attribute identifier of a database object
ATTRIBUTE_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application id which the object attribute belong to
COLUMN_NAME	NULL	VARCHAR2(30)	User friendly name of object attribute
ATTRIBUTE_LABEL_LENGTH	NOT NULL	NUMBER(15)	Length of the attribute's prompt/label
BOLD	NOT NULL	VARCHAR2(1)	Bold flag ('Y' - Bold the object attribute value, 'N' - Do not bold the object attribute value)
ITALIC	NOT NULL	VARCHAR2(1)	Italic flag ('Y' - Italicize the object attribute value, 'N' - Do not italicize the object attribute value)
VERTICAL_ALIGNMENT	NOT NULL	VARCHAR2(30)	Vertical Alignment for the object attribute

Oracle Proprietary, Confidential Information--Use Restricted by Contract

HORIZONTAL_ALIGNMENT	NOT NULL	VARCHAR2(30)	Horizontal alignment for object attribute
DATA_SOURCE_TYPE	NOT NULL	VARCHAR2(30)	Data source type specifies where the object attribute comes from
DATA_STORAGE_TYPE	NULL	VARCHAR2(30)	Data source type specifies where the object attribute is stored
TABLE_NAME	NULL	VARCHAR2(30)	User friendly name of database object
BASE_TABLE_COLUMN_NAME	NULL	VARCHAR2(30)	Base table column name
REQUIRED_FLAG	NOT NULL	VARCHAR2(1)	Flag to indicate whether the object attribute should be required ('Y' - required, 'N' - not required)
DISPLAY_VALUE_LENGTH	NOT NULL	NUMBER(15)	Number of characters of object attribute to be displayed
LOV_REGION_CODE	NULL	VARCHAR2(30)	LOV Region identifier
LOV_REGION_APPLICATION_ID	NULL	NUMBER(15)	Product team's application ID which the LOV region is belonged to
LOV_FOREIGN_KEY_NAME	NULL	VARCHAR2(30)	Lov foreign key relationship identifier
LOV_ATTRIBUTE_CODE	NULL	VARCHAR2(30)	LOV attribute identifier
LOV_ATTRIBUTE_APPLICATION_ID	NULL	NUMBER(15)	Product team's application id which the lov attribute belong to
DEFAULTING_API_PKG	NULL	VARCHAR2(30)	PL/SQL package name which contains the stored procedure to populate default values into this object attribute
DEFAULTING_API_PROC	NULL	VARCHAR2(30)	Procedure name in PL/SQL package which populates default values into this object attribute
VALIDATION_API_PKG	NULL	VARCHAR2(30)	PL/SQL package name which contains the procedure to validate the object attribute's value
VALIDATION_API_PROC	NULL	VARCHAR2(30)	Procedure name in PL/SQL package which contains the procedure to validate the object attribute's value
DEFAULT_VALUE_VARCHAR2	NULL	VARCHAR2(240)	Default value of object attribute when the data type of the object attribute is VARCHAR
DEFAULT_VALUE_NUMBER	NULL	NUMBER(15)	Default value of object attribute when the data type of the object attribute is NUMBER
DEFAULT_VALUE_DATE	NULL	DATE	Default value of object attribute when the data type of the object attribute is DATE
TRANSLATION_FLAG	NULL	VARCHAR2(1)	Flag which indicates whether the mapping database column is translatable, valid values are 'Y' and 'N'.
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column

Indexes

Index Name	Index Type	Sequence	Column Name
AK_OBJECT_ATTRIBUTES_U1	UNIQUE	2	DATABASE_OBJECT_NAME
		6	ATTRIBUTE_CODE
		8	ATTRIBUTE_APPLICATION_ID

AK_OBJECT_ATTRIBUTES_TL

AK_OBJECT_ATTRIBUTES_TL stores translated information about the object attribute in AK_OBJECT_ATTRIBUTES. Each row includes the language the row is translated to, the translated attributes of the object attribute, and the object attribute identifier which uniquely identifies the object attribute. You need one row for each object attribute in each of the installed languages. Each row includes a language and SOURCE_LANG column which can be used to determine if a value has been translated or defaulted.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AK_OBJECT_ATTRIBUTES	ATTRIBUTE_APPLICATION_ID	ATTRIBUTE_APPLICATION_ID
	ATTRIBUTE_CODE	ATTRIBUTE_CODE
	DATABASE_OBJECT_NAME	DATABASE_OBJECT_NAME

Column Descriptions

Name	Null?	Type	Description
DATABASE_OBJECT_NAME (PK)	NOT NULL	VARCHAR2(30)	Database object identifier
ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	Attribute identifier of a database object
ATTRIBUTE_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application id which the object attribute belong to
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	The language code of the language which the translatable fields are translated to
ATTRIBUTE_LABEL_LONG	NULL	VARCHAR2(80)	Label/Prompt of object attribute
ATTRIBUTE_LABEL_SHORT	NULL	VARCHAR2(30)	A short label/prompt of object attribute (this column is obsolete, do not use)
SOURCE_LANG	NOT NULL	VARCHAR2(4)	The language code of the language which the translatable fields are translated to
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column

Indexes

Index Name	Index Type	Sequence	Column Name
AK_OBJECT_ATTRIBUTES_TL_U1	UNIQUE	2	DATABASE_OBJECT_NAME
		6	ATTRIBUTE_CODE
		8	ATTRIBUTE_APPLICATION_ID
		10	LANGUAGE

Oracle Proprietary, Confidential Information--Use Restricted by Contract

AK_OBJECT_ATTRIBUTE_NAVIGATION

AK_OBJECT_ATTRIBUTE_NAVIGATION is used only by Configurator (CZ). This table provides navigation to a region by attribute value. You need to create one row for each object attribute value that will allow navigation to a region.

You must specify a target "To" region for each object attribute value. If at run time, the object attributes value entered by the user matches a row in this table, the user will have access to the target region associated with this object attribute value.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AK_OBJECT_ATTRIBUTES	DATABASE_OBJECT_NAME	DATABASE_OBJECT_NAME
	ATTRIBUTE_APPLICATION_ID	ATTRIBUTE_APPLICATION_ID
	ATTRIBUTE_CODE	ATTRIBUTE_CODE
AK_REGIONS	REGION_APPLICATION_ID	TO_REGION_APPL_ID
	REGION_CODE	TO_REGION_CODE

Column Descriptions

Name	Null?	Type	Description
DATABASE_OBJECT_NAME (PK)	NOT NULL	VARCHAR2(30)	Database object identifier
ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	Attribute identifier of a database object
ATTRIBUTE_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application id which the object attribute belong to
VALUE_VARCHAR2 (PK)	NUL	VARCHAR2(240)	Value of object attribute if attribute is a VARCHAR
VALUE_DATE (PK)	NUL	DATE	Value of object attribute if attribute is a DATE
VALUE_NUMBER (PK)	NUL	NUMBER(15)	Value of object attribute if attribute is a NUMBER
TO_REGION_CODE	NOT NULL	VARCHAR2(30)	Target region identifier
TO_REGION_APPL_ID	NOT NULL	NUMBER(15)	Product team's application id that the target region belong to
ATTRIBUTE_CATEGORY	NUL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NUL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NUL	VARCHAR2(150)	Descriptive flexfield segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column

Indexes

Index Name	Index Type	Sequence	Column Name
AK_OBJECT_ATTRIBUTE_NAVIGAT_U1	UNIQUE	2	DATABASE_OBJECT_NAME
		6	ATTRIBUTE_CODE
		8	ATTRIBUTE_APPLICATION_ID
		10	VALUE_VARCHAR2
		12	VALUE_DATE
		14	VALUE_NUMBER

AK_OBJECT_VALUES_TEMP

AK_OBJECT_VALUES_TEMP is used to create the LOV for the Value field on the Run Flows form. The lov for the Value field calls a package called AK_RUN_FLOW_PKG which uses this table to store the results from running AK_QUERY_PKG.EXEC_QUERY.

This table should never be populated by any user.

Column Descriptions

Name	Null?	Type	Description
TRACE_NUM	NOT NULL	NUMBER(15)	Trace number
REGION_APPLICATION_ID	NULL	NUMBER(15)	Product team's application id that this region belong to
REGION_CODE	NULL	VARCHAR2(30)	Region identifier
DISPLAY_VALUE	NULL	VARCHAR2(510)	Display value
KEY_VALUE1	NULL	VARCHAR2(240)	First key value of the database object which the region is based on
KEY_VALUE2	NULL	VARCHAR2(240)	Second key value of the database object which the region is based on
KEY_VALUE3	NULL	VARCHAR2(240)	Third key value of the database object which the region is based on
KEY_VALUE4	NULL	VARCHAR2(240)	Fourth key value of the database object which the region is based on
KEY_VALUE5	NULL	VARCHAR2(240)	Fifth key value of the database object which the region is based on
KEY_VALUE6	NULL	VARCHAR2(240)	Sixth key value of the database object which the region is based on
KEY_VALUE7	NULL	VARCHAR2(240)	Seventh key value of the database object which the region is based on
KEY_VALUE8	NULL	VARCHAR2(240)	Eighth key value of the database object which the region is based on
KEY_VALUE9	NULL	VARCHAR2(240)	Ninth key value of the database object which the region is based on
KEY_VALUE10	NULL	VARCHAR2(240)	Tenth key value of the database object which the region is based on

AK_QUERY_OBJECTS

AK_QUERY_OBJECTS table contains query object identifier and the application id of the owner of the query object

Column Descriptions

Name	Null?	Type	Description
QUERY_CODE (PK)	NOT NULL	VARCHAR2(30)	Unique identifier of a query object
APPLICATION_ID	NOT NULL	NUMBER	Application ID of query object owner
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column

Indexes

Index Name	Index Type	Sequence	Column Name
AK_QUERY_OBJECTS_U1	UNIQUE	5	QUERY_CODE

AK_QUERY_OBJECT_LINES

AK_QUERY_OBJECT_LINES contains children of a query object, each of them is a query object line. A query object line usually is a sql statement, it's ordered by seq_num column and its typed is identified by TYPE column.

Column Descriptions

Name	Null?	Type	Description
QUERY_CODE (PK)	NOT NULL	VARCHAR2(30)	Identifier of query object
SEQ_NUM (PK)	NOT NULL	NUMBER	Sequence number of query object line
QUERY_LINE_TYPE	NULL	VARCHAR2(30)	Type of the query object line which indicates what kind of sql clause this is.
QUERY_LINE	NULL	VARCHAR2(4000)	content of query object line, which is usually a sql statement
LINKED_PARAMETER	NULL	VARCHAR2(30)	Not being used, created for future development
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column

Indexes

Index Name	Index Type	Sequence	Column Name
AK_QUERY_OBJECT_LINES_U1	UNIQUE	5 10	QUERY_CODE SEQ_NUM

AK_REGIONS

AK_REGIONS contains regions and the application owner of the region. A region contains a set of items that may be returned by AK_QUERY_PKG. You need to one row for each region.

Each row must include a database object name and a region style. You can also specify the number of columns that are to be displayed on the region as well as an URL for the region.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AK_OBJECTS	DATABASE_OBJECT_NAME	DATABASE_OBJECT_NAME

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
REGION_STYLE	REGION_STYLE	AK_LOOKUP_CODES
	FORM	Single Row
	TABLE	Multi Row

Column Descriptions

Name	Null?	Type	Description
REGION_CODE (PK)	NOT NULL	VARCHAR2(30)	Region identifier
REGION_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application id which the region belong to
DATABASE_OBJECT_NAME	NOT NULL	VARCHAR2(30)	Database object identifier
REGION_STYLE	NOT NULL	VARCHAR2(30)	Region style of the region to be displayed
NUM_COLUMNS	NULL	NUMBER(15)	Number of columns of region to be displayed
REGION_DEFAULTING_API_PKG	NULL	VARCHAR2(30)	PL/SQL package name which contains the stored procedure to populate default values of regions
REGION_DEFAULTING_API_PROC	NULL	VARCHAR2(30)	Procedure name in PL/SQL package which populates default values of regions
REGION_VALIDATION_API_PKG	NULL	VARCHAR2(30)	PL/SQL package name which contains the procedure to validate default values of regions
REGION_VALIDATION_API_PROC	NULL	VARCHAR2(30)	Procedure name in PL/SQL package which contains the procedure to validate default values of regions
ICX_CUSTOM_CALL	NULL	VARCHAR2(80)	A URL to launch an html file
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column
APPLICATIONMODULE_OBJECT_TYPE	NULL	VARCHAR2(240)	
NUM_ROWS_DISPLAY	NULL	NUMBER	
REGION_OBJECT_TYPE	NULL	VARCHAR2(240)	
IMAGE_FILE_NAME	NULL	VARCHAR2(80)	column for putting icon file name when displaying region title
ISFORM_FLAG	NOT NULL	VARCHAR2(1)	column to indicate whether this region is a form
HELP_TARGET	NULL	VARCHAR2(240)	stores location of product team's specific help file

Indexes

Index Name	Index Type	Sequence	Column Name
AK_REGIONS_U1	UNIQUE	4	REGION_CODE
		6	REGION_APPLICATION_ID

AK_REGIONS_TL

AK_REGIONS_TL stores translated information about the regions in AK_REGIONS. Each row includes the language the row is translated to, the translated attributes of the region, and the region identifier which uniquely identifies the region. You need one row for each region in each of the installed languages. Each row includes a language and SOURCE_LANG column which can be used to determine if a value has been translated or defaulted.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AK_REGIONS	REGION_APPLICATION_ID REGION_CODE	REGION_APPLICATION_ID REGION_CODE

Column Descriptions

Name	Null?	Type	Description
REGION_CODE (PK)	NOT NULL	VARCHAR2(30)	Region identifier
REGION_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application id which the region belong to
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	The language code of the language which the translatable fields are translated to
NAME	NOT NULL	VARCHAR2(80)	Friendly user name of region
DESCRIPTION	NULL	VARCHAR2(2000)	Description of region
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language code of the language which the values of the translatable columns were originally entered
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column

Indexes

Index Name	Index Type	Sequence	Column Name
AK_REGIONS_TL_U1	UNIQUE	4	REGION_CODE
		6	REGION_APPLICATION_ID
		8	LANGUAGE

AK_REGION_ITEMS

AK_REGION_ITEMS defines the item (attribute or object attribute) on a region. An item is a single attribute or object attribute that exists on a region. You will need one row for each item you want to assign to a region.

You must define formatting properties (i.e., ATTRIBUTE_LABEL_LENGTH, BOLD, ITALIC, VERTICAL_ALIGNMENT, etc.) for each item. You must also specify if the item is an attribute or object attribute with the OBJECT_ATTRIBUTE_FLAG. This table also allows you to specify other properties for the item.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AK_ATTRIBUTES	ATTRIBUTE_APPLICATION_ID ATTRIBUTE_CODE	ATTRIBUTE_APPLICATION_ID ATTRIBUTE_CODE
AK_REGIONS	REGION_APPLICATION_ID REGION_CODE	REGION_APPLICATION_ID REGION_CODE

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
HORIZONTAL_ALIGNMENT	HORIZONTAL_ALIGNMENT	AK_LOOKUP_CODES
	CENTER	Center
	LEFT	Left
	RIGHT	Right
	ITEM_STYLE	AK_LOOKUP_CODES
	BUTTON	Button
	CHECKBOX	Checkbox
	HIDDEN	Hidden
	IMAGE	Image
	POPLIST	Poplist
	SPINBOX	Spinbox
	TEXT	Text
LOV_DEFAULT_FLAG	LOV_DEFAULT_FLAG	AK_LOOKUP_CODES
	N	No
	Y	Yes
OBJECT_ATTRIBUTE_FLAG	OBJECT_ATTRIBUTE_FLAG	AK_LOOKUP_CODES
	N	Attribute
	Y	Object Attribute
ORDER_DIRECTION	ORDER_DIRECTION	AK_LOOKUP_CODES
	ASC	Ascending
	DESC	Descending
VERTICAL_ALIGNMENT	VERTICAL_ALIGNMENT	AK_LOOKUP_CODES
	BOTTOM	Bottom
	CENTER	Center
	TOP	Top

Column Descriptions

Name	Null?	Type	Description
REGION_CODE (PK)	NOT NULL	VARCHAR2(30)	Region identifier
REGION_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application id which the region belong to
ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	Attribute identifier
ATTRIBUTE_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application ID which the attribute belong to
DISPLAY_SEQUENCE	NOT NULL	NUMBER(15)	Sequence number for displaying region items. Each sequence number should be unique within the same region
NODE_DISPLAY_FLAG	NOT NULL	VARCHAR2(1)	Node display flag ('Y' - Display this region item in a node, 'N' - Do not display this region item in a node)
NODE_QUERY_FLAG	NOT NULL	VARCHAR2(1)	This flag indicates whether the value of this region item can be queried (NODE_QUERY_FLAG = 'Y') or not (NODE_QUERY_FLAG='N')
ATTRIBUTE_LABEL_LENGTH	NOT NULL	NUMBER(15)	Prompt/label length for this item
BOLD	NOT NULL	VARCHAR2(1)	Bold flag ('Y' - Bold the region item, 'N' - Do not bold the region item)
ITALIC	NOT NULL	VARCHAR2(1)	Italic flag ('Y' - Italicize the region item, 'N' - Do not italicize the region item)
VERTICAL_ALIGNMENT	NOT NULL	VARCHAR2(30)	Vertical Alignment for the region item
HORIZONTAL_ALIGNMENT	NOT NULL	VARCHAR2(30)	Horizontal alignment for the region item
ITEM_STYLE	NOT NULL	VARCHAR2(30)	Style of region item
OBJECT_ATTRIBUTE_FLAG	NOT NULL	VARCHAR2(1)	Flag indicates if this item is an attribute (OBJECT_ATTRIBUTE_FLAG = 'N') or an object attribute (OBJECT_ATTRIBUTE_FLAG = 'Y')
UPDATE_FLAG	NOT NULL	VARCHAR2(1)	Flag indicates whether this attribute is updatable (UPDATE_FLAG = 'Y') or not (UPDATE_FLAG = 'N')
REQUIRED_FLAG	NOT NULL	VARCHAR2(1)	Flag indicates whether this attribute is input required for the region (REQUIRED_FLAG = 'Y') or not (REQUIRED_FLAG = 'N')
DISPLAY_VALUE_LENGTH	NOT NULL	NUMBER(15)	Length of region item to be displayed
SECURITY_CODE	NULL	VARCHAR2(30)	Security Code
LOV_REGION_CODE	NULL	VARCHAR2(30)	LOV region identifier
LOV_REGION_APPLICATION_ID	NULL	NUMBER(15)	Product team's application id which the LOV region belong to
LOV_FOREIGN_KEY_NAME	NULL	VARCHAR2(30)	LOV foreign key relationship identifier
LOV_ATTRIBUTE_CODE	NULL	VARCHAR2(30)	LOV attribute identifier
LOV_ATTRIBUTE_APPLICATION_ID	NULL	NUMBER(15)	Product team's application id which the lov attribute belong to
LOV_DEFAULT_FLAG	NULL	VARCHAR2(1)	LOV default flag

Oracle Proprietary, Confidential Information--Use Restricted by Contract

REGION_DEFAULTING_API_PKG	NULL	VARCHAR2(30)	PL/SQL package name which contains the stored procedure to populate default values into this region item
REGION_DEFAULTING_API_PROC	NULL	VARCHAR2(30)	Procedure name in PL/SQL package which populates default values into this region item
REGION_VALIDATION_API_PKG	NULL	VARCHAR2(30)	PL/SQL package name which contains the procedure to validate the region item's value
REGION_VALIDATION_API_PROC	NULL	VARCHAR2(30)	Procedure name in PL/SQL package which contains the procedure to validate the region item's value
ORDER_SEQUENCE	NULL	NUMBER(15)	Order Sequence
ORDER_DIRECTION	NULL	VARCHAR2(30)	Direction of sorting values of region items
DEFAULT_VALUE_VARCHAR2	NULL	VARCHAR2(240)	Default value of region item when the data type of the region item is VARCHAR
DEFAULT_VALUE_NUMBER	NULL	NUMBER(15)	Default value of region item when the data type of the region item is NUMBER
DEFAULT_VALUE_DATE	NULL	DATE	Default value of region item when the data type of the region item is DATE
ICX_CUSTOM_CALL	NULL	VARCHAR2(80)	A URL to launch an html file
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column
DISPLAY_HEIGHT	NULL	NUMBER	
SUBMIT	NOT NULL	VARCHAR2(1)	
ENCRYPT	NOT NULL	VARCHAR2(1)	
NESTED_REGION_CODE	NULL	VARCHAR2(30)	
NESTED_REGION_APPLICATION_ID	NULL	NUMBER	
VIEW_USAGE_NAME	NULL	VARCHAR2(80)	
VIEW_ATTRIBUTE_NAME	NULL	VARCHAR2(80)	
CSS_CLASS_NAME	NULL	VARCHAR2(80)	
POPLIST_VIEWOBJECT	NULL	VARCHAR2(240)	
IMAGE_FILE_NAME	NULL	VARCHAR2(80)	
URL	NULL	VARCHAR2(2000)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

POPLIST_DISPLAY_ATTRIBUTE	NULL	VARCHAR2(80)	
POPLIST_VALUE_ATTRIBUTE	NULL	VARCHAR2(80)	
ITEM_NAME	NULL	VARCHAR2(30)	
CSS_LABEL_CLASS_NAME	NULL	VARCHAR2(80)	
MENU_ID	NULL	NUMBER	menu_id references menu_id in FND_MENUS table

Indexes

Index Name	Index Type	Sequence	Column Name
AK_REGION_ITEMS_U1	UNIQUE	4	REGION_CODE
		6	REGION_APPLICATION_ID
		10	ATTRIBUTE_CODE
		12	ATTRIBUTE_APPLICATION_ID
AK_REGION_ITEMS_U2	UNIQUE	4	REGION_CODE
		6	REGION_APPLICATION_ID
		8	DISPLAY_SEQUENCE

AK_REGION_ITEMS_TL

AK_REGION_ITEMS_TL stores translated information about the region items in AK_REGION_ITEMS. Each row includes the language the row is translated to, the translated attributes of the region item, the region identifier which uniquely identifies the region item and the region items label. You need one row for each region item in each of the installed languages. Each row includes a language and SOURCE_LANG column which can be used to determine if a value has been translated or defaulted.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AK_REGION_ITEMS	REGION_APPLICATION_ID	REGION_APPLICATION_ID
	REGION_CODE	REGION_CODE
	ATTRIBUTE_CODE	ATTRIBUTE_CODE
	ATTRIBUTE_APPLICATION_ID	ATTRIBUTE_APPLICATION_ID

Column Descriptions

Name	Null?	Type	Description
REGION_CODE (PK)	NOT NULL	VARCHAR2(30)	Region identifier
REGION_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application id which the region belong to
ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	Attribute identifier
ATTRIBUTE_APPLICATION_ID (PK)	NOT NULL	NUMBER(15)	Product team's application ID which the attribute belong to
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	The language code of the language which the translatable fields are translated to
ATTRIBUTE_LABEL_LONG	NUL	VARCHAR2(80)	Label/Prompt for this region item
ATTRIBUTE_LABEL_SHORT	NUL	VARCHAR2(30)	A short label/prompt for this region item (this column is obsolete, do not use)
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language code of the language which the values of the translatable columns were originally entered
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER(15)	Standard Who Column
DESCRIPTION	NUL	VARCHAR2(2000)	

Indexes

Index Name	Index Type	Sequence	Column Name
AK_REGION_ITEMS_TL_U1	UNIQUE	4	REGION_CODE
		6	REGION_APPLICATION_ID
		10	ATTRIBUTE_CODE
		12	ATTRIBUTE_APPLICATION_ID
		14	LANGUAGE

AK_REGION_LOV_RELATIONS

Column Descriptions

Name	Null?	Type	Description
REGION_APPLICATION_ID (PK)	NOT NULL	NUMBER	Region Application Id of the region item which launches the LOV
REGION_CODE (PK)	NOT NULL	VARCHAR2(30)	Region Code of the region item which launches the LOV
ATTRIBUTE_APPLICATION_ID (PK)	NOT NULL	NUMBER	Attribute application id of the region item which launches this LOV
ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	Attribute Code of the region item which launches the LOV
LOV_REGION_APPL_ID (PK)	NOT NULL	NUMBER	Region Application ID of LOV Region
LOV_REGION_CODE (PK)	NOT NULL	VARCHAR2(30)	Region code of LOV Region
LOV_ATTRIBUTE_APPL_ID (PK)	NOT NULL	NUMBER	Attribute Application Id of LOV Region Item
LOV_ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	Attribute code of LOV Region Item
BASE_ATTRIBUTE_APPL_ID (PK)	NOT NULL	NUMBER	
BASE_ATTRIBUTE_CODE (PK)	NOT NULL	VARCHAR2(30)	
DIRECTION_FLAG (PK)	NOT NULL	VARCHAR2(30)	indicates this attribute value is a result returning to the caller or it's a criteria adding to another LOV
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who Column
REQUIRED_FLAG	NOT NULL	VARCHAR2(1)	valid values of this column are 'Y' and 'N'

Indexes

Index Name	Index Type	Sequence	Column Name
AK_REGION_LOV_RELATIONS_U1	UNIQUE	5	REGION_APPLICATION_ID
		10	REGION_CODE
		15	ATTRIBUTE_APPLICATION_ID
		20	ATTRIBUTE_CODE
		25	LOV_REGION_APPL_ID
		30	LOV_REGION_CODE
		35	LOV_ATTRIBUTE_APPL_ID
		40	LOV_ATTRIBUTE_CODE
		45	BASE_ATTRIBUTE_APPL_ID
		50	BASE_ATTRIBUTE_CODE
		52	DIRECTION_FLAG

ASO_HEADER_RELATIONSHIPS

ASO_HEADER_RELATIONSHIPS links one quote to another and records the type of relationship. The reciprocal flag indicates if the relationship is bidirectional.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
ASO_QUOTE_HEADERS_ALL	QUOTE_HEADER_ID	QUOTE_HEADER_ID
ASO_QUOTE_HEADERS_ALL	QUOTE_HEADER_ID	RELATED_HEADER_ID

Column Descriptions

Name	Null?	Type	Description
HEADER_RELATIONSHIP_ID	NOT NULL	NUMBER	Header relationship identifier
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard who column
REQUEST_ID	NULL	NUMBER	Request identifier
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
QUOTE_HEADER_ID	NOT NULL	NUMBER	Quote header identifier
RELATED_HEADER_ID	NOT NULL	NUMBER	Related quote header identifier
RELATIONSHIP_TYPE_CODE	NOT NULL	VARCHAR2(30)	Code defined in ASO_LOOKUPS that describes the relationship type
RECIPROCAL_FLAG	NULL	VARCHAR2(1)	Flag indicating if this is a reciprocal relationship
SECURITY_GROUP_ID	NULL	NUMBER	Used in hosted environments
OBJECT_VERSION_NUMBER	NULL	NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
ASO_HDR_RLTNSPS_N4	NOT UNIQUE	5	RELATIONSHIP_TYPE_CODE
ASO_HDR_RLTNSPS_U1	UNIQUE	5	HEADER_RELATIONSHIP_ID
ASO_HEADER_RELATIONSHIPS_N1	NOT UNIQUE	5	QUOTE_HEADER_ID
		7	RELATED_HEADER_ID
ASO_HEADER_RELATIONSHIPS_N2	NOT UNIQUE	5	QUOTE_HEADER_ID
ASO_HEADER_RELATIONSHIPS_N3	NOT UNIQUE	5	RELATED_HEADER_ID

ASO_HEADER_RELATIONSHIPS_V

View Definition

```
CREATE VIEW ASO_HEADER_RELATIONSHIPS_V
as SELECT
    HEADER_RELATIONSHIP_ID,
    CREATION_DATE ,
    CREATED_BY,
    LAST_UPDATE_DATE,
    LAST_UPDATED_BY,
    LAST_UPDATE_LOGIN,
    REQUEST_ID,
    PROGRAM_APPLICATION_ID,
    PROGRAM_ID,
    PROGRAM_UPDATE_DATE,
    QUOTE_HEADER_ID,
    RELATED_HEADER_ID,
    RELATIONSHIP_TYPE_CODE,
    RECIPROCAL_FLAG
FROM ASO_HEADER_RELATIONSHIPS
```

Column Descriptions

Name	Null?	Type	Description
HEADER_RELATIONSHIP_ID	NULL	VARCHAR2(240)	Refer to base table.
CREATION_DATE	NULL	VARCHAR2(240)	Refer to base table.
CREATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_LOGIN	NULL	VARCHAR2(240)	Refer to base table.
REQUEST_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_APPLICATION_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_HEADER_ID	NULL	VARCHAR2(240)	Refer to base table.
RELATED_HEADER_ID	NULL	VARCHAR2(240)	Refer to base table.
RELATIONSHIP_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
RECIPROCAL_FLAG	NULL	VARCHAR2(240)	Refer to base table.

ASO_I_OE_ORDER_HEADERS_V

This view includes all columns from the Oracle Order Management tables and is currently used by Oracle Sales Compensation only.

View Definition

```
CREATE VIEW ASO_I_OE_ORDER_HEADERS_V
as SELECT
    "HEADER_ID", "ORG_ID",
    "ORDER_TYPE_ID", "ORDER_NUMBER", "VERSION_NUMBER", "EXPIRATION_DATE",
    "ORDER_SOURCE_ID", "SOURCE_DOCUMENT_TYPE_ID", "ORIG_SYS_DOCUMENT_REF",
    "SOURCE_DOCUMENT_ID", "ORDERED_DATE", "REQUEST_DATE", "PRICING_DATE",
    "SHIPMENT_PRIORITY_CODE", "DEMAND_CLASS_CODE", "PRICE_LIST_ID",
    "TAX_EXEMPT_FLAG", "TAX_EXEMPT_NUMBER", "TAX_EXEMPT_REASON_CODE",
    "CONVERSION_RATE", "CONVERSION_TYPE_CODE", "CONVERSION_RATE_DATE",
    "PARTIAL_SHIPMENTS_ALLOWED", "SHIP_TOLERANCE_ABOVE",
    "SHIP_TOLERANCE_BELOW", "TRANSACTIONAL_CURR_CODE", "AGREEMENT_ID",
    "TAX_POINT_CODE", "CUST_PO_NUMBER", "INVOICING_RULE_ID",
    "ACCOUNTING_RULE_ID", "PAYMENT_TERM_ID", "SHIPPING_METHOD_CODE",
    "FREIGHT_CARRIER_CODE", "FOB_POINT_CODE", "FREIGHT_TERMS_CODE",
    "SOLD_TO_ORG_ID", "SOLD_FROM_ORG_ID", "SHIP_FROM_ORG_ID",
    "SHIP_TO_ORG_ID", "INVOICE_TO_ORG_ID", "DELIVER_TO_ORG_ID",
    "SOLD_TO_CONTACT_ID", "SHIP_TO_CONTACT_ID", "INVOICE_TO_CONTACT_ID",
    "DELIVER_TO_CONTACT_ID", "CREATION_DATE", "CREATED_BY", "LAST_UPDATED_BY",
    "LAST_UPDATE_DATE", "LAST_UPDATE_LOGIN", "PROGRAM_APPLICATION_ID",
    "PROGRAM_ID", "PROGRAM_UPDATE_DATE", "REQUEST_ID", "CONTEXT",
    "ATTRIBUTE1", "ATTRIBUTE2", "ATTRIBUTE3", "ATTRIBUTE4", "ATTRIBUTE5",
    "ATTRIBUTE6", "ATTRIBUTE7", "ATTRIBUTE8", "ATTRIBUTE9", "ATTRIBUTE10",
    "ATTRIBUTE11", "ATTRIBUTE12", "ATTRIBUTE13", "ATTRIBUTE14", "ATTRIBUTE15",
    "GLOBAL_ATTRIBUTE_CATEGORY", "GLOBAL_ATTRIBUTE1", "GLOBAL_ATTRIBUTE2",
    "GLOBAL_ATTRIBUTE3", "GLOBAL_ATTRIBUTE4", "GLOBAL_ATTRIBUTE5",
    "GLOBAL_ATTRIBUTE6", "GLOBAL_ATTRIBUTE7", "GLOBAL_ATTRIBUTE8",
    "GLOBAL_ATTRIBUTE9", "GLOBAL_ATTRIBUTE10", "GLOBAL_ATTRIBUTE11",
    "GLOBAL_ATTRIBUTE12", "GLOBAL_ATTRIBUTE13", "GLOBAL_ATTRIBUTE14",
    "GLOBAL_ATTRIBUTE15", "GLOBAL_ATTRIBUTE16", "GLOBAL_ATTRIBUTE17",
    "GLOBAL_ATTRIBUTE18", "GLOBAL_ATTRIBUTE19", "GLOBAL_ATTRIBUTE20",
    "CANCELLED_FLAG", "OPEN_FLAG", "BOOKED_FLAG", "BOOKED_DATE", "SALESREP_ID",
    "R
    RETURN_REASON_CODE", "ORDER_DATE_TYPE_CODE", "EARLIEST_SCHEDULE_LIMIT",
    "LATEST_SCHEDULE_LIMIT", "PAYMENT_TYPE_CODE", "PAYMENT_AMOUNT",
    "CHECK_NUMBER", "CREDIT_CARD_CODE", "CREDIT_CARD HOLDER_NAME",
    "CREDIT_CARD_NUMBER", "CREDIT_CARD_EXPIRATION_DATE",
    "CREDIT_CARD_APPROVAL_CODE", "SALES_CHANNEL_CODE", "FIRST_ACK_CODE",
    "FIRST_ACK_DATE", "LAST_ACK_CODE", "LAST_ACK_DATE", "CHANGE_SEQUENCE",
    "DROP_SHIP_FLAG", "CUSTOMER_PAYMENT_TERM_ID", "ORDER_CATEGORY_CODE",
    "SHIPPING_INSTRUCTIONS", "PACKING_INSTRUCTIONS", "FLOW_STATUS_CODE",
    "TP_CONTEXT", "TP_ATTRIBUTE1", "TP_ATTRIBUTE2", "TP_ATTRIBUTE3",
    "TP_ATTRIBUTE4", "TP_ATTRIBUTE5", "TP_ATTRIBUTE6", "TP_ATTRIBUTE7",
    "TP_ATTRIBUTE8", "TP_ATTRIBUTE9", "TP_ATTRIBUTE10", "TP_ATTRIBUTE11",
    "TP_ATTRIBUTE12", "TP_ATTRIBUTE13", "TP_ATTRIBUTE14", "TP_ATTRIBUTE15",
    "MARKETING_SOURCE_CODE_ID", "CREDIT_CARD_APPROVAL_DATE"
FROM OE_ORDER_HEADERS_ALL
```

Column Descriptions

Name	Null?	Type	Description
HEADER_ID	NOT NULL	NUMBER	Order Header Id
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
ORDER_TYPE_ID	NOT NULL	NUMBER	type of order
ORDER_NUMBER	NOT NULL	NUMBER	user visible number of the order
VERSION_NUMBER	NOT NULL	NUMBER	Order version number. Order number and version is a unique key in this table
EXPIRATION_DATE	NULL	DATE	date of expiration
ORDER_SOURCE_ID	NULL	NUMBER	Refer to base table.
SOURCE_DOCUMENT_TYPE_ID	NULL	NUMBER	Refer to base table.
ORIG_SYS_DOCUMENT_REF	NULL	VARCHAR2(50)	Order import original source order number
SOURCE_DOCUMENT_ID	NULL	NUMBER	Refer to base table.
ORDERED_DATE	NULL	DATE	Date order was placed
REQUEST_DATE	NULL	DATE	Customer request date
PRICING_DATE	NULL	DATE	Date order was priced
SHIPMENT_PRIORITY_CODE	NULL	VARCHAR2(30)	Shipment priority
DEMAND_CLASS_CODE	NULL	VARCHAR2(30)	Demand class
PRICE_LIST_ID	NULL	NUMBER	Price list for order lines
TAX_EXEMPT_FLAG	NULL	VARCHAR2(1)	Tax-exempt indicator
TAX_EXEMPT_NUMBER	NULL	VARCHAR2(80)	Tax exemption certificate number
TAX_EXEMPT_REASON_CODE	NULL	VARCHAR2(30)	Tax exemption reason
CONVERSION_RATE	NULL	NUMBER	Rate of currency conversion
CONVERSION_TYPE_CODE	NULL	VARCHAR2(30)	Currency conversion type
CONVERSION_RATE_DATE	NULL	DATE	Date of currency conversion
PARTIAL_SHIPMENTS_ALLOWED	NULL	VARCHAR2(1)	Indicates whether all items on the order must ship together or can ship seperately
SHIP_TOLERANCE_ABOVE	NULL	NUMBER	Refer to base table.
SHIP_TOLERANCE_BELOW	NULL	NUMBER	Refer to base table.
TRANSACTIONAL_CURR_CODE	NULL	VARCHAR2(3)	Currency for the order
AGREEMENT_ID	NULL	NUMBER	Agreement associated with the order
TAX_POINT_CODE	NULL	VARCHAR2(30)	Refer to base table.
CUST_PO_NUMBER	NULL	VARCHAR2(50)	Customer Purchase Order Number
INVOICING_RULE_ID	NULL	NUMBER	Invoicing rule used by AR for generating invoices
ACCOUNTING_RULE_ID	NULL	NUMBER	Accounting rule used by AR for generating invoices
PAYMENT_TERM_ID	NULL	NUMBER	payment terms that apply to this order
SHIPPING_METHOD_CODE	NULL	VARCHAR2(30)	Freight Carrier and method. Foreign key to table Org_Freight
FREIGHT_CARRIER_CODE	NULL	VARCHAR2(30)	Freight carrier
FOB_POINT_CODE	NULL	VARCHAR2(30)	Point of ownership transfer
FREIGHT_TERMS_CODE	NULL	VARCHAR2(30)	Freight terms
SOLD_TO_ORG_ID	NULL	NUMBER	Sold to organization id
SOLD_FROM_ORG_ID	NULL	NUMBER	Sold from organization id
SHIP_FROM_ORG_ID	NULL	NUMBER	Ship from organization id - warehouse
SHIP_TO_ORG_ID	NULL	NUMBER	Ship to organization id
INVOICE_TO_ORG_ID	NULL	NUMBER	Order level invoice to customer/address

Oracle Proprietary, Confidential Information--Use Restricted by Contract

DELIVER_TO_ORG_ID	NULL	NUMBER	Order level deliver to customer/address
SOLD_TO_CONTACT_ID	NULL	NUMBER	Contact for the order
SHIP_TO_CONTACT_ID	NULL	NUMBER	Contact for shipping
INVOICE_TO_CONTACT_ID	NULL	NUMBER	Contact for invoicing
DELIVER_TO_CONTACT_ID	NULL	NUMBER	Deliver to contact
CREATION_DATE	NOT NULL	DATE	standard who column
CREATED_BY	NOT NULL	NUMBER	standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	standard who column
LAST_UPDATE_DATE	NOT NULL	DATE	standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER	standard who column
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application of concurrent program which last updated row
PROGRAM_ID	NULL	NUMBER	Concurrent program that last updated row
PROGRAM_UPDATE_DATE	NULL	DATE	Last date changed by concurrent program
REQUEST_ID	NULL	NUMBER	Concurrent request that last updated the row
CONTEXT	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(240)	Descriptive flexfield segment
GLOBAL_ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE1	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE2	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE3	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE4	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE5	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE6	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE7	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE8	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE9	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE10	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE11	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment

GLOBAL_ATTRIBUTE12	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE13	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE14	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE15	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE16	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE17	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE18	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE19	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE20	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
CANCELLED_FLAG	NULL	VARCHAR2(1)	Indicates whether the order has been cancelled ('Y') or not ('N')
OPEN_FLAG	NULL	VARCHAR2(1)	Indicates whether the order has been closed ('N') or not ('Y')
BOOKED_FLAG	NULL	VARCHAR2(1)	Indicates whether the order has been booked ('Y') or not ('N')
BOOKED_DATE	NULL	DATE	date the order was booked
SALESREP_ID	NULL	NUMBER(15)	Primary salesperson
RETURN_REASON_CODE	NULL	VARCHAR2(30)	Return reason code for a return order, and for defaulting to a return line
ORDER_DATE_TYPE_CODE	NULL	VARCHAR2(30)	Refer to base table.
EARLIEST_SCHEDULE_LIMIT	NULL	NUMBER	Refer to base table.
LATEST_SCHEDULE_LIMIT	NULL	NUMBER	Refer to base table.
PAYMENT_TYPE_CODE	NULL	VARCHAR2(30)	Type of payment for the order (e.g., cash, credit card, PO)
PAYMENT_AMOUNT	NULL	NUMBER	Amount being paid
CHECK_NUMBER	NULL	VARCHAR2(50)	Check number if payment type is Check
CREDIT_CARD_CODE	NULL	VARCHAR2(80)	Credit card name if payment type is Credit
CREDIT_CARD HOLDER_NAME	NULL	VARCHAR2(80)	Cardholder name of the credit card
CREDIT_CARD_NUMBER	NULL	VARCHAR2(80)	Credit card number
CREDIT_CARD_EXPIRATION_DATE	NULL	DATE	Credit card expiration date
CREDIT_CARD_APPROVAL_CODE	NULL	VARCHAR2(80)	Credit card approval code
SALES_CHANNEL_CODE	NULL	VARCHAR2(30)	Sales channel through which order was placed
FIRST_ACK_CODE	NULL	VARCHAR2(30)	Refer to base table.
FIRST_ACK_DATE	NULL	DATE	Refer to base table.
LAST_ACK_CODE	NULL	VARCHAR2(30)	Refer to base table.
LAST_ACK_DATE	NULL	DATE	Refer to base table.
CHANGE_SEQUENCE	NULL	VARCHAR2(50)	Refer to base table.
DROP_SHIP_FLAG	NULL	VARCHAR2(1)	Refer to base table.
CUSTOMER_PAYMENT_TERM_ID	NULL	NUMBER	customer payment term
ORDER_CATEGORY_CODE	NULL	VARCHAR2(30)	Refer to base table.
SHIPPING_INSTRUCTIONS	NULL	VARCHAR2(2000)	Refer to base table.
PACKING_INSTRUCTIONS	NULL	VARCHAR2(2000)	Refer to base table.
FLOW_STATUS_CODE	NULL	VARCHAR2(30)	Refer to base table.
TP_CONTEXT	NULL	VARCHAR2(30)	Descriptive flex-field segment
TP_ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE2	NULL	VARCHAR2(240)	Descriptive flex-field segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

TP_ATTRIBUTE3	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE4	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE5	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE6	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE7	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE8	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE9	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE10	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE11	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE12	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE13	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE14	NULL	VARCHAR2(240)	Descriptive flex-field segment
TP_ATTRIBUTE15	NULL	VARCHAR2(240)	Descriptive flex-field segment
MARKETING_SOURCE_CODE_ID	NULL	NUMBER	Campaign that is applied to this order
CREDIT_CARD_APPROVAL_DATE	NULL	DATE	date on which credit card was approved

ASO_I_OE_ORDER_LINES_V

View Definition

```
CREATE VIEW ASO_I_OE_ORDER_LINES_V
as SELECT
    LINE_ID
  ,ORG_ID
  ,HEADER_ID
  ,LINE_TYPE_ID
  ,LINE_NUMBER
  ,REQUEST_DATE
  ,PROMISE_DATE
  ,SCHEDULE_SHIP_DATE
  ,ORDER_QUANTITY_UOM
  ,PRICING_QUANTITY
  ,PRICING_QUANTITY_UOM
  ,CANCELLED_QUANTITY
  ,SHIPPED_QUANTITY
  ,ORDERED_QUANTITY
  ,FULFILLED_QUANTITY
  ,SHIPPING_QUANTITY
  ,SHIPPING_QUANTITY_UOM
  ,DELIVERY_LEAD_TIME
  ,TAX_EXEMPT_FLAG
  ,TAX_EXEMPT_NUMBER
  ,TAX_EXEMPT_REASON_CODE
  ,SHIP_FROM_ORG_ID
  ,SHIP_TO_ORG_ID
  ,INVOICE_TO_ORG_ID
  ,DELIVER_TO_ORG_ID
  ,SHIP_TO_CONTACT_ID
  ,DELIVER_TO_CONTACT_ID
  ,INVOICE_TO_CONTACT_ID
  ,SOLD_TO_ORG_ID
  ,SOLD_FROM_ORG_ID
  ,CUST_PO_NUMBER
  ,SHIP_TOLERANCE_ABOVE
  ,SHIP_TOLERANCE_BELOW
  ,DEMAND_BUCKET_TYPE_CODE
  ,VEH_CUS_ITEM_CUM_KEY_ID
  ,RLA_SCHEDULE_TYPE_CODE
  ,CUSTOMER_DOCK_CODE
  ,CUSTOMER_JOB
  ,CUSTOMER_PRODUCTION_LINE
  ,CUST_MODEL_SERIAL_NUMBER
  ,PROJECT_ID
  ,TASK_ID
  ,INVENTORY_ITEM_ID
  ,TAX_DATE
  ,TAX_CODE
  ,TAX_RATE
  ,DEMAND_CLASS_CODE
  ,PRICE_LIST_ID
```

Oracle Proprietary, Confidential Information--Use Restricted by Contract


```

,PRICING_DATE
,SHIPMENT_NUMBER
,AGREEMENT_ID
,SHIPMENT_PRIORITY_CODE
,SHIPPING_METHOD_CODE
,FREIGHT_CARRIER_CODE
,FREIGHT_TERMS_CODE
,FOB_POINT_CODE
,TAX_POINT_CODE
,PAYMENT_TERM_ID
,INVOICING_RULE_ID
,ACCOUNTING_RULE_ID
,SOURCE_DOCUMENT_TYPE_ID
,ORIG_SYS_DOCUMENT_REF
,SOURCE_DOCUMENT_ID
,ORIG_SYS_LINE_REF
,SOURCE_DOCUMENT_LINE_ID
,REFERENCE_LINE_ID
,REFERENCE_TYPE
,REFERENCE_HEADER_ID
,ITEM_REVISION
,UNIT_SELLING_PRICE
,UNIT_LIST_PRICE
,TAX_VALUE
,CONTEXT
,ATTRIBUTE1
,ATTRIBUTE2
,ATTRIBUTE3
,ATTRIBUTE4
,ATTRIBUTE5
,ATTRIBUTE6
,ATTRIBUTE7
,ATTRIBUTE8

      ATTRIBUTE9
,ATTRIBUTE10
,ATTRIBUTE11
,ATTRIBUTE12
,ATTRIBUTE13
,ATTRIBUTE14
,ATTRIBUTE15
,GLOBAL_ATTRIBUTE_CATEGORY
,GLOBAL_ATTRIBUTE1
,GLOBAL_ATTRIBUTE2
,GLOBAL_ATTRIBUTE3
,GLOBAL_ATTRIBUTE4
,GLOBAL_ATTRIBUTE5
,GLOBAL_ATTRIBUTE6
,GLOBAL_ATTRIBUTE7
,GLOBAL_ATTRIBUTE8
,GLOBAL_ATTRIBUTE9
,GLOBAL_ATTRIBUTE10
,GLOBAL_ATTRIBUTE11
,GLOBAL_ATTRIBUTE12
,GLOBAL_ATTRIBUTE13
,GLOBAL_ATTRIBUTE14
,GLOBAL_ATTRIBUTE15

```

Oracle Proprietary, Confidential Information—Use Restricted by Contract

```

,GLOBAL_ATTRIBUTE16
,GLOBAL_ATTRIBUTE17
,GLOBAL_ATTRIBUTE18
,GLOBAL_ATTRIBUTE19
,GLOBAL_ATTRIBUTE20
,PRICING_CONTEXT
,PRICING_ATTRIBUTE1
,PRICING_ATTRIBUTE2
,PRICING_ATTRIBUTE3
,PRICING_ATTRIBUTE4
,PRICING_ATTRIBUTE5
,PRICING_ATTRIBUTE6
,PRICING_ATTRIBUTE7
,PRICING_ATTRIBUTE8
,PRICING_ATTRIBUTE9
,PRICING_ATTRIBUTE10
,INDUSTRY_CONTEXT
,INDUSTRY_ATTRIBUTE1
,INDUSTRY_ATTRIBUTE2
,INDUSTRY_ATTRIBUTE3
,INDUSTRY_ATTRIBUTE4
,INDUSTRY_ATTRIBUTE5
,INDUSTRY_ATTRIBUTE6
,INDUSTRY_ATTRIBUTE7
,INDUSTRY_ATTRIBUTE8
,INDUSTRY_ATTRIBUTE9
,INDUSTRY_ATTRIBUTE10
,INDUSTRY_ATTRIBUTE11
,INDUSTRY_ATTRIBUTE13
,INDUSTRY_ATTRIBUTE12
,INDUSTRY_ATTRIBUTE14
,INDUSTRY_ATTRIBUTE15
,INDUSTRY_ATTRIBUTE16
,INDUSTRY_ATTRIBUTE17
,INDUSTRY_ATTRIBUTE18
,INDUSTRY_ATTRIBUTE19
,INDUSTRY_ATTRIBUTE20
,INDUSTRY_ATTRIBUTE21
,INDUSTRY_ATTRIBUTE22
,INDUSTRY_ATTRIBUTE23
,INDUSTRY_ATTRIBUTE24
,INDUSTRY_ATTRIBUTE25
,INDUSTRY_ATTRIBUTE26
,INDUSTRY_ATTRIBUTE27
,INDUSTRY_ATTRIBUTE28
,INDUSTRY_ATTRIBUTE29
,INDUSTRY_ATTRIBUTE30
,CREATION_DATE
,CREATED_BY
,LAST_UPDATE
  _DATE
,LAST_UPDATED_BY
,LAST_UPDATE_LOGIN
,PROGRAM_APPLICATION_ID
,PROGRAM_ID
,PROGRAM_UPDATE_DATE
,REQUEST_ID

```

Oracle Proprietary, Confidential Information--Use Restricted by Contract

, CONFIGURATION_ID
 , LINK_TO_LINE_ID
 , COMPONENT_SEQUENCE_ID
 , COMPONENT_CODE
 , CONFIG_DISPLAY_SEQUENCE
 , SORT_ORDER
 , ITEM_TYPE_CODE
 , OPTION_NUMBER
 , OPTION_FLAG
 , DEP_PLAN_REQUIRED_FLAG
 , VISIBLE_DEMAND_FLAG
 , LINE_CATEGORY_CODE
 , ACTUAL_SHIPMENT_DATE
 , CUSTOMER_TRX_LINE_ID
 , RETURN_CONTEXT
 , RETURN_ATTRIBUTE1
 , RETURN_ATTRIBUTE2
 , RETURN_ATTRIBUTE3
 , RETURN_ATTRIBUTE4
 , RETURN_ATTRIBUTE5
 , RETURN_ATTRIBUTE6
 , RETURN_ATTRIBUTE7
 , RETURN_ATTRIBUTE8
 , RETURN_ATTRIBUTE9
 , RETURN_ATTRIBUTE10
 , RETURN_ATTRIBUTE11
 , RETURN_ATTRIBUTE12
 , RETURN_ATTRIBUTE13
 , RETURN_ATTRIBUTE14
 , RETURN_ATTRIBUTE15
 , INTMED_SHIP_TO_ORG_ID
 , INTMED_SHIP_TO_CONTACT_ID
 , ACTUAL_ARRIVAL_DATE
 , ATO_LINE_ID
 , AUTO_SELECTED_QUANTITY
 , COMPONENT_NUMBER
 , EARLIEST_ACCEPTABLE_DATE
 , EXPLOSION_DATE
 , LATEST_ACCEPTABLE_DATE
 , MODEL_GROUP_NUMBER
 , SCHEDULE_ARRIVAL_DATE
 , SHIP_MODEL_COMPLETE_FLAG
 , SCHEDULE_STATUS_CODE
 , SOURCE_TYPE_CODE
 , TOP_MODEL_LINE_ID
 , BOOKED_FLAG
 , CANCELLED_FLAG
 , OPEN_FLAG
 , SALESREP_ID
 , RETURN_REASON_CODE
 , ARRIVAL_SET_ID
 , SHIP_SET_ID
 , SPLIT_FROM_LINE_ID
 , CUST_PRODUCTION_SEQ_NUM
 , AUTHORIZED_TO_SHIP_FLAG
 , OVER_SHIP_REASON_CODE
 , OVER_SHIP_RESOLVED_FLAG

Oracle Proprietary, Confidential Information--Use Restricted by Contract

```

,ITEM_IDENTIFIER_TYPE
,SHIPPING_INTERFACED_FLAG
,CREDIT_INVOICE_LINE_ID
,FULFILLED_FLAG
,END_ITEM_UNIT_NUMBER
,COMMITMENT_ID
,FIRST_ACK_CODE
,FIRST_ACK_DATE
,LAST_ACK_CODE
,LAST_ACK_DATE
,ORDER_SOURCE_ID
,ORIG_SYS_SHIPMENT_REF

,CHANGE_SEQUENCE
,DROP_SHIP_FLAG
,CUSTOMER_LINE_NUMBER
,CUSTOMER_SHIPMENT_NUMBER
,CUSTOMER_ITEM_NET_PRICE
,CUSTOMER_PAYMENT_TERM_ID
,PLANNING_PRIORITY
,CONFIG_HEADER_ID
,CONFIG_REV_NBR
,MFG_COMPONENT_SEQUENCE_ID
,SHIPPING_INSTRUCTIONS
,PACKING_INSTRUCTIONS
,INVOICED_QUANTITY
,REFERENCE_CUSTOMER_TRX_LINE_ID
,SPLIT_BY
,LINE_SET_ID
,SERVICE_TXN_REASON_CODE
,SERVICE_DURATION
,SERVICE_START_DATE
,SERVICE_END_DATE
,SERVICE_COTERMINATE_FLAG
,SERVICE_TXN_COMMENTS
,UNIT_SELLING_PERCENT
,UNIT_LIST_PERCENT
,UNIT_PERCENT_BASE_PRICE
,SERVICE_NUMBER
,SERVICE_PERIOD
,SHIPPABLE_FLAG
,MODEL_REMNANT_FLAG
,RE_SOURCE_FLAG
,FLOW_STATUS_CODE
,TP_CONTEXT
,TP_ATTRIBUTE1
,TP_ATTRIBUTE2
,TP_ATTRIBUTE3
,TP_ATTRIBUTE4
,TP_ATTRIBUTE5
,TP_ATTRIBUTE6
,TP_ATTRIBUTE7
,TP_ATTRIBUTE8
,TP_ATTRIBUTE9
,TP_ATTRIBUTE10
,TP_ATTRIBUTE11
,TP_ATTRIBUTE12

```

Oracle Proprietary, Confidential Information--Use Restricted by Contract

```

,TP_ATTRIBUTE13
,TP_ATTRIBUTE14
,TP_ATTRIBUTE15
,FULFILLMENT_METHOD_CODE
,SERVICE_REFERENCE_TYPE_CODE
,SERVICE_REFERENCE_LINE_ID
,SERVICE_REFERENCE_SYSTEM_ID
,INVOICE_INTERFACE_STATUS_CODE
,ORDERED_ITEM
,ORDERED_ITEM_ID
,CALCULATE_PRICE_FLAG
,MARKETING_SOURCE_CODE_ID
,REVENUE_AMOUNT
,FULFILLMENT_DATE
FROM OE_ORDER_LINES_ALL

```

Column Descriptions

Name	Null?	Type	Description
LINE_ID	NOT NULL	VARCHAR2(240)	Order Line identifier
ORG_ID	NULL	VARCHAR2(240)	Operating unit which performed this transaction
HEADER_ID	NULL	VARCHAR2(240)	Order header identifier. Foreign key reference to oe_order_headers_all; the order to which this line belongs
LINE_TYPE_ID	NULL	VARCHAR2(240)	Refer to base table.
LINE_NUMBER	NULL	VARCHAR2(240)	Line sequence number within the order
REQUEST_DATE	NULL	VARCHAR2(240)	Customer request date
PROMISE_DATE	NULL	VARCHAR2(240)	Date promised to customer to receive item
SCHEDULE_SHIP_DATE	NULL	VARCHAR2(240)	Date planned to ship item
ORDER_QUANTITY_UOM	NULL	VARCHAR2(240)	Unit of measure of the ordered quantity
PRICING_QUANTITY	NULL	VARCHAR2(240)	Quantity that is priced. Typically, pricing quantity is the ordered quantity - cancelled quantity
PRICING_QUANTITY_UOM	NULL	VARCHAR2(240)	unit of measure of the pricing quantity
CANCELLED_QUANTITY	NULL	VARCHAR2(240)	cancelled quantity
SHIPPED_QUANTITY	NULL	VARCHAR2(240)	Shipped quantity
ORDERED_QUANTITY	NULL	VARCHAR2(240)	ordered quantity
FULFILLED_QUANTITY	NULL	VARCHAR2(240)	Refer to base table.
SHIPPING_QUANTITY	NULL	VARCHAR2(240)	Refer to base table.
SHIPPING_QUANTITY_UOM	NULL	VARCHAR2(240)	unit of measure of shipping quantity
DELIVERY_LEAD_TIME	NULL	VARCHAR2(240)	Refer to base table.
TAX_EXEMPT_FLAG	NULL	VARCHAR2(240)	Tax-exempt indicator
TAX_EXEMPT_NUMBER	NULL	VARCHAR2(240)	Tax exemption certificate number
TAX_EXEMPT_REASON_CODE	NULL	VARCHAR2(240)	Tax exemption reason code
SHIP_FROM_ORG_ID	NULL	VARCHAR2(240)	Ship from organization id
SHIP_TO_ORG_ID	NULL	VARCHAR2(240)	Location to which line is to be shipped
INVOICE_TO_ORG_ID	NULL	VARCHAR2(240)	Invoice to organization id
DELIVER_TO_ORG_ID	NULL	VARCHAR2(240)	Deliver to organization id

SHIP_TO_CONTACT_ID	NULL	VARCHAR2(240)	Person to whom line is to be shipped
DELIVER_TO_CONTACT_ID	NULL	VARCHAR2(240)	Person to whom line item is delivered
INVOICE_TO_CONTACT_ID	NULL	VARCHAR2(240)	Person to whom line is billed
SOLD_TO_ORG_ID	NULL	VARCHAR2(240)	Sold to organization id
SOLD_FROM_ORG_ID	NULL	VARCHAR2(240)	Sold from organization id
CUST_PO_NUMBER	NULL	VARCHAR2(240)	Customer Purchase Order Number
SHIP_TOLERANCE_ABOVE	NULL	VARCHAR2(240)	Refer to base table.
SHIP_TOLERANCE_BELOW	NULL	VARCHAR2(240)	Refer to base table.
DEMAND_BUCKET_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
VEH_CUS_ITEM_CUM_KEY_ID	NULL	VARCHAR2(240)	Refer to base table.
RLA_SCHEDULE_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
CUSTOMER_DOCK_CODE	NULL	VARCHAR2(240)	Dock code
CUSTOMER_JOB	NULL	VARCHAR2(240)	Customer job number
CUSTOMER_PRODUCTION_LINE	NULL	VARCHAR2(240)	Customer production line
CUST_MODEL_SERIAL_NUMBER	NULL	VARCHAR2(240)	serial number (e.g., vehicle ID number - VIN)
PROJECT_ID	NULL	VARCHAR2(240)	Project associated with this transaction
TASK_ID	NULL	VARCHAR2(240)	Task associated with this transaction
INVENTORY_ITEM_ID	NULL	VARCHAR2(240)	Inventory item identifier
TAX_DATE	NULL	VARCHAR2(240)	date for tax calculation
TAX_CODE	NULL	VARCHAR2(240)	tax code associated with a user specified rate
TAX_RATE	NULL	VARCHAR2(240)	tax rate in percentage
DEMAND_CLASS_CODE	NULL	VARCHAR2(240)	Demand class
PRICE_LIST_ID	NULL	VARCHAR2(240)	Price list
PRICING_DATE	NULL	VARCHAR2(240)	Date on which the item was priced
SHIPMENT_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
AGREEMENT_ID	NULL	VARCHAR2(240)	User agreement for the order line
SHIPMENT_PRIORITY_CODE	NULL	VARCHAR2(240)	Shipment priority
SHIPPING_METHOD_CODE	NULL	VARCHAR2(240)	Freight Carrier and method. Foreign key to table Org_Freight
FREIGHT_CARRIER_CODE	NULL	VARCHAR2(240)	Freight carrier
FREIGHT_TERMS_CODE	NULL	VARCHAR2(240)	Freight terms
FOB_POINT_CODE	NULL	VARCHAR2(240)	Point of ownership transfer
TAX_POINT_CODE	NULL	VARCHAR2(240)	Refer to base table.
PAYMENT_TERM_ID	NULL	VARCHAR2(240)	Payment terms that apply to this line
INVOICING_RULE_ID	NULL	VARCHAR2(240)	invoicing rule to be used by AR while generating invoices
ACCOUNTING_RULE_ID	NULL	VARCHAR2(240)	Accounting rule used by AR to generate invoices
SOURCE_DOCUMENT_TYPE_ID	NULL	VARCHAR2(240)	Refer to base table.
ORIG_SYS_DOCUMENT_REF	NULL	VARCHAR2(240)	Refer to base table.
SOURCE_DOCUMENT_ID	NULL	VARCHAR2(240)	Refer to base table.
ORIG_SYS_LINE_REF	NULL	VARCHAR2(240)	Identifier of a line from a source system outside of Order Management
SOURCE_DOCUMENT_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
REFERENCE_LINE_ID	NULL	VARCHAR2(240)	line id of the referenced object
REFERENCE_TYPE	NULL	VARCHAR2(240)	return reference type (e.g., ORDER, PO, Invoice)
REFERENCE_HEADER_ID	NULL	VARCHAR2(240)	header id of the referenced object

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ITEM_REVISION	NULL	VARCHAR2(240)	revision number of the item
UNIT_SELLING_PRICE	NULL	VARCHAR2(240)	Actual price charged to a customer
UNIT_LIST_PRICE	NULL	VARCHAR2(240)	Price list price of the item
TAX_VALUE	NULL	VARCHAR2(240)	total tax amount
CONTEXT	NULL	VARCHAR2(240)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(240)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(240)	Descriptive flexfield segment
GLOBAL_ATTRIBUTE_CATEGORY	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE1	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE2	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE3	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE4	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE5	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE6	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE7	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE8	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE9	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE10	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE11	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE12	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE13	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE14	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE15	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE16	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE17	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE18	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment

GLOBAL_ATTRIBUTE19	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
GLOBAL_ATTRIBUTE20	NULL	VARCHAR2(240)	Globalization specific descriptive flex-field segment
PRICING_CONTEXT	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield structure defining column
PRICING_ATTRIBUTE1	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
PRICING_ATTRIBUTE2	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
PRICING_ATTRIBUTE3	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
PRICING_ATTRIBUTE4	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
PRICING_ATTRIBUTE5	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
PRICING_ATTRIBUTE6	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
PRICING_ATTRIBUTE7	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
PRICING_ATTRIBUTE8	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
PRICING_ATTRIBUTE9	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
PRICING_ATTRIBUTE10	NULL	VARCHAR2(240)	Pricing attribute descriptive flexfield segment
INDUSTRY_CONTEXT	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield structure defining column
INDUSTRY_ATTRIBUTE1	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE2	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE3	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE4	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE5	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE6	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE7	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE8	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE9	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE10	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE11	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE13	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE12	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE14	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE15	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE16	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE17	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

INDUSTRY_ATTRIBUTE18	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE19	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE20	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE21	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE22	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE23	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE24	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE25	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE26	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE27	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE28	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE29	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
INDUSTRY_ATTRIBUTE30	NULL	VARCHAR2(240)	Industry attribute descriptive flexfield segment
CREATION_DATE	NULL	VARCHAR2(240)	Standard who column
CREATED_BY	NULL	VARCHAR2(240)	Standard who column
LAST_UPDATE_DATE	NULL	VARCHAR2(240)	Standard who column
LAST_UPDATED_BY	NULL	VARCHAR2(240)	Standard who column
LAST_UPDATE_LOGIN	NULL	VARCHAR2(240)	Standard who column
PROGRAM_APPLICATION_ID	NULL	VARCHAR2(240)	Application of concurrent program which last updated the row
PROGRAM_ID	NULL	VARCHAR2(240)	Concurrent program that last updated the row
PROGRAM_UPDATE_DATE	NULL	VARCHAR2(240)	Last date changed by concurrent program
REQUEST_ID	NULL	VARCHAR2(240)	Concurrent request that last updated the row
CONFIGURATION_ID	NULL	VARCHAR2(240)	Refer to base table.
LINK_TO_LINE_ID	NULL	VARCHAR2(240)	Order Line id of the immediate parent component line
COMPONENT_SEQUENCE_ID	NULL	VARCHAR2(240)	Bill of Materials component (option) or bill (model)
COMPONENT_CODE	NULL	VARCHAR2(240)	Identifier of a component within an exploded bill
CONFIG_DISPLAY_SEQUENCE	NULL	VARCHAR2(240)	configuration display sequence
SORT_ORDER	NULL	VARCHAR2(240)	Sorting sequence for a component within a bill
ITEM_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
OPTION_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
OPTION_FLAG	NULL	VARCHAR2(240)	Indicates whether a line is an option in a configuration
DEP_PLAN_REQUIRED_FLAG	NULL	VARCHAR2(240)	Departure Planning Required Flag possible values Y/N
VISIBLE_DEMAND_FLAG	NULL	VARCHAR2(240)	Refer to base table.
LINE_CATEGORY_CODE	NULL	VARCHAR2(240)	Refer to base table.
ACTUAL_SHIPMENT_DATE	NULL	VARCHAR2(240)	date on which the line items have been shipped
CUSTOMER_TRX_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

RETURN_CONTEXT	NULL	VARCHAR2(240)	Descriptive flexfield structure defining column
RETURN_ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE2	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE3	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE4	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE5	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE6	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE7	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE8	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE9	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE10	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE11	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE12	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE13	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE14	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
RETURN_ATTRIBUTE15	NULL	VARCHAR2(240)	Descriptive flexfield segment for return items
INTMED_SHIP_TO_ORG_ID	NULL	VARCHAR2(240)	intermediate ship to site id
INTMED_SHIP_TO_CONTACT_ID	NULL	VARCHAR2(240)	intermediate ship to contact id
ACTUAL_ARRIVAL_DATE	NULL	VARCHAR2(240)	actual arrival date
ATO_LINE_ID	NULL	VARCHAR2(240)	Order line id of ATO configuration top model line
AUTO_SELECTED_QUANTITY	NULL	VARCHAR2(240)	Refer to base table.
COMPONENT_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
EARLIEST_ACCEPTABLE_DATE	NULL	VARCHAR2(240)	Refer to base table.
EXPLOSION_DATE	NULL	VARCHAR2(240)	Refer to base table.
LATEST_ACCEPTABLE_DATE	NULL	VARCHAR2(240)	Refer to base table.
MODEL_GROUP_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
SCHEDULE_ARRIVAL_DATE	NULL	VARCHAR2(240)	date of scheduled arrival
SHIP_MODEL_COMPLETE_FLAG	NULL	VARCHAR2(240)	Indicates whether the line is in a ship complete configuration
SCHEDULE_STATUS_CODE	NULL	VARCHAR2(240)	Refer to base table.
SOURCE_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
TOP_MODEL_LINE_ID	NULL	VARCHAR2(240)	Order line id of the top model
BOOKED_FLAG	NULL	VARCHAR2(240)	Indicates whether order line is booked ('Y') or not ('N')
CANCELLED_FLAG	NULL	VARCHAR2(240)	Indicates whether order line is cancelled('Y') or not ('N')
OPEN_FLAG	NULL	VARCHAR2(240)	Indicates whether order line is closed('Y') or not ('N')
SALESREP_ID	NULL	VARCHAR2(240)	primary salesrep for this line
RETURN_REASON_CODE	NULL	VARCHAR2(240)	return reason for this line if the line type is RETURN
ARRIVAL_SET_ID	NULL	VARCHAR2(240)	Refer to base table.
SHIP_SET_ID	NULL	VARCHAR2(240)	Refer to base table.
SPLIT_FROM_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CUST_PRODUCTION_SEQ_NUM	NULL	VARCHAR2(240)	Refer to base table.
AUTHORIZED_TO_SHIP_FLAG	NULL	VARCHAR2(240)	Refer to base table.
OVER_SHIP_REASON_CODE	NULL	VARCHAR2(240)	Refer to base table.
OVER_SHIP_RESOLVED_FLAG	NULL	VARCHAR2(240)	Refer to base table.
ITEM_IDENTIFIER_TYPE	NULL	VARCHAR2(240)	Refer to base table.
SHIPPING_INTERFACED_FLAG	NULL	VARCHAR2(240)	Refer to base table.
CREDIT_INVOICE_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
FULFILLED_FLAG	NULL	VARCHAR2(240)	Refer to base table.
END_ITEM_UNIT_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
COMMITMENT_ID	NULL	VARCHAR2(240)	Refer to base table.
FIRST_ACK_CODE	NULL	VARCHAR2(240)	Refer to base table.
FIRST_ACK_DATE	NULL	VARCHAR2(240)	Refer to base table.
LAST_ACK_CODE	NULL	VARCHAR2(240)	Refer to base table.
LAST_ACK_DATE	NULL	VARCHAR2(240)	Refer to base table.
ORDER_SOURCE_ID	NULL	VARCHAR2(240)	Refer to base table.
ORIG_SYS_SHIPMENT_REF	NULL	VARCHAR2(240)	Refer to base table.
CHANGE_SEQUENCE	NULL	VARCHAR2(240)	Refer to base table.
DROP_SHIP_FLAG	NULL	VARCHAR2(240)	Refer to base table.
CUSTOMER_LINE_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
CUSTOMER_SHIPMENT_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
CUSTOMER_ITEM_NET_PRICE	NULL	VARCHAR2(240)	Refer to base table.
CUSTOMER_PAYMENT_TERM_ID	NULL	VARCHAR2(240)	Refer to base table.
PLANNING_PRIORITY	NULL	VARCHAR2(240)	Refer to base table.
CONFIG_HEADER_ID	NULL	VARCHAR2(240)	configuration header id
CONFIG_REV_NBR	NULL	VARCHAR2(240)	configuration revision number
MFG_COMPONENT_SEQUENCE_ID	NULL	VARCHAR2(240)	Refer to base table.
SHIPPING_INSTRUCTIONS	NULL	VARCHAR2(240)	shipping instructions for this line
PACKING_INSTRUCTIONS	NULL	VARCHAR2(240)	packing instructions for this line
INVOICED_QUANTITY	NULL	VARCHAR2(240)	invoiced quantity
REFERENCE_CUSTOMER_TRX_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
SPLIT_BY	NULL	VARCHAR2(240)	Refer to base table.
LINE_SET_ID	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_TXN_REASON_CODE	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_DURATION	NULL	VARCHAR2(240)	duration of service
SERVICE_START_DATE	NULL	VARCHAR2(240)	effective start date for service
SERVICE_END_DATE	NULL	VARCHAR2(240)	end date for service
SERVICE_COTERMINATE_FLAG	NULL	VARCHAR2(240)	Cotermination indicator for service order lines
SERVICE_TXN_COMMENTS	NULL	VARCHAR2(240)	Refer to base table.
UNIT_SELLING_PERCENT	NULL	VARCHAR2(240)	Percent actually charged to customer (percent based pricing only)
UNIT_LIST_PERCENT	NULL	VARCHAR2(240)	Price list percent of the item (percent based pricing only)
UNIT_PERCENT_BASE_PRICE	NULL	VARCHAR2(240)	base price used for percent based pricing
SERVICE_NUMBER	NULL	VARCHAR2(240)	service number
SERVICE_PERIOD	NULL	VARCHAR2(240)	period for which this service is purchased
SHIPPABLE_FLAG	NULL	VARCHAR2(240)	Indicates whether or not the item is shippable
MODEL_REMNANT_FLAG	NULL	VARCHAR2(240)	Refer to base table.
RE_SOURCE_FLAG	NULL	VARCHAR2(240)	Refer to base table.
FLOW_STATUS_CODE	NULL	VARCHAR2(240)	Refer to base table.
TP_CONTEXT	NULL	VARCHAR2(240)	Descriptive flexfield structure defining column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

TP_ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE2	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE3	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE4	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE5	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE6	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE7	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE8	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE9	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE10	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE11	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE12	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE13	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE14	NULL	VARCHAR2(240)	Descriptive flexfield segment
TP_ATTRIBUTE15	NULL	VARCHAR2(240)	Descriptive flexfield segment
FULFILLMENT_METHOD_CODE	NULL	VARCHAR2(240)	fulfillment method code
SERVICE_REFERENCE_TYPE_CODE	NULL	VARCHAR2(240)	object type to which this service is linked to.
SERVICE_REFERENCE_LINE_ID	NULL	VARCHAR2(240)	Order line id to which this service is linked to (if reference type is 'ORDER')
SERVICE_REFERENCE_SYSTEM_ID	NULL	VARCHAR2(240)	system id of the sytem to which this service is linked to
INVOICE_INTERFACE_STATUS_CODE	NULL	VARCHAR2(240)	status of invoice interface
ORDERED_ITEM	NULL	VARCHAR2(240)	ordered item
ORDERED_ITEM_ID	NULL	VARCHAR2(240)	ordered item id
CALCULATE_PRICE_FLAG	NULL	VARCHAR2(240)	If 'Y' Order Management has recalculated the price for this order line
MARKETING_SOURCE_CODE_ID	NULL	VARCHAR2(240)	Campaign that is applied to this order line
REVENUE_AMOUNT	NULL	VARCHAR2(240)	Unit price to invoice (prorated prices only)
FULFILLMENT_DATE	NULL	VARCHAR2(240)	Fulfillment Date for the Line

ASO_I_OE_SALES_CREDITS_V

View Definition

```
CREATE VIEW ASO_I_OE_SALES_CREDITS_V
as SELECT
```

```
SALES_CREDIT_ID, CREATION_DATE, CREATED_BY, LAST_UPDATE_DATE, LAST_UPDATED_BY, LAST_UPDATE_LOGIN, HEA
DER_ID, SALESREP_ID, PERCENT, LINE_ID, CONTEXT, ATTRIBUTE1, ATTRIBUTE2, ATTRIBUTE3, ATTRIBUTE4, ATTRIBUT
E5, ATTRIBUTE6, ATTRIBUTE7, ATTRIBUTE8, ATTRIBUTE9, ATTRIBUTE10, ATTRIBUTE11, ATTRIBUTE12, ATTRIBUTE13,
ATTRIBUTE14, ATTRIBUTE15, DW_UPDATE_ADVICE_FLAG, WH_UPDATE_DATE, ORIG_SYS_CREDIT_REF, SALES_CREDIT_T
YPE_ID from oe_sales_credits
```

Column Descriptions

Name	Null?	Type	Description
SALES_CREDIT_ID	NOT NULL	NUMBER	Refer to base table.
CREATION_DATE	NOT NULL	DATE	Refer to base table.
CREATED_BY	NOT NULL	NUMBER	Refer to base table.
LAST_UPDATE_DATE	NOT NULL	DATE	Refer to base table.
LAST_UPDATED_BY	NOT NULL	NUMBER	Refer to base table.
LAST_UPDATE_LOGIN	NULL	NUMBER	Refer to base table.
HEADER_ID	NOT NULL	NUMBER	Refer to base table.
SALESREP_ID	NOT NULL	NUMBER(15)	Refer to base table.
PERCENT	NOT NULL	NUMBER	Refer to base table.
LINE_ID	NULL	NUMBER	Refer to base table.
CONTEXT	NULL	VARCHAR2(30)	Refer to base table.
ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.
DW_UPDATE_ADVICE_FLAG	NULL	VARCHAR2(1)	Refer to base table.
WH_UPDATE_DATE	NULL	DATE	Refer to base table.
ORIG_SYS_CREDIT_REF	NULL	VARCHAR2(50)	Refer to base table.
SALES_CREDIT_TYPE_ID	NULL	NUMBER	Refer to base table.

ASO_I_ORDER_TYPES_V

View Definition

```
CREATE VIEW ASO_I_ORDER_TYPES_V
as SELECT
    ORDER_TYPE_ID
,   NAME
,   ORDER_CATEGORY_CODE
,   START_DATE_ACTIVE
,   END_DATE_ACTIVE
,   CUST_TRX_TYPE_ID
,   PRICE_LIST_ID
,   ACCOUNTING_RULE_ID
,   INVOICING_RULE_ID
,   AGREEMENT_REQUIRED_FLAG
,   PO_REQUIRED_FLAG
,   SHIPMENT_PRIORITY_CODE
,   SHIPPING_METHOD_CODE
,   FREIGHT_TERMS_CODE
,   FOB_POINT_CODE
,   org_id
from
    OE_ORDER_TYPES_V
```

Column Descriptions

Name	Null?	Type	Description
ORDER_TYPE_ID	NULL	VARCHAR2(240)	Order type identifier
NAME	NULL	VARCHAR2(240)	Order type name
ORDER_CATEGORY_CODE	NULL	VARCHAR2(240)	order category
START_DATE_ACTIVE	NULL	VARCHAR2(240)	Effectivity date for this order type
END_DATE_ACTIVE	NULL	VARCHAR2(240)	Last active day for this order type
CUST_TRX_TYPE_ID	NULL	VARCHAR2(240)	Customer Transaction Type ID
PRICE_LIST_ID	NULL	VARCHAR2(240)	Price list information for the order type
ACCOUNTING_RULE_ID	NULL	VARCHAR2(240)	Accounting rule used by AR for generating Invoice
INVOICING_RULE_ID	NULL	VARCHAR2(240)	Invoicing rule used by AR for generating Invoice
AGREEMENT_REQUIRED_FLAG	NULL	VARCHAR2(240)	Indicates whether or not an agreement is required
PO_REQUIRED_FLAG	NULL	VARCHAR2(240)	Indicates whether or not a Purchase order is required
SHIPMENT_PRIORITY_CODE	NULL	VARCHAR2(240)	shipment priority code
SHIP_METHOD_CODE	NULL	VARCHAR2(240)	ship method code
FREIGHT_TERMS_CODE	NULL	VARCHAR2(240)	freight terms
FOB_POINT_CODE	NULL	VARCHAR2(240)	Point of ownership transfer
ORG_ID	NULL	NUMBER	organization identifier

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ASO_I_SALES_CHANNELS_V

View Definition

```
CREATE VIEW ASO_I_SALES_CHANNELS_V
as SELECT
    LOOKUP_CODE,
    MEANING,
    DESCRIPTION,
    ENABLED_FLAG,
    START_DATE_ACTIVE,
    END_DATE_ACTIVE
from OE_LOOKUPS
    Where LOOKUP_TYPE = 'SALES_CHANNEL'
```

Column Descriptions

Name	Null?	Type	Description
SALES_CHANNEL_CODE	NOT NULL	VARCHAR2(30)	sales channel code
SALES_CHANNEL	NOT NULL	VARCHAR2(80)	name of the sales channel
DESCRIPTION	NULL	VARCHAR2(240)	sales channel description
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	Flag Indicates wheather a Sales Channel is Enabled
START_DATE_ACTIVE	NULL	DATE	Start Date of Activation
END_DATE_ACTIVE	NULL	DATE	End Date of Activation

ASO_I_SALES_CREDITS_V

View Definition

```
CREATE VIEW ASO_I_SALES_CREDITS_V
as SELECT
    sc.sales_credit_id
,   sc.header_id
,   sc.line_id
,   sc.salesrep_id
,   rs.name salesrep_name
,   sc.percent
from
    OE_SALES_CREDITS SC,
    RA_SALESREPS_ALL RS
    Where RS.SALESREP_ID = SC.SALESREP_ID
```

Column Descriptions

Name	Null?	Type	Description
SALES_CREDIT_ID	NULL	NUMBER	Sales credit identifier
HEADER_ID	NULL	NUMBER	Header identifier
LINE_ID	NULL	NUMBER	Line identifier
SALESREP_ID	NULL	NUMBER	Salesrep identifier
SALESREP_NAME	NULL	VARCHAR2(240)	Salesrep name
PERCENT	NULL	NUMBER	Percent

ASO_I_SALES_CREDIT_TYPES_V

View Definition

```
CREATE VIEW ASO_I_SALES_CREDIT_TYPES_V
as SELECT
    OE_SALES_CREDIT_TYPES.SALES_CREDIT_TYPE_ID
  , OE_SALES_CREDIT_TYPES.NAME
  , OE_SALES_CREDIT_TYPES.DESCRPTION
  , OE_SALES_CREDIT_TYPES.QUOTA_FLAG
  , OE_SALES_CREDIT_TYPES.ENABLED_FLAG
  , OE_SALES_CREDIT_TYPES.CONTEXT
from
    OE_SALES_CREDIT_TYPES
```

Column Descriptions

Name	Null?	Type	Description
SALES_CREDIT_TYPE_ID	NULL	NUMBER	unique identifier of the sales credit
NAME	NULL	VARCHAR2(240)	Name of the sales credit type
DESCRIPTION	NULL	VARCHAR2(240)	Description of the sales credit type
QUOTA_FLAG	NULL	VARCHAR2(240)	Indicates whether the sales credit type is a quota or a non quota flag
ENABLED_FLAG	NULL	VARCHAR2(240)	Indicates whether the sales credit type is active
CONTEXT	NULL	VARCHAR2(30)	context

ASO_PARTY_RELATIONSHIPS_V

View Definition

```
CREATE VIEW ASO_PARTY_RELATIONSHIPS_V
as SELECT
    PARTY_RELATIONSHIP_ID
  , CREATION_DATE
  , CREATED_BY
  , LAST_UPDATE_DATE
  , LAST_UPDATED_BY
  , LAST_UPDATE_LOGIN
  , REQUEST_ID
  , PROGRAM_APPLICATION_ID
  , PROGRAM_ID
  , PROGRAM_UPDATE_DATE
  , QUOTE_HEADER_ID
  , QUOTE_LINE_ID
  , OBJECT_TYPE_CODE
  , OBJECT_ID
  , RELATIONSHIP_TYPE_CODE
FROM ASO_PARTY_RELATIONSHIPS
```

Column Descriptions

Name	Null?	Type	Description
PARTY_RELATIONSHIP_ID	NULL	VARCHAR2(240)	Refer to base table.
CREATION_DATE	NULL	VARCHAR2(240)	Refer to base table.
CREATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_LOGIN	NULL	VARCHAR2(240)	Refer to base table.
REQUEST_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_APPLICATION_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_HEADER_ID	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
OBJECT_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
OBJECT_ID	NULL	VARCHAR2(240)	Refer to base table.
RELATIONSHIP_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.

ASO_QUOTE_HEADERS_ALL

ASO_QUOTE_HEADERS holds Order Capture quotation information. It has the header data of a quote. For each quote header, there can be zero or many quote lines attached to it.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
ASO_QUOTE_STATUSES_B	QUOTE_STATUS_ID	QUOTE_STATUS_ID

Column Descriptions

Name	Null?	Type	Description
QUOTE_HEADER_ID	NOT NULL	NUMBER	Unique identifier for quote
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard who column
REQUEST_ID	NULL	NUMBER	Request identifier
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
QUOTE_NAME	NULL	VARCHAR2(50)	Quote name
QUOTE_NUMBER	NOT NULL	NUMBER	Quote number. Quote number and version uniquely identifies a quote
QUOTE_VERSION	NOT NULL	NUMBER	Quote version. Quote number and quote version uniquely identifies a quote
QUOTE_STATUS_ID	NOT NULL	NUMBER	Quote status
QUOTE_SOURCE_CODE	NULL	VARCHAR2(240)	Source of the quote
QUOTE_EXPIRATION_DATE	NULL	DATE	Expiration date of the quote
PRICE_FROZEN_DATE	NULL	DATE	Price Frozen Date
QUOTE_PASSWORD	NULL	VARCHAR2(240)	Quote Password
ORIGINAL_SYSTEM_REFERENCE	NULL	VARCHAR2(240)	Original system reference
PARTY_ID	NULL	NUMBER	Customer Identifier
CUST_ACCOUNT_ID	NULL	NUMBER	Customer Account Identifier
ORG_CONTACT_ID	NULL	NUMBER	Contact Identifier
PHONE_ID	NULL	NUMBER	Phone Identifier
INVOICE_TO_PARTY_SITE_ID	NULL	NUMBER	Bill to site identifier
INVOICE_TO_PARTY_ID	NULL	NUMBER	Bill to contact identifier
ORIG_MKTG_SOURCE_CODE_ID	NULL	NUMBER	Campaign from which this quote originates
MARKETING_SOURCE_CODE_ID	NULL	NUMBER	Campaign that is applied to this quote
ORDER_TYPE_ID	NULL	NUMBER	Order type identifier, determines the type of order to be created
QUOTE_CATEGORY_CODE	NULL	VARCHAR2(240)	QUOTE CATEGORY CODE
ORDERED_DATE	NULL	DATE	Date which the quote is turned into an order

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ACCOUNTING_RULE_ID	NULL	NUMBER	Accounting rule identifier
INVOICING_RULE_ID	NULL	NUMBER	Invoicing rule identifier
EMPLOYEE_PERSON_ID	NULL	NUMBER	Employee person identifier
PRICE_LIST_ID	NULL	NUMBER	Price list identifier
CURRENCY_CODE	NOT NULL	VARCHAR2(15)	Currency code
TOTAL_LIST_PRICE	NULL	NUMBER	Total list price
TOTAL_ADJUSTED_AMOUNT	NULL	NUMBER	Total amount after price adjustments
TOTAL_ADJUSTED_PERCENT	NULL	NUMBER	Price adjustment percent
TOTAL_TAX	NULL	NUMBER	Total tax amount
TOTAL_SHIPPING_CHARGE	NULL	NUMBER	Total shipping charge
SURCHARGE	NULL	NUMBER	Surcharge
TOTAL_QUOTE_PRICE	NULL	NUMBER	Total price quoted
PAYMENT_AMOUNT	NULL	NUMBER	Payment amount
EXCHANGE_RATE	NULL	NUMBER	Exchange rate
EXCHANGE_TYPE_CODE	NULL	VARCHAR2(15)	Exchange type code
EXCHANGE_RATE_DATE	NULL	DATE	Date of exchange rate
CONTRACT_ID	NULL	NUMBER	Contract identifier
SALES_CHANNEL_CODE	NULL	VARCHAR2(30)	Sales Channel Code
ORDER_ID	NULL	NUMBER	Order Header ID - Retrofitted
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield column
SECURITY_GROUP_ID	NULL	NUMBER	Used in hosted environments
OBJECT_VERSION_NUMBER	NULL	NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
ASO_QUOTE_HEADERS_N1	NOT UNIQUE	5	PARTY_ID
ASO_QUOTE_HEADERS_N2	NOT UNIQUE	5	QUOTE_NUMBER
ASO_QUOTE_HEADERS_N3	NOT UNIQUE	5	CUST_ACCOUNT_ID
ASO_QUOTE_HEADERS_N4	NOT UNIQUE	5	ORDER_ID
ASO_QUOTE_HEADERS_N5	NOT UNIQUE	5	PRICE_LIST_ID
ASO_QUOTE_HEADERS_N6	NOT UNIQUE	5	QUOTE_STATUS_ID
ASO_QUOTE_HEADERS_N7	NOT UNIQUE	5	ORDER_TYPE_ID
ASO_QUOTE_HEADERS_N8	NOT UNIQUE	5	ORG_ID
ASO_QUOTE_HEADERS_U1	UNIQUE	7	QUOTE_NUMBER
		9	QUOTE_VERSION
ASO_QUOTE_HEADERS_U2	UNIQUE	5	QUOTE_HEADER_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ASO_QUOTE_HEADERS_ALL_V

View Definition

```
CREATE VIEW ASO_QUOTE_HEADERS_ALL_V
as SELECT
    QUOTE_HEADER_ID
  , CREATION_DATE
  , CREATED_BY
  , LAST_UPDATE_DATE
  , LAST_UPDATED_BY
  , LAST_UPDATE_LOGIN
  , REQUEST_ID
  , PROGRAM_APPLICATION_ID
  , PROGRAM_ID
  , PROGRAM_UPDATE_DATE
  , ORG_ID
  , QUOTE_NAME
  , QUOTE_NUMBER
  , QUOTE_VERSION
  , QUOTE_STATUS_ID
  , QUOTE_SOURCE_CODE
  , QUOTE_EXPIRATION_DATE
  , PRICE_FROZEN_DATE
  , QUOTE_PASSWORD
  , ORIGINAL_SYSTEM_REFERENCE
  , PARTY_ID
  , CUST_ACCOUNT_ID
  , ORG_CONTACT_ID
  , PHONE_ID
  , INVOICE_TO_PARTY_SITE_ID
  , INVOICE_TO_PARTY_ID
  , ORIG_MKTG_SOURCE_CODE_ID
  , MARKETING_SOURCE_CODE_ID
  , ORDER_TYPE_ID
  , QUOTE_CATEGORY_CODE
  , ORDERED_DATE
  , ACCOUNTING_RULE_ID
  , INVOICING_RULE_ID
  , EMPLOYEE_PERSON_ID
  , PRICE_LIST_ID
  , CURRENCY_CODE
  , TOTAL_LIST_PRICE
  , TOTAL_ADJUSTED_AMOUNT
  , TOTAL_ADJUSTED_PERCENT
  , TOTAL_TAX
  , TOTAL_SHIPPING_CHARGE
  , SURCHARGE
  , TOTAL_QUOTE_PRICE
  , PAYMENT_AMOUNT
  , EXCHANGE_RATE
  , EXCHANGE_TYPE_CODE
  , EXCHANGE_RATE_DATE
  , CONTRACT_ID
```

```

SALES_CHANNEL_CODE      ,
ORDER_ID                ,
ATTRIBUTE_CATEGORY      ,
ATTRIBUTE1              ,
ATTRIBUTE2              ,
ATTRIBUTE3              ,
ATTRIBUTE4              ,
ATTRIBUTE5              ,
ATTRIBUTE6              ,
ATTRIBUTE7              ,
ATTRIBUTE8              ,
ATTRIBUTE9              ,
ATTRIBUTE10             ,
ATTRIBUTE11             ,
ATTRIBUTE12             ,
ATTRIBUTE13             ,
ATTRIBUTE14             ,
ATTRIBUTE15
FROM ASO_QUOTE_HEADERS_ALL

```

Column Descriptions

Name	Null?	Type	Description
QUOTE_HEADER_ID	NULL	VARCHAR2(240)	Refer to base table.
CREATION_DATE	NULL	VARCHAR2(240)	Refer to base table.
CREATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_LOGIN	NULL	VARCHAR2(240)	Refer to base table.
REQUEST_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_APPLICATION_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
ORG_ID	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_NAME	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_VERSION	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_STATUS_ID	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_SOURCE_CODE	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_EXPIRATION_DATE	NULL	VARCHAR2(240)	Refer to base table.
PRICE_FROZEN_DATE	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_PASSWORD	NULL	VARCHAR2(240)	Refer to base table.
ORIGINAL_SYSTEM_REFERENCE	NULL	VARCHAR2(240)	Refer to base table.
PARTY_ID	NULL	VARCHAR2(240)	Refer to base table.
CUST_ACCOUNT_ID	NULL	VARCHAR2(240)	Refer to base table.
ORG_CONTACT_ID	NULL	VARCHAR2(240)	Refer to base table.
PHONE_ID	NULL	VARCHAR2(240)	Refer to base table.
INVOICE_TO_PARTY_SITE_ID	NULL	VARCHAR2(240)	Refer to base table.
INVOICE_TO_PARTY_ID	NULL	VARCHAR2(240)	Refer to base table.
ORIG_MKTG_SOURCE_CODE_ID	NULL	VARCHAR2(240)	Refer to base table.
MARKETING_SOURCE_CODE_ID	NULL	VARCHAR2(240)	Refer to base table.
ORDER_TYPE_ID	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_CATEGORY_CODE	NULL	VARCHAR2(240)	Refer to base table.
ORDERED_DATE	NULL	VARCHAR2(240)	Refer to base table.
ACCOUNTING_RULE_ID	NULL	VARCHAR2(240)	Refer to base table.
INVOICING_RULE_ID	NULL	VARCHAR2(240)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EMPLOYEE_PERSON_ID	NULL	VARCHAR2(240)	Refer to base table.
PRICE_LIST_ID	NULL	VARCHAR2(240)	Refer to base table.
CURRENCY_CODE	NULL	VARCHAR2(240)	Refer to base table.
TOTAL_LIST_PRICE	NULL	VARCHAR2(240)	Refer to base table.
TOTAL_ADJUSTED_AMOUNT	NULL	VARCHAR2(240)	Refer to base table.
TOTAL_ADJUSTED_PERCENT	NULL	VARCHAR2(240)	Refer to base table.
TOTAL_TAX	NULL	VARCHAR2(240)	Refer to base table.
TOTAL_SHIPPING_CHARGE	NULL	VARCHAR2(240)	Refer to base table.
SURCHARGE	NULL	VARCHAR2(240)	Refer to base table.
TOTAL_QUOTE_PRICE	NULL	VARCHAR2(240)	Refer to base table.
PAYMENT_AMOUNT	NULL	VARCHAR2(240)	Refer to base table.
EXCHANGE_RATE	NULL	VARCHAR2(240)	Refer to base table.
EXCHANGE_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
EXCHANGE_RATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
CONTRACT_ID	NULL	VARCHAR2(240)	Refer to base table.
SALES_CHANNEL_CODE	NULL	VARCHAR2(240)	Refer to base table.
ORDER_ID	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.

ASO_QUOTE_HEADERS_V

View Definition

```
CREATE VIEW ASO_QUOTE_HEADERS_V
as SELECT
    ASO_QUOTES.ROWID ROW_ID
    , ASO_QUOTES.QUOTE_HEADER_ID
    , ASO_QUOTES.ORDER_ID
    , ASO_QUOTES.ORG_ID
    , ASO_QUOTES.LAST_UPDATE_DATE
    , ASO_QUOTES.LAST_UPDATED_BY
    , ASO_QUOTES.CREATION_DATE
    , ASO_QUOTES.CREATED_BY
    , ASO_QUOTES.LAST_UPDATE_LOGIN
    , ASO_QUOTES.REQUEST_ID
    , ASO_QUOTES.PROGRAM_APPLICATION_ID
    , ASO_QUOTES.PROGRAM_ID
    , ASO_QUOTES.PROGRAM_UPDATE_DATE
    , ASO_QUOTES.ORIGINAL_SYSTEM_REFERENCE
    , ASO_QUOTES.EMPLOYEE_PERSON_ID
    , I_PPF.FIRST_NAME SALESREP_FIRST_NAME
    , I_PPF.LAST_NAME SALESREP_LAST_NAME
    , ASO_QUOTES.PRICE_LIST_ID
    , I_PRICE_LISTS.NAME PRICE_LIST_NAME
    , ASO_QUOTES.QUOTE_STATUS_ID
    , ASO_STATUS_VL.STATUS_CODE QUOTE_STATUS_CODE
    , ASO_STATUS_VL.MEANING QUOTE_STATUS
    , ASO_STATUS_VL.UPDATE_ALLOWED_FLAG
    , ASO_STATUS_VL.AUTO_VERSION_FLAG

    , ASO_QUOTES.QUOTE_SOURCE_CODE
    , ASO_QUOTES.PARTY_ID
    , DECODE(I_PARTIES.PARTY_TYPE, 'ORGANIZATION', I_PARTIES.PARTY_NAME, NULL)
    , I_PARTIES.PARTY_TYPE
    , DECODE(I_PARTIES.PARTY_TYPE, 'ORGANIZATION',
I_CONTACT.FIRST_NAME,I_PARTIES.PERSON_FIRST_NAME)

    , DECODE(I_PARTIES.PARTY_TYPE, 'ORGANIZATION',
I_CONTACT.MIDDLE_NAME,I_PARTIES.PERSON_MIDDLE_NAME)

    , DECODE(I_PARTIES.PARTY_TYPE, 'ORGANIZATION', I_CONTACT.LAST_NAME,I_PARTIES.PERSON_LAST_NAME)

    , ASO_QUOTES.CUST_ACCOUNT_ID
    , I_ACCTS.ACCOUNT_NUMBER
    , ASO_QUOTES.ORG_CONTACT_ID
    , ASO_QUOTES.PHONE_ID
    , I_PHONE.PHONE_AREA_CODE
    , I_PHONE.PHONE_NUMBER
    , I_PHONE.PHONE_EXTENSION
    , I_PHONE.PHONE_LINE_TYPE
    , ASO_QUOTES.QUOTE_NAME
    , ASO_QUOTES.QUOTE_NUMBER
    , ASO_QUOTES.QUOTE_VERSION
```

Oracle Proprietary, Confidential Information--Use Restricted by Contract


```

, ASO_QUOTES.QUOTE_EXPIRATION_DATE
, ASO_QUOTES.QUOTE_CATEGORY_CODE
, ASO_QUOTES.CURRENCY_CODE

, ASO_QUOTES.EXCHANGE_RATE
, ASO_QUOTES.EXCHANGE_TYPE_CODE
, ASO_QUOTES.EXCHANGE_RATE_DATE
, ASO_QUOTES.ORIG_MKTG_SOURCE_CODE_ID
, ASO_QUOTES.MARKETING_SOURCE_CODE_ID
, I_MKTG_SRC.NAME
, I_MKTG_SRC.SOURCE_CODE
, ASO_QUOTES.ORDERED_DATE
, ASO_QUOTES.ORDER_TYPE_ID
, I_ORDER_TYPES.NAME ORDER_TYPE_NAME
, ASO_TAX.TAX_EXEMPT_NUMBER
, ASO_TAX.TAX_EXEMPT_REASON_CODE
, ASO_TAX.TAX_EXEMPT_FLAG
, ASO_QUOTES.TOTAL_LIST_PRICE
, ASO_QUOTES.TOTAL_ADJUSTED_AMOUNT
, ASO_QUOTES.TOTAL_ADJUSTED_PERCENT
, ASO_QUOTES.TOTAL_TAX
, ASO_QUOTES.SURCHARGE
, ASO_QUOTES.TOTAL_SHIPPING_CHARGE
, ASO_QUOTES.TOTAL_QUOTE_PRICE
, ASO_QUOTES.ACCOUNTING_RULE_ID
, ASO_QUOTES.INVOICING_RULE_ID
, ASO_QUOTES.INVOICE_TO_PARTY_ID
, ASO_QUOTES.INVOICE_TO_PARTY_SITE_ID

, I_INVOICE_PARTIES.PARTY_NAME INVOICE_TO_PARTY_NAME
, I_INVOICE_PARTIES.PERSON_FIRST_NAME INVOICE_TO_CONTACT_FIRST_NAME
, I_INVOICE_PARTIES.PERSON_MIDDLE_NAME INVOICE_TO_CONTACT_MIDDLE_NAME
, I_INVOICE_PARTIES.PERSON_LAST_NAME INVOICE_TO_CONTACT_LAST_NAME
, I_INVOICE_LOCATIONS.ADDRESS1 INVOICE_TO_ADDRESS1
, I_INVOICE_LOCATIONS.ADDRESS2 INVOICE_TO_ADDRESS2
, I_INVOICE_LOCATIONS.ADDRESS3 INVOICE_TO_ADDRESS3
, I_INVOICE_LOCATIONS.ADDRESS4 INVOICE_TO_ADDRESS4
, I_INVOICE_LOCATIONS.COUNTRY_CODE INVOICE_TO_COUNTRY_CODE
, I_INVOICE_LOCATIONS.COUNTRY INVOICE_TO_COUNTRY
, I_INVOICE_LOCATIONS.CITY INVOICE_TO_CITY
, I_INVOICE_LOCATIONS.POSTAL_CODE INVOICE_TO_POSTAL_CODE
, I_INVOICE_LOCATIONS.STATE INVOICE_TO_STATE
, I_INVOICE_LOCATIONS.PROVINCE INVOICE_TO_PROVINCE
, I_INVOICE_LOCATIONS.COUNTY INVOICE_TO_COUNTY
, ASO_QUOTES.CONTRACT_ID

, ASO_QUOTES.PRICE_FROZEN_DATE
, ASO_QUOTES.QUOTE_PASSWORD
, ASO_QUOTES.PAYMENT_AMOUNT
, ASO_QUOTES.SALES_CHANNEL_CODE
, ASO_QUOTES.ATTRIBUTE_CATEGORY
, ASO_QUOTES.ATTRIBUTE1
, ASO_QUOTES.ATTRIBUTE2
, ASO_QUOTES.ATTRIBUTE3
, ASO_QUOTES.ATTRIBUTE4
, ASO_QUOTES.ATTRIBUTE5
, ASO_QUOTES.ATTRIBUTE6

```

Oracle Proprietary, Confidential Information--Use Restricted by Contract

```

, ASO_QUOTES.ATTRIBUTE7
, ASO_QUOTES.ATTRIBUTE8
, ASO_QUOTES.ATTRIBUTE9
, ASO_QUOTES.ATTRIBUTE10
, ASO_QUOTES.ATTRIBUTE11
, ASO_QUOTES.ATTRIBUTE12
, ASO_QUOTES.ATTRIBUTE13
, ASO_QUOTES.ATTRIBUTE14
, ASO_QUOTES.ATTRIBUTE15
FROM ASO_I_CONTACT_POINTS_V I_PHONE,ASO_I_CURRENCIES_V I_CURRENCY,
ASO_I_HR_PEOPLE_V I_PPF,ASO_I_ORDER_TYPES_V I_ORDER_TYPES,
ASO_I_ORG_CONTACTS_V I_CONTACT , ASO_I_PRICE_LISTS_V I_PRICE_LISTS,
ASO_QUOTE_HEADERS_ALL ASO_QUOTES,ASO_QUOTE_STATUSES_VL
ASO_STATUS_VL,ASO_TAX_DETAILS ASO_TAX,ASO_I_MKTG_SRC_CODES_V I_MKTG_SRC,
ASO_I_PARTIES_V I_INVOICE_PARTIES,ASO_I_PARTY_ADDRESSES_V I_INVOICE_LOCATIONS,

ASO_I_PARTIES_V I_PARTIES,ASO_I_CUST_ACCOUNTS_V I_ACCTS
Where ASO_QUOTES.QUOTE_STATUS_ID = ASO_STATUS_VL.QUOTE_STATUS_ID(+)
AND ASO_QUOTES.PRICE_LIST_ID = I_PRICE_LISTS.PRICE_LIST_ID(+)
AND ASO_QUOTES.PARTY_ID = I_PARTIES.PARTY_ID(+)
AND ASO_QUOTES.ORG_CONTACT_ID = I_CONTACT.ORG_CONTACT_ID(+)
AND ASO_QUOTES.CURRENCY_CODE = I_CURRENCY.CURRENCY_CODE(+)
AND ASO_QUOTES.MARKETING_SOURCE_CODE_ID = I_MKTG_SRC.SOURCE_CODE_ID (+)
AND ASO_QUOTES.INVOICE_TO_PARTY_SITE_ID = I_INVOICE_LOCATIONS.PARTY_SITE_ID (+)

AND ASO_QUOTES.INVOICE_TO_PARTY_ID = I_INVOICE_PARTIES.PARTY_ID (+)
AND ASO_QUOTES.ORDER_TYPE_ID = I_ORDER_TYPES.ORDER_TYPE_ID (+)
AND I_PPF.PERSON_ID (+) = ASO_QUOTES.EMPLOYEE_PERSON_ID
AND SYSDATE BETWEEN NVL(I_PPF.EFFECTIVE_START_DATE, sysdate) AND
NVL( I_PPF.EFFECTIVE_END_DATE, sysdate)
AND I_ACCTS.CUST_ACCOUNT_ID(+) = ASO_QUOTES.CUST_ACCOUNT_ID
AND aso_quotes.quote_header_id = aso_tax.quote_header_id(+)
AND aso_quotes.phone_id = i_phone.contact_point_id(+)
and aso_tax.quote_line_id(+) is null
order by quote_number,quote_version desc

```

Column Descriptions

Name	Null?	Type	Description
ROW_ID	NULL	ROWID	Row ID
QUOTE_HEADER_ID	NULL	NUMBER	Unique Identifier
ORDER_ID	NOT NULL	NUMBER	Refer to base table.
ORG_ID	NOT NULL	NUMBER	Operating unit which performed this transaction
LAST_UPDATE_DATE	NOT NULL	DATE	Standard WHO Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard WHO Column
CREATION_DATE	NOT NULL	DATE	Standard WHO Column
CREATED_BY	NOT NULL	NUMBER	Standard WHO Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard WHO Column
REQUEST_ID	NULL	NUMBER	Standard WHO Column
PROGRAM_APPLICATION_ID	NULL	NUMBER	Standard WHO Column
PROGRAM_ID	NULL	NUMBER	Standard WHO Column
PROGRAM_UPDATE_DATE	NULL	DATE	Standard WHO Column
ORIGINAL_SYSTEM_REFERENCE	NULL	VARCHAR2(240)	Original System Reference
EMPLOYEE_PERSON_ID	NULL	NUMBER	Employee Person ID
SALESREP_FIRST_NAME	NULL	VARCHAR2(20)	Sales Rep Name

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SALESREP_LAST_NAME	NULL	VARCHAR2(40)	Sales Rep Last Name
PRICE_LIST_ID	NULL	NUMBER	Price List ID from Pricing
PRICE_LIST_NAME	NULL	VARCHAR2(240)	Price List Name
QUOTE_STATUS_ID	NOT NULL	NUMBER	Quote Status Id
QUOTE_STATUS_CODE	NULL	VARCHAR2(30)	Quote Status Code
QUOTE_STATUS	NULL	VARCHAR2(240)	Quote Status
UPDATE_ALLOWED_FLAG	NULL	VARCHAR2(1)	Update Flag
AUTO_VERSION_FLAG	NULL	VARCHAR2(1)	If Set to Yes , Auto Version will be active
QUOTE_SOURCE_CODE	NOT NULL	VARCHAR2(240)	Quote Source Code
PARTY_ID	NULL	NUMBER	Party ID
ORGANIZATION_NAME	NOT NULL	VARCHAR2(255)	Organization Name
PARTY_TYPE	NOT NULL	VARCHAR2(30)	Type Of Party
PERSON_FIRST_NAME	NULL	VARCHAR2(150)	First Name of Party
PERSON_MIDDLE_NAME	NULL	VARCHAR2(60)	Middle Name
PERSON_LAST_NAME	NULL	VARCHAR2(150)	Last Name
CUST_ACCOUNT_ID	NULL	NUMBER	Customer Account Identifier
ACCOUNT_NUMBER	NULL	VARCHAR2(240)	Account Number
ORG_CONTACT_ID	NULL	NUMBER	Contact ID
PHONE_ID	NULL	NUMBER	Phone ID
PHONE_AREA_CODE	NULL	VARCHAR2(10)	Phone Area Code
PHONE_NUMBER	NULL	VARCHAR2(40)	Phone Number
PHONE_EXTENSION	NULL	VARCHAR2(20)	Phone Extension IF Any
PHONE_LINE_TYPE	NULL	VARCHAR2(30)	Type of the Phone Line
QUOTE_NAME	NULL	VARCHAR2(50)	Name of the Quote
QUOTE_NUMBER	NOT NULL	NUMBER	Quote Number
QUOTE_VERSION	NOT NULL	NUMBER	Version Of Quote
QUOTE_EXPIRATION_DATE	NULL	DATE	Date on which quote is expiring
QUOTE_CATEGORY_CODE	NULL	VARCHAR2(240)	quote category code
CURRENCY_CODE	NOT NULL	VARCHAR2(15)	Currency Code
EXCHANGE_RATE	NULL	NUMBER	Exchange Rate
EXCHANGE_TYPE_CODE	NULL	VARCHAR2(15)	Exchange type Code
EXCHANGE_RATE_DATE	NULL	DATE	Exchange Rate Date
ORIG_MKTG_SOURCE_CODE_ID	NULL	NUMBER	ORIG MKTG SOURCE CODE ID
MARKETING_SOURCE_CODE_ID	NULL	NUMBER	Marketing Source Code
MARKETING_SOURCE_NAME	NULL		Marketing Source Name
MARKETING_SOURCE_CODE	NULL		Marketing Source Code
ORDERED_DATE	NULL	DATE	Order Date
ORDER_TYPE_ID	NULL	NUMBER	Order Type
ORDER_TYPE_NAME	NULL	VARCHAR2(80)	Order Type Name
TAX_EXEMPT_NUMBER	NULL	VARCHAR2(80)	Tax Exemption Number
TAX_EXEMPT_REASON_CODE	NULL	VARCHAR2(30)	Tax Exemption Reason Code
TAX_EXEMPT_FLAG	NULL	VARCHAR2(1)	Tax Exemption Flag
TOTAL_LIST_PRICE	NULL	NUMBER	Total List Price
TOTAL_ADJUSTED_AMOUNT	NULL	NUMBER	Total Adjustment Amount
TOTAL_ADJUSTED_PERCENT	NULL	NUMBER	Total Adjusted Percent
TOTAL_TAX	NULL	NUMBER	Total Tax
SURCHARGE	NULL	NUMBER	Total Surcharge
TOTAL_SHIPPING_CHARGE	NULL	NUMBER	Total Shipping Charge
TOTAL_QUOTE_PRICE	NULL	NUMBER	Total Quote Price
ACCOUNTING_RULE_ID	NULL	NUMBER	Accounting Rule ID
INVOICING_RULE_ID	NULL	NUMBER	Invoicing Rule ID
INVOICE_TO_PARTY_ID	NULL	NUMBER	Bill to contact identifier
INVOICE_TO_PARTY_SITE_ID	NULL	NUMBER	Bill to site identifier
INVOICE_TO_PARTY_NAME	NULL	VARCHAR2(255)	Bill to Party Name
INVOICE_TO_CONTACT_FIRST_NAME	NULL	VARCHAR2(150)	Contact First Name of the Bill to person

Oracle Proprietary, Confidential Information--Use Restricted by Contract

INVOICE_TO_CONTACT_MIDDLE_NAME	NULL VARCHAR2(60)	Contact Middle Name of the Bill to person
INVOICE_TO_CONTACT_LAST_NAME	NULL VARCHAR2(150)	Contact Last Name of the Bill to person
INVOICE_TO_ADDRESS1	NULL VARCHAR2(240)	Bill To Address
INVOICE_TO_ADDRESS2	NULL VARCHAR2(240)	Bill To Address
INVOICE_TO_ADDRESS3	NULL VARCHAR2(240)	Bill To Address
INVOICE_TO_ADDRESS4	NULL VARCHAR2(240)	Bill To Address
INVOICE_TO_COUNTRY_CODE	NULL VARCHAR2(60)	Bill to Country Code
INVOICE_TO_COUNTRY	NULL VARCHAR2(80)	Bill to Country
INVOICE_TO_CITY	NULL VARCHAR2(60)	Bill To City
INVOICE_TO_POSTAL_CODE	NULL VARCHAR2(60)	Bill to Postal Code
INVOICE_TO_STATE	NULL VARCHAR2(60)	Bill to State
INVOICE_TO_PROVINCE	NULL VARCHAR2(60)	Bill to Province
INVOICE_TO_COUNTY	NULL VARCHAR2(60)	Bill to County
CONTRACT_ID	NULL NUMBER	Contract Id
PRICE_FROZEN_DATE	NULL DATE	Price Frozen Code
QUOTE_PASSWORD	NULL VARCHAR2(240)	Quote Password
PAYMENT_AMOUNT	NULL NUMBER	Payment amount
SALES_CHANNEL_CODE	NULL VARCHAR2(30)	Sales Channel Code
ATTRIBUTE_CATEGORY	NULL VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE2	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE3	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE4	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE5	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE6	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE7	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE8	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE9	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE10	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE11	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE12	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE13	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE14	NULL VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE15	NULL VARCHAR2(150)	Descriptive flexfield column

ASO_QUOTE_LINES_ALL

ASO_QUOTE_LINES_ALL stores information for a typical quote or an order line. This includes the item, item organization, unit of measure, quantity ordered, price list etc. The ITEM_TYPE column specifies what kind of item is quoted for this line. Each quote line can have zero or many detail lines in ASO_QUOTE_LINE_DETAILS_ALL, which stores specific line information about certain item types (e.g. service, configuration details).

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
ASO_QUOTE_HEADERS_ALL	QUOTE_HEADER_ID	QUOTE_HEADER_ID

Column Descriptions

Name	Null?	Type	Description
QUOTE_LINE_ID	NOT NULL	NUMBER	Quote line identifier
CREATION_DATE	NULL	DATE	Standard who column
CREATED_BY	NULL	NUMBER	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard who column
REQUEST_ID	NULL	NUMBER	Request identifier
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
QUOTE_HEADER_ID	NOT NULL	NUMBER	Quote header identifier to which the quote line is attached
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
LINE_CATEGORY_CODE	NULL	VARCHAR2(30)	Category Code
ITEM_TYPE_CODE	NULL	VARCHAR2(30)	Type of item quoted on this line
LINE_NUMBER	NULL	NUMBER	Line number
START_DATE_ACTIVE	NULL	DATE	Effective start date
END_DATE_ACTIVE	NULL	DATE	Effective end date
ORDER_LINE_TYPE_ID	NULL	NUMBER	Order line type identifier
INVOICE_TO_PARTY_SITE_ID	NULL	NUMBER	Bill to site identifier
INVOICE_TO_PARTY_ID	NULL	NUMBER	Bill to contact identifier
ORGANIZATION_ID	NOT NULL	NUMBER	Inventory organization identifier
INVENTORY_ITEM_ID	NOT NULL	NUMBER	Inventory item identifier
QUANTITY	NOT NULL	NUMBER	Quantity quoted
UOM_CODE	NOT NULL	VARCHAR2(3)	Unit of measure
MARKETING_SOURCE_CODE_ID	NULL	NUMBER	Identifier for campaign used
PRICE_LIST_ID	NULL	NUMBER	Price list identifier
PRICE_LIST_LINE_ID	NULL	NUMBER	Price list line identifier
CURRENCY_CODE	NULL	VARCHAR2(15)	Currency code
LINE_LIST_PRICE	NULL	NUMBER	Unit price for the item

Oracle Proprietary, Confidential Information--Use Restricted by Contract

LINE_ADJUSTED_AMOUNT	NULL	NUMBER	Adjustment or discount amount applied at the line level. A negative column is stored if the amount is to be deducted from the list price.
LINE_ADJUSTED_PERCENT	NULL	NUMBER	Adjustment or discount percent applied to this line
LINE_QUOTE_PRICE	NULL	NUMBER	Summation of line list price and line adjusted amount
RELATED_ITEM_ID	NULL	NUMBER	Related item identifier as a result of an substitute/up-sell/cross-sell effort
ITEM_RELATIONSHIP_TYPE	NULL	VARCHAR2(15)	Type of relationship between the related item and the quoted item (e.g. up-sell, cross-sell, substitute)
ACCOUNTING_RULE_ID	NULL	NUMBER	Accounting rule identifier
INVOICING_RULE_ID	NULL	NUMBER	Invoicing rule identifier
SPLIT_SHIPMENT_FLAG	NULL	VARCHAR2(1)	Flag to indicate whether the quote line is splitted into multiple shipments
BACKORDER_FLAG	NULL	VARCHAR2(1)	Flag to indicate whether the quote line is being backordered
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield column
SECURITY_GROUP_ID	NULL	NUMBER	Used in hosted environments
OBJECT_VERSION_NUMBER	NULL	NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
ASO_QUOTE_LINES_N1	NOT UNIQUE	5	QUOTE_HEADER_ID
ASO_QUOTE_LINES_N2	NOT UNIQUE	5	ORGANIZATION_ID
		10	INVENTORY_ITEM_ID
ASO_QUOTE_LINES_N3	NOT UNIQUE	5	PRICE_LIST_ID
		10	PRICE_LIST_LINE_ID
ASO_QUOTE_LINES_N4	NOT UNIQUE	5	ORG_ID
ASO_QUOTE_LINES_U1	UNIQUE	5	QUOTE_LINE_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ASO_QUOTE_LINES_ALL_V

View Definition

```
CREATE VIEW ASO_QUOTE_LINES_ALL_V
as SELECT
    QUOTE_LINE_ID
  CREATION_DATE
  CREATED_BY
  LAST_UPDATE_DATE
  LAST_UPDATED_BY
  LAST_UPDATE_LOGIN
  REQUEST_ID
  PROGRAM_APPLICATION_ID
  PROGRAM_ID
  PROGRAM_UPDATE_DATE
  QUOTE_HEADER_ID
  ORG_ID
  LINE_CATEGORY_CODE
  ITEM_TYPE_CODE
  LINE_NUMBER
  START_DATE_ACTIVE
  END_DATE_ACTIVE
  ORDER_LINE_TYPE_ID
  INVOICE_TO_PARTY_SITE_ID
  INVOICE_TO_PARTY_ID
  ORGANIZATION_ID
  INVENTORY_ITEM_ID
  QUANTITY
  UOM_CODE
  MARKETING_SOURCE_CODE_ID
  PRICE_LIST_ID
  PRICE_LIST_LINE_ID
  CURRENCY_CODE
  LINE_LIST_PRICE
  LINE_ADJUSTED_AMOUNT
  LINE_ADJUSTED_PERCENT
  LINE_QUOTE_PRICE
  RELATED_ITEM_ID
  ITEM_RELATIONSHIP_TYPE
  ACCOUNTING_RULE_ID
  INVOICING_RULE_ID
  SPLIT_SHIPMENT_FLAG
  BACKORDER_FLAG
  ATTRIBUTE_CATEGORY
  ATTRIBUTE1
  ATTRIBUTE2
  ATTRIBUTE3
  ATTRIBUTE4
  ATTRIBUTE5
  ATTRIBUTE6
  ATTRIBUTE7
  ATTRIBUTE8
  ATTRIBUTE9
```

```

ATTRIBUTE10      ,
ATTRIBUTE11      ,
ATTRIBUTE12      ,
ATTRIBUTE13      ,
ATTRIBUTE14      ,
ATTRIBUTE15
FROM ASO_QUOTE_LINES_ALL

```

Column Descriptions

Name	Null?	Type	Description
QUOTE_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
CREATION_DATE	NULL	VARCHAR2(240)	Refer to base table.
CREATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_LOGIN	NULL	VARCHAR2(240)	Refer to base table.
REQUEST_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_APPLICATION_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_HEADER_ID	NULL	VARCHAR2(240)	Refer to base table.
ORG_ID	NULL	VARCHAR2(240)	Refer to base table.
LINE_CATEGORY_CODE	NULL	VARCHAR2(240)	Refer to base table.
ITEM_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
LINE_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
START_DATE_ACTIVE	NULL	VARCHAR2(240)	Refer to base table.
END_DATE_ACTIVE	NULL	VARCHAR2(240)	Refer to base table.
ORDER_LINE_TYPE_ID	NULL	VARCHAR2(240)	Refer to base table.
INVOICE_TO_PARTY_SITE_ID	NULL	VARCHAR2(240)	Refer to base table.
INVOICE_TO_PARTY_ID	NULL	VARCHAR2(240)	Refer to base table.
ORGANIZATION_ID	NULL	VARCHAR2(240)	Refer to base table.
INVENTORY_ITEM_ID	NULL	VARCHAR2(240)	Refer to base table.
QUANTITY	NULL	VARCHAR2(240)	Refer to base table.
UOM_CODE	NULL	VARCHAR2(240)	Refer to base table.
MARKETING_SOURCE_CODE_ID	NULL	VARCHAR2(240)	Refer to base table.
PRICE_LIST_ID	NULL	VARCHAR2(240)	Refer to base table.
PRICE_LIST_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
CURRENCY_CODE	NULL	VARCHAR2(240)	Refer to base table.
LINE_LIST_PRICE	NULL	VARCHAR2(240)	Refer to base table.
LINE_ADJUSTED_AMOUNT	NULL	VARCHAR2(240)	Refer to base table.
LINE_ADJUSTED_PERCENT	NULL	VARCHAR2(240)	Refer to base table.
LINE_QUOTE_PRICE	NULL	VARCHAR2(240)	Refer to base table.
RELATED_ITEM_ID	NULL	VARCHAR2(240)	Refer to base table.
ITEM_RELATIONSHIP_TYPE	NULL	VARCHAR2(240)	Refer to base table.
ACCOUNTING_RULE_ID	NULL	VARCHAR2(240)	Refer to base table.
INVOICING_RULE_ID	NULL	VARCHAR2(240)	Refer to base table.
SPLIT_SHIPMENT_FLAG	NULL	VARCHAR2(240)	Refer to base table.
BACKORDER_FLAG	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.

ASO_QUOTE_LINES_V

View Definition

```
CREATE VIEW ASO_QUOTE_LINES_V
as SELECT
    QUOTE_LINES.ROWID ROW_ID
,QUOTE_LINES.QUOTE_LINE_ID QUOTE_LINE_ID
,QUOTE_LINES.QUOTE_HEADER_ID QUOTE_HEADER_ID
,QUOTE_LINES.CREATION_DATE CREATION_DATE
,QUOTE_LINES.CREATED_BY CREATED_BY
,QUOTE_LINES.LAST_UPDATE_DATE LAST_UPDATE_DATE
,QUOTE_LINES.LAST_UPDATED_BY LAST_UPDATED_BY
,QUOTE_LINES.LAST_UPDATE_LOGIN LAST_UPDATE_LOGIN
,QUOTE_LINES.REQUEST_ID REQUEST_ID
,QUOTE_LINES.PROGRAM_APPLICATION_ID PROGRAM_APPLICATION_ID
,QUOTE_LINES.PROGRAM_ID PROGRAM_ID
,QUOTE_LINES.PROGRAM_UPDATE_DATE PROGRAM_UPDATE_DATE
,QUOTE_LINES.ORG_ID ORG_ID
,QUOTE_LINES.LINE_CATEGORY_CODE LINE_CATEGORY_CODE
,QUOTE_LINES.ITEM_TYPE_CODE ITEM_TYPE_CODE
,LOOKUP.MEANING ITEM_TYPE
,QUOTE_LINES.LINE_NUMBER LINE_NUMBER
,QUOTE_LINES.START_DATE_ACTIVE START_DATE_ACTIVE
,QUOTE_LINES.END_DATE_ACTIVE END_DATE_ACTIVE
,QUOTE_LINES.ORDER_LINE_TYPE_ID ORDER_LINE_TYPE_ID
,QUOTE_LINES.ORGANIZATION_ID ORGANIZATION_ID
,QUOTE_LINES.INVENTORY_ITEM_ID INVENTORY_ITEM_ID
,QUOTE_LINES.QUANTITY QUANTITY
,QUOTE_LINES.UOM_CODE UOM_CODE
,QUOTE_LINES.MARKETING_SOURCE_CODE_ID MARKETING_SOURCE_CODE_ID
,QUOTE_LINES.PRICE_LIST_ID PRICE_LIST_ID
,I_PRICE_LISTS.NAME PRICE_LIST_NAME
,QUOTE_LINES.PRICE_LIST_LINE_ID PRICE_LIST_LINE_ID
,QUOTE_LINES.CURRENCY_CODE CURRENCY_CODE
,QUOTE_LINES.LINE_LIST_PRICE LINE_LIST_PRICE
,QUOTE_LINES.LINE_ADJUSTED_AMOUNT LINE_ADJUSTED_AMOUNT
,QUOTE_LINES.LINE_ADJUSTED_PERCENT LINE_ADJUSTED_PERCENT
,QUOTE_LINES.LINE_QUOTE_PRICE LINE_QUOTE_PRICE
,QUOTE_LINES.RELATED_ITEM_ID RELATED_ITEM_ID
,QUOTE_LINES.ITEM_RELATIONSHIP_TYPE ITEM_RELATIONSHIP_TYPE
,QUOTE_LINES.ACCOUNTING_RULE_ID ACCOUNTING_RULE_ID
,QUOTE_LINES.INVOICING_RULE_ID INVOICING_RULE_ID
,QUOTE_LINES.INVOICE_TO_PARTY_SITE_ID
,QUOTE_LINES.INVOICE_TO_PARTY_ID
,QUOTE_LINES.SPLIT_SHIPMENT_FLAG SPLIT_SHIPMENT_FLAG
,QUOTE_LINES.BACKORDER_FLAG BACKORDER_FLAG

    QUOTE_DETAILS.QUOTE_LINE_DETAIL_ID QUOTE_LINE_DETAIL_ID
,QUOTE_DETAILS.SERVICE_COTERMINATE_FLAG SERVICE_COTERMINATE_FLAG
,QUOTE_DETAILS.SERVICE_DURATION SERVICE_DURATION
,QUOTE_DETAILS.SERVICE_UNIT_SELLING_PERCENT SERVICE_UNIT_SELLING_PERCENT
,QUOTE_DETAILS.SERVICE_UNIT_LIST_PERCENT SERVICE_UNIT_LIST_PERCENT
,QUOTE_DETAILS.SERVICE_NUMBER SERVICE_NUMBER
```

Oracle Proprietary, Confidential Information--Use Restricted by Contract

```

,QUOTE_DETAILS.SERVICE_REF_TYPE_CODE
,QUOTE_DETAILS.SERVICE_REF_LINE_ID
,QUOTE_DETAILS.SERVICE_REF_SYSTEM_ID
,QUOTE_DETAILS.UNIT_PERCENT_BASE_PRICE          UNIT_PERCENT_BASE_PRICE
,QUOTE_DETAILS.SERVICE_PERIOD                    SERVICE_PERIOD
,QUOTE_LINES.ATTRIBUTE_CATEGORY      ATTRIBUTE_CATEGORY
,QUOTE_LINES.ATTRIBUTE1              ATTRIBUTE1
,QUOTE_LINES.ATTRIBUTE2              ATTRIBUTE2
,QUOTE_LINES.ATTRIBUTE3              ATTRIBUTE3
,QUOTE_LINES.ATTRIBUTE4              ATTRIBUTE4
,QUOTE_LINES.ATTRIBUTE5              ATTRIBUTE5
,QUOTE_LINES.ATTRIBUTE6              ATTRIBUTE6
,QUOTE_LINES.ATTRIBUTE7              ATTRIBUTE7
,QUOTE_LINES.ATTRIBUTE8              ATTRIBUTE8
,QUOTE_LINES.ATTRIBUTE9              ATTRIBUTE9
,QUOTE_LINES.ATTRIBUTE10             ATTRIBUTE10
,QUOTE_LINES.ATTRIBUTE11             ATTRIBUTE11
,QUOTE_LINES.ATTRIBUTE12             ATTRIBUTE12
,QUOTE_LINES.ATTRIBUTE13             ATTRIBUTE13
,QUOTE_LINES.ATTRIBUTE14             ATTRIBUTE14
,QUOTE_LINES.ATTRIBUTE15             ATTRIBUTE15
,ITEMS.SEGMENT1 INVENTORY_ITEM
,ITEMS.DESCRPTION ITEM_DESCRIPTION
,QUOTE_LINES.LINE_QUOTE_PRICE * QUOTE_LINES.QUANTITY  LINE_EXTENDED_PRICE
,QUOTE_DETAILS.CONFIG_HEADER_ID
,QUOTE_DETAILS.CONFIG_REVISION_NUM
,QUOTE_DETAILS.COMPLETE_CONFIGURATION_FLAG
,QUOTE_DETAILS.VALID_CONFIGURATION_FLAG
from
ASO_QUOTE_LINES_ALL QUOTE_LINES,
ASO_I_PRICE_LISTS_V I_PRICE_LISTS,
ASO_QUOTE_LINE_DETAILS QUOTE_DETAILS,
ASO_I_ITEMS_V ITEMS,
ASO_LOOKUPS LOOKUP

Where QUOTE_LINES.PRICE_LIST_ID = I_PRICE_LISTS.PRICE_LIST_ID(+) AND
QUOTE_LINES.QUOTE_LINE_ID = QUOTE_DETAILS.QUOTE_LINE_ID(+) AND
QUOTE_LINES.INVENTORY_ITEM_ID = ITEMS.INVENTORY_ITEM_ID AND
QUOTE_LINES.ORGANIZATION_ID = ITEMS.ORGANIZATION_ID AND
LOOKUP.LOOKUP_TYPE = 'ASO_ITEM_TYPE' AND
LOOKUP.LOOKUP_CODE = QUOTE_LINES.ITEM_TYPE_CODE

```

Column Descriptions

Name	Null?	Type	Description
ROW_ID	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_LINE_ID	NULL	NUMBER	Refer to base table.
QUOTE_HEADER_ID	NULL	NUMBER	Refer to base table.
CREATION_DATE	NULL	DATE	Refer to base table.
CREATED_BY	NULL	NUMBER	Refer to base table.
LAST_UPDATE_DATE	NULL	DATE	Refer to base table.
LAST_UPDATED_BY	NULL	NUMBER	Refer to base table.
LAST_UPDATE_LOGIN	NULL	NUMBER	Refer to base table.
REQUEST_ID	NULL	NUMBER	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

PROGRAM_APPLICATION_ID	NULL	NUMBER	Refer to base table.
PROGRAM_ID	NULL	NUMBER	Refer to base table.
PROGRAM_UPDATE_DATE	NULL	DATE	Refer to base table.
ORG_ID	NULL	NUMBER	Refer to base table.
LINE_CATEGORY_CODE	NULL	VARCHAR2(30)	Category Code
ITEM_TYPE_CODE	NULL	VARCHAR2(30)	Type of item quoted on this line
ITEM_TYPE	NULL	VARCHAR2(240)	Refer to base table.
LINE_NUMBER	NULL	NUMBER	Refer to base table.
START_DATE_ACTIVE	NULL	DATE	Refer to base table.
END_DATE_ACTIVE	NULL	DATE	Refer to base table.
ORDER_LINE_TYPE_ID	NULL	NUMBER	Refer to base table.
ORGANIZATION_ID	NULL	NUMBER	Refer to base table.
INVENTORY_ITEM_ID	NULL	VARCHAR2(240)	Refer to base table.
QUANTITY	NULL	NUMBER	Refer to base table.
UOM_CODE	NULL	VARCHAR2(240)	Refer to base table.
MARKETING_SOURCE_CODE_ID	NULL	NUMBER	Refer to base table.
PRICE_LIST_ID	NULL	NUMBER	Refer to base table.
PRICE_LIST_NAME	NULL	VARCHAR2(240)	Refer to base table.
PRICE_LIST_LINE_ID	NULL	NUMBER	Refer to base table.
CURRENCY_CODE	NULL	VARCHAR2(240)	Refer to base table.
LINE_LIST_PRICE	NULL	NUMBER	Refer to base table.
LINE_ADJUSTED_AMOUNT	NULL	NUMBER	Refer to base table.
LINE_ADJUSTED_PERCENT	NULL	NUMBER	Refer to base table.
LINE_QUOTE_PRICE	NULL	NUMBER	Refer to base table.
RELATED_ITEM_ID	NULL	NUMBER	Refer to base table.
ITEM_RELATIONSHIP_TYPE	NULL	VARCHAR2(240)	Refer to base table.
ACCOUNTING_RULE_ID	NULL	NUMBER	Refer to base table.
INVOICING_RULE_ID	NULL	NUMBER	Refer to base table.
INVOICE_TO_PARTY_SITE_ID	NULL	VARCHAR2(240)	Refer to base table.
INVOICE_TO_PARTY_ID	NULL	VARCHAR2(240)	Refer to base table.
SPLIT_SHIPMENT_FLAG	NULL	VARCHAR2(1)	Refer to base table.
BACKORDER_FLAG	NULL	VARCHAR2(1)	Refer to base table.
QUOTE_LINE_DETAIL_ID	NULL	NUMBER	Refer to base table.
SERVICE_COTERMINATE_FLAG	NULL	VARCHAR2(1)	Refer to base table.
SERVICE_DURATION	NULL	NUMBER	Refer to base table.
SERVICE_UNIT_SELLING_PERCENT	NULL	NUMBER	Refer to base table.
SERVICE_UNIT_LIST_PERCENT	NULL	NUMBER	Refer to base table.
SERVICE_NUMBER	NULL	NUMBER	Refer to base table.
SERVICE_REF_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_REF_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_REF_SYSTEM_ID	NULL	VARCHAR2(240)	Refer to base table.
UNIT_PERCENT_BASE_PRICE	NULL	NUMBER	Refer to base table.
SERVICE_PERIOD	NULL	VARCHAR2(3)	Refer to base table.
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.
INVENTORY_ITEM	NULL	VARCHAR2(240)	Refer to base table.
ITEM_DESCRIPTION	NULL	VARCHAR2(240)	Refer to base table.
LINE_EXTENDED_PRICE	NULL	NUMBER	Refer to base table.
CONFIG_HEADER_ID	NULL	VARCHAR2(240)	Refer to base table.
CONFIG_REVISION_NUM	NULL	VARCHAR2(240)	Refer to base table.
COMPLETE_CONFIGURATION_FLAG	NULL	VARCHAR2(240)	Refer to base table.
VALID_CONFIGURATION_FLAG	NULL	VARCHAR2(240)	Refer to base table.

ASO_QUOTE_LINE_ATTRIBS_V

View Definition

```
CREATE VIEW ASO_QUOTE_LINE_ATTRIBS_V
as SELECT
    attr.line_attribute_id
  ,attr.creation_date
  ,attr.created_by
  ,attr.last_update_date
  ,attr.last_updated_by
  ,attr.last_update_login
  ,attr.application_id
  ,ship.order_line_id
  ,attr.quote_line_id
  ,attr.attribute_type_code
  ,attr.name
  ,attr.value
  ,attr.value_type
  ,attr.status
  ,attr.start_date_active
  ,attr.end_date_active
from aso_quote_line_attribs_ext attr,
aso_shipments ship
  Where attr.quote_line_id = ship.quote_line_id
```

Column Descriptions

Name	Null?	Type	Description
LINE_ATTRIBUTE_ID	NOT NULL	NUMBER	Refer to base table.
CREATION_DATE	NULL	DATE	Refer to base table.
CREATED_BY	NULL	NUMBER	Refer to base table.
LAST_UPDATE_DATE	NULL	DATE	Refer to base table.
LAST_UPDATED_BY	NULL	NUMBER	Refer to base table.
LAST_UPDATE_LOGIN	NULL	NUMBER	Refer to base table.
APPLICATION_ID	NULL	NUMBER	Refer to base table.
ORDER_LINE_ID	NULL	NUMBER	Refer to base table.
QUOTE_LINE_ID	NOT NULL	NUMBER	Refer to base table.
ATTRIBUTE_TYPE_CODE	NOT NULL	VARCHAR2(30)	Refer to base table.
NAME	NULL	VARCHAR2(30)	Refer to base table.
VALUE	NULL	VARCHAR2(2000)	Refer to base table.
VALUE_TYPE	NULL	VARCHAR2(240)	Refer to base table.
STATUS	NULL	VARCHAR2(30)	Refer to base table.
START_DATE_ACTIVE	NULL	DATE	Refer to base table.
END_DATE_ACTIVE	NULL	DATE	Refer to base table.

ASO_QUOTE_LINE_DETAILS

ASO_QUOTE_LINE_DETAILS_ALL stores information specific to certain types of quote lines. This includes service related attributes, model/option related attributes and return related attributes.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
ASO_QUOTE_LINES_ALL	QUOTE_LINE_ID	QUOTE_LINE_ID

Column Descriptions

Name	Null?	Type	Description
QUOTE_LINE_DETAIL_ID	NOT NULL	NUMBER	Quote line detail identifier
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN		NUMBER	Standard who column
REQUEST_ID	NULL	NUMBER	Request identifier
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
QUOTE_LINE_ID	NOT NULL	NUMBER	Quote line identifier
CONFIG_HEADER_ID	NULL	NUMBER	Configuration header id
CONFIG_REVISION_NUM	NULL	NUMBER	Configuration revision number
CONFIG_ITEM_ID	NULL	NUMBER	Unique identifier for a configured item in CZ table.
COMPLETE_CONFIGURATION_FLAG	NULL	VARCHAR2(1)	Value is set to 'Y' if configuration is complete
VALID_CONFIGURATION_FLAG	NULL	VARCHAR2(1)	Value set to 'Y' if configuration is valid
COMPONENT_CODE	NULL	VARCHAR2(1000)	Concatenation of component item ids
SERVICE_COTERMINATE_FLAG	NULL	VARCHAR2(1)	Cotermination indicator for service order lines
SERVICE_DURATION	NULL	NUMBER	Duration for which the product is serviced
SERVICE_PERIOD	NULL	VARCHAR2(3)	Period for which the product is serviced
SERVICE_UNIT_SELLING_PERCENT	NULL	NUMBER	Percent actually charged to customer (percent based pricing only)
SERVICE_UNIT_LIST_PERCENT	NULL	NUMBER	Price list percent of the item (percent based pricing only)
SERVICE_NUMBER	NULL	NUMBER	service number
UNIT_PERCENT_BASE_PRICE	NULL	NUMBER	Base price used for percent based pricing
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield column
SERVICE_REF_TYPE_CODE	NULL	VARCHAR2(30)	type of object to which the service is linked
SERVICE_REF_ORDER_NUMBER	NULL	NUMBER	order number if the service reference is ORDER
SERVICE_REF_LINE_NUMBER	NULL	NUMBER	line number if the service reference is ORDER
SERVICE_REF_LINE_ID	NULL	NUMBER	line id of the line to which the service is linked if the service reference is ORDER
SERVICE_REF_SYSTEM_ID	NULL	NUMBER	system id
SERVICE_REF_OPTION_NUMB	NULL	NUMBER	option number
SERVICE_REF_SHIPMENT_NUMB	NULL	NUMBER	shipment number
RETURN_REF_TYPE	NULL	VARCHAR2(30)	Reference information for returns. (e.g., Order, Invoice, PO etc)
RETURN_REF_HEADER_ID	NULL	NUMBER	header id of the referenced object
RETURN_REF_LINE_ID	NULL	NUMBER	Line id of the referenced object
RETURN_ATTRIBUTE1	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE2	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE3	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE4	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE5	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE6	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE7	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE8	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE9	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE10	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE11	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE12	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE13	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE14	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_ATTRIBUTE15	NULL	VARCHAR2(240)	descriptive flexfields for returns
RETURN_REASON_CODE	NULL	VARCHAR2(240)	reason for return
SECURITY_GROUP_ID	NULL	NUMBER	Used in hosted environments

Oracle Proprietary, Confidential Information--Use Restricted by Contract

OBJECT_VERSION_NUMBER

NULL NUMBER

Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
ASO_QTE_LINE_DETLS_N2	NOT UNIQUE	5	CONFIG_HEADER_ID
		5	CONFIG_ITEM_ID
ASO_QTE_LINE_DETLS_N3	NOT UNIQUE	5	RETURN_REF_HEADER_ID
		5	RETURN_REF_LINE_ID
ASO_QTE_LINE_DETLS_N4	NOT UNIQUE	5	SERVICE_REF_SYSTEM_ID
		5	SERVICE_REF_LINE_ID
ASO_QUOTE_LINE_DETAILS_N1	NOT UNIQUE	5	QUOTE_LINE_ID
ASO_QUOTE_LINE_DETAILS_U1	UNIQUE	5	QUOTE_LINE_DETAIL_ID

ASO_QUOTE_LINE_DETAILS_V

View Definition

```
CREATE VIEW ASO_QUOTE_LINE_DETAILS_V
as SELECT
    QUOTE_LINE_DETAIL_ID
  , CREATION_DATE
  , CREATED_BY
  , LAST_UPDATE_DATE
  , LAST_UPDATED_BY
  , LAST_UPDATE_LOGIN
  , REQUEST_ID
  , PROGRAM_APPLICATION_ID
  , PROGRAM_ID
  , PROGRAM_UPDATE_DATE
  , QUOTE_LINE_ID
  , CONFIG_HEADER_ID
  , CONFIG_REVISION_NUM
  , CONFIG_ITEM_ID
  , COMPLETE_CONFIGURATION_FLAG
  , VALID_CONFIGURATION_FLAG
  , COMPONENT_CODE
  , SERVICE_COTERMINATE_FLAG
  , SERVICE_DURATION
  , SERVICE_PERIOD
  , SERVICE_UNIT_SELLING_PERCENT
  , SERVICE_UNIT_LIST_PERCENT
  , SERVICE_NUMBER
  , UNIT_PERCENT_BASE_PRICE
  , ATTRIBUTE_CATEGORY
  , ATTRIBUTE1
  , ATTRIBUTE2
  , ATTRIBUTE3
  , ATTRIBUTE4
  , ATTRIBUTE5
  , ATTRIBUTE6
  , ATTRIBUTE7
  , ATTRIBUTE8
  , ATTRIBUTE9
  , ATTRIBUTE10
  , ATTRIBUTE11
  , ATTRIBUTE12
  , ATTRIBUTE13
  , ATTRIBUTE14
  , ATTRIBUTE15
  , SERVICE_REF_TYPE_CODE
  , SERVICE_REF_ORDER_NUMBER
  , SERVICE_REF_LINE_NUMBER
  , SERVICE_REF_LINE_ID
  , SERVICE_REF_SYSTEM_ID
  , SERVICE_REF_OPTION_NUMB
  , SERVICE_REF_SHIPMENT_NUMB
  , RETURN_REF_TYPE
```

Oracle Proprietary, Confidential Information--Use Restricted by Contract

```

RETURN_REF_HEADER_ID      ,
RETURN_REF_LINE_ID        ,
RETURN_ATTRIBUTE1         ,
RETURN_ATTRIBUTE2         ,
RETURN_ATTRIBUTE3         ,
RETURN_ATTRIBUTE4         ,
RETURN_ATTRIBUTE5         ,
RETURN_ATTRIBUTE6         ,
RETURN_ATTRIBUTE7         ,
RETURN_ATTRIBUTE8         ,
RETURN_ATTRIBUTE9         ,
RETURN_ATTRIBUTE10        ,
RETURN_ATTRIBUTE11        ,
RETURN_ATTRIBUTE12        ,
RETURN_ATTRIBUTE13        ,
RETURN_ATTRIBUTE14        ,
RETURN_ATTRIBUTE15        ,
FROM ASO_QUOTE_LINE_DETAILS

```

Column Descriptions

Name	Null?	Type	Description
QUOTE_LINE_DETAIL_ID	NULL	VARCHAR2(240)	Refer to base table.
CREATION_DATE	NULL	VARCHAR2(240)	Refer to base table.
CREATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_LOGIN	NULL	VARCHAR2(240)	Refer to base table.
REQUEST_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_APPLICATION_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
CONFIG_HEADER_ID	NULL	VARCHAR2(240)	Refer to base table.
CONFIG_REVISION_NUM	NULL	VARCHAR2(240)	Refer to base table.
CONFIG_ITEM_ID	NULL	VARCHAR2(240)	Refer to base table.
COMPLETE_CONFIGURATION_FLAG	NULL	VARCHAR2(240)	Refer to base table.
VALID_CONFIGURATION_FLAG	NULL	VARCHAR2(240)	Refer to base table.
COMPONENT_CODE	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_COTERMINATE_FLAG	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_DURATION	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_PERIOD	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_UNIT_SELLING_PERCENT	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_UNIT_LIST_PERCENT	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
UNIT_PERCENT_BASE_PRICE	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_REF_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_REF_ORDER_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_REF_LINE_NUMBER	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_REF_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_REF_SYSTEM_ID	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_REF_OPTION_NUMB	NULL	VARCHAR2(240)	Refer to base table.
SERVICE_REF_SHIPMENT_NUMB	NULL	VARCHAR2(240)	Refer to base table.
RETURN_REF_TYPE	NULL	VARCHAR2(240)	Refer to base table.
RETURN_REF_HEADER_ID	NULL	VARCHAR2(240)	Refer to base table.
RETURN_REF_LINE_ID	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.

ASO_QUOTE_RELATED_OBJECTS

ASO_QUOTE_RELATED_OBJECTS stores the relationship between a quote or a quote line to any entity in the schema and records the type of relationship. The OBJECT_TYPE_CODE defines the type of entity the quote or quote line is related to, and the OBJECT_ID is the unique identifier of the related object.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
ASO_QUOTE_HEADERS_ALL	QUOTE_HEADER_ID	QUOTE_OBJECT_ID
ASO_QUOTE_LINES_ALL	QUOTE_LINE_ID	QUOTE_OBJECT_ID

Column Descriptions

Name	Null?	Type	Description
RELATED_OBJECT_ID	NOT NULL	NUMBER	Unique identifier of this record
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN		NUMBER	Standard who column
REQUEST_ID		NUMBER	Request identifier.
PROGRAM_APPLICATION_ID		NUMBER	Application identifier of last concurrent program to update record.
PROGRAM_ID		NUMBER	Identifier of last concurrent program to update record.
PROGRAM_UPDATE_DATE		DATE	Last date concurrent program updated record.
QUOTE_OBJECT_TYPE_CODE	NOT NULL	VARCHAR2(50)	Quote header identifier
QUOTE_OBJECT_ID	NOT NULL	NUMBER	Quote line identifier
OBJECT_TYPE_CODE	NOT NULL	VARCHAR2(30)	Type of the object defined in ASO_LOOKUPS
OBJECT_ID		NUMBER	Unique identifier of object
RELATIONSHIP_TYPE_CODE	NOT NULL	VARCHAR2(30)	Type of relationship defined in ASO_LOOKUPS
RECIPROCAL_FLAG		VARCHAR2(1)	Flag indicating whether this is a reciprocal relationship
SECURITY_GROUP_ID		NUMBER	Used in hosted environments
OBJECT_VERSION_NUMBER		NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
ASO_QTE_RLTD_OBJS_U1	UNIQUE	5	RELATED_OBJECT_ID

ASO_QUOTE_RELATED_OBJECTS_V

View Definition

```
CREATE VIEW ASO_QUOTE_RELATED_OBJECTS_V
as SELECT
    RELATED_OBJECT_ID
  , CREATION_DATE
  , CREATED_BY
  , LAST_UPDATE_DATE
  , LAST_UPDATED_BY
  , LAST_UPDATE_LOGIN
  , REQUEST_ID
  , PROGRAM_APPLICATION_ID
  , PROGRAM_ID
  , PROGRAM_UPDATE_DATE
  , QUOTE_OBJECT_TYPE_CODE
  , QUOTE_OBJECT_ID
  , OBJECT_TYPE_CODE
  , OBJECT_ID
  , RELATIONSHIP_TYPE_CODE
  , RECIPROCAL_FLAG
FROM ASO_QUOTE_RELATED_OBJECTS
```

Column Descriptions

Name	Null?	Type	Description
RELATED_OBJECT_ID	NULL	VARCHAR2(240)	Refer to base table.
CREATION_DATE	NULL	VARCHAR2(240)	Refer to base table.
CREATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATED_BY	NULL	VARCHAR2(240)	Refer to base table.
LAST_UPDATE_LOGIN	NULL	VARCHAR2(240)	Refer to base table.
REQUEST_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_APPLICATION_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_ID	NULL	VARCHAR2(240)	Refer to base table.
PROGRAM_UPDATE_DATE	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_OBJECT_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
QUOTE_OBJECT_ID	NULL	VARCHAR2(240)	Refer to base table.
OBJECT_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
OBJECT_ID	NULL	VARCHAR2(240)	Refer to base table.
RELATIONSHIP_TYPE_CODE	NULL	VARCHAR2(240)	Refer to base table.
RECIPROCAL_FLAG	NULL	VARCHAR2(240)	Refer to base table.

AS_ACCESSSES_ALL

AS_ACCESSSES_ALL stores information that indicates whether an employee can access an account or an opportunity.

Each record in AS_ACCESSSES_ALL includes values that identify an employee for which the access applies and the account or opportunity to which access is granted.

A TEAM_LEADER_FLAG of 'Y' means that the employee can update all information on the record to which he has access.

A TEAM_LEADER_FLAG of 'N' for an account access record means that the employee only can update the relationship column and contacts for the account.

A TEAM_LEADER_FLAG of 'N' for an opportunity access record means that the employee only can update the obstacles and competitor information for the opportunity.

A FREEZE_FLAG of 'Y' means that the employees access to the specified account or opportunity record has been frozen. The row will not be affected by changes made to the territory or to subsequent runs of the Territory Assignment program.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_LEADS_ALL	LEAD_ID	LEAD_ID
AS_SALES_LEADS	SALES_LEAD_ID	SALES_LEAD_ID
HZ_PARTIES	PARTY_ID	CUSTOMER_ID
HZ_PARTIES	PARTY_ID	PARTNER_ADDRESS_ID
HZ_PARTY_SITES	PARTY_SITE_ID	ADDRESS_ID
HZ_PARTY_SITES	PARTY_SITE_ID	PARTNER_CUSTOMER_ID
JTF_RS_GROUPS_B	GROUP_ID	SALES_GROUP_ID
JTF_RS_GROUPS_B	GROUP_ID	SALES_GROUP_ID
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	SALESFORCE_ID
PER_ALL_PEOPLE_F	PERSON_ID	PERSON_ID
PER_ALL_PEOPLE_F	PERSON_ID	CREATED_PERSON_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
ACCESS_TYPE	ACCESS_TYPE	AS_LOOKUPS
	ACCOUNT	Account
	ACCOUNT AND LEADS	Account and Leads
	LEAD	Lead
FREEZE_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
REASSIGN_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Oracle Proprietary, Confidential Information--Use Restricted by Contract

TEAM_LEADER_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
ACCESS_ID (PK)	NOT NULL	NUMBER	Access identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
ACCESS_TYPE	NOT NULL	VARCHAR2(30)	Obsolete. Use 'X' when creating records
FREEZE_FLAG	NOT NULL	VARCHAR2(1)	Flag indicating whether the record is frozen
REASSIGN_FLAG	NOT NULL	VARCHAR2(1)	Flag indicating whether the record may need to be reassigned to another employee
TEAM_LEADER_FLAG	NOT NULL	VARCHAR2(1)	Flag indicating if the employee is a team leader of an account or opportunity
CUSTOMER_ID	NOT NULL	NUMBER	Customer/prospect identifier
ADDRESS_ID	NULL	NUMBER	Account identifier
SALESFORCE_ID	NOT NULL	NUMBER	Salesforce identifier
PERSON_ID	NULL	NUMBER(9)	Identifier of employee who has access to the record
PARTNER_CUSTOMER_ID	NULL	NUMBER	Partner customer identifier
PARTNER_ADDRESS_ID	NULL	NUMBER	Partner account identifier
CREATED_PERSON_ID	NULL	NUMBER(9)	Identifier of who created the access record
FREEZE_DATE	NULL	DATE	The date on which the access record was frozen
LEAD_ID	NULL	NUMBER	Lead identifier
REASSIGN_REASON	NULL	VARCHAR2(240)	The reason that the access record needs reassigning to another employee
SALESFORCE_ROLE_CODE	NULL	VARCHAR2(30)	The role the salesforce plays in the team
SALESFORCE_RELATIONSHIP_CODE	NULL	VARCHAR2(30)	Sales and Marketing lookup code for 'RELATIONSHIP', Prospect or Customer
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
DOWNLOADABLE_FLAG	NULL	VARCHAR2(1)	Obsolete in CRM 11i - Specify if the row is to be downloaded to the laptop
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive Flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive Flexfield segment column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
SALES_GROUP_ID	NULL	NUMBER	group id of this sales rep.
REASSIGN_REQUESTED_PERSON_ID	NULL	NUMBER(9)	Reassign requested person identifier
REASSIGN_REQUEST_DATE	NULL	DATE	Reassign request date
INTERNAL_UPDATE_ACCESS	NULL	NUMBER(1)	Internal Update Access
SALES_LEAD_ID	NULL	NUMBER	Sales Lead identifier - FK to AS_SALES_LEADS table
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
PARTNER_CONT_PARTY_ID	NULL	NUMBER	Partner contact party id. Used by PRM

Indexes

Index Name	Index Type	Sequence	Column Name
AS_ACCESSSES_N1	NOT UNIQUE	1	PERSON_ID
AS_ACCESSSES_N2	NOT UNIQUE	1	CUSTOMER_ID
		2	ADDRESS_ID
AS_ACCESSSES_N3	NOT UNIQUE	1	LEAD_ID
AS_ACCESSSES_N4	NOT UNIQUE	2	REASSIGN_FLAG
AS_ACCESSSES_N5	NOT UNIQUE	1	ADDRESS_ID
AS_ACCESSSES_N6	NOT UNIQUE	5	SALES_LEAD_ID
AS_ACCESSSES_U1	UNIQUE	5	ACCESS_ID
		11	ORG_ID
AS_ACCESSSES_U2	UNIQUE	1	SALESFORCE_ID
		4	SALES_GROUP_ID
		6	ADDRESS_ID
		9	LEAD_ID
		11	SALES_LEAD_ID
		15	ORG_ID

Sequences

Sequence	Derived Column
AS_ACCESSES_S	ACCESS_ID

AS_FORECAST_PROB_ALL_B

AS_FORECAST_PROB_ALL defines win probability values for sales opportunities. When LEAD_STATUS_CHANGE_CODE is present, the record associates the win probability with the opportunity status. The association affects the opportunity from behavior, such that changing update on either win probability or opportunity status affects the counterpart as specified by the association in AS_FORECAST_PROB.

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
ENABLED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
USAGE_INDICATOR	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
PROBABILITY_VALUE (PK)	NOT NULL	NUMBER	Win probability value of sales opportunity in the range from 0 to 100
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
START_DATE_ACTIVE	NOT NULL	DATE	Date which the win probability becomes active
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	Flag to indicate if the win probability is enabled
MEANING	NUL	VARCHAR2(80)	Obsolete
LEAD_STATUS_CHANGE_CODE	NUL	VARCHAR2(30)	After an opportunity win probability exceeds this record's value, the opportunity status changes to this value
END_DATE_ACTIVE	NUL	DATE	Date which the win probability becomes inactive
ORG_ID	NUL	NUMBER	Operating unit which performed this transaction
USAGE_INDICATOR	NUL	VARCHAR2(30)	Indicates to whom the data will be exposed to. valid values are "OS" , "PRM" ,"ALL"
ATTRIBUTE_CATEGORY	NUL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NUL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2	NUL	VARCHAR2(150)	Descriptive flexfield segment column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
INTERNAL_UPGRADE_PROB_VALUE	NULL	NUMBER	For internal use only on data migration- to keep the new probability value

Indexes

Index Name	Index Type	Sequence	Column Name
AS_FORECAST_PROB_ALL_B_U1	UNIQUE	1 3	PROBABILITY_VALUE ORG_ID

AS_FORECAST_PROB_ALL_TL

Columns that move from AS_FORECAST_PROB_ALL_B are 1 Probability_Value, 2) Meaning Primary Key is Probability_Value + Language

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_FORECAST_PROB_ALL_B	PROBABILITY_VALUE	PROBABILITY_VALUE

Column Descriptions

Name	Null?	Type	Description
PROBABILITY_VALUE (PK)	NOT NULL	NUMBER	Win probability value of sales opportunity in the range from 0 to 100
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	language
SOURCE_LANG	NOT NULL	VARCHAR2(4)	source language
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
MEANING	NULL	VARCHAR2(80)	Text description of the win probability
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_FORECAST_PROB_ALL_TL_U1	UNIQUE	2	PROBABILITY_VALUE
		4	LANGUAGE

AS_FORECAST_WORKSHEETS

This will store header information for the opportunity and product category worksheet.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_INTERNAL_FORECASTS	FORECAST_ID	FORECAST_ID

Column Descriptions

Name	Null?	Type	Description
FORECAST_WORKSHEET_ID (PK)	NOT NULL	NUMBER	Forecast Worksheet Identifier
FORECAST_CATEGORY_ID	NULL	NUMBER	Foreign Key to AS_FORECAST_CATEGORIES
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who Column
REQUEST_ID	NULL	NUMBER	Request Identifier
PROGRAM_APPLICATION_ID	NULL	NUMBER	Program Application Identifier
PROGRAM_ID	NULL	NUMBER	Program Identifier
PROGRAM_UPDATE_DATE	NULL	DATE	Program Update Date
FORECAST_ID	NOT NULL	NUMBER	Forecast Identifier (Foreign Key to AS_INTERNAL_FORECASTS)
SALESFORCE_ID	NULL	NUMBER	Sales Force Identifier (De-normalized from AS_INTERNAL_FORECASTS Table)
SALES_GROUP_ID	NULL	NUMBER	Sales Group Identifier (De-normalized from AS_INTERNAL_FORECASTS Table)
WORKSHEET_TYPE	NOT NULL	NUMBER(30)	Worksheet Type (If the record is header for Opportunity Worksheet or Product Category Worksheet . Values : "OPPORTUNITY" / "PRODUCT"
EMPLOYEE_PERSON_ID	NULL	NUMBER	Employee Person Identifier from HR .(De-normalized from AS_INTERNAL_FORECASTS)
PERIOD_NAME	NULL	VARCHAR2(15)	Period Name (e.g. 'Q4-00' / 'JAN-00') . De-normalized from AS_INTERNAL_FORECASTS.
CURRENCY_CODE	NOT NULL	VARCHAR2(15)	Currency Code (e.g. 'USD', 'CAD'). De-normalized from AS_INTERNAL_FORECASTS
STATUS_CODE	NOT NULL	VARCHAR2(30)	Status Code of worksheet (e.g. 'SUBMITTED' or 'SAVED')
SAVE_DATE	NULL	DATE	Date on which worksheet was saved .
CREDIT_TYPE_ID	NULL	NUMBER	Credit Type Identifier (Used to determine if the amount is revenue or non-revenue)
WORST_FORECAST_AMOUNT_FLAG	NULL	VARCHAR2(1)	Flag to indicate the currency conversion rate was not found while rolling up the worst forecast amount)
WORST_FORECAST_AMOUNT	NULL	NUMBER	Worst forecast amount

Oracle Proprietary, Confidential Information--Use Restricted by Contract

FORECAST_AMOUNT_FLAG	NULL	VARCHAR2(1)	Flag to indicate the currency conversion rate was not found while rolling up the forecast amount)
FORECAST_AMOUNT	NULL	NUMBER	Forecast Amount .
BEST_FORECAST_AMOUNT_FLAG	NULL	VARCHAR2(1)	Flag to indicate the currency conversion rate was not found while rolling up the best forecast amount)
BEST_FORECAST_AMOUNT	NULL	NUMBER	best forecast amount
ACTIVE_FLAG	NULL	VARCHAR2(1)	Obsolete
START_DATE_ACTIVE	NULL	DATE	Start Date of this record .
END_DATE_ACTIVE	NULL	DATE	End Date of using this record . No more changes allowed after the end date.
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_FORECAST_WORKSHEETS_N1	NOT UNIQUE	5	FORECAST_ID
AS_FORECAST_WORKSHEETS_U1	NOT UNIQUE	5	FORECAST_WORKSHEET_ID

Sequences

Sequence	Derived Column
AS_FORECAST_WORKSHEETS_S	FORECAST_WORKSHEET_ID

AS_INTERESTS_ALL

AS_INTERESTS_ALL stores information about a product that an account, contact, or opportunity has interested in.

Each row includes a value that identifies the customer, contact or lead that the interest applies to. Each row can also include values that identify the interaction that led to the interest, the item of interest, a description of the nature of the interest, and the level of interest.

You can create records in AS_SCRIPT_ANSWER_ACTIONS that will trigger the creation of a row in AS_INTERESTS_ALL when a contact gives a pre-defined answer to a script question.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_INTEREST_CODES_B	INTEREST_CODE_ID	PRIMARY_INTEREST_CODE_ID
AS_INTEREST_CODES_B	INTEREST_CODE_ID	SECONDARY_INTEREST_CODE_ID
AS_INTEREST_TYPES_B	INTEREST_TYPE_ID	INTEREST_TYPE_ID
AS_LEADS_ALL	LEAD_ID	LEAD_ID
HZ_ORG_CONTACTS	ORG_CONTACT_ID	CONTACT_ID
HZ_PARTY_SITES	PARTY_SITE_ID	ADDRESS_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
INTEREST_USE_CODE	INTEREST_USE	AS_LOOKUPS
	COMPANY_CLASSIFICATION	Company Classification
	CONTACT_INTEREST	Contact Interest
	LEAD_CLASSIFICATION	Lead Classification
STATUS_CODE	INTEREST_STATUS	AS_LOOKUPS

Column Descriptions

Name	Null?	Type	Description
INTEREST_ID (PK)	NOT NULL	NUMBER	Product interest identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
REQUEST_ID	NULL	NUMBER	Standard who column
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record.
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
INTEREST_USE_CODE	NOT NULL	VARCHAR2(30)	Type of interest/classification (LEAD, CONTACT, or COMPANY)
INTEREST_TYPE_ID	NOT NULL	NUMBER	Type of interest
CUSTOMER_ID	NOT NULL	NUMBER	Customer/prospect identifier
ADDRESS_ID	NULL	NUMBER	Account identifier
LEAD_ID	NULL	NUMBER	Lead identifier

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CONTACT_ID	NULL	NUMBER	Contact identifier
PRIMARY_INTEREST_CODE_ID	NULL	NUMBER	Primary interest code identifier
SECONDARY_INTEREST_CODE_ID	NULL	NUMBER	Secondary interest code identifier
STATUS_CODE	NULL	VARCHAR2(30)	Level of interest code
DESCRIPTION	NULL	VARCHAR2(240)	Description of the interest
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
INTERNAL_UPGRADE_CUST_ID	NULL	NUMBER	Column used to store old customer id for interest_use_code = 'CONTACT_INTEREST'

Indexes

Index Name	Index Type	Sequence	Column Name
AS_INTERESTS_N1	NOT UNIQUE	3	CUSTOMER_ID
		4	ADDRESS_ID
AS_INTERESTS_N2	NOT UNIQUE	4	CONTACT_ID
AS_INTERESTS_N3	NOT UNIQUE	1	LEAD_ID
AS_INTERESTS_N4	NOT UNIQUE	1	INTEREST_TYPE_ID
		2	INTEREST_USE_CODE
AS_INTERESTS_N5	NOT UNIQUE	2	ADDRESS_ID
AS_INTERESTS_U1	UNIQUE	1	INTEREST_ID
		2	ORG_ID

Sequences

Sequence	Derived Column
AS_INTERESTS_S	INTEREST_ID

Database Triggers

Trigger Name : AS_INTERESTS_BIUD
 Trigger Time : BEFORE
 Trigger Level : ROW
 Trigger Event : INSERT, UPDATE, DELETE

The trigger inserts/changes changed accounts/leads caused by changed interests of territory qualifiers into AS_CHANGED_ACCOUNTS_ALL table.

AS_INTEREST_CATEGORY_SETS_ALL

AS_INTEREST_CATEGORY_SETS_ALL stores information about product types that a customer or contact is interested in, and the (inventory) category set that corresponds to it. Each row includes a value that identifies the interest type, and a value that identifies the category set. The table is used only by the concurrent program which pulls inventory categories into sales..

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_INTEREST_TYPES_B	INTEREST_TYPE_ID	INTEREST_TYPE_ID
MTL_CATEGORY_SETS_B	CATEGORY_SET_ID	CATEGORY_SET_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
ENABLED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
CATEGORY_SET_ID (PK)	NOT NULL	NUMBER	Inventory Category set identifier
INTEREST_TYPE_ID (PK)	NOT NULL	NUMBER	Interest type identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
ENABLED_FLAG	NULL	VARCHAR2(1)	Flag to indicate weather the interest category set is enabled or not
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_INTEREST_CATEGORY_SETS_U1	UNIQUE	1	CATEGORY_SET_ID
		2	INTEREST_TYPE_ID
		3	ORG_ID

AS_INTEREST_CODES_B

This stores the code that are used for anything that a customer or a contact may be interested in. This includes anything from products to applications and even to competitors. It should not be used for items that are tracked in Oracle Inventory. These items have their own code, the Item Number, already defined in the Inventory system.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_INTEREST_CODES_B	INTEREST_CODE_ID	PARENT_INTEREST_CODE_ID
AS_INTEREST_TYPES_B	INTEREST_TYPE_ID	INTEREST_TYPE_ID
MTL_CATEGORIES_B	CATEGORY_ID	CATEGORY_ID
MTL_CATEGORY_SETS_B	CATEGORY_SET_ID	CATEGORY_SET_ID
MTL_SYSTEM_ITEMS_B	INVENTORY_ITEM_ID	PF_ITEM_ID
	ORGANIZATION_ID	PF_ORGANIZATION_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
ENABLED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
INTEREST_CODE_ID (PK)	NOT NULL	NUMBER	Interest code identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
REQUEST_ID	N	NUMBER	Request identifier
PROGRAM_APPLICATION_ID	N	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	N	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	N	DATE	Last date concurrent program updated record
INTEREST_TYPE_ID	NOT NULL	NUMBER	Type of interest
PARENT_INTEREST_CODE_ID	N	NUMBER	Parent interest code identifier
CATEGORY_ID	N	NUMBER	Category identifier
CATEGORY_SET_ID	N	NUMBER	Category set identifier
PF_ITEM_ID	N	NUMBER	Product Family item identifier
PF_ORGANIZATION_ID	N	NUMBER	Product Family item's organization identifier
CURRENCY_CODE	N	VARCHAR2(15)	Currency Code for the Product Family Price
PRICE	N	NUMBER	Price in the currency.
ATTRIBUTE_CATEGORY	N	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	N	VARCHAR2(150)	Flex field Columns
ATTRIBUTE2	N	VARCHAR2(150)	Flex field Columns
ATTRIBUTE3	N	VARCHAR2(150)	Flex field Columns

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE4	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE5	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE6	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE7	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE8	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE9	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE10	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE11	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE12	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE13	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE14	NULL	VARCHAR2(150)	Flex field Columns
ATTRIBUTE15	NULL	VARCHAR2(150)	Flex field Columns
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
INTERNAL_UPGRADE_CODE_ID	NULL	NUMBER	For internal use only. To keep the new interest code id upon data migration.
ENABLED_FLAG	NULL	VARCHAR2(1)	Master Enabled flag

Indexes

Index Name	Index Type	Sequence	Column Name
AS_INTEREST_CODES_B_N1	NOT UNIQUE	1	PARENT_INTEREST_CODE_ID
AS_INTEREST_CODES_B_N2	NOT UNIQUE	2	INTEREST_TYPE_ID
		6	PARENT_INTEREST_CODE_ID
AS_INTEREST_CODES_B_U1	UNIQUE	2	INTEREST_CODE_ID

Sequences

Sequence	Derived Column
AS_INTEREST_CODES_S	INTEREST_CODE_ID

AS_INTEREST_CODES_MC

This provides the MC support in product family pricing. Users need to set up prices in different currencies for an product family, and store those prices in.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_INTEREST_CODES_B	INTEREST_CODE_ID	INTEREST_CODE_ID

Column Descriptions

Name	Null?	Type	Description
INTEREST_CODE_ID (PK)	NOT NULL	NUMBER	Interest Code Identifier.
CURRENCY_CODE (PK)	NOT NULL	VARCHAR2(15)	Currency.
PRICE	NOT NULL	NUMBER	Price in the currency.
DESCRIPTION	NULL	VARCHAR2(80)	Description.
LAST_UPDATE_DATE	NOT NULL	DATE	WHO columns.
LAST_UPDATED_BY	NOT NULL	NUMBER	WHO columns.
CREATION_DATE	NOT NULL	DATE	WHO columns.
CREATED_BY	NOT NULL	NUMBER	WHO columns.
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	WHO columns.
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_INTEREST_CODES_MC_U1	UNIQUE	5	INTEREST_CODE_ID
		7	CURRENCY_CODE

AS_INTEREST_CODES_TL

This holds the translatable columns in interest codes

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_INTEREST_CODES_B	INTEREST_CODE_ID	INTEREST_CODE_ID

Column Descriptions

Name	Null?	Type	Description
INTEREST_CODE_ID (PK)	NOT NULL	NUMBER	Interest code identifier
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Defined language for the row's translated columns
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language used at the time of insertion
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
CODE	NOT NULL	VARCHAR2(100)	A code to identify an interest item
DESCRIPTION	NULL	VARCHAR2(240)	A full description of the interest code
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_INTEREST_CODES_TL_U1	UNIQUE	2	INTEREST_CODE_ID
		5	LANGUAGE
AS_INTEREST_CODES_TL_U2	UNIQUE	1	CODE
		2	INTEREST_CODE_ID
		5	LANGUAGE

Sequences

Sequence	Derived Column
AS_INTEREST_CODES_S	INTEREST_CODE_ID

AS_INTEREST_TYPES_ALL

This stores the MO flags information of an Interest Types.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_INTEREST_TYPES_B	INTEREST_TYPE_ID	INTEREST_TYPE_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
COMPANY_CLASSIFICATION_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
CONTACT_INTEREST_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
ENABLED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
EXPECTED_PURCHASE_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
LEAD_CLASSIFICATION_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
INTEREST_TYPE_ID (PK)	NOT NULL	NUMBER	Interest type identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who column
INTEREST_TYPE	NULL	VARCHAR2(80)	Obsolete. Moved to _TL table
REVENUE_CLASS_ID	NULL	NUMBER	Obsolete.
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	Interest type enable flag for an organization
COMPANY_CLASSIFICATION_FLAG	NULL	VARCHAR2(1)	Obsolete. Moved to _B table
CONTACT_INTEREST_FLAG	NULL	VARCHAR2(1)	Obsolete. Moved to _B table
LEAD_CLASSIFICATION_FLAG	NULL	VARCHAR2(1)	Obsolete. Moved to _B table
EXPECTED_PURCHASE_FLAG	NULL	VARCHAR2(1)	Obsolete. Moved to _B table
CURRENT_ENVIRONMENT_FLAG	NULL	VARCHAR2(1)	Obsolete. Moved to _B table
DESCRIPTION	NULL	VARCHAR2(240)	Obsolete. Moved to _TL table
ORG_ID (PK)	NOT NULL	NUMBER	Operating unit high performed this transaction
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_INTEREST_TYPES_ALL_N1	NOT UNIQUE	1	COMPANY_CLASSIFICATION_FLAG

Oracle Proprietary, Confidential Information--Use Restricted by Contract

AS_INTEREST_TYPES_ALL_N2	NOT UNIQUE	1	CONTACT_INTEREST_FLAG
AS_INTEREST_TYPES_ALL_N3	NOT UNIQUE	1	LEAD_CLASSIFICATION_FLAG
AS_INTEREST_TYPES_ALL_N4	NOT UNIQUE	1	EXPECTED_PURCHASE_FLAG
AS_INTEREST_TYPES_ALL_U1	UNIQUE	2	INTEREST_TYPE_ID
		3	ORG_ID

Sequences

Sequence	Derived Column
AS_INTEREST_TYPES_S	INTEREST_TYPE_ID

AS_INTEREST_TYPES_B

This table classifies various products customers, contacts or sales opportunities are interested in into different types. This is the base table for Interest types.

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
COMPANY_CLASSIFICATION_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
CONTACT_INTEREST_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
CURRENT_ENVIRONMENT_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
ENABLED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
EXPECTED_PURCHASE_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
LEAD_CLASSIFICATION_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
INTEREST_TYPE_ID (PK)	NOT NULL	NUMBER	Interest type identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
ENABLED_FLAG	NULL	VARCHAR2(1)	Master Enabled Flag
COMPANY_CLASSIFICATION_FLAG	NULL	VARCHAR2(1)	Master Company Classification Flag
CONTACT_INTEREST_FLAG	NULL	VARCHAR2(1)	Master Contact Interest Flag
LEAD_CLASSIFICATION_FLAG	NULL	VARCHAR2(1)	Master Lead Classification Flag
CURRENT_ENVIRONMENT_FLAG	NULL	VARCHAR2(1)	Master Current Environment Flag
EXPECTED_PURCHASE_FLAG	NULL	VARCHAR2(1)	Master Expected Purchase Flag
INTERNAL_UPGRADE_TYPE_ID	NULL	NUMBER	For internal use only. To keep the new interest type id upon data migration.

Indexes

Index Name	Index Type	Sequence	Column Name
AS_INTEREST_TYPES_B_U1	UNIQUE	1	INTEREST_TYPE_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Sequences

Sequence	Derived Column
AS_INTEREST_TYPES_S	INTEREST_TYPE_ID

AS_INTEREST_TYPES_TL

This holds MLS columns of interest types.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_INTEREST_TYPES_B	INTEREST_TYPE_ID	INTEREST_TYPE_ID

Column Descriptions

Name	Null?	Type	Description
INTEREST_TYPE_ID (PK)	NOT NULL	NUMBER	Interest type identifier
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Defined language for the row's translated columns
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language used at the time of insertion
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who column
INTEREST_TYPE	NOT NULL	VARCHAR2(80)	Name of the interest type
DESCRIPTION	NULL	VARCHAR2(240)	Description of interest type
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_INTEREST_TYPES_TL_U1	UNIQUE	2 5	INTEREST_TYPE_ID LANGUAGE
AS_INTEREST_TYPES_TL_U2	UNIQUE	1 2 5	INTEREST_TYPE INTEREST_TYPE_ID LANGUAGE

Sequences

Sequence	Derived Column
AS_INTEREST_TYPES_S	INTEREST_TYPE_ID

AS_INTERNAL_FORECASTS

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_FORECAST_CATEGORIES	FORECAST_CATEGORY_ID	FORECAST_CATEGORY_ID
AS_INTERNAL_FORECASTS	FORECAST_ID	ORIGINAL_FORECAST_ID
GL_PERIODS	PERIOD_NAME	PERIOD_NAME
JTF_RS_GROUPS_B	GROUP_ID	SALES_GROUP_ID
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	SALESFORCE_ID
PER_ALL_PEOPLE_F	PERSON_ID	EMPLOYEE_PERSON_ID

Column Descriptions

Name	Null?	Type	Description
FORECAST_ID (PK)	NOT NULL	NUMBER	Forecast Identifier
FORECAST_CATEGORY_ID	NOT NULL	NUMBER	Foreign Key to AS_FORECAST_CATEGORIES
CREATED_BY	NOT NULL	NUMBER	Standard WHO Column
CREATION_DATE	NOT NULL	DATE	Standard WHO Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard WHO Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard WHO Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard WHO Column
REQUEST_ID	NULL	NUMBER	Request Identifier
PROGRAM_APPLICATION_ID	NULL	NUMBER	Program Application Identifier
PROGRAM_ID	NULL	NUMBER	Program Identifier
PROGRAM_UPDATE_DATE	NULL	DATE	Program Update Date
SUBMISSION_DATE	NULL	DATE	Forecast Submission Date
PERIOD_NAME	NOT NULL	VARCHAR2(15)	Period Name (e.g. Q4-00, MAR-00, ...)
SALESFORCE_ID	NULL	NUMBER	Salesforce Identifier
EMPLOYEE_PERSON_ID	NULL	NUMBER	Employee Person Identifier from HR
SALES_GROUP_ID	NULL	NUMBER	Sales Group Identifier
PARTNER_ADDRESS_ID	NULL	NUMBER	Partner Address Identifier
PARTNER_CUSTOMER_ID	NULL	NUMBER	Partner Customer Identifier
CURRENCY_CODE	NOT NULL	VARCHAR2(15)	Forecast Currency Code (e.g. USD, CAD .etc)
CREDIT_TYPE_ID	NULL	NUMBER	Credit Type Identifier .Used to verify the type of credit amount used for forecast
REVENUE_FLAG	NULL	VARCHAR2(1)	Obsolete
WORKSHEET_TYPE	NULL	VARCHAR2(30)	Obsolete
ACTIVE_FLAG	NULL	VARCHAR2(1)	Obsolete
WORST_FORECAST_AMOUNT_FLAG	NULL	VARCHAR2(1)	Flag to indicate the currency conversion rate was not found while rolling up the worst forecast amount)
WORST_FORECAST_AMOUNT	NULL	NUMBER	Worst Forecast Amount
FORECAST_AMOUNT_FLAG	NULL	VARCHAR2(1)	Flag to indicate the currency conversion rate was not found while rolling up the forecast amount)
FORECAST_AMOUNT	NULL	NUMBER	Forecast Amount
BEST_FORECAST_AMOUNT_FLAG	NULL	VARCHAR2(1)	Flag to indicate the currency conversion rate was not found while rolling up the best forecast amount)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

BEST_FORECAST_AMOUNT	NULL	NUMBER	best forecast amount
WEIGHTED_PIPELINE_AMOUNT_FLAG	NULL	VARCHAR2(1)	Flag to indicate the currency conversion rate was not found while rolling up the weighted pipeline amount)
WEIGHTED_PIPELINE_AMOUNT	NULL	NUMBER	The weighted Pipeline Amount
PIPELINE_AMOUNT_FLAG	NULL	VARCHAR2(1)	Flag to indicate the currency conversion rate was not found while rolling up the pipeline amount)
PIPELINE_AMOUNT	NULL	NUMBER	Pipeline Amount .This represents total amount which can be forecasted within a given period for a sales rep or Sales Group
WON_PIPELINE_AMOUNT_FLAG	NULL	VARCHAR2(1)	Flag to indicate the currency conversion rate was not found while rolling up the won pipeline amount)
WON_PIPELINE_AMOUNT	NULL	NUMBER	Amount Won till date
QUOTA_AMOUNT_FLAG	NULL	VARCHAR2(1)	Obsolete
QUOTA_AMOUNT	NULL	NUMBER	Obsolete
ORIGINAL_FORECAST_ID	NULL	NUMBER	Id of Original forecast record
STATUS_CODE	NOT NULL	VARCHAR2(30)	Status of forecast (SUBMITTED or SAVED)
START_DATE_ACTIVE	NULL	DATE	Effective Start Date of forecast
END_DATE_ACTIVE	NULL	DATE	End Date for the forecast .You can not make any changes once end date is stored in this column.
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_INTERNAL_FORECASTS_U1	NOT UNIQUE	5	FORECAST_ID

Sequences

Sequence	Derived Column
AS_INTERNAL_FORECASTS_S	FORECAST_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

AS_LEADS_ALL

AS_LEADS_ALL stores information about unqualified leads and qualified sales opportunities being worked on by your salesforce. Each row can include values that describe your actual revenue and timeframe expectations for the deal. Each row can also include values to indicate how far into the sales cycle the lead has progressed, and the likelihood that the lead will be won. Additionally, closing information about the opportunity can be stored for reporting and analysis purposes.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AMS_SOURCE_CODES	SOURCE_CODE_ID	SOURCE_PROMOTION_ID
AS_FORECAST_PROB_ALL_B	PROBABILITY_VALUE	WIN_PROBABILITY
AS_PRICE_LISTS	PRICE_LIST_ID	PRICE_LIST_ID
AS_SALES_STAGES_ALL_B	SALES_STAGE_ID	SALES_STAGE_ID
AS_STATUSES_B	STATUS_CODE	STATUS
HZ_PARTIES	PARTY_ID	CUSTOMER_ID
HZ_PARTIES	PARTY_ID	CLOSE_COMPETITOR_ID
HZ_PARTIES	PARTY_ID	END_USER_CUSTOMER_ID
HZ_PARTY_SITES	PARTY_SITE_ID	END_USER_ADDRESS_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
CLOSE_REASON	CLOSE_REASON	AS_LOOKUPS
	B	No Budget Available
	C	Competitor Deal Chosen
DELETED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
DELETE_ALLOWED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
END_USER_CUSTOMER_NAME	COMPETITOR	AS_LOOKUPS
NO_OPP_ALLOWED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
RANK	RANK	AS_LOOKUPS
	1	Very Low
	2	Low
	3	Moderate
	4	High
	5	Very High
STATUS	LEAD_STATUS	AS_LOOKUPS
	C	Closed
	O	Open

Column Descriptions

Name	Null?	Type	Description
LEAD_ID (PK)	NOT NULL	NUMBER	Lead identifier

Oracle Proprietary, Confidential Information--Use Restricted by Contract

REQUEST_ID	NULL	NUMBER	Standard who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
LEAD_NUMBER	NOT NULL	VARCHAR2(30)	Unique number for lead, system generated by sequence as_lead_number_s
STATUS	NOT NULL	VARCHAR2(30)	The status of this lead validated against as_statuses_vl
CUSTOMER_ID	NOT NULL	NUMBER	Customer identifier
ADDRESS_ID	NULL	NUMBER	Address identifier
LEAD_SOURCE_CODE	NULL	VARCHAR2(30)	Originating source code of lead/opportunity
ORIG_SYSTEM_REFERENCE	NULL	VARCHAR2(240)	Unique lead identifier from foreign system
SALES_STAGE_ID	NULL	NUMBER	Sales stage identifier of this lead
INITIATING_CONTACT_ID	NULL	NUMBER	for future use
CHANNEL_CODE	NULL	VARCHAR2(30)	Sales channel for this lead, validated against 'LEAD_CHANNEL' from order capture
TOTAL_AMOUNT	NULL	NUMBER	The likely amount of sale from this lead, summed from total amounts at the lead line level
CURRENCY_CODE	NULL	VARCHAR2(15)	The currency code used for this lead, validated against fnd_currencies_vl
DECISION_DATE	NULL	DATE	The date the purchase decision will be made by the prospect
WIN_PROBABILITY	NULL	NUMBER	The percentage or probability that this lead will result in a sale. The higher the percentage the higher the chance of making a sale.
CLOSE_REASON	NULL	VARCHAR2(30)	A reason for closing a lead, validated against 'CLOSE_REASON' from as_lookups
CLOSE_COMPETITOR_CODE	NULL	VARCHAR2(30)	Obsolete
CLOSE_COMPETITOR_ID	NULL	NUMBER	Customer identifier that is marked as a competitor
CLOSE_COMPETITOR	NULL	VARCHAR2(255)	obsolete
CLOSE_COMMENT	NULL	VARCHAR2(240)	Additional comment about the closing of this lead
RANK	NULL	VARCHAR2(30)	The rank of the lead -for future use
DESCRIPTION	NULL	VARCHAR2(240)	Opportunity name of the lead, usually the main interest for the lead
END_USER_CUSTOMER_NAME	NULL	VARCHAR2(255)	Name of the end user who purchase the product from this lead if the lead was worked through a VAR

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SOURCE_PROMOTION_ID	NULL	NUMBER	Promotion identifier that initiated the creation of the lead
END_USER_CUSTOMER_ID	NULL	NUMBER	End User Customer identifier if lead was worked through a VAR
END_USER_ADDRESS_ID	NULL	NUMBER	End user address identifier if the lead was worked through a VAR
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
NO_OPP_ALLOWED_FLAG	NULL	VARCHAR2(1)	Flag to determine whether this lead can still be set to a status of NO OPPORTUNITY based on profile OSM: No Opportunity Ceiling
DELETE_ALLOWED_FLAG	NULL	VARCHAR2(1)	Flag to determine if this lead can still be deleted based on profile OSM: Opportunity Delete Ceiling
PARENT_PROJECT	NULL	VARCHAR2(80)	Project to which this lead belongs
PRICE_LIST_ID	NULL	NUMBER	Price list for revenue-volume correspondence
DELETED_FLAG	NULL	VARCHAR2(1)	Flag to indicate if this lead is soft deleted
AUTO_ASSIGNMENT_TYPE	NULL	VARCHAR2(30)	Automatic assignment type
PRM_ASSIGNMENT_TYPE	NULL	VARCHAR2(30)	PRM assignment type
CUSTOMER_BUDGET	NULL	NUMBER	Customer budget for this lead
METHODOLOGY_CODE	NULL	VARCHAR2(30)	Methodology code validated against 'METHODOLOGY_TYPE' from fnd_lookups
ORIGINAL_LEAD_ID	NULL	NUMBER	Lead identifier which the current lead was copied from
DECISION_TIMEFRAME_CODE	NULL	VARCHAR2(30)	specify the time by when decision will be made, lookup_type DECISION_TIMEFRAME
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
INCUMBENT_PARTNER_RESOURCE_ID	NULL	NUMBER	Incumbent partner resource identifier, used for PRM
INCUMBENT_PARTNER_PARTY_ID	NULL	NUMBER	Incumbent partner identifier, used for PRM
OFFER_ID	NULL	NUMBER	Promotion offer identifier from Marketing
VEHICLE_RESPONSE_CODE	NULL	VARCHAR2(30)	Indicates how the lead was created
BUDGET_STATUS_CODE	NULL	VARCHAR2(30)	PRM use
FOLLOWUP_DATE	NULL	DATE	PRM use
PRM_EXEC_SPONSOR_FLAG	NULL	VARCHAR2(1)	PRM use
PRM_PRJ_LEAD_IN_PLACE_FLAG	NULL	VARCHAR2(1)	PRM use
PRM_IND_CLASSIFICATION_CODE	NULL	VARCHAR2(30)	industry classification code for prm. lookup_type - prm_industry_classification_type
PRM_LEAD_TYPE	NULL	VARCHAR2(30)	For prm use to identify the lead_type. Valid values are DIRECT and INDIRECT based on lookup type PRM_LEAD_TYPE

Indexes

Index Name	Index Type	Sequence	Column Name
AS_LEADS_N1	NOT UNIQUE	1	CUSTOMER_ID
		2	ADDRESS_ID
AS_LEADS_N2	NOT UNIQUE	1	SALES_STAGE_ID
AS_LEADS_N3	NOT UNIQUE	5	LAST_UPDATE_DATE
AS_LEADS_N4	NOT UNIQUE	5	SOURCE_PROMOTION_ID
AS_LEADS_N5	NOT UNIQUE	5	STATUS
AS_LEADS_N6	NOT UNIQUE	5	WIN_PROBABILITY
AS_LEADS_U1	UNIQUE	1	LEAD_ID

Sequences

Sequence	Derived Column
AS_LEADS_S	LEAD_ID
AS_LEAD_NUMBER_S	LEAD_NUMBER

Database Triggers

Trigger Name : AS_LEADS_BIUD
 Trigger Time : BEFORE
 Trigger Level : ROW
 Trigger Event : INSERT, UPDATE, DELETE

This trigger handles two parts. The first one is for Territory Assignment Program. It inserts/changes changed accounts/leads caused by changed leads into AS_CHANGED_ACCOUNTS_ALL table by calling AS_ASTATA_DBASE_TRIGGERS package. The second part is for Opportunity Adjustment. It changes/inserts original leads into AS_LEAD_ADJS table by calling AS_LEAD_ADJS_TRIGGERS_PKG package.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

AS_LEADS_LOG

AS_LEAD_LOG stores opportunity change history

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_LEADS_ALL	LEAD_ID	LEAD_ID

Column Descriptions

Name	Null?	Type	Description
LOG_ID	NOT NULL	NUMBER	Lead Log Identifier
LEAD_ID	NOT NULL	NUMBER	Lead Identifier
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
CREATION_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who Column
STATUS_CODE	NULL	VARCHAR2(30)	The status of the lead validated against as_statuses_vl
SALES_STAGE_ID	NOT NULL	NUMBER	Sales stage identifier of the lead
WIN_PROBABILITY	NULL	NUMBER	Probability that this lead will be won. The higher the percentage the higher the chance of making the sale.
DECISION_DATE	NULL	DATE	The date that the purchase decision will be made by the prospect
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_LEAD_LOG_N1	NOT UNIQUE	5	LEAD_ID
AS_LEAD_LOG_U1	UNIQUE	5	LOG_ID

Sequences

Sequence	Derived Column
AS_LEAD_LOG_S	LOG_ID

AS_LEAD_LINES_ALL

AS_LEAD_LINES_ALL stores information about the individual items associated with an opportunity.

Each lead item can have it's own status, close probability, expected close date, etc., which are independent of the same columns on it's associated lead. So although the close probability for the whole lead may be moderate, that of an individual item for the lead may be high.

When a new row is added to AS_LEAD_LINES_ALL, the expected revenue amount for its associated lead is updated to include the expected revenue amount of this new item. All other columns such as close probability, expected close date etc., on the associated lead are not automatically affected when new items are created for it. Changes to these columns must be made manually by you.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AMS_ACT_OFFERS	ACTIVITY_OFFER_ID	OFFER_ID
AMS_SOURCE_CODES	SOURCE_CODE_ID	SOURCE_PROMOTION_ID
AS_INTEREST_CODES_B	INTEREST_CODE_ID	PRIMARY_INTEREST_CODE_ID
AS_INTEREST_CODES_B	INTEREST_CODE_ID	SECONDARY_INTEREST_CODE_ID
AS_INTEREST_TYPES_B	INTEREST_TYPE_ID	INTEREST_TYPE_ID
AS_LEADS_ALL	LEAD_ID	LEAD_ID
MTL_SYSTEM_ITEMS_B	INVENTORY_ITEM_ID	INVENTORY_ITEM_ID
	ORGANIZATION_ID	ORGANIZATION_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
INTEREST_STATUS_CODE	INTEREST_STATUS	AS_LOOKUPS
QUOTED_LINE_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
STATUS_CODE	LEAD_STATUS	AS_LOOKUPS
	C	Closed
	O	Open

Column Descriptions

Name	Null?	Type	Description
LEAD_LINE_ID (PK)	NOT NULL	NUMBER	Lead item identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record

Oracle Proprietary, Confidential Information--Use Restricted by Contract

PROGRAM_ID		NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE		NULL	DATE	Last date concurrent program updated record
LEAD_ID	NOT	NULL	NUMBER	Lead identifier
STATUS_CODE		NULL	VARCHAR2(30)	Obsolete
INTEREST_TYPE_ID		NULL	NUMBER	The interest type identifier for the lead
PRIMARY_INTEREST_CODE_ID		NULL	NUMBER	Primary interest code identifier for the lead
SECONDARY_INTEREST_CODE_ID		NULL	NUMBER	Secondary interest code identifier
INTEREST_STATUS_CODE		NULL	VARCHAR2(30)	Obsolete
INVENTORY_ITEM_ID		NULL	NUMBER	Referenced inventory item identifier
ORGANIZATION_ID		NULL	NUMBER	Reference inventory organization identifier
UOM_CODE		NULL	VARCHAR2(3)	Unit of measure code from mtl_unit_of_measures, valid UOM for inventory_item_id if one exists
QUANTITY		NULL	NUMBER	The quantity of this lead item that is expected to be sold
TOTAL_AMOUNT		NULL	NUMBER	The amount of sale likely to result from this lead item
SALES_STAGE_ID		NULL	NUMBER	Obsolete
SHIP_DATE		NULL	DATE	The date that the purchase decision will be made by the prospect
WIN_PROBABILITY		NULL	NUMBER	Obsolete
DECISION_DATE		NULL	DATE	Obsolete
CHANNEL_CODE		NULL	VARCHAR2(30)	Obsolete
QUOTED_LINE_FLAG		NULL	VARCHAR2(1)	Flag to signify if a quote has been created for the line.
ORIGINAL_LEAD_LINE_ID		NULL	NUMBER	The lead line identifier from which the current lead line was copied from
ORG_ID		NULL	NUMBER	Operating unit which performed this transaction
PRICE		NULL	NUMBER	Price for revenue-volume correspondence
SOURCE_PROMOTION_ID		NULL	NUMBER	The promotion identifier from which the opportunity was created
PRICE_VOLUME_MARGIN		NULL	NUMBER	Revenue Volume correspondence difference tolerance margin
ATTRIBUTE_CATEGORY		NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1		NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2		NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE3		NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE4		NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5		NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6		NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE7		NULL	VARCHAR2(150)	Descriptive flexfield segment column

ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
OFFER_ID	NULL	NUMBER	Promotion offer identifier from Marketing

Indexes

Index Name	Index Type	Sequence	Column Name
AS_LEAD_LINES_N1	NOT UNIQUE	2	LEAD_ID
AS_LEAD_LINES_N2	NOT UNIQUE	2	SECONDARY_INTEREST_CODE_ID
		3	PRIMARY_INTEREST_CODE_ID
		5	INTEREST_TYPE_ID
AS_LEAD_LINES_N3	NOT UNIQUE	2	ORGANIZATION_ID
		4	INVENTORY_ITEM_ID
AS_LEAD_LINES_N4	NOT UNIQUE	5	LAST_UPDATE_DATE
AS_LEAD_LINES_U1	UNIQUE	1	LEAD_LINE_ID

Sequences

Sequence	Derived Column
AS_LEAD_LINES_S	LEAD_LINE_ID

Database Triggers

Trigger Name : AS_LEAD_LINE_BIUD
 Trigger Time : BEFORE
 Trigger Level : ROW
 Trigger Event : INSERT, UPDATE, DELETE

This trigger handles two parts. The first one is for Territory Assignment Program. It inserts/changes changed accounts/leads caused by changed leads into AS_CHANGED_ACCOUNTS_ALL table by calling AS_ASTATA_DBASE_TRIGGERS package. The second part is for Opportunity Adjustment. It changes/inserts original leads into AS_LEAD_LINE_ADJS table by calling AS_LEAD_ADJS_TRIGGERS_PKG package.

AS_LEAD_ORDERS

AS_LEAD_ORDERS is a join table between as_leads and so_headers. It contains a link to determine what orders in Oracle Order Entry resulted from the lead/opportunity in Oracle Sales and Marketing.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_LEADS_ALL	LEAD_ID	LEAD_ID

Column Descriptions

Name	Null?	Type	Description
LEAD_ORDER_ID (PK)	NOT NULL	NUMBER	Lead order identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
LEAD_ID	NOT NULL	NUMBER	Lead identifier
ORDER_HEADER_ID	NOT NULL	NUMBER	Order header identifier, from oe_order_headers
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column

ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_LEAD_ORDERS_N1	NOT UNIQUE	1	ORDER_HEADER_ID
AS_LEAD_ORDERS_U1	UNIQUE	1	LEAD_ORDER_ID
AS_LEAD_ORDERS_U2	UNIQUE	1	LEAD_ID
		2	ORDER_HEADER_ID

Sequences

Sequence	Derived Column
AS_LEAD_ORDERS_S	LEAD_ORDER_ID

AS_SALES_CREDITS

AS_SALES_CREDITS stores the sales credit information for AS_LEAD_LINES_ALL. The sales credits can be revenue credits, quota (non-revenue) credits or both.

For a single lead line, the revenue credits must sum to the total amount of that lead line. In addition, only one of the two fields, amount or percent, can be entered for either revenue or quota credits. The other field is derived at runtime based on the total amount of the lead line.

A sales credit record can be associated with either a salesforce partner or a salesforce employee. Either the person_id column or the partner columns (partner_customer_id and partner_address_id) will be populated, but not both.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_LEADS_ALL	LEAD_ID	LEAD_ID
AS_LEAD_LINES_ALL	LEAD_LINE_ID	LEAD_LINE_ID
HZ_PARTIES	PARTY_ID	PARTNER_CUSTOMER_ID
HZ_PARTY_SITES	PARTY_SITE_ID	PARTNER_ADDRESS_ID
JTF_RS_GROUPS_B	GROUP_ID	SALESGROUP_ID
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	SALESFORCE_ID
PER_ALL_PEOPLE_F	PERSON_ID	PERSON_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
CREDIT_TYPE_ID	INTERACTION_TYPE	AS_LOOKUPS
	CS	Call Script
	M	Mailing
	T	Telephone Call
	V	Personal Visit

Column Descriptions

Name	Null?	Type	Description
SALES_CREDIT_ID (PK)	NOT NULL	NUMBER	Sales credit identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
LEAD_ID	NOT NULL	NUMBER	Lead identifier

Oracle Proprietary, Confidential Information--Use Restricted by Contract

LEAD_LINE_ID	NOT NULL	NUMBER	Lead line identifier
SALESFORCE_ID	NOT NULL	NUMBER	Salesforce member identifier who has credit on this purchase item
PERSON_ID	NULL	NUMBER(9)	Employee identifier of this salesforce
SALESGROUP_ID	NULL	NUMBER	Sales group identifier which the sales rep belongs to
PARTNER_CUSTOMER_ID	NULL	NUMBER	Customer identifier for a partner
PARTNER_ADDRESS_ID	NULL	NUMBER	Account Identifier of a partner
REVENUE_AMOUNT	NULL	NUMBER	Obsolete Sales credit revenue credit amount
REVENUE_PERCENT	NULL	NUMBER	Obsolete Sales credit revenue credit percentage (0 - 100)
CREDIT_TYPE_ID	NULL	NUMBER	Type identifier of the sales credit
QUOTA_CREDIT_AMOUNT	NULL	NUMBER	Obsolete Sales credit quota credit amount
QUOTA_CREDIT_PERCENT	NULL	NUMBER	Obsolete Sales credit quota credit percentage (0-100)
MANAGER_REVIEW_FLAG	NULL	VARCHAR2(1)	Obsolete
MANAGER_REVIEW_DATE	NULL	DATE	Obsolete
ORIGINAL_SALES_CREDIT_ID	NULL	NUMBER	Obsolete column
CREDIT_PERCENT	NULL	NUMBER	Credit percentage (0 - 100) with the credit type defined by column CREDIT_TYPE
CREDIT_AMOUNT	NULL	NUMBER	Credit amount with the credit type defined by the column CREDIT_TYPE
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SECURITY_GROUP_ID

NULL NUMBER

Subscriber id, for CRM Online
Services use*Indexes*

Index Name	Index Type	Sequence	Column Name
AS_SALES_CREDITS_N1	NOT UNIQUE	1	LEAD_ID
		2	LEAD_LINE_ID
AS_SALES_CREDITS_N2	NOT UNIQUE	1	PERSON_ID
AS_SALES_CREDITS_N3	NOT UNIQUE	1	SALESFORCE_ID
AS_SALES_CREDITS_N4	NOT UNIQUE	1	SALESGROUP_ID
AS_SALES_CREDITS_N5	NOT UNIQUE	1	PARTNER_ADDRESS_ID
AS_SALES_CREDITS_U1	UNIQUE	1	SALES_CREDIT_ID

Sequences

Sequence	Derived Column
AS_SALES_CREDITS_S	SALES_CREDIT_ID

Database Triggers

Trigger Name : AS_SALES_CREDITS_BD
Trigger Time : BEFORE
Trigger Level : ROW
Trigger Event : INSERT, UPDATE, DELETE

The trigger inserts/changes original sales credits into AS_SALES_CREDIT_ADJS table by calling AS_LEAD_ADJS_TRIGGERS_PKG.

AS_SALES_CREDITS_DENORM

Denormalized table to store opportunity data denormalized from AS_LEADS_ALL, AS_LEAD_LINES_ALL, AS_SALES_CREDITS, AS_SALES_STAGE_ALL, AS_INTEREST_TYPES_ALL, AS_INTEREST_CODES_ALL, HZ_PARTIES, AS_SALES_GROUPS, PER_ALL_PEOPLR_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_FORECAST_PROB_ALL_B	PROBABILITY_VALUE	WIN_PROBABILITY
AS_INTEREST_CODES_B	INTEREST_CODE_ID	PRIMARY_INTEREST_CODE_ID
AS_INTEREST_CODES_B	INTEREST_CODE_ID	SECONDARY_INTEREST_CODE_ID
AS_INTEREST_TYPES_B	INTEREST_TYPE_ID	INTEREST_TYPE_ID
AS_LEADS_ALL	LEAD_ID	LEAD_ID
AS_LEAD_LINES_ALL	LEAD_LINE_ID	LEAD_LINE_ID
AS_SALES_CREDITS	SALES_CREDIT_ID	SALES_CREDIT_ID
AS_SALES_STAGES_ALL_B	SALES_STAGE_ID	SALES_STAGE_ID
AS_STATUSES_B	STATUS_CODE	STATUS_CODE
HZ_PARTIES	PARTY_ID	CUSTOMER_ID
HZ_PARTY_SITES	PARTY_SITE_ID	ADDRESS_ID
JTF_RS_GROUPS_B	GROUP_ID	SALES_GROUP_ID
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	SALESFORCE_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
OPP_DELETED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
OPP_OPEN_STATUS_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
SALES_CREDIT_ID (PK)	NOT NULL	NUMBER	Sales credit identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column.
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column.
CREATION_DATE	NOT NULL	DATE	Standard who column.
CREATED_BY	NOT NULL	NUMBER	Standard who column.
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column.
SALES_GROUP_ID	NULL	NUMBER	Sales group identifier
SALES_GROUP_NAME	NULL	VARCHAR2(30)	Name of the sales group
SALESFORCE_ID	NOT NULL	NUMBER	Salesforce identifier
EMPLOYEE_PERSON_ID	NULL	NUMBER(9)	Employee identifier
SALES_REP_NAME	NULL	VARCHAR2(240)	Name of sales representative
CUSTOMER_ID	NOT NULL	NUMBER	Customer identifier
CUSTOMER_NAME	NULL	VARCHAR2(50)	Customer name
CUSTOMER_CATEGORY	NULL	VARCHAR2(80)	User-defined customer category
CUSTOMER_CATEGORY_CODE	NULL	VARCHAR2(30)	Code of customer category
ADDRESS_ID	NULL	NUMBER	Address identifier
LEAD_ID	NOT NULL	NUMBER	Lead identifier

Oracle Proprietary, Confidential Information--Use Restricted by Contract

LEAD_NUMBER	NOT NULL	VARCHAR2(30)	Lead number
OPP_DESCRIPTION	NULL	VARCHAR2(240)	A description of the opportunity
DECISION_DATE	NULL	DATE	The date the purchase will be made by the prospect
SALES_STAGE_ID	NOT NULL	NUMBER	Sales stage identifier
SALES_STAGE	NULL	VARCHAR2(60)	Sales stage name
WIN_PROBABILITY	NULL	NUMBER	The percentage or the probability that this opportunity will result in a sale
STATUS_CODE	NOT NULL	VARCHAR2(30)	Code of the status of this opportunity
STATUS	NULL	VARCHAR2(80)	The status of this opportunity
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
CHANNEL_CODE	NULL	VARCHAR2(30)	Sales channel for this opportunity
LEAD_SOURCE_CODE	NULL	VARCHAR2(30)	Original source of opportunity
ORIG_SYSTEM_REFERENCE	NULL	VARCHAR2(240)	Unique opportunity identifier from foreign system
LEAD_LINE_ID	NOT NULL	NUMBER	Opportunity item identifier
INTEREST_TYPE_ID	NULL	NUMBER	The interest type identifier for the opportunity
PRIMARY_INTEREST_CODE_ID	NULL	NUMBER	Primary interest code identifier
SECONDARY_INTEREST_CODE_ID	NULL	NUMBER	Secondary interest code identifier
CURRENCY_CODE	NULL	VARCHAR2(15)	The currency code used for this opportunity
TOTAL_AMOUNT	NULL	NUMBER	The amount of the sale likely to result from this lead item
SALES_CREDIT_AMOUNT	NULL	NUMBER	Sales credit amount
WON_AMOUNT	NULL	NUMBER	Won amount
WEIGHTED_AMOUNT	NULL	NUMBER	Weighted amount
C1_CURRENCY_CODE	NULL	VARCHAR2(15)	User's currecnry code
C1_TOTAL_AMOUNT	NULL	NUMBER	Total amount in USD
C1_SALES_CREDIT_AMOUNT	NULL	NUMBER	Sales credit amount in USD
C1_WON_AMOUNT	NULL	NUMBER	Won amount in USD
C1_WEIGHTED_AMOUNT	NULL	NUMBER	Weighted amount in USD
LAST_NAME	NULL	VARCHAR2(40)	Sales rep's last name
FIRST_NAME	NULL	VARCHAR2(20)	Sales rep's first name
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
INTEREST_TYPE	NULL	VARCHAR2(80)	Interest type
PRIMARY_INTEREST_CODE	NULL	VARCHAR2(100)	Primary Interest Code
SECONDARY_INTEREST_CODE	NULL	VARCHAR2(100)	Secondary Interest Code
OPPORTUNITY_LAST_UPDATE_DATE	NOT NULL	DATE	Last date the opportunity was updated
OPPORTUNITY_LAST_UPDATED_BY	NOT NULL	NUMBER	The user identifier that the opportunity was last updated by
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CONVERSION_STATUS_FLAG	NULL	NUMBER	Flag to indicate the currency conversion status
CREDIT_TYPE_ID	NULL	NUMBER	from as_sales_credits
QUANTITY	NULL	NUMBER	from as_lead_lines_all
UOM_CODE	NULL	VARCHAR2(3)	from as_lead_lines_all
UOM_DESCRIPTION	NULL	VARCHAR2(25)	description for UOM_CODE
FORECAST_ROLLUP_FLAG	NULL	VARCHAR2(1)	from as_statuses_b
WIN_LOSS_INDICATOR	NULL	VARCHAR2(1)	from as_statuses_b
ITEM_ID	NULL	NUMBER	from as_lead_lines_all
ORGANIZATION_ID	NULL	NUMBER	from as_lead_lines_all
ITEM_DESCRIPTION	NULL	VARCHAR2(240)	description for item_id
EMPLOYEE_NUMBER	NULL	VARCHAR2(30)	Employee Number from per_people_all
OPP_OPEN_STATUS_FLAG	NULL	VARCHAR2(1)	from as_statuses_b
OPP_DELETED_FLAG	NULL	VARCHAR2(1)	soft delete flag from as_leads_all
PARTY_TYPE	NULL	VARCHAR2(30)	party_type from hz_parties table

Indexes

Index Name	Index Type	Sequence	Column Name
AS_SALES_CREDITS_DENORM_N1	NOT UNIQUE	5	EMPLOYEE_PERSON_ID
AS_SALES_CREDITS_DENORM_N2	NOT UNIQUE	2	DECISION_DATE
AS_SALES_CREDITS_DENORM_N3	NOT UNIQUE	5	SALES_GROUP_ID
		10	STATUS_CODE
		15	PRIMARY_INTEREST_CODE_ID
		20	SECONDARY_INTEREST_CODE_ID
AS_SALES_CREDITS_DENORM_N4	NOT UNIQUE	5	SALES_GROUP_ID
		10	INTEREST_TYPE_ID
AS_SALES_CREDITS_DENORM_N5	NOT UNIQUE	5	LEAD_ID
AS_SALES_CREDITS_DENORM_U1	UNIQUE	5	SALES_CREDIT_ID

AS_SALES_LEADS

AS_SALES_LEADS stores information about leads. Each row can include values that describe your budget_status, timeframe, contact, contact's role etc. These parameters are used to qualify it and route the lead to the corresponding sales person.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AMS_ACT_OFFERS	ACTIVITY_OFFER_ID	OFFER_ID
AS_SALES_LEAD_RANKS_B	RANK_ID	LEAD_RANK_ID
AS_SALES_LEAD_SCORECARDS	SCORECARD_ID	SCORECARD_ID
AS_STATUSES_B	STATUS_CODE	STATUS_CODE
HZ_PARTIES	PARTY_ID	CUSTOMER_ID
JTF_RS_GROUPS_B	GROUP_ID	ASSIGN_SALES_GROUP_ID
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	ASSIGN_TO_PERSON_ID

Column Descriptions

Name	Null?	Type	Description
SALES_LEAD_ID (PK)	NOT NULL	NUMBER	Sales Lead Identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who column
REQUEST_ID	NULL	NUMBER	Standard Who column
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
LEAD_NUMBER	NOT NULL	VARCHAR2(30)	Unique number for Sales Leads.
STATUS_CODE	NOT NULL	VARCHAR2(30)	The status of this lead validated against as_statuses_vl
CUSTOMER_ID	NOT NULL	NUMBER	Customer identifier
ADDRESS_ID	NULL	NUMBER	Address identifier
SOURCE_PROMOTION_ID	NOT NULL	NUMBER	Promotion identifier that initiated the creation of the lead
INITIATING_CONTACT_ID	NULL	NUMBER	For future use, store primary contact id
ORIG_SYSTEM_REFERENCE	NULL	VARCHAR2(240)	Identifies the source of sales lead - MKT,ISTORE
CONTACT_ROLE_CODE	NULL	VARCHAR2(30)	Obsolete in 11i
CHANNEL_CODE	NULL	VARCHAR2(30)	Sales channel for this lead, validated against 'SALES_LEAD_CHANNEL' from order capture
BUDGET_AMOUNT	NULL	NUMBER	Estimated budget amount
CURRENCY_CODE	NULL	VARCHAR2(15)	The currency code used for this lead, validated against fnd_currencies_vl
DECISION_TIMEFRAME_CODE	NULL	VARCHAR2(30)	Specifies the time by when decision will be made

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CLOSE_REASON	NULL VARCHAR2(30)	A reason for closing a lead, validated against 'CLOSE_REASON' from as_lookups
LEAD_RANK_ID	NULL NUMBER	FK to AS_SALES_LEAD_RANKS_B
LEAD_RANK_CODE	NULL VARCHAR2(30)	Obsolete in lli -- use lead_rank_id instead
PARENT_PROJECT	NULL VARCHAR2(80)	Parent project of this sales lead
DESCRIPTION	NULL VARCHAR2(2000)	Description of sales lead
ATTRIBUTE_CATEGORY	NULL VARCHAR2(30)	Descriptive Flexfield structure defining column
ATTRIBUTE1	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE2	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE3	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE4	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE5	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE6	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE7	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE8	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE9	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE10	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE11	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE12	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE13	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE14	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE15	NULL VARCHAR2(150)	Descriptive Flexfield segment column
ASSIGN_TO_PERSON_ID	NULL NUMBER	The RESOURCE_ID to whom the lead is assigned to
ASSIGN_SALES_GROUP_ID	NULL NUMBER	The sales group id for assign_to_person
ASSIGN_DATE	NULL DATE	Assign Date
BUDGET_STATUS_CODE	NULL VARCHAR2(30)	Budget status , validated values are APPROVED, NOT APPROVED and PENDING
ACCEPT_FLAG	NULL VARCHAR2(1)	Indicates the Lead is accepted
VEHICLE_RESPONSE_CODE	NULL VARCHAR2(30)	Indicates how the lead was created
TOTAL_SCORE	NULL NUMBER	Total score of this sales lead
SCORECARD_ID	NULL NUMBER	Indicates the score card used by the lead to rank it
KEEP_FLAG	NULL VARCHAR2(1)	To indicate user would like to keep the lead
URGENT_FLAG	NULL VARCHAR2(1)	To signify this is an urgent lead
IMPORT_FLAG	NULL VARCHAR2(1)	Indicates the deal is imported
REJECT_REASON_CODE	NULL VARCHAR2(30)	reject_reason_code
DELETED_FLAG	NULL VARCHAR2(1)	To indicate this sales lead has been soft deleted.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

OFFER_ID	NULL	NUMBER	Promotions offer
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
INCUMBENT_PARTNER_PARTY_ID	NULL	NUMBER	Incumbent partner identifier, used for PRM
INCUMBENT_PARTNER_RESOURCE_ID	NULL	NUMBER	Incumbent partner resource identifier, used for PRM
PRM_EXEC_SPONSOR_FLAG	NULL	VARCHAR2(1)	PRM use
PRM_PRJ_LEAD_IN_PLACE_FLAG	NULL	VARCHAR2(1)	PRM use
PRM_SALES_LEAD_TYPE	NULL	VARCHAR2(30)	For prm use to identify the sales_lead_type. Valid values are DIRECT and INDIRECT based on lookup type PRM_LEAD_TYPE
PRM_IND_CLASSIFICATION_CODE	NULL	VARCHAR2(30)	industry classification code for prm. lookup_type - prm_industry_classification_type

Indexes

Index Name	Index Type	Sequence	Column Name
AS_SALES_LEADS_N1	NOT UNIQUE	5	ASSIGN_TO_PERSON_ID
AS_SALES_LEADS_N2	NOT UNIQUE	5 10	CUSTOMER_ID ADDRESS_ID
AS_SALES_LEADS_N3	NOT UNIQUE	2	ASSIGN_SALES_GROUP_ID
AS_SALES_LEADS_N4	NOT UNIQUE	5	SOURCE_PROMOTION_ID
AS_SALES_LEADS_N5	NOT UNIQUE	5	CHANNEL_CODE
AS_SALES_LEADS_N6	NOT UNIQUE	2	OFFER_ID
AS_SALES_LEADS_N7	NOT UNIQUE	5	LAST_UPDATE_DATE
AS_SALES_LEADS_U1	UNIQUE	5	SALES_LEAD_ID

Sequences

Sequence	Derived Column
AS_SALES_LEADS_S	SALES_LEAD_ID
AS_SALES_LEADS_LEADNUMBER_S	LEAD_NUMBER

AS_SALES_LEADS_LOG

AS_LEAD_LOG stores opportunity change history

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_SALES_LEADS	SALES_LEAD_ID	SALES_LEAD_ID

Column Descriptions

Name	Null?	Type	Description
LOG_ID (PK)	NOT NULL	NUMBER	Lead Log Identifier
SALES_LEAD_ID	NOT NULL	NUMBER	Sales Lead Identifier
CREATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who column
REQUEST_ID	NULL	NUMBER	Standard Who column
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
STATUS_CODE	NULL	VARCHAR2(30)	The status of the lead validated against as_statuses_vl
ASSIGN_TO_PERSON_ID	NULL	NUMBER	The Tele Sales Agent to whom the lead is assigned to
ASSIGN_SALES_GROUP_ID	NULL	NUMBER	Assign to person's sales group id
LEAD_RANK_ID	NULL	NUMBER	Rank id of the sales lead
REJECT_REASON_CODE	NULL	VARCHAR2(30)	reject_reason_code
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_SALES_LEADS_LOG_N1	NOT UNIQUE	2	SALES_LEAD_ID
AS_SALES_LEADS_LOG_U1	UNIQUE	4	LOG_ID

Sequences

Sequence	Derived Column
AS_SALES_LEADS_LOG_S	LOG_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

AS_SALES_LEAD_LINES

AS_SALES_LEAD_LINES stores information about the individual items associated with the Lead.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AMS_ACT_OFFERS	ACTIVITY_OFFER_ID	OFFER_ID
AMS_SOURCE_CODES	SOURCE_CODE_ID	SOURCE_PROMOTION_ID
AS_INTEREST_CODES_B	INTEREST_CODE_ID	PRIMARY_INTEREST_CODE_ID
AS_INTEREST_CODES_B	INTEREST_CODE_ID	SECONDARY_INTEREST_CODE_ID
AS_INTEREST_TYPES_B	INTEREST_TYPE_ID	INTEREST_TYPE_ID
AS_SALES_LEADS	SALES_LEAD_ID	SALES_LEAD_ID
MTL_SYSTEM_ITEMS_B	INVENTORY_ITEM_ID	INVENTORY_ITEM_ID
	ORGANIZATION_ID	ORGANIZATION_ID

Column Descriptions

Name	Null?	Type	Description
SALES_LEAD_LINE_ID (PK)	NOT NULL	NUMBER	Sales lead line identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who column
REQUEST_ID		NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID		NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID		NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE		DATE	Last date concurrent program updated record
SALES_LEAD_ID	NOT NULL	NUMBER	Sales Lead Identifier
STATUS_CODE		VARCHAR2(30)	Obsolete in lli
INTEREST_TYPE_ID		NUMBER	The interest type identifier for the lead
PRIMARY_INTEREST_CODE_ID		NUMBER	Primary interest code identifier for the lead
SECONDARY_INTEREST_CODE_ID		NUMBER	Secondary interest code identifier
INVENTORY_ITEM_ID		NUMBER	Referenced inventory item identifier
ORGANIZATION_ID		NUMBER	Reference inventory organization identifier
UOM_CODE		VARCHAR2(3)	Unit of measure code from mtl_unit_of_measures, valid UOM for inventory_item_id if one exists
QUANTITY		NUMBER	Lead item quantity
BUDGET_AMOUNT		NUMBER	The amount of sale likely to result from this lead item
SOURCE_PROMOTION_ID		NUMBER	Promotion identifier that initiated the creation of the lead
ATTRIBUTE_CATEGORY		VARCHAR2(30)	Descriptive Flexfield structure defining column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
OFFER_ID	NULL	NUMBER	Promotions offer
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_SALES_LEAD_LINES_N1	NOT UNIQUE	5	SALES_LEAD_ID
AS_SALES_LEAD_LINES_N2	NOT UNIQUE	5	INTEREST_TYPE_ID
		10	PRIMARY_INTEREST_CODE_ID
		15	SECONDARY_INTEREST_CODE_ID
AS_SALES_LEAD_LINES_N3	NOT UNIQUE	5	INVENTORY_ITEM_ID
		7	ORGANIZATION_ID
AS_SALES_LEAD_LINES_N4	NOT UNIQUE	2	SOURCE_PROMOTION_ID
AS_SALES_LEAD_LINES_N5	NOT UNIQUE	2	OFFER_ID
AS_SALES_LEAD_LINES_N6	NOT UNIQUE	5	LAST_UPDATE_DATE
AS_SALES_LEAD_LINES_U1	UNIQUE	5	SALES_LEAD_LINE_ID

Sequences

Sequence	Derived Column
AS_SALES_LEAD_LINES_S	SALES_LEAD_LINE_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

AS_SALES_LEAD_OPPORTUNITY

AS_SALES_LEAD_OPPORTUNITY is used to maintain information about the leads which are converted to opportunity. It stores information about which leads/lead is linked to an opportunity.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_LEADS_ALL	LEAD_ID	OPPORTUNITY_ID
AS_SALES_LEADS	SALES_LEAD_ID	SALES_LEAD_ID

Column Descriptions

Name	Null?	Type	Description
LEAD_OPPORTUNITY_ID	NOT NULL	NUMBER	Sales lead opportunity identifier
SALES_LEAD_ID	NOT NULL	NUMBER	sales lead identifier
OPPORTUNITY_ID	NOT NULL	NUMBER	opportunity identifier
LAST_UPDATE_DATE	NOT NULL	DATE	standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	standard who column
CREATION_DATE	NOT NULL	DATE	standard who column
CREATED_BY	NOT NULL	NUMBER	standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	standard who column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive Flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive Flexfield segment column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive Flexfield segment column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_SALES_LEAD_OPP_N1	NOT UNIQUE	5	OPPORTUNITY_ID
AS_SALES_LEAD_OPP_N2	NOT UNIQUE	5	SALES_LEAD_ID
AS_SALES_LEAD_OPP_U1	UNIQUE	2	LEAD_OPPORTUNITY_ID

Sequences

Sequence	Derived Column
AS_SALES_LEAD_OPP_S	LEAD_OPPORTUNITY_ID

AS_SALES_LEAD_RANKS_B

AS_SALES_LEAD_RANKS_B , defines the various ranks a lead can have depending on the score. Eg: Hot Lead, Cold Lead, Medium Lead and Low Lead.

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
ENABLED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
RANK_ID (PK)	NOT NULL	NUMBER	Rank Identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who column
MIN_SCORE	NOT NULL	NUMBER	Stores the Minimum score
MAX_SCORE	NOT NULL	NUMBER	Stores the Maximum score
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	Identifies wheather the row is enabled or not
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_SALES_LEAD_RANKS_B_U1	UNIQUE	5	RANK_ID

Sequences

Sequence	Derived Column
AS_SALES_LEAD_RANKS_S	RANK_ID

AS_SALES_STAGES_ALL_B

AS_SALES_STAGES_ALL stores all sales stages for sales opportunities. A sales stage is defined by a name and a range of minimum and maximum win probability. There is a start and end date defining the period for which the sales stage is active.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_FORECAST_PROB_ALL_B	PROBABILITY_VALUE	MAX_WIN_PROBABILITY
AS_FORECAST_PROB_ALL_B	PROBABILITY_VALUE	MIN_WIN_PROBABILITY

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
ENABLED_FLAG	FLAG	AS_LOOKUPS
	N	No
	Y	Yes
USAGE_INDICATOR	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
SALES_STAGE_ID (PK)	NOT NULL	NUMBER	Sales stage identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
NAME	NULL	VARCHAR2(60)	Obsolete in lli, moved to _TL table
MIN_WIN_PROBABILITY	NOT NULL	NUMBER	Sales stage minimum win probability
MAX_WIN_PROBABILITY	NOT NULL	NUMBER	Sales stage maximum win probability
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	Flag to indicate if sales stage is enabled
START_DATE_ACTIVE	NOT NULL	DATE	Date which the sales stage becomes active
END_DATE_ACTIVE	NULL	DATE	Date which sales stage becomes inactive
DESCRIPTION	NULL	VARCHAR2(240)	Obsolete in lli, moved to _TL table
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
USAGE_INDICATOR	NULL	VARCHAR2(30)	Indicates to whom the data will be exposed to. valid values are "OS" , "PRM" , "ALL"
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use
INTERNAL_UPGRADE_STAGE_ID	NULL	NUMBER	For internal use only on data migration- to keep the new sales_stage_id

Indexes

Index Name	Index Type	Sequence	Column Name
AS_SALES_STAGES_ALL_B_U1	UNIQUE	1	SALES_STAGE_ID
		2	ORG_ID

Sequences

Sequence	Derived Column
AS_SALES_STAGES_S	SALES_STAGE_ID

AS_SALES_STAGES_ALL_TL

Columns that move from AS_SALES_STAGES_ALL_B are 1) Sales_stage_Id, 2) Description, 3) Name Primary Key is Sales_stage_Id + Language

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_SALES_STAGES_ALL_B	SALES_STAGE_ID	SALES_STAGE_ID

Column Descriptions

Name	Null?	Type	Description
SALES_STAGE_ID (PK)	NOT NULL	NUMBER	Sales stage identifier
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Language
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Source Lang
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
NAME	NOT NULL	VARCHAR2(60)	Sales stage name
DESCRIPTION	NULL	VARCHAR2(240)	Sales stage description
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_SALES_STAGES_ALL_TL_U1	UNIQUE	2	SALES_STAGE_ID
		4	LANGUAGE

Sequences

Sequence	Derived Column
AS_SALES_STAGES_S	SALES_STAGE_ID

AS_STATUSES_B

AS_STATUSES holds three types of status. They are opportunity, lead and quote.

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
USAGE_INDICATOR	FLAG	AS_LOOKUPS
	N	No
	Y	Yes

Column Descriptions

Name	Null?	Type	Description
STATUS_CODE (PK)	NOT NULL	VARCHAR2(30)	status code for the status
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	indicates the status is enabled or not
LEAD_FLAG	NULL	VARCHAR2(1)	Flag to indicate that this status is for sales leads
OPP_FLAG	NULL	VARCHAR2(1)	Flag to indicate that this status is for sales opportunity
OPP_OPEN_STATUS_FLAG	NULL	VARCHAR2(1)	Flag to indicate that this status is for open opportunity
OPP_DECISION_DATE_FLAG	NULL	VARCHAR2(1)	Not currently used
STATUS_RANK	NULL	NUMBER	Not currently used
FORECAST_ROLLUP_FLAG	NULL	VARCHAR2(1)	Flag to indicate opportunity with this status will appear in forecast
WIN_LOSS_INDICATOR	NULL	VARCHAR2(1)	Indicates whether the opportunity or lead is Won and Closed or Lost and Closed or just Closed because it is not an opportunity anymore. Validation will be made against Open Flag. Possible values are 'W', 'L', 'N' (neither equivalent to NULL)
USAGE_INDICATOR	NULL	VARCHAR2(30)	Indicates to whom the data will be exposed to. valid values are "OS", "PRM", "ALL"
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment column

ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_STATUSES_B_U1	UNIQUE	5	STATUS_CODE

AS_STATUSES_TL

Hold the translated columns (meaning, description) of the base table, AS_STATUSES_B.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_STATUSES_B	STATUS_CODE	STATUS_CODE

Column Descriptions

Name	Null?	Type	Description
STATUS_CODE	NOT NULL	VARCHAR2(30)	Status Code
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard who column
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Language
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Source Lang
MEANING	NULL	VARCHAR2(240)	Meaning
DESCRIPTION	NULL	VARCHAR2(240)	Description
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_STATUSES_TL_U1	UNIQUE	2	STATUS_CODE
		4	LANGUAGE

AS_TERRITORY_ACCESSES

Intersection table between AS_TERRITORIES_ALL and AS_ACCESSES_ALL.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
AS_ACCESSES_ALL	ACCESS_ID	ACCESS_ID
JTF_TERR_ALL	TERR_ID	TERRITORY_ID

Column Descriptions

Name	Null?	Type	Description
ACCESS_ID (PK)	NOT NULL	NUMBER	Access identifier
TERRITORY_ID (PK)	NOT NULL	NUMBER	Territory identifier
USER_TERRITORY_ID	NOT NULL	NUMBER	No longer used.
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column.
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column.
CREATION_DATE	NOT NULL	DATE	Standard Who column.
CREATED_BY	NOT NULL	NUMBER	Standard Who column.
LAST_UPDATE_LOGIN	NOT NULL	NUMBER	Standard Who column.
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
AS_TERRITORY_ACCESSES_U1	UNIQUE	1	ACCESS_ID
		2	TERRITORY_ID
AS_TERRITORY_ACCESSES_U2	UNIQUE	1	TERRITORY_ID
		2	ACCESS_ID

BIL_IMP_CUST_SUMM

Stores summary customer sales revenue, forecasted revenue, service requests and customer satisfaction measures.

Summarization is along Time, Territory, Customer and Incident Severities dimensions.

Column Descriptions

Name	Null?	Type	Description
PERIOD_NAME	NOT NULL	VARCHAR2(15)	System generated accounting period name
ADDRESS_ID	NULL	NUMBER	Obsleted in version 11.5.2 with migration to new TCA customer model. Formerly used as customer address identifier.
TERRITORY_ID	NOT NULL	NUMBER	Territory identifier
CUSTOMER_ID	NOT NULL	NUMBER	Customer identifier
INCIDENT_SEVERITY_ID	NOT NULL	NUMBER(15)	Incident Severity identifier (customer service request incidents).
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who Column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
START_DATE	NOT NULL	DATE	Date on which accounting period begins
END_DATE	NOT NULL	DATE	Date on which accounting period ends
EXPECTED_REVENUE	NULL	NUMBER	SUM of forecasted customer revenue
SALES_REVENUE	NULL	NUMBER	SUM of actual customer revenue
CUST_SATISFACTION_PCT	NULL	NUMBER	Customer satisfaction measure - derived from CRM Customer Intelligence (BIC) application
SERVICE_REQUESTS	NULL	NUMBER	COUNT of number of customer service request incidents
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_IMP_CUST_SUMM_U1	UNIQUE	10	START_DATE
		20	END_DATE
		30	TERRITORY_ID
		40	CUSTOMER_ID
		52	INCIDENT_SEVERITY_ID
		60	PERIOD_NAME

BIL_INV_TERR_INTF

Table used to assign invoices to territories for use in relating territories to invoices during the data load process. A single invoice may be assigned to multiple territories.

The purpose of the table is to enable reporting by territory for invoices. Territories are assigned per the CRM Foundation territory assignment engine, using territory assignment qualifiers that are used during territory assignment for sales leads.

Column Descriptions

Name	Null?	Type	Description
INVOICE_ID (PK)	NOT NULL	NUMBER	Invoice Identifier
TERRITORY_ID (PK)	NOT NULL	NUMBER	Territory identifier
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who Column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
WEIGHT	NULL	NUMBER	Pct by which money amounts are multiplied during loads. Based on count of invoice_id territory_id combination.
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_INV_TERR_INTF_U1	NOT UNIQUE	5	INVOICE_ID
		6	TERRITORY_ID

BIL_OPTY_PERF_SUMM

BIL_OPTY_PERF_SUMM stores summary sales information related to sales opportunity performance, including invoice and opportunity amounts, customer satisfaction measures and win probability.

Information is summarized along the Time, Territory, Product, Salesforce, Sales Channel and Customer dimensions.

Column Descriptions

Name	Null?	Type	Description
PERIOD_NAME	NOT NULL	VARCHAR2(15)	System generated accounting period name
TERRITORY_ID	NOT NULL	NUMBER	Territory identifier
INTEREST_TYPE_ID	NOT NULL	NUMBER	Interest Type identifier
PRIMARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Primary Interest Code identifier
SECONDARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Secondary Interest Code identifier
SALES_CHANNEL_ID	NOT NULL	VARCHAR2(30)	Sales Channel identifier
SALESREP_ID	NOT NULL	NUMBER	Sales Representative identifier
SALES_GROUP_ID	NOT NULL	NUMBER	Sales Group identifier
CUSTOMER_ID	NOT NULL	NUMBER	Customer identifier
ADDRESS_ID	NULL	NUMBER	Address identifier. Obsolete in version 11.5.2 with migration to new TCA customer model.
LEAD_ID	NULL	NUMBER	Obsolete in 11.5.2 Lead identifier
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who Column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
START_DATE	NULL	DATE	Date on which accounting period begins
END_DATE	NULL	DATE	Date on which accounting period ends
INVOICED_AMOUNT	NULL	NUMBER	SUM of invoiced amount
OPTY_AMOUNT	NULL	NUMBER	SUM of sales opportunity amount
WIN_PROBABILITY	NULL	NUMBER	Win Probability for sales opportunity

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CUST_SATISFACTION_PCT	NULL	NUMBER	Customer satisfaction measure - derived from CRM Customer Intelligence (BIC) application
OPTY_NAME	NULL	VARCHAR2(240)	Sales opportunity name. Obsolete.
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_OPTY_PERF_SUMM_U1	UNIQUE	10	START_DATE
		20	END_DATE
		30	TERRITORY_ID
		40	INTEREST_TYPE_ID
		50	PRIMARY_INTEREST_CODE_ID
		60	SECONDARY_INTEREST_CODE_ID
		70	SALES_CHANNEL_ID
		80	SALESREP_ID
		85	SALES_GROUP_ID
		90	CUSTOMER_ID
		92	LEAD_ID
		110	PERIOD_NAME

BIL_ORD_TERR_INTF

Table used to assign orders to territories for use in relating territories to orders during the data load process. A single order may be assigned to multiple territories.

The purpose of the table is to enable reporting by territory for orders. Territories are assigned per the CRM Foundation territory assignment engine, using territory assignment qualifiers that are used during territory assignment for sales leads.

Column Descriptions

Name	Null?	Type	Description
ORDER_ID (PK)	NOT NULL	NUMBER	Order Identifier
TERRITORY_ID (PK)	NOT NULL	NUMBER	Territory identifier
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who Column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
WEIGHT	NULL	NUMBER	Pct by which money amounts are multiplied during loads. Based on count of order_id territory_id combination.
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_ORD_TERR_INTF_U1	NOT UNIQUE	5	ORDER_ID
		6	TERRITORY_ID

BIL_PROD_SCT_WL_SUMM

Stores sales summary information for revenue, units sold, cost of good sold, sales margins, forecasted revenue, sales cycle time and number of won and lost opportunities.

Informations is summarized by Time, Sales Territory, Salesforce, Sales Channel and Product dimensions.

Column Descriptions

Name	Null?	Type	Description
PERIOD_NAME	NOT NULL	VARCHAR2(15)	System generated accounting period name
TERRITORY_ID	NOT NULL	NUMBER	Territory identifier
SALESREP_ID	NOT NULL	NUMBER	Sales representative identifier
SALES_CHANNEL_ID	NOT NULL	VARCHAR2(30)	Sales channel identifier
INTEREST_TYPE_ID	NOT NULL	NUMBER	Interest type identifier
PRIMARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Primary interest code identifier
SECONDARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Secondary interest code identifier
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NUL	NUMBER	Standard Who Column
REQUEST_ID	NUL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NUL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NUL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NUL	DATE	Last date concurrent program updated record
TERRITORY_NAME	NUL	VARCHAR2(240)	Territory Name. Obsolete.
SALES_CHANNEL	NUL	VARCHAR2(80)	Sales Channel description. Obsolete.
SALESREP_NAME	NUL	VARCHAR2(80)	Sales Representative name. Obsolete.
START_DATE	NUL	DATE	Date on which accounting period begins
END_DATE	NUL	DATE	Date on which accounting period ends
INVOICED_AMOUNT	NUL	NUMBER	
COGS_AMOUNT	NUL	NUMBER	
MARGIN	NUL	NUMBER	
EXPECTED_REVENUE	NUL	NUMBER	
SALES_CYCLE	NUL	NUMBER	
UNITS_SOLD	NUL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

NO_OF_WON_OPTY	NULL	NUMBER	Count of won opportunities
NO_OF_LOSSES	NULL	NUMBER	Count of lost opportunities
NO_OF_CLOSED_OPTY	NULL	NUMBER	Count of closed opportunities
SALES_GROUP_ID	NULL	NUMBER	Sales Group identifier - for future use
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_PROD_SCT_WL_SUMM_U1	UNIQUE	10	START_DATE
		20	END_DATE
		30	TERRITORY_ID
		70	SALESREP_ID
		80	SALES_CHANNEL_ID
		82	INTEREST_TYPE_ID
		84	PRIMARY_INTEREST_CODE_ID
		86	SECONDARY_INTEREST_CODE_ID
		96	PERIOD_NAME

BIL_QUOTE_TERR_INTF

Table used to assign quotes to territories for use in relating territories to quotes during the data load process. A single quote may be assigned to multiple territories.

The purpose of the table is to enable reporting by territory for quotes. Territories are assigned per the CRM Foundation territory assignment engine, using territory assignment qualifiers that are used during territory assignment for sales leads.

Column Descriptions

Name	Null?	Type	Description
QUOTE_ID (PK)	NOT NULL	NUMBER	Quote identifier
TERRITORY_ID (PK)	NOT NULL	NUMBER	Territory identifier
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who Column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
WEIGHT	NULL	NUMBER	Pct by which money amounts are multiplied during loads. Based on count of quote_id territory_id combination.
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_QUOTE_TERR_INTF_U1	NOT UNIQUE	5	QUOTE_ID
		6	TERRITORY_ID

BIL_REV_CUST_SUMM

Stores sales information for invoice and order amounts, number of units sold, sales margins, cost of goods sold and number of sales orders.

Information is summarized by Time, Sales Territory, Salesforce, Sales Channel, Product and Customer dimensions.

Column Descriptions

Name	Null?	Type	Description
PERIOD_NAME	NOT NULL	VARCHAR2(15)	System generated accounting period name
TERRITORY_ID	NOT NULL	NUMBER	Territory identifier
INTEREST_TYPE_ID	NOT NULL	NUMBER	Interest type identifier
PRIMARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Primary interest code identifier
SECONDARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Secondary interest code identifier
SALES_CHANNEL_ID	NOT NULL	VARCHAR2(30)	Sales channel identifier
SALESREP_ID	NOT NULL	NUMBER	Sales representative identifier
CUSTOMER_ID	NOT NULL	NUMBER	Customer identifier(party_id from hz_parties).
ADDRESS_ID	NULL	NUMBER	Obsolete with migration to new TCA customer model. Formerly used as customeraddress identifier.
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who Column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
START_DATE	NULL	DATE	Date on which accounting period begins
END_DATE	NULL	DATE	Date on which accounting period ends
CUSTOMER_DURATION	NULL	NUMBER	Time elapsed from customer creation to current date.
NO_OF_LEADS	NULL	NUMBER	Count of sales leads
NO_OF_OPPTS	NULL	NUMBER	Count of sales opportunities
NO_OF_QUOTES	NULL	NUMBER	Count of quotes
NO_OF_ORDERS	NULL	NUMBER	Count of sales orders
EXPECTED_REVENUE	NULL	NUMBER	SUM of forecasted revenue

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SALES_REVENUE	NULL	NUMBER	SUM of sales revenue
ORDER_AMOUNT	NULL	NUMBER	SUM of order amounts
AVG_ORDER_AMOUNT	NULL	NUMBER	AVG of order amount generated along primary key
INVOICED_AMOUNT	NULL	NUMBER	SUM of invoiced amount
UNITS_SOLD	NULL	NUMBER	SUM of units sold
COGS_AMOUNT	NULL	NUMBER	SUM of cost of goods sold amount
MARGIN	NULL	NUMBER	SUM of sales margin
SALES_GROUP_ID	NULL	NUMBER	Sales Group Identifier - For future use
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_REV_CUST_SUMM_N1	NOT UNIQUE	0	TERRITORY_ID
BIL_REV_CUST_SUMM_N2	NOT UNIQUE	0	INTEREST_TYPE_ID
BIL_REV_CUST_SUMM_N3	NOT UNIQUE	0	PRIMARY_INTEREST_CODE_ID
BIL_REV_CUST_SUMM_N4	NOT UNIQUE	0	SECONDARY_INTEREST_CODE_ID
BIL_REV_CUST_SUMM_N5	NOT UNIQUE	0	SALES_CHANNEL_ID
BIL_REV_CUST_SUMM_N6	NOT UNIQUE	0	SALESREP_ID
BIL_REV_CUST_SUMM_N7	NOT UNIQUE	0	SALES_GROUP_ID
BIL_REV_CUST_SUMM_N8	NOT UNIQUE	0	CUSTOMER_ID
BIL_REV_CUST_SUMM_N9	NOT UNIQUE	0	ADDRESS_ID
BIL_REV_CUST_SUMM_U1	UNIQUE	10	START_DATE
		20	END_DATE
		30	TERRITORY_ID
		40	INTEREST_TYPE_ID
		50	PRIMARY_INTEREST_CODE_ID
		60	SECONDARY_INTEREST_CODE_ID
		70	SALES_CHANNEL_ID
		80	SALESREP_ID
		100	CUSTOMER_ID
		120	PERIOD_NAME

BIL_ROC_SUMM

BIL_ROC_SUMM stores information related to return on sales compensation, including sales revenue, commission and bonus information.

Information is summarized by Time, Compensation Plan and Salesforce dimensions.

Column Descriptions

Name	Null?	Type	Description
PERIOD_NAME	NOT NULL	VARCHAR2(15)	System generated accounting period name
COMP_PLAN_ID	NOT NULL	NUMBER(15)	Compensation Plan identifier
PLAN_ELEMENT_ID	NOT NULL	NUMBER	Compensation Plan element identifier(quota_id from as_quotas_all)
SALESREP_ID	NOT NULL	NUMBER	Sales Representative identifier (resource_id from jtf_rs_resource_extns)
ROLE_ID	NOT NULL	NUMBER(15)	Sales Representative employee role identifier
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN		NUMBER	Standard Who Column
REQUEST_ID		NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID		NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID		NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE		DATE	Last date concurrent program updated record
START_DATE		DATE	Date on which accounting period begins
END_DATE		DATE	Date on which accounting period ends
SALES_REVENUE		NUMBER	SUM of sales revenue amount
COMMISSION		NUMBER	Amount of commission for a given accounting period for a SUM of sales representative commission amount
BONUS		NUMBER	SUM of sales representative bonus amount
TARGET_MET		NUMBER	Flag to indicate salerep met targeted quota amount for period. Met = '1', Not Met = '0'. Column is used summed for period of data collection.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

TARGET_NOT_MET	NULL NUMBER	Flag to indicate salerep did not meet targeted quota amount for period. Not Met = '1', Met = '0'. Column is used summed for period of data collection.
SALES_GROUP_ID	NULL NUMBER	Sales Group Identifier - For future use
SECURITY_GROUP_ID	NULL NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_ROC_SUMM_U1	UNIQUE	10	START_DATE
		20	END_DATE
		30	COMP_PLAN_ID
		40	PLAN_ELEMENT_ID
		50	SALESREP_ID
		60	PERIOD_NAME

BIL_SLS_CHNL_PERF_SUMM

BIL_SLS_CHNL_PERF_SUMM stores summary sales information related to sale channel performance, including invoice and margin amounts, cost of goods sold, units sold, number of leads, number of sales orders, number of won opportunities, number of closed opportunities and overall measure of customer satisfaction.

Information is summarized by Time, Product, Sales Channel and Sales Territory dimensions.

Column Descriptions

Name	Null?	Type	Description
PERIOD_NAME	NOT NULL	VARCHAR2(15)	System generated accounting period name
TERRITORY_ID	NOT NULL	NUMBER	Territory identifier
INTEREST_TYPE_ID	NOT NULL	NUMBER	Interest type identifier
PRIMARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Primary Interest Code identifier
SECONDARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Secondary Interest Code identifier
SALES_CHANNEL_ID	NOT NULL	VARCHAR2(30)	Sales Channel identifier
SALES_CHANNEL	NOT NULL	VARCHAR2(30)	Sales Channel meaning. Obsolete.
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who Column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
START_DATE	NOT NULL	DATE	Date on which accounting period begins
END_DATE	NOT NULL	DATE	Date on which accounting period ends
INVOICED_AMOUNT	NULL	NUMBER	SUM of invoiced amount
COGS_AMOUNT	NULL	NUMBER	SUM of cost of goods sold amount
MARGIN	NULL	NUMBER	SUM of gross margin amount
NO_OF_WON_OPTY	NULL	NUMBER	COUNT of won sales opportunities for period
NO_OF_CLOSED_OPTY	NULL	NUMBER	COUNT of closed opportunities for period

Oracle Proprietary, Confidential Information--Use Restricted by Contract

UNITS_SOLD	NULL	NUMBER	SUM of number of units sold
CUST_SATISFACTION_PCT	NULL	NUMBER	Customer satisfaction measure - derived from CRM Customer Intelligence (BIC) application
NO_OF_LEADS	NULL	NUMBER	COUNT of sales leads
NO_OF_ORDERS	NULL	NUMBER	COUNT of sales orders
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_SALES_CHNL_PERF_SUMM_U1	UNIQUE	10	START_DATE
		20	END_DATE
		30	TERRITORY_ID
		32	SALES_CHANNEL_ID
		40	INTEREST_TYPE_ID
		50	PRIMARY_INTEREST_CODE_ID
		60	SECONDARY_INTEREST_CODE_ID
		70	PERIOD_NAME

BIL_SREP_PERF_SUMM

Stores summary sales information related to salesforce performance, including, invoice amounts, cost of goods sold, sales revenue credits, number of won and lost opportunities, sales cycle time, units sold and compensation amount.

Information is summarized by Time, Sales Territory, Product, Sales Channel and Compensation Plan.

Column Descriptions

Name	Null?	Type	Description
PERIOD_NAME	NOT NULL	VARCHAR2(15)	System generated accounting period name
TERRITORY_ID	NOT NULL	NUMBER	Territory identifier
INTEREST_TYPE_ID	NOT NULL	NUMBER	Interest Type identifier
PRIMARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Primary Interest Code identifier
SECONDARY_INTEREST_CODE_ID	NOT NULL	NUMBER	Secondary Interest Code identifier
SALES_CHANNEL_ID	NOT NULL	VARCHAR2(30)	Sales Channel identifier
SALESREP_ID	NOT NULL	NUMBER	Sales Representative identifier(resource_id from jtf_rs_resource_extns)
COMP_PLAN_ID	NOT NULL	NUMBER(15)	Compensation Plan identifier
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN		NUMBER	Standard Who Column
REQUEST_ID		NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID		NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID		NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE		DATE	Last date concurrent program updated record
START_DATE		DATE	Date on which accounting period begins
END_DATE		DATE	Date on which accounting period ends
INVOICED_AMOUNT		NUMBER	SUM of invoiced amount
REVENUE_CREDITS		NUMBER	SUM of sales representative revenue credits
COGS_AMOUNT		NUMBER	SUM of cost of goods sold amount
MARGIN		NUMBER	SUM of gross margin amount
NO_OF_WON_OPTY		NUMBER	COUNT of sales opportunities won for a period

Oracle Proprietary, Confidential Information--Use Restricted by Contract

NO_OF_CLOSED_OPTY	NULL	NUMBER(15)	COUNT of sales opportunities closed for a period
SALES_CYCLE	NULL	NUMBER	Time in days for an opportunity decision to be made (decision_date - creation_date)
UNITS_SOLD	NULL	NUMBER	COUNT of number of units sold
COMP_AMT	NULL	NUMBER	SUM of sales representative compensation amount
SALES_GROUP_ID	NULL	NUMBER	Sales Group Identifier - For future use
SECURITY_GROUP_ID	NULL	NUMBER	Subscriber id, for CRM Online Services use

Indexes

<u>Index Name</u>	<u>Index Type</u>	<u>Sequence</u>	<u>Column Name</u>
BIL_SREP_PERF_SUMM_U1	UNIQUE	10	START_DATE
		20	END_DATE
		30	TERRITORY_ID
		40	INTEREST_TYPE_ID
		50	PRIMARY_INTEREST_CODE_ID
		60	SECONDARY_INTEREST_CODE_ID
		70	SALES_CHANNEL_ID
		80	SALESREP_ID
		100	COMP_PLAN_ID
		110	PERIOD_NAME

BIL_SRV_RQST_SUMM

Table is Obsolete.

Column Descriptions

Name	Null?	Type	Description
PERIOD_NAME	NOT NULL	VARCHAR2(15)	System generated accounting period name
TERRITORY_ID	NOT NULL	NUMBER	Territory identifier
CUSTOMER_ID	NOT NULL	NUMBER	Customer identifier
ADDRESS_ID	NULL	NUMBER	Address identifier. Obsolete in version 11.5.1 with migration to new TCA customer model.
INCIDENT_SEVERITY_ID	NOT NULL	NUMBER(15)	Incident Severity identifier (customer service request incidents)
CREATION_DATE	NOT NULL	DATE	Standard Who Column
CREATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who Column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who Column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who Column
REQUEST_ID	NULL	NUMBER	Request identifier of last concurrent program to update record
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application identifier of last concurrent program to update record
PROGRAM_ID	NULL	NUMBER	Identifier of last concurrent program to update record
PROGRAM_UPDATE_DATE	NULL	DATE	Last date concurrent program updated record
START_DATE	NOT NULL	DATE	Date on which accounting period begins
END_DATE	NOT NULL	DATE	Date on which accounting period ends
NO_OF_INCIDENTS	NULL	NUMBER	COUNT of number of customer service request incidents
SECURITY_GROUP_ID	NULL	NUMBER	

Indexes

Index Name	Index Type	Sequence	Column Name
BIL_SRV_RQST_SUMM_U1	UNIQUE	1	PERIOD_NAME
		2	START_DATE
		3	END_DATE
		4	TERRITORY_ID
		8	CUSTOMER_ID
		10	INCIDENT_SEVERITY_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CN_COMMISSION_HEADERS_ALL

CN_COMMISSION_HEADERS contains information about direct credit salesperson transactions. It always has one to one correspondence to a record in CN_COMM_LINES_API table after transactions are loaded using Transaction Interface Loader and LOAD_STATUS is set to 'LOADED'. It has 100 descriptive flexfields which can either be used for defining classification rules or defining performance measures and calculation formulas.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_REVENUE_CLASSES_ALL	REVENUE_CLASS_ID	REVENUE_CLASS_ID

Column Descriptions

Name	Null?	Type	Description
COMMISSION_HEADER_ID (PK)	NOT NULL	NUMBER(15)	Primary Key.
DIRECT_SALESPER_ID	NOT NULL	NUMBER(15)	Direct Salesperson ID.
PROCESSED_DATE	NOT NULL	DATE	Revenue Recognition Date.
PROCESSED_PERIOD_ID	NULL	NUMBER(15)	Revenue Recognition Period ID
ROLLUP_DATE	NULL	DATE	Date that the transaction was rolled up.
TRANSACTION_AMOUNT	NULL	NUMBER	Functional transaction amount.
QUANTITY	NULL	NUMBER	Quantity amount.
DISCOUNT_PERCENTAGE	NULL	NUMBER	Discount percentage for discount based commission.
MARGIN_PERCENTAGE	NULL	NUMBER	Margin percentage for margin based commission.
ORIG_CURRENCY_CODE	NULL	VARCHAR2(3)	Original Currency Code.
TRANSACTION_AMOUNT_ORIG	NULL	NUMBER	Original transaction amount.
TRX_TYPE	NULL	VARCHAR2(30)	Transaction type.
STATUS	NULL	VARCHAR2(30)	Calculation status.
PRE_PROCESSED_CODE	NULL	VARCHAR2(30)	Pre processed code.
COMM_LINES_API_ID	NULL	NUMBER(15)	Foreign key to CN_COMM_LINES_API.
SOURCE_DOC_TYPE	NULL	VARCHAR2(80)	Source doc type.
SOURCE_TRX_NUMBER	NULL	VARCHAR2(80)	Source transaction number.
QUOTA_ID	NULL	NUMBER(15)	Quota that this transaction falls under.
SRP_PLAN_ASSIGN_ID	NULL	NUMBER(15)	Foreign key to CN_SRP_PLAN_ASSIGNS
REVENUE_CLASS_ID	NULL	NUMBER(15)	Revenue class that this transaction matches.
ROLE_ID	NULL	NUMBER(15)	Foreign key to CN_ROLES.
COMP_GROUP_ID	NULL	NUMBER(15)	Foreign key to CN_COMP_GROUPS
COMMISSION_AMOUNT	NULL	NUMBER	Amount of commission payed on this transaction.
TRX_BATCH_ID	NULL	NUMBER(15)	Transaction batch ID.
REVERSAL_FLAG	NULL	VARCHAR2(1)	Reversal flag.
REVERSAL_HEADER_ID	NULL	NUMBER(15)	Reversal header ID.
REASON_CODE	NULL	VARCHAR2(30)	Reason code.
COMMENTS	NULL	VARCHAR2(1800)	Comments.
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column.
ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive flexfield segment.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE59	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE60	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE61	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE62	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE63	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE64	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE65	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE66	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE67	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE68	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE69	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE70	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE71	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE72	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE73	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE74	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE75	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE76	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE77	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE78	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE79	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE80	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE81	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE82	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE83	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE84	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE85	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE86	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE87	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE88	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE89	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE90	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE91	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE92	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE93	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE94	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE95	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE96	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE97	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE98	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE99	NULL	VARCHAR2(240)	Descriptive flexfield segment.
ATTRIBUTE100	NULL	VARCHAR2(240)	Descriptive flexfield segment.
LAST_UPDATE_DATE	NULL	DATE	Standard who column.
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column.
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column.
CREATION_DATE	NULL	DATE	Standard who column.
CREATED_BY	NULL	NUMBER(15)	Standard who column.
ORG_ID	NULL	NUMBER(15)	Organization identifier.
EXCHANGE_RATE	NULL	NUMBER	Exchange rate used to convert the line
FORECAST_ID	NULL	NUMBER(15)	Forecast ID
UPSIDE_QUANTITY	NULL	NUMBER	Upside quantity
UPSIDE_AMOUNT	NULL	NUMBER	Upside Amount
UOM_CODE	NULL	VARCHAR2(3)	Unit of measurement code
SOURCE_TRX_ID	NULL	NUMBER(15)	Header ID of the source trx
SOURCE_TRX_LINE_ID	NULL	NUMBER(15)	Line ID of the source trx

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SOURCE_TRX_SALES_LINE_ID	NULL	NUMBER(15)	Sales credit id of the source trx
NEGATED_FLAG	NULL	VARCHAR2(1)	Flag indicating whether the line has already been negated or not. Used for OE adjustment.
CUSTOMER_ID	NULL	NUMBER(15)	Customer ID
INVENTORY_ITEM_ID	NULL	NUMBER(15)	Inventory Item ID
ORDER_NUMBER	NULL	NUMBER	Order number
BOOKED_DATE	NULL	DATE	Date order gets booked
INVOICE_NUMBER	NULL	VARCHAR2(20)	Invoice number
INVOICE_DATE	NULL	DATE	Date order gets invoiced
BILL_TO_ADDRESS_ID	NULL	NUMBER	Bill To Address Id
SHIP_TO_ADDRESS_ID	NULL	NUMBER	Ship To Address Id
BILL_TO_CONTACT_ID	NULL	NUMBER	Bill To Contact Id
SHIP_TO_CONTACT_ID	NULL	NUMBER	Ship To Contact Id
ADJ_COMM_LINES_API_ID	NULL	NUMBER(15)	Comm lines API ID which points to the parent transaction.
ADJUST_DATE	NULL	DATE	Date transaction was adjusted.
ADJUSTED_BY	NULL	VARCHAR2(100)	User ID that transaction was adjusted by.
REVENUE_TYPE	NULL	VARCHAR2(15)	Revenue type code.
ADJUST_ROLLUP_FLAG	NULL	VARCHAR2(1)	Adjust rollup flag.
ADJUST_COMMENTS	NULL	VARCHAR2(2000)	Adjust comments for the transaction.
ADJUST_STATUS	NULL	VARCHAR2(10)	Adjust status code of the transaction.
LINE_NUMBER	NULL	NUMBER	Line number.
REQUEST_ID	NULL	NUMBER(15)	Request identifier of last concurrent program to update
PROGRAM_ID	NULL	NUMBER(15)	Application identifier of last concurrent program to
PROGRAM_APPLICATION_ID	NULL	NUMBER(15)	Application identifier of last concurrent program to
PROGRAM_UPDATE_DATE	NULL	DATE	Last update date of this record by a concurrent program
TYPE	NULL	VARCHAR2(80)	Salesrep Type.
SALES_CHANNEL	NULL	VARCHAR2(30)	Sales Channel.

Indexes

Index Name	Index Type	Sequence	Column Name
CN_COMMISSION_HEADERS_N1	NOT UNIQUE	1	DIRECT_SALESREP_ID
		2	PROCESSED_DATE
		4	COMP_GROUP_ID
CN_COMMISSION_HEADERS_U1	UNIQUE	1	COMMISSION_HEADER_ID
		3	ORG_ID

Sequences

Sequence	Derived Column
CN_COMMISSION_HEADERS_S	COMMISSION_HEADER_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CN_COMMISSION_LINES_ALL

CN_COMMISSION_LINES contains information about the transactions and processing status through the system. You need one row for each possible combination of transaction, rate and salesperson which might cause a payment to be issued. Under no circumstances should this table be modified directly using SQL*Plus. During the process of calculation the system will create the rollup transactions and transactions if the revenue class overlaps between more than one plan element. To identify the transactions which are created by the system the payee_line_id and created_during are used. Payee_line_id refers to the commission_line_id of the base transaction. When a rollup transaction is created the Created_During column will show 'ROLL', when a transaction is created because of the revenue class overlap then the CREATED_DURING will show 'POP'. Transactions are also created during the Calculation phase when the commission is split across all the commission tiers. In which case the CREATED_DURING will show 'CALC'. Also if the Direct_Salesrep_id and the Created_salesrep_id are different it means the transaction is a rollup transaction. The 45 attribute columns which are used for classification purpose the information will appear only in the base transaction. The different values for Status are COL --- Transactions have been collected. XCLS --- Transactions could not be classified CLS --- Transactions got classified, updates the revenue_class_id of the transaction. ROLL - Transaction are in the rollup phase XPOP --- Transactions failed in the populate phase, usually it means the revenue class identified did not match to any of the plan elements assigned to a salesrep. POP --- Populate phase. Plan Element identified for the transaction. XCALC --- Failed calculation. Usually because of 0 transaction amount. CALC --- Calculated status.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_COMMISSION_HEADERS_ALL	COMMISSION_HEADER_ID	COMMISSION_HEADER_ID
CN_COMMISSION_LINES_ALL	COMMISSION_LINE_ID	PAYEE_LINE_ID
CN_PERIOD_STATUSES_ALL	PERIOD_ID	PROCESSED_PERIOD_ID
CN_QUOTAS_ALL	QUOTA_ID	QUOTA_ID
CN_QUOTA_RULES_ALL	QUOTA_RULE_ID	QUOTA_RULE_ID
CN_RATE_TIERS_ALL	RATE_TIER_ID	RATE_TIER_ID
CN_SALESREPS_API_ALL	SALESREP_API_ID	CREDITED_SALESREP_ID

Column Descriptions

Name	Null?	Type	Description
COMMISSION_LINE_ID (PK)	NOT NULL	NUMBER(15)	Commission line primary key
CREDITED_SALESREP_ID	NULL	NUMBER(15)	Which salesrep may be payed for this revenue
PROCESSED_PERIOD_ID	NULL	NUMBER(15)	Period in which revenue is recognized

PROCESSED_DATE	NULL	DATE	Date on which revenue was recognized
QUOTA_ID	NULL	NUMBER(15)	Quota that matches this transaction for this salesrep. References CN_QUOTAS
QUOTA_RULE_ID	NULL	NUMBER(15)	Rule in the quota that matched. References CN_QUOTA_RULES, and must be a detail of the quota specified by QUOTA_ID
EVENT_FACTOR	NULL	NUMBER	Factor derived from quota rule
PAYMENT_FACTOR	NULL	NUMBER	Factor derived from quota rule
QUOTA_FACTOR	NULL	NUMBER	Factor derived from quota rule
COMMISSION_AMOUNT	NULL	NUMBER	Amount of commission paid for this transaction
RATE_TIER_ID	NULL	NUMBER(15)	Rate tier that the transaction was paid on. References CN_RATE_TIERS
COMMISSION_RATE	NULL	NUMBER(10,5)	The rate at which the transaction was paid
PAYEE_LINE_ID	NULL	NUMBER(15)	A reference to CN_COMMISSION_LINES, pointing the "parent" transaction for this record, if it is the result of a split.
STATUS	NOT NULL	VARCHAR2(30)	Status of the transaction vis a vis calculation. DOMAIN = 'TRX_STATUS'
TRX_TYPE	NOT NULL	VARCHAR2(30)	Type as defined by source transaction. DOMAIN = 'TRX_TYPES'
TIER_SPLIT	NULL	NUMBER(1)	If TIER_SPLIT is non-zero, then this transaction was broken into two (or more) transactions by a tier boundary.
CREATED_DURING	NULL	VARCHAR2(30)	Used to identify when transaction is created by OSC. For source transaction, this is NULL
CREATED_BY	NULL	NUMBER(15)	Standard who column
CREATION_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
REQUEST_ID	NULL	NUMBER(15)	Request identifier of last concurrent program to update
PROGRAM_ID	NULL	NUMBER(15)	Application identifier of last concurrent program to
PROGRAM_APPLICATION_ID	NULL	NUMBER(15)	Application identifier of last concurrent program to
PROGRAM_UPDATE_DATE	NULL	DATE	Last update date of this record by a concurrent program
ORG_ID	NULL	NUMBER(15)	Organization Identifier
COMMISSION_HEADER_ID	NULL	NUMBER(15)	Foreign key to CN_COMMISSION_HEADERS
SRP_PLAN_ASSIGN_ID	NULL	NUMBER(15)	Foreign key to CN_SRP_PLAN_ASSIGNS
POSTING_STATUS	NULL	VARCHAR2(30)	Posting Status
INPUT_ACHIEVED	NULL	NUMBER	Input achieved amount
OUTPUT_ACHIEVED	NULL	NUMBER	Output achieve amount.
PERF_ACHIEVED	NULL	NUMBER	Performance achieved amount.
REVERSAL_HEADER_ID	NULL	NUMBER(15)	Reversal Header ID
ERROR_REASON	NULL	VARCHAR2(150)	Error reason for failed transaction

Oracle Proprietary, Confidential Information--Use Restricted by Contract

PAY_PERIOD_ID	NULL	NUMBER(15)	Pay period ID.
PENDING_STATUS	NULL	VARCHAR2(30)	Pending status.
ROLE_ID	NULL	NUMBER(15)	Foreign key to CN_ROLES
SRP_PAYEE_ASSIGN_ID	NULL	NUMBER(15)	Foreign key to CN_SRP_PAYEE_ASSIGNS
PENDING_DATE	NULL	DATE	Pending Date
THRESHOLD_CHECK_STATUS	NULL	VARCHAR2(30)	Threshold check status
CREDITED_COMP_GROUP_ID	NULL	NUMBER(15)	Credit comp group ID

Indexes

Index Name	Index Type	Sequence	Column Name
CN_COMMISSION_LINES_N3	NOT UNIQUE	5	PROCESSED_PERIOD_ID
CN_COMMISSION_LINES_N6	NOT UNIQUE	1	PAYEE_LINE_ID
CN_COMMISSION_LINES_N7	NOT UNIQUE	1	CREDITED_SALESREP_ID
		2	PROCESSED_PERIOD_ID
		3	QUOTA_ID
		4	QUOTA_RULE_ID
CN_COMMISSION_LINES_N9	NOT UNIQUE	5	CREDITED_SALESREP_ID
		6	PAY_PERIOD_ID
		7	QUOTA_ID
CN_COMMISSION_LINES_U1	UNIQUE	1	COMMISSION_LINE_ID
		3	ORG_ID

Sequences

Sequence	Derived Column
CN_COMMISSION_LINES_S	COMMISSION_LINE_ID

CN_QUOTAS_ALL

CN_QUOTAS contains information about your plan elements. You need one row for each plan element you create. There are four types of plan element:

- Revenue Quota
- Revenue Non Quota
- Draw
- Manual
-
- Unit Non Quota
- Discount
- Margin

Quota based plan elements do not use the CUMULATIVE_FLAG.

Revenue based plan elements do not use TARGET. They do use the CUMULATIVE_FLAG. It is set to Y by default.

Draw plan elements store the draw amount in the PAYMENT_AMOUNT column. They do not have revenue classes or a rate table. They do not use TARGET, PAYMENT_TYPE_CODE, TRX_GROUP_CODE, CUMULATIVE_FLAG or RATE_SCHEDULE_ID

Manual plan elements do not have revenue classes, period targets or a rate table. They do not use TARGET, PAYMENT_TYPE_CODE, PAYMENT_AMOUNT, TRX_GROUP_CODE, CUMULATIVE_FLAG, PERIOD_TARGET_UNIT_CODE or RATE_SCHEDULE_ID.

QUOTA_ID is the unique system-generated primary key and is invisible to the user. NAME is the unique user defined value you use to identify the plan element in forms and reports.

Currently USAGE_CODE is invisible to the user and is always set to 'ABSOLUTE'

ITD_GLAG when checked enable to define different quotas for the valid periods as defined by the start_preiod and the end_period of the Plan Element.

SPLIT_FLAG when checked splits the commission across the commission rate tiers. If the SPLIT_FLAG is not checked then the commission will be be paid at the higher rate tier. SPLIT_FLAG is checked as default for the Revene Quota Plan Element type when the Apply Trasnaction is INDIVIDUAL.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_CALC_FORMULAS_ALL	CALC_FORMULA_ID	CALC_FORMULA_ID
CN_CREDIT_TYPES_ALL_B	CREDIT_TYPE_ID	CREDIT_TYPE_ID
CN_INTERVAL_TYPES_ALL_B	INTERVAL_TYPE_ID	INTERVAL_TYPE_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
QUOTA_TYPE_CODE	QUOTA_TYPE	CN_LOOKUPS
	DISCOUNT	Discount
	DRAW	Draw
	MANUAL	Manual
	MARGIN	Margin
	REVENUE	Revenue Quota
	TARGET	Revenue Non Quota
	UNIT_BASED_NON_QUOTA	Unit Non Quota
TRX_GROUP_CODE	UNIT_BASED_QUOTA	Unit Quota
	QUOTA_TRX_GROUP	CN_LOOKUPS
	GROUP	Grouped By Interval
	INDIVIDUAL	Individually

Column Descriptions

Name	Null?	Type	Description
ORG_ID	NULL	NUMBER(15)	Organization Identifier
QUOTA_ID (PK)	NOT NULL	NUMBER(15)	Primary key
NAME	NOT NULL	VARCHAR2(80)	Plan Element name. Unique identifier
DESCRIPTION	NULL	VARCHAR2(1900)	Plan Element Description
START_DATE	NOT NULL	DATE	Start Date
END_DATE	NULL	DATE	End Date
QUOTA_TYPE_CODE	NOT NULL	VARCHAR2(30)	The type of plan element
TRX_GROUP_CODE	NULL	VARCHAR2(30)	Describes how the transactions are grouped in order to calculate compensation
INCENTIVE_TYPE_CODE	NOT NULL	VARCHAR2(30)	Incentive Type Code
INCREMENTAL_TYPE	NULL	VARCHAR2(1)	Y' if plan element is of incremental type
CREDIT_TYPE_ID	NULL	NUMBER(15)	Credit Type Id
BONUS_CREDIT_TYPE_ID	NULL	NUMBER(15)	Calculate bonus based on which credit type. Default to the credit type of the plan element.
INTERVAL_TYPE_ID	NULL	NUMBER(15)	Accumulation Interval Type Id
CALC_FORMULA_ID	NULL	NUMBER(15)	Formula Id
TARGET	NOT NULL	NUMBER	Target quota amount for quota based plan elements
PAYMENT_AMOUNT	NULL	NUMBER	Draw amount for draw type plan elements. For other element types is is the amount to which the percentage is applied if the payment type is "Payment Amount Percentage"
CUMULATIVE_FLAG	NULL	VARCHAR2(1)	Whether the quota is cumulative or not
SPLIT_FLAG	NULL	VARCHAR2(1)	Whether split should be used
RT_SCHED_CUSTOM_FLAG	NULL	VARCHAR2(1)	Customizable Rate Table Flag default to 'N'

PAYEE_ASSIGN_FLAG	NULL	VARCHAR2(1)	Eligibility for Payee Assignment default to 'N'
VESTING_FLAG	NULL	VARCHAR2(1)	Eligibility for Vesting Flag default to 'N'
PERFORMANCE_GOAL	NULL	NUMBER	Performance Goal
QUOTA_STATUS	NULL	VARCHAR2(30)	Plan Element Status
PACKAGE_NAME	NULL	VARCHAR2(30)	External Package Name
ADDUP_FROM_REV_CLASS_FLAG	NULL	VARCHAR2(1)	Indicating whether the quota/fixed amount equal to the sum of those values at revenue class level
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
CREATED_BY	NULL	NUMBER(15)	Standard who column
CREATION_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column
LIABILITY_ACCOUNT_ID	NULL	NUMBER(15)	
EXPENSE_ACCOUNT_ID	NULL	NUMBER(15)	
QUOTA_GROUP_CODE	NULL	VARCHAR2(30)	

Indexes

Index Name	Index Type	Sequence	Column Name
CN_QUOTAS_N1	NOT UNIQUE	5	CALC_FORMULA_ID
CN_QUOTAS_U1	UNIQUE	1	QUOTA_ID
		3	ORG_ID
CN_QUOTAS_U2	UNIQUE	2	NAME
		4	ORG_ID

Sequences

Sequence	Derived Column
CN_QUOTAS_S	QUOTA_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CN_QUOTA_ASSIGNS_ALL

CN_QUOTA_ASSIGNS contains foreign keys to identify the plan elements used by a compensation plan. You need one row for each plan element you assign to a compensation plan.

QUOTA_ASSIGN_ID is the system generated primary key and is invisible to the user.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_COMP_PLANS_ALL	COMP_PLAN_ID	COMP_PLAN_ID
CN_QUOTAS_ALL	QUOTA_ID	QUOTA_ID

Column Descriptions

Name	Null?	Type	Description
ORG_ID	NULL	NUMBER(15)	Organization Identifier
QUOTA_ASSIGN_ID (PK)	NOT NULL	NUMBER(15)	Unique identifier
QUOTA_ID	NOT NULL	NUMBER(15)	Plan Element unique identifier
COMP_PLAN_ID	NOT NULL	NUMBER(15)	Compensation Plan unique identifier
CREATED_BY	NULL	NUMBER(15)	Standard who column
WEIGHT	NULL	NUMBER(5,2)	Quota Weight
CREATION_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column

Indexes

Index Name	Index Type	Sequence	Column Name
CN_QUOTA_ASSIGNS_U1	UNIQUE	1	QUOTA_ASSIGN_ID
		3	ORG_ID
CN_QUOTA_ASSIGNS_U2	UNIQUE	1	COMP_PLAN_ID
		2	QUOTA_ID

CN_SRP_PERIODS_ALL

CN_SRP_PERIODS stores detailed information about a salesperson's compensation. You need one row for each period in which the salesperson is active.

The user cannot directly insert into this table. Rows are automatically created when you define a new salesperson. One row is created for each period forward from and including the salesperson's start period (RA_SALESREPS.START_PROCESING_PERIOD_ID). Rows are never deleted.

SRP_PERIOD_ID is the unique system generated primary key invisible to the user.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_CREDIT_TYPES_ALL_B	CREDIT_TYPE_ID	CREDIT_TYPE_ID
CN_PERIOD_STATUSES_ALL	PERIOD_ID	PERIOD_ID
CN_SRP_PLAN_ASSIGNS_ALL	SRP_PLAN_ASSIGN_ID	SRP_PLAN_ASSIGN_ID

Column Descriptions

Name	Null?	Type	Description
ORG_ID	NULL	NUMBER(15)	Organization Identifier
SRP_PERIOD_ID (PK)	NOT NULL	NUMBER(15)	Primary key
SALESREP_ID	NOT NULL	NUMBER(15)	Salesperson unique identifier
PERIOD_ID	NOT NULL	NUMBER(15)	Sales compensation period unique identifier
START_DATE	NULL	DATE	Start Date
END_DATE	NULL	DATE	End Date
SRP_PLAN_ASSIGN_ID	NULL	NUMBER(15)	Salesperson compensation plan unique identifier
CREDIT_TYPE_ID	NOT NULL	NUMBER(15)	Credit type identifier
ROLE_ID	NOT NULL	NUMBER(15)	Role identifier
PAY_GROUP_ID	NULL	NUMBER(15)	Pay Group Identifier
CONSISTENCY_FLAG	NULL	VARCHAR2(1)	whether consistent or not
PAID_FLAG	NULL	VARCHAR2(1)	Paid Flag
BALANCE1_DTD	NULL	NUMBER	System generated balance
BALANCE1_CTD	NULL	NUMBER	System generated balance
BALANCE1_BBD	NULL	NUMBER	System generated balance
BALANCE1_BBC	NULL	NUMBER	System generated balance
BALANCE2_DTD	NULL	NUMBER	System generated balance
BALANCE2_CTD	NULL	NUMBER	System generated balance
BALANCE2_BBD	NULL	NUMBER	System generated balance
BALANCE2_BBC	NULL	NUMBER	System generated balance
BALANCE3_DTD	NULL	NUMBER	System generated balance
BALANCE3_CTD	NULL	NUMBER	System generated balance
BALANCE3_BBD	NULL	NUMBER	System generated balance
BALANCE3_BBC	NULL	NUMBER	System generated balance
BALANCE4_DTD	NULL	NUMBER	System generated balance
BALANCE4_CTD	NULL	NUMBER	System generated balance
BALANCE4_BBD	NULL	NUMBER	System generated balance
BALANCE4_BBC	NULL	NUMBER	System generated balance

Oracle Proprietary, Confidential Information--Use Restricted by Contract

BALANCE5_DTD	NULL	NUMBER	System	generated	balance
BALANCE5_CTD	NULL	NUMBER	System	generated	balance
BALANCE5_BBD	NULL	NUMBER	System	generated	balance
BALANCE5_BBC	NULL	NUMBER	System	generated	balance
BALANCE6_DTD	NULL	NUMBER	System	generated	balance
BALANCE6_CTD	NULL	NUMBER	System	generated	balance
BALANCE6_BBD	NULL	NUMBER	System	generated	balance
BALANCE6_BBC	NULL	NUMBER	System	generated	balance
BALANCE7_DTD	NULL	NUMBER	System	generated	balance
BALANCE7_CTD	NULL	NUMBER	System	generated	balance
BALANCE7_BBD	NULL	NUMBER	System	generated	balance
BALANCE7_BBC	NULL	NUMBER	System	generated	balance
BALANCE8_DTD	NULL	NUMBER	System	generated	balance
BALANCE8_CTD	NULL	NUMBER	System	generated	balance
BALANCE8_BBD	NULL	NUMBER	System	generated	balance
BALANCE8_BBC	NULL	NUMBER	System	generated	balance
BALANCE9_DTD	NULL	NUMBER	System	generated	balance
BALANCE9_CTD	NULL	NUMBER	System	generated	balance
BALANCE9_BBD	NULL	NUMBER	System	generated	balance
BALANCE9_BBC	NULL	NUMBER	System	generated	balance
BALANCE10_DTD	NULL	NUMBER	System	generated	balance
BALANCE10_CTD	NULL	NUMBER	System	generated	balance
BALANCE10_BBD	NULL	NUMBER	System	generated	balance
BALANCE10_BBC	NULL	NUMBER	System	generated	balance
BALANCE11_DTD	NULL	NUMBER	System	generated	balance
BALANCE11_CTD	NULL	NUMBER	System	generated	balance
BALANCE11_BBD	NULL	NUMBER	System	generated	balance
BALANCE11_BBC	NULL	NUMBER	System	generated	balance
BALANCE12_DTD	NULL	NUMBER	System	generated	balance
BALANCE12_CTD	NULL	NUMBER	System	generated	balance
BALANCE12_BBD	NULL	NUMBER	System	generated	balance
BALANCE12_BBC	NULL	NUMBER	System	generated	balance
BALANCE13_DTD	NULL	NUMBER	System	generated	balance
BALANCE13_CTD	NULL	NUMBER	System	generated	balance
BALANCE13_BBD	NULL	NUMBER	System	generated	balance
BALANCE13_BBC	NULL	NUMBER	System	generated	balance
BALANCE14_DTD	NULL	NUMBER	System	generated	balance
BALANCE14_CTD	NULL	NUMBER	System	generated	balance
BALANCE14_BBD	NULL	NUMBER	System	generated	balance
BALANCE14_BBC	NULL	NUMBER	System	generated	balance
BALANCE15_DTD	NULL	NUMBER	System	generated	balance
BALANCE15_CTD	NULL	NUMBER	System	generated	balance
BALANCE15_BBD	NULL	NUMBER	System	generated	balance
BALANCE15_BBC	NULL	NUMBER	System	generated	balance
BALANCE16_DTD	NULL	NUMBER	System	generated	balance
BALANCE16_CTD	NULL	NUMBER	System	generated	balance
BALANCE16_BBD	NULL	NUMBER	System	generated	balance
BALANCE16_BBC	NULL	NUMBER	System	generated	balance
BALANCE17_DTD	NULL	NUMBER	System	generated	balance
BALANCE17_CTD	NULL	NUMBER	System	generated	balance
BALANCE17_BBD	NULL	NUMBER	System	generated	balance
BALANCE17_BBC	NULL	NUMBER	System	generated	balance
BALANCE18_DTD	NULL	NUMBER	System	generated	balance
BALANCE18_CTD	NULL	NUMBER	System	generated	balance
BALANCE18_BBD	NULL	NUMBER	System	generated	balance
BALANCE18_BBC	NULL	NUMBER	System	generated	balance
BALANCE19_DTD	NULL	NUMBER	System	generated	balance

Oracle Proprietary, Confidential Information--Use Restricted by Contract

BALANCE19_CTD	NULL	NUMBER	System	generated	balance
BALANCE19_BBD	NULL	NUMBER	System	generated	balance
BALANCE19_BBC	NULL	NUMBER	System	generated	balance
BALANCE20_DTD	NULL	NUMBER	System	generated	balance
BALANCE20_CTD	NULL	NUMBER	System	generated	balance
BALANCE20_BBD	NULL	NUMBER	System	generated	balance
BALANCE20_BBC	NULL	NUMBER	System	generated	balance
BALANCE21_DTD	NULL	NUMBER	System	generated	balance
BALANCE21_CTD	NULL	NUMBER	System	generated	balance
BALANCE21_BBD	NULL	NUMBER	System	generated	balance
BALANCE21_BBC	NULL	NUMBER	System	generated	balance
BALANCE22_DTD	NULL	NUMBER	System	generated	balance
BALANCE22_CTD	NULL	NUMBER	System	generated	balance
BALANCE22_BBD	NULL	NUMBER	System	generated	balance
BALANCE22_BBC	NULL	NUMBER	System	generated	balance
BALANCE23_DTD	NULL	NUMBER	System	generated	balance
BALANCE23_CTD	NULL	NUMBER	System	generated	balance
BALANCE23_BBD	NULL	NUMBER	System	generated	balance
BALANCE23_BBC	NULL	NUMBER	System	generated	balance
BALANCE24_DTD	NULL	NUMBER	System	generated	balance
BALANCE24_CTD	NULL	NUMBER	System	generated	balance
BALANCE24_BBD	NULL	NUMBER	System	generated	balance
BALANCE24_BBC	NULL	NUMBER	System	generated	balance
BALANCE25_DTD	NULL	NUMBER	System	generated	balance
BALANCE25_CTD	NULL	NUMBER	System	generated	balance
BALANCE25_BBD	NULL	NUMBER	System	generated	balance
BALANCE25_BBC	NULL	NUMBER	System	generated	balance
BALANCE26_DTD	NULL	NUMBER	System	generated	balance
BALANCE26_CTD	NULL	NUMBER	System	generated	balance
BALANCE26_BBD	NULL	NUMBER	System	generated	balance
BALANCE26_BBC	NULL	NUMBER	System	generated	balance
BALANCE27_DTD	NULL	NUMBER	System	generated	balance
BALANCE27_CTD	NULL	NUMBER	System	generated	balance
BALANCE27_BBD	NULL	NUMBER	System	generated	balance
BALANCE27_BBC	NULL	NUMBER	System	generated	balance
BALANCE28_DTD	NULL	NUMBER	System	generated	balance
BALANCE28_CTD	NULL	NUMBER	System	generated	balance
BALANCE28_BBD	NULL	NUMBER	System	generated	balance
BALANCE28_BBC	NULL	NUMBER	System	generated	balance
BALANCE29_DTD	NULL	NUMBER	System	generated	balance
BALANCE29_CTD	NULL	NUMBER	System	generated	balance
BALANCE29_BBD	NULL	NUMBER	System	generated	balance
BALANCE29_BBC	NULL	NUMBER	System	generated	balance
BALANCE30_DTD	NULL	NUMBER	System	generated	balance
BALANCE30_CTD	NULL	NUMBER	System	generated	balance
BALANCE30_BBD	NULL	NUMBER	System	generated	balance
BALANCE30_BBC	NULL	NUMBER	System	generated	balance
BALANCE31_DTD	NULL	NUMBER	System	generated	balance
BALANCE31_CTD	NULL	NUMBER	System	generated	balance
BALANCE31_BBD	NULL	NUMBER	System	generated	balance
BALANCE31_BBC	NULL	NUMBER	System	generated	balance
BALANCE32_DTD	NULL	NUMBER	System	generated	balance
BALANCE32_CTD	NULL	NUMBER	System	generated	balance
BALANCE32_BBD	NULL	NUMBER	System	generated	balance
BALANCE32_BBC	NULL	NUMBER	System	generated	balance
BALANCE33_DTD	NULL	NUMBER	System	generated	balance
BALANCE33_CTD	NULL	NUMBER	System	generated	balance

Oracle Proprietary, Confidential Information--Use Restricted by Contract

BALANCE33_BBD	NULL	NUMBER	System generated balance
BALANCE33_BBC	NULL	NUMBER	System generated balance
REQUEST_ID	NULL	NUMBER(15)	Standard
PROGRAM_ID	NULL	NUMBER(15)	Standard
PROGRAM_APPLICATION_ID	NULL	NUMBER(15)	Standard
PROGRAM_UPDATE_DATE	NULL	DATE	Standard
CREATED_BY	NULL	NUMBER(15)	Standard who column
CREATION_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column

Indexes

Index Name	Index Type	Sequence	Column Name
CN_SRP_PERIODS_U1	UNIQUE	1	SRP_PERIOD_ID
		3	ORG_ID
CN_SRP_PERIODS_U2	UNIQUE	5	SALESREP_ID
		6	ROLE_ID
		7	CREDIT_TYPE_ID
		8	PERIOD_ID

Sequences

Sequence	Derived Column
CN_SRP_PERIODS_S	SRP_PERIOD_ID

CN_SRP_PERIOD_QUOTAS_ALL

CN_SRP_PERIOD_QUOTAS stores period target and draw amounts assigned to a salesperson's plan element. You need one row for each period in which the salesperson's compensation plan is active.

The user cannot directly insert into or delete from this table. Rows are automatically created for each period that the salesperson's compensation plan is active. Rows are deleted when you delete the compensation plan assignment or reduce the active period range.

SRP_PERIOD_QUOTA_ID is the unique system generated primary key invisible to the user.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_PERIOD_STATUSES_ALL	PERIOD_ID	PERIOD_ID
CN_QUOTAS_ALL	QUOTA_ID	QUOTA_ID
CN_SRP_PLAN_ASSIGNS_ALL	SRP_PLAN_ASSIGN_ID	SRP_PLAN_ASSIGN_ID
CN_SRP_QUOTA_ASSIGNS_ALL	SRP_QUOTA_ASSIGN_ID	SRP_QUOTA_ASSIGN_ID

Column Descriptions

Name	Null?	Type	Description
SRP_PERIOD_QUOTA_ID (PK)	NOT NULL	NUMBER(15)	Unique identifier
SRP_PLAN_ASSIGN_ID	NOT NULL	NUMBER(15)	Salesperson plan assignment unique identifier
SRP_QUOTA_ASSIGN_ID	NOT NULL	NUMBER(15)	Salesperson plan element assignment unique identifier
SALESREP_ID	NOT NULL	NUMBER(15)	Salesperson unique identifier
PERIOD_ID	NOT NULL	NUMBER(15)	Unique identifier of period to which the target applies
QUOTA_ID	NOT NULL	NUMBER(15)	Plan element unique identifier
TARGET_AMOUNT	NOT NULL	NUMBER	Target
ITD_TARGET		NUMBER	Interval to date target
PERIOD_PAYMENT		NUMBER	Payment amount for this period
ITD_PAYMENT		NUMBER	Interval to date payment
COMMISSION_PAYED_PTD	NOT NULL	NUMBER	Commission paid period-to-date
COMMISSION_PAYED_ITD		NUMBER	Interval to date commission payed
INPUT_ACHIEVED_PTD		NUMBER	Input Achieved Period to date
INPUT_ACHIEVED_ITD		NUMBER	Input Achieved Interval to date
OUTPUT_ACHIEVED_PTD		NUMBER	Output Achieved Period to date
OUTPUT_ACHIEVED_ITD		NUMBER	Output Achieved Interval to date
PERF_ACHIEVED_PTD		NUMBER	Performance Achieved Period to Date
PERF_ACHIEVED_ITD		NUMBER	Performance Achieved Interval to date
ADVANCE_RECOVERED_PTD		NUMBER	Advance recovered PTD
ADVANCE_RECOVERED_ITD		NUMBER	Advance recovered ITD
ADVANCE_TO_REC_PTD		NUMBER	Advance to recover PTD
ADVANCE_TO_REC_ITD		NUMBER	Advance to recover ITD
COMM_PEND_PTD		NUMBER	Commission pending PTD
COMM_PEND_ITD		NUMBER	Commission pending ITD

Oracle Proprietary, Confidential Information--Use Restricted by Contract

RECOVERY_AMOUNT_PTD	NULL	NUMBER	Recovery Amount Period to date
RECOVERY_AMOUNT_ITD	NULL	NUMBER	Recovery Amount Interval to date
PERFORMANCE_GOAL_PTD	NULL	NUMBER	Period to date Performance Goal
PERFORMANCE_GOAL_ITD	NULL	NUMBER	Interval To Date performance goal
LAST_RATE_TIER_ID	NULL	NUMBER(15)	Last rate tier
LAST_RATES	NULL	NUMBER	Last commission rate
COMMISSION_PAYED_PTD_F	NULL	NUMBER	Forecast commission period-to-date
COMMISSION_PAYED_ITD_F	NULL	NUMBER	forecast commissioninterval-to-date
INPUT_ACHIEVED_PTD_F	NULL	NUMBER	Forecast Input Achieved Period to date
INPUT_ACHIEVED_ITD_F	NULL	NUMBER	Forecast Input Achieved Interval to date
OUTPUT_ACHIEVED_PTD_F	NULL	NUMBER	Forecast Output Achieved Period to date
OUTPUT_ACHIEVED_ITD_F	NULL	NUMBER	Forecast Output Achieved Interval to date
PERF_ACHIEVED_PTD_F	NULL	NUMBER	Forecast Performance Achieved Period to date
PERF_ACHIEVED_ITD_F	NULL	NUMBER	Forecast Performance Achieved Interval to date
CREATED_BY	NULL	NUMBER(15)	Standard who column
CREATION_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column
ORG_ID	NULL	NUMBER(15)	Organization Identifier

Indexes

Index Name	Index Type	Sequence	Column Name
CN_SRP_PERIOD_QUOTAS_N2	NOT UNIQUE	1	SRP_QUOTA_ASSIGN_ID
CN_SRP_PERIOD_QUOTAS_U1	UNIQUE	4	SRP_PERIOD_QUOTA_ID
		6	ORG_ID
CN_SRP_PERIOD_QUOTAS_U3	UNIQUE	1	SRP_PLAN_ASSIGN_ID
		2	QUOTA_ID
		3	PERIOD_ID

Sequences

Sequence	Derived Column
CN_SRP_PERIOD_QUOTAS_S	SRP_PERIOD_QUOTA_ID

CN_SRP_PER_QUOTA_RC_ALL

CN_SRP_PER_QUOTA_RC contains a salesperson's compensation information broken down by period and revenue class. You need one row for each revenue class a salesperson has been assigned in each period they have used it.

The user cannot directly insert into or delete from this table. Rows are automatically created when assigning a compensation plan to a salesperson, expanding the active period range, adding revenue classes to a plan element or adding a new plan element to a compensation plan. Rows are deleted in the converse situations.

SRP_PER_QUOTA_RC_ID is the unique system generated primary key invisible to the user.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_QUOTAS_ALL	QUOTA_ID	QUOTA_ID
CN_REVENUE_CLASSES_ALL	REVENUE_CLASS_ID	REVENUE_CLASS_ID
CN_SRP_PERIOD_QUOTAS_ALL	SRP_PERIOD_QUOTA_ID	SRP_PERIOD_QUOTA_ID
CN_SRP_PLAN_ASSIGNS_ALL	SRP_PLAN_ASSIGN_ID	SRP_PLAN_ASSIGN_ID

Column Descriptions

Name	Null?	Type	Description
ORG_ID	NULL	NUMBER(15)	Organization Identifier
SRP_PER_QUOTA_RC_ID (PK)	NOT NULL	NUMBER(15)	Primary key
SRP_PERIOD_QUOTA_ID	NOT NULL	NUMBER(15)	Unique identifier of the parent plan element/period
SRP_PLAN_ASSIGN_ID	NOT NULL	NUMBER(15)	Salesperson plan assignment unique identifier
REVENUE_CLASS_ID	NOT NULL	NUMBER(15)	Revenue class unique identifier
PERIOD_ID	NOT NULL	NUMBER(15)	Sales compensation period unique identifier
QUOTA_ID	NOT NULL	NUMBER(15)	Plan element unique identifier
SALESREP_ID	NOT NULL	NUMBER(15)	Salesperson unique identifier
TARGET_AMOUNT	NULL	NUMBER	Revenue class target amount
YEAR_TO_DATE	NOT NULL	NUMBER	Target achievement year-to-date
PERIOD_TO_DATE	NOT NULL	NUMBER	Target achievement period-to-date
CREATED_BY	NULL	NUMBER(15)	Standard who column
CREATION_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column
QUARTER_TO_DATE	NOT NULL	NUMBER	Target achievement quarter-to-date
PERIOD_TO_DATE_F	NULL	NUMBER	Forecasted period to date achievement
YEAR_TO_DATE_F	NULL	NUMBER	Forecasted year to date achievement

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Indexes

<u>Index Name</u>	<u>Index Type</u>	<u>Sequence</u>	<u>Column Name</u>
CN_SRP_PER_QUOTA_RC_N1	NOT UNIQUE	5	SRP_PLAN_ASSIGN_ID
		7	QUOTA_ID
		9	REVENUE_CLASS_ID
		11	PERIOD_ID
CN_SRP_PER_QUOTA_RC_U1	UNIQUE	1	SRP_PER_QUOTA_RC_ID
		3	ORG_ID

Sequences

<u>Sequence</u>	<u>Derived Column</u>
CN_SRP_PER_QUOTA_RC_S	SRP_PER_QUOTA_RC_ID

CN_SRP_PLAN_ASSIGNS_ALL

CN_SRP_PLAN_ASSIGNS contains information about the compensation plans assigned to a salesperson. You need one row for each compensation plan

for each range of periods over which the plan is active.

SRP_PLAN_ASSIGN_ID is the unique system generated primary key invisible to the user.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_COMP_PLANS_ALL	COMP_PLAN_ID	COMP_PLAN_ID
CN_ROLE_PLANS_ALL	ROLE_PLAN_ID	ROLE_PLAN_ID

Column Descriptions

Name	Null?	Type	Description
SRP_PLAN_ASSIGN_ID (PK)	NOT NULL	NUMBER(15)	Primary key
ROLE_PLAN_ID	NOT NULL	NUMBER(15)	Compensation role plan identifier
SRP_ROLE_ID	NOT NULL	NUMBER(15)	Foreign key to CN_SRP_ROLES
SALESREP_ID	NOT NULL	NUMBER(15)	Salesperson unique identifier
COMP_PLAN_ID	NOT NULL	NUMBER(15)	Compensation plan unique identifier
ROLE_ID	NULL	NUMBER(15)	Sales role for the salesrep on this compensation plan assignment
START_DATE	NOT NULL	DATE	Effective start date
END_DATE	NULL	DATE	Effective end date
CREATION_DATE	NULL	DATE	Standard who column
CREATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
ORG_ID	NULL	NUMBER(15)	Organization Identifier

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Indexes

<u>Index Name</u>	<u>Index Type</u>	<u>Sequence</u>	<u>Column Name</u>
CN_SRP_PLAN_ASSIGNS_N1	NOT UNIQUE	1	SALESREP_ID
CN_SRP_PLAN_ASSIGNS_N2	NOT UNIQUE	4	SRP_ROLE_ID
		5	ROLE_PLAN_ID
CN_SRP_PLAN_ASSIGNS_U1	UNIQUE	1	SRP_PLAN_ASSIGN_ID
		3	ORG_ID
CN_SRP_PLAN_ASSIGN_N3	NOT UNIQUE	1	COMP_PLAN_ID

Sequences

<u>Sequence</u>	<u>Derived Column</u>
CN_SRP_PLAN_ASSIGNS_S	SRP_PLAN_ASSIGN_ID

CN_SRP_QUOTA_ASSIGNS_ALL

CN_SRP_QUOTA_ASSIGNS contains information about the plan elements that have been assigned to a salesperson. You need one row for each plan element that belongs to the compensation plan.

Most values in this table are denormalized from the source plan element in table CN_QUOTAS. You can customize the TARGET or PAYMENT_AMOUNT by setting the CUSTOMIZED_FLAG TO 'Y' – these values are now 'local' and will not be changed by an update to the corresponding columns in CN_QUOTAS. When the plan element is not customized all changes to the record in CN_QUOTAS will be propagated to all occurrences of the plan element in CN_SRP_QUOTA_ASSIGNS

The user cannot directly insert into or delete from this table. Rows are automatically created when you assign a compensation plan to a salesperson and when you add a plan element to the source compensation plan. Rows are deleted when you delete the compensation plan assignment from CN_SRP_PLAN_ASSIGNS or the source record from CN_QUOTAS.

There are four types of plan element:

- Revenue Quota
- Revenue Non Quota
- Draw
- Manual
- Unit Quota
- Unit Non Quota
- Discount
- Margin

Revenue based plan elements do not use TARGET.

Draw plan elements store the draw amount in the PAYMENT_AMOUNT column.

They do not have revenue classes or a rate table. They do not use TARGET, PAYMENT_TYPE_CODE or RATE_SCHEDULE_ID

Manual plan elements do not have revenue classes, period targets or a rate table. They do not use TARGET, PAYMENT_TYPE_CODE, PAYMENT_AMOUNT, PERIOD_TARGET_UNIT_CODE or RATE_SCHEDULE_ID.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SRP_QUOTA_ASSIGN_ID is the unique system-generated primary key and is invisible to the user. Currently PERIOD_TARGET_DIST_RULE_CODE is invisible to the user and is always set to 'EQUAL'.

There are three types of period target unit: Period, Quarter and Year.

They determine how period target/draw values are displayed. Period displays values for each individual period, quarter displays the total for each quarter and year displays the total for the calendar year.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_QUOTAS_ALL	QUOTA_ID	QUOTA_ID
CN_RATE_SCHEDULES_ALL	RATE_SCHEDULE_ID	RATE_SCHEDULE_ID
CN_SRP_PLAN_ASSIGNS_ALL	SRP_PLAN_ASSIGN_ID	SRP_PLAN_ASSIGN_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
PERIOD_TARGET_UNIT_CODE	TIMESCALE	CN_LOOKUPS
	PERIOD	Period
	QUARTER	Quarter
	YEAR	Year
PERIOD_TYPE_CODE	TIMESCALE	CN_LOOKUPS
	PERIOD	Period
	QUARTER	Quarter
	YEAR	Year
QUOTA_TYPE_CODE	QUOTA_TYPE	CN_LOOKUPS
	DISCOUNT	Discount
	DRAW	Draw
	MANUAL	Manual
	MARGIN	Margin
	REVENUE	Revenue Quota
	TARGET	Revenue Non Quota
	UNIT_BASED_NON_QUOTA	Unit Non Quota
	UNIT_BASED_QUOTA	Unit Quota

Column Descriptions

Name	Null?	Type	Description
SRP_QUOTA_ASSIGN_ID (PK)	NOT NULL	NUMBER(15)	Primary key
SRP_PLAN_ASSIGN_ID	NOT NULL	NUMBER(15)	Salesperson compensation plan assignment unique identifier
QUOTA_ID	NOT NULL	NUMBER(15)	Source plan element unique identifier
RATE_SCHEDULE_ID	NULL	NUMBER(15)	Compensation rate table unique identifier
TARGET	NOT NULL	NUMBER	Salesperson's quota target amount
CUSTOMIZED_FLAG	NOT NULL	VARCHAR2(1)	Indicates whether the plan element information has been customized for this salesperson

PERIOD_TARGET_DIST_RULE_CODE	NOT NULL	VARCHAR2(30)	Defines how the total quota or draw amount is distributed over the compensation plan assignment's active periods
QUOTA_TYPE_CODE	NOT NULL	VARCHAR2(30)	The type of plan element
PAYMENT_AMOUNT	NULL	NUMBER	Salesperson's draw amount for draw type plan elements. For other element types is is the amount to which the percentage is applied if the payment type is "Payment Amount Percentage"
PERIOD_TYPE_CODE	NULL	VARCHAR2(30)	Period Type
PERIOD_TARGET_UNIT_CODE	NOT NULL	VARCHAR2(30)	Granularity with which you can view period targets.
DISC_RATE_SCHEDULE_ID	NULL	NUMBER(15)	Compensation discount rate table unique identifier
PAYEE_SALESREP_ID	NULL	NUMBER(15)	Not Currently used
SHARED_ACC_SALESREP_ID	NULL	NUMBER(15)	Not currently used
PERFORMANCE_GOAL	NULL	NUMBER	Performance Goal
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
CREATED_BY	NULL	NUMBER(15)	Standard who column
CREATION_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column
ORG_ID	NULL	NUMBER(15)	Organization Identifier

Indexes

Index Name	Index Type	Sequence	Column Name
CN_SRP_QUOTA_ASSIGNS_U1	UNIQUE	1	SRP_QUOTA_ASSIGN_ID
		3	ORG_ID
CN_SRP_QUOTA_ASSIGNS_U2	UNIQUE	1	SRP_PLAN_ASSIGN_ID
		2	QUOTA_ID

Sequences

Sequence	Derived Column
CN_SRP_QUOTA_ASSIGNS_S	SRP_QUOTA_ASSIGN_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CN_SRP_QUOTA_RULES_ALL

CN_SRP_QUOTA_RULES stores information about the revenue classes assigned to a salesperson's plan element. You need one row for each revenue class assigned to a plan element.

The revenue class and target information are denormalized from the source record in CN_QUOTA_RULES. You can customize the target providing the column CUSTOMIZED_FLAG in CN_SRP_QUOTA_ASSIGNS is set to 'Y'.

The user cannot directly insert into or delete from this table. Rows are automatically created when you assign a compensation plan to a salesperson and when you add a revenue class to the plan element in CN_QUOTAS. Rows are deleted when you delete the compensation plan assignment or the source record in CN_QUOTA_RULES.

SRP_QUOTA_RULE_ID is the unique system generated primary key invisible to the user.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CN_QUOTA_RULES_ALL	QUOTA_RULE_ID	QUOTA_RULE_ID
CN_REVENUE_CLASSES_ALL	REVENUE_CLASS_ID	REVENUE_CLASS_ID
CN_SRP_PLAN_ASSIGNS_ALL	SRP_PLAN_ASSIGN_ID	SRP_PLAN_ASSIGN_ID
CN_SRP_QUOTA_ASSIGNS_ALL	SRP_QUOTA_ASSIGN_ID	SRP_QUOTA_ASSIGN_ID

Column Descriptions

Name	Null?	Type	Description
ORG_ID	NULL	NUMBER(15)	Organization Identifier
SRP_QUOTA_RULE_ID (PK)	NOT NULL	NUMBER(15)	Primary key
SRP_PLAN_ASSIGN_ID	NOT NULL	NUMBER(15)	Salesperson compensation plan assignment unique identifier
SRP_QUOTA_ASSIGN_ID	NOT NULL	NUMBER(15)	Salesperson plan element unique identifier
QUOTA_RULE_ID	NOT NULL	NUMBER(15)	Source quota rule record unique identifier
REVENUE_CLASS_ID	NOT NULL	NUMBER(15)	Revenue class unique identifier
TARGET	NULL	NUMBER	Revenue class target
PAYMENT_AMOUNT	NULL	NUMBER	Payment Amount
PERFORMANCE_GOAL	NULL	NUMBER	Performance Goal
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
CREATION_DATE	NULL	DATE	Standard who column
CREATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_DATE	NULL	DATE	Standard who column
LAST_UPDATED_BY	NULL	NUMBER(15)	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard who column

Indexes

Index Name	Index Type	Sequence	Column Name
CN_SRP_QUOTA_RULES_N1	NOT UNIQUE	1	SRP_PLAN_ASSIGN_ID
		2	SRP_QUOTA_ASSIGN_ID
CN_SRP_QUOTA_RULES_N2	NOT UNIQUE	4	SRP_PLAN_ASSIGN_ID
		6	QUOTA_RULE_ID
CN_SRP_QUOTA_RULES_N3	NOT UNIQUE	3	REVENUE_CLASS_ID
CN_SRP_QUOTA_RULES_U1	UNIQUE	1	SRP_QUOTA_RULE_ID
		3	ORG_ID

Sequences

Sequence	Derived Column
CN_SRP_QUOTA_RULES_S1	SRP_QUOTA_RULE_ID

CS_INCIDENTS_ALL_B

CS_INCIDENTS_ALL_B stores information about service requests. A service request can be logged against any product, any product in inventory, or any product in the install base. Each row contains information about a single service request. This table is partitioned by ORG_ID in a multi-organizational environment. This is the multi-language support base table and contains all of the fields from this table that are not translatable.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CSS_DEF_LANGUAGES_B	LANGUAGE_ID	LANGUAGE_ID
CSS_DEF_PLATFORMS_B	PLATFORM_ID	PLATFORM_ID
CSS_DEF_PLAT_VERSIONS	PLATFORM_VERSION_ID	PLATFORM_VERSION_ID
CS_CP_REVISIONS	CP_REVISION_ID	CP_COMPONENT_VERSION_ID
CS_CP_REVISIONS	CP_REVISION_ID	CP_SUBCOMPONENT_VERSION_ID
CS_CP_REVISIONS	CP_REVISION_ID	CP_REVISION_ID
CS_CP_SERVICES_ALL_OBSOLETE	CP_SERVICE_ID	CONTRACT_SERVICE_ID
CS_CUSTOMER_PRODUCTS_ALL	CUSTOMER_PRODUCT_ID	CUSTOMER_PRODUCT_ID
CS_CUSTOMER_PRODUCTS_ALL	CUSTOMER_PRODUCT_ID	CP_COMPONENT_ID
CS_CUSTOMER_PRODUCTS_ALL	CUSTOMER_PRODUCT_ID	CP_SUBCOMPONENT_ID
CS_INCIDENT_SEVERITIES_B	INCIDENT_SEVERITY_ID	INCIDENT_SEVERITY_ID
CS_INCIDENT_STATUSES_B	INCIDENT_STATUS_ID	INCIDENT_STATUS_ID
CS_INCIDENT_TYPES_B	INCIDENT_TYPE_ID	INCIDENT_TYPE_ID
CS_INCIDENT_URGENCIES_B	INCIDENT_URGENCY_ID	INCIDENT_URGENCY_ID
CS_TIME_ZONES	TIME_ZONE_ID	TIME_ZONE_ID
FND_LOOKUP_VALUES	LOOKUP_CODE	PROBLEM_CODE
FND_LOOKUP_VALUES	LOOKUP_CODE	RESOLUTION_CODE
HZ_CUST_ACCOUNTS	CUST_ACCOUNT_ID	ACCOUNT_ID
HZ_CUST_ACCOUNTS	CUST_ACCOUNT_ID	ACCOUNT_ID
HZ_CUST_SITE_USES_ALL	SITE_USE_ID	BILL_TO_SITE_USE_ID
HZ_CUST_SITE_USES_ALL	SITE_USE_ID	SHIP_TO_SITE_USE_ID
HZ_CUST_SITE_USES_ALL	SITE_USE_ID	INSTALL_SITE_USE_ID
HZ_PARTIES	PARTY_ID	CUSTOMER_ID
HZ_PARTIES	PARTY_ID	BILL_TO_CONTACT_ID
HZ_PARTIES	PARTY_ID	SHIP_TO_CONTACT_ID
HZ_PARTY_SITE_USES	PARTY_SITE_ID	SITE_ID
HZ_PARTY_SITE_USES	PARTY_SITE_ID	CUSTOMER_SITE_ID
HZ_TIMEZONES	TIMEZONE_ID	TIME_ZONE_ID
JTF_RESOURCE_SUBTYPES_B	RESOURCE_SUBTYPE_ID	RESOURCE_SUBTYPE_ID
JTF_RS_GROUPS_B	GROUP_ID	INCIDENT_OWNER_ID
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	INCIDENT_OWNER_ID
JTF_RS_TEAMS_B	TEAM_ID	INCIDENT_OWNER_ID
JTF_TERR_RSC_ALL	RESOURCE_ID	INCIDENT_OWNER_ID
	TERR_ID	TERRITORY_ID
MTL_SYSTEM_ITEMS_B	INVENTORY_ITEM_ID	INVENTORY_ITEM_ID
MTL_SYSTEM_ITEMS_B	INVENTORY_ITEM_ID	INV_COMPONENT_ID
MTL_SYSTEM_ITEMS_B	INVENTORY_ITEM_ID	INV_SUBCOMPONENT_ID
OKC_K_LINES_B	ID	CONTRACT_SERVICE_ID
PER_ALL_PEOPLE_F	PERSON_ID	EMPLOYEE_ID
QA_PLANS	PLAN_ID	QA_COLLECTION_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
PROBLEM_CODE	REQUEST_PROBLEM_CODE	CS_LOOKUPS
RESOLUTION_CODE	REQUEST_RESOLUTION_CODE	CS_LOOKUPS

Column Descriptions

Name	Null?	Type	Description
INCIDENT_ID (PK)	NOT NULL	NUMBER(15)	Service request identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard Who column
INCIDENT_NUMBER	NOT NULL	VARCHAR2(64)	Service request number
INCIDENT_DATE	NULL	DATE	Service request date
INCIDENT_STATUS_ID	NOT NULL	NUMBER(15)	Identifier for service request status
INCIDENT_TYPE_ID	NOT NULL	NUMBER(15)	Identifier for service request type
INCIDENT_URGENCY_ID	NULL	NUMBER(15)	Identifier for service request urgency
INCIDENT_SEVERITY_ID	NOT NULL	NUMBER(15)	Identifier for service request severity
INCIDENT_OWNER_ID	NOT NULL	NUMBER(15)	Identifier for the owner of the service request
RESOURCE_TYPE	NULL	VARCHAR2(30)	Identifier for the owner type of the service request. The owner type could be an Employee, a Group or a Team.
RESOURCE_SUBTYPE_ID	NULL	NUMBER	Not used.
INVENTORY_ITEM_ID	NULL	NUMBER(15)	Item identifier
CUSTOMER_ID	NULL	NUMBER(15)	Customer identifier
ACCOUNT_ID	NULL	NUMBER	Account Identifier
BILL_TO_SITE_USE_ID	NULL	NUMBER(15)	Identifier for bill-to site use
PURCHASE_ORDER_NUM	NULL	VARCHAR2(50)	Purchase order number
EMPLOYEE_ID	NULL	NUMBER(15)	Identifier for the employee if the service request is made by an employee
FILED_BY_EMPLOYEE_FLAG	NULL	VARCHAR2(1)	Indicates whether the request was made by an employee
SHIP_TO_SITE_USE_ID	NULL	NUMBER(15)	Identifier for ship- to site use
PROBLEM_CODE	NULL	VARCHAR2(50)	Problem code
EXPECTED_RESOLUTION_DATE	NULL	DATE	Expected date for the problem resolution
ACTUAL_RESOLUTION_DATE	NULL	DATE	Actual date of resolution
CUSTOMER_PRODUCT_ID	NULL	NUMBER(15)	Customer product identifier
INSTALL_SITE_USE_ID	NULL	NUMBER(15)	Identifier for installed site use
BILL_TO_CONTACT_ID	NULL	NUMBER(15)	Bill-to contact identifier
SHIP_TO_CONTACT_ID	NULL	NUMBER(15)	Ship-to contact identifier
CURRENT_SERIAL_NUMBER	NULL	VARCHAR2(30)	Product serial number for product not in installed base
CUSTOMER_NUMBER	NULL	VARCHAR2(30)	Customer number for non-verified requests
SYSTEM_ID	NULL	NUMBER(15)	Not used

Oracle Proprietary, Confidential Information--Use Restricted by Contract

INCIDENT_ATTRIBUTE_1	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_2	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_3	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_6	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_ATTRIBUTE_15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
INCIDENT_CONTEXT	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
RECORD_IS_VALID_FLAG	NULL	VARCHAR2(1)	Flag to denote if the service request is verified or not
RESOLUTION_CODE	NULL	VARCHAR2(50)	Problem resolution quick code
ORG_ID	NULL	NUMBER	Operating unit identifier
ORIGINAL_ORDER_NUMBER	NULL	NUMBER	Order number for the product if installed base is not used
WORKFLOW_PROCESS_ID	NULL	NUMBER	Sequence number used for this action's last workflow process
CLOSE_DATE	NULL	DATE	Date the service request is closed
PUBLISH_FLAG	NULL	VARCHAR2(1)	Flag to denote whether the service request is published or not.
INTERFACED_TO_DEPOT_FLAG	NULL	VARCHAR2(1)	Flag to denote service request is linked to repairs
QA_COLLECTION_ID	NULL	NUMBER	Foreign key to Quality results table
CONTRACT_SERVICE_ID	NULL	NUMBER	Service line unique identifier
KB_TYPE	NULL	VARCHAR2(15)	Not used.
KB_SOLUTION_ID	NULL	VARCHAR2(240)	External knowledge base solution identifier.
TIME_ZONE_ID	NULL	NUMBER(15)	This field stores the time zone id of the time zone specified in the field service request form
TIME_DIFFERENCE	NULL	NUMBER	GMT offset of the contact person's time.
CUSTOMER_PO_NUMBER	NULL	VARCHAR2(50)	Customers Purchase Order number.
OWNER_GROUP_ID	NULL	NUMBER	Not used

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CUSTOMER_TICKET_NUMBER	NULL	VARCHAR2(50)	Customer's internal helpdesk tracking number.
OBLIGATION_DATE	NULL	DATE	Obligation Date
SITE_ID	NULL	NUMBER	Identifier for Support Site.
CUSTOMER_SITE_ID	NULL	NUMBER	Identifier for Customer Site.
CALLER_TYPE	NOT NULL	VARCHAR2(30)	Type of the Calling Party. It could be an Organization, Person, Employee.
PLATFORM_VERSION_ID	NULL	NUMBER	Identifier for Platform Version.
OBJECT_VERSION_NUMBER	NULL	NUMBER(9)	Sequential number used for database locking control when using HTML as a user interface
CP_COMPONENT_ID	NULL	NUMBER	Identifier for Installed Base Component.
CP_COMPONENT_VERSION_ID	NULL	NUMBER	Identifier for Installed Base Component Revision.
CP_SUBCOMPONENT_ID	NULL	NUMBER	Identifier for Installed Base Subcomponent.
CP_SUBCOMPONENT_VERSION_ID	NULL	NUMBER	Identifier for Installed Base Subcomponent Revision.
PLATFORM_ID	NULL	NUMBER	Identifier for Platform.
LANGUAGE_ID	NULL	NUMBER	Identifier for the Product's Language.
TERRITORY_ID	NULL	NUMBER	Identifier for the Territory of the Service Request.
CP_REVISION_ID	NULL	NUMBER	Identifier for Installed Base Product Revision.
INV_ITEM_REVISION	NULL	VARCHAR2(3)	Identifier for the Item Revision for a product not in Installed Base.
INV_COMPONENT_ID	NULL	NUMBER	Identifier for the Component for a product not in Installed Base.
INV_COMPONENT_VERSION	NULL	VARCHAR2(3)	Identifier for the Component Revision for a product not in Installed Base.
INV_SUBCOMPONENT_ID	NULL	NUMBER	Identifier for the Subcomponent for a product not in Installed Base.
INV_SUBCOMPONENT_VERSION	NULL	VARCHAR2(3)	Identifier for the Subcomponent Revision for a product not in Installed Base.
PROJECT_ID	NULL	NUMBER	This column is not currently used.
TASK_ID	NULL	NUMBER	This column is not currently used.
INV_ORGANIZATION_ID	NULL	NUMBER	This field stores the inventory organization id based on the profile AS_PRODUCT_ORGANIZATION_ID.
SECURITY_GROUP_ID	NULL	NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
CS_INCIDENTS_N1	NOT UNIQUE	4	INVENTORY_ITEM_ID
CS_INCIDENTS_N12	NOT UNIQUE	2	CLOSE_DATE
		5	EXPECTED_RESOLUTION_DATE
CS_INCIDENTS_N13	NOT UNIQUE	2	EXPECTED_RESOLUTION_DATE
		5	CLOSE_DATE
CS_INCIDENTS_N2	NOT UNIQUE	2	CUSTOMER_ID
CS_INCIDENTS_N3	NOT UNIQUE	2	INCIDENT_OWNER_ID
		4	INCIDENT_STATUS_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CS_INCIDENTS_N4	NOT UNIQUE	1	INCIDENT_STATUS_ID
		3	INCIDENT_OWNER_ID
CS_INCIDENTS_N5	NOT UNIQUE	1	INCIDENT_TYPE_ID
CS_INCIDENTS_N6	NOT UNIQUE	1	INCIDENT_URGENCY_ID
CS_INCIDENTS_N7	NOT UNIQUE	1	INCIDENT_SEVERITY_ID
CS_INCIDENTS_N8	NOT UNIQUE	1	CUSTOMER_PRODUCT_ID
CS_INCIDENTS_N9	NOT UNIQUE	1	INCIDENT_DATE
CS_INCIDENTS_U1	UNIQUE	5	INCIDENT_ID
CS_INCIDENTS_U2	UNIQUE	2	INCIDENT_NUMBER

Sequences

<u>Sequence</u>	<u>Derived Column</u>
CS_INCIDENTS_S	INCIDENT_ID
CS_INCIDENTS_NUMBER_S	INCIDENT_NUMBER
CS_WF_PROCESS_ID_S	WORKFLOW_PROCESS_ID

CS_INCIDENTS_ALL_TL

This table stores information about service requests made by customers. A service request can be logged against any product, or a product in the installed base. Each row contains information about a single service request. ORG_ID partitions data in this table by organization in a multi-organization environment.

The primary key for this table is INCIDENT_ID.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CS_INCIDENTS_ALL_B	INCIDENT_ID	INCIDENT_ID
FND_LANGUAGES	LANGUAGE_CODE	LANGUAGE
FND_LANGUAGES	LANGUAGE_CODE	SOURCE_LANG

Column Descriptions

Name	Null?	Type	Description
INCIDENT_ID (PK)	NOT NULL	NUMBER(15)	Service request identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard Who column
SUMMARY	NOT NULL	VARCHAR2(80)	Service request summary
SR_CREATION_CHANNEL	NULL	VARCHAR2(50)	Source of channel through which a Service Request is created. The channel of creation.
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Language of Text. The language to which things are translated.
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language from which things are translated.
SECURITY_GROUP_ID	NULL	NUMBER	Used in hosted environments

Sequences

Sequence	Derived Column
CS_INCIDENTS_S	INCIDENT_ID

CS_INCIDENT_SEVERITIES_B

CS_INCIDENT_SEVERITIES_B contains information about severities defined for service requests. This is the multi-language support base table and contains all of the fields from this table that are not translatable.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CSS_DEF_SEVERITIES_B	SEVERITY_ID	DEFECT_SEVERITY_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
INCIDENT_SUBTYPE	INCIDENT_SUBTYPE	CS_LOOKUPS
	ACT	Action
	INC	Service request

Column Descriptions

Name	Null?	Type	Description
INCIDENT_SEVERITY_ID (PK)	NOT NULL	NUMBER(15)	Identifies severity uniquely
INCIDENT_SUBTYPE	NOT NULL	VARCHAR2(30)	For lli, is set to INC and identifies that the severity is for service requests.
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
LAST_UPDATE_LOGIN		NUMBER(15)	Standard Who column
IMPORTANCE_LEVEL	NOT NULL	NUMBER(2)	A numeric identifier to indicate the Level of importance associated with this severity.
DISPLAY_COLOR		VARCHAR2(30)	The name of the Visual attribute used to set the Text color of the severity field in the Service requests form. The visual attribute can be selected from a defined color palette form only.
RGB_COLOR		VARCHAR2(20)	The RGB value of color for use by non-forms clients only
START_DATE_ACTIVE		DATE	Date this severity becomes active, if limited
END_DATE_ACTIVE		DATE	Date this severity becomes inactive, if limited
SEDED_FLAG		VARCHAR2(1)	Flag indicating pre-defined severity
DEFECT_SEVERITY_ID		NUMBER	This is the SEVERITY_ID in the Defects module which corresponds to this Severity.
ATTRIBUTE1		VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2		VARCHAR2(150)	Descriptive flexfield segment column

ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
CONTEXT	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
OBJECT_VERSION_NUMBER	NULL	NUMBER(9)	Sequential number used for database locking control when using HTML as a user interface
SECURITY_GROUP_ID	NULL	NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
CS_INCIDENT_SEVERITY_B_N1	NOT UNIQUE	2	INCIDENT_SUBTYPE
CS_INCIDENT_SEVERITY_B_U1	UNIQUE	1	INCIDENT_SEVERITY_ID

Sequences

Sequence	Derived Column
CS_INCIDENT_SEVERITIES_S	INCIDENT_SEVERITY_ID

CS_INCIDENT_SEVERITIES_TL

CS_INCIDENT_SEVERITIES_TL contains information about severities defined for service requests. This is the multi-language support translation table and contains all of the fields from this table that are translatable.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CS_INCIDENT_SEVERITIES_B	INCIDENT_SEVERITY_ID	INCIDENT_SEVERITY_ID
FND_LANGUAGES	LANGUAGE_CODE	LANGUAGE
FND_LANGUAGES	LANGUAGE_CODE	SOURCE_LANG

Column Descriptions

Name	Null?	Type	Description
INCIDENT_SEVERITY_ID (PK)	NOT NULL	NUMBER(15)	Severity unique identifier
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Language of Text. The language to which things are translated.
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language from which things are translated.
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
LAST_UPDATE_LOGIN		NUMBER(15)	Standard Who column
DESCRIPTION		VARCHAR2(240)	Severity description
NAME	NOT NULL	VARCHAR2(30)	The name given to this Severity.
SECURITY_GROUP_ID		NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
CS_INCIDENT_SEVERITY_TL_N1	NOT UNIQUE	4	NAME
		5	LANGUAGE
CS_INCIDENT_SEVERITY_TL_U1	UNIQUE	3	INCIDENT_SEVERITY_ID
		4	LANGUAGE

Sequences

Sequence	Derived Column
CS_INCIDENT_SEVERITIES_S	INCIDENT_SEVERITY_ID

CS_INCIDENT_STATUSES_B

CS_INCIDENT_STATUSES_B contains information about statuses defined for service requests. This is the multi-language support base table and contains all of the fields from this table that are not translatable.

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
INCIDENT_SUBTYPE	INCIDENT_SUBTYPE	CS_LOOKUPS
	ACT	Action
	INC	Service request

Column Descriptions

Name	Null?	Type	Description
INCIDENT_STATUS_ID (PK)	NOT NULL	NUMBER(15)	Status unique identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard Who column
INCIDENT_SUBTYPE	NOT NULL	VARCHAR2(30)	Identifies whether the status is a service request status or action status. For lli always 'INC'
SEEDED_FLAG	NULL	VARCHAR2(1)	Flag indicating pre-defined status
STATUS_CODE	NULL	VARCHAR2(32)	Not used
CLOSE_FLAG	NULL	VARCHAR2(1)	Indicates whether service requests having this status are closed
DISPLAY_COLOR	NULL	VARCHAR2(30)	The name of the Visual attribute used to set the Text color of the status field in the Service requests form. Visual attribute can be selected from a pre-defined set via a color palette form only.
RGB_COLOR	NULL	VARCHAR2(20)	The RGB value of color for use by non-forms clients only
START_DATE_ACTIVE	NULL	DATE	Date this status becomes active, if limited
END_DATE_ACTIVE	NULL	DATE	Date this status becomes inactive, if limited
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
CONTEXT	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
DISALLOW_REQUEST_UPDATE	NULL	VARCHAR2(1)	Service Request update not allowed
DISALLOW_NEW_ACTION	NULL	VARCHAR2(1)	New Actions not allowed
DISALLOW_ACTION_UPDATE	NULL	VARCHAR2(1)	Action update not allowed.
DISALLOW_NEW_CHARGE	NULL	VARCHAR2(1)	New charges not allowed
DISALLOW_AGENT_DISPATCH	NULL	VARCHAR2(1)	Agent Dispatch not allowed
DISALLOW_RMA	NULL	VARCHAR2(1)	RMA not allowed
DISALLOW_CHARGE_UPDATE	NULL	VARCHAR2(1)	Charges update not allowed
DISALLOW_PRODUCT_UPDATE	NULL	VARCHAR2(1)	For a given status, if this flag is yes, 'Y', do not allow the product to be updatable on the Service Request form.
OBJECT_VERSION_NUMBER	NULL	NUMBER(9)	Sequential number used for database locking control when using HTML as a user interface
SECURITY_GROUP_ID	NULL	NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
CS_INCIDENT_STATUS_B_N1	NOT UNIQUE	4	INCIDENT_SUBTYPE
CS_INCIDENT_STATUS_B_U1	UNIQUE	2	INCIDENT_STATUS_ID

Sequences

Sequence	Derived Column
CS_INCIDENT_STATUSES_S	INCIDENT_STATUS_ID

CS_INCIDENT_STATUSES_TL

CS_INCIDENT_STATUSES_TL contains information about statuses defined for service requests.This is the multi-language support translation table and contains all of the fields from this table that are translatable.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CS_INCIDENT_STATUSES_B	INCIDENT_STATUS_ID	INCIDENT_STATUS_ID
FND_LANGUAGES	LANGUAGE_CODE	LANGUAGE
FND_LANGUAGES	LANGUAGE_CODE	SOURCE_LANG

Column Descriptions

Name	Null?	Type	Description
INCIDENT_STATUS_ID (PK)	NOT NULL	NUMBER(15)	Status unique identifier
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Language of Text. The language to which things are translated.
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language from which things are translated.
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
LAST_UPDATE_LOGIN	NUL	NUMBER(15)	Standard Who column
NAME	NOT NULL	VARCHAR2(30)	Status name
DESCRIPTION	NUL	VARCHAR2(240)	Status description
SECURITY_GROUP_ID	NUL	NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
CS_INCIDENT_STATUS_TL_N1	NOT UNIQUE	4	NAME
		5	LANGUAGE
CS_INCIDENT_STATUS_TL_U1	UNIQUE	4	INCIDENT_STATUS_ID
		5	LANGUAGE

Sequences

Sequence	Derived Column
CS_INCIDENT_STATUSES_S	INCIDENT_STATUS_ID

CS_INCIDENT_TYPES_B

CS_INCIDENT_TYPES_B contains information about type codes defined for service requests. This is the multi-language support base table and contains all of the fields from this table that are not translatable.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CS_BUSINESS_PROCESSES	BUSINESS_PROCESS_ID	BUSINESS_PROCESS_ID
CS_INCIDENT_TYPES_B	INCIDENT_TYPE_ID	PARENT_INCIDENT_TYPE_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
INCIDENT_SUBTYPE	INCIDENT_SUBTYPE	CS_LOOKUPS
	ACT	Action
	INC	Service request

Column Descriptions

Name	Null?	Type	Description
INCIDENT_TYPE_ID (PK)	NOT NULL	NUMBER(15)	Type unique identifier
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard Who column
INCIDENT_SUBTYPE	NOT NULL	VARCHAR2(30)	For 11i, it will always be 'INC'. Identifies that the type is a service request
SEEDED_FLAG	NULL	VARCHAR2(1)	Flag if 'Y' indicates that this type is a pre-defined one
PARENT_INCIDENT_TYPE_ID	NULL	NUMBER(15)	Not used
START_DATE_ACTIVE	NULL	DATE	Date this type becomes active, if limited
END_DATE_ACTIVE	NULL	DATE	Date this type becomes inactive, if limited
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment column
CONTEXT	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
ABORT_WORKFLOW_CLOSE_FLAG	NULL	VARCHAR2(1)	If yes, 'Y', abort workflow if the Service Request is closed.
WORKFLOW	NULL	VARCHAR2(30)	Name of the workflow process associated with this type
WEB_ENTRY_FLAG	NULL	VARCHAR2(1)	Indicates whether this type is also used for Web entry. Not Used
WEB_WORKFLOW	NULL	VARCHAR2(30)	Not used
BUSINESS_PROCESS_ID	NULL	NUMBER(15)	Identifies the transaction group associated with this type
TASK_WORKFLOW	NULL	VARCHAR2(30)	Not used
WEIGHT	NULL	NUMBER	Not Used
WEB_IMAGE_FILENAME	NULL	VARCHAR2(80)	Not used
OBJECT_VERSION_NUMBER	NULL	NUMBER(9)	Sequential number used for database locking control when using HTML as a user interface
AUTOLAUNCH_WORKFLOW_FLAG	NULL	VARCHAR2(1)	If yes, 'Y', launch workflow from the Service Request automatically
SECURITY_GROUP_ID	NULL	NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
CS_INCIDENT_TYPES_B_N1	NOT UNIQUE	4	INCIDENT_SUBTYPE
CS_INCIDENT_TYPES_B_U1	UNIQUE	2	INCIDENT_TYPE_ID

Sequences

Sequence	Derived Column
CS_INCIDENT_TYPES_S	INCIDENT_TYPE_ID

CS_INCIDENT_TYPES_TL

CS_INCIDENT_TYPES_TL contains information about type codes defined for service requests. This is the multi-language support translation table and contains all of the fields from this table that are translatable.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
CS_INCIDENT_TYPES_B	INCIDENT_TYPE_ID	INCIDENT_TYPE_ID
FND_LANGUAGES	LANGUAGE_CODE	LANGUAGE
FND_LANGUAGES	LANGUAGE_CODE	SOURCE_LANG

Column Descriptions

Name	Null?	Type	Description
INCIDENT_TYPE_ID (PK)	NOT NULL	NUMBER(15)	Type unique identifier
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Language of Text. The language to which things are translated.
SOURCE_LANG	NOT NULL	VARCHAR2(4)	Language from which things are translated.
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who column - with the user id from FND_USER
LAST_UPDATE_LOGIN		NUMBER(15)	Standard Who column
NAME	NOT NULL	VARCHAR2(30)	A name given to Urgency.
DESCRIPTION		VARCHAR2(240)	Type description
SECURITY_GROUP_ID		NUMBER	Used in hosted environments

Indexes

Index Name	Index Type	Sequence	Column Name
CS_INCIDENT_TYPE_TL_N1	NOT UNIQUE	4	NAME
		5	LANGUAGE
CS_INCIDENT_TYPE_TL_U1	UNIQUE	4	INCIDENT_TYPE_ID
		5	LANGUAGE

Sequences

Sequence	Derived Column
CS_INCIDENT_TYPES_S	INCIDENT_TYPE_ID

EDW_BIL_COMP_PLANS_M

Column Descriptions

Name	Null?	Type	Description
ELMNT_PLAN_ELEMENT_ID_PK	NOT NULL	NUMBER	
ELMNT_PLAN_ELEMENT_ID_PK_KEY	NOT NULL	NUMBER	
ELMNT_PK_ROWID	NULL	VARCHAR2(20)	
ELMNT_DP	NULL	VARCHAR2(240)	
ELMNT_TYPE	NOT NULL	VARCHAR2(4)	Type of compensation element - 'B'-bonus 'Q'-quota 'O'-other
ELMNT_NAME	NULL	VARCHAR2(240)	
ELMNT_DESCRIPTION	NULL	VARCHAR2(77)	Compensation element description
ELMNT_INSTANCE	NULL	VARCHAR2(40)	
ELMNT_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
CPLN_COMP_PLAN_ID_PK	NOT NULL	NUMBER(15)	
CPLN_COMP_PLAN_ID_PK_KEY	NOT NULL	NUMBER(15)	
CPLN_DP	NULL	VARCHAR2(240)	
CPLN_PK_ROWID	NULL	VARCHAR2(20)	
CPLN_NAME	NOT NULL	VARCHAR2(30)	
CPLN_DESCRIPTION	NULL	VARCHAR2(1900)	
CPLN_STATUS	NOT NULL	VARCHAR2(30)	
CPLN_COMP_PLAN	NULL	VARCHAR2(100)	
CPLN_QUOTA_NAME	NOT NULL	VARCHAR2(30)	
CPLN_QUOTA_DESCRIPTION	NULL	VARCHAR2(1900)	
CPLN_QUOTA_TYPE	NOT NULL	VARCHAR2(30)	
CPLN_QUOTA_INTERVAL_TYPE	NULL	NUMBER(15)	
CPLN_QUOTA_CREDIT_TYPE	NULL	NUMBER(15)	
CPLN_QUOTA_TARGET	NOT NULL	NUMBER	
CPLN_QUOTA_PERIOD_TYPE	NULL	VARCHAR2(30)	
CPLN_QUOTA_INCENTIVE_TYPE	NULL	VARCHAR2(30)	
CPLN_QUOTA_PERFORMANCE_GOAL	NULL	NUMBER(15)	
CPLN_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CPLN_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
CPLN_USER_ATTRIBUTE10	NULL	VARCHAR2(240)
CPLN_USER_ATTRIBUTE11	NULL	VARCHAR2(240)
CPLN_USER_ATTRIBUTE12	NULL	VARCHAR2(240)
CPLN_USER_ATTRIBUTE13	NULL	VARCHAR2(240)
CPLN_USER_ATTRIBUTE14	NULL	VARCHAR2(240)
CPLN_USER_ATTRIBUTE15	NULL	VARCHAR2(240)
ALL_ALL_PK	NULL	VARCHAR2(40)
ALL_ALL_PK_KEY	NULL	NUMBER
ALL_ALL_ROWID	NULL	VARCHAR2(20)
ALL_ALL_NAME	NULL	VARCHAR2(80)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

EDW_BIL_COMP_PRF_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_COMP_PLANS_M	ELMNT_PLAN_ELEMENT_ID_PK_KEY	PLAN_ELEMENT_ID_PK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY

Column Descriptions

Name	Null?	Type	Description
COMP_PERF_SUM_PK	NULL	VARCHAR2(240)	
COMP_PERF_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
PLAN_ELEMENT_ID_PK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
QUOTA_AMOUNT_T	NULL	NUMBER	Quota monetary amount
QUOTA_AMOUNT_S	NULL	NUMBER	Quota monetary amount
QUOTA_AMOUNT_G	NULL	NUMBER	Quota monetary amount
QUOTA_ACHIEVED_T	NULL	NUMBER	
QUOTA_ACHIEVED_S	NULL	NUMBER	
QUOTA_ACHIEVED_G	NULL	NUMBER	
SALES_CYCLE	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

EDW_BIL_CPLNS_A_LTC

Column Descriptions

Name	Null?	Type	Description
ALL_PK	NULL	VARCHAR2 (40)	
ALL_PK_KEY	NULL	NUMBER	
ALL_PK_ROW_ID	NULL	VARCHAR2 (20)	
NAME	NULL	VARCHAR2 (80)	

EDW_BIL_CPLNS_CPLN_LSTG

Column Descriptions

Name	Null?	Type	Description
COMP_PLAN_ID_PK	NOT NULL	NUMBER(15)	
PK_ROW_ID	NULL	VARCHAR2(20)	
COMP_PLAN	NULL	VARCHAR2(100)	
NAME	NOT NULL	VARCHAR2(30)	
DESCRIPTION	NULL	VARCHAR2(1900)	
STATUS_CODE	NOT NULL	VARCHAR2(30)	
VERSION	NULL	VARCHAR2(30)	
TITLE	NULL	VARCHAR2(200)	
ALLOW_REV_CLASS_OVERLAP	NULL	VARCHAR2(1)	
QUO_ADDUP_FROM_REV_CLASS_FLAG	NULL	VARCHAR2(1)	
START_DATE	NULL	DATE	
END_DATE	NULL	DATE	
ON_QUOTA_DATE	NULL	DATE	
QUOTA_BONUS_CREDIT_TYPE	NULL	NUMBER(15)	
QUOTA_NAME	NOT NULL	VARCHAR2(30)	
QUOTA_DESCRIPTION	NULL	VARCHAR2(1900)	
QUOTA_TYPE	NOT NULL	VARCHAR2(30)	
QUOTA_TARGET	NOT NULL	NUMBER	
QUOTA_INTERVAL_TYPE	NULL	NUMBER(15)	
QUOTA_PERIOD_TYPE	NULL	VARCHAR2(30)	
QUOTA_INCENTIVE_TYPE	NULL	VARCHAR2(30)	
QUOTA_PERFORMANCE_GOAL	NULL	NUMBER(15)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
INSTANCE	NULL	VARCHAR2(40)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CPLNS_CPLN_N1	NOT UNIQUE	0	COMP_PLAN_ID_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_CPLNS_CPLN_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_CPLNS_A_LTC	ALL_PK_KEY	ALL_FK_KEY

Column Descriptions

Name	Null?	Type	Description
CPLN_COMP_PLAN_ID_PK	NOT NULL	NUMBER(15)	
CPLN_COMP_PLAN_ID_PK_KEY	NOT NULL	VARCHAR2(240)	
CPLN_PK_ROWID	NULL	VARCHAR2(20)	
ALL_FK	NULL	VARCHAR2(40)	
ALL_FK_KEY	NOT NULL	NUMBER	
CPLAN_DP	NULL	VARCHAR2(240)	
CPLN_COMP_PLAN	NULL	VARCHAR2(100)	
CPLN_NAME	NOT NULL	VARCHAR2(30)	
CPLN_DESCRIPTION	NULL	VARCHAR2(1900)	
CPLN_STATUS_CODE	NOT NULL	VARCHAR2(30)	
CPLN_VERSION	NULL	VARCHAR2(30)	
CPLN_TITLE	NULL	VARCHAR2(200)	
CPLN_ALLOW_REV_CLASS_OVERLAP	NULL	VARCHAR2(1)	
CPLN_START_DATE	NULL	DATE	
CPLN_END_DATE	NULL	DATE	
CPLN_ON_QUOTA_DATE	NULL	VARCHAR2(240)	
QUOTA_CREDIT_TYPE	NULL	NUMBER(15)	
QUOTA_NAME	NOT NULL	VARCHAR2(30)	
QUOTA_DESCRIPTION	NULL	VARCHAR2(1900)	
QUOTA_TYPE	NOT NULL	VARCHAR2(30)	
QUOTA_TARGET	NOT NULL	NUMBER	
QUOTA_INTERVAL_TYPE	NULL	NUMBER(15)	
QUOTA_PERIOD_TYPE	NULL	VARCHAR2(30)	
QUOTA_PERFORMANCE_GOAL	NULL	NUMBER(15)	
QUOTA_INCENTIVE_TYPE	NULL	VARCHAR2(30)	
CPLN_INSTANCE	NULL	DATE	
CPLN_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
CPLN_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CPLNS_CPLN_LTC_U1	NOT UNIQUE	5	CPLN_COMP_PLAN_ID_PK_KEY
EDW_BIL_CPLNS_CPLN_LTC_U2	NOT UNIQUE	5	CPLN_COMP_PLAN_ID_PK
		6	CPLN_COMP_PLAN_ID_PK_KEY

EDW_BIL_CPLNS_ELMNT_LSTG

Column Descriptions

Name	Null?	Type	Description
PLAN_ELEMENT_ID_PK	NULL	NUMBER	
PK_ROW_ID	NULL	VARCHAR2(20)	
COMP_PLAN_ID_FK	NOT NULL	NUMBER(15)	
COMP_PLAN_ID_FK_KEY	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(77)	Compensation element description
ELEMENT_TYPE	NOT NULL	VARCHAR2(4)	Type of compensation element - 'B'-bonus 'Q'-quota 'O'-other
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
INSTANCE	NULL	VARCHAR2(40)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CPLNS_ELEMNT_N1	NOT UNIQUE	0	PLAN_ELEMENT_ID_PK

EDW_BIL_CPLNS_ELMNT_LTC

Column Descriptions

Name	Null?	Type	Description
ELMNT_PLAN_ELEMENT_ID_PK	NOT NULL	NUMBER	
ELMNT_PLAN_ELEMENT_ID_PK_KEY	NOT NULL	NUMBER	
ELMNT_PK_ROWID	NULL	VARCHAR2(20)	
CPLN_COMP_PLAN_ID_FK	NOT NULL	NUMBER(15)	
CPLN_COMP_PLAN_ID_FK_KEY	NOT NULL	VARCHAR2(240)	
ELMNT_DP	NULL	VARCHAR2(240)	
ELEMENT_TYPE	NOT NULL	VARCHAR2(4)	Type of compensation element - 'B'-bonus 'Q'-quota 'O'-other
ELMNT_NAME	NULL	VARCHAR2(240)	
ELMNT_DESCRIPTION	NULL	VARCHAR2(77)	Compensation element description
ELMNT_INSTANCE	NULL	VARCHAR2(40)	
ELMNT_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
ELMNT_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_CMP_PLN_ELEMNT_LTC_U1	NOT UNIQUE	5	ELMNT_PLAN_ELEMENT_ID_PK_KEY
EDW_CMP_PLN_ELEMNT_LTC_U2	NOT UNIQUE	5	ELMNT_PLAN_ELEMENT_ID_PK
		15	ELMNT_PLAN_ELEMENT_ID_PK_KEY

EDW_BIL_CRIT_CUST_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIL_SREQ_SEV_M	SRSV_SERV_RQST_SEV_PK_KEY	SERV_REQ_SEV_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
CRIT_CUST_SUM_PK	NULL	VARCHAR2(240)	
CRIT_CUST_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
SERV_REQ_SEV_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
NO_OF_REQUESTS	NULL	NUMBER	
REVENUE_AMOUNT_T	NULL	NUMBER	
REVENUE_AMOUNT_S	NULL	NUMBER	
REVENUE_AMOUNT_G	NULL	NUMBER	
EXPECTED_REVENUE_T	NULL	NUMBER	
EXPECTED_REVENUE_S	NULL	NUMBER	
EXPECTED_REVENUE_G	NULL	NUMBER	
CUST_SATISFACTION_PCT	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CRIT_CUST_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_CRIT_CUST_SUM_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_CRIT_CUST_SUM_F_N3	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_CRIT_CUST_SUM_F_N4	NOT UNIQUE	0	SERV_REQ_SEV_FK_KEY
EDW_BIL_CRIT_CUST_SUM_F_N5	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_CRIT_CUST_SUM_F_N6	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_CRIT_CUST_SUM_F_N7	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_CRIT_CUST_SUM_F_N8	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_CRIT_CUST_SUM_F_N9	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_CRIT_CUST_SUM_F_U1	UNIQUE	0	CRIT_CUST_SUM_PK

EDW_BIL_CUST_PRF_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
CUST_PER_SUM_PK	NULL	VARCHAR2(240)	
CUST_PER_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
NO_OF_LEADS	NULL	NUMBER	
NO_OF_OPPS	NULL	NUMBER	
NO_OF_QUOTES	NULL	NUMBER	
NO_OF_ORDERS	NULL	NUMBER	
NO_OF_WINS	NULL	NUMBER	
NO_OF_LOSSES	NULL	NUMBER	
NO_OF_RETURNS	NULL	NUMBER	
COGS_AMOUNT_T	NULL	NUMBER	
COGS_AMOUNT_S	NULL	NUMBER	
COGS_AMOUNT_G	NULL	NUMBER	
ORDER_AMOUNT_T	NULL	NUMBER	
ORDER_AMOUNT_S	NULL	NUMBER	
ORDER_AMOUNT_G	NULL	NUMBER	
REVENUE_CREDITS_T	NULL	NUMBER	
REVENUE_CREDITS_S	NULL	NUMBER	
REVENUE_CREDITS_G	NULL	NUMBER	
EXPECTED_REVENUE_T	NULL	NUMBER	
EXPECTED_REVENUE_S	NULL	NUMBER	
EXPECTED_REVENUE_G	NULL	NUMBER	
RETURN_AMOUNT_T	NULL	NUMBER	
RETURN_AMOUNT_S	NULL	NUMBER	
RETURN_AMOUNT_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_MEASURE3	NULL	NUMBER
USER_MEASURE4	NULL	NUMBER
USER_MEASURE5	NULL	NUMBER
USER_FK1_KEY	NULL	NUMBER
USER_FK2_KEY	NULL	NUMBER
USER_FK3_KEY	NULL	NUMBER
USER_FK4_KEY	NULL	NUMBER
USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CUST_PRF_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_CUST_PRF_SUM_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_CUST_PRF_SUM_F_N3	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_CUST_PRF_SUM_F_N4	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_CUST_PRF_SUM_F_N5	NOT UNIQUE	5	TRX_CURRENCY_FK_KEY
EDW_BIL_CUST_PRF_SUM_F_N6	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_CUST_PRF_SUM_F_N7	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_CUST_PRF_SUM_F_N8	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_CUST_PRF_SUM_F_N9	NOT UNIQUE	5	TERRITORY_FK_KEY
EDW_BIL_CUST_PRF_SUM_F_U1	UNIQUE	0	CUST_PER_SUM_PK

EDW_BIL_CUST_REQSTS_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIL_SREQ_SEV_M	SRSV_SERV_RQST_SEV_PK_KEY	SERV_REQ_SEV_FK
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
CUST_REQ_PK	NULL	VARCHAR2(240)	
CUST_REQ_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
SERV_REQ_SEV_FK	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
NO_OF_REQUESTS	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CUST_REQSTS_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_CUST_REQSTS_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_CUST_REQSTS_F_N3	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_CUST_REQSTS_F_N4	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_CUST_REQSTS_F_N5	NOT UNIQUE	0	SERV_REQ_SEV_FK
EDW_BIL_CUST_REQSTS_F_N6	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_CUST_REQSTS_F_N7	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_CUST_REQSTS_F_U1	UNIQUE	0	CUST_REQ_PK

EDW_BIL_CUST_REQSTS_FSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK	TERRITORY_ID_FK
EDW_BIL_SREQ_SEV_M	SRSV_SERV_RQST_SEV_PK	SERV_REQ_SEV_FK
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK	GLOC_LOCATION_FK
EDW_ITEMS_M	IREV_ITEM_REVISION_PK	ITEM_FK
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK	ORGANIZATION_FK
EDW_TIME_M	CDAY_CALL_DAY_PK	TIME_FK
EDW_TRD_PARTNER_M	TPLO_TRADE_PARTNER_LOC_PK	BILL_TO_CUSTOMER_FK

Column Descriptions

Name	Null?	Type	Description
CUST_REQ_PK	NULL	VARCHAR2(240)	
TIME_FK	NOT NULL	VARCHAR2(120)	
TIME_FK_KEY	NULL	NUMBER	
BILL_TO_CUSTOMER_FK	NOT NULL	VARCHAR2(320)	
BILL_TO_CUSTOMER_FK_KEY	NULL	NUMBER	
ITEM_FK	NOT NULL	VARCHAR2(320)	
ITEM_FK_KEY	NULL	VARCHAR2(240)	
SERV_REQ_SEV_FK	NOT NULL	NUMBER	
SERV_RQST_SEV_FK_KEY	NULL	VARCHAR2(100)	
TERRITORY_ID_FK	NOT NULL	VARCHAR2(240)	
TERRITORY_FK_KEY	NULL	NUMBER	
GLOC_LOCATION_FK	NOT NULL	VARCHAR2(240)	
GLOC_LOCATION_FK_KEY	NULL	NUMBER	
ORGANIZATION_FK	NOT NULL	VARCHAR2(120)	
ORGANIZATION_FK_KEY	NULL	NUMBER	
NO_OF_REQUESTS	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_FK1	NULL	VARCHAR2(2000)	
USER_FK2	NULL	VARCHAR2(2000)	
USER_FK3	NULL	VARCHAR2(2000)	
USER_FK4	NULL	VARCHAR2(2000)	
USER_FK5	NULL	VARCHAR2(2000)	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
USER_MEASURE1	NULL	NUMBER
USER_MEASURE2	NULL	NUMBER
USER_MEASURE3	NULL	NUMBER
USER_MEASURE4	NULL	NUMBER
USER_MEASURE5	NULL	NUMBER
REQUEST_ID	NULL	NUMBER
ROW_ID	NULL	VARCHAR2(20)
OPERATION_CODE	NULL	VARCHAR2(40)
ERROR_CODE	NULL	VARCHAR2(2000)
COLLECTION_STATUS	NULL	VARCHAR2(40)

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CUST_REQSTS_FSTG_N1	NOT UNIQUE	0	CUST_REQ_PK

EDW_BIL_CUST_RMGT_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_MTL_UNIT_OF_MEASR_M	UOM_UOM_PK_KEY	UOM_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
CUST_REVMGMT_PK	NULL	VARCHAR2(240)	
CUST_REVMGT_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
UOM_FK_KEY	NOT NULL	NUMBER	
NO_OF_ORDERS	NULL	NUMBER	
UNITS_SOLD	NULL	NUMBER	
QUANTITY_ORDERED	NULL	NUMBER	
COGS_AMOUNT_T	NULL	NUMBER	
COGS_AMOUNT_S	NULL	NUMBER	
COGS_AMOUNT_G	NULL	NUMBER	
INVOICED_AMOUNT_T	NULL	NUMBER	
INVOICED_AMOUNT_S	NULL	NUMBER	
INVOICED_AMOUNT_G	NULL	NUMBER	
ORDER_AMOUNT_T	NULL	NUMBER	
ORDER_AMOUNT_S	NULL	NUMBER	
ORDER_AMOUNT_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CUST_RMGT_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_CUST_RMGT_SUM_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_CUST_RMGT_SUM_F_N3	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_CUST_RMGT_SUM_F_N5	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_CUST_RMGT_SUM_F_N6	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_CUST_RMGT_SUM_F_N7	NOT UNIQUE	0	UOM_FK_KEY
EDW_BIL_CUST_RMGT_SUM_F_U1	UNIQUE	0	CUST_REVMGMT_PK
EDW_BIL_CUST_RMGT_SUN_F_N4	NOT UNIQUE	0	SALESREP_ID_FK_KEY

EDW_BIL_CUST_SATFCTN_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SALESCHNL_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
CUST_SATISFCTN_PK	NULL	VARCHAR2(240)	
CUST_SATISFCTN_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
SALESCHNL_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
CUST_SATISFACTION	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CUST_SATFCTN_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_CUST_SATFCTN_F_N2	NOT UNIQUE	0	SALESCHNL_FK_KEY
EDW_BIL_CUST_SATFCTN_F_N3	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_CUST_SATFCTN_F_N4	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_CUST_SATFCTN_F_N5	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_CUST_SATFCTN_F_N6	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_CUST_SATFCTN_F_U1	UNIQUE	0	CUST_SATISFCTN_PK
EDW_BIL_CUST_SATTCTN_F_N7	NOT UNIQUE	0	ORGANIZATION_FK_KEY

EDW_BIL_CUST_SATFCTN_FSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK	SALESREP_ID_FK
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK	TERRITORY_ID_FK
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK	GLOC_LOCATION_FK
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK	ORGANIZATION_FK
EDW_TIME_M	CDAY_CALL_DAY_PK	TIME_FK
EDW_TRD_PARTNER_M	TPLO_TRADE_PARTNER_LOC_PK	BILL_TO_CUSTOMER_FK

Column Descriptions

Name	Null?	Type	Description
CUST_SATISFCTN_PK	NULL	VARCHAR2(240)	
CUST_SATISFCTN_PK_KEY	NULL	NUMBER	
TIME_FK	NOT NULL	DATE	Accounting period number
TIME_FK_KEY	NULL	NUMBER	
BILL_TO_CUSTOMER_FK	NOT NULL	VARCHAR2(320)	
BILL_TO_CUSTOMER_FK_KEY	NULL	NUMBER	
SALESREP_ID_FK	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
TERRITORY_ID_FK	NOT NULL	VARCHAR2(240)	
TERRITORY_FK_KEY	NULL	NUMBER	
GLOC_LOCATION_FK	NOT NULL	VARCHAR2(240)	
GLOC_LOCATION_FK_KEY	NULL	NUMBER	
ORGANIZATION_FK	NOT NULL	VARCHAR2(120)	
ORGANIZATION_FK_KEY	NULL	NUMBER	
CUST_SATISFACTION	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_FK1	NULL	VARCHAR2(2000)	
USER_FK2	NULL	VARCHAR2(2000)	
USER_FK3	NULL	VARCHAR2(2000)	
USER_FK4	NULL	VARCHAR2(2000)	
USER_FK5	NULL	VARCHAR2(2000)	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
USER_MEASURE1	NULL	NUMBER
USER_MEASURE2	NULL	NUMBER
USER_MEASURE3	NULL	NUMBER
USER_MEASURE4	NULL	NUMBER
USER_MEASURE5	NULL	NUMBER
REQUEST_ID	NULL	NUMBER
ROW_ID	NULL	VARCHAR2(20)
OPERATION_CODE	NULL	VARCHAR2(40)
ERROR_CODE	NULL	VARCHAR2(2000)

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CUST_SATFCTN_FSTG_N1	NOT UNIQUE	5	CUST_SATISFCTN_PK

EDW_BIL_CUST_SATIS_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_MTL_UNIT_OF_MEASR_M	UOM_UOM_PK_KEY	UOM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
CUST_SATSFCTN_SUM_PK	NULL	VARCHAR2(240)	
CUST_SATISFCTN_SUM_PK_KEY	NULL	NUMBER	
TIME_FK	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
UOM_FK_KEY	NOT NULL	NUMBER	
NO_OF_LEADS	NULL	NUMBER	
NO_OF_ORDERS	NULL	NUMBER	
NO_OF_WINS	NULL	NUMBER	
NO_OF_LOSSES	NULL	NUMBER	
UNITS_SOLD	NULL	NUMBER	
SALES_CYCLE	NULL	NUMBER	
CUST_SATISFACTION	NULL	NUMBER	
COGS_AMOUNT_T	NULL	NUMBER	
COGS_AMOUNT_S	NULL	NUMBER	
COGS_AMOUNT_G	NULL	NUMBER	
INVOICED_AMOUNT_T	NULL	NUMBER	
INVOICED_AMOUNT_S	NULL	NUMBER	
INVOICED_AMOUNT_G	NULL	NUMBER	
EXPECTED_REVENUE_T	NULL	NUMBER	
EXPECTED_REVENUE_S	NULL	NUMBER	
EXPECTED_REVENUE_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_FK1_KEY	NULL	NUMBER
USER_FK2_KEY	NULL	NUMBER
USER_FK3_KEY	NULL	NUMBER
USER_FK4_KEY	NULL	NUMBER
USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CUST_SATIS_SUM_F_N1	NOT UNIQUE	0	TIME_FK
EDW_BIL_CUST_SATIS_SUM_F_N10	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_N11	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_N3	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_N4	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_N5	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_N6	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_N7	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_N8	NOT UNIQUE	0	UOM_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_N9	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_CUST_SATIS_SUM_F_U1	UNIQUE	0	CUST_SATSFCTN_SUM_PK

EDW_BIL_LEADS_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_LEADS_TER_GRP	LEADS_TER_GRP_PK_KEY	LEADS_TER_GRP_FK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIM_LEAD_STATUSES_M	L1_LEADSTATUS_PK_KEY	LEAD_STATUS_FK_KEY
EDW_BIM_SLSCHNL_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
LEADS_PK	NULL	VARCHAR2(240)	
LEADS_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
LEAD_STATUS_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
LEADS_TER_GRP_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
LEAD_ID	NULL	NUMBER	
LEAD_AMOUNT_T	NULL	NUMBER	
LEAD_AMOUNT_S	NULL	NUMBER	
LEAD_AMOUNT_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_LEADS_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_LEADS_F_N10	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_LEADS_F_N11	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_LEADS_F_N12	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_LEADS_F_N13	NOT UNIQUE	5	LEADS_TER_GRP_FK_KEY
EDW_BIL_LEADS_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_LEADS_F_N3	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_LEADS_F_N4	NOT UNIQUE	0	LEAD_STATUS_FK_KEY
EDW_BIL_LEADS_F_N5	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_LEADS_F_N6	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_LEADS_F_N7	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_LEADS_F_N8	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_LEADS_F_N9	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_LEADS_F_U1	UNIQUE	0	LEADS_PK

EDW_BIL_LEADS_FSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_LEADS_TER_GRP	LEADS_TER_GRP_PK	LEADS_TER_GRP_ID_FK
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK	SALESREP_ID_FK
EDW_BIM_LEAD_STATUSES_M	L1_LEADSTATUS_PK	LEAD_STATUS_FK
EDW_BIM_SLSCHNL_MS	L1_SLSCHNL_PK	SLSCHNL_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	GLBL_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	SOB_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	TRX_CURRENCY_FK
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK	GLOC_LOCATION_FK
EDW_ITEMS_M	IREV_ITEM_REVISION_PK	ITEM_FK
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK	ORGANIZATION_FK
EDW_TIME_M	CDAY_CALL_DAY_PK	TIME_FK
EDW_TRD_PARTNER_M	TPLO_TRADE_PARTNER_LOC_PK	BILL_TO_CUSTOMER_FK

Column Descriptions

Name	Null?	Type	Description
LEADS_PK	NULL	VARCHAR2(240)	
TIME_FK	NOT NULL	DATE	Accounting period number
TIME_FK_KEY	NULL	NUMBER	
ITEM_FK	NOT NULL	VARCHAR2(320)	
ITEM_FK_KEY	NULL	NUMBER	
BILL_TO_CUSTOMER_FK	NOT NULL	VARCHAR2(320)	
BILL_TO_CUSTOMER_FK_KEY	NULL	NUMBER	
SLSCHNL_FK	NOT NULL	VARCHAR2(120)	
SLSCHNL_FK_KEY	NULL	NUMBER	
SALESREP_ID_FK	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NULL	NUMBER	
ORGANIZATION_FK	NOT NULL	VARCHAR2(240)	
ORGANIZATION_FK_KEY	NULL	NUMBER	
LEADS_TER_GRP_ID_FK	NOT NULL	NUMBER(15)	
LEADS_TER_GRP_FK_KEY	NULL	NUMBER	
LEAD_STATUS_FK	NOT NULL	VARCHAR2(240)	
LEAD_STATUS_FK_KEY	NULL	NUMBER	
GLOC_LOCATION_FK	NOT NULL	VARCHAR2(240)	
GLOC_LOCATION_FK_KEY	NULL	NUMBER	
TRX_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
TRX_CURRENCY_FK_KEY	NULL	NUMBER	
SOB_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
SOB_CURRENCY_FK_KEY	NULL	NUMBER	
GLBL_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
GLBL_CURRENCY_FK_KEY	NULL	NUMBER	
LEAD_ID	NULL	NUMBER	
LEAD_AMOUNT_T	NULL	NUMBER	
LEAD_AMOUNT_S	NULL	NUMBER	
LEAD_AMOUNT_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_FK1	NULL	VARCHAR2(2000)	
USER_FK2	NULL	VARCHAR2(2000)	
USER_FK3	NULL	VARCHAR2(2000)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_FK4	NULL	VARCHAR2(2000)
USER_FK5	NULL	VARCHAR2(2000)
USER_FK1_KEY	NULL	NUMBER
USER_FK2_KEY	NULL	NUMBER
USER_FK3_KEY	NULL	NUMBER
USER_FK4_KEY	NULL	NUMBER
USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
USER_MEASURE1	NULL	NUMBER
USER_MEASURE2	NULL	NUMBER
USER_MEASURE3	NULL	NUMBER
USER_MEASURE4	NULL	NUMBER
USER_MEASURE5	NULL	NUMBER
REQUEST_ID	NULL	NUMBER
ROW_ID	NULL	VARCHAR2(20)
OPERATION_CODE	NULL	VARCHAR2(40)
ERROR_CODE	NULL	VARCHAR2(2000)
COLLECTION_STATUS	NULL	VARCHAR2(40)

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_LEADS_FSTG_N1	NOT UNIQUE	0	LEADS_PK

EDW_BIL_LEADS_TER_GRP

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
LEADS_TER_GRP_PK	NOT NULL	VARCHAR2(240)	
LEADS_TER_GRP_PK_KEY	NOT NULL	NUMBER	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER(15)	
INSTANCE	NULL	VARCHAR2(40)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_LEADS_TER_GRP_N1	NOT UNIQUE	5	TERRITORY_ID_FK_KEY
EDW_BIL_LEADS_TER_GRP_U1	UNIQUE	5	LEADS_TER_GRP_PK

EDW_BIL_OPTYS_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_OPTY_TER_GRP	OPTY_TER_GRP_PK_KEY	OPTY_TER_GRP_FK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIL_WIN_PROB_M	WINP_PROBABILITY_VALUE_PK_KEY	WIN_PROBABILITY_FK_KEY
EDW_BIM_OPP_STATUSES_M	L1_OPPSTATUS_PK_KEY	OPPTY_STATUS_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
OPTYS_PK	NULL	VARCHAR2(240)	
OPTYS_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
OPPTY_STATUS_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
WIN_PROBABILITY_FK_KEY	NOT NULL	NUMBER	
OPTY_TER_GRP_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
OPPORTUNITY_ID	NOT NULL	NUMBER	
OPTY_AMOUNT_T	NULL	NUMBER	
OPTY_AMOUNT_S	NULL	NUMBER	
OPTY_AMOUNT_G	NULL	NUMBER	
EXPECTED_REVENUE_T	NULL	NUMBER	
EXPECTED_REVENUE_S	NULL	NUMBER	
EXPECTED_REVENUE_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_OPTYS_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_OPTYS_F_N10	NOT UNIQUE	5	ORGANIZATION_FK_KEY
EDW_BIL_OPTYS_F_N11	NOT UNIQUE	5	TRX_CURRENCY_FK_KEY
EDW_BIL_OPTYS_F_N12	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_OPTYS_F_N13	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_OPTYS_F_N14	NOT UNIQUE	5	PTY_TER_GRP_FK_KEY
EDW_BIL_OPTYS_F_N2	NOT UNIQUE	0	OPPTY_STATUS_FK_KEY
EDW_BIL_OPTYS_F_N3	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_OPTYS_F_N4	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_OPTYS_F_N6	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_OPTYS_F_N7	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_OPTYS_F_N8	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_OPTYS_F_N9	NOT UNIQUE	0	WIN_PROBABILITY_FK_KEY
EDW_BIL_OPTYS_F_U1	UNIQUE	0	OPTYS_PK

EDW_BIL_OPTYS_FSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_OPTY_TER_GRP	PTY_TER_GRP_PK	PTY_TER_GRP_FK
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK	SALESREP_ID_FK
EDW_BIL_WIN_PROB_M	WINP_PROBABILITY_VALUE_PK	WIN_PROBABILITY_FK
EDW_BIM_OPP_STATUSES_M	L1_OPPSTATUS_PK_KEY	OPPTY_STATUS_FK
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK	SLSCHNL_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	GLBL_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	SOB_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	TRX_CURRENCY_FK
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK	GLOC_LOCATION_FK
EDW_ITEMS_M	IREV_ITEM_REVISION_PK	ITEM_FK
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK	ORGANIZATION_FK
EDW_TIME_M	CDAY_CALL_DAY_PK	TIME_FK
EDW_TRD_PARTNER_M	TPLO_TRADE_PARTNER_LOC_PK	BILL_TO_CUSTOMER_FK

Column Descriptions

Name	Null?	Type	Description
OPTYS_PK	NULL	VARCHAR2(240)	
TIME_FK	NOT NULL	VARCHAR2(120)	
TIME_FK_KEY	NULL	NUMBER	
ITEM_FK	NOT NULL	VARCHAR2(320)	
ITEM_FK_KEY	NULL	NUMBER	
BILL_TO_CUSTOMER_FK	NOT NULL	VARCHAR2(320)	
BILL_TO_CUSTOMER_FK_KEY	NULL	NUMBER	
OPPTY_STATUS_FK	NOT NULL	VARCHAR2(240)	
OPPTY_STATUS_FK_KEY	NULL	NUMBER	
SALESREP_ID_FK	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NULL	NUMBER	
SLSCHNL_FK	NOT NULL	VARCHAR2(120)	
SLSCHNL_FK_KEY	NULL	NUMBER	
ORGANIZATION_FK	NOT NULL	VARCHAR2(120)	
ORGANIZATION_FK_KEY	NULL	NUMBER	
PTY_TER_GRP_FK	NOT NULL	VARCHAR2(240)	
PTY_TER_GRP_FK_KEY	NULL	NUMBER	
WIN_PROBABILITY_FK	NOT NULL	VARCHAR2(240)	
WIN_PROBABILITY_FK_KEY	NULL	NUMBER	
GLOC_LOCATION_FK	NOT NULL	VARCHAR2(240)	
GLOC_LOCATION_FK_KEY	NULL	NUMBER	
TRX_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
TRX_CURRENCY_FK_KEY	NULL	NUMBER	
SOB_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
SOB_CURRENCY_FK_KEY	NULL	NUMBER	
GLBL_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
GLBL_CURRENCY_FK_KEY	NULL	NUMBER	
OPPORTUNITY_ID	NULL	NUMBER	
EXPECTED_REVENUE_T	NULL	NUMBER	
EXPECTED_REVENUE_S	NULL	NUMBER	
EXPECTED_REVENUE_G	NULL	NUMBER	
PTY_AMOUNT_T	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

OPTY_AMOUNT_S	NULL	NUMBER
OPTY_AMOUNT_G	NULL	NUMBER
INSTANCE	NULL	VARCHAR2(40)
USER_FK1	NULL	VARCHAR2(2000)
USER_FK2	NULL	VARCHAR2(2000)
USER_FK3	NULL	VARCHAR2(2000)
USER_FK4	NULL	VARCHAR2(2000)
USER_FK5	NULL	VARCHAR2(2000)
USER_FK1_KEY	NULL	NUMBER
USER_FK2_KEY	NULL	NUMBER
USER_FK3_KEY	NULL	NUMBER
USER_FK4_KEY	NULL	NUMBER
USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
USER_MEASURE1	NULL	NUMBER
USER_MEASURE2	NULL	NUMBER
USER_MEASURE3	NULL	NUMBER
USER_MEASURE4	NULL	NUMBER
USER_MEASURE5	NULL	NUMBER
REQUEST_ID	NULL	NUMBER
ROW_ID	NULL	VARCHAR2(20)
OPERATION_CODE	NULL	VARCHAR2(40)
ERROR_CODE	NULL	VARCHAR2(2000)
COLLECTION_STATUS	NULL	VARCHAR2(40)

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_CURR_OPTY_FSTG_N1	NOT UNIQUE	0	OPTYS_PK

EDW_BIL_OPTY_PERF_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIL_WIN_PROB_M	WINP_PROBABILITY_VALUE_PK_KEY	WIN_PROBABILITY_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
OPTY_PERF_SUM_PK	NULL	VARCHAR2(240)	
OPTY_PERF_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
WIN_PROBABILITY_FK_KEY	NOT NULL	NUMBER	
NO_OF_OPPS	NULL	NUMBER	
NO_OF_LEADS	NULL	NUMBER	
OPTY_AMOUNT_T	NULL	NUMBER	
OPTY_AMOUNT_S	NULL	NUMBER	
OPTY_AMOUNT_G	NULL	NUMBER	
INVOICED_AMOUNT_T	NULL	NUMBER	
INVOICED_AMOUNT_S	NULL	NUMBER	
INVOICED_AMOUNT_G	NULL	NUMBER	
CUST_SATISFACTION_PCT	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE4	NULL VARCHAR2(240)
USER_ATTRIBUTE5	NULL VARCHAR2(240)
USER_ATTRIBUTE6	NULL VARCHAR2(240)
USER_ATTRIBUTE7	NULL VARCHAR2(240)
USER_ATTRIBUTE8	NULL VARCHAR2(240)
USER_ATTRIBUTE9	NULL VARCHAR2(240)
USER_ATTRIBUTE10	NULL VARCHAR2(240)
USER_ATTRIBUTE11	NULL VARCHAR2(240)
USER_ATTRIBUTE12	NULL VARCHAR2(240)
USER_ATTRIBUTE13	NULL VARCHAR2(240)
USER_ATTRIBUTE14	NULL VARCHAR2(240)
USER_ATTRIBUTE15	NULL VARCHAR2(240)
LAST_UPDATE_DATE	NULL DATE
CREATION_DATE	NULL DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_OPTY_PERF_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_N10	NOT UNIQUE	5	TERRITORY_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_N3	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_N4	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_N5	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_N6	NOT UNIQUE	0	WIN_PROBABILITY_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_N7	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_N8	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_N9	NOT UNIQUE	5	SLSCHNL_FK_KEY
EDW_BIL_OPTY_PERF_SUM_F_U1	UNIQUE	0	OPTY_PERF_SUM_PK

EDW_BIL_OPTY_TER_GRP

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
OPTY_TER_GRP_PK	NOT NULL	VARCHAR2(240)	
OPTY_TER_GRP_PK_KEY	NOT NULL	NUMBER(15)	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER(15)	
INSTANCE	NULL	VARCHAR2(40)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_OPTY_TER_GRP_N1	NOT UNIQUE	5	TERRITORY_ID_FK_KEY
EDW_BIL_OPTY_TER_GRP_U1	NOT UNIQUE	5	OPTY_TER_GRP_PK

EDW_BIL_OPTY_TGRP_BSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK	TERRITORY_ID_FK

Column Descriptions

Name	Null?	Type	Description
OPTY_TER_GRP_PK	NOT NULL	VARCHAR2(240)	
OPTY_TER_GRP_PK_KEY	NOT NULL	NUMBER(15)	
ROW_ID	NULL	VARCHAR2(20)	
TERRITORY_ID_FK	NOT NULL	NUMBER	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER(15)	
OPPORTUNITY_ID	NOT NULL	NUMBER	
TERRITORY_ID	NOT NULL	NUMBER(15)	
INSTANCE	NULL	VARCHAR2(40)	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_OPTY_TER_GRP_BSTG_N1	NOT UNIQUE	5	OPTY_TER_GRP_PK

EDW_BIL_ORDRS_TER_GRP

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
ORDRS_TER_GRP_PK	NOT NULL	VARCHAR2(240)	
ORDRS_TER_GRP_PK_KEY	NOT NULL	NUMBER	
TERRITORY_ID_FK	NOT NULL	NUMBER(15)	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER(15)	
INSTANCE	NULL	VARCHAR2(40)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_ORDRS_TER_GRP_N1	NOT UNIQUE	2	TERRITORY_ID_FK_KEY

EDW_BIL_ORDRS_TGRP_BSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK	TERRITORY_ID_FK

Column Descriptions

Name	Null?	Type	Description
ORDRS_TER_GRP_PK	NOT NULL	VARCHAR2(240)	
ROW_ID	NULL	VARCHAR2(20)	
ORDRS_TER_GRP_PK_KEY	NOT NULL	NUMBER	
TERRITORY_ID_FK	NOT NULL	NUMBER(15)	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER(15)	
ORDER_NUMBER	NOT NULL	NUMBER	
TERRITORY_ID	NOT NULL	NUMBER(15)	
INSTANCE	NULL	VARCHAR2(40)	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_ORDRS_TGRP_BSTG_U	NOT UNIQUE	2	TERRITORY_ID_FK

EDW_BIL_PROD_PERF_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_MTL_UNIT_OF_MEASR_M	UOM_UOM_PK_KEY	UOM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY

Column Descriptions

Name	Null?	Type	Description
PRD_PERF_SUM_PK	NULL	VARCHAR2(240)	
PROD_PERF_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
UOM_FK_KEY	NOT NULL	NUMBER	
CREDITED_UNITS	NULL	NUMBER	
NO_OF_WINS	NULL	NUMBER	
NO_OF_LOSSES	NULL	NUMBER	
COGS_AMOUNT_T	NULL	NUMBER	
COGS_AMOUNT_S	NULL	NUMBER	
COGS_AMOUNT_G	NULL	NUMBER	
INVOICED_AMOUNT_T	NULL	NUMBER	
INVOICED_AMOUNT_S	NULL	NUMBER	
INVOICED_AMOUNT_G	NULL	NUMBER	
EXPECTED_REVENUE_T	NULL	NUMBER	
EXPECTED_REVENUE_S	NULL	NUMBER	
EXPECTED_REVENUE_G	NULL	NUMBER	
SALES_CYCLE	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_FK3_KEY	NULL	NUMBER
USER_FK4_KEY	NULL	NUMBER
USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_PROD_PERF_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N10	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N11	NOT UNIQUE	5	UOM_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N2	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N3	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N4	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N5	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N6	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N7	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N8	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_N9	UNIQUE	2	SOB_CURRENCY_FK_KEY
EDW_BIL_PROD_PERF_SUM_F_U1	UNIQUE	5	PRD_PERF_SUM_PK

EDW_BIL_QUOTES_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_QUOTE_TER_GRP	QUOTE_TER_GRP_PK_KEY	QUOTES_TER_GRP_FK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
QUOTES_PK	NULL	VARCHAR2(240)	
QUOTES_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
QUOTES_TER_GRP_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
QUOTE_ID	NULL	NUMBER	
QUOTE_AMOUNT_T	NULL	NUMBER	
QUOTE_AMOUNT_G	NULL	NUMBER	
QUOTE_AMOUNT_S	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE7	NULL VARCHAR2(240)
USER_ATTRIBUTE8	NULL VARCHAR2(240)
USER_ATTRIBUTE9	NULL VARCHAR2(240)
USER_ATTRIBUTE10	NULL VARCHAR2(240)
USER_ATTRIBUTE11	NULL VARCHAR2(240)
USER_ATTRIBUTE12	NULL VARCHAR2(240)
USER_ATTRIBUTE13	NULL VARCHAR2(240)
USER_ATTRIBUTE14	NULL VARCHAR2(240)
USER_ATTRIBUTE15	NULL VARCHAR2(240)
LAST_UPDATE_DATE	NULL DATE
CREATION_DATE	NULL DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_QUOTES_F_N1	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_QUOTES_F_N10	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_QUOTES_F_N11	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_QUOTES_F_N2	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_QUOTES_F_N3	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_QUOTES_F_N4	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_QUOTES_F_N5	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_QUOTES_F_N6	NOT UNIQUE	5	QUOTES_TER_GRP_FK_KEY
EDW_BIL_QUOTES_F_N7	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_QUOTES_F_N8	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_QUOTES_F_N9	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_QUOTES_F_U1	UNIQUE	0	QUOTES_PK

EDW_BIL_QUOTES_FSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_QUOTE_TER_GRP	QUOTE_TER_GRP_PK	QUOTE_TER_GRP_FK
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK	SALESREP_ID_FK
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK	SLSCHNL_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	GLBL_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	SOB_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	TRX_CURRENCY_FK
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK	GLOC_LOCATION_FK
EDW_ITEMS_M	IREV_ITEM_REVISION_PK	ITEM_FK
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK	ORGANIZATION_FK
EDW_TIME_M	CDAY_CALL_DAY_PK	TIME_FK
EDW_TRD_PARTNER_M	TPLO_TRADE_PARTNER_LOC_PK	BILL_TO_CUSTOMER_FK

Column Descriptions

Name	Null?	Type	Description
QUOTES_PK	NULL	VARCHAR2(240)	
TIME_FK	NOT NULL	VARCHAR2(120)	
TIME_FK_KEY	NULL	NUMBER	
BILL_TO_CUSTOMER_FK	NOT NULL	VARCHAR2(320)	
BILL_TO_CUSTOMER_FK_KEY	NULL	NUMBER	
ITEM_FK	NOT NULL	VARCHAR2(320)	
ITEM_FK_KEY	NULL	NUMBER	
SALESREP_ID_FK	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NULL	NUMBER	
SLSCHNL_FK	NOT NULL	VARCHAR2(120)	
SLSCHNL_FK_KEY	NULL	NUMBER	
QUOTE_TER_GRP_FK	NOT NULL	VARCHAR2(240)	
QUOTE_TER_GRP_FK_KEY	NULL	NUMBER	
ORGANIZATION_FK_KEY	NULL	NUMBER	
ORGANIZATION_FK	NOT NULL	VARCHAR2(120)	
GLOC_LOCATION_FK	NOT NULL	VARCHAR2(240)	
GLOC_LOCATION_FK_KEY	NULL	NUMBER	
TRX_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
TRX_CURRENCY_FK_KEY	NULL	NUMBER	
SOB_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
SOB_CURRENCY_FK_KEY	NULL	NUMBER	
GLBL_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
GLBL_CURRENCY_FK_KEY	NULL	NUMBER	
QUOTE_ID	NULL	NUMBER	
QUOTE_AMOUNT_T	NULL	NUMBER	
QUOTE_AMOUNT_S	NULL	NUMBER	
QUOTE_AMOUNT_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_FK1	NULL	VARCHAR2(2000)	
USER_FK2	NULL	VARCHAR2(2000)	
USER_FK3	NULL	VARCHAR2(2000)	
USER_FK4	NULL	VARCHAR2(2000)	
USER_FK5	NULL	VARCHAR2(2000)	
USER_FK1_KEY	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_FK2_KEY	NULL	NUMBER
USER_FK3_KEY	NULL	NUMBER
USER_FK4_KEY	NULL	NUMBER
USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
USER_MEASURE1	NULL	NUMBER
USER_MEASURE2	NULL	NUMBER
USER_MEASURE3	NULL	NUMBER
USER_MEASURE4	NULL	NUMBER
USER_MEASURE5	NULL	NUMBER
REQUEST_ID	NULL	NUMBER
ROW_ID	NULL	VARCHAR2(20)
OPERATION_CODE	NULL	VARCHAR2(40)
ERROR_CODE	NULL	VARCHAR2(2000)
COLLECTION_STATUS	NULL	VARCHAR2(40)

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_QUOTES_FSTG_N1	NOT UNIQUE	0	QUOTES_PK

EDW_BIL_QUOTE_TER_GRP

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
QUOTE_TER_GRP_PK	NOT NULL	VARCHAR2(240)	
QUOTE_TER_GRP_PK_KEY	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
TERRITORY_GRP_FK	NOT NULL	NUMBER(15)	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER(15)	
INSTANCE	NULL	VARCHAR2(40)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_QUOTE_TER_GRP_N1	NOT UNIQUE	2	TERRITORY_ID_FK_KEY
EDW_BIL_QUOTE_TER_GRP_U1	UNIQUE	5	QUOTE_TER_GRP_PK_KEY

EDW_BIL_QUOTE_TGRP_BSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK	TERRITORY_ID_FK

Column Descriptions

Name	Null?	Type	Description
QUOTE_TER_GRP_PK	NOT NULL	VARCHAR2(240)	
QUOTE_TER_GRP_PK_KEY	NOT NULL	NUMBER	
TERRITORY_ID_FK	NOT NULL	NUMBER(15)	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER(15)	
QUOTE_ID	NOT NULL	NUMBER	
TERRITORY_ID	NOT NULL	NUMBER(15)	
INSTANCE	NULL	VARCHAR2(40)	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_QUOTE_TER_GRP_BSTG_N1	NOT UNIQUE	2	TERRITORY_ID_FK

EDW_BIL_ROC_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_COMP_PLANS_M	ELMNT_PLAN_ELEMENT_ID_PK_KEY	PLAN_ELEMENT_ID_FK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY

Column Descriptions

Name	Null?	Type	Description
ROC_SUM_PK	NULL	VARCHAR2(240)	
ROC_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
PLAN_ELEMENT_ID_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
QUOTA_AMOUNT_T	NULL	NUMBER	Quota monetary amount
QUOTA_AMOUNT_S	NULL	NUMBER	Quota monetary amount
QUOTA_AMOUNT_G	NULL	NUMBER	Quota monetary amount
QUOTA_ACHIEVED_T	NULL	NUMBER	
QUOTA_ACHIEVED_S	NULL	NUMBER	
QUOTA_ACHIEVED_G	NULL	NUMBER	
REVENUE_CREDITS_T	NULL	NUMBER	
REVENUE_CREDITS_S	NULL	NUMBER	
REVENUE_CREDITS_G	NULL	NUMBER	
COMMISSION_T	NULL	NUMBER	
COMMISSION_S	NULL	NUMBER	
COMMISSION_G	NULL	NUMBER	
BONUS_L	NULL	NUMBER	
BONUS_S	NULL	NUMBER	
BONUS_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_ROC_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_ROC_SUM_F_N2	NOT UNIQUE	0	PLAN_ELEMENT_ID_FK_KEY
EDW_BIL_ROC_SUM_F_N3	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_ROC_SUM_F_N4	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_ROC_SUM_F_N5	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_ROC_SUM_F_N6	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_ROC_SUM_F_N7	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_ROC_SUM_F_U1	UNIQUE	0	ROC_SUM_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SCHN_PER_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_MTL_UNIT_OF_MEASR_M	UOM_UOM_PK_KEY	UOM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SLSCHNL_PERF_SUM_PK	NULL	VARCHAR2(240)	
SLSCHNL_PER_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
UOM_FK_KEY	NOT NULL	NUMBER	
NO_OF_WINS	NULL	NUMBER	
NO_OF_LOSSES	NULL	NUMBER	
NO_OF_LEADS	NULL	NUMBER	
NO_OF_ORDERS	NULL	NUMBER	
SALES_CYCLE	NULL	NUMBER	
UNITS_SOLD	NULL	NUMBER	
INVOICED_AMOUNT_T	NULL	NUMBER	
INVOICED_AMOUNT_S	NULL	NUMBER	
INVOICED_AMOUNT_G	NULL	NUMBER	
COGS_AMOUNT_T	NULL	NUMBER	
COGS_AMOUNT_S	NULL	NUMBER	
COGS_AMOUNT_G	NULL	NUMBER	
CUST_SATISFACTION_PCT	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SCHN_PER_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_SCHN_PER_SUM_F_N2	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_SCHN_PER_SUM_F_N3	NOT UNIQUE	5	UOM_FK_KEY
EDW_BIL_SCHN_PER_SUM_F_N4	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_SCHN_PER_SUM_F_N5	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_SCHN_PER_SUM_F_N6	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_SCHN_PER_SUM_F_N7	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_SCHN_PER_SUM_F_N8	NOT UNIQUE	5	TRX_CURRENCY_FK_KEY
EDW_BIL_SCHN_PER_SUM_F_N9	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_SCHN_PER_SUM_F_U1	UNIQUE	0	SLSCHNL_PERF_SUM_PK

EDW_BIL_SF_COMP_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_COMP_PLANS_M	ELMNT_PLAN_ELEMENT_ID_PK_KEY	PLAN_ELEMENT_ID_PK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SLSFRCE_COMP_PK	NULL	VARCHAR2(240)	
SLSFRCE_COMP_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
PLAN_ELEMENT_ID_PK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
BONUS_T	NULL	NUMBER	
BONUS_S	NULL	NUMBER	
BONUS_G	NULL	NUMBER	
COMMISSION_T	NULL	NUMBER	
COMMISSION_S	NULL	NUMBER	
COMMISSION_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SF_COMP_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_SF_COMP_F_N10	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_SF_COMP_F_N11	NOT UNIQUE	5	ITEM_FK_KEY
EDW_BIL_SF_COMP_F_N2	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_SF_COMP_F_N3	NOT UNIQUE	5	TRADING_PARTNR_FK_KEY
EDW_BIL_SF_COMP_F_N4	NOT UNIQUE	0	PLAN_ELEMENT_ID_PK_KEY
EDW_BIL_SF_COMP_F_N5	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_SF_COMP_F_N6	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_SF_COMP_F_N7	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_SF_COMP_F_N8	NOT UNIQUE	5	GLOC_LOCATION_FK_KEY
EDW_BIL_SF_COMP_F_N9	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_SF_COMP_F_U1	UNIQUE	0	SLSFRCE_COMP_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SF_COMP_FSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_COMP_PLANS_M	ELMNT_PLAN_ELEMENT_ID_PK	PLAN_ELEMENT_ID_FK
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK	SALESREP_ID_FK
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK	SLSCHNL_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	GLBL_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	SOB_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	TRX_CURRENCY_FK
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK	GLOC_LOCATION_FK
EDW_ITEMS_M	IREV_ITEM_REVISION_PK	ITEM_FK
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK	ORGANIZATION_FK
EDW_TIME_M	CDAY_CALL_DAY_PK	TIME_FK
EDW_TRD_PARTNER_M	TPLO_TRADE_PARTNER_LOC_PK	BILL_TO_CUSTOMER_FK

Column Descriptions

Name	Null?	Type	Description
SLSFRCE_COMP_PK	NULL	VARCHAR2(240)	
TIME_FK	NOT NULL	VARCHAR2(120)	
TIME_FK_KEY	NULL	NUMBER	
SALESREP_ID_FK	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NULL	NUMBER	
ITEM_FK	NOT NULL	VARCHAR2(320)	
ITEM_FK_KEY	NULL	NUMBER	
PLAN_ELEMENT_ID_FK	NOT NULL	NUMBER	
PLAN_ELEMENT_ID_FK_KEY	NULL	NUMBER	
BILL_TO_CUSTOMER_FK	NOT NULL	VARCHAR2(320)	
BILL_TO_CUSTOMER_FK_KEY	NULL	NUMBER	
SLSCHNL_FK	NOT NULL	VARCHAR2(120)	
SLSCHNL_FK_KEY	NULL	NUMBER	
TERRITORY_FK_KEY	NULL	NUMBER	
TERRITORY_ID_FK	NULL	VARCHAR2(240)	
ORGANIZATION_FK	NOT NULL	VARCHAR2(120)	
ORGANIZATION_FK_KEY	NULL	NUMBER	
GLOC_LOCATION_FK	NOT NULL	VARCHAR2(240)	
GLOC_LOCATION_FK_KEY	NULL	NUMBER	
TRX_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
TRX_CURRENCY_FK_KEY	NULL	NUMBER	
GLBL_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
GLBL_CURRENCY_FK_KEY	NULL	NUMBER	
SOB_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
SOB_CURRENCY_FK_KEY	NULL	NUMBER	
QUOTA_AMOUNT_T	NULL	NUMBER	Quota monetary amount
QUOTA_AMOUNT_S	NULL	NUMBER	Quota monetary amount
QUOTA_AMOUNT_G	NULL	NUMBER	Quota monetary amount
QUOTA_ACHIEVED_T	NULL	NUMBER	
QUOTA_ACHIEVED_S	NULL	NUMBER	
QUOTA_ACHIEVED_G	NULL	NUMBER	
BONUS_T	NULL	NUMBER	
BONUS_S	NULL	NUMBER	
BONUS_G	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

INSTANCE	NULL VARCHAR2(40)
USER_FK1	NULL VARCHAR2(2000)
USER_FK2	NULL VARCHAR2(2000)
USER_FK3	NULL VARCHAR2(2000)
USER_FK4	NULL VARCHAR2(2000)
USER_FK5	NULL VARCHAR2(2000)
USER_FK1_KEY	NULL NUMBER
USER_FK2_KEY	NULL NUMBER
USER_FK3_KEY	NULL NUMBER
USER_FK4_KEY	NULL NUMBER
USER_FK5_KEY	NULL NUMBER
USER_ATTRIBUTE1	NULL VARCHAR2(240)
USER_ATTRIBUTE2	NULL VARCHAR2(240)
USER_ATTRIBUTE3	NULL VARCHAR2(240)
USER_ATTRIBUTE4	NULL VARCHAR2(240)
USER_ATTRIBUTE5	NULL VARCHAR2(240)
USER_ATTRIBUTE6	NULL VARCHAR2(240)
USER_ATTRIBUTE7	NULL VARCHAR2(240)
USER_ATTRIBUTE8	NULL VARCHAR2(240)
USER_ATTRIBUTE9	NULL VARCHAR2(240)
USER_ATTRIBUTE10	NULL VARCHAR2(240)
USER_ATTRIBUTE11	NULL VARCHAR2(240)
USER_ATTRIBUTE12	NULL VARCHAR2(240)
USER_ATTRIBUTE13	NULL VARCHAR2(240)
USER_ATTRIBUTE14	NULL VARCHAR2(240)
USER_ATTRIBUTE15	NULL VARCHAR2(240)
USER_MEASURE1	NULL NUMBER
USER_MEASURE2	NULL NUMBER
USER_MEASURE3	NULL NUMBER
USER_MEASURE4	NULL NUMBER
USER_MEASURE5	NULL NUMBER
REQUEST_ID	NULL NUMBER
ROW_ID	NULL VARCHAR2(20)
OPERATION_CODE	NULL VARCHAR2(40)
ERROR_CODE	NULL VARCHAR2(2000)

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SF_COMP_FSTG_N1	NOT UNIQUE	0	SLSFRCF_COMP_PK

EDW_BIL_SF_PROFILE_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_COMP_PLANS_M	ELMNT_PLAN_ELEMENT_ID_PK_KEY	PLAN_ELEMENT_ID_PK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SLSFRCE_PROFILE_PK	NULL	VARCHAR2(240)	
SLSFRCE_PROFILE_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
PLAN_ELEMENT_ID_PK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
TRAINING_COST_T	NULL	NUMBER	
TRAINING_COST_S	NULL	NUMBER	
TRAINING_COST_G	NULL	NUMBER	
TRAINING_CREDITS	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SF_PROFILE_F_N1	NOT UNIQUE	5	TIME_FK_KEY
EDW_BIL_SF_PROFILE_F_N2	NOT UNIQUE	5	SALESREP_ID_FK_KEY
EDW_BIL_SF_PROFILE_F_N3	NOT UNIQUE	5	PLAN_ELEMENT_ID_PK_KEY
EDW_BIL_SF_PROFILE_F_N4	NOT UNIQUE	5	ORGANIZATION_FK_KEY
EDW_BIL_SF_PROFILE_F_N5	NOT UNIQUE	5	TRX_CURRENCY_FK_KEY
EDW_BIL_SF_PROFILE_F_N6	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_SF_PROFILE_F_N7	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_SF_PROFILE_F_U1	NOT UNIQUE	5	SLSFRCE_PROFILE_PK

EDW_BIL_SF_PROFILE_FSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_COMP_PLANS_M	ELMNT_PLAN_ELEMENT_ID_PK	PLAN_ELEMENT_ID_FK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK	SALESREP_ID_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	GLBL_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	SOB_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	TRX_CURRENCY_FK
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK	ORGANIZATION_FK
EDW_TIME_M	CDAY_CALL_DAY_PK	TIME_FK

Column Descriptions

Name	Null?	Type	Description
SLSFRCE_PROFILE_PK	NULL	VARCHAR2(240)	
TIME_FK	NOT NULL	VARCHAR2(120)	
TIME_FK_KEY	NULL	NUMBER	
SALESREP_ID_FK	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NULL	NUMBER	
PLAN_ELEMENT_ID_PK	NULL	NUMBER	
PLAN_ELEMENT_ID_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK	NOT NULL	VARCHAR2(120)	
ORGANIZATION_FK_KEY	NULL	NUMBER	
TRX_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
TRX_CURRENCY_FK_KEY	NULL	NUMBER	
SOB_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
SOB_CURRENCY_FK_KEY	NULL	NUMBER	
GLBL_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
GLBL_CURRENCY_FK_KEY	NULL	NUMBER	
TRAINING_CREDITS	NULL	NUMBER	
TRAINING_COST_T	NULL	NUMBER	
TRAINING_COST_S	NULL	NUMBER	
TRAINING_COST_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_FK1	NULL	VARCHAR2(2000)	
USER_FK2	NULL	VARCHAR2(2000)	
USER_FK3	NULL	VARCHAR2(2000)	
USER_FK4	NULL	VARCHAR2(2000)	
USER_FK5	NULL	VARCHAR2(2000)	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
USER_MEASURE1	NULL	NUMBER
USER_MEASURE2	NULL	NUMBER
USER_MEASURE3	NULL	NUMBER
USER_MEASURE4	NULL	NUMBER
USER_MEASURE5	NULL	NUMBER
REQUEST_ID	NULL	NUMBER
ROW_ID	NULL	VARCHAR2(20)
OPERATION_CODE	NULL	VARCHAR2(40)
ERROR_CODE	NULL	VARCHAR2(2000)
COLLECTION_STATUS	NULL	VARCHAR2(40)

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSFRCE_PROFL_FSTG_N1	NOT UNIQUE	0	SLSFRCE_PROFILE_PK

EDW_BIL_SF_STER_REV_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_COMP_PLANS_M	ELMNT_PLAN_ELEMENT_ID_PK_KEY	PLAN_ELEMENT_ID_FK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_MTL_UNIT_OF_MEASR_M	UOM_UOM_PK_KEY	UOM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SLSFRCE_SLSTER_REV_PK	NULL	VARCHAR2(240)	
SLSFRCE_SLSTER_REV_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
PLAN_ELEMENT_ID_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
UOM_FK_KEY	NOT NULL	NUMBER	
CREDITED_QUANTITY	NULL	NUMBER	
REVENUE_CREDITS_T	NULL	NUMBER	
REVENUE_CREDITS_S	NULL	NUMBER	
REVENUE_CREDITS_G	NULL	NUMBER	
SALES_CYCLE	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SF_STER_REV_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_SF_STER_REV_F_N10	NOT UNIQUE	5	TRADING_PARTNR_FK_KEY
EDW_BIL_SF_STER_REV_F_N11	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_SF_STER_REV_F_N12	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_SF_STER_REV_F_N13	NOT UNIQUE	5	SLSCHNL_FK_KEY
EDW_BIL_SF_STER_REV_F_N2	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_SF_STER_REV_F_N3	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_SF_STER_REV_F_N4	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_SF_STER_REV_F_N5	NOT UNIQUE	0	PLAN_ELEMENT_ID_FK_KEY
EDW_BIL_SF_STER_REV_F_N6	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_SF_STER_REV_F_N7	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_SF_STER_REV_F_N8	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_SF_STER_REV_F_N9	NOT UNIQUE	0	UOM_FK_KEY
EDW_BIL_SF_STER_REV_F_U1	UNIQUE	0	SLSFRCE_SLSTER_REV_PK

EDW_BIL_SF_STER_REV_FSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_COMP_PLANS_M	ELMNT_PLAN_ELEMENT_ID_PK	PLAN_ELEMENT_ID_FK
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK	SALESREP_ID_FK
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK	TERRITORY_ID_FK
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK	SLSCHNL_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	GLBL_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	SOB_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	TRX_CURRENCY_FK
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK	GLOC_LOCATION_FK
EDW_ITEMS_M	IREV_ITEM_REVISION_PK	ITEM_FK
EDW_MTL_UNIT_OF_MEASR_M	UOM_UOM_PK	UOM_FK
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK	ORGANIZATION_FK
EDW_TIME_M	CDAY_CALL_DAY_PK	TIME_FK
EDW_TRD_PARTNER_M	TPRT_TRADE_PARTNER_PK	BILL_TO_CUSTOMER_FK

Column Descriptions

Name	Null?	Type	Description
SLSFRCE_SLSTER_REV_PK	NULL	VARCHAR2(240)	
TIME_FK_KEY	NULL	NUMBER	
TIME_FK	NOT NULL	VARCHAR2(120)	
SALESREP_ID_FK	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NULL	NUMBER	
PLAN_ELEMENT_ID_FK_KEY	NULL	NUMBER	
PLAN_ELEMENT_ID_FK	NOT NULL	NUMBER	
BILL_TO_CUSTOMER_FK	NOT NULL	VARCHAR2(320)	
BILL_TO_CUSTOMER_FK_KEY	NULL	NUMBER	
SLSCHNL_FK	NOT NULL	VARCHAR2(120)	
SLSCHNL_FK_KEY	NULL	NUMBER	
ITEM_FK	NOT NULL	VARCHAR2(320)	
ITEM_FK_KEY	NULL	NUMBER	
TERRITORY_ID_FK	NOT NULL	VARCHAR2(240)	
TERRITORY_FK_KEY	NULL	NUMBER	
GLOC_LOCATION_FK	NOT NULL	VARCHAR2(240)	
GLOC_LOCATION_FK_KEY	NULL	NUMBER	
ORGANIZATION_FK	NOT NULL	VARCHAR2(120)	
ORGANIZATION_FK_KEY	NULL	NUMBER	
UOM_FK_KEY	NULL	NUMBER	
UOM_FK	NOT NULL	VARCHAR2(80)	
TRX_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
TRX_CURRENCY_FK_KEY	NULL	NUMBER	
SOB_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
SOB_CURRENCY_FK_KEY	NULL	NUMBER	
GLBL_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
GLBL_CURRENCY_FK_KEY	NULL	NUMBER	
CREDITED_QUANTITY	NULL	NUMBER	
REVENUE_CREDITS_T	NULL	NUMBER	
REVENUE_CREDITS_S	NULL	NUMBER	
REVENUE_CREDITS_G	NULL	NUMBER	
SALES_CYCLE	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

INSTANCE	NULL VARCHAR2(40)
USER_FK1	NULL VARCHAR2(2000)
USER_FK2	NULL VARCHAR2(2000)
USER_FK3	NULL VARCHAR2(2000)
USER_FK4	NULL VARCHAR2(2000)
USER_FK5	NULL VARCHAR2(2000)
USER_FK1_KEY	NULL NUMBER
USER_FK2_KEY	NULL NUMBER
USER_FK3_KEY	NULL NUMBER
USER_FK4_KEY	NULL NUMBER
USER_FK5_KEY	NULL NUMBER
USER_ATTRIBUTE1	NULL VARCHAR2(240)
USER_ATTRIBUTE2	NULL VARCHAR2(240)
USER_ATTRIBUTE3	NULL VARCHAR2(240)
USER_ATTRIBUTE4	NULL VARCHAR2(240)
USER_ATTRIBUTE5	NULL VARCHAR2(240)
USER_ATTRIBUTE6	NULL VARCHAR2(240)
USER_ATTRIBUTE7	NULL VARCHAR2(240)
USER_ATTRIBUTE8	NULL VARCHAR2(240)
USER_ATTRIBUTE9	NULL VARCHAR2(240)
USER_ATTRIBUTE10	NULL VARCHAR2(240)
USER_ATTRIBUTE11	NULL VARCHAR2(240)
USER_ATTRIBUTE12	NULL VARCHAR2(240)
USER_ATTRIBUTE13	NULL VARCHAR2(240)
USER_ATTRIBUTE14	NULL VARCHAR2(240)
USER_ATTRIBUTE15	NULL VARCHAR2(240)
USER_MEASURE1	NULL NUMBER
USER_MEASURE2	NULL NUMBER
USER_MEASURE3	NULL NUMBER
USER_MEASURE4	NULL NUMBER
USER_MEASURE5	NULL NUMBER
REQUEST_ID	NULL NUMBER
ROW_ID	NULL VARCHAR2(20)
OPERATION_CODE	NULL VARCHAR2(40)
ERROR_CODE	NULL VARCHAR2(2000)
COLLECTION_STATUS	NULL VARCHAR2(40)

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SF_STER_REV_FSTG_N1	NOT UNIQUE	0	SLSFRCE_SLSTER_REV_PK

EDW_BIL_SLSFRCE_M

Column Descriptions

Name	Null?	Type	Description
SREP_SALESREP_ID_PK_KEY	NOT NULL	VARCHAR2(240)	
SREP_SALESREP_ID_PK	NOT NULL	NUMBER	
SREP_ROW_ID	NULL	VARCHAR2(20)	
SREP_NAME	NOT NULL	VARCHAR2(40)	
SREP_SALESFORCE_ID	NULL	NUMBER	
SREP_PERSON_ID	NULL	NUMBER(15)	- Retrofitted
SREP_JOB_ID	NULL	NUMBER	
SREP_JOB_TITLE	NULL	VARCHAR2(30)	
SREP_ROLE_ID	NOT NULL	NUMBER(15)	
SREP_START_DATE	NULL	DATE	
SREP_END_DATE	NULL	DATE	
SREP_STATUS	NOT NULL	VARCHAR2(1)	Status of salesforce record - either Active or Inactive
SREP_COMPEN_CURRENCY_CODE	NULL	VARCHAR2(15)	- Retrofitted
SREP_EMAIL_ADDRESS	NULL	VARCHAR2(30)	- Retrofitted
SREP_COST_CENTER	NULL	VARCHAR2(30)	- Retrofitted
SREP_COMMISSIONABLE_FLAG	NULL	VARCHAR2(1)	
SREP_TYPE	NOT NULL	VARCHAR2(30)	The type of salesforce record - either employee or sales partner
SREP_ASSIGNED_TO_USER_ID	NULL	NUMBER(15)	- Retrofitted
SREP_ADDUP_FROM_REV_CLASS_FLAG	NULL	VARCHAR2(1)	
SREP_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
SREP_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
SGRP1_SALES_GROUP1_PK	NOT NULL	NUMBER	
SGRP1_SALES_GROUP1_PK_KEY	NOT NULL	NUMBER	
SGRP1_PK_ROWID	NULL	VARCHAR2(20)	
SGRP1_DP	NULL	VARCHAR2(240)	
SGRP1_NAME	NULL	VARCHAR2(240)	
SGRP1_DESCRIPTION	NULL	VARCHAR2(240)	
SGRP1_ACCOUNTING_CODE	NULL	VARCHAR2(80)	
SGRP1_START_DATE_ACTIVE	NULL	DATE	
SGRP1_END_DATE_ACTIVE	NULL	VARCHAR2(240)	
SGRP1_INSTANCE	NULL	VARCHAR2(40)	
SGRP1_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
SGRP1_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
SGRP1_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SGRP1_USER_ATTRIBUTE4	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE5	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE6	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE7	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE8	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE10	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE11	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE12	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE13	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE14	NULL	VARCHAR2(240)
SGRP1_USER_ATTRIBUTE15	NULL	VARCHAR2(240)
SGRP2_SALES_GROUP2_PK	NOT NULL	NUMBER
SGRP2_SALES_GROUP2_PK_KEY	NOT NULL	NUMBER
SGRP2_PK_ROWID	NULL	VARCHAR2(20)
SGRP2_DP	NULL	VARCHAR2(240)
SGRP2_INSTANCE	NULL	VARCHAR2(40)
SGRP2_NAME	NULL	VARCHAR2(80)
SGRP2_DESCRIPTION	NULL	VARCHAR2(240)
SGRP2_ACCOUNTING_CODE	NULL	VARCHAR2(80)
SGRP2_START_DATE_ACTIVE	NULL	VARCHAR2(240)
SGRP2_END_DATE_ACTIVE	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE1	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE2	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE3	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE4	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE5	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE6	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE7	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE8	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE10	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE11	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE12	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE13	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE14	NULL	VARCHAR2(240)
SGRP2_USER_ATTRIBUTE15	NULL	VARCHAR2(240)
SGRP3_SALES_GROUP3_PK	NOT NULL	NUMBER
SGRP3_SALES_GROUP3_PK_KEY	NOT NULL	NUMBER
SGRP3_PK_ROWID	NULL	VARCHAR2(20)
SGRP3_DP	NULL	VARCHAR2(240)
SGRP3_INSTANCE	NULL	VARCHAR2(40)
SGRP3_NAME	NULL	VARCHAR2(80)
SGRP3_DESCRIPTION	NULL	VARCHAR2(240)
SGRP3_ACCOUNTING_CODE	NULL	VARCHAR2(80)
SGRP3_START_DATE_ACTIVE	NULL	VARCHAR2(240)
SGRP3_END_DATE_ACTIVE	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE1	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE2	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE3	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE4	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE5	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE6	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE7	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE8	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE10	NULL	VARCHAR2(240)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SGRP3_USER_ATTRIBUTE11	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE12	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE13	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE14	NULL	VARCHAR2(240)
SGRP3_USER_ATTRIBUTE15	NULL	VARCHAR2(240)
SGRP4_SALES_GROUP_PK	NULL	NUMBER
SGRP4_SALES_GROUP4_PK_KEY	NULL	NUMBER
SGRP4_PK_ROWID	NULL	VARCHAR2(20)
SGRP4_DP	NULL	VARCHAR2(240)
SGRP4_INSTANCE	NULL	VARCHAR2(40)
SGRP4_NAME	NULL	VARCHAR2(80)
SGRP4_DESCRIPTION	NULL	VARCHAR2(240)
SGRP4_ACCOUNTING_CODE	NULL	VARCHAR2(80)
SGRP4_START_DATE_ACTIVE	NULL	VARCHAR2(240)
SGRP4_END_DATE_ACTIVE	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE1	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE2	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE3	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE4	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE5	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE6	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE7	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE8	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE10	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE11	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE12	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE13	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE14	NULL	VARCHAR2(240)
SGRP4_USER_ATTRIBUTE15	NULL	VARCHAR2(240)
SGRP5_SALES_GROUP_PK	NULL	NUMBER
SGRP5_SALES_GROUP_PK_KEY	NULL	NUMBER
SGRP5_PK_ROWID	NULL	VARCHAR2(20)
SGRP5_DP	NULL	VARCHAR2(240)
SGRP5_INSTANCE	NULL	VARCHAR2(40)
SGRP5_NAME	NULL	VARCHAR2(80)
SGRP5_DESCRIPTION	NULL	VARCHAR2(240)
SGRP5_ACCOUNTING_CODE	NULL	VARCHAR2(80)
SGRP5_START_DATE_ACTIVE	NULL	VARCHAR2(240)
SGRP5_END_DATE_ACTIVE	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE1	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE2	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE3	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE4	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE5	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE6	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE7	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE8	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE10	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE11	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE12	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE13	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE14	NULL	VARCHAR2(240)
SGRP5_USER_ATTRIBUTE15	NULL	VARCHAR2(240)
SGRP6_SALES_GROUP6_PK	NULL	NUMBER
SGRP6_SALES_GROUP6_PK_KEY	NULL	NUMBER

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SGRP6_PK_ROWID	NULL VARCHAR2(20)
SGRP6_DP	NULL VARCHAR2(240)
SGRP6_INSTANCE	NULL VARCHAR2(40)
SGRP6_NAME	NULL VARCHAR2(40)
SGRP6_DESCRIPTION	NULL VARCHAR2(240)
SGRP6_ACCOUNTING_CODE	NULL VARCHAR2(80)
SGRP6_START_DATE_ACTIVE	NULL VARCHAR2(240)
SGRP6_END_DATE_ACTIVE	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE1	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE2	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE3	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE4	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE5	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE6	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE7	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE8	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE9	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE10	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE11	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE12	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE13	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE14	NULL VARCHAR2(240)
SGRP6_USER_ATTRIBUTE15	NULL VARCHAR2(240)
SGRP7_SALES_GROUP7_PK	NULL NUMBER
SGRP7_SALES_GROUP7_PK_KEY	NULL NUMBER
SGRP7_PK_ROWID	NULL VARCHAR2(20)
SGRP7_DP	NULL VARCHAR2(240)
SGRP7_INSTANCE	NULL VARCHAR2(40)
SGRP7_NAME	NULL VARCHAR2(80)
SGRP7_DESCRIPTION	NULL VARCHAR2(240)
SGRP7_ACCOUNTING_CODE	NULL VARCHAR2(80)
SGRP7_START_DATE_ACTIVE	NULL VARCHAR2(240)
SGRP7_END_DATE_ACTIVE	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE1	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE2	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE3	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE4	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE5	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE6	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE7	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE8	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE9	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE10	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE11	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE12	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE13	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE14	NULL VARCHAR2(240)
SGRP7_USER_ATTRIBUTE15	NULL VARCHAR2(240)
ALL_PK	NULL VARCHAR2(40)
ALL_PK_KEY	NULL NUMBER
ALL_PK_ROWID	NULL VARCHAR2(20)
ALL_NAME	NULL VARCHAR2(80)
LAST_UPDATE_DATE	NULL DATE
CREATION_DATE	NULL DATE

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSF_A_LTC

Column Descriptions

Name	Null?	Type	Description
ALL_PK	NULL	VARCHAR2(40)	
ALL_PK_KEY	NULL	NUMBER	
ALL_PK_ROW_ID	NULL	VARCHAR2(20)	
NAME	NULL	VARCHAR2(80)	

EDW_BIL_SLSF_SGRP1_LSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP2_LSTG	SALES_GROUP2_PK	SALES_GROUP2_FK

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP1_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
SALES_GROUP2_FK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP2_FK_KEY	NULL	NUMBER	
SGRP1_DP	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
ACCOUNTING_CODE	NULL	VARCHAR2(80)	
START_DATE_ACTIVE	NULL	DATE	
END_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP_LSTG_N1	NOT UNIQUE	0	SALES_GROUP1_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSF_SGRP1_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP2_LTC	SALES_GROUP2_PK_KEY	SALES_GROUP2_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP1_PK	NOT NULL	NUMBER	
SALES_GROUP1_PK_KEY	NOT NULL	NUMBER	
SALES_GROUP2_FK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP2_FK_KEY	NOT NULL	NUMBER	
SGRP1_DP		NULL VARCHAR2(240)	
NAME		NULL VARCHAR2(240)	
DESCRIPTION		NULL VARCHAR2(240)	
ACCOUNTING_CODE		NULL VARCHAR2(80)	
START_DATE_ACTIVE		NULL DATE	
END_DATE_ACTIVE		NULL DATE	
INSTANCE		NULL VARCHAR2(40)	
USER_ATTRIBUTE1		NULL VARCHAR2(240)	
USER_ATTRIBUTE2		NULL VARCHAR2(240)	
USER_ATTRIBUTE3		NULL VARCHAR2(240)	
USER_ATTRIBUTE4		NULL VARCHAR2(240)	
USER_ATTRIBUTE5		NULL VARCHAR2(240)	
USER_ATTRIBUTE6		NULL VARCHAR2(240)	
USER_ATTRIBUTE7		NULL VARCHAR2(240)	
USER_ATTRIBUTE8		NULL VARCHAR2(240)	
USER_ATTRIBUTE9		NULL VARCHAR2(240)	
USER_ATTRIBUTE10		NULL VARCHAR2(240)	
USER_ATTRIBUTE11		NULL VARCHAR2(240)	
USER_ATTRIBUTE12		NULL VARCHAR2(240)	
USER_ATTRIBUTE13		NULL VARCHAR2(240)	
USER_ATTRIBUTE14		NULL VARCHAR2(240)	
USER_ATTRIBUTE15		NULL VARCHAR2(240)	
LAST_UPDATE_DATE		NULL DATE	
CREATION_DATE		NULL DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSFRCE_TGRP1_U1	UNIQUE	0	SALES_GROUP2_FK_KEY
EDW_BIL_SLSFRCE_TGRP1_U2	UNIQUE	0	SALES_GROUP1_PK
		2	SALES_GROUP1_PK_KEY

EDW_BIL_SLSF_SGRP2_LSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP3_LSTG	SALES_GROUP3_PK	SALES_GROUP3_FK

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP2_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
SALES_GROUP3_FK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP3_FK_KEY	NULL	NUMBER	
SGRP2_DP	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
ACCOUNTING_CODE	NULL	VARCHAR2(80)	
END_DATE_ACTIVE	NULL	DATE	
START_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP2_LSTG_N1	NOT UNIQUE	0	SALES_GROUP2_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSF_SGRP2_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP3_LTC	SALES_GROUP3_PK_KEY	SALES_GROUP3_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP2_PK	NOT NULL	NUMBER	
SALES_GROUP2_PK_KEY	NOT NULL	NUMBER	
SALES_GROUP3_FK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP3_FK_KEY	NOT NULL	NUMBER	
SGRP2_DP		NULL VARCHAR2(240)	
NAME		NULL VARCHAR2(240)	
DESCRIPTION		NULL VARCHAR2(240)	
ACCOUNTING_CODE		NULL VARCHAR2(80)	
START_DATE_ACTIVE		NULL DATE	
END_DATE_ACTIVE		NULL DATE	
INSTANCE		NULL VARCHAR2(40)	
USER_ATTRIBUTE1		NULL VARCHAR2(240)	
USER_ATTRIBUTE2		NULL VARCHAR2(240)	
USER_ATTRIBUTE3		NULL VARCHAR2(240)	
USER_ATTRIBUTE4		NULL VARCHAR2(240)	
USER_ATTRIBUTE5		NULL VARCHAR2(240)	
USER_ATTRIBUTE6		NULL VARCHAR2(240)	
USER_ATTRIBUTE7		NULL VARCHAR2(240)	
USER_ATTRIBUTE8		NULL VARCHAR2(240)	
USER_ATTRIBUTE9		NULL VARCHAR2(240)	
USER_ATTRIBUTE10		NULL VARCHAR2(240)	
USER_ATTRIBUTE11		NULL VARCHAR2(240)	
USER_ATTRIBUTE12		NULL VARCHAR2(240)	
USER_ATTRIBUTE13		NULL VARCHAR2(240)	
USER_ATTRIBUTE14		NULL VARCHAR2(240)	
USER_ATTRIBUTE15		NULL VARCHAR2(240)	
LAST_UPDATE_DATE		NULL DATE	
CREATION_DATE		NULL DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSFRCE_SGRP2_LSTG_U1	UNIQUE	0	SALES_GROUP2_PK_KEY
EDW_BIL_SLSFRCE_SGRP2_LTC_U2	UNIQUE	0	SALES_GROUP2_PK
		2	SALES_GROUP2_PK_KEY

EDW_BIL_SLSF_SGRP3_LSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP4_LSTG	SALES_GROUP4_PK	SALES_GROUP4_FK

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP3_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
SALES_GROUP4_FK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP4_FK_KEY	NULL	NUMBER	
SGRP3_DP	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
ACCOUNTING_CODE	NULL	VARCHAR2(80)	
START_DATE_ACTIVE	NULL	DATE	
END_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP3_LSTG_N1	NOT UNIQUE	0	SALES_GROUP3_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSF_SGRP3_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP4_LTC	SALES_GROUP4_PK_KEY	SALES_GROUP4_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP3_PK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP3_PK_KEY	NOT NULL	NUMBER	
SALES_GROUP4_FK	NOT NULL	NUMBER	
SALES_GROUP4_FK_KEY	NOT NULL	NUMBER	
SGRP3_DP		NULL VARCHAR2(240)	
NAME		NULL VARCHAR2(240)	
DESCRIPTION		NULL VARCHAR2(240)	
ACCOUNTING_CODE		NULL VARCHAR2(80)	
START_DATE_ACTIVE		NULL DATE	
END_DATE_ACTIVE		NULL DATE	
INSTANCE		NULL VARCHAR2(40)	
USER_ATTRIBUTE1		NULL VARCHAR2(240)	
USER_ATTRIBUTE2		NULL VARCHAR2(240)	
USER_ATTRIBUTE3		NULL VARCHAR2(240)	
USER_ATTRIBUTE4		NULL VARCHAR2(240)	
USER_ATTRIBUTE5		NULL VARCHAR2(240)	
USER_ATTRIBUTE6		NULL VARCHAR2(240)	
USER_ATTRIBUTE7		NULL VARCHAR2(240)	
USER_ATTRIBUTE8		NULL VARCHAR2(240)	
USER_ATTRIBUTE9		NULL VARCHAR2(240)	
USER_ATTRIBUTE10		NULL VARCHAR2(240)	
USER_ATTRIBUTE11		NULL VARCHAR2(240)	
USER_ATTRIBUTE12		NULL VARCHAR2(240)	
USER_ATTRIBUTE13		NULL VARCHAR2(240)	
USER_ATTRIBUTE14		NULL VARCHAR2(240)	
USER_ATTRIBUTE15		NULL VARCHAR2(240)	
LAST_UPDATE_DATE		NULL DATE	
CREATION_DATE		NULL DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP3_LTC_U1	UNIQUE	0	SALES_GROUP3_PK_KEY
EDW_BIL_SLSF_SGRP3_LTC_U2	UNIQUE	0	SALES_GROUP3_PK
		2	SALES_GROUP3_PK_KEY

EDW_BIL_SLSF_SGRP4_LSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP5_LSTG	SALES_GROUP5_PK	SALES_GROUP5_FK

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP4_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
SALES_GROUP5_FK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP5_FK_KEY	NULL	NUMBER	
SGRP4_DP	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
ACCOUNTING_CODE	NULL	VARCHAR2(80)	
START_DATE_ACTIVE	NULL	DATE	
END_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP4_LTC_N1	NOT UNIQUE	0	SALES_GROUP4_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSF_SGRP4_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP5_LTC	SALES_GROUP5_PK_KEY	SALES_GROUP5_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP4_PK	NOT NULL	NUMBER	
SALES_GROUP4_PK_KEY	NOT NULL	NUMBER	
SALES_GROUP5_FK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP5_FK_KEY	NOT NULL	NUMBER	
SGRP4_DP		NULL VARCHAR2(240)	
NAME		NULL VARCHAR2(240)	
DESCRIPTION		NULL VARCHAR2(240)	
ACCOUNTING_CODE		NULL VARCHAR2(80)	
START_DATE_ACTIVE		NULL DATE	
END_DATE_ACTIVE		NULL DATE	
INSTANCE		NULL VARCHAR2(40)	
USER_ATTRIBUTE1		NULL VARCHAR2(240)	
USER_ATTRIBUTE2		NULL VARCHAR2(240)	
USER_ATTRIBUTE3		NULL VARCHAR2(240)	
USER_ATTRIBUTE4		NULL VARCHAR2(240)	
USER_ATTRIBUTE5		NULL VARCHAR2(240)	
USER_ATTRIBUTE6		NULL VARCHAR2(240)	
USER_ATTRIBUTE7		NULL VARCHAR2(240)	
USER_ATTRIBUTE8		NULL VARCHAR2(240)	
USER_ATTRIBUTE9		NULL VARCHAR2(240)	
USER_ATTRIBUTE10		NULL VARCHAR2(240)	
USER_ATTRIBUTE11		NULL VARCHAR2(240)	
USER_ATTRIBUTE12		NULL VARCHAR2(240)	
USER_ATTRIBUTE13		NULL VARCHAR2(240)	
USER_ATTRIBUTE14		NULL VARCHAR2(240)	
USER_ATTRIBUTE15		NULL VARCHAR2(240)	
LAST_UPDATE_DATE		NULL DATE	
CREATION_DATE		NULL DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP4_LTC_U1	UNIQUE	0	SALES_GROUP4_PK_KEY
EDW_BIL_SLSF_SGRP4_LTC_U2	UNIQUE	0	SALES_GROUP4_PK
		2	SALES_GROUP4_PK_KEY

EDW_BIL_SLSF_SGRP5_LSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP6_LSTG	SALES_GROUP6_PK	SALES_GROUP6_FK

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP5_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
SALES_GROUP6_FK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP6_FK_KEY	NULL	NUMBER	
SGRP5_DP	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
ACCOUNTING_CODE	NULL	VARCHAR2(80)	
START_DATE_ACTIVE	NULL	DATE	
END_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP5_LTC_N1	NOT UNIQUE	0	SALES_GROUP5_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSF_SGRP5_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP6_LTC	SALES_GROUP6_PK_KEY	SALES_GROUP6_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP5_PK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP5_PK_KEY	NOT NULL	NUMBER	
SALES_GROUP6_FK	NOT NULL	NUMBER	
SALES_GROUP6_FK_KEY	NOT NULL	NUMBER	
SGRP5_DP		NULL VARCHAR2(240)	
NAME		NULL VARCHAR2(240)	
DESCRIPTION		NULL VARCHAR2(240)	
ACCOUNTING_CODE		NULL VARCHAR2(80)	
START_DATE_ACTIVE		NULL DATE	
END_DATE_ACTIVE		NULL DATE	
INSTANCE		NULL VARCHAR2(40)	
USER_ATTRIBUTE1		NULL VARCHAR2(240)	
USER_ATTRIBUTE2		NULL VARCHAR2(240)	
USER_ATTRIBUTE3		NULL VARCHAR2(240)	
USER_ATTRIBUTE4		NULL VARCHAR2(240)	
USER_ATTRIBUTE5		NULL VARCHAR2(240)	
USER_ATTRIBUTE6		NULL VARCHAR2(240)	
USER_ATTRIBUTE7		NULL VARCHAR2(240)	
USER_ATTRIBUTE8		NULL VARCHAR2(240)	
USER_ATTRIBUTE9		NULL VARCHAR2(240)	
USER_ATTRIBUTE10		NULL VARCHAR2(240)	
USER_ATTRIBUTE11		NULL VARCHAR2(240)	
USER_ATTRIBUTE12		NULL VARCHAR2(240)	
USER_ATTRIBUTE13		NULL VARCHAR2(240)	
USER_ATTRIBUTE14		NULL VARCHAR2(240)	
USER_ATTRIBUTE15		NULL VARCHAR2(240)	
LAST_UPDATE_DATE		NULL DATE	
CREATION_DATE		NULL DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP5_LTC_U1	UNIQUE	0	SALES_GROUP5_PK_KEY
EDW_BIL_SLSF_SGRP5_LTC_U2	UNIQUE	0	SALES_GROUP5_PK
		2	SALES_GROUP5_PK_KEY

EDW_BIL_SLSF_SGRP6_LSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP7_LSTG	SALES_GROUP7_PK	SALES_GROUP7_FK

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP6_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
SALES_GROUP7_FK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP7_FK_KEY	NULL	NUMBER	
SGRP6_DP	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
ACCOUNTING_CODE	NULL	VARCHAR2(80)	
START_DATE_ACTIVE	NULL	DATE	
END_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP6_LSTG_N1	NOT UNIQUE	0	SALES_GROUP6_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSF_SGRP6_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP7_LTC	SALES_GROUP7_PK_KEY	SALES_GROUP7_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP6_PK	NOT NULL	NUMBER	Parent sales group identifier
SALES_GROUP6_PK_KEY	NOT NULL	NUMBER	
SALES_GROUP7_FK	NOT NULL	NUMBER	
SALES_GROUP7_FK_KEY	NOT NULL	NUMBER	
SGRP6_DP		NULL VARCHAR2(240)	
NAME		NULL VARCHAR2(240)	
DESCRIPTION		NULL VARCHAR2(240)	
ACCOUNTING_CODE		NULL VARCHAR2(80)	
START_DATE_ACTIVE		NULL DATE	
END_DATE_ACTIVE		NULL DATE	
INSTANCE		NULL VARCHAR2(40)	
USER_ATTRIBUTE1		NULL VARCHAR2(240)	
USER_ATTRIBUTE2		NULL VARCHAR2(240)	
USER_ATTRIBUTE3		NULL VARCHAR2(240)	
USER_ATTRIBUTE4		NULL VARCHAR2(240)	
USER_ATTRIBUTE5		NULL VARCHAR2(240)	
USER_ATTRIBUTE6		NULL VARCHAR2(240)	
USER_ATTRIBUTE7		NULL VARCHAR2(240)	
USER_ATTRIBUTE8		NULL VARCHAR2(240)	
USER_ATTRIBUTE9		NULL VARCHAR2(240)	
USER_ATTRIBUTE10		NULL VARCHAR2(240)	
USER_ATTRIBUTE11		NULL VARCHAR2(240)	
USER_ATTRIBUTE12		NULL VARCHAR2(240)	
USER_ATTRIBUTE13		NULL VARCHAR2(240)	
USER_ATTRIBUTE14		NULL VARCHAR2(240)	
USER_ATTRIBUTE15		NULL VARCHAR2(240)	
LAST_UPDATE_DATE		NULL DATE	
CREATION_DATE		NULL DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP6_LTC_U1	UNIQUE	0	SALES_GROUP6_PK_KEY
EDW_BIL_SLSF_SGRP6_LTC_U2	UNIQUE	0	SALES_GROUP6_PK
		2	SALES_GROUP6_PK_KEY

EDW_BIL_SLSF_SGRP7_LSTG

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP7_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
ALL_FK	NULL	VARCHAR2(40)	
ALL_FK_KEY	NULL	NUMBER	
SGRP7_DP	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
ACCOUNTING_CODE	NULL	VARCHAR2(80)	
START_DATE_ACTIVE	NULL	DATE	
END_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP7_LSTG_N1	NOT UNIQUE	0	SALES_GROUP7_PK

EDW_BIL_SLSF_SGRP7_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_A_LTC	ALL_PK_KEY	ALL_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SALES_GROUP7_PK	NOT NULL	NUMBER	
SALES_GROUP7_PK_KEY	NOT NULL	NUMBER	
ALL_FK	NULL	VARCHAR2(40)	
ALL_FK_KEY	NOT NULL	NUMBER	
SGRP7_DP	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
ACCOUNTING_CODE	NULL	VARCHAR2(80)	
START_DATE_ACTIVE	NULL	DATE	
END_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SGRP7_LTC_U1	UNIQUE	0	SALES_GROUP7_PK_KEY
EDW_BIL_SLSF_SGRP7_LTC_U2	UNIQUE	0	SALES_GROUP7_PK
		2	SALES_GROUP7_PK_KEY

EDW_BIL_SLSF_SREP_LSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP1_LSTG	SALES_GROUP1_PK	SALES_GROUP1_FK

Column Descriptions

Name	Null?	Type	Description
SALESREP_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
SALES_GROUP1_FK	NOT NULL	NUMBER	
SALES_GROUP1_FK_KEY	NULL	NUMBER	
SREP_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(40)	
PERSON_ID	NULL	NUMBER(15)	- Retrofitted
SALESFORCE_ID	NULL	NUMBER	
START_DATE	NULL	DATE	
END_DATE	NULL	DATE	
JOB_TITLE	NULL	VARCHAR2(30)	
JOB_ID	NULL	NUMBER	
ROLE_ID	NOT NULL	NUMBER(15)	
STATUS	NULL	VARCHAR2(30)	- Retrofitted
ADDUP_FROM_REV_CLASS_FLAG	NULL	VARCHAR2(1)	
EMAIL_ADDRESS	NULL	VARCHAR2(30)	- Retrofitted
ASSIGNED_TO_USER_ID	NULL	NUMBER(15)	- Retrofitted
COST_CENTER	NULL	VARCHAR2(30)	- Retrofitted
COMPENSATION_CURRENCY_CODE	NULL	VARCHAR2(15)	- Retrofitted
TYPE	NULL	VARCHAR2(80)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSFRCE_SREP_LSTG_N1	NOT UNIQUE	0	SALESREP_PK

EDW_BIL_SLSF_SREP_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSF_SGRP1_LTC	SALES_GROUP1_PK_KEY	SALES_GROUP1_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SALESREP_PK	NOT NULL	NUMBER	
SALESREP_PK_KEY	NOT NULL	VARCHAR2(240)	
SALES_GROUP1_FK	NOT NULL	NUMBER	
SALES_GROUP1_FK_KEY	NOT NULL	NUMBER	
SREP_DP		VARCHAR2(240)	
PERSON_ID		NUMBER(15)	- Retrofitted
START_DATE		DATE	
END_DATE		DATE	
JOB_TITLE		VARCHAR2(30)	
JOB_ID		NUMBER	
ROLE_ID	NOT NULL	NUMBER(15)	
ROLE_NAME		VARCHAR2(240)	
STATUS		VARCHAR2(30)	- Retrofitted
ADDUP_FROM_REV_CLASS_FLAG		VARCHAR2(1)	
ROLE_DESCRIPTION		VARCHAR2(240)	
EMAIL_ADDRESS		VARCHAR2(30)	- Retrofitted
ASSIGNED_TO_USER_ID		NUMBER(15)	- Retrofitted
COST_CENTER		VARCHAR2(30)	- Retrofitted
COMPENSATION_CURRENCY_CODE		VARCHAR2(15)	- Retrofitted
TYPE		VARCHAR2(80)	
INSTANCE		VARCHAR2(40)	
USER_ATTRIBUTE1		VARCHAR2(240)	
USER_ATTRIBUTE2		VARCHAR2(240)	
USER_ATTRIBUTE3		VARCHAR2(240)	
USER_ATTRIBUTE4		VARCHAR2(240)	
USER_ATTRIBUTE5		VARCHAR2(240)	
USER_ATTRIBUTE6		VARCHAR2(240)	
USER_ATTRIBUTE7		VARCHAR2(240)	
USER_ATTRIBUTE8		VARCHAR2(240)	
USER_ATTRIBUTE9		VARCHAR2(240)	
USER_ATTRIBUTE10		VARCHAR2(240)	
USER_ATTRIBUTE11		VARCHAR2(240)	
USER_ATTRIBUTE12		VARCHAR2(240)	
USER_ATTRIBUTE13		VARCHAR2(240)	
USER_ATTRIBUTE14		VARCHAR2(240)	
USER_ATTRIBUTE15		VARCHAR2(240)	
LAST_UPDATE_DATE		DATE	
CREATION_DATE		DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSF_SREP_U1	UNIQUE	0	SALESREP_PK_KEY
EDW_BIL_SLSF_SREP_U2	UNIQUE	0	SALESREP_PK
		2	SALESREP_PK_KEY

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSTER_A_LTC

Column Descriptions

Name	Null?	Type	Description
ALL_PK	NULL	VARCHAR2(40)	
ALL_PK_KEY	NULL	NUMBER	
ALL_PK_ROW_ID	NULL	VARCHAR2(20)	
NAME	NULL	VARCHAR2(80)	

EDW_BIL_SLSTER_M

Column Descriptions

Name	Null?	Type	Description
TERR_TERRITORY_ID_PK	NOT NULL	NUMBER	
TERR_TERRITORY_ID_PK_KEY (PK)	NOT NULL	NUMBER	
TERR_PK_ROWID	NULL	VARCHAR2(20)	
TERR_DP	NULL	VARCHAR2(240)	
TERR_INSTANCE	NULL	VARCHAR2(40)	
TERR_NAME	NULL	VARCHAR2(240)	
TERR_DESCRIPTION	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
TERR_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
TGRP1_TERRITORY_ID_PK	NULL	NUMBER	
TGRP1_TERRITORY_ID_PK_KEY	NOT NULL	NUMBER	
TGRP1_PK_ROWID	NULL	VARCHAR2(20)	
TGRP1_DP	NULL	VARCHAR2(240)	
TGRP1_INSTANCE	NULL	VARCHAR2(40)	
TGRP1_NAME	NOT NULL	VARCHAR2(60)	
TGRP1_DESCRIPTION	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
TGRP1_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
TGRP2_TERRITORY_ID_PK	NULL	NUMBER	
TGRP2_TERRITORY_ID_PK_KEY	NULL	NUMBER	
TGRP2_PK_ROWID	NULL	VARCHAR2(20)	
TGRP2_DP	NULL	VARCHAR2(240)	
TGRP2_INSTANCE	NULL	VARCHAR2(40)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

TGRP2_NAME	NULL	VARCHAR2(60)
TGRP2_DESCRIPTION	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE1	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE2	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE3	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE4	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE5	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE6	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE7	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE8	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE10	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE11	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE12	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE13	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE14	NULL	VARCHAR2(240)
TGRP2_USER_ATTRIBUTE15	NULL	VARCHAR2(240)
TGRP3_TERRITORY_ID_PK	NULL	NUMBER
TGRP3_TERRITORY_ID_PK_KEY	NULL	VARCHAR2(240)
TGRP3_PK_ROWID	NULL	VARCHAR2(20)
TGRP3_DP	NULL	VARCHAR2(240)
TGRP3_INSTANCE	NULL	VARCHAR2(40)
TGRP3_NAME	NULL	NUMBER
TGRP3_DESCRIPTION	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE1	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE2	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE3	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE4	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE5	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE6	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE7	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE8	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE10	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE11	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE12	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE13	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE14	NULL	VARCHAR2(240)
TGRP3_USER_ATTRIBUTE15	NULL	VARCHAR2(240)
TGRP4_TERRITORY_ID_PK	NULL	NUMBER
TGRP4_TERRITORY_ID_PK_KEY	NULL	NUMBER
TGRP4_PK_ROWID	NULL	VARCHAR2(20)
TGRP4_DP	NULL	VARCHAR2(240)
TGRP4_NAME	NULL	VARCHAR2(60)
TGRP4_INSTANCE	NULL	VARCHAR2(40)
TGRP4_DESCRIPTION	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE1	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE2	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE3	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE4	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE5	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE6	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE7	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE8	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE10	NULL	VARCHAR2(240)
TGRP4_USER_ATTRIBUTE11	NULL	VARCHAR2(240)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

TGRP4_USER_ATTRIBUTE12	NULL VARCHAR2(240)
TGRP4_USER_ATTRIBUTE13	NULL VARCHAR2(240)
TGRP4_USER_ATTRIBUTE14	NULL VARCHAR2(240)
TGRP4_USER_ATTRIBUTE15	NULL VARCHAR2(240)
TGRP5_TERRITORY_ID_PK	NULL VARCHAR2(240)
TGRP5_TERRITORY_ID_PK_KEY	NULL VARCHAR2(240)
TGRP5_PK_ROWID	NULL VARCHAR2(20)
TGRP5_DP	NULL VARCHAR2(240)
TGRP5_INSTANCE	NULL VARCHAR2(40)
TGRP5_NAME	NULL VARCHAR2(60)
TGRP5_DESCRIPTION	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE1	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE2	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE3	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE4	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE5	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE6	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE7	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE8	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE9	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE10	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE11	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE12	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE13	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE14	NULL VARCHAR2(240)
TGRP5_USER_ATTRIBUTE15	NULL VARCHAR2(240)
TGRP6_TERRITORY_ID_PK_KEY	NULL NUMBER
TGRP6_TERRITORY_ID_PK	NULL NUMBER
TGRP6_PK_ROWID	NULL VARCHAR2(20)
TGRP6_DP	NULL VARCHAR2(240)
TGRP6_INSTANCE	NULL VARCHAR2(40)
TGRP6_NAME	NULL VARCHAR2(60)
TGRP6_DESCRIPTION	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE1	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE2	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE3	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE4	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE5	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE6	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE7	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE8	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE9	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE10	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE11	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE12	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE13	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE14	NULL VARCHAR2(240)
TGRP6_USER_ATTRIBUTE15	NULL VARCHAR2(240)
TGRP7_TERRITORY_ID_PK	NULL NUMBER
TGRP7_TERRITORY_ID_PK_KEY	NULL NUMBER
TGRP7_PK_ROWID	NULL VARCHAR2(20)
TGRP7_DP	NULL VARCHAR2(240)
TGRP7_INSTANCE	NULL VARCHAR2(40)
TGRP7_NAME	NULL VARCHAR2(60)
TGRP7_DESCRIPTION	NULL VARCHAR2(240)
TGRP7_USER_ATTRIBUTE1	NULL VARCHAR2(240)
TGRP7_USER_ATTRIBUTE2	NULL VARCHAR2(240)

Oracle Proprietary, Confidential Information--Use Restricted by Contract

TGRP7_USER_ATTRIBUTE3	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE4	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE5	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE6	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE7	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE8	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE9	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE10	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE11	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE12	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE13	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE14	NULL	VARCHAR2(240)
TGRP7_USER_ATTRIBUTE15	NULL	VARCHAR2(240)
ALL_PK	NULL	VARCHAR2(40)
ALL_PK_KEY	NULL	NUMBER
ALL_PK_ROWID	NULL	VARCHAR2(20)
ALL_NAME	NULL	VARCHAR2(80)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

EDW_BIL_SLSTER_TERR_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_TGRP1_LTC	TERRITORY_GROUP1_ID_PK_KEY	TERRITORY_GROUP1_FK_KEY

Column Descriptions

Name	Null?	Type	Description
TERRITORY_ID_PK	NOT NULL	NUMBER(15)	
TERRITORY_ID_PK_KEY	NOT NULL	NUMBER	
TERRITORY_GROUP1_FK	NULL	VARCHAR2(240)	
TERRITORY_GROUP1_FK_KEY	NOT NULL	NUMBER(15)	
TERR_DP	NULL	VARCHAR2(240)	
TERR_QUAL_ID	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(2000)	
QUAL_USG_ID	NULL	VARCHAR2(240)	
ENABLED_FLAG	NULL	VARCHAR2(240)	
START_DATE_ACTIVE	NULL	VARCHAR2(240)	
END_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTERR_TERR_LTC_U2	UNIQUE	0	TERRITORY_ID_PK
		2	TERRITORY_ID_PK_KEY
EDW_BIL_SLSTER_TERR_LTC_U1	UNIQUE	0	TERRITORY_ID_PK_KEY

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSTER_TER_LSTG

Column Descriptions

Name	Null?	Type	Description
TERRITORY_ID_PK	NOT NULL	NUMBER(15)	
ROW_ID	NULL	VARCHAR2(20)	
TERRITORY_GROUP1_FK	NULL	VARCHAR2(240)	
TERRITORY_GROUP1_FK_KEY	NOT NULL	NUMBER(15)	
TERR_DP	NULL	VARCHAR2(240)	
TERR_QUAL_ID	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(2000)	
QUAL_USG_ID	NULL	VARCHAR2(240)	
ENABLED_FLAG	NULL	VARCHAR2(240)	
START_DATE_ACTIVE	NULL	VARCHAR2(240)	
END_DATE_ACTIVE	NULL	DATE	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TERR_LSTG_N1	NOT UNIQUE	0	TERRITORY_ID_PK

EDW_BIL_SLSTER_TGRP1_LSTG

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP1_ID_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
TERRITORY_GROUP2_ID_FK	NULL	NUMBER	
TERRITORY_GROUP2_ID_FK_KEY	NULL	NUMBER	
TGRP1_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTERR_TGRP1_LSTG_N1	NOT UNIQUE	0	TERRITORY_GROUP1_ID_PK

EDW_BIL_SLSTER_TGRP1_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_TGRP2_LTC	TERRITORY_GROUP2_ID_PK_KEY	TERRITORY_GROUP2_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP1_ID_PK	NOT NULL	NUMBER	
TERRITORY_GROUP1_ID_PK_KEY	NOT NULL	NUMBER	
TERRITORY_GROUP2_ID_FK	NULL	NUMBER	
TERRITORY_GROUP2_ID_FK_KEY	NOT NULL	NUMBER	
TGRP1_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP1_LTC_U1	UNIQUE	0	TERRITORY_GROUP1_ID_PK_KEY
EDW_BIL_SLSTER_TGRP1_LTC_U2	UNIQUE	0	TERRITORY_GROUP1_ID_PK
		2	TERRITORY_GROUP1_ID_PK_KEY

EDW_BIL_SLSTER_TGRP2_LSTG

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP2_ID_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
TERRITORY_GROUP3_ID_FK	NULL	NUMBER	
TERRITORY_GROUP3_ID_FK_KEY	NULL	NUMBER	
TGRP2_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTERR_TGRP2_LSTG_N1	NOT UNIQUE	0	TERRITORY_GROUP2_ID_PK

EDW_BIL_SLSTER_TGRP2_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_TGRP3_LTC	TERRITORY_GROUP3_ID_PK_KEY	TERRITORY_GROUP3_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP2_ID_PK	NOT NULL	NUMBER	
TERRITORY_GROUP2_ID_PK_KEY	NOT NULL	NUMBER	
TERRITORY_GROUP3_ID_FK	NULL	NUMBER	
TERRITORY_GROUP3_ID_FK_KEY	NOT NULL	NUMBER	
TGRP2_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP2_LTC_U1	UNIQUE	0	TERRITORY_GROUP2_ID_PK_KEY
EDW_BIL_SLSTER_TGRP2_LTC_U2	UNIQUE	0	TERRITORY_GROUP2_ID_PK
		2	TERRITORY_GROUP2_ID_PK_KEY

EDW_BIL_SLSTER_TGRP3_LSTG

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP3_ID_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
TERRITORY_GROUP4_ID_FK	NULL	NUMBER	
TERRITORY_GROUP4_ID_FK_KEY	NULL	NUMBER	
TGRP3_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP3_LSTG_N1	NOT UNIQUE	0	TERRITORY_GROUP3_ID_PK

EDW_BIL_SLSTER_TGRP3_LTC

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP3_ID_PK_KEY	NOT NULL	NUMBER	
TERRITORY_GROUP4_ID_FK	NULL	NUMBER	
TERRITORY_GROUP4_ID_FK_KEY	NULL	NUMBER	
TGRP3_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
TERRITORY_GROUP3_ID_PK	NOT NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP3_LTC_U1	UNIQUE	5	TERRITORY_GROUP3_ID_PK_KEY
EDW_BIL_SLSTER_TGRP3_LTC_U2	UNIQUE	0	TERRITORY_GROUP3_ID_PK
		2	TERRITORY_GROUP3_ID_PK_KEY

EDW_BIL_SLSTER_TGRP4_LSTG

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP4_ID_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
TERRITORY_GROUP5_ID_FK	NULL	NUMBER	
TERRITORY_GROUP5_ID_FK_KEY	NULL	NUMBER	
TGRP4_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP4_LSTG_N1	NOT UNIQUE	0	TERRITORY_GROUP4_ID_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSTER_TGRP4_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_TGRP5_LTC	TERRITORY_GROUP5_ID_PK_KEY	TERRITORY_GROUP5_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP4_ID_PK	NOT NULL	NUMBER	
TERRITORY_GROUP4_ID_PK_KEY	NOT NULL	NUMBER	
TERRITORY_GROUP5_ID_FK	NULL	NUMBER	
TERRITORY_GROUP5_ID_FK_KEY	NOT NULL	NUMBER	
TGRP4_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP4_LTC_U1	UNIQUE	0	TERRITORY_GROUP4_ID_PK_KEY
EDW_BIL_SLSTER_TGRP4_U2	UNIQUE	0	TERRITORY_GROUP4_ID_PK
		2	TERRITORY_GROUP4_ID_PK_KEY

EDW_BIL_SLSTER_TGRP5_LSTG

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP5_ID_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
TERRITORY_GROUP6_ID_FK	NULL	NUMBER	
TERRITORY_GROUP6_ID_FK_KEY	NULL	NUMBER	
TGRP5_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP5_LSTG_N1	NOT UNIQUE	0	TERRITORY_GROUP5_ID_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSTER_TGRP5_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_TGRP6_LTC	TERRITORY_GROUP6_ID_PK_KEY	TERRITORY_GROUP6_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP5_ID_PK	NOT NULL	NUMBER	
TERRITORY_GROUP5_ID_PK_KEY	NOT NULL	NUMBER	
TERRITORY_GROUP6_ID_FK	NULL	NUMBER	
TERRITORY_GROUP6_ID_FK_KEY	NOT NULL	NUMBER	
TGRP5_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP5_LTC_U1	UNIQUE	0	TERRITORY_GROUP5_ID_PK_KEY
EDW_BIL_SLSTER_TGRP5_LTC_U2	UNIQUE	0	TERRITORY_GROUP5_ID_PK
		2	TERRITORY_GROUP5_ID_PK_KEY

EDW_BIL_SLSTER_TGRP6_LSTG

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP6_ID_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
TERRITORY_GROUP7_ID_FK	NULL	NUMBER	
TERRITORY_GROUP7_ID_FK_KEY	NULL	NUMBER	
TGRP6_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP6_LSTG_N1	NOT UNIQUE	0	TERRITORY_GROUP6_ID_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSTER_TGRP6_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_TGRP7_LTC	TERRITORY_GROUP7_ID_PK_KEY	TERRITORY_GROUP7_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP6_ID_PK	NOT NULL	NUMBER	
TERRITORY_GROUP6_ID_PK_KEY	NOT NULL	NUMBER	
TERRITORY_GROUP7_ID_FK	NULL	NUMBER	
TERRITORY_GROUP7_ID_FK_KEY	NOT NULL	NUMBER	
TGRP6_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP6_LTC_U1	UNIQUE	0	TERRITORY_GROUP6_ID_PK_KEY
EDW_BIL_SLSTER_TGRP6_LTC_U2	UNIQUE	0	TERRITORY_GROUP6_ID_PK
		2	TERRITORY_GROUP6_ID_PK_KEY

EDW_BIL_SLSTER_TGRP7_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_A_LTC	ALL_PK_KEY	ALL_FK_KEY

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP7_ID_PK	NOT NULL	NUMBER	
TERRITORY_GROUP7_ID_PK_KEY	NOT NULL	NUMBER	
ALL_FK	NULL	VARCHAR2(40)	
ALL_FK_KEY	NOT NULL	NUMBER	
TGRP7_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ACCOUNTING_CODE	NULL	VARCHAR2(80)	
START_DATE_ACTIVE	NULL	DATE	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP7_LTC_U1	UNIQUE	0	TERRITORY_GROUP7_ID_PK_KEY
EDW_BIL_SLSTER_TGRP7_LTC_U2	UNIQUE	0	TERRITORY_GROUP7_ID_PK
		2	TERRITORY_GROUP7_ID_PK_KEY

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SLSTER_TGRP7_LTSG

Column Descriptions

Name	Null?	Type	Description
TERRITORY_GROUP7_ID_PK	NOT NULL	NUMBER	
ROW_ID	NULL	VARCHAR2(20)	
ALL_FK	NULL	VARCHAR2(40)	
ALL_FK_KEY	NULL	NUMBER	
TGRP7_DP	NULL	VARCHAR2(240)	
NAME	NOT NULL	VARCHAR2(60)	
DESCRIPTION	NULL	VARCHAR2(240)	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLSTER_TGRP7_LSTG_N1	NOT UNIQUE	0	TERRITORY_GROUP7_ID_PK

EDW_BIL_SLS_CYCLE_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SLS_CYCLE_SUM_PK	NULL	VARCHAR2(240)	
SLS_CYCLE_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
NO_OF_LEADS	NULL	NUMBER	
NO_OF_OPPTS	NULL	NUMBER	
NO_OF_QUOTES	NULL	NUMBER	
NO_OF_ORDERS	NULL	NUMBER	
NO_OF_WINS	NULL	NUMBER	
NO_OF_LOSSES	NULL	NUMBER	
SALES_CYCLE	NULL	NUMBER	
LEAD_AMOUNT_T	NULL	NUMBER	
LEAD_AMOUNT_S	NULL	NUMBER	
LEAD_AMOUNT_G	NULL	NUMBER	
OPTY_AMOUNT_T	NULL	NUMBER	
OPTY_AMOUNT_S	NULL	NUMBER	
OPTY_AMOUNT_G	NULL	NUMBER	
QUOTE_AMOUNT_T	NULL	NUMBER	
QUOTE_AMOUNT_S	NULL	NUMBER	
QUOTE_AMOUNT_G	NULL	NUMBER	
ORDER_AMOUNT_T	NULL	NUMBER	
ORDER_AMOUNT_S	NULL	NUMBER	
ORDER_AMOUNT_G	NULL	NUMBER	
EXPECTED_REVENUE_T	NULL	NUMBER	
EXPECTED_REVENUE_S	NULL	NUMBER	
EXPECTED_REVENUE_G	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

WIN_AMOUNT_T	NULL	NUMBER
WIN_AMOUNT_S	NULL	NUMBER
WIN_AMOUNT_G	NULL	NUMBER
LOSS_AMOUNT_T	NULL	NUMBER
LOSS_AMOUNT_S	NULL	NUMBER
LOSS_AMOUNT_G	NULL	NUMBER
INSTANCE	NULL	VARCHAR2(40)
USER_MEASURE1	NULL	NUMBER
USER_MEASURE2	NULL	NUMBER
USER_MEASURE3	NULL	NUMBER
USER_MEASURE4	NULL	NUMBER
USER_MEASURE5	NULL	NUMBER
USER_FK1_KEY	NULL	NUMBER
USER_FK2_KEY	NULL	NUMBER
USER_FK3_KEY	NULL	NUMBER
USER_FK4_KEY	NULL	NUMBER
USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SLS_CYCLE_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N10	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N11	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N3	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N4	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N5	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N6	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N7	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N8	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_N9	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_SLS_CYCLE_SUM_F_U1	UNIQUE	0	SLS_CYCLE_SUM_PK

EDW_BIL_SREP_PERF_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_COMP_PLANS_M	ELMNT_PLAN_ELEMENT_ID_PK_KEY	PLAN_ELEMENT_ID_FK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	PLAN_ELEMENT_ID_FK_KEY
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_MTL_UNIT_OF_MEASR_M	UOM_UOM_PK_KEY	UOM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SLSREP_PER_SUM_PK	NULL	VARCHAR2(240)	
SLSREP_PER_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
PLAN_ELEMENT_ID_FK_KEY	NOT NULL	NUMBER	
TERRITORY_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
UOM_FK_KEY	NOT NULL	NUMBER	
NO_OF_WINS	NOT NULL	NUMBER	
NO_OF_LOSSES	NOT NULL	NUMBER	
CREDITED_QUANTITY	NULL	NUMBER	
COGS_AMOUNT_T	NULL	NUMBER	
COGS_AMOUNT_S	NULL	NUMBER	
COGS_AMOUNT_G	NULL	NUMBER	
INVOICED_AMOUNT_T	NULL	NUMBER	
INVOICED_AMOUNT_S	NULL	NUMBER	
INVOICED_AMOUNT_G	NULL	NUMBER	
REVENUE_CREDITS_T	NULL	NUMBER	
REVENUE_CREDITS_G	NULL	NUMBER	
REVENUE_CREDITS_S	NULL	NUMBER	
QUOTA_ACHIEVED_T	NULL	NUMBER	
QUOTA_ACHIEVED_S	NULL	NUMBER	
QUOTA_ACHIEVED_G	NULL	NUMBER	
COMP_AMOUNT_T	NULL	NUMBER	
COMP_AMOUNT_S	NULL	NUMBER	
COMP_AMOUNT_G	NULL	NUMBER	
SALES_CYCLE	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

INSTANCE	NULL	VARCHAR2(40)
USER_MEASURE1	NULL	NUMBER
USER_MEASURE3	NULL	NUMBER
USER_MEASURE2	NULL	NUMBER
USER_MEASURE4	NULL	NUMBER
USER_MEASURE5	NULL	NUMBER
USER_FK1_KEY	NULL	NUMBER
USER_FK2_KEY	NULL	NUMBER
USER_FK3_KEY	NULL	NUMBER
USER_FK4_KEY	NULL	NUMBER
USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SREP_PERF_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N10	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N11	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N12	NOT UNIQUE	5	ITEM_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N2	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N3	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N4	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N5	NOT UNIQUE	0	PLAN_ELEMENT_ID_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N6	NOT UNIQUE	0	TERRITORY_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N7	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N8	NOT UNIQUE	0	UOM_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_N9	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_SREP_PERF_SUM_F_U1	UNIQUE	0	SLSREP_PER_SUM_PK

EDW_BIL_SREQ_SEV_M

Column Descriptions

Name	Null?	Type	Description
SRSV_SERV_RQST_SEV_PK	NULL	VARCHAR2(100)	
SRSV_PK_ROWID	NULL	VARCHAR2(240)	
SRSV_SERV_RQST_SEV_PK_KEY	NOT NULL	NUMBER	
SRSV_DP	NULL	VARCHAR2(240)	
SRSV_INSTANCE	NULL	VARCHAR2(40)	
SRSV_NAME	NULL	VARCHAR2(240)	
SRSV_DESCRIPTION	NULL	VARCHAR2(240)	Severity description
SRSV_INCIDENT_SUBTYPE	NOT NULL	VARCHAR2(30)	Identifies whether the severity is for service requests or actions
SRSV_IMPORTANCE_LEVEL	NOT NULL	NUMBER(2)	Level of importance associated with this severity
SRSV_START_DATE_ACTIVE	NULL	DATE	Date this severity becomes active, if limited
SRSV_END_DATE_ACTIVE	NULL	DATE	Date this severity becomes inactive, if limited
SRSV_LAST_UPDATE_LOGIN	NULL	NUMBER(15)	Standard Who column
SRSV_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
ALL_ALL_PK	NULL	VARCHAR2(40)	
ALL_ALL_PK_KEY	NULL	NUMBER	
ALL_ALL_PK_ROWID	NULL	VARCHAR2(20)	
ALL_ALL_NAME	NULL	VARCHAR2(80)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SRV_REQ_SUM_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_ID_FK_KEY
EDW_BIL_SREQ_SEV_M	SRSV_SERV_RQST_SEV_PK_KEY	SERV_REQ_SEV_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SERV_REQ_SUM_PK	NULL	VARCHAR2(240)	
SERV_REQ_SUM_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
SERV_REQ_SEV_FK_KEY	NOT NULL	NUMBER	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER	
NO_OF_INCIDENTS	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	
USER_MEASURE5	NULL	NUMBER	
USER_FK1_KEY	NULL	NUMBER	
USER_FK3_KEY	NULL	NUMBER	
USER_FK2_KEY	NULL	NUMBER	
USER_FK4_KEY	NULL	NUMBER	
USER_FK5_KEY	NULL	NUMBER	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SERV_REQ_SUM_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_SERV_REQ_SUM_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_SERV_REQ_SUM_F_N3	NOT UNIQUE	0	SERV_REQ_SEV_FK_KEY

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SERV_REQ_SUM_F_N4	NOT UNIQUE	5	TERRITORY_ID_FK_KEY
EDW_BIL_SERV_REQ_SUM_F_U1	UNIQUE	0	SERV_REQ_SUM_PK

EDW_BIL_SR_SV_SRSV_A_LTC

Column Descriptions

Name	Null?	Type	Description
ALL_PK	NULL	VARCHAR2(40)	
ALL_PK_KEY	NULL	NUMBER	
ALL_PK_ROW_ID	NULL	VARCHAR2(20)	
NAME	NULL	VARCHAR2(80)	

EDW_BIL_SR_SV_SRSV_LSTG

Column Descriptions

Name	Null?	Type	Description
INCIDENT_SERVERITY_ID_PK	NULL	VARCHAR2(240)	
SERV_RQST_DP	NULL	VARCHAR2(240)	
NAME	NULL	VARCHAR2(240)	
DESCRIPTION	NULL	VARCHAR2(240)	Severity description
IMPORTANCE_LEVEL	NOT NULL	NUMBER(2)	Level of importance associated with this severity
INCIDENT_SUBTYPE	NOT NULL	VARCHAR2(30)	Identifies whether the severity is for service requests or actions
START_DATE_ACTIVE	NULL	DATE	Date this severity becomes active, if limited
END_DATE_ACTIVE	NULL	DATE	Date this severity becomes inactive, if limited
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SERV_REQ_SEV_LSTG_N1	NOT UNIQUE	0	INCIDENT_SERVERITY_ID_PK

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_SR_SV_SRSV_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SR_SV_SRSV_A_LTC	ALL_PK_KEY	ALL_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SRSV_SERVERITY_ID_PK	NULL	VARCHAR2(240)	
SRSV_SEVERITY_ID_PK_KEY	NOT NULL	NUMBER	
SRSV_ROWID	NULL	VARCHAR2(20)	
ALL_FK	NULL	VARCHAR2(40)	
ALL_FK_KEY	NOT NULL	NUMBER	
SRSV_DP	NULL	VARCHAR2(240)	
SRSV_NAME	NULL	VARCHAR2(240)	
SRSV_DESCRIPTION	NULL	VARCHAR2(240)	Severity description
SRSV_INCIDENT_SUBTYPE	NOT NULL	VARCHAR2(30)	Identifies whether the severity is for service requests or actions
SRSV_IMPORTANCE_LEVEL	NOT NULL	NUMBER(2)	Level of importance associated with this severity
SRSV_START_DATE_ACTIVE	NULL	DATE	Date this severity becomes active, if limited
SRSV_END_DATE_ACTIVE	NULL	DATE	Date this severity becomes inactive, if limited
SRSV_INSTANCE	NULL	VARCHAR2(40)	
SRSV_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
SRSV_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SR_SEV_SRSV_LTC_U2	UNIQUE	0	SRSV_SERVERITY_ID_PK
		2	SRSV_SEVERITY_ID_PK_KEY
EDW_BIL_SR_SV_SRSV_LTC_U1	UNIQUE	0	SRSV_SEVERITY_ID_PK_KEY

EDW_BIL_SR_TER_GRP_B

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK_KEY	TERRITORY_ID_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SRVRQSTS_TER_GRP_PK	NOT NULL	VARCHAR2(240)	
SRVRQSTS_TER_GRP_PK_KEY	NOT NULL	NUMBER	
TERRITORY_ID_FK	NOT NULL	NUMBER(15)	
INSTANCE	NULL	VARCHAR2(40)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER(15)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SR_TER_GRP_B_N1	NOT UNIQUE	2	TERRITORY_ID_FK_KEY

EDW_BIL_SR_TER_GRP_BSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_SLSTER_M	TERR_TERRITORY_ID_PK	TERRITORY_ID_FK

Column Descriptions

Name	Null?	Type	Description
SRVRQSTS_TER_GRP_PK	NOT NULL	VARCHAR2(240)	
ROW_ID	NULL	VARCHAR2(20)	
SRVRQSTS_TER_GRP_PK_KEY	NOT NULL	NUMBER	
TERRITORY_ID_FK	NOT NULL	NUMBER(15)	
TERRITORY_ID_FK_KEY	NOT NULL	NUMBER(15)	
INCIDENT_ID	NOT NULL	NUMBER	
TERRITORY_ID	NOT NULL	NUMBER(15)	
INSTANCE	NULL	VARCHAR2(40)	
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_SR_TER_GRP_BSTG_N1	NOT UNIQUE	2	TERRITORY_ID_FK

EDW_BIL_STER_ORDRS_F

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_ORDRS_TER_GRP	ORDRS_TER_GRP_PK_KEY	ORDRS_TER_GRP_FK_KEY
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK_KEY	SALESREP_ID_FK_KEY
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK_KEY	SLSCHNL_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	TRX_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	SOB_CURRENCY_FK_KEY
EDW_CURRENCY_M	CRNC_CURRENCY_PK_KEY	GLBL_CURRENCY_FK_KEY
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK_KEY	GLOC_LOCATION_FK_KEY
EDW_ITEMS_M	EDW_ITEMS_M_ID	ITEM_FK_KEY
EDW_MTL_UNIT_OF_MEASR_M	UOM_UOM_PK_KEY	UOM_FK_KEY
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK_KEY	ORGANIZATION_FK_KEY
EDW_TIME_M	CDAY_CAL_DAY_PK_KEY	TIME_FK_KEY
EDW_TRD_PARTNER_M	EDW_TRD_PARTNER_M_ID	TRADING_PARTNR_FK_KEY

Column Descriptions

Name	Null?	Type	Description
SLSTER_ORDERS_PK	NULL	VARCHAR2(240)	
SLSTER_ORDERS_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TRADING_PARTNR_FK_KEY	NOT NULL	NUMBER	
ITEM_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
ORDRS_TER_GRP_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
UOM_FK_KEY	NOT NULL	NUMBER	
ORDER_NUMBER	NULL	NUMBER	
QUANTITY_ORDERED	NULL	NUMBER	
CANCELLED_QUANTITY	NULL	NUMBER	
SERVICED_QUANTITY	NULL	NUMBER	
SHIPPED_QUANTITY	NULL	NUMBER	
LIST_PRICE_T	NULL	NUMBER	
LIST_PRICE_S	NULL	NUMBER	
LIST_PRICE_G	NULL	NUMBER	
SELLING_PRICE_T	NULL	NUMBER	
SELLING_PRICE_S	NULL	NUMBER	
SELLING_PRICE_G	NULL	NUMBER	
ORDER_AMOUNT_T	NULL	NUMBER	
ORDER_AMOUNT_S	NULL	NUMBER	
ORDER_AMOUNT_G	NULL	NUMBER	
INSTANCE	NULL	VARCHAR2(40)	
USER_MEASURE1	NULL	NUMBER	
USER_MEASURE2	NULL	NUMBER	
USER_MEASURE3	NULL	NUMBER	
USER_MEASURE4	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

USER_MEASURE5	NULL	NUMBER
USER_FK1_KEY	NULL	NUMBER
USER_FK2_KEY	NULL	NUMBER
USER_FK3_KEY	NULL	NUMBER
USER_FK4_KEY	NULL	NUMBER
USER_FK5_KEY	NULL	NUMBER
USER_ATTRIBUTE1	NULL	VARCHAR2(240)
USER_ATTRIBUTE2	NULL	VARCHAR2(240)
USER_ATTRIBUTE3	NULL	VARCHAR2(240)
USER_ATTRIBUTE4	NULL	VARCHAR2(240)
USER_ATTRIBUTE5	NULL	VARCHAR2(240)
USER_ATTRIBUTE6	NULL	VARCHAR2(240)
USER_ATTRIBUTE7	NULL	VARCHAR2(240)
USER_ATTRIBUTE8	NULL	VARCHAR2(240)
USER_ATTRIBUTE9	NULL	VARCHAR2(240)
USER_ATTRIBUTE10	NULL	VARCHAR2(240)
USER_ATTRIBUTE11	NULL	VARCHAR2(240)
USER_ATTRIBUTE12	NULL	VARCHAR2(240)
USER_ATTRIBUTE13	NULL	VARCHAR2(240)
USER_ATTRIBUTE14	NULL	VARCHAR2(240)
USER_ATTRIBUTE15	NULL	VARCHAR2(240)
LAST_UPDATE_DATE	NULL	DATE
CREATION_DATE	NULL	DATE

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_STER_ORDRS_F_N1	NOT UNIQUE	0	TIME_FK_KEY
EDW_BIL_STER_ORDRS_F_N10	NOT UNIQUE	0	UOM_FK_KEY
EDW_BIL_STER_ORDRS_F_N11	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
EDW_BIL_STER_ORDRS_F_N12	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
EDW_BIL_STER_ORDRS_F_N2	NOT UNIQUE	0	TRADING_PARTNR_FK_KEY
EDW_BIL_STER_ORDRS_F_N3	NOT UNIQUE	0	ITEM_FK_KEY
EDW_BIL_STER_ORDRS_F_N4	NOT UNIQUE	0	SLSCHNL_FK_KEY
EDW_BIL_STER_ORDRS_F_N5	NOT UNIQUE	5	ORDRS_TER_GRP_FK_KEY
EDW_BIL_STER_ORDRS_F_N6	NOT UNIQUE	0	SALESREP_ID_FK_KEY
EDW_BIL_STER_ORDRS_F_N7	NOT UNIQUE	0	ORGANIZATION_FK_KEY
EDW_BIL_STER_ORDRS_F_N8	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
EDW_BIL_STER_ORDRS_F_N9	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
EDW_BIL_STER_ORDRS_F_U1	UNIQUE	0	SLSTER_ORDERS_PK

EDW_BIL_STER_ORDRS_FSTG

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_ORDRS_TER_GRP	ORDRS_TER_GRP_PK	ORDRS_TER_GRP_FK
EDW_BIL_SLSFRCE_M	SREP_SALESREP_ID_PK	SALESREP_ID_FK
EDW_BIM_SLSCHNLS_MS	L1_SLSCHNL_PK	SLSCHNL_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	TRX_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	SOB_CURRENCY_FK
EDW_CURRENCY_M	CRNC_CURRENCY_PK	GLBL_CURRENCY_FK
EDW_GEOGRAPHY_M	GLOC_LOCATION_PK	GLOC_LOCATION_FK
EDW_ITEMS_M	IREV_ITEM_REVISION_PK_ROWID	ITEM_FK
EDW_MTL_UNIT_OF_MEASR_M	UOM_UOM_PK	UOM_FK
EDW_ORGANIZATION_M	ORGA_ORGANIZATION_PK	ORGANIZATION_FK
EDW_TIME_M	CDAY_CALL_DAY_PK	TIME_FK
EDW_TRD_PARTNER_M	TPLO_TRADE_PARTNER_LOC_PK	BILL_TO_CUSTOMER_FK

Column Descriptions

Name	Null?	Type	Description
SLSTER_ORDERS_PK	NULL	VARCHAR2(240)	
SLSTER_ORDERS_PK_KEY	NULL	NUMBER	
TIME_FK_KEY	NOT NULL	NUMBER	
TIME_FK	NOT NULL	DATE	Accounting period number
BILL_TO_CUSTOMER_FK	NOT NULL	VARCHAR2(320)	
BILL_TO_CUSTOMER_FK_KEY	NOT NULL	NUMBER	
ITEM_FK	NOT NULL	VARCHAR2(320)	
ITEM_FK_KEY	NOT NULL	NUMBER	
SLSCHNL_FK	NOT NULL	VARCHAR2(120)	
SLSCHNL_FK_KEY	NOT NULL	NUMBER	
ORDRS_TER_GRP_FK	NOT NULL	VARCHAR2(240)	
ORDRS_TER_GRP_FK_KEY	NOT NULL	NUMBER	
SALESREP_ID_FK	NOT NULL	NUMBER	
SALESREP_ID_FK_KEY	NOT NULL	NUMBER	
ORGANIZATION_FK_KEY	NOT NULL	NUMBER	
GLOC_LOCATION_FK	NOT NULL	VARCHAR2(240)	
GLOC_LOCATION_FK_KEY	NOT NULL	NUMBER	
TRX_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
TRX_CURRENCY_FK_KEY	NOT NULL	NUMBER	
SOB_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
SOB_CURRENCY_FK_KEY	NOT NULL	NUMBER	
GLBL_CURRENCY_FK	NOT NULL	VARCHAR2(20)	
GLBL_CURRENCY_FK_KEY	NOT NULL	NUMBER	
UOM_FK	NOT NULL	VARCHAR2(80)	
UOM_FK_KEY	NOT NULL	NUMBER	
ORDER_NUMBER	NULL	NUMBER	
QUANTITY_ORDERED	NULL	NUMBER	
CANCELLED_QUANTITY	NULL	NUMBER	
SERVICED_QUANTITY	NULL	NUMBER	
SHIPPED_QUANTITY	NULL	NUMBER	
LIST_PRICE_T	NULL	NUMBER	
LIST_PRICE_S	NULL	NUMBER	
LIST_PRICE_G	NULL	NUMBER	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SELLING_PRICE_T		NULL	NUMBER
SELLING_PRICE_S		NULL	NUMBER
SELLING_PRICE_G		NULL	NUMBER
ORDER_AMOUNT_T		NULL	NUMBER
ORGANIZATION_FK	NOT	NULL	VARCHAR2(240)
ORDER_AMOUNT_S		NULL	NUMBER
ORDER_AMOUNT_G		NULL	NUMBER
INSTANCE		NULL	VARCHAR2(40)
USER_MEASURE1		NULL	NUMBER
USER_MEASURE2		NULL	NUMBER
USER_MEASURE3		NULL	NUMBER
USER_MEASURE4		NULL	NUMBER
USER_MEASURE5		NULL	NUMBER
USER_FK1_KEY		NULL	NUMBER
USER_FK2_KEY		NULL	NUMBER
USER_FK3_KEY		NULL	NUMBER
USER_FK4_KEY		NULL	NUMBER
USER_FK5_KEY		NULL	NUMBER
USER_ATTRIBUTE1		NULL	VARCHAR2(240)
USER_ATTRIBUTE2		NULL	VARCHAR2(240)
USER_ATTRIBUTE3		NULL	VARCHAR2(240)
USER_ATTRIBUTE4		NULL	VARCHAR2(240)
USER_ATTRIBUTE5		NULL	VARCHAR2(240)
USER_ATTRIBUTE6		NULL	VARCHAR2(240)
USER_ATTRIBUTE7		NULL	VARCHAR2(240)
USER_ATTRIBUTE8		NULL	VARCHAR2(240)
USER_ATTRIBUTE9		NULL	VARCHAR2(240)
USER_ATTRIBUTE10		NULL	VARCHAR2(240)
USER_ATTRIBUTE11		NULL	VARCHAR2(240)
USER_ATTRIBUTE12		NULL	VARCHAR2(240)
USER_ATTRIBUTE13		NULL	VARCHAR2(240)
USER_ATTRIBUTE14		NULL	VARCHAR2(240)
USER_ATTRIBUTE15		NULL	VARCHAR2(240)
REQUEST_ID		NULL	NUMBER
ROW_ID		NULL	VARCHAR2(20)
OPERATION_CODE		NULL	VARCHAR2(40)
ERROR_CODE		NULL	VARCHAR2(2000)
COLLECTION_STATUS		NULL	VARCHAR2(40)

Indexes

Index Name	Index Type	Sequence	Column Name
IND_20854538	NOT UNIQUE	5	SOB_CURRENCY_FK_KEY
IND_20854540	NOT UNIQUE	5	GLBL_CURRENCY_FK_KEY
IND_20854542	NOT UNIQUE	5	ORDRS_TER_GRP_FK_KEY
IND_20854544	NOT UNIQUE	0	SALESREP_ID_FK_KEY
IND_20854546	UNIQUE	0	SLSTER_ORDERS_PK
IND_20854548	NOT UNIQUE	0	TIME_FK_KEY
IND_20854550	NOT UNIQUE	0	BILL_TO_CUSTOMER_FK_KEY
IND_20854552	NOT UNIQUE	0	ITEM_FK_KEY
IND_20854554	NOT UNIQUE	0	SLSCHNL_FK_KEY
IND_20854556	NOT UNIQUE	0	ORGANIZATION_FK_KEY
IND_20854558	NOT UNIQUE	0	GLOC_LOCATION_FK_KEY
IND_20854560	NOT UNIQUE	0	TRX_CURRENCY_FK_KEY
IND_20854562	NOT UNIQUE	0	UOM_FK_KEY

EDW_BIL_WIN_PROB_A_LTC

Column Descriptions

Name	Null?	Type	Description
ALL_PK	NULL	VARCHAR2 (40)	
ALL_PK_KEY	NULL	NUMBER	
ALL_PK_ROW_ID	NULL	VARCHAR2 (20)	
NAME	NULL	VARCHAR2 (80)	

EDW_BIL_WIN_PROB_LSTG

Column Descriptions

Name	Null?	Type	Description
PROBABILITY_VALUE_PK	NOT NULL	NUMBER	Win probability value of sales opportunity in the range from 0 to 100
ROW_ID	NULL	VARCHAR2(20)	
WIN_PROBABILITY_DP	NULL	VARCHAR2(240)	
MEANING	NULL	VARCHAR2(80)	Text description of the win probability
ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
CREATED_BY	NOT NULL	NUMBER	Standard who column
START_DATE_ACTIVE	NOT NULL	DATE	Date which the win probability becomes active
END_DATE_ACTIVE	NULL	DATE	Date which the win probability becomes inactive
LEAD_STATUS_CHANGE_CODE	NULL	VARCHAR2(30)	After an opportunity win probability exceeds this record's value, the opportunity status changes to this value
INSTANCE	NULL	VARCHAR2(40)	
USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	
ENABLED_FLAG	NOT NULL	VARCHAR2(1)	Flag to indicate if sales stage is enabled
REQUEST_ID	NULL	NUMBER	
OPERATION_CODE	NULL	VARCHAR2(40)	
ERROR_CODE	NULL	VARCHAR2(2000)	
COLLECTION_STATUS	NULL	VARCHAR2(40)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_WIN_PROB_LSTG_N1	NOT UNIQUE	5	PROBABILITY_VALUE_PK

EDW_BIL_WIN_PROB_LTC

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
EDW_BIL_WIN_PROB_A_LTC	ALL_PK_KEY	ALL_FK_KEY

Column Descriptions

Name	Null?	Type	Description
WINP_PROBABILITY_VALUE_PK	NOT NULL	NUMBER	Sales stage minimum win probability
WINP_PROBABILITY_VALUE_PK_KEY	NOT NULL	NUMBER	Sales stage minimum win probability
ALL_FK	NULL	VARCHAR2(40)	
ALL_FK_KEY	NOT NULL	NUMBER	
WINP_MEANING	NULL	VARCHAR2(80)	Text description of the win probability
WINP_ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
WINP_WIN_PROBABILITY_DP	NULL	VARCHAR2(240)	
WINP_CREATED_BY	NOT NULL	NUMBER	Standard who column
WINP_START_DATE_ACTIVE	NOT NULL	DATE	Date which the win probability becomes active
WINP_END_DATE_ACTIVE	NULL	DATE	Date which the win probability becomes inactive
WINP_LEAD_STATUS_CHANGE_CODE	NULL	VARCHAR2(30)	After an opportunity win probability exceeds this record's value, the opportunity status changes to this value
WINP_INSTANCE	NULL	VARCHAR2(40)	
WINP_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_BIL_WIN_PROB_LTC_U1	UNIQUE	0	WINP_PROBABILITY_VALUE_PK_KEY
EDW_BIL_WIN_PROB_LTC_U2	UNIQUE	0	WINP_PROBABILITY_VALUE_PK
		2	WINP_PROBABILITY_VALUE_PK_KEY

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIL_WIN_PROB_M

Column Descriptions

Name	Null?	Type	Description
WINP_PROBABILITY_VALUE_PK	NULL	VARCHAR2(240)	
WINP_PROBABILITY_VALUE_PK_KEY	NOT NULL	NUMBER	
WINP_PK_ROW_ID	NULL	VARCHAR2(20)	
WINP_MEANING	NULL	VARCHAR2(80)	Text description of the win probability
WINP_ORG_ID	NULL	NUMBER	Operating unit which performed this transaction
WINP_INSTANCE	NULL	VARCHAR2(40)	
WINP_WIN_PROBABILITY_DP	NULL	VARCHAR2(240)	
WINP_CREATED_BY	NOT NULL	NUMBER	Standard who column
WINP_LEAD_STATUS_CHANGE_CODE	NULL	VARCHAR2(30)	After an opportunity win probability exceeds this record's value, the opportunity status changes to this value
WINP_START_DATE_ACTIVE	NOT NULL	DATE	Date which the win probability becomes active
WINP_END_DATE_ACTIVE	NULL	DATE	Date which the win probability becomes inactive
WINP_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
WINP_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	
ALL_PK	NULL	VARCHAR2(40)	
ALL_PK_KEY	NULL	NUMBER	
ALL_PK_ROWID	NULL	VARCHAR2(20)	
ALL_NAME	NULL	VARCHAR2(80)	
LAST_UPDATE_DATE	NULL	DATE	
CREATION_DATE	NULL	DATE	

EDW_BIM_LEAD_STATUSES_M

Column Descriptions

Name	Null?	Type	Description
L0_ALL_PK_KEY	NULL	NUMBER	
L0_ALL_PK	NULL	VARCHAR2(40)	
L0_ALL_PK_ROWID	NULL	VARCHAR2(20)	
L0_NAME	NULL	VARCHAR2(80)	
L1_LEADSTATUS_PK_KEY (PK)	NOT NULL	NUMBER	
L1_LEADSTATUS_PK	NULL	VARCHAR2(240)	
L1_LEADSTATUS_PK_ROWID	NULL	VARCHAR2(20)	
L1_LEADSTATUS_DP	NULL	VARCHAR2(240)	
L1_NAME	NULL	VARCHAR2(80)	
L1_INSTANCE	NULL	VARCHAR2(240)	
L1_STATUS_CODE	NULL	VARCHAR2(240)	
L1_MEANING	NULL	VARCHAR2(240)	
L1_DESCRIPTION	NULL	VARCHAR2(240)	
L1_CREATION_DATE	NULL	DATE	
L1_LAST_UPDATE_DATE	NULL	DATE	
L1_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

EDW_BIM_OPP_STATUSES_M

Column Descriptions

Name	Null?	Type	Description
L0_ALL_PK_KEY	NULL	NUMBER	
L0_ALL_PK	NULL	VARCHAR2(40)	
L0_ALL_PK_ROWID	NULL	VARCHAR2(20)	
L0_NAME	NULL	VARCHAR2(80)	
L1_OPPSTATUS_PK_KEY (PK)	NOT NULL	NUMBER	
L1_OPPSTATUS_PK	NULL	VARCHAR2(240)	
L1_OPPSTATUS_PK_ROWID	NULL	VARCHAR2(20)	
L1_OPPSTATUS_DP	NULL	VARCHAR2(240)	
L1_NAME	NULL	VARCHAR2(80)	
L1_INSTANCE	NULL	VARCHAR2(40)	
L1_STATUS_CODE	NULL	VARCHAR2(240)	
L1_MEANING	NULL	VARCHAR2(240)	
L1_DESCRIPTION	NULL	VARCHAR2(240)	
L1_CREATION_DATE	NULL	DATE	
L1_LAST_UPDATE_DATE	NULL	DATE	
L1_USER_ATTRIBUTE1	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE2	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE3	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE4	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE5	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE6	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE7	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE8	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE9	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE10	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE11	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE12	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE13	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE14	NULL	VARCHAR2(240)	
L1_USER_ATTRIBUTE15	NULL	VARCHAR2(240)	

EDW_SOURCE_INSTANCES

Column Descriptions

Name	Null?	Type	Description
INSTANCE_CODE	NULL	VARCHAR2(30)	
WAREHOUSE_TO_INSTANCE_LINK	NULL	VARCHAR2(240)	
CREATION_DATE	NULL	DATE	
CREATED_BY	NULL	NUMBER	
LAST_UPDATE_DATE	NULL	DATE	
LAST_UPDATE_LOGIN	NULL	NUMBER	
LAST_UPDATED_BY	NULL	NUMBER	
ENABLED_FLAG	NULL	VARCHAR2(10)	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_SOURCE_INSTANCES_U1	UNIQUE	1	INSTANCE_CODE

EDW_SOURCE_INSTANCES_TL

Column Descriptions

Name	Null?	Type	Description
INSTANCE_CODE	NULL	VARCHAR2(30)	
LANGUAGE	NULL	VARCHAR2(30)	
TRANSLATED	NULL	VARCHAR2(1)	
SOURCE_LANG	NULL	VARCHAR2(30)	
NAME	NULL	VARCHAR2(80)	
DESCRIPTION	NULL	VARCHAR2(240)	
CREATION_DATE	NULL	DATE	
CREATED_BY	NULL	NUMBER	
LAST_UPDATE_DATE	NULL	DATE	
LAST_UPDATE_LOGIN	NULL	NUMBER	
LAST_UPDATED_BY	NULL	NUMBER	

Indexes

Index Name	Index Type	Sequence	Column Name
EDW_SOURCE_INSTANCES_TL_U1	UNIQUE	1	INSTANCE_CODE
		2	LANGUAGE

JTF_BIS_CHART_FUNCTIONS

This table is for storing the hyperlink information of each chart plug report.

Column Descriptions

Name	Null?	Type	Description
SECURITY_GROUP_ID	NULL	NUMBER	
FUNCTION_ID	NOT NULL	NUMBER	Function ID of the Chart Report
CREATION_DATE	NOT NULL	DATE	Creation date of the Chart report record
CREATED_BY	NOT NULL	NUMBER	User ID of the user that created this record
LAST_UPDATE_DATE	NOT NULL	DATE	The last update date of this record
LAST_UPDATED_BY	NOT NULL	NUMBER	User that last updated the record
LAST_UPDATE_LOGIN	NULL	NUMBER	Login ID of the user that last updated the record
LINK_REPORT_FILE_NAME	NOT NULL	VARCHAR2(30)	The file name of the report navigated from the Chart report
CHART_REPORT_FILE_NAME	NOT NULL	VARCHAR2(30)	The file name of the Chart report
LINK_REPORT_ID	NOT NULL	VARCHAR2(30)	The report ID of the report navigated from the Chart report
CHART_REPORT_ID	NOT NULL	VARCHAR2(30)	The report ID of the Chart report

JTF_BIS_USER_CHART_PLUGS

This table is for storing Chart report information for each user-defined Chart Plug

Column Descriptions

Name	Null?	Type	Description
SECURITY_GROUP_ID	NULL	NUMBER	
PLUG_ID	NOT NULL	NUMBER	Plug ID of ICX PHP Plugs
USER_ID	NOT NULL	NUMBER	The User ID of the user that created this record
FUNCTION_ID	NOT NULL	NUMBER	Function ID of the Chart report
RESPONSIBILITY_ID	NOT NULL	NUMBER	Responsibility ID of the user that created this record
CREATION_DATE	NOT NULL	DATE	Creation date of this record
CREATED_BY	NOT NULL	NUMBER	The user that created this record
LAST_UPDATE_DATE	NOT NULL	DATE	Last update date of this record
LAST_UPDATED_BY	NOT NULL	NUMBER	The user that last updated this record
LAST_UPDATE_LOGIN	NULL	NUMBER	The login ID of the user that last updated this record
SEQ	NOT NULL	NUMBER	Sequential number of the report
REPORT_PARAMETER	NULL	VARCHAR2(2000)	For the storage of the HTML strings of report parameters

JTF_BIS_USER_FAVORITE_PLUGS

This table is for storing Chart report information for each user-defined Favorite Plug

Column Descriptions

Name	Null?	Type	Description
SECURITY_GROUP_ID	NULL	NUMBER	
PLUG_ID	NOT NULL	NUMBER	Plug ID for ICX PHP Plugs
USER_ID	NOT NULL	NUMBER	The User ID of the user that created this record
FUNCTION_ID	NOT NULL	NUMBER	Function ID of the Favorite report
RESPONSIBILITY_ID	NOT NULL	NUMBER	Responsibility ID of the user that created this record
CREATION_DATE	NOT NULL	DATE	Creation date of this record
CREATED_BY	NOT NULL	NUMBER	The user that created this record
LAST_UPDATE_DATE	NOT NULL	DATE	Last update date of this record
LAST_UPDATED_BY	NOT NULL	NUMBER	The user that last updated this record
LAST_UPDATE_LOGIN	NULL	NUMBER	The login ID of the user that last updated this record
SEQ	NOT NULL	NUMBER	Sequential number of the report
REPORT_PARAMETER	NULL	VARCHAR2(2000)	For the storage of the HTML strings of report parameters
FAVORITE_LINK_NAME	NULL	VARCHAR2(240)	The name of the Favorite report
REPORT_ID	NULL	VARCHAR2(30)	The report ID of the Favorite report
RDF_FILE_NAME	NULL	VARCHAR2(30)	The report file name of the Favorite report
APPLICATION_ID	NULL	NUMBER	The application ID of the Favorite report

JTF_BRM_PARAMETERS

The JTF_BRM_PARAMETERS table is used to store the parameter values for the main workflow process of the Business Rule Monitor. Values for the BRM_UOM_CODE, BRM_WF_COMMAND_CODE are provided and validated through lookups to the FND_LOOKUPS view. The table holds only one record.

Column Descriptions

Name	Null?	Type	Description
PARAMETER_ID (PK)	NOT NULL	NUMBER	Unique identifier for the parameter
CREATED_BY	NOT NULL	NUMBER(15)	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER(15)	Standard Who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN		NUMBER(15)	Standard Who column
BRM_UOM_TYPE	NULL	VARCHAR2(30)	Lookup type for the unit of measure
BRM_UOM_CODE	NULL	VARCHAR2(30)	Lookup code for the check business rule monitor's unit of measure
BRM_INTERVAL	NULL	NUMBER(9)	Business rule monitor interval
BRM_WF_COMMAND_TYPE	NULL	VARCHAR2(30)	Lookup type for the workflow command
BRM_WF_COMMAND_CODE	NULL	VARCHAR2(30)	Lookup code for the workflow command
WORKFLOW_PROCESS_ID	NULL	NUMBER	Workflow process identifier
WORKFLOW_ITEM_TYPE	NULL	VARCHAR2(8)	Workflow item type
WORKFLOW_PROCESS_NAME	NULL	VARCHAR2(30)	Workflow process name
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive Flexfield segment
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive Flexfield segment
SECURITY_GROUP_ID	NULL	NUMBER	

Sequences

Sequence	Derived Column
JTF_BRM_PARAMETERS_S	PARAMETER_ID

JTF_RS_GROUPS_B

Base Table JTF_RS_GROUPS_B stores general information about a given Group.

Column Descriptions

Name	Null?	Type	Description
GROUP_ID (PK)	NOT NULL	NUMBER	Resource group unique identifier
GROUP_NUMBER	NOT NULL	VARCHAR2(30)	Group Number
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
EXCLUSIVE_FLAG	NULL	VARCHAR2(1)	Indicates whether the group is exclusive
START_DATE_ACTIVE	NULL	DATE	Date before which the group is not enabled
END_DATE_ACTIVE	NULL	DATE	Date after which the group is not enabled
ACCOUNTING_CODE	NULL	VARCHAR2(80)	Account code, used by Sales
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
EMAIL_ADDRESS	NULL	VARCHAR2(240)	Email Address of Group
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking control

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes
-------------------	------	--------	--

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_GROUPS_B_U1	UNIQUE	1	GROUP_ID

Sequences

Sequence	Derived Column
JTF_RS_GROUPS_S	GROUP_ID
JTF_RS_GROUP_NUMBER_S	GROUP_NUMBER

JTF_RS_GROUPS_DENORM

This is a denormalized table for Group. It stores information about parent group and immediate parent flag.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_GROUPS_B	GROUP_ID	GROUP_ID
JTF_RS_GROUPS_B	GROUP_ID	PARENT_GROUP_ID

Column Descriptions

Name	Null?	Type	Description
DENORM_GRP_ID (PK)	NOT NULL	NUMBER	Unique Identifier for Group Denorm
GROUP_ID	NOT NULL	NUMBER	Group identifier
PARENT_GROUP_ID	NOT NULL	NUMBER	Parent Group identifier
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
IMMEDIATE_PARENT_FLAG	NOT NULL	VARCHAR2(1)	Indicates whether the value in PARENT_GROUP_ID is the identifier of immediate parent group
START_DATE_ACTIVE	NULL	DATE	Date this group becomes active
END_DATE_ACTIVE	NULL	DATE	Date this group becomes inactive
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking control when using HTML as a user interface
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_GROUPS_DENORM_N1	NOT UNIQUE	1	GROUP_ID
		2	PARENT_GROUP_ID
JTF_RS_GROUPS_DENORM_N2	NOT UNIQUE	5	PARENT_GROUP_ID
JTF_RS_GROUPS_DENORM_U1	UNIQUE	5	DENORM_GRP_ID

Sequences

Sequence	Derived Column
JTF_RS_GROUPS_DENORM_S	DENORM_GRP_ID

JTF_RS_GROUPS_TL

Translation table for JTF_RS_GROUPS_B. It is used to store all columns and data that are needed for Multi-Language Support.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_GROUPS_B	GROUP_ID	GROUP_ID

Column Descriptions

Name	Null?	Type	Description
GROUP_ID (PK)	NOT NULL	NUMBER	Group identifier
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
GROUP_NAME	NOT NULL	VARCHAR2(30)	Name of Group
GROUP_DESC	NULL	VARCHAR2(80)	Group Description
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Language of text . The language to which things are translated.
SOURCE_LANG	NOT NULL	VARCHAR2(4)	The language from which things are translated .
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_GROUPS_TL_U1	UNIQUE	1	GROUP_ID
		2	LANGUAGE

JTF_RS_GROUP_MEMBERS

This table stores the resources who are assigned to be group members.
Primary key is Group_member_id.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_GROUPS_B	GROUP_ID	GROUP_ID
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	RESOURCE_ID

Column Descriptions

Name	Null?	Type	Description
GROUP_MEMBER_ID (PK)	NOT NULL	NUMBER	Resource Group Member identifier
GROUP_ID	NOT NULL	NUMBER	Resource Group identifier (foreign key to JTF_RS_GROUPS)
RESOURCE_ID	NOT NULL	NUMBER	Resource identifier
PERSON_ID	NULL	NUMBER	Employee identifier
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column

DELETE_FLAG	NULL	VARCHAR2(1)	Delete Flag. Indicates whether this member is logically deleted or not
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_GROUP_MEMBERS_N1	NOT UNIQUE	5	GROUP_ID
		10	RESOURCE_ID
JTF_RS_GROUP_MEMBERS_U1	UNIQUE	1	GROUP_MEMBER_ID

Sequences

Sequence	Derived Column
JTF_RS_GROUP_MEMBERS_S	GROUP_MEMBER_ID

JTF_RS_GROUP_USAGES

This table stores the usages which are assigned to be groups. Primary key is Group_usage_id. Group_id and usage are unique key.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_GROUPS_B	GROUP_ID	GROUP_ID

Column Descriptions

Name	Null?	Type	Description
GROUP_USAGE_ID (PK)	NOT NULL	NUMBER	Group Usage Identifier
GROUP_ID	NOT NULL	NUMBER	Group Identifier
USAGE	NOT NULL	VARCHAR2(240)	Usage attached to Group
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_GROUP_USAGES_U1	UNIQUE	1	GROUP_USAGE_ID
JTF_RS_GROUP_USAGES_U2	UNIQUE	1	GROUP_ID
		2	USAGE

Sequences

Sequence	Derived Column
JTF_RS_GROUP_USAGES_S	GROUP_USAGE_ID

JTF_RS_GRP_RELATE_AUD

The table that stores audit information for a group relation

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_GRP_RELATIONS	GROUP_RELATE_ID	GROUP_RELATE_ID

Column Descriptions

Name	Null?	Type	Description
GROUP_RELATE_AUDIT_ID (PK)	NOT NULL	NUMBER	Group Relation audit identifier
GROUP_RELATE_ID	NOT NULL	NUMBER	The group relate id for which the audit record is stored
NEW_GROUP_ID	NULL	NUMBER	New group id
OLD_GROUP_ID	NULL	NUMBER	Old group id
NEW_RELATED_GROUP_ID	NULL	NUMBER	New related group id
OLD_RELATED_GROUP_ID	NULL	NUMBER	Old related group id
NEW_START_DATE_ACTIVE	NULL	DATE	New start date active
OLD_START_DATE_ACTIVE	NULL	DATE	Old start date active
NEW_END_DATE_ACTIVE	NULL	DATE	New end date active
OLD_END_DATE_ACTIVE	NULL	DATE	Old end date active
NEW_OBJECT_VERSION_NUMBER	NULL	NUMBER	New object version number
OLD_OBJECT_VERSION_NUMBER	NULL	NUMBER	Old object version number
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user_id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user_id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
NEW_RELATION_TYPE	NULL	VARCHAR2(30)	New value for relation type
OLD_RELATION_TYPE	NULL	VARCHAR2(30)	Old value for Relation Type
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_GRP_RELATE_AUD_U1	UNIQUE	5	GROUP_RELATE_AUDIT_ID

Sequences

Sequence	Derived Column
JTF_RS_GRP_RELATE_AUD_S	GROUP_RELATE_AUDIT_ID

JTF_RS_GRP_RELATIONS

This table stores the relations between Groups. Primary key is Group_relate_id. Ex. for relation_type is 'PARENT_GROUP'

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_GROUPS_B	GROUP_ID	GROUP_ID
JTF_RS_GROUPS_B	GROUP_ID	RELATED_GROUP_ID

Column Descriptions

Name	Null?	Type	Description
GROUP_RELATE_ID	NOT NULL	NUMBER	Group Relation Identifier
GROUP_ID	NOT NULL	NUMBER	Group Identifier
RELATED_GROUP_ID	NOT NULL	NUMBER	Related Group Identifier. If Relation Type is 'PARENT_GROUP' then this will be parent Group
RELATION_TYPE	NOT NULL	VARCHAR2(240)	Relation Type. Ex. 'PARENT_GROUP'
START_DATE_ACTIVE	NOT NULL	DATE	Active Start date of Relation
END_DATE_ACTIVE	NULL	DATE	Active End date of Relation
DELETE_FLAG	NULL	VARCHAR2(1)	Delete Flag. Indicates whether this member is logically deleted or not
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield Structure defining Column
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_GRP_RELATIONS_N1	NOT UNIQUE	1	GROUP_ID
		2	RELATED_GROUP_ID
		3	RELATION_TYPE
JTF_RS_GRP_RELATIONS_U1	UNIQUE	1	GROUP_RELATE_ID

Sequences

Sequence	Derived Column
JTF_RS_GRP_RELATIONS_S	GROUP_RELATE_ID

JTF_RS_JOB_ROLES

This table stores the relations between roles and jobs. Primary key is job_role_id.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_ROLES_B	ROLE_ID	ROLE_ID

Column Descriptions

Name	Null?	Type	Description
JOB_ROLE_ID	NOT NULL	NUMBER	Job Role Identifier.
JOB_ID	NOT NULL	NUMBER	Job Identifier from PER_JOBS
ROLE_ID	NOT NULL	NUMBER	Role Identifier from JTF_RS_ROLES_VL
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield Structure defining Column
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_JOB_ROLES_U1	UNIQUE	1	JOB_ROLE_ID
JTF_RS_JOB_ROLES_U2	UNIQUE	1	JOB_ID
		2	ROLE_ID

Sequences

Sequence	Derived Column
JTF_RS_JOB_ROLES_S	JOB_ROLE_ID

JTF_RS_REP_MANAGERS

Denormalized table that stores the reporting hierarchy of group members

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_GROUPS_B	GROUP_ID	GROUP_ID
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	RESOURCE_ID

Column Descriptions

Name	Null?	Type	Description
DENORM_MGR_ID	NOT NULL	NUMBER	Unique identifier for denorm record
RESOURCE_ID	NOT NULL	NUMBER	Resource identifier of the member
PERSON_ID	NULL	NUMBER	Person id of the member -maps to source id of resource
CATEGORY	NOT NULL	VARCHAR2(30)	category of the resource (eg. EMPLOYEE)
MANAGER_PERSON_ID	NULL	NUMBER	The person identifier of the manager
GROUP_ID	NOT NULL	NUMBER	The group identifier to which this record refers to
HIERARCHY_TYPE	NOT NULL	VARCHAR2(240)	the hierarchy type (refers to fnd_lookups where looup type is JTF_RS_HIERARCHY
CREATED_BY	NOT NULL	NUMBER	standard who column - with user_id from FND_USERS
CREATION_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	standard who column - with user_id from FND_USERS
LAST_UPDATE_DATE	NOT NULL	DATE	standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER	standard who column
REPORTS_TO_FLAG	NOT NULL	VARCHAR2(1)	This flag indicates whether the resource is directly reporting to the manager
START_DATE_ACTIVE	NOT NULL	DATE	Active Start date of the Relation
END_DATE_ACTIVE	NULL	DATE	Active End date od Relation
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking control when using HTML as a user interface
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
PAR_ROLE_RELATE_ID	NULL	NUMBER	The role relation Identifier of the manager record
CHILD_ROLE_RELATE_ID	NULL	NUMBER	The Role Relate Identifier of the member
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_REP_MANAGERS_N1	NOT UNIQUE	1	RESOURCE_ID
		2	MANAGER_PERSON_ID
		3	GROUP_ID
JTF_RS_REP_MANAGERS_N2	NOT UNIQUE	1	MANAGER_PERSON_ID
JTF_RS_REP_MANAGERS_N3	NOT UNIQUE	1	GROUP_ID
JTF_RS_REP_MANAGERS_N4	NOT UNIQUE	1	PERSON_ID
JTF_RS_REP_MANAGERS_N5	NOT UNIQUE	1	PERSON_ID
		2	MANAGER_PERSON_ID
		3	GROUP_ID
JTF_RS_REP_MANAGERS_N6	NOT UNIQUE	1	PERSON_ID
		2	GROUP_ID
		3	MANAGER_PERSON_ID
JTF_RS_REP_MANAGERS_U1	UNIQUE	1	DENORM_MGR_ID

Sequences

Sequence	Derived Column
JTF_RS_REP_MANAGERS_S	DENORM_MGR_ID

JTF_RS_RESOURCE_EXTNS

This is table stores all important information about Resources. These Resources are coming from HR or HZ or Vonder table etc. Primary key is resource_id. Resource_number, user_id sre also unique keys.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_OBJECTS_B	OBJECT_CODE	CATEGORY

Column Descriptions

Name	Null?	Type	Description
RESOURCE_ID (PK)	NOT NULL	NUMBER	Resource Identifier
CREATED_BY	NOT NULL	NUMBER	Standard who column - with user_id from FND_USERS
CREATION_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column - with user_id from FND_USERS
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard who column
CATEGORY	NOT NULL	VARCHAR2(30)	Category of Resource. Validating from JTF_OBJECTS_VL. Allowed values: EMPLOYEE, PARTNER, PARTY, SUPPLIER_CONTACT, OTHER
RESOURCE_NUMBER	NOT NULL	VARCHAR2(30)	Resource Number. This is a Unique and shown to user on forms.
SOURCE_ID	NULL	NUMBER	Source identifier (foreign key to PER_ALL_PEOPLE_F) or (foreign key to HZ_PARTIES) or (foreign key to PO_VENDOR_CONTACTS)
ADDRESS_ID	NULL	NUMBER	Address identifier (foreign key to HZ_PARTY_SITES)
CONTACT_ID	NULL	NUMBER	Contact identifier (foreign key to HZ_ORG_CONTACTS)
MANAGING_EMPLOYEE_ID	NULL	NUMBER	Managing Employee Identifier
START_DATE_ACTIVE	NOT NULL	DATE	Date this Resource becomes active, if limited
END_DATE_ACTIVE	NULL	DATE	Date this Resource becomes inactive, if limited
TIME_ZONE	NULL	NUMBER	This field is used by Service for time zone information (foreign key to HZ_TIMEZONES)
COST_PER_HR	NULL	NUMBER	This field is used by Service for cost per hour of the resource
PRIMARY_LANGUAGE	NULL	VARCHAR2(30)	This field is used by Service for the primary language of the resource
SECONDARY_LANGUAGE	NULL	VARCHAR2(30)	This field is used by Service for the secondary language of the resource
IES_AGENT_LOGIN	NULL	VARCHAR2(240)	Email Center Agent Login
SERVER_GROUP_ID	NULL	NUMBER	Server Group Identifier to which this resource is attached. FK to IEO_SVR_GROUPS , used by interaction centers.
ASSIGNED_TO_GROUP_ID	NULL	NUMBER	Assigned to User Identifier , Foreign Key to FND_USER.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

COST_CENTER	NULL	VARCHAR2(30)	Cost Center to which this resource is attached
CHARGE_TO_COST_CENTER	NULL	VARCHAR2(30)	Cost center which will be charged for this resource
COMPENSATION_CURRENCY_CODE	NULL	VARCHAR2(15)	The currency code in which the resource will be compensated.
COMMISSIONABLE_FLAG	NULL	VARCHAR2(1)	Flag indicating whether the resource is commissionable or not
HOLD_REASON_CODE	NULL	VARCHAR2(30)	Reason Code why the payment will be hold
HOLD_PAYMENT	NULL	VARCHAR2(1)	Flag indicating whether the payment for the resource is on hold or not.
COMP_SERVICE_TEAM_ID	NULL	NUMBER	Comp Service Team Id , FK to jtf_rs_teams_vl
TRANSACTION_NUMBER	NULL	NUMBER	Transaction Number. This will be used at the time of importing Resources.
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking control when using HTML as a user interface
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
USER_ID	NULL	NUMBER	User Id from FND_USER
SUPPORT_SITE_ID	NULL	NUMBER	Support Site from Service
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_RESOURCE_EXTNS_U1	UNIQUE	1	RESOURCE_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

JTF_RS_RESOURCE_EXTNS_U2	UNIQUE	1	RESOURCE_NUMBER
JTF_RS_RESOURCE_EXTNS_U3	UNIQUE	1	USER_ID

Sequences

Sequence	Derived Column
JTF_RS_RESOURCE_EXTNS_S	RESOURCE_ID
JTF_RS_RESOURCE_NUMBER_S	RESOURCE_NUMBER
JTF_RS_TRANSACTION_NUM_S	TRANSACTION_NUMBER

JTF_RS_RESOURCE_VALUES

This table stores resource values. Resource_param_value_id is the primary key.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	RESOURCE_ID
JTF_RS_RESOURCE_PARAMS	RESOURCE_PARAM_ID	RESOURCE_PARAM_ID

Column Descriptions

Name	Null?	Type	Description
RESOURCE_PARAM_VALUE_ID	NOT NULL	NUMBER	Resource value identifier (PK)
RESOURCE_ID	NOT NULL	NUMBER	Resource Identifier
RESOURCE_PARAM_ID	NOT NULL	NUMBER	Resource Param Identifier
VALUE	NULL	VARCHAR2(255)	Value of this parameter
VALUE_TYPE	NULL	VARCHAR2(30)	Application specific grouping of a parameter value. For eg., CCT can use this for associating middleware configuration with values.
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield Structure defining Column
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_RESOURCE_VALUES_U1	UNIQUE	1	RESOURCE_PARAM_VALUE_ID
JTF_RS_RESOURCE_VALUES_U2	UNIQUE	1	RESOURCE_ID
		2	RESOURCE_PARAM_ID
		3	VALUE_TYPE

Sequences

Sequence	Derived Column
JTF_RS_RESOURCE_VALUES_S	RESOURCE_PARAM_VALUE_ID

JTF_RS_ROLES_B

Base Table JTF_RS_ROLES_B stores general information about a given Role.

Column Descriptions

Name	Null?	Type	Description
ROLE_ID (PK)	NOT NULL	NUMBER	Unique role identifier
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
SEDED_FLAG	NULL	VARCHAR2(1)	Flag indicating pre-defined role types
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield Structure defining Column
ROLE_CODE	NOT NULL	VARCHAR2(30)	Role Code
ROLE_TYPE_CODE	NOT NULL	VARCHAR2(240)	Role type identifier (lookup type: JTF_RS_ROLE_TYPE)
MEMBER_FLAG	NULL	VARCHAR2(1)	Flag indicating if this role is a member role or not
ADMIN_FLAG	NULL	VARCHAR2(1)	Flag indicating if this role is an admin role or not
LEAD_FLAG	NULL	VARCHAR2(1)	Flag indicating if this role is a leader role or not
MANAGER_FLAG	NULL	VARCHAR2(1)	Flag indicating if this role is a manager role or not

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ACTIVE_FLAG	NOT NULL	VARCHAR2(1)	Flag indicating this role is an active role or not
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

<u>Index Name</u>	<u>Index Type</u>	<u>Sequence</u>	<u>Column Name</u>
JTF_RS_ROLES_B_U1	UNIQUE	1	ROLE_ID

JTF_RS_ROLES_TL

Translation table for JTF_RS_ROLES_B. It is used to store all columns and data that are needed for Multi-Language Support.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_ROLES_B	ROLE_ID	ROLE_ID

Column Descriptions

Name	Null?	Type	Description
ROLE_ID (PK)	NOT NULL	NUMBER	Unique role identifier
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with the user id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN		NUMBER	Standard Who column
ROLE_NAME	NOT NULL	VARCHAR2(30)	Role name
ROLE_DESC		VARCHAR2(80)	Role Description
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Language of text . The language to which things are translated.
SOURCE_LANG	NOT NULL	VARCHAR2(4)	The language from which things are translated .
SECURITY_GROUP_ID		NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_ROLES_TL_U1	UNIQUE	1	ROLE_ID
		2	LANGUAGE

Sequences

Sequence	Derived Column
JTF_RS_ROLES_S	ROLE_ID

JTF_RS_ROLE_RELATE_AUD

Base Table which stores audit information for a Role Relation.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_ROLE_RELATIONS	ROLE_RELATE_ID	ROLE_RELATE_ID

Column Descriptions

Name	Null?	Type	Description
ROLE_RELATE_AUDIT_ID (PK)	NOT NULL	NUMBER	Audit Id for Role Relation
ROLE_RELATE_ID	NOT NULL	NUMBER	Role Relation Identifier
NEW_ROLE_ID	NULL	NUMBER	New Role Identifier
OLD_ROLE_ID	NULL	NUMBER	Old Role Identifier
NEW_START_DATE_ACTIVE	NULL	DATE	New Active Start Date
OLD_START_DATE_ACTIVE	NULL	DATE	End Active Start Date
NEW_END_DATE_ACTIVE	NULL	DATE	New Active End Date
OLD_END_DATE_ACTIVE	NULL	DATE	End Active End Date
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with theuser id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with theuser id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
NEW_ROLE_RESOURCE_TYPE	NULL	VARCHAR2(30)	New role resource type
OLD_ROLE_RESOURCE_TYPE	NULL	VARCHAR2(30)	Old role resource type
NEW_OBJECT_VERSION_NUMBER	NULL	NUMBER	New object version number
OLD_OBJECT_VERSION_NUMBER	NULL	NUMBER	Old object version number
NEW_ROLE_RESOURCE_ID	NULL	NUMBER	New role resource id
OLD_ROLE_RESOURCE_ID	NULL	NUMBER	Old role resource id
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_ROLE_RELATE_AUD_U1	UNIQUE	1	ROLE_RELATE_AUDIT_ID

Sequences

Sequence	Derived Column
JTF_RS_ROLE_RELATE_AUD_S	ROLE_RELATE_AUDIT_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

JTF_RS_ROLE_RELATIONS

This table stores the association between resources and roles. Primary key is Resource_id and Role_id. Each resource can be assigned to multiple roles.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_OBJECTS_B	OBJECT_CODE	ROLE_RESOURCE_TYPE
JTF_RS_GROUPS_B	GROUP_ID	ROLE_RESOURCE_ID
JTF_RS_GROUP_MEMBERS	GROUP_MEMBER_ID	ROLE_RESOURCE_ID
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	ROLE_RESOURCE_ID
JTF_RS_ROLES_B	ROLE_ID	ROLE_ID
JTF_RS_TEAMS_B	TEAM_ID	ROLE_RESOURCE_ID
JTF_RS_TEAM_MEMBERS	TEAM_MEMBER_ID	ROLE_RESOURCE_ID

Column Descriptions

Name	Null?	Type	Description
ROLE_RELATE_ID	NOT NULL	NUMBER	Role Relation identifier (PK)
ROLE_RESOURCE_TYPE	NOT NULL	VARCHAR2(30)	Resource type. (lookup type: JTF_RS_ROLE_RES_TYPE)
ROLE_RESOURCE_ID	NOT NULL	NUMBER	Resource identifier (foreign key to JTF_RESOURCE_EXTN) or (foreign key to JTF_RS_GROUPS_VL) or (foreign key to JTF_RS_GROUPS_MEMBERS or (foreign key to JTF_RS_TEAMS_VL) or (foreign key to JTF_RS_TEAM_MEMBERS)
ROLE_ID	NOT NULL	NUMBER	Role identifier (foreign key to JTF_RS_ROLES)
START_DATE_ACTIVE	NOT NULL	DATE	Date this role-resource becomes active
END_DATE_ACTIVE		DATE	Date this role-resource becomes inactive
DELETE_FLAG		NULL VARCHAR2(1)	Delete Flag indicates whether this record is logically deleted or not?
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking
CREATED_BY	NOT NULL	NUMBER	Standard Who column - with theuser id from FND_USER
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column - with theuser id from FND_USER
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN		NULL NUMBER	Standard Who column
ATTRIBUTE1		NULL VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE2		NULL VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE3		NULL VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE4		NULL VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE5		NULL VARCHAR2(150)	Descriptive flexfield segment Column

ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment Column
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_ROLE_RELATIONS_U1	UNIQUE	1	ROLE_RELATE_ID
JTF_RS_ROLE_RELATIONS_U2	UNIQUE	1	ROLE_RESOURCE_TYPE
		2	ROLE_RESOURCE_ID
		3	ROLE_ID
		5	DELETE_FLAG
		7	START_DATE_ACTIVE

Sequences

Sequence	Derived Column
JTF_RS_ROLE_RELATIONS_S	ROLE_RELATE_ID

JTF_RS_SALESREPS

This table stores information about salesreps. Salesrep_id is the primary key. If resource category is 'OTHERS' then salesrep_number and org_id are unique.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_RESOURCE_EXTNS	RESOURCE_ID	RESOURCE_ID

Column Descriptions

Name	Null?	Type	Description
SALESREP_ID	NOT NULL	NUMBER	Unique Salesrep Identifier (PK)
RESOURCE_ID	NOT NULL	NUMBER	Resource Identifier (FK to JTF_RS_RESOURCE_EXTNS)
LAST_UPDATE_DATE	NOT NULL	DATE	standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	standard who column
CREATION_DATE	NOT NULL	DATE	standard who column
CREATED_BY	NOT NULL	NUMBER	standard who column
LAST_UPDATE_LOGIN	NULL	NUMBER	standard who column
SALES_CREDIT_TYPE_ID	NOT NULL	NUMBER	Sales Credit Type Identifier (FK to so_sales_credit_types)
NAME	NULL	VARCHAR2(240)	Salesrep Name (used for OTHER type of salesrep)
STATUS	NULL	VARCHAR2(30)	Status of salesrep whether he or she is active in AR or not (Used for OTHER type of Salesreps)
START_DATE_ACTIVE	NOT NULL	DATE	Date this salesrep becomes active
END_DATE_ACTIVE	NULL	DATE	Date this salesrep becomes inactive
GL_ID_REV	NULL	NUMBER	Revenue account id (key flex field for revenue account)
GL_ID_FREIGHT	NULL	NUMBER	Freight account id (key flex field for freight account)
GL_ID_REC	NULL	NUMBER	Receivable account id (key flex field for rceivables account)
SET_OF_BOOKS_ID	NULL	NUMBER	Set of books id
SALESREP_NUMBER	NULL	VARCHAR2(30)	Unique number given to salesrep (used for OTHER type of salesreps)
ORG_ID	NULL	NUMBER	org id of salesrep
EMAIL_ADDRESS	NULL	VARCHAR2(30)	Email address of salesreps
WH_UPDATE_DATE	NULL	DATE	wh update date (used by AR)
PERSON_ID	NULL	NUMBER	Person id of salesrep (In case of EMPLOYEE)
SALES_TAX_GEOCODE	NULL	VARCHAR2(30)	sales tax geocode (used by AR)
SALES_TAX_INSIDE_CITY_LIMITS	NULL	VARCHAR2(1)	sales Tax inside city limits (used by AR)
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking control
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive Flexfield Structure Defining Column
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive Flexfield Segment Column
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_SALESREPS_N1	NOT UNIQUE	5	PERSON_ID
JTF_RS_SALESREPS_N2	NOT UNIQUE	5	NAME
JTF_RS_SALESREPS_N3	NOT UNIQUE	5	SALESREP_NUMBER
JTF_RS_SALESREPS_N4	NOT UNIQUE	1	RESOURCE_ID
JTF_RS_SALESREPS_U1	UNIQUE	1	SALESREP_ID
		2	ORG_ID

Sequences

Sequence	Derived Column
JTF_RS_SALESREPS_S	SALESREP_ID

JTF_RS_SRP_TERRITORIES

This table stores information about combination of salesrep and territories.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_SALESREPS	SALESREP_ID	SALESREP_ID

Column Descriptions

Name	Null?	Type	Description
SALESREP_TERRITORY_ID	NOT NULL	NUMBER	Salesrep Territory Identifier (PK)
LAST_UPDATE_DATE	NOT NULL	DATE	Standard who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard who column
CREATION_DATE	NOT NULL	DATE	Standard who column
CREATED_BY	NOT NULL	NUMBER	Standard who column
LAST_UPDATE_LOGIN		NUMBER	Standard who column
SALESREP_ID	NOT NULL	NUMBER	Salesrep Identifier (foreign key to JTF_RS_Salesreps)
TERRITORY_ID	NOT NULL	NUMBER	Territory Identifier (FK to RA_TERRITORIES)
STATUS		VARCHAR2(30)	Status
START_DATE_ACTIVE	NOT NULL	DATE	Date this salesrep territory combination becomes active
END_DATE_ACTIVE		DATE	Date this salesrep territory combination becomes inactive
WH_UPDATE_DATE		DATE	WH update date (used by AR)
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking control
ATTRIBUTE_CATEGORY		VARCHAR2(30)	Descriptive flexfield structure defining column
ATTRIBUTE1		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE2		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE3		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE4		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE5		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE6		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE7		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE8		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE9		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE10		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE11		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE12		VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE13		VARCHAR2(150)	Descriptive flexfield Segment Column

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield Segment Column
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield Segment Column
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_SRP_TERRITORIES_U1	UNIQUE	1	SALESREP_TERRITORY_ID

Sequences

Sequence	Derived Column
JTF_RS_SRP_TERRITORIES_S	SALESREP_TERRITORY_ID

JTF_RS_TEAMS_B

Base Table JTF_RS_TEAMS_B stores general information about a given Team.

Column Descriptions

Name	Null?	Type	Description
TEAM_ID (PK)	NOT NULL	NUMBER	Resource team unique identifier
TEAM_NUMBER	NOT NULL	VARCHAR2(30)	Team Number
CREATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
EXCLUSIVE_FLAG	NULL	VARCHAR2(1)	Indicates whether the group is exclusive
START_DATE_ACTIVE	NULL	DATE	Date before which the group is not enabled
END_DATE_ACTIVE	NULL	DATE	Date after which the group is not enabled
ATTRIBUTE1	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(150)	Descriptive flexfield segment
ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Descriptive flexfield structure defining column
EMAIL_ADDRESS	NULL	VARCHAR2(240)	Email Address of Team
OBJECT_VERSION_NUMBER	NOT NULL	NUMBER	Sequential number used for database locking control
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_TEAMS_B_U1	UNIQUE	1	TEAM_ID

Sequences

Sequence	Derived Column
JTF_RS_TEAMS_S	TEAM_ID
JTF_RS_TEAM_NUMBER_S	TEAM_NUMBER

JTF_RS_TEAMS_TL

Translation table for JTF_RS_TEAMS_B. It is used to store all columns and data that are needed for Multi-Language Support.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
JTF_RS_TEAMS_B	TEAM_ID	TEAM_ID

Column Descriptions

Name	Null?	Type	Description
TEAM_ID (PK)	NOT NULL	NUMBER	Resource team unique identifier
CREATED_BY	NOT NULL	NUMBER	Standard Who column
CREATION_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
TEAM_NAME	NOT NULL	VARCHAR2(30)	Team name
TEAM_DESC	NULL	VARCHAR2(80)	Team Description
LANGUAGE (PK)	NOT NULL	VARCHAR2(4)	Language of text . The language to which things are translated.
SOURCE_LANG	NOT NULL	VARCHAR2(4)	The language from which things are translated .
SECURITY_GROUP_ID	NULL	NUMBER	Column used for Applications Hosting purposes

Indexes

Index Name	Index Type	Sequence	Column Name
JTF_RS_TEAMS_TL_U1	UNIQUE	1	TEAM_ID
		2	LANGUAGE

OE_CRM_ORDER_HEADERS_V

Compatible view provided for CRM usage only. The view is based on oe_order_headers_all table.

View Definition

```
CREATE VIEW OE_CRM_ORDER_HEADERS_V
as SELECT
    HEADER_ID,
    ORG_ID,
    ORDER_TYPE_ID,
    ORDER_NUMBER,
    VERSION_NUMBER,
    EXPIRATION_DATE,
    ORDER_SOURCE_ID,
    SOURCE_DOCUMENT_TYPE_ID,
    ORIG_SYS_DOCUMENT_REF,
    SOURCE_DOCUMENT_ID,
    ORDERED_DATE,
    REQUEST_DATE,
    PRICING_DATE,
    SHIPMENT_PRIORITY_CODE,
    DEMAND_CLASS_CODE,
    PRICE_LIST_ID,
    TAX_EXEMPT_FLAG,
    TAX_EXEMPT_NUMBER,
    TAX_EXEMPT_REASON_CODE,
    CONVERSION_RATE,
    CONVERSION_TYPE_CODE,
    CONVERSION_RATE_DATE,
    PARTIAL_SHIPMENTS_ALLOWED,
    SHIP_TOLERANCE_ABOVE,
    SHIP_TOLERANCE_BELOW,
    TRANSACTIONAL_CURR_CODE,
    AGREEMENT_ID,
    TAX_POINT_CODE,
    CUST_PO_NUMBER,
    INVOICING_RULE_ID,
    ACCOUNTING_RULE_ID,
    PAYMENT_TERM_ID,
    SHIPPING_METHOD_CODE,
    FREIGHT_CARRIER_CODE,
    FOB_POINT_CODE,
    FREIGHT_TERMS_CODE,
    SOLD_TO_ORG_ID,
    SOLD_FROM_ORG_ID,
    SHIP_FROM_ORG_ID,
    SHIP_TO_ORG_ID,
    INVOICE_TO_ORG_ID,
    DELIVER_TO_ORG_ID,
    SOLD_TO_CONTACT_ID,
    SHIP_TO_CONTACT_ID,
    INVOICE_TO_CONTACT_ID,
    DELIVER_TO_CONTACT_ID,
    CREATION_DATE,
```

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CREATED_BY,
 LAST_UPDATED_BY,
 LAST_UPDATE_DATE,
 LAST_UPDATE_LOGIN,
 PROGRAM_APPLICATION_ID,
 PROGRAM_ID,
 PROGRAM_UPDATE_DATE,
 REQUEST_ID,
 CONTEXT,
 ATTRIBUTE1,
 ATTRIBUTE2,
 ATTRIBUTE3,
 ATTRIBUTE4,
 ATTRIBUTE5,
 ATTRIBUTE6,
 ATTRIBUTE7,
 ATTRIBUTE8,
 ATTRIBUTE9,
 ATTRIBUTE10,
 ATTRIBUTE11,
 ATTRIBUTE12,
 ATTRIBUTE13,
 ATTRIBUTE14,
 ATTRIBUTE15,
 GLOBAL_ATTRIBUTE_CATEGORY,
 GLOBAL_ATTRIBUTE1,
 GLOBAL_ATTRIBUTE2,
 GLOBAL_ATTRIBUTE3,
 GLOBAL_ATTRIBUTE4,
 GLOBAL_ATTRIBUTE5,
 GLOBAL_ATTRIBUTE6,
 GLOBAL_ATTRIBUTE7,
 GLOBAL_ATTRIBUTE8,
 GLOBAL_ATTRIBUTE9,
 GLOBAL_ATTRIBUTE10,
 GLOBAL_ATTRIBUTE11,
 GLOBAL_ATTRIBUTE12,
 GLOBAL_ATTRIBUTE13,
 GLOBAL_ATTRIBUTE14,
 GLOBAL_ATTRIBUTE15,
 GLOBAL_ATTRIBUTE16,
 GLOBAL_ATTRIBUTE17,
 GLOBAL_ATTRIBUTE18,
 GLOBAL_ATTRIBUTE19,
 GLOBAL_ATTRIBUTE20,
 CANCELLED_FLAG,
 OPEN_FLAG,
 BOOKED_FLAG,
 SALESREP_ID,
 RETURN_REASON_CODE,
 ORDER_DATE_TYPE_CODE,
 EARLIEST_SCHEDULE_LIMIT,
 LATEST_SCHEDULE_LIMIT,
 PAYMENT_TYPE_CODE,
 PAYMENT_AMOUNT,
 CHECK_NUMBER,
 CREDIT_CARD_CODE,

Oracle Proprietary, Confidential Information--Use Restricted by Contract

```

CREDIT
    _CARD_HOLDER_NAME,
CREDIT_CARD_NUMBER,
CREDIT_CARD_EXPIRATION_DATE,
CREDIT_CARD_APPROVAL_CODE,
CREDIT_CARD_APPROVAL_DATE,
SALES_CHANNEL_CODE,
FIRST_ACK_CODE,
FIRST_ACK_DATE,
LAST_ACK_CODE,
LAST_ACK_DATE,
ORDER_CATEGORY_CODE,
SHIPPING_INSTRUCTIONS,
PACKING_INSTRUCTIONS
from OE_ORDER_HEADERS_ALL
    Where NVL(ORG_ID,NVL(TO_NUMBER(DECODE(SUBSTR(USERENV('CLIENT_INFO'),1,1), ' ',
        NULL, SUBSTR(USERENV('CLIENT_INFO'),1,10))),-99)) =
        NVL(TO_NUMBER(DECODE(SUBSTR(USERENV('CLIENT_INFO'),1,1), ' ', NULL,
            SUBSTR(USERENV('CLIENT_INFO'),1,10))),-99)

```

Column Descriptions

Name	Null?	Type	Description
HEADER_ID	NOT NULL	NUMBER	Refer to base table.
ORG_ID	NULL	NUMBER	Refer to base table.
ORDER_TYPE_ID	NOT NULL	NUMBER	Refer to base table.
ORDER_NUMBER	NOT NULL	NUMBER	Refer to base table.
VERSION_NUMBER	NOT NULL	NUMBER	Refer to base table.
EXPIRATION_DATE	NULL	DATE	Refer to base table.
ORDER_SOURCE_ID	NULL	NUMBER	Refer to base table.
SOURCE_DOCUMENT_TYPE_ID	NULL	NUMBER	Refer to base table.
ORIG_SYS_DOCUMENT_REF	NULL	VARCHAR2(50)	Refer to base table.
SOURCE_DOCUMENT_ID	NULL	NUMBER	Refer to base table.
ORDERED_DATE	NULL	DATE	Refer to base table.
REQUEST_DATE	NULL	DATE	Refer to base table.
PRICING_DATE	NULL	DATE	Refer to base table.
SHIPMENT_PRIORITY_CODE	NULL	VARCHAR2(30)	Refer to base table.
DEMAND_CLASS_CODE	NULL	VARCHAR2(30)	Refer to base table.
PRICE_LIST_ID	NULL	NUMBER	Refer to base table.
TAX_EXEMPT_FLAG	NULL	VARCHAR2(1)	Refer to base table.
TAX_EXEMPT_NUMBER	NULL	VARCHAR2(80)	Refer to base table.
TAX_EXEMPT_REASON_CODE	NULL	VARCHAR2(30)	Refer to base table.
CONVERSION_RATE	NULL	NUMBER	Refer to base table.
CONVERSION_TYPE_CODE	NULL	VARCHAR2(30)	Refer to base table.
CONVERSION_RATE_DATE	NULL	DATE	Refer to base table.
PARTIAL_SHIPMENTS_ALLOWED	NULL	VARCHAR2(1)	Refer to base table.
SHIP_TOLERANCE_ABOVE	NULL	NUMBER	Refer to base table.
SHIP_TOLERANCE_BELOW	NULL	NUMBER	Refer to base table.
TRANSACTIONAL_CURR_CODE	NULL	VARCHAR2(3)	Refer to base table.
AGREEMENT_ID	NULL	NUMBER	Refer to base table.
TAX_POINT_CODE	NULL	VARCHAR2(30)	Refer to base table.
CUST_PO_NUMBER	NULL	VARCHAR2(50)	Refer to base table.
INVOICING_RULE_ID	NULL	NUMBER(15)	Refer to base table.
ACCOUNTING_RULE_ID	NULL	NUMBER(15)	Refer to base table.
PAYMENT_TERM_ID	NULL	NUMBER(15)	Refer to base table.
SHIPPING_METHOD_CODE	NULL	VARCHAR2(30)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

FREIGHT_CARRIER_CODE	NULL	VARCHAR2(30)	Refer to base table.
FOB_POINT_CODE	NULL	VARCHAR2(30)	Refer to base table.
FREIGHT_TERMS_CODE	NULL	VARCHAR2(30)	Refer to base table.
SOLD_TO_ORG_ID	NULL	NUMBER	Refer to base table.
SOLD_FROM_ORG_ID	NULL	NUMBER	Refer to base table.
SHIP_FROM_ORG_ID	NULL	NUMBER	Refer to base table.
SHIP_TO_ORG_ID	NULL	NUMBER	Refer to base table.
INVOICE_TO_ORG_ID	NULL	NUMBER	Refer to base table.
DELIVER_TO_ORG_ID	NULL	NUMBER	Refer to base table.
SOLD_TO_CONTACT_ID	NULL	NUMBER	Refer to base table.
SHIP_TO_CONTACT_ID	NULL	NUMBER	Refer to base table.
INVOICE_TO_CONTACT_ID	NULL	NUMBER	Refer to base table.
DELIVER_TO_CONTACT_ID	NULL	NUMBER	Refer to base table.
CREATION_DATE	NOT NULL	DATE	Refer to base table.
CREATED_BY	NOT NULL	NUMBER	Refer to base table.
LAST_UPDATED_BY	NOT NULL	NUMBER	Refer to base table.
LAST_UPDATE_DATE	NOT NULL	DATE	Refer to base table.
LAST_UPDATE_LOGIN	NULL	NUMBER	Refer to base table.
PROGRAM_APPLICATION_ID	NULL	NUMBER	Refer to base table.
PROGRAM_ID	NULL	NUMBER	Refer to base table.
PROGRAM_UPDATE_DATE	NULL	DATE	Refer to base table.
REQUEST_ID	NULL	NUMBER	Refer to base table.
CONTEXT	NULL	VARCHAR2(30)	Refer to base table.
ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Refer to base table.
GLOBAL_ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE16	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE17	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE18	NULL	VARCHAR2(240)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

GLOBAL_ATTRIBUTE19		NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE20		NULL	VARCHAR2(240)	Refer to base table.
CANCELLED_FLAG		NULL	VARCHAR2(1)	Refer to base table.
OPEN_FLAG	NOT	NULL	VARCHAR2(1)	Refer to base table.
BOOKED_FLAG	NOT	NULL	VARCHAR2(1)	Refer to base table.
SALESREP_ID		NULL	NUMBER(15)	Refer to base table.
RETURN_REASON_CODE		NULL	VARCHAR2(30)	Refer to base table.
ORDER_DATE_TYPE_CODE		NULL	VARCHAR2(30)	Refer to base table.
EARLIEST_SCHEDULE_LIMIT		NULL	NUMBER	Refer to base table.
LATEST_SCHEDULE_LIMIT		NULL	NUMBER	Refer to base table.
PAYMENT_TYPE_CODE		NULL	VARCHAR2(30)	Refer to base table.
PAYMENT_AMOUNT		NULL	NUMBER	Refer to base table.
CHECK_NUMBER		NULL	VARCHAR2(50)	Refer to base table.
CREDIT_CARD_CODE		NULL	VARCHAR2(80)	Refer to base table.
CREDIT_CARD HOLDER_NAME		NULL	VARCHAR2(80)	Refer to base table.
CREDIT_CARD_NUMBER		NULL	VARCHAR2(80)	Refer to base table.
CREDIT_CARD_EXPIRATION_DATE		NULL	DATE	Refer to base table.
CREDIT_CARD_APPROVAL_CODE		NULL	VARCHAR2(80)	Refer to base table.
CREDIT_CARD_APPROVAL_DATE		NULL	DATE	Refer to base table.
SALES_CHANNEL_CODE		NULL	VARCHAR2(30)	Refer to base table.
FIRST_ACK_CODE		NULL	VARCHAR2(30)	Refer to base table.
FIRST_ACK_DATE		NULL	DATE	Refer to base table.
LAST_ACK_CODE		NULL	VARCHAR2(30)	Refer to base table.
LAST_ACK_DATE		NULL	DATE	Refer to base table.
ORDER_CATEGORY_CODE	NOT	NULL	VARCHAR2(30)	Refer to base table.
SHIPPING_INSTRUCTIONS		NULL	VARCHAR2(2000)	Refer to base table.
PACKING_INSTRUCTIONS		NULL	VARCHAR2(2000)	Refer to base table.

OE_CRM_ORDER_LINES_V

Compatible view provided for CRM usage only. The view is based on oe_order_lines_all table.

View Definition

```
CREATE VIEW OE_CRM_ORDER_LINES_V
as SELECT
    LINE_ID,
    ORG_ID,
    HEADER_ID,
    LINE_TYPE_ID,
    LINE_NUMBER,
    ORDERED_ITEM,
    REQUEST_DATE,
    PROMISE_DATE,
    SCHEDULE_SHIP_DATE,
    ORDER_QUANTITY_UOM,
    PRICING_QUANTITY,
    PRICING_QUANTITY_UOM,
    CANCELLED_QUANTITY,
    SHIPPED_QUANTITY,
    ORDERED_QUANTITY,
    FULFILLED_QUANTITY,
    SHIPPING_QUANTITY,
    SHIPPING_QUANTITY_UOM,
    DELIVERY_LEAD_TIME,
    TAX_EXEMPT_FLAG,
    TAX_EXEMPT_NUMBER,
    TAX_EXEMPT_REASON_CODE,
    SHIP_FROM_ORG_ID,
    SHIP_TO_ORG_ID,
    INVOICE_TO_ORG_ID,
    DELIVER_TO_ORG_ID,
    SHIP_TO_CONTACT_ID,
    DELIVER_TO_CONTACT_ID,
    INVOICE_TO_CONTACT_ID,
    SOLD_TO_ORG_ID,
    CUST_PO_NUMBER,
    SHIP_TOLERANCE_ABOVE,
    SHIP_TOLERANCE_BELOW,
    DEMAND_BUCKET_TYPE_CODE,
    RLA_SCHEDULE_TYPE_CODE,
    CUSTOMER_DOCK_CODE,
    CUSTOMER_JOB,
    CUSTOMER_PRODUCTION_LINE,
    CUST_MODEL_SERIAL_NUMBER,
    PROJECT_ID,
    TASK_ID,
    INVENTORY_ITEM_ID,
    TAX_DATE,
    TAX_CODE,
    TAX_RATE,
    DEMAND_CLASS_CODE,
    PRICE_LIST_ID,
```

Oracle Proprietary, Confidential Information--Use Restricted by Contract

PRICING_DATE,
 SHIPMENT_NUMBER,
 AGREEMENT_ID,
 SHIPMENT_PRIORITY_CODE,
 SHIPPING_METHOD_CODE,
 FREIGHT_CARRIER_CODE,
 FREIGHT_TERMS_CODE,
 FOB_POINT_CODE,
 TAX_POINT_CODE,
 PAYMENT_TERM_ID,
 INVOICING_RULE_ID,
 ACCOUNTING_RULE_ID,
 SOURCE_DOCUMENT_TYPE_ID,
 ORIG_SYS_DOCUMENT_REF,
 SOURCE_DOCUMENT_ID,
 ORIG_SYS_LINE_REF,
 SOURCE_DOCUMENT_LINE_ID,
 REFERENCE_LINE_ID,
 REFERENCE_TYPE,
 REFERENCE_HEADER_ID,
 ITEM_REVISION,
 UNIT_SELLING_PRICE,
 UNIT_LIST_PRICE,
 TAX_VALUE,
 CONTEXT,
 ATTRIBUTE1,
 ATTRIBUTE2,
 ATTRIBUTE3,
 ATTRIBUTE4,
 ATTRIBUTE5,
 ATTRIBUTE6,
 ATTRIBUTE7,
 ATTRIBUTE8,
 ATTRIBUTE9,
 ATTRIBUTE10,
 ATTRIBUTE11,
 ATTRIBUTE12,
 ATTRIBUTE13,
 ATTRIBUTE14,
 ATTRIBUTE15,
 GLOBAL_ATTRIBUTE_CATEGORY,
 GLOBAL_ATTRIBUTE1,
 GLOBAL_ATTRIBUTE2,
 GLOBAL_ATTRIBUTE3,
 GLOBAL_ATTRIBUTE4,
 GLOBAL_ATTRIBUTE5,
 GLOBAL_ATTRIBUTE6,
 GLOBAL_ATTRIBUTE7,
 GLOBAL_ATTRIBUTE8,
 GLOBAL_ATTRIBUTE9,
 GLOBAL_ATTRIBUTE10,
 GLOBAL_ATTRIBUTE11,
 GLOBAL_ATTRIBUTE12,
 GLOBAL_
 ATTRIBUTE13,
 GLOBAL_ATTRIBUTE14,
 GLOBAL_ATTRIBUTE15,

GLOBAL_ATTRIBUTE16,
 GLOBAL_ATTRIBUTE17,
 GLOBAL_ATTRIBUTE18,
 GLOBAL_ATTRIBUTE19,
 GLOBAL_ATTRIBUTE20,
 PRICING_CONTEXT,
 PRICING_ATTRIBUTE1,
 PRICING_ATTRIBUTE2,
 PRICING_ATTRIBUTE3,
 PRICING_ATTRIBUTE4,
 PRICING_ATTRIBUTE5,
 PRICING_ATTRIBUTE6,
 PRICING_ATTRIBUTE7,
 PRICING_ATTRIBUTE8,
 PRICING_ATTRIBUTE9,
 PRICING_ATTRIBUTE10,
 INDUSTRY_CONTEXT,
 INDUSTRY_ATTRIBUTE1,
 INDUSTRY_ATTRIBUTE2,
 INDUSTRY_ATTRIBUTE3,
 INDUSTRY_ATTRIBUTE4,
 INDUSTRY_ATTRIBUTE5,
 INDUSTRY_ATTRIBUTE6,
 INDUSTRY_ATTRIBUTE7,
 INDUSTRY_ATTRIBUTE8,
 INDUSTRY_ATTRIBUTE9,
 INDUSTRY_ATTRIBUTE10,
 INDUSTRY_ATTRIBUTE11,
 INDUSTRY_ATTRIBUTE13,
 INDUSTRY_ATTRIBUTE12,
 INDUSTRY_ATTRIBUTE14,
 INDUSTRY_ATTRIBUTE15,
 INDUSTRY_ATTRIBUTE16,
 INDUSTRY_ATTRIBUTE17,
 INDUSTRY_ATTRIBUTE18,
 INDUSTRY_ATTRIBUTE19,
 INDUSTRY_ATTRIBUTE20,
 INDUSTRY_ATTRIBUTE21,
 INDUSTRY_ATTRIBUTE22,
 INDUSTRY_ATTRIBUTE23,
 INDUSTRY_ATTRIBUTE24,
 INDUSTRY_ATTRIBUTE25,
 INDUSTRY_ATTRIBUTE26,
 INDUSTRY_ATTRIBUTE27,
 INDUSTRY_ATTRIBUTE28,
 INDUSTRY_ATTRIBUTE29,
 INDUSTRY_ATTRIBUTE30,
 CREATION_DATE,
 CREATED_BY,
 LAST_UPDATE_DATE,
 LAST_UPDATED_BY,
 LAST_UPDATE_LOGIN,
 PROGRAM_APPLICATION_ID,
 PROGRAM_ID,
 PROGRAM_UPDATE_DATE,
 REQUEST_ID,
 CONFIGURATION_ID,

Oracle Proprietary, Confidential Information--Use Restricted by Contract

LINK_TO_LINE_ID,
 COMPONENT_SEQUENCE_ID,
 COMPONENT_CODE,
 CONFIG_DISPLAY_SEQUENCE,
 SORT_ORDER,
 ITEM_TYPE_CODE,
 OPTION_NUMBER,
 OPTION_FLAG,
 DEP_PLAN_REQUIRED_FLAG,
 VISIBLE_DEMAND_FLAG,
 LINE_CATEGORY_CODE,
 ACTUAL_SHIPMENT_DATE,
 CUSTOMER_TRX_LINE_ID,
 RETURN_CONTEXT,
 RETURN_ATTRIBUTE1,
 RETURN_ATTRIBUTE2,
 RETURN_ATTRIBUTE3,
 RETURN_ATTRIBUTE4,
 RETURN_ATTRIBUTE5,
 RETURN_ATTRIBUTE6,
 RETURN_ATTRIBUTE7,
 RETURN_ATTRIBUTE8,
 RETURN_ATTRIBUTE9,
 RETURN_ATTRIBUTE10,
 RETURN_ATTRIBUTE11,
 RETURN_ATTRIBUTE12,
 RETURN_ATTRIBUTE13,
 RETURN_ATTRIBUTE14,
 RETURN_ATTRIBUTE15,
 I
 NTMED_SHIP_TO_ORG_ID,
 INTMED_SHIP_TO_CONTACT_ID,
 ACTUAL_ARRIVAL_DATE,
 ATO_LINE_ID,
 AUTO_SELECTED_QUANTITY,
 COMPONENT_NUMBER,
 EARLIEST_ACCEPTABLE_DATE,
 EXPLOSION_DATE,
 LATEST_ACCEPTABLE_DATE,
 MODEL_GROUP_NUMBER,
 SCHEDULE_ARRIVAL_DATE,
 SHIP_MODEL_COMPLETE_FLAG,
 SCHEDULE_STATUS_CODE,
 SOURCE_TYPE_CODE,
 TOP_MODEL_LINE_ID,
 BOOKED_FLAG,
 CANCELLED_FLAG,
 OPEN_FLAG,
 SALESREP_ID,
 RETURN_REASON_CODE,
 ARRIVAL_SET_ID,
 SHIP_SET_ID,
 INVOICE_INTERFACE_STATUS_CODE,
 SPLIT_FROM_LINE_ID,
 CUST_PRODUCTION_SEQ_NUM,
 AUTHORIZED_TO_SHIP_FLAG,
 VEH_CUS_ITEM_CUM_KEY_ID,

```

OVER_SHIP_REASON_CODE,
OVER_SHIP_RESOLVED_FLAG,
ITEM_IDENTIFIER_TYPE,
COMMITMENT_ID,
SHIPPING_INTERFACED_FLAG,
CREDIT_INVOICE_LINE_ID,
FIRST_ACK_CODE,
FIRST_ACK_DATE,
LAST_ACK_CODE,
LAST_ACK_DATE,
PLANNING_PRIORITY,
CONFIG_HEADER_ID,
CONFIG_REV_NBR,
SOLD_FROM_ORG_ID,
FULFILLED_FLAG,
END_ITEM_UNIT_NUMBER,
SHIPPING_INSTRUCTIONS,
PACKING_INSTRUCTIONS,
INVOICED_QUANTITY,
REFERENCE_CUSTOMER_TRX_LINE_ID,
SERVICE_TXN_REASON_CODE,
SERVICE_TXN_COMMENTS,
SERVICE_DURATION,
SERVICE_START_DATE,
SERVICE_END_DATE,
SERVICE_COTERMINATE_FLAG,
UNIT_LIST_PERCENT,
UNIT_SELLING_PERCENT,
UNIT_PERCENT_BASE_PRICE,
SERVICE_NUMBER,
SERVICE_REFERENCE_TYPE_CODE,
SERVICE_REFERENCE_LINE_ID,
SERVICE_REFERENCE_SYSTEM_ID,
MARKETING_SOURCE_CODE_ID,
FLOW_STATUS_CODE,
MODEL_REMNANT_FLAG,
FULFILLMENT_METHOD_CODE,
ORDERED_ITEM_ID
from OE_ORDER_LINES_ALL
      where NVL(ORG_ID,NVL(TO_NUMBER(DECODE(SUBSTRB(USERENV('CLIENT_INFO'),1,1), ' ',
              NULL, SUBSTRB(USERENV('CLIENT_INFO'),1,10))),-99))
             = NVL(TO_NUMBER(DECODE(SUBSTRB(USERENV('CLIENT_INFO'),1,1), ' ', NULL,
              SUBSTRB(USERENV('CLIENT_INFO'),1,10))),-99)

```

Column Descriptions

Name	Null?	Type	Description
LINE_ID	NOT NULL	NUMBER	Refer to base table.
ORG_ID	NULL	NUMBER	Refer to base table.
HEADER_ID	NOT NULL	NUMBER	Refer to base table.
LINE_TYPE_ID	NOT NULL	NUMBER	Refer to base table.
LINE_NUMBER	NOT NULL	NUMBER	Refer to base table.
ORDERED_ITEM	NULL	VARCHAR2(2000)	Refer to base table.
REQUEST_DATE	NULL	DATE	Refer to base table.
PROMISE_DATE	NULL	DATE	Refer to base table.
SCHEDULE_SHIP_DATE	NULL	DATE	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ORDER_QUANTITY_UOM		NULL	VARCHAR2(3)	Refer to base table.
PRICING_QUANTITY		NULL	NUMBER	Refer to base table.
PRICING_QUANTITY_UOM		NULL	VARCHAR2(3)	Refer to base table.
CANCELLED_QUANTITY		NULL	NUMBER	Refer to base table.
SHIPPED_QUANTITY		NULL	NUMBER	Refer to base table.
ORDERED_QUANTITY		NULL	NUMBER	Refer to base table.
FULFILLED_QUANTITY		NULL	NUMBER	Refer to base table.
SHIPPING_QUANTITY		NULL	NUMBER	Refer to base table.
SHIPPING_QUANTITY_UOM		NULL	VARCHAR2(3)	Refer to base table.
DELIVERY_LEAD_TIME		NULL	NUMBER	Refer to base table.
TAX_EXEMPT_FLAG		NULL	VARCHAR2(1)	Refer to base table.
TAX_EXEMPT_NUMBER		NULL	VARCHAR2(80)	Refer to base table.
TAX_EXEMPT_REASON_CODE		NULL	VARCHAR2(30)	Refer to base table.
SHIP_FROM_ORG_ID		NULL	NUMBER	Refer to base table.
SHIP_TO_ORG_ID		NULL	NUMBER	Refer to base table.
INVOICE_TO_ORG_ID		NULL	NUMBER	Refer to base table.
DELIVER_TO_ORG_ID		NULL	NUMBER	Refer to base table.
SHIP_TO_CONTACT_ID		NULL	NUMBER	Refer to base table.
DELIVER_TO_CONTACT_ID		NULL	NUMBER	Refer to base table.
INVOICE_TO_CONTACT_ID		NULL	NUMBER	Refer to base table.
SOLD_TO_ORG_ID		NULL	NUMBER	Refer to base table.
CUST_PO_NUMBER		NULL	VARCHAR2(50)	Refer to base table.
SHIP_TOLERANCE_ABOVE		NULL	NUMBER	Refer to base table.
SHIP_TOLERANCE_BELOW		NULL	NUMBER	Refer to base table.
DEMAND_BUCKET_TYPE_CODE		NULL	VARCHAR2(30)	Refer to base table.
RLA_SCHEDULE_TYPE_CODE		NULL	VARCHAR2(30)	Refer to base table.
CUSTOMER_DOCK_CODE		NULL	VARCHAR2(50)	Refer to base table.
CUSTOMER_JOB		NULL	VARCHAR2(50)	Refer to base table.
CUSTOMER_PRODUCTION_LINE		NULL	VARCHAR2(50)	Refer to base table.
CUST_MODEL_SERIAL_NUMBER		NULL	VARCHAR2(50)	Refer to base table.
PROJECT_ID		NULL	NUMBER	Refer to base table.
TASK_ID		NULL	NUMBER	Refer to base table.
INVENTORY_ITEM_ID	NOT	NULL	NUMBER	Refer to base table.
TAX_DATE		NULL	DATE	Refer to base table.
TAX_CODE		NULL	VARCHAR2(50)	Refer to base table.
TAX_RATE		NULL	NUMBER	Refer to base table.
DEMAND_CLASS_CODE		NULL	VARCHAR2(30)	Refer to base table.
PRICE_LIST_ID		NULL	NUMBER	Refer to base table.
PRICING_DATE		NULL	DATE	Refer to base table.
SHIPMENT_NUMBER	NOT	NULL	NUMBER	Refer to base table.
AGREEMENT_ID		NULL	NUMBER	Refer to base table.
SHIPMENT_PRIORITY_CODE		NULL	VARCHAR2(30)	Refer to base table.
SHIPPING_METHOD_CODE		NULL	VARCHAR2(30)	Refer to base table.
FREIGHT_CARRIER_CODE		NULL	VARCHAR2(30)	Refer to base table.
FREIGHT_TERMS_CODE		NULL	VARCHAR2(30)	Refer to base table.
FOB_POINT_CODE		NULL	VARCHAR2(30)	Refer to base table.
TAX_POINT_CODE		NULL	VARCHAR2(30)	Refer to base table.
PAYMENT_TERM_ID		NULL	NUMBER(15)	Refer to base table.
INVOICING_RULE_ID		NULL	NUMBER(15)	Refer to base table.
ACCOUNTING_RULE_ID		NULL	NUMBER(15)	Refer to base table.
SOURCE_DOCUMENT_TYPE_ID		NULL	NUMBER	Refer to base table.
ORIG_SYS_DOCUMENT_REF		NULL	VARCHAR2(50)	Refer to base table.
SOURCE_DOCUMENT_ID		NULL	NUMBER	Refer to base table.
ORIG_SYS_LINE_REF		NULL	VARCHAR2(50)	Refer to base table.
SOURCE_DOCUMENT_LINE_ID		NULL	NUMBER	Refer to base table.
REFERENCE_LINE_ID		NULL	NUMBER	Refer to base table.
REFERENCE_TYPE		NULL	VARCHAR2(30)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

REFERENCE_HEADER_ID	NULL	NUMBER	Refer to base table.
ITEM_REVISION	NULL	VARCHAR2(3)	Refer to base table.
UNIT_SELLING_PRICE	NULL	NUMBER	Refer to base table.
UNIT_LIST_PRICE	NULL	NUMBER	Refer to base table.
TAX_VALUE	NULL	NUMBER	Refer to base table.
CONTEXT	NULL	VARCHAR2(30)	Refer to base table.
ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Refer to base table.
GLOBAL_ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE16	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE17	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE18	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE19	NULL	VARCHAR2(240)	Refer to base table.
GLOBAL_ATTRIBUTE20	NULL	VARCHAR2(240)	Refer to base table.
PRICING_CONTEXT	NULL	VARCHAR2(30)	Refer to base table.
PRICING_ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
PRICING_ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
PRICING_ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
PRICING_ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
PRICING_ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
PRICING_ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
PRICING_ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
PRICING_ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
PRICING_ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
PRICING_ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_CONTEXT	NULL	VARCHAR2(30)	Refer to base table.
INDUSTRY_ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

INDUSTRY_ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE16	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE17	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE18	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE19	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE20	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE21	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE22	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE23	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE24	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE25	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE26	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE27	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE28	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE29	NULL	VARCHAR2(240)	Refer to base table.
INDUSTRY_ATTRIBUTE30	NULL	VARCHAR2(240)	Refer to base table.
CREATION_DATE	NOT NULL	DATE	Refer to base table.
CREATED_BY	NOT NULL	NUMBER	Refer to base table.
LAST_UPDATE_DATE	NOT NULL	DATE	Refer to base table.
LAST_UPDATED_BY	NOT NULL	NUMBER	Refer to base table.
LAST_UPDATE_LOGIN	NULL	NUMBER	Refer to base table.
PROGRAM_APPLICATION_ID	NULL	NUMBER	Refer to base table.
PROGRAM_ID	NULL	NUMBER	Refer to base table.
PROGRAM_UPDATE_DATE	NULL	DATE	Refer to base table.
REQUEST_ID	NULL	NUMBER	Refer to base table.
CONFIGURATION_ID	NULL	NUMBER	Refer to base table.
LINK_TO_LINE_ID	NULL	NUMBER	Refer to base table.
COMPONENT_SEQUENCE_ID	NULL	NUMBER	Refer to base table.
COMPONENT_CODE	NULL	VARCHAR2(1000)	Refer to base table.
CONFIG_DISPLAY_SEQUENCE	NULL	NUMBER	Refer to base table.
SORT_ORDER	NULL	VARCHAR2(240)	Refer to base table.
ITEM_TYPE_CODE	NULL	VARCHAR2(30)	Refer to base table.
OPTION_NUMBER	NULL	NUMBER	Refer to base table.
OPTION_FLAG	NULL	VARCHAR2(1)	Refer to base table.
DEP_PLAN_REQUIRED_FLAG	NULL	VARCHAR2(1)	Refer to base table.
VISIBLE_DEMAND_FLAG	NULL	VARCHAR2(1)	Refer to base table.
LINE_CATEGORY_CODE	NOT NULL	VARCHAR2(30)	Refer to base table.
ACTUAL_SHIPMENT_DATE	NULL	DATE	Refer to base table.
CUSTOMER_TRX_LINE_ID	NULL	NUMBER	Refer to base table.
RETURN_CONTEXT	NULL	VARCHAR2(30)	Refer to base table.
RETURN_ATTRIBUTE1	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE2	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE3	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE4	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE5	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE6	NULL	VARCHAR2(240)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

RETURN_ATTRIBUTE7	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE8	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE9	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE10	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE11	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE12	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE13	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE14	NULL	VARCHAR2(240)	Refer to base table.
RETURN_ATTRIBUTE15	NULL	VARCHAR2(240)	Refer to base table.
INTMED_SHIP_TO_ORG_ID	NULL	NUMBER	Refer to base table.
INTMED_SHIP_TO_CONTACT_ID	NULL	NUMBER	Refer to base table.
ACTUAL_ARRIVAL_DATE	NULL	DATE	Refer to base table.
ATO_LINE_ID	NULL	NUMBER	Refer to base table.
AUTO_SELECTED_QUANTITY	NULL	NUMBER	Refer to base table.
COMPONENT_NUMBER	NULL	NUMBER	Refer to base table.
EARLIEST_ACCEPTABLE_DATE	NULL	DATE	Refer to base table.
EXPLOSION_DATE	NULL	DATE	Refer to base table.
LATEST_ACCEPTABLE_DATE	NULL	DATE	Refer to base table.
MODEL_GROUP_NUMBER	NULL	NUMBER	Refer to base table.
SCHEDULE_ARRIVAL_DATE	NULL	DATE	Refer to base table.
SHIP_MODEL_COMPLETE_FLAG	NULL	VARCHAR2(1)	Refer to base table.
SCHEDULE_STATUS_CODE	NULL	VARCHAR2(30)	Refer to base table.
SOURCE_TYPE_CODE	NULL	VARCHAR2(30)	Refer to base table.
TOP_MODEL_LINE_ID	NULL	NUMBER	Refer to base table.
BOOKED_FLAG	NOT NULL	VARCHAR2(1)	Refer to base table.
CANCELLED_FLAG	NULL	VARCHAR2(1)	Refer to base table.
OPEN_FLAG	NOT NULL	VARCHAR2(1)	Refer to base table.
SALESREP_ID	NULL	NUMBER(15)	Refer to base table.
RETURN_REASON_CODE	NULL	VARCHAR2(30)	Refer to base table.
ARRIVAL_SET_ID	NULL	NUMBER	Refer to base table.
SHIP_SET_ID	NULL	NUMBER	Refer to base table.
INVOICE_INTERFACE_STATUS_CODE	NULL	VARCHAR2(30)	Refer to base table.
SPLIT_FROM_LINE_ID	NULL	NUMBER	Refer to base table.
CUST_PRODUCTION_SEQ_NUM	NULL	VARCHAR2(50)	Refer to base table.
AUTHORIZED_TO_SHIP_FLAG	NULL	VARCHAR2(1)	Refer to base table.
VEH_CUS_ITEM_CUM_KEY_ID	NULL	NUMBER	Refer to base table.
OVER_SHIP_REASON_CODE	NULL	VARCHAR2(30)	Refer to base table.
OVER_SHIP_RESOLVED_FLAG	NULL	VARCHAR2(1)	Refer to base table.
ITEM_IDENTIFIER_TYPE	NULL	VARCHAR2(30)	Refer to base table.
COMMITMENT_ID	NULL	NUMBER	Refer to base table.
SHIPPING_INTERFACED_FLAG	NULL	VARCHAR2(1)	Refer to base table.
CREDIT_INVOICE_LINE_ID	NULL	NUMBER	Refer to base table.
FIRST_ACK_CODE	NULL	VARCHAR2(30)	Refer to base table.
FIRST_ACK_DATE	NULL	DATE	Refer to base table.
LAST_ACK_CODE	NULL	VARCHAR2(30)	Refer to base table.
LAST_ACK_DATE	NULL	DATE	Refer to base table.
PLANNING_PRIORITY	NULL	NUMBER	Refer to base table.
CONFIG_HEADER_ID	NULL	NUMBER	Refer to base table.
CONFIG_REV_NBR	NULL	NUMBER	Refer to base table.
SOLD_FROM_ORG_ID	NULL	NUMBER	Refer to base table.
FULFILLED_FLAG	NULL	VARCHAR2(1)	Refer to base table.
END_ITEM_UNIT_NUMBER	NULL	VARCHAR2(30)	Refer to base table.
SHIPPING_INSTRUCTIONS	NULL	VARCHAR2(2000)	Refer to base table.
PACKING_INSTRUCTIONS	NULL	VARCHAR2(2000)	Refer to base table.
INVOICED_QUANTITY	NULL	NUMBER	Refer to base table.
REFERENCE_CUSTOMER_TRX_LINE_ID	NULL	NUMBER	Refer to base table.
SERVICE_TXN_REASON_CODE	NULL	VARCHAR2(30)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SERVICE_TXN_COMMENTS	NULL	VARCHAR2(2000)	Refer to base table.
SERVICE_DURATION	NULL	NUMBER	Refer to base table.
SERVICE_START_DATE	NULL	DATE	Refer to base table.
SERVICE_END_DATE	NULL	DATE	Refer to base table.
SERVICE_COTERMINATE_FLAG	NULL	VARCHAR2(1)	Refer to base table.
UNIT_LIST_PERCENT	NULL	NUMBER	Refer to base table.
UNIT_SELLING_PERCENT	NULL	NUMBER	Refer to base table.
UNIT_PERCENT_BASE_PRICE	NULL	NUMBER	Refer to base table.
SERVICE_NUMBER	NULL	NUMBER	Refer to base table.
SERVICE_REFERENCE_TYPE_CODE	NULL	VARCHAR2(30)	Refer to base table.
SERVICE_REFERENCE_LINE_ID	NULL	NUMBER	Refer to base table.
SERVICE_REFERENCE_SYSTEM_ID	NULL	NUMBER	Refer to base table.
MARKETING_SOURCE_CODE_ID	NULL	NUMBER	Refer to base table.
FLOW_STATUS_CODE	NULL	VARCHAR2(30)	Refer to base table.
MODEL_REMNANT_FLAG	NULL	VARCHAR2(1)	Refer to base table.
FULFILLMENT_METHOD_CODE	NULL	VARCHAR2(30)	Refer to base table.
ORDERED_ITEM_ID	NULL	NUMBER	Refer to base table.

OE_CRM_SALES_CREDITS_V

Compatible view provided for CRM usage only. The view is based on oe_sales_credits and ra_salesreps.

View Definition

```
CREATE VIEW OE_CRM_SALES_CREDITS_V
as SELECT
    SSC.ROWID ROW_ID ,
    SSC.SALES_CREDIT_ID ,
    RS.NAME salesrep ,
    SSC.SALES_CREDIT_TYPE_ID,
    SSC.PERCENT PERCENT ,
    SSC.HEADER_ID ,
    SSC.LINE_ID ,
    SSC.SALESREP_ID ,
    SSC.CREATION_DATE ,
    SSC.CREATED_BY ,
    SSC.LAST_UPDATE_DATE ,
    SSC.LAST_UPDATED_BY ,
    SSC.LAST_UPDATE_LOGIN ,
    SSC.CONTEXT ,
    SSC.ATTRIBUTE1 ,
    SSC.ATTRIBUTE2 ,
    SSC.ATTRIBUTE3 ,
    SSC.ATTRIBUTE4 ,
    SSC.ATTRIBUTE5 ,
    SSC.ATTRIBUTE6 ,
    SSC.ATTRIBUTE7 ,
    SSC.ATTRIBUTE8 ,
    SSC.ATTRIBUTE9 ,
    SSC.ATTRIBUTE10 ,
    SSC.ATTRIBUTE11 ,
    SSC.ATTRIBUTE12 ,
    SSC.ATTRIBUTE13 ,
    SSC.ATTRIBUTE14 ,
    SSC.ATTRIBUTE15,
    SSC.DW_UPDATE_ADVICE_FLAG,
    SSC.WH_UPDATE_DATE
FROM OE_SALES_CREDITS SSC
    , RA_SALESREPS RS
Where RS.SALESREP_ID = SSC.SALESREP_ID
```

Column Descriptions

Name	Null?	Type	Description
ROW_ID	NULL	ROWID	Refer to base table.
SALES_CREDIT_ID	NOT NULL	NUMBER	Refer to base table.
SALESREP	NULL	VARCHAR2(240)	Refer to base table.
SALES_CREDIT_TYPE_ID	NULL	NUMBER	Refer to base table.
PERCENT	NOT NULL	NUMBER	Refer to base table.
HEADER_ID	NOT NULL	NUMBER	Refer to base table.
LINE_ID	NULL	NUMBER	Refer to base table.
SALESREP_ID	NOT NULL	NUMBER(15)	Refer to base table.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CREATION_DATE	NOT NULL	DATE	Refer to base table.
CREATED_BY	NOT NULL	NUMBER	Refer to base table.
LAST_UPDATE_DATE	NOT NULL	DATE	Refer to base table.
LAST_UPDATED_BY	NOT NULL	NUMBER	Refer to base table.
LAST_UPDATE_LOGIN		NUMBER	Refer to base table.
CONTEXT		VARCHAR2(30)	Refer to base table.
ATTRIBUTE1		VARCHAR2(240)	Refer to base table.
ATTRIBUTE2		VARCHAR2(240)	Refer to base table.
ATTRIBUTE3		VARCHAR2(240)	Refer to base table.
ATTRIBUTE4		VARCHAR2(240)	Refer to base table.
ATTRIBUTE5		VARCHAR2(240)	Refer to base table.
ATTRIBUTE6		VARCHAR2(240)	Refer to base table.
ATTRIBUTE7		VARCHAR2(240)	Refer to base table.
ATTRIBUTE8		VARCHAR2(240)	Refer to base table.
ATTRIBUTE9		VARCHAR2(240)	Refer to base table.
ATTRIBUTE10		VARCHAR2(240)	Refer to base table.
ATTRIBUTE11		VARCHAR2(240)	Refer to base table.
ATTRIBUTE12		VARCHAR2(240)	Refer to base table.
ATTRIBUTE13		VARCHAR2(240)	Refer to base table.
ATTRIBUTE14		VARCHAR2(240)	Refer to base table.
ATTRIBUTE15		VARCHAR2(240)	Refer to base table.
DW_UPDATE_ADVICE_FLAG		VARCHAR2(1)	Refer to base table.
WH_UPDATE_DATE		DATE	Refer to base table.

OE_ORDER_HEADERS_ALL

OE_ORDER_HEADERS_ALL stores header information for orders in Order Management.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
FND_APPLICATION	APPLICATION_ID	PROGRAM_APPLICATION_ID
HR_ALL_ORGANIZATION_UNITS	ORGANIZATION_ID	SHIP_FROM_ORG_ID
HR_ALL_ORGANIZATION_UNITS	ORGANIZATION_ID	SOLD_FROM_ORG_ID
OE_AGREEMENTS_B	AGREEMENT_ID	AGREEMENT_ID
OE_ORDER_HEADERS_ALL	SOURCE_DOCUMENT_ID	HEADER_ID
OE_ORDER_SOURCES	ORDER_SOURCE_ID	ORDER_SOURCE_ID
OE_ORDER_SOURCES	ORDER_SOURCE_ID	SOURCE_DOCUMENT_TYPE_ID
OE_TRANSACTION_TYPES_ALL	TRANSACTION_TYPE_ID	ORDER_TYPE_ID
QP_LIST_HEADERS_B	LIST_HEADER_ID	PRICE_LIST_ID
RA_CONTACTS_	CONTACT_ID	DELIVER_TO_CONTACT_ID
RA_CONTACTS_	CONTACT_ID	INVOICE_TO_CONTACT_ID
RA_CONTACTS_	CONTACT_ID	SHIP_TO_CONTACT_ID
RA_CONTACTS_	CONTACT_ID	SOLD_TO_CONTACT_ID
RA_CUSTOMERS_	CUSTOMER_ID	SOLD_TO_ORG_ID
RA_RULES	RULE_ID	INVOICING_RULE_ID
RA_RULES	RULE_ID	ACCOUNTING_RULE_ID
RA_SALESREPS_ALL	SALESREP_ID	SALESREP_ID
RA_SITE_USES_ALL	SITE_USE_ID	DELIVER_TO_ORG_ID
RA_SITE_USES_ALL	SITE_USE_ID	INVOICE_TO_ORG_ID
RA_SITE_USES_ALL	SITE_USE_ID	SHIP_TO_ORG_ID
RA_TERMS_B	TERM_ID	PAYMENT_TERM_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
FOB_POINT_CODE	FOB	AR_LOOKUPS
	BUY	Buyer
	CUSTOMER SITE	Customer Site
	FACTORY	Factory
	LOAD	Loading Dock
	SEL	Seller
	SHIP POINT	Shipping Point
BOOKED_FLAG	YES_NO	FND_LOOKUPS
	N	No
	Y	Yes
CANCELLED_FLAG	YES_NO	FND_LOOKUPS
	N	No
	Y	Yes
FREIGHT_TERMS_CODE	FREIGHT_TERMS	OE_LOOKUPS
OPEN_FLAG	YES_NO	FND_LOOKUPS
	N	No
	Y	Yes
ORDER_CATEGORY_CODE	ORDER_CATEGORY	OE_LOOKUPS
	MIXED	Mixed
	ORDER	Order

Oracle Proprietary, Confidential Information--Use Restricted by Contract

	RETURN	Return
SALES_CHANNEL_CODE	SALES_CHANNEL	OE_LOOKUPS

Column Descriptions

Name	Null?	Type	Description
HEADER_ID (PK)	NOT NULL	NUMBER	Order Header Identifier
ORG_ID	NULL	NUMBER	Operating Unit which performed this transaction
ORDER_TYPE_ID	NOT NULL	NUMBER	Order Transaction Type Identifier
ORDER_NUMBER	NOT NULL	NUMBER	User-visible number of the order
VERSION_NUMBER	NOT NULL	NUMBER	Not Used
EXPIRATION_DATE	NULL	DATE	Not Used
ORDER_SOURCE_ID	NULL	NUMBER	Source of the order
SOURCE_DOCUMENT_TYPE_ID	NULL	NUMBER	Indicates the source of the order
ORIG_SYS_DOCUMENT_REF	NULL	VARCHAR2(50)	Original document reference for the order in external system
SOURCE_DOCUMENT_ID	NULL	NUMBER	Source Order Header Identifier
ORDERED_DATE	NULL	DATE	Ordered Date
REQUEST_DATE	NULL	DATE	Request date for the order
PRICING_DATE	NULL	DATE	Determines effective list and price modifiers
SHIPMENT_PRIORITY_CODE	NULL	VARCHAR2(30)	Shipment Priority Code
DEMAND_CLASS_CODE	NULL	VARCHAR2(30)	Demand Class
PRICE_LIST_ID	NULL	NUMBER	Price list Identification for the order
TAX_EXEMPT_FLAG	NULL	VARCHAR2(1)	It will decide the tax handling for the order. Possible values can be S - Standard, E - Exempt, R - Required
TAX_EXEMPT_NUMBER	NULL	VARCHAR2(80)	The Tax exemption Number
TAX_EXEMPT_REASON_CODE	NULL	VARCHAR2(30)	The reason code for Tax exemption
CONVERSION_RATE	NULL	NUMBER	Rate of the currency conversion
CONVERSION_TYPE_CODE	NULL	VARCHAR2(30)	Currency Conversion type
CONVERSION_RATE_DATE	NULL	DATE	Date of the currency conversion
PARTIAL_SHIPMENTS_ALLOWED	NULL	VARCHAR2(1)	Not Used
SHIP_TOLERANCE_ABOVE	NULL	NUMBER	Over Shipment/Return Tolerance
SHIP_TOLERANCE_BELOW	NULL	NUMBER	Under Shipment/Return Tolerance
TRANSACTIONAL_CURR_CODE	NULL	VARCHAR2(15)	Currency for the order
AGREEMENT_ID	NULL	NUMBER	Internal use only
TAX_POINT_CODE	NULL	VARCHAR2(30)	For future use
CUST_PO_NUMBER	NULL	VARCHAR2(50)	Customer Purchase Order Number
INVOICING_RULE_ID	NULL	NUMBER(15)	Invoicing rule used by AR for generating Invoice
ACCOUNTING_RULE_ID	NULL	NUMBER(15)	Accounting rule used by AR for generating Invoice
PAYMENT_TERM_ID	NULL	NUMBER(15)	Payment Terms
SHIPPING_METHOD_CODE	NULL	VARCHAR2(30)	Shipping method to be used to ship the order
FREIGHT_CARRIER_CODE	NULL	VARCHAR2(30)	Freight Carrier Code
FOB_POINT_CODE	NULL	VARCHAR2(30)	FOB Point Code
FREIGHT_TERMS_CODE	NULL	VARCHAR2(30)	Freight Terms Code
SOLD_FROM_ORG_ID	NULL	NUMBER	Selling Organization
SOLD_TO_ORG_ID	NULL	NUMBER	Sold to customer
SHIP_FROM_ORG_ID	NULL	NUMBER	Ship From Organization Id - Warehouse

Oracle Proprietary, Confidential Information--Use Restricted by Contract

SHIP_TO_ORG_ID	NULL	NUMBER	Ship to Organization Id
INVOICE_TO_ORG_ID	NULL	NUMBER	Invoice To Organization ID
DELIVER_TO_ORG_ID	NULL	NUMBER	Deliver to Organization Id
SOLD_TO_CONTACT_ID	NULL	NUMBER	Customer contact
SHIP_TO_CONTACT_ID	NULL	NUMBER	Ship to Contact Id
INVOICE_TO_CONTACT_ID	NULL	NUMBER	Invoice To Contact ID
DELIVER_TO_CONTACT_ID	NULL	NUMBER	Deliver to Contact Id
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application of concurrent program that last updated row.
PROGRAM_ID	NULL	NUMBER	Concurrent program that last updated row.
PROGRAM_UPDATE_DATE	NULL	DATE	Last date changed by concurrent program
REQUEST_ID	NULL	NUMBER	Concurrent request that last changed row
CONTEXT	NULL	VARCHAR2(30)	Descriptive Flexfield segment
ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE5	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(240)	Descriptive Flexfield segment
GLOBAL_ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE1	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE2	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE3	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE4	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE5	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE6	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE7	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE8	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE9	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE10	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE11	NULL	VARCHAR2(240)	Reserved for country-specific functionality.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

GLOBAL_ATTRIBUTE12	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE13	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE14	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE15	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE16	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE17	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE18	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE19	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE20	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
CANCELLED_FLAG	NULL	VARCHAR2(1)	Cancelled Flag
OPEN_FLAG	NOT NULL	VARCHAR2(1)	Indicates whether the order has been closed ('N') or not ('Y')
BOOKED_FLAG	NOT NULL	VARCHAR2(1)	Indicates whether order is booked ('Y') or not ('N')
SALESREP_ID	NULL	NUMBER(15)	Sales representative Identification
RETURN_REASON_CODE	NULL	VARCHAR2(30)	This column stores return reason code for a return order, and is for defaulting to a return line
ORDER_DATE_TYPE_CODE	NULL	VARCHAR2(30)	Order Date Type Code
EARLIEST_SCHEDULE_LIMIT	NULL	NUMBER	Limit in number of days earlier than the requested date when the item can be shipped
LATEST_SCHEDULE_LIMIT	NULL	NUMBER	Limit in number of days later than the requested date when the item can be shipped
PAYMENT_TYPE_CODE	NULL	VARCHAR2(30)	Stores type of payment for orders (cash, check, credit)
PAYMENT_AMOUNT	NULL	NUMBER	Stores amount of payment
CHECK_NUMBER	NULL	VARCHAR2(50)	Stores check number if payment type is Check
CREDIT_CARD_CODE	NULL	VARCHAR2(80)	Stores credit card name if payment type is Credit Card
CREDIT_CARD HOLDER_NAME	NULL	VARCHAR2(80)	Stores credit card holder name if payment type is Credit Card
CREDIT_CARD_NUMBER	NULL	VARCHAR2(80)	Stores credit card number if payment type is Credit Card
CREDIT_CARD_EXPIRATION_DATE	NULL	DATE	Stores credit card expiration date if payment type is Credit Card
CREDIT_CARD_APPROVAL_CODE	NULL	VARCHAR2(80)	Stores credit card approval code if payment type is Credit Card
SALES_CHANNEL_CODE	NULL	VARCHAR2(30)	Sales channel through which order was placed
FIRST_ACK_CODE	NULL	VARCHAR2(30)	Initial acknowledgment code for outbound EDI transaction
FIRST_ACK_DATE	NULL	DATE	Initial acknowledgment date for outbound EDI transaction
LAST_ACK_CODE	NULL	VARCHAR2(30)	Latest acknowledgment code for outbound EDI transaction
LAST_ACK_DATE	NULL	DATE	Latest acknowledgment date for outbound EDI transaction
ORDER_CATEGORY_CODE	NOT NULL	VARCHAR2(30)	Order Category Code

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CHANGE_SEQUENCE	NULL	VARCHAR2(50)	It is sequence number in which changes will be applied. It will make sure that later changes are not over-written by previous order change.
DROP_SHIP_FLAG	NULL	VARCHAR2(1)	Not Used
CUSTOMER_PAYMENT_TERM_ID	NULL	NUMBER	Not Used
SHIPPING_INSTRUCTIONS	NULL	VARCHAR2(2000)	Shipping Instructions for Order
PACKING_INSTRUCTIONS	NULL	VARCHAR2(2000)	Packing Instructions for Order
TP_CONTEXT	NULL	VARCHAR2(30)	Descriptive Flexfield segment
TP_ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE2	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE3	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE4	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE5	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE6	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE7	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE8	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE9	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE10	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE11	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE12	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE13	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE14	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE15	NULL	VARCHAR2(240)	Descriptive Flexfield segment
FLOW_STATUS_CODE	NULL	VARCHAR2(30)	Workflow status for the header
MARKETING_SOURCE_CODE_ID	NULL	NUMBER	Marketing Source Code Identifier, Foreign key reference to AMS_SOURCE_CODES
CREDIT_CARD_APPROVAL_DATE	NULL	DATE	The date on which credit card authorization was taken.
UPGRADED_FLAG	NULL	VARCHAR2(1)	Denotes if this line is upgraded into R11i or newly created in R11i version.
CUSTOMER_PREFERENCE_SET_CODE	NULL	VARCHAR2(30)	Indicates whether items on the order must ship/arrive together
BOOKED_DATE	NULL	DATE	Indicates the date when the order was booked
LOCK_CONTROL	NULL	NUMBER	

Indexes

Index Name	Index Type	Sequence	Column Name
OE_ORDER_HEADERS_N1	NOT UNIQUE	1	ORDER_NUMBER
		2	ORDER_TYPE_ID
OE_ORDER_HEADERS_N2	NOT UNIQUE	1	SOLD_TO_ORG_ID
OE_ORDER_HEADERS_N3	NOT UNIQUE	1	SHIP_TO_ORG_ID
OE_ORDER_HEADERS_N4	NOT UNIQUE	1	INVOICE_TO_ORG_ID
OE_ORDER_HEADERS_N5	NOT UNIQUE	1	CUST_PO_NUMBER
OE_ORDER_HEADERS_N6	NOT UNIQUE	2	ORDER_TYPE_ID
		2	ORIG_SYS_DOCUMENT_REF
OE_ORDER_HEADERS_N7	NOT UNIQUE	4	ORDER_SOURCE_ID
		2	OPEN_FLAG
OE_ORDER_HEADERS_N8	NOT UNIQUE	2	OPEN_FLAG
OE_ORDER_HEADERS_U1	UNIQUE	1	HEADER_ID
OE_ORDER_HEADERS_U2	UNIQUE	1	ORDER_NUMBER
		2	ORDER_TYPE_ID
		4	VERSION_NUMBER

Oracle Proprietary, Confidential Information--Use Restricted by Contract

Sequences

Sequence	Derived Column
OE_ORDER_HEADERS_S	HEADER_ID

OE_ORDER_LINES_ALL

OE_ORDER_LINES_ALL stores information for all order lines in Oracle Order Management.

Foreign Keys

Primary Key Table	Primary Key Column	Foreign Key Column
BOM_INVENTORY_COMPONENTS	COMPONENT_SEQUENCE_ID	COMPONENT_SEQUENCE_ID
FND_APPLICATION	APPLICATION_ID	PROGRAM_APPLICATION_ID
HR_ALL_ORGANIZATION_UNITS	ORGANIZATION_ID	SHIP_FROM_ORG_ID
HR_ALL_ORGANIZATION_UNITS	ORGANIZATION_ID	SOLD_FROM_ORG_ID
MTL_CROSS_REFERENCES	CROSS_REFERENCE	ORDERED_ITEM
MTL_CROSS_REFERENCE_TYPES	CROSS_REFERENCE_TYPE	ITEM_IDENTIFIER_TYPE
MTL_CUSTOMER_ITEMS	CUSTOMER_ITEM_ID	ORDERED_ITEM_ID
MTL_SYSTEM_ITEMS_B	INVENTORY_ITEM_ID	INVENTORY_ITEM_ID
OE_AGREEMENTS_B	AGREEMENT_ID	AGREEMENT_ID
OE_ORDER_HEADERS_ALL	HEADER_ID	HEADER_ID
OE_ORDER_HEADERS_ALL	HEADER_ID	SOURCE_DOCUMENT_ID
OE_ORDER_HEADERS_ALL	HEADER_ID	REFERENCE_HEADER_ID
OE_ORDER_LINES_ALL	LINE_ID	SPLIT_FROM_LINE_ID
OE_ORDER_LINES_ALL	LINE_ID	ATO_LINE_ID
OE_ORDER_LINES_ALL	LINE_ID	LINK_TO_LINE_ID
OE_ORDER_LINES_ALL	LINE_ID	TOP_MODEL_LINE_ID
OE_ORDER_LINES_ALL	SOURCE_DOCUMENT_LINE_ID	LINE_ID
OE_ORDER_LINES_ALL	REFERENCE_LINE_ID	LINE_ID
OE_ORDER_SOURCES	ORDER_SOURCE_ID	SOURCE_DOCUMENT_TYPE_ID
OE_SETS	SET_ID	ARRIVAL_SET_ID
OE_SETS	SET_ID	SHIP_SET_ID
OE_SETS	SET_ID	LINE_SET_ID
OE_TRANSACTION_TYPES_ALL	TRANSACTION_TYPE_ID	LINE_TYPE_ID
QP_LIST_HEADERS_B	LIST_HEADER_ID	PRICE_LIST_ID
RA_CONTACTS_	CONTACT_ID	SHIP_TO_CONTACT_ID
RA_CONTACTS_	CONTACT_ID	INVOICE_TO_CONTACT_ID
RA_CONTACTS_	CONTACT_ID	DELIVER_TO_CONTACT_ID
RA_CUSTOMERS_	CUSTOMER_ID	SOLD_TO_ORG_ID
RA_CUSTOMER_TRX_LINES_ALL	CUSTOMER_TRX_LINE_ID	REFERENCE_CUSTOMER_TRX_LINE_ID
RA_RULES	RULE_ID	INVOICING_RULE_ID
RA_RULES	RULE_ID	ACCOUNTING_RULE_ID
RA_SALESREPS_ALL	SALESREP_ID	SALESREP_ID
RA_SITE_USES_ALL	SITE_USE_ID	DELIVER_TO_ORG_ID
RA_SITE_USES_ALL	SITE_USE_ID	INVOICE_TO_ORG_ID
RA_SITE_USES_ALL	SITE_USE_ID	SHIP_TO_ORG_ID
RA_TERMS_B	TERM_ID	PAYMENT_TERM_ID

QuickCodes Columns

Column	QuickCodes Type	QuickCodes Table
FOB_POINT_CODE	FOB	AR_LOOKUPS
	BUY	Buyer
	CUSTOMER SITE	Customer Site
	FACTORY	Factory
	LOAD	Loading Dock
	SEL	Seller
	SHIP POINT	Shipping Point
	User defined	

Oracle Proprietary, Confidential Information--Use Restricted by Contract

BOOKED_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
CANCELLED_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
DEP_PLAN_REQUIRED_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
FREIGHT_TERMS_CODE	FREIGHT_TERMS	OE_LOOKUPS
FULFILLED_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
ITEM_TYPE_CODE	ITEM TYPE CLASS CONFIG INCLUDED KIT MODEL OPTION SERVICE STANDARD	OE_LOOKUPS Class Config_Item Included_Item Kit Model Option Service Standard
MODEL_REMNANT_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
OPEN_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
OVER_SHIP_RESOLVED_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
SHIPMENT_PRIORITY_CODE	SHIPMENT_PRIORITY	OE_LOOKUPS
SHIPABLE_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
SHIPPING_INTERFACED_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
SHIP_MODEL_COMPLETE_FLAG	YES_NO N Y	FND_LOOKUPS No Yes
SOURCE_TYPE_CODE	SOURCE TYPE EXTERNAL INTERNAL	OE_LOOKUPS External Internal

Column Descriptions

Name	Null?	Type	Description
LINE_ID (PK)	NOT NULL	NUMBER	System Generated Line Identifier.
ORG_ID	NULL	NUMBER	Operating Unit which performed this transaction.

HEADER_ID	NOT NULL	NUMBER	Foreign key reference to OE_ORDER_HEADERS_ALL; the order to which this line belongs.
LINE_TYPE_ID	NOT NULL	NUMBER	Line Transaction Type Identifier
LINE_NUMBER	NOT NULL	NUMBER	Line sequence number within the order
ORDERED_ITEM		NULL VARCHAR2(2000)	Stores name of Ordered Item
REQUEST_DATE		NULL DATE	Ordered Item Request date
PROMISE_DATE		NULL DATE	Date promised to customer to receive item
SCHEDULE_SHIP_DATE		NULL DATE	Date Scheduled to ship item
ORDER_QUANTITY_UOM		NULL VARCHAR2(3)	Ordered quantity Unit of measure
PRICING_QUANTITY		NULL NUMBER	Quantity based on pricing unit of measure
PRICING_QUANTITY_UOM		NULL VARCHAR2(3)	Unit of measure used for pricing
CANCELLED_QUANTITY		NULL NUMBER	Cancelled Quantity
SHIPPED_QUANTITY		NULL NUMBER	Shipped Quantity
ORDERED_QUANTITY		NULL NUMBER	Quantity Ordered
FULFILLED_QUANTITY		NULL NUMBER	Fulfilled Quantity
SHIPPING_QUANTITY		NULL NUMBER	Shipping Quantity
SHIPPING_QUANTITY_UOM		NULL VARCHAR2(3)	Shipping Quantity UOM
DELIVERY_LEAD_TIME		NULL NUMBER	Deliver Lead time
TAX_EXEMPT_FLAG		NULL VARCHAR2(1)	It will decide the tax handling for the order line. Possible values can be S - Standard, E - Exempt, R - Required
TAX_EXEMPT_NUMBER		NULL VARCHAR2(80)	The Tax exemption Number
TAX_EXEMPT_REASON_CODE		NULL VARCHAR2(30)	The reason code for Tax exemption
SHIP_FROM_ORG_ID		NULL NUMBER	Ship from organization id -warehouse
SHIP_TO_ORG_ID		NULL NUMBER	Ship to Organization Id
INVOICE_TO_ORG_ID		NULL NUMBER	Invoice To Organization ID
DELIVER_TO_ORG_ID		NULL NUMBER	Deliver to Organization Id
SHIP_TO_CONTACT_ID		NULL NUMBER	Person to which line is to be shipped
DELIVER_TO_CONTACT_ID		NULL NUMBER	Deliver to Contact Id
INVOICE_TO_CONTACT_ID		NULL NUMBER	Invoice To Contact ID
INTMED_SHIP_TO_ORG_ID		NULL NUMBER	Intermediate ship to organization id for the line
INTMED_SHIP_TO_CONTACT_ID		NULL NUMBER	Intermediate ship to contact id for the Line
SOLD_FROM_ORG_ID		NULL NUMBER	Selling organization
SOLD_TO_ORG_ID		NULL NUMBER	Customer to whom the item is sold to
CUST_PO_NUMBER		NULL VARCHAR2(50)	Customer Purchase Order Number
SHIP_TOLERANCE_ABOVE		NULL NUMBER	Over Shipment/Return Tolerance
SHIP_TOLERANCE_BELOW		NULL NUMBER	Under Shipment/Return Tolerance
DEMAND_BUCKET_TYPE_CODE		NULL VARCHAR2(30)	Bucket Type designator (e.g, discrete, weekly, monthly) associated with the order line.
VEH_CUS_ITEM_CUM_KEY_ID		NULL NUMBER	Customer Item cum key unique identifier. Updated at the time of shipment.
RLA_SCHEDULE_TYPE_CODE		NULL VARCHAR2(30)	Source to determine replacement eligibility and hierarchy for the netting logic.
CUSTOMER_DOCK_CODE		NULL VARCHAR2(50)	Doc code
CUSTOMER_JOB		NULL VARCHAR2(50)	Customer Job number

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CUSTOMER_PRODUCTION_LINE	NULL	VARCHAR2(50)	Customer Production Line
CUST_MODEL_SERIAL_NUMBER	NULL	VARCHAR2(50)	Vehicle Id Number (VIN)
PROJECT_ID	NULL	NUMBER	Project associated with this transaction
TASK_ID	NULL	NUMBER	Task associated with this transaction
INVENTORY_ITEM_ID	NOT NULL	NUMBER	Inventory Item ID
TAX_DATE	NULL	DATE	It will store the date for tax calculation
TAX_CODE	NULL	VARCHAR2(50)	Tax code for the line
TAX_RATE	NULL	NUMBER	The tax rate in percentage
INVOICE_INTERFACE_STATUS_CODE	NULL	VARCHAR2(30)	To indicate whether the invoicing activity is complete
DEMAND_CLASS_CODE	NULL	VARCHAR2(30)	Demand Class
PRICE_LIST_ID	NULL	NUMBER	Price List
PRICING_DATE	NULL	DATE	Determines effective list and price modifiers
SHIPMENT_NUMBER	NOT NULL	NUMBER	System generated identifier of a shipment within a line
AGREEMENT_ID	NULL	NUMBER	Internal use only
SHIPMENT_PRIORITY_CODE	NULL	VARCHAR2(30)	Shipment Priority Code
SHIPPING_METHOD_CODE	NULL	VARCHAR2(30)	Shipping method
FREIGHT_CARRIER_CODE	NULL	VARCHAR2(30)	Freight carrier for the order line.
FREIGHT_TERMS_CODE	NULL	VARCHAR2(30)	Freight Terms, specifying the responsibility for Freight charges
FOB_POINT_CODE	NULL	VARCHAR2(30)	FOB Point Code
TAX_POINT_CODE	NULL	VARCHAR2(30)	For Future release
PAYMENT_TERM_ID	NULL	NUMBER(15)	Payment Terms
INVOICING_RULE_ID	NULL	NUMBER(15)	Invoicing rule used by AR for generating Invoice
ACCOUNTING_RULE_ID	NULL	NUMBER(15)	Accounting rule used by AR for generating Invoice
SOURCE_DOCUMENT_TYPE_ID	NULL	NUMBER	Indicates the source of the order
ORIG_SYS_DOCUMENT_REF	NULL	VARCHAR2(50)	Original document reference for the order in external system
SOURCE_DOCUMENT_ID	NULL	NUMBER	Source Order Header Id
ORIG_SYS_LINE_REF	NULL	VARCHAR2(50)	Identifier of line from a source system outside of Oracle Order Management
SOURCE_DOCUMENT_LINE_ID	NULL	NUMBER	Source Order Line Id
REFERENCE_LINE_ID	NULL	NUMBER	This column stores the sales order line id this return line references
REFERENCE_TYPE	NULL	VARCHAR2(30)	This column is now obsolete
REFERENCE_HEADER_ID	NULL	NUMBER	This column stores the sales order header id this return line references
ITEM_REVISION	NULL	VARCHAR2(3)	This column stores the item revision for a return line
UNIT_SELLING_PRICE	NULL	NUMBER	Actual price charged to customer
UNIT_LIST_PRICE	NULL	NUMBER	Price List price for the item
TAX_VALUE	NULL	NUMBER	The Tax amount in order currency
CONTEXT	NULL	VARCHAR2(30)	Descriptive Flexfield segment
ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE2	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE3	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE4	NULL	VARCHAR2(240)	Descriptive Flexfield segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

ATTRIBUTE5	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE6	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE7	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE8	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE9	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE10	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE11	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE12	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE13	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE14	NULL	VARCHAR2(240)	Descriptive Flexfield segment
ATTRIBUTE15	NULL	VARCHAR2(240)	Descriptive Flexfield segment
GLOBAL_ATTRIBUTE_CATEGORY	NULL	VARCHAR2(30)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE1	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE2	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE3	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE4	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE5	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE6	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE7	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE8	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE9	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE10	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE11	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE12	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE13	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE14	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE15	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE16	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE17	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE18	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE19	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
GLOBAL_ATTRIBUTE20	NULL	VARCHAR2(240)	Reserved for country-specific functionality.
PRICING_CONTEXT	NULL	VARCHAR2(30)	Descriptive Flexfield segment
PRICING_ATTRIBUTE1	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment
PRICING_ATTRIBUTE2	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment
PRICING_ATTRIBUTE3	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment
PRICING_ATTRIBUTE4	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

PRICING_ATTRIBUTE5	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment
PRICING_ATTRIBUTE6	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment
PRICING_ATTRIBUTE7	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment
PRICING_ATTRIBUTE8	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment
PRICING_ATTRIBUTE9	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment
PRICING_ATTRIBUTE10	NULL	VARCHAR2(240)	Pricing Related Descriptive Flexfield segment
INDUSTRY_CONTEXT	NULL	VARCHAR2(30)	Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE1	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE2	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE3	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE4	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE5	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE6	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE7	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE8	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE9	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE10	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE11	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE13	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE12	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE14	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE15	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE16	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE17	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE18	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE19	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE20	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE21	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE22	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE23	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE24	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE25	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

INDUSTRY_ATTRIBUTE26	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE27	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE28	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE29	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
INDUSTRY_ATTRIBUTE30	NULL	VARCHAR2(240)	Industry specific Descriptive Flexfield segment
CREATION_DATE	NOT NULL	DATE	Standard Who column
CREATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_DATE	NOT NULL	DATE	Standard Who column
LAST_UPDATED_BY	NOT NULL	NUMBER	Standard Who column
LAST_UPDATE_LOGIN	NULL	NUMBER	Standard Who column
PROGRAM_APPLICATION_ID	NULL	NUMBER	Application of concurrent program that last updated row.
PROGRAM_ID	NULL	NUMBER	Concurrent program that last updated row.
PROGRAM_UPDATE_DATE	NULL	DATE	Last date changed by concurrent program
REQUEST_ID	NULL	NUMBER	Concurrent request that last changed row
TOP_MODEL_LINE_ID	NULL	NUMBER	System-generated identifier of configuration top parent line
LINK_TO_LINE_ID	NULL	NUMBER	System-generated identifier of immediate parent component line
COMPONENT_SEQUENCE_ID	NULL	NUMBER	Bill of materials component (option) or bill (top model)
COMPONENT_CODE	NULL	VARCHAR2(1000)	Identifier of component within an exploded bill
CONFIG_DISPLAY_SEQUENCE	NULL	NUMBER	Not used
SORT_ORDER	NULL	VARCHAR2(240)	Sorting sequence for a component within ordered bill
ITEM_TYPE_CODE	NULL	VARCHAR2(30)	Type of item
OPTION_NUMBER	NULL	NUMBER	System generated identifier for an option or a class within a model
OPTION_FLAG	NULL	VARCHAR2(1)	Not used
DEP_PLAN_REQUIRED_FLAG	NULL	VARCHAR2(1)	Departure Planning Required Flag possible values Y/N
VISIBLE_DEMAND_FLAG	NULL	VARCHAR2(1)	Indicated line is visible to planning as demand
LINE_CATEGORY_CODE	NOT NULL	VARCHAR2(30)	Indicates whether the line is regular or return
ACTUAL_SHIPMENT_DATE	NULL	DATE	Actual Shipment Date of the line
CUSTOMER_TRX_LINE_ID	NULL	NUMBER	Customer transaction Line
RETURN_CONTEXT	NULL	VARCHAR2(30)	Descriptive Flexfield segment
RETURN_ATTRIBUTE1	NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE2	NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE3	NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE4	NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE5	NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE6	NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment

Oracle Proprietary, Confidential Information--Use Restricted by Contract

RETURN_ATTRIBUTE7		NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE8		NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE9		NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE10		NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE11		NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE12		NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE13		NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE14		NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
RETURN_ATTRIBUTE15		NULL	VARCHAR2(240)	Returns specific Descriptive Flexfield segment
ACTUAL_ARRIVAL_DATE		NULL	DATE	Date the item actually arrived at customer's site
ATO_LINE_ID		NULL	NUMBER	System-generated identifier if ATO configuration top model line
AUTO_SELECTED_QUANTITY		NULL	NUMBER	Not used
COMPONENT_NUMBER		NULL	NUMBER	System Generated Identifier of the included item within a model or a class
EARLIEST_ACCEPTABLE_DATE		NULL	DATE	Earliest Date the item is acceptable.
EXPLOSION_DATE		NULL	DATE	Date when the included items were exploded and frozen
LATEST_ACCEPTABLE_DATE		NULL	DATE	Latest Date the item is acceptable.
MODEL_GROUP_NUMBER		NULL	NUMBER	Currently not used
SCHEDULE_ARRIVAL_DATE		NULL	DATE	Date Scheduled for the item to arrive at the customer site
SHIP_MODEL_COMPLETE_FLAG		NULL	VARCHAR2(1)	Indicates whether line is in ship-complete configuration
SCHEDULE_STATUS_CODE		NULL	VARCHAR2(30)	Indicates if the line is scheduled
SOURCE_TYPE_CODE		NULL	VARCHAR2(30)	Sourcing indicator (internal or external)
CANCELLED_FLAG		NULL	VARCHAR2(1)	Indicates whether line is completely cancelled
OPEN_FLAG	NOT NULL	NULL	VARCHAR2(1)	Indicates whether the line has been closed ('N') or not ('Y')
BOOKED_FLAG	NOT NULL	NULL	VARCHAR2(1)	Indicates whether order line is booked ('Y') or not ('N')
SALESREP_ID		NULL	NUMBER(15)	Sales person identifier
RETURN_REASON_CODE		NULL	VARCHAR2(30)	This column stores return reason code for a return line, and is required for a return line
ARRIVAL_SET_ID		NULL	NUMBER	Arrival Set Identifier
SHIP_SET_ID		NULL	NUMBER	Ship Set Id; if the line belongs to a ship set
SPLIT_FROM_LINE_ID		NULL	NUMBER	System generated identifier of original line which was split
CUST_PRODUCTION_SEQ_NUM		NULL	VARCHAR2(50)	Unique production sequence that indicates how the customer transmitted the demand lines.
AUTHORIZED_TO_SHIP_FLAG		NULL	VARCHAR2(1)	Field to identify whether the demand lines are authorized to ship.

Oracle Proprietary, Confidential Information--Use Restricted by Contract

OVER_SHIP_REASON_CODE	NULL	VARCHAR2(30)	Overshipment Reason Code
OVER_SHIP_RESOLVED_FLAG	NULL	VARCHAR2(1)	Overshipment Resolved Flag
ORDERED_ITEM_ID	NULL	NUMBER	Stores Id of Ordered Item
ITEM_IDENTIFIER_TYPE	NULL	VARCHAR2(30)	To distinguish different types of items (internal, customer, and generic items)
CONFIGURATION_ID	NULL	NUMBER	Not Used
COMMITMENT_ID	NULL	NUMBER	Commitment to apply line against
SHIPPING_INTERFACED_FLAG	NULL	VARCHAR2(1)	Shipping Interfaced Flag to indicate whether a line has been interfaced to shipping or not
CREDIT_INVOICE_LINE_ID	NULL	NUMBER	This column stores the invoice line id this return line applies credit to
FIRST_ACK_CODE	NULL	VARCHAR2(30)	Initial acknowledgment code for outbound EDI transaction
FIRST_ACK_DATE	NULL	DATE	Initial acknowledgment date for outbound EDI transaction
LAST_ACK_CODE	NULL	VARCHAR2(30)	Latest acknowledgment code for outbound EDI transaction
LAST_ACK_DATE	NULL	DATE	Latest acknowledgment date for outbound EDI transaction
PLANNING_PRIORITY	NULL	NUMBER	Planning Priority
ORDER_SOURCE_ID	NULL	NUMBER	Source of order line
ORIG_SYS_SHIPMENT_REF	NULL	VARCHAR2(50)	Original shipment information for the line of the order in external system
CHANGE_SEQUENCE	NULL	VARCHAR2(50)	It is sequence number in which changes will be applied. It will make sure that later changes are not over-written by previous order change.
DROP_SHIP_FLAG	NULL	VARCHAR2(1)	Not Used
CUSTOMER_LINE_NUMBER	NULL	VARCHAR2(50)	Reference Information. Contains customers line number, if specified while importing an order. Customers who have an alphanumeric line number can store their line number information in this field.
CUSTOMER_SHIPMENT_NUMBER	NULL	VARCHAR2(50)	Reference Information. Contains Customers Shipment number, if specified while importing an order. Customers who have an alphanumeric shipment number can store their shipment number information in this field.
CUSTOMER_ITEM_NET_PRICE	NULL	NUMBER	Reference Information. Contains Customers net price, if specified while importing an order.
CUSTOMER_PAYMENT_TERM_ID	NULL	NUMBER	Reference Information. Contains Customers payment term, if specified while importing an order.
FULFILLED_FLAG	NULL	VARCHAR2(1)	Fulfilled Flag to indicate whether the line has been fulfilled.
END_ITEM_UNIT_NUMBER	NULL	VARCHAR2(30)	Uniquely identifies which bill of material to be used for building a specific Model/Unit Number effectivity controlled item

Oracle Proprietary, Confidential Information--Use Restricted by Contract

CONFIG_HEADER_ID	NULL	NUMBER	System-generated identifier for Oracle Configurator reference
CONFIG_REV_NBR	NULL	NUMBER	System-generated identifier for Oracle Configurator reference
MFG_COMPONENT_SEQUENCE_ID	NULL	NUMBER	Not used
SHIPPING_INSTRUCTIONS	NULL	VARCHAR2(2000)	Shipping Instructions for Line
PACKING_INSTRUCTIONS	NULL	VARCHAR2(2000)	Packing Instructions for Line
INVOICED_QUANTITY	NULL	NUMBER	To indicate whether the invoicing activity is complete
REFERENCE_CUSTOMER_TRX_LINE_ID	NULL	NUMBER	This column stores the invoice line id this return line references
SPLIT_BY	NULL	VARCHAR2(30)	Indicates whether the line is system or user level split
LINE_SET_ID	NULL	NUMBER	Line Set id
SERVICE_TXN_REASON_CODE	NULL	VARCHAR2(30)	To store service transaction reason.
SERVICE_TXN_COMMENTS	NULL	VARCHAR2(2000)	Placeholder for service comments.
SERVICE_DURATION	NULL	NUMBER	Internal use only
SERVICE_START_DATE	NULL	DATE	Start date for the service
SERVICE_END_DATE	NULL	DATE	Internal use only
SERVICE_COTERMINATE_FLAG	NULL	VARCHAR2(1)	To identify whether the service can be coterminated.
UNIT_LIST_PERCENT	NULL	NUMBER	Price list percent of the item (percent-based pricing only)
UNIT_SELLING_PERCENT	NULL	NUMBER	Percent actually charged to customer (percent based pricing only)
UNIT_PERCENT_BASE_PRICE	NULL	NUMBER	Based price used for percent based pricing
SERVICE_NUMBER	NULL	NUMBER	Unique number to identify the service line/s.
SERVICE_PERIOD	NULL	VARCHAR2(3)	Period for which service is offered.
SHIPPABLE_FLAG	NULL	VARCHAR2(1)	A flag to indicate whether a line is shippable or not.
MODEL_REMNANT_FLAG	NULL	VARCHAR2(1)	Indicates whether model has partially shipped components
RE_SOURCE_FLAG	NULL	VARCHAR2(1)	Indicates whether user entered the warehouse or the system did
FLOW_STATUS_CODE	NULL	VARCHAR2(30)	Workflow status for the line
TP_CONTEXT	NULL	VARCHAR2(30)	Descriptive Flexfield segment
TP_ATTRIBUTE1	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE2	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE3	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE4	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE5	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE6	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE7	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE8	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE9	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE10	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE11	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE12	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE13	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE14	NULL	VARCHAR2(240)	Descriptive Flexfield segment
TP_ATTRIBUTE15	NULL	VARCHAR2(240)	Descriptive Flexfield segment
FULFILLMENT_METHOD_CODE	NULL	VARCHAR2(30)	Fulfillment Method Code

MARKETING_SOURCE_CODE_ID	NULL	NUMBER	Marketing source code identifier. Foreign key reference to CRM table AMS_SOURCE_CODE.
SERVICE_REFERENCE_TYPE_CODE	NULL	VARCHAR2(30)	To identify the service reference type. Typical values are Order and Customer Product
SERVICE_REFERENCE_LINE_ID	NULL	NUMBER	Identifies the immediate parent line to which the service is attached.
SERVICE_REFERENCE_SYSTEM_ID	NULL	NUMBER	To store system id for either reference type like order or customer product.
CALCULATE_PRICE_FLAG	NULL	VARCHAR2(1)	Controls repricing of order lines
UPGRADED_FLAG	NULL	VARCHAR2(1)	Denotes if this column is upgraded into R11i or is newly created in R11i version.
REVENUE_AMOUNT	NULL	NUMBER	For future use
FULFILLMENT_DATE	NULL	DATE	Fulfillment Date for the Line
PREFERRED_GRADE	NULL	VARCHAR2(4)	Grade requested by the customer
ORDERED_QUANTITY2	NULL	NUMBER	Ordered quantity in secondary inventory unit of measure
ORDERED_QUANTITY_UOM2	NULL	VARCHAR2(3)	Ordered Quantity unit of measure
SHIPPING_QUANTITY2	NULL	NUMBER	Shipping quantity in secondary shipping unit of measure
CANCELLED_QUANTITY2	NULL	NUMBER	Cancelled Quantity
SHIPPED_QUANTITY2	NULL	NUMBER	Shipped quantity in ordered_quantity_uom2
SHIPPING_QUANTITY_UOM2	NULL	VARCHAR2(3)	Secondary unit of measure the item is shipped
FULFILLED_QUANTITY2	NULL	NUMBER	Fulfilled quantity in ordered_quantity_uom2
MFG_LEAD_TIME	NULL	NUMBER	This column stores the Manufacturing Lead time for ATO Options.
LOCK_CONTROL	NULL	NUMBER	

Indexes

Index Name	Index Type	Sequence	Column Name
OE_ORDER_LINES_N1	NOT UNIQUE	1	HEADER_ID
OE_ORDER_LINES_N10	NOT UNIQUE	1	TOP_MODEL_LINE_ID
OE_ORDER_LINES_N11	NOT UNIQUE	1	ORDER_SOURCE_ID
		2	ORIG_SYS_DOCUMENT_REF
		3	ORIG_SYS_LINE_REF
		4	ORIG_SYS_SHIPMENT_REF
OE_ORDER_LINES_N12	NOT UNIQUE	2	ARRIVAL_SET_ID
OE_ORDER_LINES_N13	NOT UNIQUE	2	SHIP_SET_ID
OE_ORDER_LINES_N14	NOT UNIQUE	2	LINK_TO_LINE_ID
OE_ORDER_LINES_N15	NOT UNIQUE	2	OPEN_FLAG
OE_ORDER_LINES_N16	NOT UNIQUE	2	CUST_PO_NUMBER
OE_ORDER_LINES_N17	NOT UNIQUE	2	ATO_LINE_ID
OE_ORDER_LINES_N2	NOT UNIQUE	1	SHIP_TO_ORG_ID
OE_ORDER_LINES_N3	NOT UNIQUE	1	INVENTORY_ITEM_ID
OE_ORDER_LINES_N4	NOT UNIQUE	2	LINE_CATEGORY_CODE
OE_ORDER_LINES_N5	NOT UNIQUE	2	PROJECT_ID
		4	TASK_ID
OE_ORDER_LINES_N6	NOT UNIQUE	2	REFERENCE_LINE_ID
OE_ORDER_LINES_N7	NOT UNIQUE	2	LINE_SET_ID

Oracle Proprietary, Confidential Information--Use Restricted by Contract

OE_ORDER_LINES_N8	NOT UNIQUE	2	HEADER_ID
		4	LINE_ID
OE_ORDER_LINES_N9	NOT UNIQUE	1	SERVICE_REFERENCE_LINE_ID
OE_ORDER_LINES_U1	UNIQUE	1	LINE_ID

Sequences

<u>Sequence</u>	<u>Derived Column</u>
OE_ORDER_LINES_S	LINE_ID

A

Application Building Block, 1 – 6

C

Column descriptions, 3 – 4

Columns, Who, 3 – 4

Concurrent Program List. *See* Concurrent Program Definitions

D

Database Diagram, 1 – 6

database diagrams, conventions, 2 – 5

Database triggers, 3 – 6

F

Foreign keys, 3 – 3

Form, 1 – 7

Form List. *See* Form Definitions

I

Indexes, 3 – 6

important note about, 3 – 6

Internal View List, 2 – 21

L

Lookup types. *See* QuickCodes

M

Module List, 2 – 24

See also Module Definitions

Modules, 1 – 6

MultiLingual View List, 2 – 23

O

Oracle8 sequences. *See* Sequences

P

Public Table List, 2 – 7

Public View List, 2 – 17

Q

QuickCodes, 1 – 6

Columns that contain, 3 – 3

R

Relationship, 1 – 6

Report List. *See* Report Definitions

S

Sequences, 3 – 6

Single Organization View List, 2 – 22

T

Table and View Definitions

AK_ATTRIBUTES, 3 – 7

AK_ATTRIBUTES_TL, 3 – 9

AK_OBJECT_ATTRIBUTE_NAVIGATION, 3 – 17

AK_OBJECT_ATTRIBUTES, 3 – 13

AK_OBJECT_ATTRIBUTES_TL, 3 – 16

AK_OBJECT_VALUES_TEMP, 3 – 19

AK_OBJECTS, 3 – 10

AK_OBJECTS_TL, 3 – 12

AK_QUERY_OBJECT_LINES, 3 – 21

AK_QUERY_OBJECTS, 3 – 20

AK_REGION_ITEMS, 3 – 25

AK_REGION_ITEMS_TL, 3 – 29

AK_REGION_LOV_RELATIONS, 3 – 30

AK_REGIONS, 3 – 22

AK_REGIONS_TL, 3 – 24

AS_ACCESSES_ALL, 3 – 85	ASO_QUOTE_LINE_ATTRIBS_V, 3 – 76
AS_FORECAST_PROB_ALL_B, 3 – 89	ASO_QUOTE_LINE_DETAILS, 3 – 77
AS_FORECAST_PROB_ALL_TL, 3 – 91	ASO_QUOTE_LINE_DETAILS_V, 3 – 80
AS_FORECAST_WORKSHEETS, 3 – 92	ASO_QUOTE_LINES, 2 – 22
AS_INTEREST_CATEGORY_SETS_ALL, 3 – 97	ASO_QUOTE_LINES_ALL, 3 – 67
AS_INTEREST_CODES_B, 3 – 98	ASO_QUOTE_LINES_ALL_V, 3 – 69
AS_INTEREST_CODES_MC, 3 – 100	ASO_QUOTE_LINES_V, 3 – 72
AS_INTEREST_CODES_TL, 3 – 101	ASO_QUOTE_RELATED_OBJECTS, 3 – 83
AS_INTEREST_TYPES_ALL, 3 – 102	ASO_QUOTE_RELATED_OBJECTS_V, 3 – 84
AS_INTEREST_TYPES_B, 3 – 104	ASO_QUOTE_STATUSES_VL, 2 – 23
AS_INTEREST_TYPES_TL, 3 – 106	BIL_IMP_CUST_SUMM, 3 – 141
AS_INTERESTS_ALL, 3 – 94	BIL_INV_TERR_INTF, 3 – 143
AS_INTERNAL_FORECASTS, 3 – 107	BIL_OPTY_PERF_SUMM, 3 – 144
AS_LEAD_LINES_ALL, 3 – 114	BIL_ORD_TERR_INTF, 3 – 146
AS_LEAD_ORDERS, 3 – 117	BIL_PROD_SCT_WL_SUMM, 3 – 147
AS_LEADS_ALL, 3 – 109	BIL_QUOTE_TERR_INTF, 3 – 149
AS_LEADS_LOG, 3 – 113	BIL_REV_CUST_SUMM, 3 – 150
AS_SALES_CREDITS, 3 – 119	BIL_ROC_SUMM, 3 – 152
AS_SALES_CREDITS_DENORM, 3 – 122	BIL_SLS_CHNL_PERF_SUMM, 3 – 154
AS_SALES_LEAD_LINES, 3 – 129	BIL_SREP_PERF_SUMM, 3 – 156
AS_SALES_LEAD_OPPORTUNITY, 3 – 131	BIL_SRV_RQST_SUMM, 3 – 158
AS_SALES_LEAD_RANKS_B, 3 – 133	CN_COMMISSION_HEADERS_ALL, 3 – 159
AS_SALES_LEADS, 3 – 125	CN_COMMISSION_LINES_ALL, 3 – 163
AS_SALES_LEADS_LOG, 3 – 128	CN_QUOTA_ASSIGNS_ALL, 3 – 169
AS_SALES_STAGES_ALL_B, 3 – 134	CN_QUOTAS_ALL, 3 – 166
AS_SALES_STAGES_ALL_TL, 3 – 136	CN_SRP_PER_QUOTA_RC_ALL, 3 – 176
AS_STATUSES_B, 3 – 137	CN_SRP_PERIOD_QUOTAS_ALL, 3 – 174
AS_STATUSES_TL, 3 – 139	CN_SRP_PERIODS_ALL, 3 – 170
AS_TERRITORY_ACCESSES, 3 – 140	CN_SRP_PLAN_ASSIGNS_ALL, 3 – 178
ASO_HEADER_RELATIONSHIPS, 3 – 31	CN_SRP_QUOTA_ASSIGNS_ALL, 3 – 180
ASO_HEADER_RELATIONSHIPS_V, 3 – 32	CN_SRP_QUOTA_RULES_ALL, 3 – 183
ASO_I_OE_ORDER_HEADERS_V, 3 – 33	CS_INCIDENT_SEVERITIES_B, 3 – 191
ASO_I_OE_ORDER_LINES_V, 3 – 38	CS_INCIDENT_SEVERITIES_TL, 3 – 193
ASO_I_OE_SALES_CREDITS_V, 3 – 51	CS_INCIDENT_STATUSES_B, 3 – 194
ASO_I_OPPORTUNITIES_V, 2 – 21	CS_INCIDENT_STATUSES_TL, 3 – 196
ASO_I_ORDER_HEADERS_V, 2 – 22	CS_INCIDENT_TYPES_B, 3 – 197
ASO_I_ORDER_LINES_V, 2 – 22	CS_INCIDENT_TYPES_TL, 3 – 199
ASO_I_ORDER_TYPES_V, 3 – 52	CS_INCIDENTS_ALL_B, 3 – 185
ASO_I_SALES_CHANNELS_V, 3 – 53	CS_INCIDENTS_ALL_TL, 3 – 190
ASO_I_SALES_CREDIT_TYPES_V, 3 – 55	EDW_BIL_COMP_PLANS_M, 3 – 200
ASO_I_SALES_CREDITS_V, 3 – 54	EDW_BIL_COMP_PRF_SUM_F, 3 – 202
ASO_PARTY_RELATIONSHIPS_V, 3 – 56	EDW_BIL_CPLNS_A_LTC, 3 – 204
ASO_QUOTE_HEADERS_ALL, 3 – 57	EDW_BIL_CPLNS_CPLN_LSTG, 3 – 205
ASO_QUOTE_HEADERS_ALL_V, 3 – 59	EDW_BIL_CPLNS_CPLN_LTC, 3 – 206
ASO_QUOTE_HEADERS_V, 3 – 62	EDW_BIL_CPLNS_ELMNT_LSTG, 3 – 208

EDW_BIL_CPLNS_ELMNT_LTC, 3 – 209	EDW_BIL_SLSF_SGRP7_LSTG, 3 – 282
EDW_BIL_CRIT_CUST_SUM_F, 3 – 210	EDW_BIL_SLSF_SGRP7_LTC, 3 – 283
EDW_BIL_CUST_PRF_SUM_F, 3 – 212	EDW_BIL_SLSF_SREP_LSTG, 3 – 284
EDW_BIL_CUST_REQSTS_F, 3 – 214	EDW_BIL_SLSF_SREP_LTC, 3 – 286
EDW_BIL_CUST_REQSTS_FSTG, 3 – 216	EDW_BIL_SLSFRCE_M, 3 – 265
EDW_BIL_CUST_RMGT_SUM_F, 3 – 218	EDW_BIL_SLSTER_A_LTC, 3 – 287
EDW_BIL_CUST_SATFCTN_F, 3 – 220	EDW_BIL_SLSTER_M, 3 – 288
EDW_BIL_CUST_SATFCTN_FSTG, 3 – 222	EDW_BIL_SLSTER_TER_LSTG, 3 – 293
EDW_BIL_CUST_SATIS_SUM_F, 3 – 224	EDW_BIL_SLSTER_TERR_LTC, 3 – 292
EDW_BIL_LEADS_F, 3 – 226	EDW_BIL_SLSTER_TGRP1_LSTG, 3 – 294
EDW_BIL_LEADS_FSTG, 3 – 228	EDW_BIL_SLSTER_TGRP1_LTC, 3 – 295
EDW_BIL_LEADS_TER_GRP, 3 – 230	EDW_BIL_SLSTER_TGRP2_LSTG, 3 – 296
EDW_BIL_OPTY_PERF_SUM_F, 3 – 235	EDW_BIL_SLSTER_TGRP2_LTC, 3 – 297
EDW_BIL_OPTY_TER_GRP, 3 – 237	EDW_BIL_SLSTER_TGRP3_LSTG, 3 – 298
EDW_BIL_OPTY_TGRP_BSTG, 3 – 238	EDW_BIL_SLSTER_TGRP3_LTC, 3 – 299
EDW_BIL_OPTYS_F, 3 – 231	EDW_BIL_SLSTER_TGRP4_LSTG, 3 – 300
EDW_BIL_OPTYS_FSTG, 3 – 233	EDW_BIL_SLSTER_TGRP4_LTC, 3 – 301
EDW_BIL_ORDRS_TER_GRP, 3 – 239	EDW_BIL_SLSTER_TGRP5_LSTG, 3 – 302
EDW_BIL_ORDRS_TGRP_BSTG, 3 – 240	EDW_BIL_SLSTER_TGRP5_LTC, 3 – 303
EDW_BIL_PROD_PERF_SUM_F, 3 – 241	EDW_BIL_SLSTER_TGRP6_LSTG, 3 – 304
EDW_BIL_QUOTE_TER_GRP, 3 – 247	EDW_BIL_SLSTER_TGRP6_LTC, 3 – 305
EDW_BIL_QUOTE_TGRP_BSTG, 3 – 248	EDW_BIL_SLSTER_TGRP7_LTC, 3 – 306
EDW_BIL_QUOTES_F, 3 – 243	EDW_BIL_SLSTER_TGRP7_LTSG, 3 – 307
EDW_BIL_QUOTES_FSTG, 3 – 245	EDW_BIL_SR_SV_SRSV_A_LTC, 3 – 315
EDW_BIL_ROC_SUM_F, 3 – 249	EDW_BIL_SR_SV_SRSV_LSTG, 3 – 316
EDW_BIL_SCHN_PER_SUM_F, 3 – 251	EDW_BIL_SR_SV_SRSV_LTC, 3 – 317
EDW_BIL_SF_COMP_F, 3 – 253	EDW_BIL_SR_TER_GRP_B, 3 – 318
EDW_BIL_SF_COMP_FSTG, 3 – 255	EDW_BIL_SR_TER_GRP_BSTG, 3 – 319
EDW_BIL_SF_PROFILE_F, 3 – 257	EDW_BIL_SREP_PERF_SUM_F, 3 – 310
EDW_BIL_SF_PROFILE_FSTG, 3 – 259	EDW_BIL_SREQ_SEV_M, 3 – 312
EDW_BIL_SF_STER_REV_F, 3 – 261	EDW_BIL_SRV_REQ_SUM_F, 3 – 313
EDW_BIL_SF_STER_REV_FSTG, 3 – 263	EDW_BIL_STER_ORDRS_F, 3 – 320
EDW_BIL_SLS_CYCLE_SUM_F, 3 – 308	EDW_BIL_STER_ORDRS_FSTG, 3 – 322
EDW_BIL_SLSF_A_LTC, 3 – 269	EDW_BIL_WIN_PROB_A_LTC, 3 – 324
EDW_BIL_SLSF_SGRP1_LSTG, 3 – 270	EDW_BIL_WIN_PROB_LSTG, 3 – 325
EDW_BIL_SLSF_SGRP1_LTC, 3 – 271	EDW_BIL_WIN_PROB_LTC, 3 – 326
EDW_BIL_SLSF_SGRP2_LSTG, 3 – 272	EDW_BIL_WIN_PROB_M, 3 – 327
EDW_BIL_SLSF_SGRP2_LTC, 3 – 273	EDW_BIM_LEAD_STATUSES_M, 3 – 328
EDW_BIL_SLSF_SGRP3_LSTG, 3 – 274	EDW_BIM_OPP_STATUSES_M, 3 – 329
EDW_BIL_SLSF_SGRP3_LTC, 3 – 275	EDW_SOURCE_INSTANCES, 3 – 330
EDW_BIL_SLSF_SGRP4_LSTG, 3 – 276	EDW_SOURCE_INSTANCES_TL, 3 – 331
EDW_BIL_SLSF_SGRP4_LTC, 3 – 277	JTF_BIS_CHART_FUNCTIONS, 3 – 332
EDW_BIL_SLSF_SGRP5_LSTG, 3 – 278	JTF_BIS_USER_CHART_PLUGS, 3 – 333
EDW_BIL_SLSF_SGRP5_LTC, 3 – 279	JTF_BIS_USER_FAVORITE_PLUGS, 3 – 334
EDW_BIL_SLSF_SGRP6_LSTG, 3 – 280	JTF_BRM_PARAMETERS, 3 – 335
EDW_BIL_SLSF_SGRP6_LTC, 3 – 281	JTF_RS_GROUP_MEMBERS, 3 – 341
	JTF_RS_GROUP_USAGES, 3 – 343

JTF_RS_GROUPS_B, 3 – 336
 JTF_RS_GROUPS_DENORM, 3 – 338
 JTF_RS_GROUPS_TL, 3 – 340
 JTF_RS_GRP_RELATE_AUD, 3 – 345
 JTF_RS_GRP_RELATIONS, 3 – 346
 JTF_RS_JOB_ROLES, 3 – 348
 JTF_RS_REP_MANAGERS, 3 – 350
 JTF_RS_RESOURCE_EXTNS, 3 – 352
 JTF_RS_RESOURCE_VALUES, 3 – 355
 JTF_RS_ROLE_RELATE_AUD, 3 – 360
 JTF_RS_ROLE_RELATIONS, 3 – 361
 JTF_RS_ROLES_B, 3 – 357
 JTF_RS_ROLES_TL, 3 – 359
 JTF_RS_SALESREPS, 3 – 363
 JTF_RS_SRP_TERRITORIES, 3 – 365
 JTF_RS_TEAMS_B, 3 – 367
 JTF_RS_TEAMS_TL, 3 – 368
 OE_CRM_ORDER_HEADERS_V, 3 – 369
 OE_CRM_ORDER_LINES_V, 3 – 374
 OE_CRM_SALES_CREDITS_V, 3 – 384

OE_ORDER_HEADERS_ALL, 3 – 386
 OE_ORDER_LINES_ALL, 3 – 392

Tables

See also Table and View Definitions
 Column descriptions, 3 – 4
 Foreign keys, 3 – 3
 Indexes. *See* Indexes
 Primary Keys, 3 – 4
 QuickCodes Columns, 3 – 3
 Who columns, 3 – 4, 3 – 5

V

View Definitions. *See* Table and View Definitions

Views

See also Table and View Definitions; View List
 Derivation, 3 – 6

Reader's Comment Form

Oracle Sales Intelligence Technical Reference Manual A86210-01

Oracle Corporation welcomes your comments and suggestions on the quality and usefulness of this publication. Your input is an important part of the information we use for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most about this manual? What did you like least about it?

If you find any errors or have any other suggestions for improvement, please indicate the topic, chapter, and page number below:

Please send your comments to:

CRM Content Development Manager
Oracle Corporation
500 Oracle Parkway
Redwood Shores, CA 94065 USA
Phone: (650) 506-7000 Fax: (650) 506-7200

If you would like a reply, please give your name, address, and telephone number below:

Thank you for helping us improve our documentation.

